

Open Source Used In Cisco AppDynamics Java Agent 26.1.0_rhel_image

Cisco Systems, Inc.
www.cisco.com

Cisco has more than 200 offices worldwide.
Addresses, phone numbers, and fax numbers
are listed on the Cisco website at
www.cisco.com/go/offices.

Text Part Number: 78EE117C99-2925164020

This document contains licenses and notices for open source software used in this product. With respect to the free/open source software listed in this document, if you have any questions or wish to receive a copy of any source code to which you may be entitled under the applicable free/open source license(s) (such as the GNU Lesser/General Public License), please submit this form.

In your requests please include the following reference number 78EE117C99-2925164020

Contents

1.1 picocontainer 2.15
1.1.1 Available under license
1.2 jetty-client 12.0.0
1.2.1 Available under license
1.3 error_prone_annotations 2.3.3
1.3.1 Available under license
1.4 jackson 2.17.3
1.4.1 Available under license
1.5 opentelemetry-sdk-extension-autoconfigure-spi 1.29.0
1.5.1 Available under license
1.6 jackson-dataformat-yaml 2.17.3
1.6.1 Available under license
1.7 opentelemetry-semconv 1.29.0-alpha
1.7.1 Available under license
1.8 annotations 13.0
1.8.1 Available under license
1.9 listenablefuture 9999.0-empty-to-avoid-conflict-with-guava
1.9.1 Available under license
1.10 jeromq 0.3.5
1.10.1 Available under license
1.11 jackson 2.17.1
1.11.1 Available under license
1.12 protobuf-java 3.25.8
1.12.1 Available under license
1.13 uuid-creator 6.1.1
1.13.1 Available under license

1.14 jcl-over-slf4j 2.0.17
1.14.1 Available under license
1.15 jsr305 3.0.2
1.15.1 Available under license
1.16 httpcomponents-core 4.4.13
1.16.1 Available under license
1.17 error_prone_annotations 2.23.0
1.17.1 Available under license
1.18 commons-jexl 3.4.0
1.18.1 Available under license
1.19 commons-math 2.2
1.19.1 Available under license
1.20 commons-codec 1.17.1
1.20.1 Available under license
1.21 kotlin 1.9.10
1.21.1 Available under license
1.22 javax-inject 1
1.22.1 Available under license
1.23 jackson-dataformat-yaml 2.17.1
1.23.1 Available under license
1.24 snake-yaml 2.2
1.24.1 Available under license
1.25 common 8.3.1
1.25.1 Available under license
1.26 javassist 3.29.2-GA
1.26.1 Available under license
1.27 zt 1.16
1.27.1 Available under license
1.28 gson 2.10.1
1.28.1 Available under license
1.29 httpclient-cache 4.5.13
1.29.1 Available under license
1.30 commons-logging 1.3.4
1.30.1 Available under license
1.31 flightrecorder 8.3.1
1.31.1 Available under license
1.32 paranamer 2.5.1
1.32.1 Available under license
1.33 animal-sniffer-annotation 1.23

1.33.1 Available under license
1.34 servlet-api 4.0.1
1.34.1 Available under license
1.35 error_prone_annotations 2.18.0
1.35.1 Available under license
1.36 opentelemetry-proto 0.11.0
1.36.1 Available under license
1.37 commons-codec 1.15
1.37.1 Available under license
1.38 gson 2.13.2
1.38.1 Available under license
1.39 failureaccess 1.0.1
1.39.1 Available under license
1.40 httpcomponents-client 4.5.14
1.40.1 Available under license
1.41 xerces-j 2.12.2
1.41.1 Available under license
1.42 perfmark-api 0.17.0
1.42.1 Available under license
1.43 guava 32.1.3-jre
1.43.1 Available under license
1.44 commons-codec 1.14
1.44.1 Available under license
1.45 encoder 1.2.3
1.45.1 Available under license
1.46 jackson-annotations 2.17.1
1.46.1 Available under license
1.47 jackson-databind 2.17.3
1.47.1 Available under license
1.48 commons-logging 1.3.2
1.48.1 Available under license
1.49 commons-io 2.17.0
1.49.1 Available under license
1.50 jctools-core 4.0.5
1.50.1 Available under license
1.51 httpcomponents-core 4.4.16
1.51.1 Available under license
1.52 dagger 2.4
1.52.1 Available under license

1.53 httpcomponents-client 4.5.13
1.53.1 Available under license
1.54 jackson-annotations 2.17.3
1.54.1 Available under license
1.55 commons-fileupload 1.6.0
1.55.1 Available under license
1.56 guava 32.0.1-jre
1.56.1 Available under license
1.57 slf4j 2.0.16
1.57.1 Available under license
1.58 httpcore-nio 4.4.13
1.58.1 Available under license
1.59 xml-apis 1.4.01
1.59.1 Available under license
1.60 opentelemetry-exporter-otlp 1.29.0
1.60.1 Available under license
1.61 j2objc-annotations 2.8
1.61.1 Available under license
1.62 okhttp 4.11.0
1.62.1 Available under license
1.63 okio 3.6.0
1.63.1 Available under license
1.64 annotations 4.1.1.4
1.64.1 Available under license
1.65 httpcomponents-mime 4.5.14
1.65.1 Available under license
1.66 jackson-databind 2.17.1
1.66.1 Available under license
1.67 glibc-minimal-langpack 2.34-231.el9_7.2
1.67.1 Available under license
1.68 langpacks-en 3.0-16.el9
1.68.1 Available under license
1.69 libcom-err 1.46.5-8.el9
1.69.1 Available under license
1.70 libzstd 1.5.5-1.el9
1.70.1 Available under license
1.71 xz-libs 5.2.5-8.el9_0
1.71.1 Available under license
1.72 libusb 1.0.26-1.el9

1.72.1 Available under license
1.73 cpp 11.5.0-11.el9
1.73.1 Available under license
1.74 shadow-utils 2:4.9-15.el9
1.74.1 Available under license
1.75 attr 2.5.1-3.el9
1.75.1 Available under license
1.76 gpg-pubkey 5a6340b3-6229229e
1.76.1 Available under license
1.77 setup 2.13.7-10.el9
1.77.1 Available under license
1.78 libtool-ltdl 2.4.6-46.el9
1.78.1 Available under license
1.79 libsepol 3.6-3.el9
1.79.1 Available under license
1.80 dnf-data 4.14.0-31.el9
1.80.1 Available under license
1.81 gnutls 3.8.3-9.el9
1.81.1 Available under license
1.82 mpfr 4.1.0-7.el9
1.82.1 Available under license
1.83 ncurses-libs 6.2-12.20210508.el9
1.83.1 Available under license
1.84 libksba 1.5.1-7.el9
1.84.1 Available under license
1.85 open-ldap 2.6.8-4.el9
1.85.1 Available under license
1.86 crypto-policies 20250905-1.git377cc42.el9_7
1.86.1 Available under license
1.87 rpm 4.16.1.3-39.el9
1.87.1 Available under license
1.88 kerberos 1.21.1-8.el9_6
1.88.1 Available under license
1.89 dejavu-sans-fonts 2.37-18.el9
1.89.1 Available under license
1.90 redhatrelease 9.7-0.7.el9
1.90.1 Available under license
1.91 openssl-fips-provider 3.0.7-8.el9
1.91.1 Available under license

1.92 libgpg-error 1.42-5.el9
1.92.1 Available under license
1.93 audit 3.1.5-7.el9
1.93.1 Available under license
1.94 libnghttp2 1.43.0-6.el9
1.94.1 Available under license
1.95 langpacks-core-font-en 3.0-16.el9
1.95.1 Available under license
1.96 sed 4.8-9.el9
1.96.1 Available under license
1.97 gdbm-libs 1:1.23-1.el9
1.97.1 Available under license
1.98 alternatives 1.24-2.el9
1.98.1 Available under license
1.99 json-glib 1.6.6-1.el9
1.99.1 Available under license
1.100 libidn 2.3.0-7.el9
1.100.1 Available under license
1.101 lua 5.4.4-4.el9
1.101.1 Available under license
1.102 pcre 8.44-4.el9
1.102.1 Available under license
1.103 coreutils 8.32-39.el9
1.103.1 Available under license
1.104 lua-libs 5.4.4-4.el9
1.104.1 Available under license
1.105 libsemanage-common 3.6-5.el9_6
1.105.1 Available under license
1.106 openssl-fips-provider-so 3.0.7-8.el9
1.106.1 Available under license
1.107 libmodulemd 2.13.0-2.el9
1.107.1 Available under license
1.108 librepo 1.14.5-3.el9
1.108.1 Available under license
1.109 audit-lib 3.1.5-7.el9
1.109.1 Available under license
1.110 libunistring 0.9.10-15.el9
1.110.1 Available under license
1.111 bzip2 1.0.8-10.el9_5

1.111.1 Available under license
1.112 fonts-filesystem 1:2.0.5-7.el9.1
1.112.1 Available under license
1.113 file 5.39-16.el9
1.113.1 Available under license
1.114 findutils 1:4.8.0-7.el9
1.114.1 Available under license
1.115 langpacks-core-en 3.0-16.el9
1.115.1 Available under license
1.116 libassuan 2.5.5-3.el9
1.116.1 Available under license
1.117 libpkit 0.25.3-3.el9_5
1.117.1 Available under license
1.118 libsolv 0.7.24-3.el9
1.118.1 Available under license
1.119 shadow 2:4.9-15.el9
1.119.1 Available under license
1.120 libevent 2.1.12-8.el9_4
1.120.1 Available under license
1.121 gobject-introspection 1.68.0-11.el9
1.121.1 Available under license
1.122 keyutils-libs 1.6.3-1.el9
1.122.1 Available under license
1.123 popt 1.18-8.el9
1.123.1 Available under license
1.124 gawk 5.1.0-6.el9
1.124.1 Available under license
1.125 readline 8.1-4.el9
1.125.1 Available under license
1.126 gmp 1:6.2.0-13.el9
1.126.1 Available under license
1.127 libcap-ng 0.8.2-7.el9
1.127.1 Available under license
1.128 sqlite 3.34.1-9.el9_7
1.128.1 Available under license
1.129 libdnf 0.69.0-16.el9
1.129.1 Available under license
1.130 file-system 3.16-5.el9
1.130.1 Available under license

1.131 e2fsprogs 1.46.5-8.el9
1.131.1 Available under license
1.132 libtasn 4.16.0-9.el9
1.132.1 Available under license
1.133 librhsm 0.0.3-9.el9
1.133.1 Available under license
1.134 rpm-libs 4.16.1.3-39.el9
1.134.1 Available under license
1.135 libnettle6 3.10.1-1.el9
1.135.1 Available under license
1.136 grep 3.6-5.el9
1.136.1 Available under license
1.137 npth 1.6-8.el9
1.137.1 Available under license
1.138 libusbx 1.0.26-1.el9
1.138.1 Available under license
1.139 libstdc++ 11.5.0-11.el9
1.139.1 Available under license
1.140 glibc 2.34-231.el9_7.2
1.140.1 Available under license
1.141 libyaml 0.2.5-7.el9
1.141.1 Available under license
1.142 libarchive 3.5.3-6.el9_6
1.142.1 Available under license
1.143 keyutils 1.6.3-1.el9
1.143.1 Available under license
1.144 ncurses 6.2-12.20210508.el9
1.144.1 Available under license
1.145 gpg-pubkey fd431d51-4ae0493b
1.145.1 Available under license
1.146 gpgme 1.15.1-6.el9
1.146.1 Available under license
1.147 acl 2.3.1-4.el9
1.147.1 Available under license
1.148 cyrus-sasl 2.1.27-22.el9
1.148.1 Available under license
1.149 zlib 1.2.11-40.el9
1.149.1 Available under license
1.150 pcre2 10.40-6.el9

1.150.1 Available under license
1.151 libsigsegv 2.13-4.el9
1.151.1 Available under license
1.152 basesystem 11-13.el9
1.152.1 Available under license
1.153 libxcrypt 4.4.18-3.el9
1.153.1 Available under license
1.154 selinux 3.6-3.el9
1.154.1 Available under license
1.155 dnf 4.14.0-31.el9
1.155.1 Available under license
1.156 libreport-filesystem 2.15.2-6.el9
1.156.1 Available under license
1.157 lz4 1.9.3-5.el9
1.157.1 Available under license
1.158 libffi 3.4.2-8.el9
1.158.1 Available under license
1.159 json-c 0.14-11.el9
1.159.1 Available under license
1.160 libcap 2.48-10.el9
1.160.1 Available under license
1.161 bash 5.1.8-9.el9
1.161.1 Available under license
1.162 rootfiles 8.1-35.el9
1.162.1 Available under license
1.163 glibc-common 2.34-231.el9_7.2
1.163.1 Available under license
1.164 libgcrypt 1.10.0-11.el9
1.164.1 Available under license
1.165 libverto 0.3.2-3.el9
1.165.1 Available under license
1.166 libgcc 11.5.0-11.el9
1.166.1 Available under license
1.167 pcre2-syntax 10.40-6.el9
1.167.1 Available under license
1.168 readline 8.1
1.168.1 Available under license
1.169 berkeley-db 5.3.28
1.169.1 Available under license

1.170 chkconfig 1.24-2.el9
1.170.1 Available under license
1.171 libtool 2.4.6-46.el9
1.171.1 Available under license
1.172 gmp 4.3.4
1.172.1 Available under license
1.173 langpacks 3.0-16.el9
1.173.1 Available under license
1.174 zstd 1.5.5-1.el9
1.174.1 Available under license
1.175 xz 5.2.5-8.el9_0
1.175.1 Available under license
1.176 nghttp2 1.43.0-6.el9
1.176.1 Available under license
1.177 gdbm 1:1.23-1.el9
1.177.1 Available under license
1.178 dejavu-fonts 2.37-18.el9
1.178.1 Available under license
1.179 ca-certificates 2025.2.80_v9.0.305-91.el9
1.179.1 Available under license
1.180 libpeas 1.30.0-4.el9
1.180.1 Available under license
1.181 microdnf 3.9.1-3.el9
1.181.1 Available under license
1.182 okhttp 5.3.2
1.182.1 Available under license
1.183 libxml2 2.9.13-14.el9_7
1.183.1 Available under license
1.184 systemd-libs 252-55.el9_7.7
1.184.1 Available under license
1.185 systemd 252-55.el9_7.7
1.185.1 Available under license
1.186 tzdata 2025c-1.el9
1.186.1 Available under license
1.187 log4j-jcl 2.25.3
1.187.1 Available under license
1.188 log4j-api 2.25.3
1.188.1 Available under license
1.189 apache-log4j 2.25.3

1.189.1 Available under license
1.190 jctools-core 4.0.1
1.190.1 Available under license
1.191 gnupg 2.3.3-5.el9_7
1.191.1 Available under license
1.192 glib 2.68.4-18.el9_7.1
1.192.1 Available under license
1.193 curl-minimal 7.76.1-35.el9_7.3
1.193.1 Available under license
1.194 libcurl 7.76.1-35.el9_7.3
1.194.1 Available under license
1.195 curl 7.76.1-35.el9_7.3
1.195.1 Available under license
1.196 openssl 1:3.5.1-7.el9_7
1.196.1 Available under license
1.197 commons-jexl3 3.6.1
1.197.1 Available under license
1.198 disruptor 3.3.6-java8
1.198.1 Available under license
1.199 commons-codec 1.15.0
1.199.1 Available under license
1.200 io-opentelemetry-proto 0.11.0
1.200.1 Available under license
1.201 io-opentelemetry-exporter-otlp 1.29.0
1.201.1 Available under license
1.202 io-opentelemetry-semconv 1.29.0-alpha
1.202.1 Available under license
1.203 io-opentelemetry-sdk-autoconfigure-spi 1.29.0
1.203.1 Available under license
1.204 libuuid 2.37.4-21.el9_7
1.204.1 Available under license
1.205 util-linux 2.37.4-21.el9_7
1.205.1 Available under license
1.206 libmount 2.37.4-21.el9_7
1.206.1 Available under license

1.1 picocontainer 2.15

1.1.1 Available under license :

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
/***
* Copyright (C) PicoContainer Organization. All rights reserved. *
* -- *
* The software in this package is published under the terms of the BSD *
* style license a copy of which has been included with this distribution in *
* the LICENSE.txt file. *
* *
* Original code by *
***/

1.2 jetty-client 12.0.0

1.2.1 Available under license :

No license file was found, but licenses were detected in source scan.

// This program and the accompanying materials are made available under the
// terms of the Eclipse Public License v. 2.0 which is available at
// https://www.eclipse.org/legal/epl-2.0, or the Apache License, Version 2.0

Found in path(s):
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Response.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ProcessingProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/internal/HttpSenderOverHTTP.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpProxy.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/RandomConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpClientTransportDynamic.java

* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpSender.java
*
 /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Authentication.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/internal/NotifyingRequestListeners.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/InputStreamResponseListener.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/SendFailure.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/LeakTrackingConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/IConnection.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpExchange.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpRedirector.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/SPNEGOAuthentication.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/EarlyHintsProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ContentDecoder.java
*
 /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpRequest.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AbstractConnectorHttpClientTransport.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AbstractAuthentication.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ValidatingConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AuthenticationProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/internal/HttpReceiverOverHTTP.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Connection.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpDestination.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ContinueProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/PathRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ProtocolHandlers.java
*
 /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/RedirectProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpReceiver.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/FutureResponseListener.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/RoundRobinConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/DigestAuthentication.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpClient.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/internal/HttpConnectionOverHTTP.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ProxyProtocolClientConnectionFactory.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ProxyConfiguration.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AbstractHttpClientTransport.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/internal/HttpAuthenticationStore.java
*
 /jetty-client-12-0-0-sources-jar/module-info.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Origin.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/internal/HttpChannelOverHTTP.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AuthenticationStore.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Socks5Proxy.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpClientTransportOverHTTP.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/jmx/HttpClientMBean.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpResponse.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/internal/HttpContentResponse.java

* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/InputStreamRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/BytesRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpChannel.java
*
 /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpResponseException.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AbstractConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpConversation.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Request.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/FormRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpUpgrader.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpConnection.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/OutputStreamRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Destination.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/UpgradeProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Result.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/ResponseListeners.java
*
 /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/BufferingResponseListener.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ContentResponse.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ProxyAuthenticationProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Socks5.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/Socks4Proxy.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/DuplexConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/MultiPartRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/AsyncRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/WWWAuthenticationProtocolHandler.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/BasicAuthentication.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/GZIPContentDecoder.java
*
 /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/internal/TunnelRequest.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/HttpClientConnectionFactory.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/MultiplexConnectionPool.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpClientTransport.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/RequestListeners.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/HttpRequestException.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/StringRequestContent.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/transport/internal/ProtocolHttpUpgrader.java
* /jetty-client-12-0-0-sources-jar/org/eclipse/jetty/client/ByteBufferRequestContent.java

1.3 error_prone_annotations 2.3.3

1.3.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Error Prone Authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/NoAllocation.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/concurrent/UnlockMethod.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/concurrent/LockMethod.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Error Prone Authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/FormatString.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/FormatMethod.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/MustBeClosed.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/RestrictedApi.java
*
 /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/CompatibleWith.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Error Prone Authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/CanIgnoreReturnValue.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/RequiredModifiers.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/SuppressPackageLocation.java
*
 /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/CompileTimeConstant.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/Immutable.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/Var.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/IncompatibleModifiers.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/concurrent/LazyInit.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/ForOverride.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Error Prone Authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/DoNotCall.java
* /error-prone-annotations-2-3-3-sources-5-
jar/com/google/errorprone/annotations/OverridingMethodsMustInvokeSuper.java
* /error-prone-annotations-2-3-3-sources-5-jar/com/google/errorprone/annotations/CheckReturnValue.java
*

1.4 jackson 2.17.3

1.4.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work

by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.5 opentelemetry-sdk-extension-autoconfigure-spi 1.29.0

1.5.1 Available under license :

Apache-2.0

1.6 jackson-dataformat-yaml 2.17.3

1.6.1 Available under license :

This copy of Jackson JSON processor YAML module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivative works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson components are licensed under Apache (Software) License, version 2.0,
as per accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.7 opentelemetry-semconv 1.29.0-alpha

1.7.1 Available under license :

Apache-2.0

1.8 annotations 13.0

1.8.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2000-2013 JetBrains s.r.o.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/Contract.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/Flow.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2000-2009 JetBrains s.r.o.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/Nullable.java

* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/Nls.java
* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/PropertyKey.java
* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/NonNls.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006 Sascha Weinreuter
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/Pattern.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/PrintFormat.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/RegExp.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/Subst.java
*
 /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/Identifier.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/Language.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2000-2012 JetBrains s.r.o.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/NotNull.java
* /annotations-13-0-sources-6-jar/org/jetbrains/annotations/TestOnly.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/MagicConstant.java
* /annotations-13-0-sources-6-jar/org/intellij/lang/annotations/JdkConstants.java

1.9 listenablefuture 9999.0-empty-to-avoid-conflict-with-guava

1.9.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.10 jeromq 0.3.5

1.10.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,

the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2)

tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that

same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you

receive it, in any medium, provided that you conspicuously and
appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other

parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided

you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and

adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some

trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that

copyright
holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying
the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that
arrangement,
or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public
License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),

EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library
is deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying
Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters,
data structure
layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the

Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license
document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that,
taken together, effectively do not restrict modification of the
portions of the Library contained in the Combined Work and reverse
engineering for debugging such modifications, if you also do each of
the following:

a) Give prominent notice with each copy of the Combined Work that
the Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license
document.

c) For a Combined Work that displays
copyright notices during
execution, include the copyright notice for the Library among
these notices, as well as a reference directing the user to the
copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this
License, and the Corresponding Application Code in a form
suitable for, and under terms that permit, the user to
recombine or relink the Application with a modified version of
the Linked Version to produce a modified Combined Work, in the
manner specified by section 6 of the GNU GPL for conveying
Corresponding Source.

1) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (a) uses at run time
a copy of the Library already present on the user's computer
system, and (b) will operate properly with a modified version
of the Library that is interface-compatible
with the Linked
Version.

e) Provide Installation Information, but only if you would otherwise
be required to provide such information under section 6 of the
GNU GPL, and only to the extent that such information is

necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the

Library.

SPECIAL EXCEPTION GRANTED BY COPYRIGHT HOLDERS

As a special exception, copyright holders give you permission to link this
library with independent modules to produce an executable, regardless of
the license terms of these independent modules, and to copy and distribute
the
resulting executable under terms of your choice, provided that you also
meet, for each linked independent module, the terms and conditions of
the license of that module. An independent module is a module which is not
derived from or based on this library. If you modify this library, you must
extend this exception to your version of the library.

Parts of the software are licensed under the MIT (X11) license as follows:

Copyright (c) 2007-2010 Contributors as listed in AUTHORS

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.11 jackson 2.17.1

1.11.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

FastDoubleParser

jackson-core bundles a shaded copy of FastDoubleParser <https://github.com/wrandelshofer/FastDoubleParser>.
That code is available under an MIT license
<https://github.com/wrandelshofer/FastDoubleParser/blob/main/LICENSE>
under the following

copyright.

Copyright 2023 Werner Randelshofer, Switzerland. MIT License.

See FastDoubleParser-NOTICE for details of other source code included in FastDoubleParser
and the licenses and copyrights that apply to that code.

1.12 protobuf-java 3.25.8

1.12.1 Available under license :

No license file was found, but licenses were detected in source scan.

java.util.List<com.google.protobuf.DescriptorProtos.FieldOptions.OptionTargetType> getTargetsList();
getEditionDefaultsList();
public java.util.List<com.google.protobuf.DescriptorProtos.FieldOptions.OptionTargetType> getTargetsList() {
public java.util.List<com.google.protobuf.DescriptorProtos.FieldOptions.EditionDefault> getEditionDefaultsList() {
if (!getEditionDefaultsList()
.equals(other.getEditionDefaultsList())) return false;
hash = (53 * hash) + getEditionDefaultsList().hashCode();
public java.util.List<com.google.protobuf.DescriptorProtos.FieldOptions.OptionTargetType> getTargetsList() {
public java.util.List<com.google.protobuf.DescriptorProtos.FieldOptions.EditionDefault> getEditionDefaultsList() {
getDefaultsList();
public java.util.List<com.google.protobuf.DescriptorProtos.FeatureSetDefaults.FeatureSetEditionDefault>
getDefaultsList() {
if (!getDefaultsList()
.equals(other.getDefaultsList())) return false;
hash
 = (53 * hash) + getDefaultsList().hashCode();
public java.util.List<com.google.protobuf.DescriptorProtos.FeatureSetDefaults.FeatureSetEditionDefault>
getDefaultsList() {
getLeadingDetachedCommentsList();
getLeadingDetachedCommentsList() {
size += 1 * getLeadingDetachedCommentsList().size();
if (!getLeadingDetachedCommentsList()
.equals(other.getLeadingDetachedCommentsList())) return false;
hash = (53 * hash) + getLeadingDetachedCommentsList().hashCode();
getLeadingDetachedCommentsList() {

Found in path(s):
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/DescriptorProtos.java
No license file was found, but licenses were detected in source scan.

// Copyright 2008 Google Inc. All rights reserved.

Found in path(s):
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ProtocolStringList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/SingleFieldBuilder.java

* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ProtobufArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Android.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageOrBuilder.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Java8Compatibility.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/TypeRegistry.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/GeneratedMessageLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/DynamicMessage.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ByteBufferWriter.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/TextFormat.java
*
/protobuf-java-3-25-8-sources-jar/com/google/protobuf/Parser.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageInfoFactory.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/DoubleArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/IterableByteBufferInputStream.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldSchemaFull.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CompileTimeConstant.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RepeatedFieldBuilder.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RpcCallback.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ProtoSyntax.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RopeByteString.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ServiceException.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CodedInputStream.java
*
/protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionRegistryFactory.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Internal.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnknownFieldSetLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/NewInstanceSchemaLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnknownFieldSetSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldSchemaLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/OneofInfo.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/StructuralMessageInfo.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/NewInstanceSchemas.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CodedInputStreamReader.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageSetSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/LazyFieldLite.java
*
/protobuf-java-3-25-8-sources-jar/com/google/protobuf/TextFormatEscaper.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ManifestSchemaFactory.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/NioByteString.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RawMessageInfo.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/AbstractMessage.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/GeneratedMessageInfoFactory.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/TextFormatParseLocation.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/TextFormatParseInfoTree.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageLiteOrBuilder.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnknownFieldSetLiteSchema.java

* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/JavaType.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/BufferAllocator.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/AbstractProtobufList.java
*
 /protobuf-java-3-25-8-sources-jar/com/google/protobuf/BlockingService.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RpcController.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionRegistry.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Schema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/FloatArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/FieldSet.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/InlineMe.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/GeneratedMessage.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Utf8.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/FieldInfo.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/BlockingRpcChannel.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Protobuf.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionLite.java
*
 /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapEntry.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/WireFormat.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnknownFieldSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RepeatedFieldBuilderV3.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/IntArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/BinaryReader.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnknownFieldSet.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/LazyField.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Reader.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionSchemaFull.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/NewInstanceSchemaFull.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/FieldType.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CheckReturnValue.java
*
 /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionSchemaLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/LazyStringArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/NewInstanceSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CodedOutputStream.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionSchemas.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/InvalidProtocolBufferException.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnsafeUtil.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/SchemaUtil.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/BooleanArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/DescriptorMessageInfoFactory.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/LegacyDescriptorsUtil.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RpcUtil.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageLiteToString.java
*
 /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Service.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/AbstractMessageLite.java

* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Extension.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ByteString.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CodedOutputStreamWriter.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/SmallSortedMap.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ByteOutput.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/PrimitiveNonBoxingCollection.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MutabilityOracle.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ListFieldSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Message.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/GeneratedMessageV3.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/CanIgnoreReturnValue.java
*
/protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExtensionRegistryLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UninitializedMessageException.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageReflection.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnsafeByteOperations.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapEntryLite.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldBuilder.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Descriptors.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/DiscardUnknownFieldsParser.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/UnmodifiableLazyStringList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ProtocolMessageEnum.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/Writer.java
*
/protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldSchemas.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageInfo.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/LongArrayList.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ArrayDecoders.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/ExperimentalApi.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/SchemaFactory.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/SingleFieldBuilderV3.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/AbstractParser.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/AllocatedBuffer.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldReflectionAccessor.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapFieldSchema.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MapField.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/LazyStringList.java
*
/protobuf-java-3-25-8-sources-jar/com/google/protobuf/BinaryWriter.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/RpcChannel.java
* /protobuf-java-3-25-8-sources-jar/com/google/protobuf/MessageSchema.java

1.13 uuid-creator 6.1.1

1.13.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* MIT License
*
* Copyright (c) 2018-2025 Fabio Lima
*
* Permission is hereby granted, free of charge, to any person obtaining a copy
* of this software and associated documentation files (the "Software"), to deal
* in the Software without restriction, including without limitation the rights
* to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
* copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in all
* copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
* IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
* FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
* AUTHORS OR COPYRIGHT HOLDERS BE LIABLE
FOR ANY CLAIM, DAMAGES OR OTHER
* LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
* SOFTWARE.
*/

Found in path(s):
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/StandardStringCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/Base16Codec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/nonstandard/PrefixCombFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/NodeIdFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/MacNodeIdFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/other/DotNetGuid1Codec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/nonstandard/ShortSuffixCombFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/internal/RandomUtil.java
*
/uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/BaseN.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNRemainderDecoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/Base32Codec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/Base64Encoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/Base32Decoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/AbstRandomBasedFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/other/NcnameCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/alt/GUID.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/UuidCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/Base16Encoder.java

* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/AbstNameBasedFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultTimeFunction.java
*
 /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/BaseNCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/nonstandard/ShortPrefixCombFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/Base64UrlCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/Base64Codec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/Base64Decoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/TimeBasedFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/StandardBinaryCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/Base16Decoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNDecoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/Base32Encoder.java
*
 /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/TimeOrderedEpochFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/UuidFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/MachineId.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/UuidBuilder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/UriCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/immutable/CharArray.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultClockSeqFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNRemainderEncoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/internal/SettingsUtil.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultNodeIdFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/immutable/ByteArray.java
*
 /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/UuidCreator.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/AbstCombFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/enums/UuidVersion.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/RandomNodeIdFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/other/TimeOrderedCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/HashNodeIdFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/enums/UuidNamespace.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/UrnCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/DceSecurityFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultRandomFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/RandomFunction.java
*
 /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/NameBasedMd5Factory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/TimeOrderedFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/TimeFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/UuidTime.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/impl/WindowsTimeFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/enums/UuidLocalDomain.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/NameBasedSha1Factory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/function/ClockSeqFunction.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/other/SlugCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/exception/InvalidUuidException.java

*
/uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNEncoder.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/AbstTimeBasedFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/nonstandard/SuffixCombFactory.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/UuidValidator.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/Base62Codec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/enums/UuidVariant.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/internal/ByteUtil.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/internal/NetworkUtil.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/base/Base58BtcCodec.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/CombUtil.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/factory/standard/RandomBasedFactory.java
*
/uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/UuidUtil.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/UuidComparator.java
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/codec/other/DotNetGuid4Codec.java
No license file was found, but licenses were detected in source scan.

/*
* MIT License
*
* Copyright (c) 2018-2025 Fabio Lima
*
* Permission is hereby granted, free of charge, to any person obtaining a copy
* of this software and associated documentation files (the "Software"), to deal
* in the Software without restriction, including without limitation the rights
* to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
* copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in all
* copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
* IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
* FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
* AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER
* LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
* SOFTWARE.
*/

Found in path(s):
* /uuid-creator-6-1-1-sources-1-jar/com/github/f4b6a3/uuid/util/internal/JavaVersionUtil.java
No license file was found, but licenses were detected in source scan.

<name>MIT License</name>

Found in path(s):
* /uuid-creator-6-1-1-sources-1-jar/META-INF/maven/com.github.f4b6a3/uuid-creator/pom.xml

1.14 jcl-over-slf4j 2.0.17

1.14.1 Available under license :

Copyright (c) 2004-2022 QOS.ch Sarl (Switzerland)
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.15 jsr305 3.0.2

1.15.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2005 Brian Goetz
* Released under the Creative Commons Attribution License
* (http://creativecommons.org/licenses/by/2.5)
* Official home: http://www.jcip.net
*/

Found in path(s):
* /jsr305-3-0-2-sources-12-jar/javax/annotation/concurrent/Immutable.java
* /jsr305-3-0-2-sources-12-jar/javax/annotation/concurrent/GuardedBy.java
* /jsr305-3-0-2-sources-12-jar/javax/annotation/concurrent/NotThreadSafe.java

* /jsr305-3-0-2-sources-12-jar/javax/annotation/concurrent/ThreadSafe.java

1.16 httpcomponents-core 4.4.13

1.16.1 Available under license :

Apache HttpCore
Copyright 2005-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s)

with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.17 error_prone_annotations 2.23.0

1.17.1 Available under license :

No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Created-By: Maven JAR Plugin 3.2.2
Build-Jdk-Spec: 17
Automatic-Module-Name: com.google.errorprone.annotations
Bundle-Description: Error Prone is a static analysis tool for Java that
catches common programming mistakes at compile-time.
Bundle-DocURL: https://errorprone.info/error_prone_annotations
Bundle-License: "Apache 2.0";link="http://www.apache.org/licenses/LICENS
E-2.0.txt"
Bundle-ManifestVersion: 2

Bundle-Name: error-prone annotations
Bundle-SCM: url="https://github.com/google/error-prone/error_prone_annot
ations",connection="scm:git:https://github.com/google/error-prone.git/e
rror_prone_annotations",developer-connection="scm:git:git@github.com:go
ogle/error-prone.git/error_prone_annotations",tag=HEAD
Bundle-SymbolicName: com.google.errorprone.annotations
Bundle-Vendor: Google LLC
Bundle-Version: 2.23.0
Export-Package: com.google.errorprone.annotations;uses:="javax.lang.mode
l.element";version="2.23.0",com.google.errorprone.annotations.concurren
t;version="2.23.0"
Import-Package: javax.lang.model.element
Require-Capability: osgi.ee;filter:="(&(osgi.ee=JavaSE)(version=1.8))"

Found in path(s):
* /error-prone-annotations-2-23-0-4-jar/META-INF/MANIFEST.MF
No license file was found, but licenses were detected in source scan.

<!--
Copyright 2015 The Error Prone Authors.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
-->

Found in path(s):
* /error-prone-annotations-2-23-0-4-jar/META-
INF/maven/com.google.errorprone/error_prone_annotations/pom.xml

1.18 commons-jexl 3.4.0

1.18.1 Available under license :

Apache Commons JEXL
Copyright 2001-2024 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate

comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.19 commons-math 2.2

1.19.1 Available under license :

Apache Commons Math
Copyright 2001-2011 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

==========

The BracketFinder (package org.apache.commons.math.optimization.univariate)
and PowellOptimizer (package org.apache.commons.math.optimization.general)
classes are based on the Python code in module "optimize.py" (version 0.5)
developed by Travis E. Oliphant for the SciPy library (http://www.scipy.org/)
Copyright Â© 2003-2009 SciPy Developers.
==========

The LinearConstraint, LinearObjectiveFunction, LinearOptimizer,
RelationShip, SimplexSolver and SimplexTableau classes in package
org.apache.commons.math.optimization.linear include software developed by
Benjamin McCann (http://www.benmccann.com) and distributed with
the following copyright: Copyright
2009 Google Inc.
==========

This product includes software developed by the
University of Chicago, as Operator of Argonne National

Laboratory.
The LevenbergMarquardtOptimizer class in package
org.apache.commons.math.optimization.general includes software
translated from the lmder, lmpar and qrsolv Fortran routines
from the Minpack package
Minpack Copyright Notice (1999) University of Chicago. All rights reserved
==========

The GraggBulirschStoerIntegrator class in package
org.apache.commons.math.ode.nonstiff includes software translated
from the odex Fortran routine developed by E. Hairer and G. Wanner.
Original source copyright:
Copyright (c) 2004, Ernst Hairer
==========

The EigenDecompositionImpl class in package
org.apache.commons.math.linear includes
software translated
from some LAPACK Fortran routines. Original source copyright:
Copyright (c) 1992-2008 The University of Tennessee. All rights reserved.
==========

The MersenneTwister class in package org.apache.commons.math.random
includes software translated from the 2002-01-26 version of
the Mersenne-Twister generator written in C by Makoto Matsumoto and Takuji
Nishimura. Original source copyright:
Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,
All rights reserved
==========

The complete text of licenses and disclaimers associated with the the original
sources enumerated above at the time of code translation are in the LICENSE.txt
file.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication
on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

APACHE COMMONS MATH DERIVATIVE WORKS:

The Apache commons-math library includes a number of subcomponents
whose implementation is derived from original sources written
in C or Fortran. License terms of the original sources
are reproduced below.

==========

For the lmder, lmpar and qrsolv Fortran routine from minpack and translated in
the LevenbergMarquardtOptimizer
class in package
org.apache.commons.math.optimization.general
Original source copyright and license statement:

Minpack Copyright Notice (1999) University of Chicago. All rights reserved

Redistribution and use in source and binary forms, with or
without modification, are permitted provided that the
following conditions are met:

1. Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials
provided with the distribution.

3. The end-user documentation included with the
redistribution, if any, must include the following
acknowledgment:

"This product includes software developed by the
University of Chicago, as Operator of Argonne National
Laboratory.

Alternately, this acknowledgment may appear in the
software
itself, if and wherever such third-party acknowledgments

normally appear.

4. WARRANTY DISCLAIMER. THE SOFTWARE IS SUPPLIED "AS IS"
WITHOUT WARRANTY OF ANY KIND. THE COPYRIGHT HOLDER, THE
UNITED STATES, THE UNITED STATES DEPARTMENT OF ENERGY, AND
THEIR EMPLOYEES: (1) DISCLAIM ANY WARRANTIES, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE
OR NON-INFRINGEMENT, (2) DO NOT ASSUME ANY LEGAL LIABILITY
OR RESPONSIBILITY FOR THE ACCURACY, COMPLETENESS, OR
USEFULNESS OF THE SOFTWARE, (3) DO NOT REPRESENT THAT USE OF
THE SOFTWARE WOULD NOT INFRINGE PRIVATELY OWNED RIGHTS, (4)
DO NOT WARRANT THAT THE SOFTWARE WILL FUNCTION
UNINTERRUPTED, THAT IT IS ERROR-FREE OR THAT ANY ERRORS WILL
BE CORRECTED.

5. LIMITATION OF LIABILITY. IN NO EVENT WILL THE COPYRIGHT
HOLDER, THE UNITED STATES, THE UNITED STATES DEPARTMENT OF
ENERGY, OR THEIR EMPLOYEES: BE LIABLE FOR ANY INDIRECT,
INCIDENTAL, CONSEQUENTIAL,
SPECIAL OR PUNITIVE DAMAGES OF
ANY KIND OR NATURE, INCLUDING BUT NOT LIMITED TO LOSS OF
PROFITS OR LOSS OF DATA, FOR ANY REASON WHATSOEVER, WHETHER
SUCH LIABILITY IS ASSERTED ON THE BASIS OF CONTRACT, TORT
(INCLUDING NEGLIGENCE OR STRICT LIABILITY), OR OTHERWISE,
EVEN IF ANY OF SAID PARTIES HAS BEEN WARNED OF THE
POSSIBILITY OF SUCH LOSS OR DAMAGES.
==========

Copyright and license statement for the odex Fortran routine developed by
E. Hairer and G. Wanner and translated in GraggBulirschStoerIntegrator class
in package org.apache.commons.math.ode.nonstiff:

Copyright (c) 2004, Ernst Hairer

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

- Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

- Redistributions in
binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
==========

Copyright
 and license statement for the original lapack fortran routines
translated in EigenDecompositionImpl class in package
org.apache.commons.math.linear:

Copyright (c) 1992-2008 The University of Tennessee. All rights reserved.

$COPYRIGHT$

Additional copyrights may follow

$HEADER$

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

- Redistributions of source code must retain the above copyright
 notice, this list of conditions and the following disclaimer.

- Redistributions in binary form must reproduce the above copyright
 notice, this list of conditions and the following disclaimer listed
 in this license in the documentation and/or other materials
 provided with the distribution.

- Neither the name of the copyright holders nor the names of its
 contributors may be used to endorse or promote products derived
 from
 this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,

SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
===

Copyright and license statement for the original Mersenne twister C routines
translated in MersenneTwister class in package org.apache.commons.math.random:

Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. The names of its contributors may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.20 commons-codec 1.17.1

1.20.1 Available under license :

Apache Commons Codec
Copyright 2002-2024 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work

by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.21 kotlin 1.9.10

1.21.1 Available under license :

Apache License 2.0

1.22 javax-inject 1

1.22.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2009 The JSR-330 Expert Group
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /javax-inject-1-sources-jar/javax/inject/Singleton.java
* /javax-inject-1-sources-jar/javax/inject/Inject.java
* /javax-inject-1-sources-jar/javax/inject/Scope.java
* /javax-inject-1-sources-jar/javax/inject/Qualifier.java
* /javax-inject-1-sources-jar/javax/inject/Named.java
* /javax-inject-1-sources-jar/javax/inject/Provider.java
*
 /javax-inject-1-sources-jar/javax/inject/package-info.java

1.23 jackson-dataformat-yaml 2.17.1

1.23.1 Available under license :

This copy of Jackson JSON processor YAML module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivative works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson components are licensed under Apache (Software) License, version 2.0,
as per accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.24 snake-yaml 2.2

1.24.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* Copyright (c) 2008, SnakeYAML
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/error/Mark.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/resolver/Resolver.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/CustomClassLoaderConstructor.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/error/MarkedYAMLException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/scanner/ScannerImpl.java
*
 /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/representer/SafeRepresenter.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/Node.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/serializer/SerializerException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/inspector/TagInspector.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/error/YAMLException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/Event.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/Yaml.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/DocumentEndEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/inspector/UnTrustedTagInspector.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/SequenceStartEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/serializer/NumberAnchorGenerator.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/CollectionNode.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/BaseConstructor.java
*
 /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/emitter/EmitterState.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/FlowSequenceStartToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/comments/CommentEventsCollector.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/util/ArrayUtils.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/composer/ComposerException.java

* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/comments/CommentType.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/SequenceNode.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/parser/VersionTagsTuple.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/ValueToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/NodeTuple.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/util/ArrayStack.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/reader/StreamReader.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/composer/Composer.java
*
/snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/emitter/ScalarAnalysis.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/internal/Logger.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/FlowMappingStartToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/NodeEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/reader/ReaderException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/DocumentEndToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/util/EnumUtils.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/parser/ParserImpl.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/emitter/Emitter.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/CollectionEndEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/PropertySubstitute.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/Property.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/ScalarNode.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/TagTuple.java
*
/snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/serializer/Serializer.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/SafeConstructor.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/StreamStartEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/representer/BaseRepresenter.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/BlockEntryToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/CommentToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/StreamEndToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/SequenceEndEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/scanner/ScannerException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/emitter/Emitable.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/AliasEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/DirectiveToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/DocumentStartEvent.java
*
/snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/CollectionStartEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/AliasToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/emitter/EmitterException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/env/EnvScalarConstructor.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/GenericProperty.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/AnchorToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/util/PlatformFeatureDetector.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/NodeId.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/DocumentStartToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/BlockMappingStartToken.java

* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/BeanAccess.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/StreamStartToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/parser/Production.java
*
 /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/parser/ParserException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/AnchorNode.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/FlowSequenceEndToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/scanner/Constant.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/scanner/Scanner.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/ScalarToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/comments/CommentLine.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/CommentEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/Construct.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/ImplicitTuple.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/ScalarEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/error/MissingEnvironmentVariableException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/representer/Represent.java
*
 /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/Tag.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/StreamEndEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/extensions/compactnotation/PackageCompactConstructor.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/AbstractConstruct.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/Constructor.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/PropertyUtils.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/DumperOptions.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/MissingProperty.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/nodes/MappingNode.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/FlowEntryToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/TagToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/parser/Parser.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/MappingEndEvent.java
*
 /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/ConstructorException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/extensions/compactnotation/CompactConstructor.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/extensions/compactnotation/CompactData.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/reader/UnicodeReader.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/representer/Representer.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/util/UriEncoder.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/KeyToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/events/MappingStartEvent.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/TypeDescription.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/LoaderOptions.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/MethodProperty.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/BlockEndToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/resolver/ResolverTuple.java
*
 /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/BlockSequenceStartToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/serializer/AnchorGenerator.java

* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/introspector/FieldProperty.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/FlowMappingEndToken.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/tokens/Token.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/constructor/DuplicateKeyException.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/scanner/SimpleKey.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2008 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /snakeyaml-2-2-sources-
jar/org/yaml/snakeyaml/external/com/google/gdata/util/common/base/UnicodeEscaper.java
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/external/com/google/gdata/util/common/base/Escaper.java
* /snakeyaml-2-2-sources-
jar/org/yaml/snakeyaml/external/com/google/gdata/util/common/base/PercentEscaper.java
No license file was found, but licenses were detected in source scan.

<name>Apache License, Version 2.0</name>
<url>http://www.apache.org/licenses/LICENSE-2.0.txt</url>

Found in path(s):
* /snakeyaml-2-2-sources-jar/META-INF/maven/org.yaml/snakeyaml/pom.xml
No license file was found, but licenses were detected in source scan.

// This module is multi-licensed and may be used under the terms
// EPL, Eclipse Public License, V1.0 or later, http://www.eclipse.org/legal
// LGPL, GNU Lesser General Public License, V2.1 or later, http://www.gnu.org/licenses/lgpl.html
// GPL, GNU General Public License, V2 or later, http://www.gnu.org/licenses/gpl.html
// AL, Apache License, V2.0 or later, http://www.apache.org/licenses
// BSD, BSD License, http://www.opensource.org/licenses/bsd-license.php
/**
* A Base64 encoder/decoder.
*
* <p>
* This class is used to encode and decode data in Base64 format as described in RFC 1521.

*
* <p>
* Project home page: www.
* source-code.biz/base64coder/java
* Author: Christian d'Heureuse, Inventec Informatik AG, Zurich, Switzerland
* Multi-licensed: EPL / LGPL / GPL / AL / BSD.
*/

Found in path(s):
* /snakeyaml-2-2-sources-jar/org/yaml/snakeyaml/external/biz/base64Coder/Base64Coder.java

1.25 common 8.3.1

1.25.1 Available under license :

Lists of 45 third-party dependencies.
(GPLv3 with Classpath Exception) Annotations (com.cedarsoft:annotations:8.3.1 - http://www.cedarsoft.org/parent/annotations)
(Apache License Version 2.0) Unit (com.cedarsoft:unit:8.3.1 - http://www.cedarsoft.org/parent/unit)
(GPLv3 with Classpath Exception) commons.Crypt (com.cedarsoft.commons:crypt:8.3.1 - http://www.cedarsoft.org/commons/crypt)
(GPLv3 with Classpath Exception) commons.Test Utils (com.cedarsoft.commons:test-utils:8.3.1 - http://www.cedarsoft.org/commons/test-utils)
(GPLv3 with Classpath Exception) commons.XML Commons (com.cedarsoft.commons:xml-commons:8.3.1 - http://www.cedarsoft.org/commons/xml-commons)
(The Apache Software License, Version 2.0) Jackson-annotations (com.fasterxml.jackson.core:jackson-annotations:2.8.9 - http://github.com/FasterXML/jackson)
(The Apache Software License, Version 2.0) Jackson-core (com.fasterxml.jackson.core:jackson-core:2.8.9 - https://github.com/FasterXML/jackson-core)
(The Apache Software License, Version 2.0) jackson-databind (com.fasterxml.jackson.core:jackson-databind:2.8.9 - http://github.com/FasterXML/jackson)
(The Apache Software License, Version 2.0) FindBugs-jsr305 (com.google.code.findbugs:jsr305:3.0.2 - http://findbugs.sourceforge.net/)
(Apache 2.0) error-prone annotations (com.google.errorprone:error_prone_annotations:2.0.21 - http://nexus.sonatype.org/oss-repository-hosting.html/error_prone_parent/error_prone_annotations)
(The Apache Software License, Version 2.0) Guava: Google Core Libraries for Java (com.google.guava:guava:22.0 - https://github.com/google/guava/guava)
(The Apache Software License, Version 2.0) J2ObjC Annotations (com.google.j2objc:j2objc-annotations:1.1 - https://github.com/google/j2objc/)
(Apache License 2) IntelliJ IDEA Annotations (com.intellij:annotations:12.0 - http://www.jetbrains.org)
(Free commercial license) (GPL with classpath exception) JIDE Common Layer (com.jidesoft:jide-oss:3.6.18 - https://github.com/jidesoft/jide-oss)
(BSD) MiGLayout Core (com.miglayout:miglayout-core:5.0 - http://www.miglayout.com/miglayout-core/)
(BSD) MiGLayout Swing (com.miglayout:miglayout-swing:5.0 - http://www.miglayout.com/miglayout-swing/)
(Apache License, Version 2.0) Apache Commons Codec (commons-codec:commons-codec:1.10 - http://commons.apache.org/proper/commons-codec/)
(Apache License, Version 2.0) Apache Commons IO (commons-io:commons-io:2.5 -

http://commons.apache.org/proper/commons-io/)

(The Apache Software License, Version 2.0) javax.inject (javax.inject:javax.inject:1 - http://code.google.com/p/atinject/)

(Eclipse Public License 1.0) JUnit (junit:junit:4.12 - http://junit.org)

(The Apache Software License, Version 2.0) Byte Buddy (without dependencies) (net.bytebuddy:byte-buddy:1.6.14 - http://bytebuddy.net/byte-buddy)

(The Apache Software License, Version 2.0) Byte Buddy Java agent (net.bytebuddy:byte-buddy-agent:1.6.14 - http://bytebuddy.net/byte-buddy-agent)

(Apache License, Version 2.0) Apache Commons Lang (org.apache.commons:commons-lang3:3.6 - http://commons.apache.org/proper/commons-lang/)

(Apache License, Version 2.0) AssertJ fluent assertions (org.assertj:assertj-core:3.8.0 - http://assertj.org/assertj-core)

(MIT license) Animal Sniffer Annotations (org.codehaus.mojo:animal-sniffer-annotations:1.14 - http://mojo.codehaus.org/animal-sniffer/animal-sniffer-annotations)

(Apache 2) EasyMock (org.easymock:easymock:3.4 - http://easymock.org/easymock)

(Apache 2) EasyMock Class extension (org.easymock:easymockclassextension:3.2 - http://www.easymock.org/easymockclassextension)

(Apache License, Version 2.0) FEST Reflection (org.easytesting:fest-reflect:1.4.1 - http://fest.easytesting.org/reflect)

(Apache License, Version 2.0) FEST Util (org.easytesting:fest-util:1.2.4 - http://fest.easytesting.org)

(New BSD License) Hamcrest Core (org.hamcrest:hamcrest-core:1.3 - https://github.com/hamcrest/JavaHamcrest/hamcrest-core)

(The Apache Software License, Version 2.0) IntelliJ IDEA Annotations (org.jetbrains:annotations:13.0 - http://www.jetbrains.org)

(The Apache License, Version 2.0) org.jetbrains.kotlin:kotlin-reflect (org.jetbrains.kotlin:kotlin-reflect:1.1.3 - https://kotlinlang.org/)

(The Apache License, Version 2.0) org.jetbrains.kotlin:kotlin-stdlib (org.jetbrains.kotlin:kotlin-stdlib:1.1.3 - https://kotlinlang.org/)

(The Apache License, Version 2.0) org.jetbrains.kotlin:kotlin-stdlib-jre7 (org.jetbrains.kotlin:kotlin-stdlib-jre7:1.1.3 - https://kotlinlang.org/)

(The Apache License, Version 2.0) org.jetbrains.kotlin:kotlin-stdlib-jre8 (org.jetbrains.kotlin:kotlin-stdlib-jre8:1.1.3 - https://kotlinlang.org/)

(The Apache License, Version 2.0) org.jetbrains.kotlin:kotlin-test-jvm (org.jetbrains.kotlin:kotlin-test:1.1.3 - https://kotlinlang.org/)

(Eclipse Public License v1.0) org.junit.jupiter:junit-jupiter-api (org.junit.jupiter:junit-jupiter-api:5.0.0-M4 - http://junit.org/junit5/)

(Eclipse Public License v1.0) org.junit.platform:junit-platform-commons (org.junit.platform:junit-platform-commons:1.0.0-M4 - http://junit.org/junit5/)

(Eclipse Public License v1.0) org.junit.platform:junit-platform-engine (org.junit.platform:junit-platform-engine:1.0.0-M4 - http://junit.org/junit5/)

(Eclipse Public License v1.0) org.junit.vintage:junit-vintage-engine (org.junit.vintage:junit-vintage-engine:4.12.0-M4 - http://junit.org/junit5/)

(The MIT License) mockito-core (org.mockito:mockito-core:2.8.47 - https://github.com/mockito/mockito)

(Apache 2) Objenesis (org.objenesis:objenesis:2.2 - http://objenesis.org)

(The Apache License, Version 2.0) org.opentest4j:opentest4j (org.opentest4j:opentest4j:1.0.0-M2 - https://github.com/ota4j-team/opentest4j)

(MIT License) SLF4J API Module (org.slf4j:slf4j-api:1.7.25 - http://www.slf4j.org)

(BSD License) XMLUnit for Java (xmlunit:xmlunit:1.6

- http://www.xmlunit.org/)

1.26 javassist 3.29.2-GA

1.26.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Javassist, a Java-bytecode translator toolkit.
* Copyright (C) 1999- Shigeru Chiba. All Rights Reserved.
*
* The contents of this file are subject to the Mozilla Public License Version
* 1.1 (the "License"); you may not use this file except in compliance with
* the License. Alternatively, the contents of this file may be used under
* the terms of the GNU Lesser General Public License Version 2.1 or later,
* or the Apache License Version 2.0.
*
* Software distributed under the License is distributed on an "AS IS" basis,
* WITHOUT WARRANTY OF ANY KIND, either express or implied. See the License
* for the specific language governing rights and limitations under the
* License.
*/

Found in path(s):
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ByteStream.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/Callback.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtConstructor.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/InnerClassesAttribute.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/compiler/Lex.java
* /javassist-3-29-2-ga-sources-jar/javassist/scopedpool/ScopedClassPoolFactoryImpl.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtNewClass.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/NewExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/CodeIterator.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtNewWrappedConstructor.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/FieldAccess.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/Loader.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/IntQueue.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Member.java
* /javassist-3-29-2-ga-sources-jar/javassist/scopedpool/ScopedClassPool.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/LineNumberAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/BinExpr.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/StackMap.java
* /javassist-3-29-2-ga-sources-jar/javassist/runtime/Desc.java
* /javassist-3-29-2-ga-sources-jar/javassist/scopedpool/SoftValueHashMap.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/web/Viewer.java

* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/stackmap/BasicBlock.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/FactoryHelper.java
* /javassist-3-29-2-ga-sources-jar/javassist/Modifier.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/Type.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/NestMembersAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/ByteArrayClassPath.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/MemberCodeGen.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/NestHostAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/KeywordTable.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/Expr.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Pair.java
* /javassist-3-29-2-ga-sources-jar/javassist/ClassClassPath.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/AccessFlag.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/Transformer.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/HotSwapAgent.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ProceedHandler.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtClassType.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/FieldInfo.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/ObjectNotFoundException.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformNewClass.java
* /javassist-3-29-2-ga-sources-jar/javassist/runtime/Inner.java
* /javassist-3-29-2-ga-sources-jar/javassist/ClassMap.java
* /javassist-3-29-2-ga-sources-jar/javassist/ClassPoolTail.java
* /javassist-3-29-2-ga-sources-jar/javassist/ClassPath.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ClassFilePrinter.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/compiler/TypeChecker.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ParameterAnnotationsAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformAfter.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ConstantAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/ClassPool.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/DeprecatedAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/web/BadHttpRequest.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/ProxyFactory.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/CastExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/ASTree.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/Frame.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtNewMethod.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/stackmap/TypeData.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtPrimitiveType.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/stackmap/MapMaker.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/InstanceOfExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/SerializedProxy.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/ExprEditor.java
* /javassist-3-29-2-ga-sources-jar/javassist/Translator.java
* /javassist-3-29-2-ga-sources-jar/javassist/LoaderClassPath.java

* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/Analyzer.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformReadField.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/Handler.java
* /javassist-3-29-2-ga-sources-jar/javassist/scopedpool/ScopedClassPoolFactory.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/NoSuchClassError.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/BadBytecode.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Stmnt.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ByteArray.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Symbol.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformCall.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformFieldAccess.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/AppletServer.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/Parser.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/Proxy.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Keyword.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/NewArray.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/CallExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/CodeConverter.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/DoubleConst.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformAccessArrayField.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/ObjectImporter.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/CannotReflectException.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformWriteField.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/Opcode.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/EnclosingMethodAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/MultiArrayType.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/Compiler.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/ProxyObjectOutputStream.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Declarator.java
* /javassist-3-29-2-ga-sources-jar/javassist/CannotCompileException.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/stackmap/Tracer.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtBehavior.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/IntConst.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/MethodCall.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/framedump.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/DefinePackageHelper.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/Subroutine.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/JvstCodeGen.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformBefore.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtMethod.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Visitor.java
* /javassist-3-29-2-ga-sources-jar/javassist/scopedpool/ScopedClassPoolRepositoryImpl.java
* /javassist-3-29-2-ga-sources-jar/javassist/Loader.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/CodeGen.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/FramePrinter.java

* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/StubGenerator.java
* /javassist-3-29-2-ga-sources-jar/javassist/runtime/DotClass.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/CodeAttribute.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ConstPool.java
* /javassist-3-29-2-ga-sources-jar/javassist/SerialVersionUID.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/FieldDecl.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/LongVector.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ExceptionsAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/stackmap/TypedBlock.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/StackMapTable.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/LocalVariableAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ClassFileWriter.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ExceptionTable.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/RemoteRef.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/Proxy.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/Javac.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtMember.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/CondExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtNewConstructor.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/ConstructorCall.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/Executor.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/SyntaxError.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/SymbolTable.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/ClassMetaobject.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/Sample.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/Dump.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtNewWrappedMethod.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/MethodHandler.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/ProxyObject.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/JvstTypeChecker.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/ControlFlow.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/NotFoundException.java
* /javassist-3-29-2-ga-sources-jar/javassist/scopedpool/ScopedClassPoolRepository.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/SyntheticAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/AccessorMaker.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/Sample.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/Metaobject.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/MethodFilter.java
* /javassist-3-29-2-ga-sources-jar/javassist/runtime/Cflow.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/CompileError.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtClass.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/CannotCreateException.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/Bytecode.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/ASTList.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtArray.java

*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/stackmap/TypeTag.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/DefineClassHelper.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/MultiType.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/MethodInfo.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/ClassFile.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/AnnotationDefaultAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/Instanceof.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/MethodDecl.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/AssignExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/Mnemonic.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/Util.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/NoFieldException.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/Cast.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/DuplicateMemberException.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/Metalevel.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/AnnotationImpl.java
* /javassist-3-29-2-ga-sources-jar/javassist/URLClassPath.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/Descriptor.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/HotSwapper.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/rmi/RemoteException.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/AnnotationsWriter.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/MemberResolver.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/LocalVariableTypeAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Expr.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/SourceFileAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/convert/TransformNew.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/ArrayInit.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/CannotInvokeException.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/SecurityActions.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/ProxyObjectInputStream.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/InstructionPrinter.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/web/Webserver.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/StringL.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/TokenId.java
* /javassist-3-29-2-ga-sources-jar/javassist/compiler/ast/Variable.java
* /javassist-3-29-2-ga-sources-jar/javassist/util/proxy/RuntimeSupport.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/AttributeInfo.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/SignatureAttribute.java
* /javassist-3-29-2-ga-sources-jar/javassist/tools/reflect/Reflection.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/AnnotationsAttribute.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/analysis/SubroutineScanner.java
* /javassist-3-29-2-ga-sources-jar/javassist/CtField.java
* /javassist-3-29-2-ga-sources-jar/javassist/expr/NewExpr.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/CodeAnalyzer.java

No license file was found, but licenses were detected in source scan.

/*
* Javassist, a Java-bytecode translator toolkit.
* Copyright (C) 2004 Bill Burke. All Rights Reserved.
*
* The contents of this file are subject to the Mozilla Public License Version
* 1.1 (the "License"); you may not use this file except in compliance with
* the License. Alternatively, the contents of this file may be used under
* the terms of the GNU Lesser General Public License Version 2.1 or later,
* or the Apache License Version 2.0.
*
* Software distributed under the License is distributed on an "AS IS" basis,
* WITHOUT WARRANTY OF ANY KIND, either express or implied. See the License
* for the specific language governing rights and limitations under the
* License.
*/

Found in path(s):
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/FloatMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/MemberValueVisitor.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/MemberValue.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/LongMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/CharMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/ByteMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/ClassMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/Annotation.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/ArrayMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/DoubleMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/ShortMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/IntegerMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/StringMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/EnumMemberValue.java
*
 /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/BooleanMemberValue.java
* /javassist-3-29-2-ga-sources-jar/javassist/bytecode/annotation/AnnotationMemberValue.java

1.27 zt 1.16

1.27.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.

```
*  The ASF licenses this file to You under the Apache License, Version 2.0
*  (the "License"); you may not use this file except in compliance with
*  the License.  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*/
```

Found in path(s):
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/ZipConstants.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/AsiExtraField.java
*
 /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/ZipShort.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/ZipExtraField.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/ExtraFieldUtils.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/UnrecognizedExtraField.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/extra/ZipLong.java
No license file was found, but licenses were detected in source scan.

```
/**
*    Copyright (C) 2012 ZeroTurnaround LLC <support@zeroturnaround.com>
*
*    Licensed under the Apache License, Version 2.0 (the "License");
*    you may not use this file except in compliance with the License.
*    You may obtain a copy of the License at
*
*       http://www.apache.org/licenses/LICENSE-2.0
*
*    Unless required by applicable law or agreed to in writing, software
*    distributed under the License is distributed on an "AS IS" BASIS,
*    WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*    See the License for the specific language governing permissions and
*    limitations under the License.
*/
```

Found in path(s):
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/timestamps/TimestampStrategy.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/Zips.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/timestamps/Java8TimestampStrategy.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/timestamps/PreJava8TimestampStrategy.java
*

/zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ZipEntryUtil.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/IdentityNameMapper.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/FileSource.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/NameMapper.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ZipEntrySource.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ByteSource.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ZipInfoCallback.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ZipUtil.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ZTFileUtil.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/timestamps/TimestampStrategyFactory.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/ZipEntryCallback.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/commons/StringBuilderWriter.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/commons/FilenameUtils.java
*
/zt-zip-1-16-sources-jar/org/zeroturnaround/zip/commons/FileUtilsV2_2.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/commons/FileExistsException.java
* /zt-zip-1-16-sources-jar/org/zeroturnaround/zip/commons/IOUtils.java

1.28 gson 2.10.1

1.28.1 Available under license :

No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Created-By: 11.0.16.1 (Azul Systems, Inc.)
Build-Jdk-Spec: 11
Bnd-LastModified: 1673019830620

Bundle-ContactAddress: https://github.com/google/gson
Bundle-Description: Gson JSON library
Bundle-Developers: google;organization=Google;organizationUrl="https://w
ww.google.com"
Bundle-DocURL: https://github.com/google/gson/gson
Bundle-License: "Apache-2.0";link="https://www.apache.org/licenses/LICEN
SE-2.0.txt"
Bundle-ManifestVersion: 2
Bundle-Name: Gson
Bundle-RequiredExecutionEnvironment: JavaSE-1.7, JavaSE-1.8
Bundle-SCM: url="https://github.com/google/gson/gson/",connection="scm:g
it:https://github.com/google/gson.git/gson",developer-connection="scm:g
it:git@github.com:google/gson.git/gson",tag="gson-parent-2.10.1"
Bundle-SymbolicName: com.google.gson
Bundle-Vendor: Google Gson Project
Bundle-Version: 2.10.1
Export-Package: com.google.gson;uses:="com.google.gson.reflect,com.googl
e.gson.stream";version="2.10.1",com.google.gson.annotations;version="2.
 10.1",com.google.gson.reflect;version="2.10.1",com.google.gson.stream;v
ersion="2.10.1"
Import-Package: sun.misc;resolution:=optional,com.google.gson.annotation
s
Require-Capability: osgi.ee;filter:="(&(osgi.ee=JavaSE)(version=1.7))"
Tool: Bnd-6.4.0.202211291949
Multi-Release: true

Found in path(s):
* /gson-2-10-1-jar/META-INF/MANIFEST.MF

1.29 httpclient-cache 4.5.13

1.29.1 Available under license :

Apache HttpClient Cache
Copyright 2010-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent

to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works

that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.

You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.30 commons-logging 1.3.4

1.30.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable

by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only

on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Logging
Copyright 2001-2024 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

1.31 flightrecorder 8.3.1

1.31.1 Available under license :

No license file was found, but licenses were detected in source scan.

Copyright (c) 2018, Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the Universal Permissive License
or the following license:
Redistribution and use in source and binary forms, with or without modification, are permitted

1. Redistributions of source code must retain the above copyright notice, this list of conditions
and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of
conditions and the following disclaimer in the documentation and/or other materials provided with
3. Neither the name of the copyright holder nor the names of its contributors may be used to
endorse or promote products derived from this software without specific prior written permission.

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/segments.properties
*
/flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/messages.properties
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/stacktrace/messages/internal/messages_ja.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/messages/internal/messages.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/messages_ja.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/messages/internal/messages.properties
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/stacktrace/messages/internal/messages_zh_CN.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/messages_zh_CN.properties
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2018, Oracle and/or its affiliates. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the name of the copyright holder nor the names of its contributors may be
used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/ValueField.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/IEventSink.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/IArrayElementParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/IPoolFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/Offset.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/ValueDescriptor.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/DataStructureParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/memleak/ReferenceTreeModel.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/NotEnoughMemoryException.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/MethodFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/filter/IOnLoadFilter.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/StringReader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ChunkStructure.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ConstantReader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ArrayReader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/IChunkLoader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/Transition.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/InvalidJfrFileException.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/UTFStringParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/IValueReader.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/EventArray.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/TypedArrayParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ProducerParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/EventTypeParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ChunkMetadata.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/EventTypeDescriptor.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/DataStructure.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/Messages.java

* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/package-info.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/ProducerDescriptor.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/messages/internal/Messages.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ContentTypeParser.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/TypeFactory.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/JavaThreadFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/util/SplitRecording.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/ContentTypeDescriptor.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/QuantityReader.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/StackTraceFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/ThreadGroup.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/model/DataType.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/util/CanonicalConstantMap.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/FrameSeparator.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/NumberReaders.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/util/DataInputToolkit.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/CouldNotLoadRecordingException.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/OldObjectFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/ChunkStructure.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ConstantMap.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/ThreadGroupFactory.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/filter/OnLoadFilters.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/JfrThread.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/ChunkMetadata.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/JdkQueries.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/OSThreadFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/BooleanReader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/util/JfrInternalConstants.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/StacktraceFormatToolkit.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/messages/internal/Messages.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ReaderFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/JfrAttributes.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/RepositoryBuilder.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/IEventSinkFactory.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/ChunkInfo.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/IChunkSupplier.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/VersionNotSupportedException.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/Chunk.java

* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/CompositeReader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/ItemBuilder.java
*
/flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/filter/FilterExtension.java
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/factories/GlobalObjectPool.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2021, 2022, Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2021, 2022, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the
name of the copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH

DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/tree/StacktraceTreeModel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2021, Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2021, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the name of the
copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/Messages.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/tree/Node.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/SpecificReaders.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2021, 2022, Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2021, 2022, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither
 the name of the copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY

* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/ParserStats.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2018, 2022 Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2022, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the name of
the copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH

DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/util/ParserToolkit.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2021, Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2021, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the name of
the copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/IParserStats.java
*
/flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/IConstantPoolExtension.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2018, 2022, Oracle and/or its affiliates. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the name of the copyright holder nor the names of its contributors
may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/StacktraceFrame.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/JdkAttributes.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/StacktraceModel.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2018, 2021, Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the Universal Permissive License
or the following license:
Redistribution and use in source and binary forms, with or without modification, are permitted
1. Redistributions of source code must retain the above copyright notice, this list of conditions
and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of
conditions and the following disclaimer in the documentation and/or other materials provided with
3. Neither the name of the copyright holder nor the names of its contributors may be used to
endorse or promote products derived from this software without specific prior written permission.

Found in path(s):
* /flightrecorder-8-3-1-sources-
jar/org/openjdk/jmc/flightrecorder/jdk/messages/internal/messages_zh_CN.properties
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/messages/internal/messages_ja.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/messages/internal/messages_zh_CN.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/messages/internal/messages_ja.properties
No license file was found, but licenses were detected in source scan.

Copyright (c) 2018, 2021 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the Universal Permissive License
or the following license:
Redistribution and use in source and binary forms, with or without modification, are permitted
1. Redistributions of source code must retain the above copyright notice, this list of conditions
and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of
conditions and the following disclaimer in the documentation and/or other materials provided with
3. Neither the name of the copyright holder nor the names of its contributors may be used to
endorse or promote products derived from this software without specific prior written permission.

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/messages/internal/messages.properties
No license file was found, but licenses were detected in source scan.

<!--
 Copyright (c) 2018, 2022, Oracle and/or its affiliates. All rights reserved.

 DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.

The contents of this file are subject to the terms of either the Universal Permissive License
v 1.0 as shown at http://oss.oracle.com/licenses/upl

or the following license:

Redistribution and use in source and binary forms, with or without modification, are permitted
provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions
and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of
conditions and the following disclaimer in the documentation and/or other materials provided with
the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used
to
endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND
FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
HOLDER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY
WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
-->

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/META-INF/maven/org.openjdk.jmc/flightrecorder/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2018, 2021, Oracle and/or its affiliates. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License

* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the name of the copyright holder nor the names of its contributors
may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/OracleJdkTypeIDsPre11.java
*
/flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/FlightRecordingLoader.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ChunkLoaderV0.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/ChunkLoaderV1.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/SyntheticAttributeExtension.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/TypeManager.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/messages/internal/Messages.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/memleak/ReferenceTreeObject.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/JdkAggregators.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/util/ChunkReader.java

* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/EventArrays.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/ValueReaders.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/EventCollection.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/ParserExtensionRegistry.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/RecordingPrinter.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/StructTypes.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/IDataInput.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/JdkFilters.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v1/SeekableInputStream.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/util/DisjointBuilder.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/JfrLoaderToolkit.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/jdk/JdkTypeIDs.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/ConstantEntryList.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/synthetic/SettingsTransformer.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/EventAppearance.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/parser/IParserExtension.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/LoaderContext.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/internal/parser/v0/EventParserManager.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2019, 2021, Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2019, 2021, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the
 name of the copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND

ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/graph/GraphModelUtils.java
*
/flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/graph/AggregatableFrame.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/tree/AggregatableFrame.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2019, 2022, Oracle and/or its affiliates. All rights reserved.
* Copyright (c) 2019, 2022, Datadog, Inc. All rights reserved.
*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS FILE HEADER.
*
* The contents of this file are subject to the terms of either the Universal Permissive License
* v 1.0 as shown at http://oss.oracle.com/licenses/upl
*
* or the following license:
*
* Redistribution and use in source and binary forms, with or without modification, are permitted
* provided that the following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions
* and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of
* conditions and the following disclaimer in the documentation and/or other materials provided with
* the distribution.
*
* 3. Neither the
name of the copyright holder nor the names of its contributors may be used to
* endorse or promote products derived from this software without specific prior written permission.

*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
* FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/graph/StacktraceGraphModel.java
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/graph/Edge.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/graph/Node.java
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/graph/Pruning.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2021, Oracle and/or its affiliates. All rights reserved.
Copyright (c) 2021, Datadog, Inc. All rights reserved.
The contents of this file are subject to the terms of either the Universal Permissive License
or the following license:
Redistribution and use in source and binary forms, with or without modification, are permitted
1. Redistributions of source code must retain the above copyright notice, this list of conditions
and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of
conditions and the following disclaimer in the documentation and/or other materials provided with
3. Neither the name of the copyright holder nor the names of its contributors may be used to
endorse or promote products derived from this software without specific prior written permission.

Found in path(s):
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/messages.properties
*
 /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/messages_ja.properties
* /flightrecorder-8-3-1-sources-jar/org/openjdk/jmc/flightrecorder/stacktrace/messages_zh_CN.properties

1.32 paranamer 2.5.1

1.32.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/***
*
* Copyright (c) 2009 Paul Hammant
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
 LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
```

Found in path(s):

* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/AnnotationParanamer.java

No license file was found, but licenses were detected in source scan.

```
/***
*
* Portions Copyright (c) 2007 Paul Hammant
* Portions copyright (c) 2000-2007 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
```

* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
 IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/BytecodeReadingParanamer.java
No license file was found, but licenses were detected in source scan.

/***
*
* Copyright (c) 2007 Paul Hammant
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT

LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/AdaptiveParanamer.java
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/NullParanamer.java
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/ParameterNamesNotFoundException.java
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/DefaultParanamer.java
*
/paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/CachingParanamer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2007 Paul Hammant
* Copyright 2007 ThinkTank Maths Limited
*
* ThinkTank Maths Limited grants a non-revocable, perpetual licence
* to Paul Hammant for unlimited use, relicensing and redistribution. No
* explicit permission is required from ThinkTank Maths Limited for
* any future decisions made with regard to this file.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR

* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/JavadocParanamer.java
No license file was found, but licenses were detected in source scan.

/***
*
* Copyright (c) 2007 Paul Hammant
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
 LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*
*/

Found in path(s):
* /paranamer-2-5-1-sources-1-jar/com/thoughtworks/paranamer/Paranamer.java

1.33 animal-sniffer-annotation 1.23

1.33.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--
The MIT License

Copyright (c) 2009 codehaus.org.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES
OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
-->

Found in path(s):
* /animal-sniffer-annotations-1-23-1-jar/META-INF/maven/org.codehaus.mojo/animal-sniffer-annotations/pom.xml

1.34 servlet-api 4.0.1

1.34.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0

1. Definitions.

1.1. Contributor. means each individual or entity that creates or contributes to the creation of Modifications.

1.2. Contributor Version. means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. Covered Software. means (a) the Original Software, or (b) Modifications, or (c) the combination of files

containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. Executable. means the Covered Software in any form other than Source Code.

1.5. Initial Developer. means the individual or entity that first makes Original Software available under this License.

1.6. Larger Work. means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. License. means this document.

1.8.
Licensable. means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. Modifications. means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. Original Software. means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. Patent Claims. means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12.
Source Code. means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. You. (or .Your.) means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, .You. includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, .control. means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under
intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software
with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the
combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.
Any Covered Software that You distribute or otherwise make available in Executable form must also be made available

in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients. rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient.s rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the
License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN .AS IS. BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES
THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as .Participant.) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses

that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY.S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS
DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a .commercial item,. as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of .commercial computer software. (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and .commercial computer software documentation. as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction.s conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys. fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for
compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer

and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California
and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software,
we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer
you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to

know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any
program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that
in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and

that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works
in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or
executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code
for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute
the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties

who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear
what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions

either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These
Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.

Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits
your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

"CLASSPATH" EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Sun Microsystems, Inc. are subject to the following clarification and special exception to the GPL Version 2, but only where Sun has expressly included in the particular
source file's header the words

"Sun designates this particular file as subject to the "Classpath" exception as provided by Sun in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library.

Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked independent module, the terms and conditions of the license of that module.? An independent module is a module which is not derived from or based on this library.? If you modify this library, you may extend this exception to your version of the library, but
you are not obligated to do so.? If you do not wish to do so, delete this exception statement from your version.

1.35 error_prone_annotations 2.18.0

1.35.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--
Copyright 2015 The Error Prone Authors.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
-->

Found in path(s):
* /error-prone-annotations-2-18-0-jar/META-INF/maven/com.google.errorprone/error_prone_annotations/pom.xml

1.36 opentelemetry-proto 0.11.0

1.36.1 Available under license :

/*
* Copyright The OpenTelemetry Authors
* SPDX-License-Identifier: Apache-2.0
*/

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner

or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices

stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.37 commons-codec 1.15

1.37.1 Available under license :

Apache Commons Codec
Copyright 2002-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

src/test/org/apache/commons/codec/language/DoubleMetaphoneTest.java
contains test data from http://aspell.net/test/orig/batch0.tab.
Copyright (C) 2002 Kevin Atkinson (kevina@gnu.org)

==========

The content of package org.apache.commons.codec.language.bm has been translated
from the original php source code available at http://stevemorse.org/phoneticinfo.htm
with permission from the original authors.
Original source copyright:
Copyright (c) 2008 Alexander Beider & Stephen P. Morse.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.38 gson 2.13.2

1.38.1 Available under license :

No license file was found, but licenses were detected in source scan.

<?xml version="1.0" encoding="UTF-8"?>

Found in path(s):
* /gson-2-13-2-sources-jar/META-INF/maven/com.google.code.gson/gson/pom.xml
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/ExclusionStrategy.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/FieldAttributes.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/FieldNamingPolicy.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/FieldNamingStrategy.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/FormattingStyle.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/Gson.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/GsonBuilder.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/InstanceCreator.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonArray.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonDeserializationContext.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonDeserializer.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonElement.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonIOException.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonNull.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonObject.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonParseException.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonParser.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-

jar/com/google/gson/JsonPrimitive.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonSerializationContext.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonSerializer.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonStreamParser.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/JsonSyntaxException.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/LongSerializationPolicy.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/ReflectionAccessFilter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/ToNumberPolicy.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/ToNumberStrategy.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/TypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/TypeAdapterFactory.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/annotations/Expose.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/annotations/JsonAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/annotations/SerializedName.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/annotations/Since.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/annotations/Until.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/annotations/package-info.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/ConstructorConstructor.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/Excluder.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/GsonBuildConfig.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/GsonTypes.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/JavaVersion.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/JsonReaderInternalAccess.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/LazilyParsedNumber.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-

jar/com/google/gson/internal/LinkedTreeMap.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/NonNullElementWrapperList.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/ObjectConstructor.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/PreJava9DateFormatProvider.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/Primitives.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/ReflectionAccessFilterHelper.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/Streams.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/UnsafeAllocator.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/ArrayTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/CollectionTypeAdapterFactory.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/DefaultDateTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/EnumTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/JsonAdapterAnnotationTypeAdapterFactory.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/JsonElementTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/JsonTreeReader.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/JsonTreeWriter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/MapTypeAdapterFactory.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/NumberTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/ObjectTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/ReflectiveTypeAdapterFactory.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/SerializationDelegatingTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/TreeTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/TypeAdapterRuntimeTypeWrapper.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-
jar/com/google/gson/internal/bind/TypeAdapters.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-

jar/com/google/gson/internal/bind/util/ISO8601Utils.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/package-info.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/reflect/ReflectionHelper.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/sql/SqlDateTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/sql/SqlTimeTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/sql/SqlTimestampTypeAdapter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/internal/sql/SqlTypesSupport.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/package-info.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/reflect/TypeToken.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/reflect/package-info.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/stream/JsonReader.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/stream/JsonScope.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/stream/JsonToken.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/stream/JsonWriter.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/stream/MalformedJsonException.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/com/google/gson/stream/package-info.java/*
/opt/cola/permits/1701353823_1761207053.5308793/0/gson-2-13-2-sources-jar/module-info.java/*

Found
in path(s):
*

1.39 failureaccess 1.0.1

1.39.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2665668644_1759873713.7185001/0/failureaccess-1-0-1-sources-15-jar/com/google/common/util/concurrent/internal/InternalFutures.java/*

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2018 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /failureaccess-1-0-1-sources-15-jar/com/google/common/util/concurrent/internal/InternalFutureFailureAccess.java

1.40 httpcomponents-client 4.5.14

1.40.1 Available under license :

Apache HttpClient
Copyright 1999-2022 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all

other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and
limitations under the License.

1.41 xerces-j 2.12.2

1.41.1 Available under license :

Apache XML Commons Resolver
Copyright 2006 The Apache Software Foundation.

This product includes software developed at
The Apache Software Foundation http://www.apache.org/

Portions of this code are derived from classes placed in the
public domain by Arbortext on 10 Apr 2000. See:
http://www.arbortext.com/customer_support/updates_and_technical_notes/catalogs/docs/README.htm

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical

transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable

(except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as

of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,

and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
==
== NOTICE file corresponding to section 4(d) of the Apache License, ==
== Version 2.0, in this case for the Apache Xerces Java distribution. ==
==

Apache Xerces Java
Copyright 1999-2022 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Portions of this software were originally based on the following:
- software copyright (c) 1999, IBM Corporation., http://www.ibm.com.
- software copyright (c) 1999, Sun Microsystems., http://www.sun.com.
- voluntary contributions made by Paul Eng on behalf of the
  Apache Software Foundation that were originally developed at iClick, Inc.,
  software copyright (c) 1999.

==
== NOTICE file corresponding to section 4(d) of the Apache License, ==
== Version 2.0, in this case for the Apache Xalan Java distribution. ==
==

Apache Xalan (Xalan serializer)
Copyright 1999-2012 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Portions of this software was originally based on the following:
- software copyright (c) 1999-2002, Lotus Development Corporation.,
  http://www.lotus.com.
- software copyright (c) 2001-2002, Sun Microsystems.,
  http://www.sun.com.
- software copyright (c) 2003, IBM Corporation.,
  http://www.ibm.com.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii)
beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the
Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of,

publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and

wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the

Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.42 perfmark-api 0.17.0

1.42.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 Carl Mastrangelo
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /perfmark-api-0-17-0-sources-3-jar/io/perfmark/PerfMark.java
* /perfmark-api-0-17-0-sources-3-jar/io/perfmark/Tag.java
* /perfmark-api-0-17-0-sources-3-jar/io/perfmark/Link.java
* /perfmark-api-0-17-0-sources-3-jar/io/perfmark/package-info.java
* /perfmark-api-0-17-0-sources-3-jar/io/perfmark/Impl.java

1.43 guava 32.1.3-jre

1.43.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its

distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.44 commons-codec 1.14

1.44.1 Available under license :

Apache Commons Codec
Copyright 2002-2019 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

src/test/org/apache/commons/codec/language/DoubleMetaphoneTest.java
contains test data from http://aspell.net/test/orig/batch0.tab.
Copyright (C) 2002 Kevin Atkinson (kevina@gnu.org)

==========

The content of package org.apache.commons.codec.language.bm has been translated
from the original php source code available at http://stevemorse.org/phoneticinfo.htm
with permission from the original authors.
Original source copyright:
Copyright (c) 2008 Alexander Beider & Stephen P. Morse.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.45 encoder 1.2.3

1.45.1 Available under license :

Copyright (c) 2015 Jeff Ichnowski
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of the OWASP nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.46 jackson-annotations 2.17.1

1.46.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally

submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.47 jackson-databind 2.17.3

1.47.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"

means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each

Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");

you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.48 commons-logging 1.3.2

1.48.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Commons Logging
Copyright 2001-2024 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

1.49 commons-io 2.17.0

1.49.1 Available under license :

Apache Commons IO
Copyright 2002-2024 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.50 jctools-core 4.0.5

1.50.1 Available under license :

No license file was found, but licenses were detected in source scan.

<name>Apache License, Version 2.0</name>

<url>http://www.apache.org/licenses/LICENSE-2.0.txt</url>

Found in path(s):
* /jctools-core-4-0-5-6-jar/META-INF/maven/org.jctools/jctools-core/pom.xml
No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Bnd-LastModified: 1717253512851
Build-Jdk-Spec: 1.8
Bundle-Description: Java Concurrency Tools Core Library
Bundle-License: http://www.apache.org/licenses/LICENSE-2.0.txt
Bundle-ManifestVersion: 2
Bundle-Name: Java Concurrency Tools Core Library
Bundle-SymbolicName: org.jctools.core
Bundle-Version: 4.0.5
Created-By: Apache Maven Bundle Plugin 5.1.8
Export-Package: org.jctools.maps;version="4.0.5",org.jctools.util;vers
ion="4.0.5";uses:="sun.misc",org.jctools.queues;version="4.0.5",org.j
ctools.queues.atomic;version="4.0.5";uses:="org.jctools.queues",org.j
ctools.queues.atomic.unpadded;version="4.0.5";uses:="org.jctools.queu
es",org.jctools.queues.unpadded;version="4.0.5";uses:="org.jctools.qu
eues",org.jctools.counters;version="4.0.5"
Import-Package: sun.misc;resolution:=optional
Require-Capability: osgi.ee;filter:="(&(osgi.ee=JavaSE)(version=1.6))"
Tool: Bnd-6.3.1.202206071316

Found in path(s):
*
/jctools-core-4-0-5-6-jar/META-INF/MANIFEST.MF

1.51 httpcomponents-core 4.4.16

1.51.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache HttpCore
Copyright 2005-2022 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.52 dagger 2.4

1.52.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2007 Google Inc.
* Copyright (C) 2012 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/Provides.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/Module.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2016 Google, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/Binds.java
* /dagger-2-4-sources-2-jar/dagger/multibindings/IntoMap.java
* /dagger-2-4-sources-2-jar/dagger/internal/DoubleCheck.java
* /dagger-2-4-sources-2-jar/dagger/Reusable.java
* /dagger-2-4-sources-2-jar/dagger/internal/Preconditions.java
* /dagger-2-4-sources-2-jar/dagger/internal/ProviderOfLazy.java
*
 /dagger-2-4-sources-2-jar/dagger/multibindings/package-info.java
* /dagger-2-4-sources-2-jar/dagger/multibindings/IntoSet.java
* /dagger-2-4-sources-2-jar/dagger/multibindings/ElementsIntoSet.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2014 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/internal/MembersInjectors.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2014 Google, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/internal/Factory.java
* /dagger-2-4-sources-2-jar/dagger/MapKey.java
* /dagger-2-4-sources-2-jar/dagger/internal/MapFactory.java
* /dagger-2-4-sources-2-jar/dagger/internal/SingleCheck.java
* /dagger-2-4-sources-2-jar/dagger/internal/MapProviderFactory.java
* /dagger-2-4-sources-2-jar/dagger/internal/InstanceFactory.java
*
 /dagger-2-4-sources-2-jar/dagger/internal/SetFactory.java
* /dagger-2-4-sources-2-jar/dagger/internal/Collections.java
* /dagger-2-4-sources-2-jar/dagger/Component.java
* /dagger-2-4-sources-2-jar/dagger/internal/DelegateFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2015 Google, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/Multibindings.java
* /dagger-2-4-sources-2-jar/dagger/internal/Beta.java
* /dagger-2-4-sources-2-jar/dagger/multibindings/StringKey.java
* /dagger-2-4-sources-2-jar/dagger/package-info.java
* /dagger-2-4-sources-2-jar/dagger/Subcomponent.java
* /dagger-2-4-sources-2-jar/dagger/multibindings/ClassKey.java
*
 /dagger-2-4-sources-2-jar/dagger/multibindings/IntKey.java
* /dagger-2-4-sources-2-jar/dagger/multibindings/LongKey.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 Google, Inc.
* Copyright (C) 2012 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/Lazy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 Square, Inc.
* Copyright (C) 2009 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /dagger-2-4-sources-2-jar/dagger/MembersInjector.java

1.53 httpcomponents-client 4.5.13

1.53.1 Available under license :

Apache HttpClient
Copyright 1999-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.54 jackson-annotations 2.17.3

1.54.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial

revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.55 commons-fileupload 1.6.0

1.55.1 Available under license :

Apache Commons FileUpload
Copyright 2002-2025 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work

by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.56 guava 32.0.1-jre

1.56.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.57 slf4j 2.0.16

1.57.1 Available under license :

Copyright (c) 2004-2022 QOS.ch Sarl (Switzerland)
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.58 httpcore-nio 4.4.13

1.58.1 Available under license :

Apache HttpCore NIO
Copyright 2005-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.59 xml-apis 1.4.01

1.59.1 Available under license :

```
 ========================================================================
==  NOTICE file corresponding to section 4(d) of the Apache License,   ==
==  Version 2.0, in this case for the Apache xml-commons xml-apis      ==
==  distribution.                                                      ==
 ========================================================================
```

Apache XML Commons XML APIs
Copyright 1999-2009 The Apache Software Foundation.

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Portions of this software were originally based on the following:
- software copyright (c) 1999, IBM Corporation., http://www.ibm.com.
- software copyright (c) 1999, Sun Microsystems., http://www.sun.com.
- software copyright (c) 2000 World Wide Web Consortium, http://www.w3.org
xml-commons/java/external/LICENSE.sax.txt $Id: LICENSE.sax.txt 225954 2002-01-31 23:26:48Z curcuru $

This license came from: http://www.megginson.com/SAX/copying.html
However please note future versions of SAX may be covered
under http://saxproject.org/?selected=pd

This page is now out of date -- see the new SAX site at
http://www.saxproject.org/ for more up-to-date
releases and other information. Please change your bookmarks.

SAX2 is Free!

I hereby abandon any property rights to SAX 2.0 (the Simple API for
XML), and release all of the SAX 2.0 source code, compiled code, and
documentation contained in this distribution into the Public Domain.
SAX comes with NO WARRANTY or guarantee of fitness for any

purpose.

David Megginson, david@megginson.com
2000-05-05
xml-commons/java/external/LICENSE.dom-software.txt $Id: LICENSE.dom-software.txt 734314 2009-01-14 03:33:27Z mrglavas $

This license came from: http://www.w3.org/TR/2004/REC-DOM-Level-3-Core-20040407/java-binding.zip (COPYRIGHT.html)

W3C SOFTWARE NOTICE AND LICENSE
Copyright 2004 World Wide Web Consortium, (Massachusetts Institute of Technology, European Research Consortium for Informatics and Mathematics, Keio University). All Rights Reserved.

The DOM bindings are published under the W3C Software Copyright Notice and License. The software license requires "Notice of any changes or modifications to the W3C files, including the date changes were made." Consequently, modified versions of the DOM bindings must document that they do not conform to the W3C standard; in the case of the IDL definitions, the pragma prefix can no longer be 'w3c.org'; in the case of the Java language binding, the package names can no longer be in the 'org.w3c' package.

Note: The original version of the
W3C Software Copyright Notice and License could
be found at http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231

This work (and included software, documentation such as READMEs, or other related items) is being provided by the copyright holders under the following license. By obtaining, using and/or copying this work, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions.

Permission to copy, modify, and distribute this software and its documentation, with or without modification, for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the software and documentation or portions thereof, including modifications:

1. The full text of this NOTICE in a location viewable to users of the redistributed or derivative work.
2. Any pre-existing intellectual property disclaimers, notices, or terms and conditions. If none exist, the
W3C Software Short Notice should be
included (hypertext is preferred, text is permitted) within the body of any redistributed or derivative code.
3. Notice of any changes or modifications to the files, including the date changes were made. (We recommend you provide URIs to the location from which the code is derived.)

THIS SOFTWARE AND DOCUMENTATION IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE SOFTWARE OR DOCUMENTATION.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to the software without
specific, written prior permission.
Title to copyright in this software and any associated documentation will at all times remain with copyright holders.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but

not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,

where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and

may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this

License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
xml-commons/java/external/LICENSE.dom-documentation.txt $Id: LICENSE.dom-documentation.txt 226215
2005-06-03 22:49:13Z mrglavas $

This license came from: http://www.w3.org/Consortium/Legal/copyright-documents-20021231

W3C DOCUMENT LICENSE
http://www.w3.org/Consortium/Legal/2002/copyright-documents-20021231

Public documents on the W3C site are provided by the copyright holders under
the following license. By using and/or copying this document, or the W3C
document from which this statement is linked, you (the licensee) agree that
you have read, understood, and will comply with the following terms and
conditions:

Permission to copy, and distribute the contents of this document, or the W3C document from which this statement is linked, in any medium for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the document, or portions thereof, that you use:

1. A link or URL to the original W3C document.
2. The pre-existing copyright notice of the original author, or if it doesn't exist, a notice (hypertext is preferred, but a textual representation is permitted) of the form: "Copyright [$date-of-document] World Wide Web Consortium, (Massachusetts Institute of Technology, European Research Consortium for Informatics and Mathematics, Keio University). All Rights Reserved. http://www.w3.org/Consortium/Legal/2002/copyright-documents-20021231"
3. If it exists, the STATUS of the W3C document.

When space permits, inclusion of the full text of this NOTICE should be provided. We request that authorship attribution be provided in any software, documents, or other items or products that you create pursuant to the implementation of the contents of this document, or any portion thereof.

No right to create modifications or derivatives of W3C documents is granted pursuant to this license. However, if additional requirements (documented in the Copyright FAQ) are satisfied, the right to create modifications or derivatives is sometimes granted by the W3C to individuals complying with those requirements.

THIS DOCUMENT IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

This formulation of W3C's notice and license became active on December 31 2002.
This version removes the copyright ownership notice such that this license can
be used with materials other than those owned by the W3C, moves information on
style sheets, DTDs, and schemas to the Copyright FAQ, reflects that ERCIM is
now a host of the W3C, includes references to this specific dated version of
the license, and removes the ambiguous grant of "use". See the older
formulation for the policy prior to this date. Please see our Copyright FAQ for
common questions about using materials from our site, such as the translating
or annotating specifications. Other questions about this notice can be directed
to site-policy@w3.org.

Joseph Reagle <site-policy@w3.org>

Last revised by Reagle $Date: 2005-06-03 18:49:13 -0400 (Fri, 03 Jun 2005) $

1.60 opentelemetry-exporter-otlp 1.29.0

1.60.1 Available under license :

Apache-2.0

1.61 j2objc-annotations 2.8

1.61.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 Google Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/Weak.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/AutoreleasePool.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/ReflectionSupport.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/J2ObjCIncompatible.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/RetainedWith.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/WeakOuter.java
*
/j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/ObjectiveCName.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/Property.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/LoopTranslation.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/OnDealloc.java
* /j2objc-annotations-2-8-sources-2-jar/com/google/j2objc/annotations/RetainedLocalRef.java

1.62 okhttp 4.11.0

1.62.1 Available under license :

Note that publicsuffixes.gz is compiled from The Public Suffix List:
https://publicsuffix.org/list/public_suffix_list.dat

It is subject to the terms of the Mozilla Public License, v. 2.0:
https://mozilla.org/MPL/2.0/

1.63 okio 3.6.0

1.63.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2020 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/nativeMain/okio/SizetVariant.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2021 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/internal/FileSystem.kt
* /okio-3-6-0-sources-jar/commonMain/okio/FileHandle.kt
* /okio-3-6-0-sources-jar/unixMain/okio/UnixFileHandle.kt
* /okio-3-6-0-sources-jar/nativeMain/okio/FileSystem.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2020 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/hashFunctions/okio/internal/Sha512.kt
* /okio-3-6-0-sources-jar/hashFunctions/okio/internal/Md5.kt
* /okio-3-6-0-sources-jar/hashFunctions/okio/internal/Sha1.kt
* /okio-3-6-0-sources-jar/hashFunctions/okio/internal/Sha256.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2020 Square, Inc. and others.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/hashFunctions/okio/internal/HashFunction.kt
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/Base64.kt
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2018 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/PeekSource.kt
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2019 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/Okio.kt
* /okio-3-6-0-sources-jar/commonMain/okio/Timeout.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/RealBufferedSink.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/Buffer.kt
* /okio-3-6-0-sources-jar/commonMain/okio/BufferedSink.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/Timeout.kt

*
/okio-3-6-0-sources-jar/commonMain/okio/Buffer.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/BufferedSink.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/Sink.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/BufferedSource.kt
* /okio-3-6-0-sources-jar/commonMain/okio/internal/Buffer.kt
* /okio-3-6-0-sources-jar/commonMain/okio/RealBufferedSource.kt
* /okio-3-6-0-sources-jar/commonMain/okio/Sink.kt
* /okio-3-6-0-sources-jar/commonMain/okio/Source.kt
* /okio-3-6-0-sources-jar/commonMain/okio/BufferedSource.kt
* /okio-3-6-0-sources-jar/commonMain/okio/RealBufferedSink.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2016 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/Options.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2018 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/internal/-Utf8.kt
* /okio-3-6-0-sources-jar/nonAppleMain/okio/ByteString.kt
* /okio-3-6-0-sources-jar/commonMain/okio/Util.kt
* /okio-3-6-0-sources-jar/commonMain/okio/CommonPlatform.kt
* /okio-3-6-0-sources-jar/commonMain/okio/internal/ByteString.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/NonJvmPlatform.kt
*
/okio-3-6-0-sources-jar/commonMain/okio/ByteString.kt
* /okio-3-6-0-sources-jar/appleMain/okio/ByteString.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2019 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/internal/RealBufferedSource.kt
* /okio-3-6-0-sources-jar/commonMain/okio/internal/SegmentedByteString.kt
* /okio-3-6-0-sources-jar/commonMain/okio/internal/RealBufferedSink.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2014 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/nonJvmMain/okio/RealBufferedSource.kt
* /okio-3-6-0-sources-jar/commonMain/okio/Segment.kt
* /okio-3-6-0-sources-jar/commonMain/okio/SegmentPool.kt
* /okio-3-6-0-sources-jar/commonMain/okio/ForwardingSource.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/SegmentPool.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/ForwardingSource.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2015 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/appleMain/okio/SegmentedByteString.kt
* /okio-3-6-0-sources-jar/nonAppleMain/okio/SegmentedByteString.kt
* /okio-3-6-0-sources-jar/commonMain/okio/SegmentedByteString.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2017 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /okio-3-6-0-sources-jar/commonMain/okio/Utf8.kt
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2020 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okio-3-6-0-sources-jar/nativeMain/okio/Cinterop.kt
* /okio-3-6-0-sources-jar/unixMain/okio/UnixPosixVariant.kt
* /okio-3-6-0-sources-jar/commonMain/okio/internal/Path.kt
* /okio-3-6-0-sources-jar/linuxMain/okio/LinuxPosixVariant.kt
* /okio-3-6-0-sources-jar/nativeMain/okio/PosixFileSystem.kt
* /okio-3-6-0-sources-jar/hashFunctions/okio/internal/Hmac.kt
*
 /okio-3-6-0-sources-jar/nativeMain/okio/PosixVariant.kt
* /okio-3-6-0-sources-jar/commonMain/okio/HashingSource.kt
* /okio-3-6-0-sources-jar/nativeMain/okio/FileSource.kt
* /okio-3-6-0-sources-jar/appleMain/okio/ApplePosixVariant.kt
* /okio-3-6-0-sources-jar/nativeMain/okio/FileSink.kt
* /okio-3-6-0-sources-jar/commonMain/okio/FileSystem.kt
* /okio-3-6-0-sources-jar/commonMain/okio/HashingSink.kt
* /okio-3-6-0-sources-jar/commonMain/okio/FileMetadata.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/Path.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/HashingSink.kt
* /okio-3-6-0-sources-jar/commonMain/okio/ForwardingFileSystem.kt
* /okio-3-6-0-sources-jar/commonMain/okio/ExperimentalFileSystem.kt
* /okio-3-6-0-sources-jar/nonJvmMain/okio/HashingSource.kt
* /okio-3-6-0-sources-jar/commonMain/okio/Path.kt

1.64 annotations 4.1.1.4

1.64.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2657836890_1759249724.2399228/0/annotations-4-1-1-4-sources-9-jar/android/annotation/TargetApi.java/*

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 The Android Open Source Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /annotations-4-1-1-4-sources-9-jar/android/annotation/SuppressLint.java

1.65 httpcomponents-mime 4.5.14

1.65.1 Available under license :

Apache HttpComponents Client
Copyright 1999-2021 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or

agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

==========

This project includes Public Suffix List copied from
<https://publicsuffix.org/list/effective_tld_names.dat>
licensed under the terms of the Mozilla Public License, v. 2.0

Full license text: <http://mozilla.org/MPL/2.0/>

Mozilla Public License Version 2.0
==========

1. Definitions

1.1. "Contributor"
means each individual or legal entity that creates, contributes to the creation of, or owns Covered Software.

1.2. "Contributor Version"
means the combination of the Contributions of others (if any) used by a Contributor and that particular Contributor's Contribution.

1.3. "Contribution"
means Covered Software of a particular Contributor.

1.4. "Covered Software"
means Source Code
Form to which the initial Contributor has attached the notice in Exhibit A, the Executable Form of such Source Code Form, and Modifications of such Source Code Form, in each case including portions thereof.

1.5. "Incompatible With Secondary Licenses"
means

(a) that the initial Contributor has attached the notice described in Exhibit B to the Covered Software; or

(b) that the Covered Software was made available under the terms of version 1.1 or earlier of the License, but not also under the terms of a Secondary License.

1.6. "Executable Form"
means any form of the work other than Source Code Form.

1.7. "Larger Work"
means a work that combines Covered Software with other material, in a separate file or files, that is not Covered Software.

1.8. "License"
means this document.

1.9. "Licensable"
means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently,
any and
all of the rights conveyed by this License.

1.10. "Modifications"
means any of the following:

(a) any file in Source Code Form that results from an addition to, deletion from, or modification of the contents of Covered Software; or

(b) any new file in Source Code Form that contains any Covered Software.

1.11. "Patent Claims" of a Contributor
means any patent claim(s), including without limitation, method, process, and apparatus claims, in any patent Licensable by such Contributor that would be infringed, but for the grant of the License, by the making, using, selling, offering for sale, having made, import, or transfer of either its Contributions or its Contributor Version.

1.12. "Secondary License"
means either the GNU General Public License, Version 2.0, the GNU Lesser General Public License, Version 2.1, the GNU Affero General Public License, Version 3.0, or any later versions of those

licenses.

1.13. "Source Code Form"
means the form of the work preferred for making modifications.

1.14. "You" (or "Your")
means an individual or a legal entity exercising rights under this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants and Conditions

2.1. Grants

Each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark)
Licensable by such Contributor to use, reproduce, make available, modify, display, perform, distribute, and otherwise
exploit its
Contributions, either on an unmodified basis, with Modifications, or

as part of a Larger Work; and

(b) under Patent Claims of such Contributor to make, use, sell, offer for sale, have made, import, and otherwise transfer either its Contributions or its Contributor Version.

2.2. Effective Date

The licenses granted in Section 2.1 with respect to any Contribution become effective for each Contribution on the date the Contributor first distributes such Contribution.

2.3. Limitations on Grant Scope

The licenses granted in this Section 2 are the only rights granted under this License. No additional rights or licenses will be implied from the distribution or licensing of Covered Software under this License. Notwithstanding Section 2.1(b) above, no patent license is granted by a Contributor:

(a) for any code that a Contributor has removed from Covered Software; or

(b) for infringements caused by: (i) Your and any other third party's modifications
of Covered Software, or (ii) the combination of its Contributions with other software (except as part of its Contributor Version); or

(c) under Patent Claims infringed by Covered Software in the absence of its Contributions.

This License does not grant any rights in the trademarks, service marks, or logos of any Contributor (except as may be necessary to comply with the notice requirements in Section 3.4).

2.4. Subsequent Licenses

No Contributor makes additional grants as a result of Your choice to distribute the Covered Software under a subsequent version of this License (see Section 10.2) or under the terms of a Secondary License (if permitted under the terms of Section 3.3).

2.5. Representation

Each Contributor represents that the Contributor believes its Contributions are its original creation(s) or it has sufficient rights to grant the rights to its Contributions conveyed by this License.

2.6. Fair Use

This License is not intended to limit any rights You have
under
applicable copyright doctrines of fair use, fair dealing, or other
equivalents.

2.7. Conditions

Sections 3.1, 3.2, 3.3, and 3.4 are conditions of the licenses granted
in Section 2.1.

3. Responsibilities

3.1. Distribution of Source Form

All distribution of Covered Software in Source Code Form, including any
Modifications that You create or to which You contribute, must be under
the terms of this License. You must inform recipients that the Source
Code Form of the Covered Software is governed by the terms of this
License, and how they can obtain a copy of this License. You may not
attempt to alter or restrict the recipients' rights in the Source Code
Form.

3.2. Distribution of Executable Form

If You distribute Covered Software in Executable Form then:

(a) such Covered Software must also be made available in Source Code
Form, as described in Section 3.1, and You must inform recipients of
the Executable Form how they can obtain a copy of such Source
Code
Form by reasonable means in a timely manner, at a charge no more
than the cost of distribution to the recipient; and

(b) You may distribute such Executable Form under the terms of this
License, or sublicense it under different terms, provided that the
license for the Executable Form does not attempt to limit or alter
the recipients' rights in the Source Code Form under this License.

3.3. Distribution of a Larger Work

You may create and distribute a Larger Work under terms of Your choice,
provided that You also comply with the requirements of this License for
the Covered Software. If the Larger Work is a combination of Covered
Software with a work governed by one or more Secondary Licenses, and the

Covered Software is not Incompatible With Secondary Licenses, this License permits You to additionally distribute such Covered Software under the terms of such Secondary License(s), so that the recipient of the Larger Work may, at their option, further distribute the Covered Software under the terms of either this License or such Secondary License(s).

3.4. Notices

You may not remove or alter the substance of any license notices (including copyright notices, patent notices, disclaimers of warranty, or limitations of liability) contained within the Source Code Form of the Covered Software, except that You may alter any license notices to the extent required to remedy known factual inaccuracies.

3.5. Application of Additional Terms

You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, You may do so only on Your own behalf, and not on behalf of any Contributor. You must make it absolutely clear that any such warranty, support, indemnity, or liability obligation is offered by You alone, and You hereby agree to indemnify every Contributor for any liability incurred by such Contributor as a result of warranty, support, indemnity or liability terms You offer. You may include additional disclaimers of warranty and limitations of liability specific to any jurisdiction.

4. Inability to Comply Due to Statute or Regulation

If it is impossible for You to comply with any of the terms of this License with respect to some or all of the Covered Software due to statute, judicial order, or regulation then You must: (a) comply with the terms of this License to the maximum extent possible; and (b) describe the limitations and the code they affect. Such description must be placed in a text file included with all distributions of the Covered Software under this License. Except to the extent prohibited by statute or regulation, such description must be sufficiently detailed for a recipient of ordinary skill to be able to understand it.

5. Termination

5.1. The rights granted under this License will terminate automatically if You fail to comply with any of its terms. However,

if You become
compliant, then the rights granted under this License from a particular Contributor are reinstated (a) provisionally, unless and until such Contributor explicitly and finally terminates Your grants, and (b) on an ongoing basis, if such Contributor fails to notify You of the non-compliance by some reasonable means prior to 60 days after You have come back into compliance. Moreover, Your grants from a particular Contributor are reinstated on an ongoing basis if such Contributor notifies You of the non-compliance by some reasonable means, this is the first time You have received notice of non-compliance with this License from such Contributor, and You become compliant prior to 30 days after Your receipt of the notice.

5.2. If You initiate litigation against any entity by asserting a patent infringement claim (excluding declaratory judgment actions, counter-claims, and cross-claims) alleging that a Contributor Version directly or indirectly infringes any patent, then the
rights granted to
You by any and all Contributors for the Covered Software under Section 2.1 of this License shall terminate.

5.3. In the event of termination under Sections 5.1 or 5.2 above, all end user license agreements (excluding distributors and resellers) which have been validly granted by You or Your distributors under this License prior to termination shall survive termination.

```
************************************************************************
*                                                                      *
*  6. Disclaimer of Warranty                                           *
*  -------------------------                                           *
*                                                                      *
*  Covered Software is provided under this License on an "as is"       *
*  basis, without warranty of any kind, either expressed, implied, or  *
*  statutory, including, without limitation, warranties that the       *
*  Covered Software is
 free of defects, merchantable, fit for a        *
*  particular purpose or non-infringing. The entire risk as to the     *
*  quality and performance of the Covered Software is with You.        *
*  Should any Covered Software prove defective in any respect, You     *
*  (not any Contributor) assume the cost of any necessary servicing,   *
*  repair, or correction. This disclaimer of warranty constitutes an   *
*  essential part of this License. No use of any Covered Software is   *
*  authorized under this License except under this disclaimer.         *
*                                                                      *
************************************************************************

************************************************************************
*                                                                      *
```

* 7. Limitation of Liability *
* ---------- *
*
*
* Under no circumstances and under no legal theory, whether tort *
* (including negligence), contract, or otherwise, shall any *
* Contributor, or anyone who distributes Covered Software as *
* permitted above, be liable to You for any direct, indirect, *
* special, incidental, or consequential damages of any character *
* including, without limitation, damages for lost profits, loss of *
* goodwill, work stoppage, computer failure or malfunction, or any *
* and all other commercial damages or losses, even if such party *
* shall have been informed of the possibility of such damages. This *
* limitation of liability shall not apply to liability for death or *
* personal injury resulting from such party's negligence to the *
* extent applicable law prohibits such limitation. Some *
* jurisdictions do not allow the exclusion or limitation
of *
* incidental or consequential damages, so this exclusion and *
* limitation may not apply to You. *
* *
****

8. Litigation

Any litigation relating to this License may be brought only in the
courts of a jurisdiction where the defendant maintains its principal
place of business and such litigation shall be governed by laws of that
jurisdiction, without reference to its conflict-of-law provisions.
Nothing in this Section shall prevent a party's ability to bring
cross-claims or counter-claims.

9. Miscellaneous

This License represents the complete agreement concerning the subject
matter hereof. If any provision of this License is held to be
unenforceable, such provision shall be reformed only to the extent
necessary to make it enforceable. Any law or regulation
which provides
that the language of a contract shall be construed against the drafter
shall not be used to construe this License against a Contributor.

10. Versions of the License

10.1. New Versions

Mozilla Foundation is the license steward. Except as provided in Section 10.3, no one other than the license steward has the right to modify or publish new versions of this License. Each version will be given a distinguishing version number.

10.2. Effect of New Versions

You may distribute the Covered Software under the terms of the version of the License under which You originally received the Covered Software, or under the terms of any subsequent version published by the license steward.

10.3. Modified Versions

If you create software not governed by this License, and you want to create a new license for such software, you may create and use a modified version of this License if you rename the license and remove any references to the name of the license steward (except to note that such modified license differs from this License).

10.4. Distributing Source Code Form that is Incompatible With Secondary Licenses

If You choose to distribute Source Code Form that is Incompatible With Secondary Licenses under the terms of this version of the License, the notice described in Exhibit B of this License must be attached.

Exhibit A - Source Code Form License Notice

This Source Code Form is subject to the terms of the Mozilla Public License, v. 2.0. If a copy of the MPL was not distributed with this file, You can obtain one at http://mozilla.org/MPL/2.0/.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.

Exhibit B - "Incompatible With Secondary Licenses" Notice

This Source Code Form is "Incompatible With Secondary Licenses", as

defined by the Mozilla Public License, v. 2.0.

1.66 jackson-databind 2.17.1

1.66.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work

by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Copyright

Copyright 2007-, Tatu Saloranta (tatu.saloranta@iki.fi)

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.67 glibc-minimal-langpack 2.34-231.el9_7.2

1.67.1 Available under license :

@c The GNU Lesser General Public License.
@center Version 2.1, February 1999

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]
@end display

@subheading Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software---to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software---typically
libraries---of the Free
Software Foundation and other authors who decide to use it. You can use
it too, but we suggest you first think carefully about whether this
license or the ordinary General Public License is the better strategy to
use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of it
in new free programs; and that you are informed that you can do these
things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for

you if you distribute copies of the library
or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation
will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative
of the original library. The ordinary
General Public License therefore permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the @dfn{Lesser} General Public License because it
does @emph{Less} to protect the user's freedom than the ordinary General

Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the
same job as widely used non-free libraries. In this
case, there is little to gain by limiting the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
``work based on the library'' and a ``work that uses the library''. The
former
contains code derived from the library, whereas the latter must
be combined with the library in order to run.

@subheading TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

@enumerate 0
@item
This License Agreement applies to any software library or other program
which contains a notice placed by the copyright holder or other
authorized party saying it may be distributed under the terms of this
Lesser General Public License (also called ``this License''). Each
licensee is addressed as ``you''.

A ``library'' means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The ``Library'', below, refers to any such software library or work which has been distributed under these terms. A ``work based on the Library'' means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it,
either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term ``modification''.)

``Source code'' for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

@item
You may copy and distribute
verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

@item
You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

@enumerate a
@item
The modified work must itself be a software library.

@item

You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

@item
You must
 cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

@item
If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)
@end enumerate

These requirements apply to the modified work as a whole. If
identifiable sections
 of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this
 License.

@item
You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

@item
You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and
2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

@item
A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a ``work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a ``work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because
it
contains portions of the Library), rather than a ``work that uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a ``work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a

derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise,
if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

@item
As an exception to the Sections above, you may also combine or
link a ``work that uses the Library'' with the Library to produce a
work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of
this License. Also, you must do one
of these things:

@enumerate a
@item
Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable ``work that
uses the Library'', as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

@item
Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable,
and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

@item
Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

@item
If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

@item
Verify that the user has already received a copy of these materials or that you have already sent this user a copy.
@end enumerate

For an executable, the required form of the ``work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that
is
normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

@item
You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on

the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

@enumerate a
@item
Accompany the combined library with a copy of the same work
based on the Library,
 uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

@item
Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.
@end enumerate

@item
You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

@item
You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited
 by law if you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

@item
Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.

@item
If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License,
 they do not
excuse you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply,
and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software
 distribution system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

@item
If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

@item
The Free Software Foundation
 may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
``any later version'', you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

@item
If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for
 this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

@center @b{NO WARRANTY}

@item
BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY ``AS IS'' WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item
IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
 BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.
@end enumerate

@subheading END OF TERMS AND CONDITIONS

@page
@subheading How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source
file to most effectively
convey the exclusion of warranty; and each file should have at least the ``copyright'' line and a pointer to where the full notice is found.

@smallexample
@var{one line to give the library's name and an idea of what it does.}
Copyright (C) @var{year} @var{name of author}

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.
@end
smallexample

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a ``copyright disclaimer'' for the library, if necessary. Here is a sample; alter the names:

@smallexample
Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

@var{signature of Ty Coon}, 1 April 1990
Ty Coon, President of Vice

@end smallexample

That's all there is to it!
Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.
                GNU GENERAL PUBLIC LICENSE
                 Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

                     Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

 When we speak of free software, we are referring to freedom, not
price.
  Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it

if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in

themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component

itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals

of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies

of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that

there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free

programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into
another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of

running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy

from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work

during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with

this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision
will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest

possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms of the
ordinary General Public License).

 To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey
 the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

  <one line to give the library's name and a brief idea of what it does.>
  Copyright (C) <year> <name of author>

  This library is free software; you can redistribute it and/or
  modify it under the terms of the GNU Lesser General Public
  License as published by the Free Software Foundation; either
  version 2.1 of the License, or (at your option) any later version.

  This library is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this library; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the
 library `Frob' (a library for tweaking knobs) written by James Random Hacker.

 <signature of Ty Coon>, 1 April 1990
 Ty Coon, President of Vice

That's all there is to it!
UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

  Unicode Data Files include all data files under the directories
http://www.unicode.org/Public/, http://www.unicode.org/reports/, and
http://www.unicode.org/cldr/data/. Unicode Data Files do not include PDF
online code charts under the directory http://www.unicode.org/Public/.

Software includes any source code published in the Unicode Standard or under
the directories http://www.unicode.org/Public/,
http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode,
Inc. All rights reserved. Distributed under
the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software
that the data or
software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.
This file contains the copying permission notices for various files in the
GNU C Library distribution that have copyright owners other than the Free

Software Foundation. These notices all require that a copy of the notice be included in the accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

All code incorporated from 4.4 BSD is distributed under the following license:

Copyright (C) 1991 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. [This condition was removed.]
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The DNS resolver code, taken from BIND 4.9.5, is copyrighted by UC Berkeley, by Digital Equipment Corporation and by Internet Software Consortium. The DEC portions are under the following license:

Portions Copyright (C) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above

copyright notice and this permission notice appear in all copies, and
that the name of Digital Equipment Corporation not be used in
advertising or publicity pertaining to distribution of the document or
software without specific, written prior permission.

THE SOFTWARE IS PROVIDED ``AS IS" AND DIGITAL EQUIPMENT CORP.
DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL
DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES
 OR ANY DAMAGES WHATSOEVER RESULTING
FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT,
NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION
WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The ISC portions are under the following license:

Portions Copyright (c) 1996-1999 by Internet Software Consortium.

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS
ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE
CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL
DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR
PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
ACTION, ARISING
 OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS
SOFTWARE.

The Sun RPC support (from rpcsrc-4.0) is covered by the following
license:

Copyright (c) 2010, Oracle America, Inc.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials
  provided with the distribution.

* Neither the name of the "Oracle America, Inc." nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following CMU license covers some of the support code for Mach,
derived from Mach 3.0:

Mach Operating System
Copyright (C) 1991,1990,1989 Carnegie Mellon University
All Rights Reserved.

Permission to use, copy, modify and distribute this software and its
documentation is hereby granted, provided that
both the copyright
notice and this permission notice appear in all copies of the
software, derivative works or modified versions, and any portions
thereof, and that both notices appear in supporting documentation.

CARNEGIE MELLON ALLOWS FREE USE OF THIS SOFTWARE IN ITS ``AS IS''
CONDITION. CARNEGIE MELLON DISCLAIMS ANY LIABILITY OF ANY KIND FOR
ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

Carnegie Mellon requests users of this software to return to

Software Distribution Coordinator
School of Computer Science
Carnegie Mellon University
Pittsburgh PA 15213-3890

or Software.Distribution@CS.CMU.EDU any improvements or
extensions that they make and grant Carnegie Mellon the rights to
redistribute these changes.

The file if_ppp.h is under the following CMU license:

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the
 above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CARNEGIE MELLON UNIVERSITY AND
CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE UNIVERSITY OR CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
 BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN
IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following license covers the files from Intel's "Highly Optimized
Mathematical Functions for Itanium" collection:

Intel License Agreement

Copyright (c) 2000, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* The name of Intel Corporation may not be used to endorse
 or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The files inet/getnameinfo.c and sysdeps/posix/getaddrinfo.c are copyright
(C) by Craig Metz and are distributed under the following license:

/* The Inner Net License,
 Version 2.00

 The author(s) grant permission for redistribution and use in source and
binary forms, with or without modification, of the software and documentation
provided that the following conditions are met:

0. If you receive a version of the software that is specifically labelled
  as not being for redistribution (check the version message and/or README),
  you are not permitted to redistribute that version of the software in any
  way or form.
1. All terms of the all other applicable copyrights and licenses must be
  followed.
2. Redistributions of source code must retain the authors' copyright
  notice(s), this list of conditions, and the following disclaimer.
3. Redistributions in binary form must reproduce the authors' copyright
  notice(s), this list of conditions, and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
4. [The copyright holder has authorized the removal of this clause.]
5. Neither the name(s)
 of the author(s) nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ITS AUTHORS AND CONTRIBUTORS ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE

DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

If these license terms cause you a real problem, contact the author. */

The file sunrpc/des_impl.c
is copyright Eric Young:

Copyright (C) 1992 Eric Young
Collected from libdes and modified for SECURE RPC by Martin Kuck 1994
This file is distributed under the terms of the GNU Lesser General
Public License, version 2.1 or later - see the file COPYING.LIB for details.
If you did not receive a copy of the license with this program, please
see <https://www.gnu.org/licenses/> to obtain a copy.

The file inet/rcmd.c is under a UCB copyright and the following:

Copyright (C) 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with
the distribution.
3. Neither the name of the project nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF

SUCH DAMAGE.

The file posix/runtests.c is copyright Tom Lord:

Copyright
1995 by Tom Lord

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its
documentation for any purpose and without fee is hereby granted,
provided that the above copyright notice appear in all copies and that
both that copyright notice and this permission notice appear in
supporting documentation, and that the name of the copyright holder not be
used in advertising or publicity pertaining to distribution of the
software without specific, written prior permission.

Tom Lord DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO
EVENT SHALL TOM LORD BE LIABLE FOR ANY SPECIAL, INDIRECT OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF
USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR
OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

The posix/rxspencer tests
are copyright Henry Spencer:

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

The file posix/PCRE.tests
is copyright University of Cambridge:

Copyright (c) 1997-2003 University of Cambridge

Permission is granted to anyone to use this software for any purpose on any computer system, and to redistribute it freely, subject to the following restrictions:

1. This software is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

2. The origin of this software must not be misrepresented, either by explicit claim or by omission. In practice, this means that if you use PCRE in software that you distribute to others, commercially or otherwise, you must put a sentence like this

Regular expression support is provided by the PCRE library package, which is open source software, written by Philip Hazel, and copyright by the University of Cambridge, England.

somewhere reasonably visible in your documentation and in any relevant files or online
help data or similar. A reference to the ftp site for the source, that is, to

ftp://ftp.csx.cam.ac.uk/pub/software/programming/pcre/

should also be given in the documentation. However, this condition is not intended to apply to whole chains of software. If package A includes PCRE, it must acknowledge it, but if package B is software that includes package A, the condition is not imposed on package B (unless it uses PCRE independently).

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. If PCRE is embedded in any software that is released under the GNU General Purpose Licence (GPL), or Lesser General Purpose Licence (LGPL), then the terms of that licence shall supersede any condition above with which it is incompatible.

Files from Sun fdlibm are copyright Sun Microsystems, Inc.:

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems,
Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice
is preserved.

Various long double libm functions are copyright Stephen L. Moshier:

Copyright 2001 by Stephen L. Moshier <moshier@na-net.ornl.gov>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, see
<https://www.gnu.org/licenses/>. */

1.68 langpacks-en 3.0-16.el9

1.68.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

Name: langpacks

Found in path(s):
* /langpacks-3.0-16.el9.src.rpm-cosi-expand-archive-HkmmLXAB/langpacks.spec

1.69 libcom-err 1.46.5-8.el9

1.69.1 Available under license :

This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

http://sourceforge.net/projects/e2fsprogs

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2001 by Andries Brouwer
Copyright (C) 1999, 2000, 2003 by Theodore Ts'o

You are free to distribute this software under the terms of the GNU
Lesser (Library) General Public License.

On Debian systems, the complete text of the GNU Lesser (Library)
General Public License can be found in /usr/share/common-licenses/LGPL-2.
This is the Debian GNU/Linux prepackaged version of the static EXT2
file system consistency checker (e2fsck.static). The EXT2 utilities
were written by Theodore Ts'o <tytso@mit.edu> and Remy Card
<card@masi.ibp.fr>.

Sources were obtained from http://sourceforge.net/projects/e2fsprogs

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <http://www.alcove.com/>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU
General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000,
2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General
Public License can be found in `/usr/share/common-licenses/GPL-2'.
#
This is a Makefile stub which handles the creation of BSD shared
libraries.
#
In order to use this stub, the following makefile variables must be defined.
#
BSDLIB_VERSION = 1.0

```
# BSDLIB_IMAGE = libce
# BSDLIB_MYDIR = et
# BSDLIB_INSTALL_DIR = $(SHLIBDIR)
#

all:: image

real-subdirs:: Makefile
 @echo " MKDIR pic"
 @mkdir -p pic

BSD_LIB = $(BSDLIB_IMAGE).so.$(BSDLIB_VERSION)
BSDLIB_PIC_FLAG = -fpic

image:  $(BSD_LIB)

$(BSD_LIB): $(OBJS)
 (cd pic; ld -Bshareable -o $(BSD_LIB) $(LDFLAGS_SHLIB) $(OBJS))
 $(MV) pic/$(BSD_LIB) .
 $(RM) -f ../$(BSD_LIB)
 (cd ..; $(LN) $(LINK_BUILD_FLAGS) \
  `echo $(my_dir) | sed -e 's;lib/;;'`/$(BSD_LIB) $(BSD_LIB))

install-shlibs install:: $(BSD_LIB)
 @echo " INSTALL_PROGRAM $(BSDLIB_INSTALL_DIR)/$(BSD_LIB)"
 @$(INSTALL_PROGRAM) $(BSD_LIB) \
  $(DESTDIR)$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
 @-$(LDCONFIG)

install-strip: install

install-shlibs-strip:: install-shlibs

uninstall-shlibs uninstall::
 $(RM) -f $(DESTDIR)$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)

clean::
 $(RM)
 -rf pic
 $(RM) -f $(BSD_LIB)
 $(RM) -f ../$(BSD_LIB)
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, and the entire permission notice in its entirety,
  including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
```

notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This is the Debian GNU/Linux prepackaged version of the translation
files of the EXT2 file system utilities. The EXT2 utilities were
written by Theodore Ts'o <tytso@mit.edu> and Remy Card
<card@masi.ibp.fr>.

Sources were obtained from http://sourceforge.net/projects/e2fsprogs

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <http://www.alcove.com/>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU
General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000,
2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General
Public License can be found in `/usr/share/common-licenses/GPL-2'.
This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Fri Dec 14 22:24:35 EST 2007

It is part of the main e2fsprogs distribution, which can be found at:

http://sourceforge.net/projects/e2fsprogs

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007 by
Theodore Ts'o

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, and the entire permission notice in its entirety,
  including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
  products derived from
 this software without specific prior
  written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
/*

Copyright 1987 by the Student Information Processing Board
 of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution

of the software without specific, written prior permission.
M.I.T. and the M.I.T. S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

*/
Index: tdbsa/tdb.c
===
--- tdbsa.orig/tdb.c
+++ tdbsa/tdb.c
@@ -4,11 +4,11 @@ Rev: 23371
Last Changed Date: 2007-06-06 20:14:06 -0400 (Wed, 06 Jun 2007)
*/
 /*
-   Unix SMB/CIFS implementation.
+   trivial database library - standalone version

-   trivial database library - private includes
-
-   Copyright (C) Andrew Tridgell   2005
+   Copyright (C) Andrew Tridgell   1999-2005
+   Copyright (C) Jeremy Allison   2000-2006
+   Copyright (C) Paul `Rusty' Russell   2000

     ** NOTE! The following LGPL license applies to the tdb
     ** library. This does NOT imply that all of Samba is released
EXT2ED is hereby placed under the terms of the GNU General Public License.
Follows the GNU license.

Gadi Oxman, August 1995

     GNU GENERAL PUBLIC LICENSE
        Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
                    675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

      Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software

Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents
constitute a work based on the
Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You
must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a

notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program
is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or
with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information
you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you

received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access
to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program
(or any work based on the
Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program

specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting
the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY
TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest

to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY;
for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into

proprietary programs. If your program is a subroutine library, you may consider
 it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.
This package, the EXT2 filesystem utilities, are made available under the GNU Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries which are made available under an MIT-style license. Please see lib/uuid/COPYING for more details for the license for the files comprising the libuuid library, and the source file headers of the libet and libss libraries for more information.

The most recent officially distributed version can be found at http://e2fsprogs.sourceforge.net. If you need to make a distribution, that's the one you should use. If there is some reason why you'd like a more recent version that is still in ALPHA testing (i.e., either using the "WIP" test distributions or one from the hg or git repository from the development branch, please contact me (tytso@mit.edu)
 before you ship. The release schedules for this package are flexible, if you give me enough lead time.

Theodore Ts'o
23-June-2007

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

 The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software

is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source
code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms
and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains

a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered
only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this

License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based
on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with
the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it
with the information you received as to the offer
to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made
by offering
access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing
the Program (or any work based on the
Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not

excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free

Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name
of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision
comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a

subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for
all its users.

This license, the Library General Public License, applies to some
specially designated Free Software Foundation software, and to any
other libraries whose authors decide to use it. You can use it for
your libraries, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if
you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a
fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link a program with the library, you must provide

complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program
is threatened constantly by software
patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is
in some sense simply using the library, and is
analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to

permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in
header files, but we have achieved it as regards
changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed
as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities
other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of

running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a
fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever
part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each
and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make
any other change in
these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the

source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work

during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library

facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has
the sole purpose of protecting the
integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as
if
written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the

"copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public
License as published by the Free Software Foundation; either
version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Library General Public License for more details.

You should have received a copy of the GNU Library General Public
License along with this library; if not, write to the Free Software
Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
This is the Debian GNU/Linux prepackaged version of the EXT2 file
system utilities (e2fsck, mke2fs, etc.). The EXT2 utilities were
written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from http://sourceforge.net/projects/e2fsprogs

Packaging is Copyright (c) 2003-2007 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <http://www.alcove.com/>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, are made available under the GNU General Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries
which are made available under an MIT-style license.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2'. The complete text of the GNU Library General Public License can be found in '/usr/share/common-licenses/LGPL-2'.

The license used for lib/et and lib/ss libraries is:

Copyright 1987 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose is hereby granted, provided that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T. S.I.P.B. make no representations about the suitability of this
software for any purpose. It is provided "as is" without express or implied warranty.

The license used for lib/uuid is:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND
FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

http://sourceforge.net/projects/e2fsprogs

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2003, 2004 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific
prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF

LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This is the Debian GNU/Linux prepackaged version of the ss
command-line interface parsing library. It is currently
distributed together with the EXT2 file system utilities, which are
otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>,
from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board
 of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
M.I.T. and
 the M.I.T. S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.
This is the Debian GNU/Linux prepackaged version of the Common Error
Description library. It is currently distributed together with the EXT2 file
system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>,
from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board
 of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,

and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
M.I.T. and the M.I.T.
S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

1.70 libzstd 1.5.5-1.el9

1.70.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the

source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt

otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made

generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.
BSD License

For Zstandard software

Copyright (c) Meta Platforms, Inc. and affiliates. All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.

* Neither the name Facebook, nor Meta, nor the names of its contributors may

be used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.71 xz-libs 5.2.5-8.el9_0

1.71.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid

anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the

Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of

this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent

access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other

circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the

GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for

software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those

products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is

not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of

technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution

medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the

Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of

rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this

License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS

THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

XZ Utils Licensing
==========

Different licenses apply to different files in this package. Here
is a rough summary of which licenses apply to which parts of this
package (but check the individual files to be sure!):

- liblzma is in the public domain.

- xz, xzdec, and lzmadec command line tools are in the public
domain unless GNU getopt_long had to be compiled and linked
in from the lib directory. The getopt_long code is under
GNU LGPLv2.1+.

- The scripts to grep, diff, and view compressed files have been
adapted from gzip. These scripts and their documentation are
under GNU GPLv2+.

- All the documentation in the doc directory and most of the
XZ Utils specific documentation files in other directories

are in the public domain.

- Translated messages are in the public domain.

- The build system contains public domain files, and files that
are under GNU GPLv2+ or GNU
GPLv3+. None of these files end up
in the binaries being built.

- Test files and test code in the tests directory, and debugging
utilities in the debug directory are in the public domain.

- The extra directory may contain public domain files, and files
that are under various free software licenses.

You can do whatever you want with the files that have been put into
the public domain. If you find public domain legally problematic,
take the previous sentence as a license grant. If you still find
the lack of copyright legally problematic, you have too many
lawyers.

As usual, this software is provided "as is", without any warranty.

If you copy significant amounts of public domain code from XZ Utils
into your project, acknowledging this somewhere in your software is
polite (especially if it is proprietary, non-free software), but
naturally it is not legally required. Here is an example of a good
notice to
put into "about box" or into documentation:

This software includes code from XZ Utils <https://tukaani.org/xz/>.

The following license texts are included in the following files:
- COPYING.LGPLv2.1: GNU Lesser General Public License version 2.1
- COPYING.GPLv2: GNU General Public License version 2
- COPYING.GPLv3: GNU General Public License version 3

Note that the toolchain (compiler, linker etc.) may add some code
pieces that are copyrighted. Thus, it is possible that e.g. liblzma
binary wouldn't actually be in the public domain in its entirety
even though it contains no copyrighted code from the XZ Utils source
package.

If you have questions, don't hesitate to ask the author(s) for more
information.

1.72 libusb 1.0.26-1.el9

1.72.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest
you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients
all the rights that we gave
you. You must make sure that they, too, receive or can get the source

code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat to the existence
of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits such linking only if the
entire combination fits
its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use
the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without

limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish
on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified
Library refers to a function or a
table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or

table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves,
then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to
a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed
under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this
License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables
containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing

the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people
have made
generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the

original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL

DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line
and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should
also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.73 cpp 11.5.0-11.el9

1.73.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide
to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs

(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify

that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative

work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object
code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the
work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in

Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies,

or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE

LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software

Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
This file contains a list of individuals who submit their patches to
the Cygwin sources under 2-clause BSD license, as well as a list of
individuals who signed the former Cygwin Copyright Assignment up to 2016.

==========
2-clause BSD:
==========
Copyright (c) <YEAR>, <OWNER>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE

ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

==========

Individuals submitting their patches under 2-clause BSD:

David Allsopp David.Allsopp@cl.cam.ac.uk
Erik M. Bray erik.bray@lri.fr
Brian Inglis Brian.Inglis@SystematicSw.ab.ca
Daniel Santos daniel.santos@pobox.com
Sergejs Lukanihins slukanihin@gmail.com
J.H.
van de Water houder@xs4all.nl

==========

Individuals who signed the former Cygwin Copyright Assignment:

AJ Reins tbisp@qwest.net
Brian E. Dessent brian@dessent.net
Brian Kenneth Ford Brian.Ford@FlightSafety.com
Charles K. Moore keithmo@exmsft.com
Christian Franke franke@computer.org
Christian Lestrade christian.lestrade@free.fr
Christopher Faylor me@cgf.cx
Christopher January chris@atomice.net
Conrad Scott conrad.scott@dsl.pipex.com
Corinna Vinschen corinna@vinschen.de
Craig Iain McGeachie slapdau@yahoo.com.au
David Korn dave.korn.cygwin@gmail.com
Davis Euresti davie@alum.mit.edu
Dennis Vshivkov walrus@amur.ru
Elfyn McBratney elfyn@ubertales.co.uk
Eric Blake eblake@redhat.com
Ernie Coskrey ernie.coskrey@steeleye.com
Gerd Spalink Gerd.Spalink@t-online.de
Hartmut Honisch hhonisch@users.sourceforge.net
Igor Pechtchanski pechtcha@cs.nyu.edu
Jacek Trzcinski jacek@certum.pl
Jeffrey
Eric Altman jaltman@openafs.org
Jerry D. Hedden jerry@hedden.us
Joe Loh joel@pivot3.com
Johan Rydberg johan@rydberg.com
Johannes Schindelin johannes.schindelin@gmx.de
John Hood cgull@glup.org
Jon Turney jon.turney@dronecode.org.uk
Yoni Londner yonihola2@gmail.com

Joseph H. Buehler jbuehler@hekimian.com
Joshua Daniel Franklin joshuadfranklin@yahoo.com
Ken Brown kbrown@cornell.edu
Lapo Luchini lapo@lapo.it
Lev Bishop lev.bishop@gmail.com
Mark Geisert mark@maxrnd.com
Max Kaehn slothman@electric-cloud.com
Micha Nelissen mdvpost@hotmail.com
Michael Haubenwallner michael.haubenwallner@ssi-schaefer.com
Nicholas S. Wourms nwourms@netscape.com
Pavel Yonkov Tsekov ptsekov@gmx.net
Peter Foley pefoley2@pefoley.com
Pierre A. Humblet phumblet@phumblet.no-ip.org
Robert G. Byrnes byrnes@curl.com
Ryan C. Gordon icculus@icculus.org
Sam Steingold sds@gnu.org
Stephen Cleary shammah@spamcop.net
Stephen Osborn bub@io.com
Takashi
Yano takashi.yano@nifty.ne.jp
Thomas Pfaff tpfaff@gmx.net
Vaclav Haisman vhaisman@gmail.com
Yaakov Selkovitz yselkowi@redhat.com
Yitzchak Scott-Thoennes sthoenna@efn.org

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we

suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the
recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat to the existence
of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and

is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination
fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we
use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without
limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish
on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library

with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License
to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be
distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the
library". The executable is therefore covered
by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any
executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable
source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the
user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed

under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying
or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any

particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing

and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL
DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line
and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either

version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You
should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,

publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and

wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the

Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
/* Copyright (C) 2013-2015 Free Software Foundation, Inc.

This file is part of GCC.

modify it under the terms of the GNU Library General Public License
as published by the Free Software Foundation; either version 2, or

```
  (at your option) any later version.

  In addition to the permissions in the GNU Library General Public
  License, the Free Software Foundation gives you unlimited
  permission to link the compiled version of this file into
  combinations with other programs, and to distribute those
  combinations without any restriction coming from the use of this
  file.  (The Library Public License restrictions do apply in other
  respects; for example, they cover modification of the file, and
  distribution when not linked into a combined executable.)

  This program is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Library
 General Public License for more details.

  You should have received a copy of the GNU Library General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street - Fifth Floor, Boston, MA
  02110-1301, USA.  */


#ifndef __VTV_H__
#define __VTV_H__

/* We could have used an enumeration here but it just makes it more
  difficult for the compiler to generate a call to this.  These are
  used as arguments to the function __VLTChangePermission, declared
  below.  */
#define __VLTP_READ_ONLY  0
#define __VLTP_READ_WRITE 1

#ifdef __cplusplus
extern "C" void __VLTChangePermission (int);
#else
extern void __VLTChangePermission (int);
#endif

#ifdef BIG_PAGE_SIZE
/* TODO - Replace '4096' below with correct big page size.  */
#define VTV_PAGE_SIZE 4096
#else
#if defined(__sun__) && defined(__svr4__) && defined(__sparc__)
#define VTV_PAGE_SIZE 8192
#else
#define VTV_PAGE_SIZE 4096
#endif
```

#endif

#endif /* __VTV_H__ */
DRuntime: Runtime Library for the D Programming Language
==========

Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED
"AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE
FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
The newlib subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source
file. Unless otherwise noted in the body of the source file(s), the following copyright
notices will apply to the contents of the newlib subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use,
modify, copy, or redistribute it subject to the terms and conditions
of the BSD License.   This program is distributed in the hope that
it will be useful, but WITHOUT ANY WARRANTY expressed or implied,
including the implied warranties of MERCHANTABILITY or FITNESS FOR
A PARTICULAR PURPOSE. A copy of this license is available at

http://www.opensource.org/licenses. Any Red Hat trademarks that are incorporated in the source code or documentation are not subject to the BSD License and may only be used or replicated with the express permission
of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY
OF SUCH DAMAGE.

(3) David M. Gay (AT&T 1991, Lucent 1998)

The author of this software is David M. Gay.

Copyright (c) 1991 by AT&T.

Permission to use, copy, modify, and distribute this software for any purpose without fee is hereby granted, provided that this entire notice is included in all copies of any software which is or includes a copy or modification of this software and in

all copies of the supporting
documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR AT&T MAKES ANY REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

The author of this software is David M. Gay.

Copyright (C) 1998-2001 by Lucent Technologies
All Rights Reserved

Permission to use, copy, modify, and distribute this software and
its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that the copyright notice and this
permission notice and warranty disclaimer appear in supporting
documentation, and that the name of Lucent or any of its entities
not be used in advertising or publicity pertaining to
distribution of the software without specific, written prior
permission.

LUCENT
DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS.
IN NO EVENT SHALL LUCENT OR ANY OF ITS ENTITIES BE LIABLE FOR ANY
SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER
IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF
THIS SOFTWARE.

(4) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which
specifically grants the user the right to modify, use and distribute this
software provided this notice is not removed or altered. All other rights
are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING,

PERFORMANCE, OR
USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the 29K Technical Support Center at 800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or 0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(5)

(6)

(7) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice is preserved.

(8) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:
permission to use, copy, modify, and distribute this file
for any purpose is hereby
granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(9) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is

freely granted, provided that the above copyright notice, this notice
and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE.

(10) Stephane Carrez (m68hc11-elf/m68hc12-elf targets only)

Copyright (C) 1999, 2000, 2001, 2002 Stephane Carrez (stcarrez@nerim.fr)

The authors hereby grant permission
to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(11) Christopher G. Demetriou

Copyright (c) 2001 Christopher G. Demetriou
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice,
this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) SuperH, Inc.

Copyright
2002 SuperH, Inc. All rights reserved

This software is the property of SuperH, Inc (SuperH) which specifically
grants the user the right to modify, use and distribute this software
provided this notice is not removed or altered. All other rights are
reserved by SuperH.

SUPERH MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL SUPERH BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the SuperH Support Center via
e-mail at softwaresupport@superh.com .

SuperH, Inc.
405 River Oaks Parkway
San Jose
CA 95134
USA

(13) Royal Institute of Technology

Copyright (c) 1999 Kungliga Tekniska Hgskolan
(Royal Institute of Technology, Stockholm, Sweden).
All rights reserved.

Redistribution and use in source and binary
forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of KTH nor the names of its contributors may be
used to endorse or promote products derived from this software without

specific prior written permission.

THIS SOFTWARE IS PROVIDED BY KTH AND ITS CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL KTH OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) Alexey Zelkin

Copyright (c) 2000, 2001 Alexey Zelkin <phantom@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS
``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(15) Andrey A. Chernov

Copyright (C) 1997 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without

modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(16)
FreeBSD

Copyright (c) 1997-2002 FreeBSD Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR
 SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(17) S. L. Moshier

Author: S. L. Moshier.

Copyright (c) 1984,2000 S.L. Moshier

Permission to use, copy, modify, and distribute this software for any
purpose without fee is hereby granted, provided that this entire notice
is included in all copies of any software which is or includes a copy
or modification of this software and in all copies of the supporting
documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
WARRANTY. IN PARTICULAR, THE AUTHOR MAKES NO REPRESENTATION
OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS
SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

(18) Citrus Project

Copyright (c)1999 Citrus Project,
All
 rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
 INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(19) Todd C. Miller

Copyright (c) 1998 Todd C. Miller <Todd.Miller@courtesan.com>

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE
 IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL
THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(20) DJ Delorie (i386 / arm)
Copyright (C) 1991 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted
provided that the above copyright notice and following paragraph are
duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even
 the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(21) Free Software Foundation LGPL License (*-linux* targets only)

  Copyright (C) 1990-1999, 2000, 2001   Free Software Foundation, Inc.
  This file is part of the GNU C Library.
  Contributed by Mark Kettenis <kettenis@phys.uva.nl>, 1997.

  The GNU C Library is free software; you can redistribute it and/or
  modify it under the terms of the GNU Lesser General Public
  License as published by the Free Software Foundation; either
  version 2.1 of the License, or (at your option) any later version.

The GNU C Library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with the GNU C Library; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA
02110-1301 USA.

(22) Xavier Leroy LGPL License (i[3456]86-*-linux* targets only)

Copyright (C) 1996 Xavier Leroy (Xavier.Leroy@inria.fr)

This program is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public License
as published by the Free Software Foundation; either version 2
of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

(23) Intel (i960)

Copyright (c) 1993 Intel Corporation

Intel hereby grants you permission to copy, modify, and distribute this
software and its documentation. Intel grants this permission provided
that the above copyright notice appears in all copies and that both the
copyright notice and this permission
notice appear in supporting
documentation. In addition, Intel grants this permission provided that
you prominently mark as "not part of the original" any modifications
made to this software or documentation, and that the name of Intel
Corporation not be used in advertising or publicity pertaining to
distribution of the software or the documentation without specific,
written prior permission.

Intel Corporation provides this AS IS, WITHOUT ANY WARRANTY, EXPRESS OR
IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY
OR FITNESS FOR A PARTICULAR PURPOSE. Intel makes no guarantee or
representations regarding the use of, or the results of the use of,
the software and documentation in terms of correctness, accuracy,
reliability, currentness, or otherwise; and you rely on the software,
documentation and results solely at your own risk.

IN NO EVENT SHALL INTEL BE LIABLE FOR ANY LOSS OF USE, LOSS OF BUSINESS, LOSS OF PROFITS, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES
OF ANY KIND. IN NO EVENT SHALL INTEL'S TOTAL LIABILITY EXCEED THE SUM PAID TO INTEL FOR THE PRODUCT LICENSED HEREUNDER.

(24) Hewlett-Packard (hppa targets only)

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:
permission to use, copy, modify, and distribute this file
for any purpose is hereby granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(25) Henry Spencer (only *-linux targets)

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the
Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
explicit claim or by omission. Since few users ever read sources,
credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
misrepresented as being the original software. Since few users
ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

(26) Mike Barcroft

Copyright (c) 2001 Mike Barcroft <mike@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
 conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
 ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(27) Konstantin Chuguev (--enable-newlib-iconv)

Copyright (c) 1999, 2000
  Konstantin Chuguev. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR
 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

iconv (Charset Conversion Library) v2.0

(28) Artem Bityuckiy (--enable-newlib-iconv)

Copyright (c) 2003, Artem B. Bityuckiy, SoftMine Corporation.
Rights transferred to Franklin Electronic Publishers.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(29) IBM, Sony, Toshiba (only spu-* targets)

(C) Copyright 2001,2006,
International Business Machines Corporation,
Sony Computer Entertainment, Incorporated,
Toshiba Corporation,

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
* Neither the names of the copyright holders nor the names of their
contributors may be used to endorse or promote products derived from this
software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

(30) - Alex Tatmanjants (targets using libc/posix)

Copyright (c) 1995 Alex Tatmanjants <alex@elvisti.kiev.ua>
at Electronni Visti IA, Kiev, Ukraine.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH
DAMAGE.

(31) - M. Warner Losh (targets using libc/posix)

Copyright (c) 1998, M. Warner Losh <imp@freebsd.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(32) - Andrey A. Chernov (targets using libc/posix)

Copyright (C) 1996 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other
materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(33) - Daniel Eischen (targets using libc/posix)

Copyright (c) 2001 Daniel Eischen <deischen@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification,
are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(34) - Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(35) - Arm Ltd

Copyright (c) 2009-2018 Arm Ltd
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer
 in the
   documentation and/or other materials provided with the distribution.
3. The name of the company may not be used to endorse or promote
   products derived from this software without specific prior written
   permission.

THIS SOFTWARE IS PROVIDED BY ARM LTD ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL ARM LTD BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(36) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright
 (c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(37) Texas Instruments Incorporated (tic6x-*, *-tirtos targets)

Copyright (c) 1996-2010,2014 Texas Instruments Incorporated
http://www.ti.com/

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Texas Instruments Incorporated nor the names

of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(38) National Semiconductor (cr16-* and crx-* targets)

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(39) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Adapteva nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(40) - Altera Corportion (nios2-* targets)

Copyright (c) 2003 Altera Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Altera Corporation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ALTERA CORPORATION, THE COPYRIGHT HOLDER, AND ITS CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(41) Ed Schouten - Free
BSD

Copyright (c) 2008 Ed Schouten <ed@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR
 SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(42) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

 * Redistributions of source code must retain the above copyright notice,
   this list of conditions and the following disclaimer.
 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
 * Neither the name of Rolls-Royce Controls
 and Data Services Limited nor
   the names of its contributors may be used to endorse or promote products
   derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER

CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(43) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The
authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(44) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2) Redistributions in binary form
must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE

OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(45) Phoenix Systems - Phoenix-RTOS targets

Copyright (c) 2016 Phoenix Systems
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(46) embedded brains - RTEMS targets

Copyright (c) 2017 embedded brains GmbH
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials
provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(47) John Baldwin - RTEMS targets

Copyright (c) 2015 John Baldwin <jhb@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(48) Jeffrey Roberson - RTEMS targets

Copyright (c) 2008, Jeffrey Roberson <jeff@freebsd.org>
All rights reserved.

Copyright (c) 2008 Nokia Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice unmodified, this list of conditions, and the following
  disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED
 BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(49) - SiFive Inc. (riscv-* targets)

Copyright (c) 2017 SiFive Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use,
modify, copy, or redistribute it subject to the terms and conditions
of the FreeBSD License.   This program is distributed in the hope that
it will be useful,
 but WITHOUT ANY WARRANTY expressed or implied,
including the implied warranties of MERCHANTABILITY or FITNESS FOR
A PARTICULAR PURPOSE. A copy of this license is available at
http://www.opensource.org/licenses.

(50) Michael R. Neilly (riscv-* targets)

(c) Copyright 2017 Michael R. Neilly
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* Neither the names of the copyright holders nor the names of their
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE
IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

(51) Mentor Graphics (amdgcn-* targets)

Copyright (c) 2014-2017 Mentor Graphics.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices
are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(52) BSD-2-Clause-FreeBSD (pru-* targets)

SPDX-License-Identifier: BSD-2-Clause-FreeBSD

Copyright (c) 2018-2019 Dimitar Dimitrov <dimitar@dinux.eu>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
/**
* DISCLAIMER
* This file has no copyright assigned and is placed in the Public Domain.
*
* Its code is distributed in the hope that it will be useful but WITHOUT
* ANY WARRANTY. ALL WARRANTIES, EXPRESSED OR IMPLIED ARE HEREBY DISCLAIMED.
* This includes but is not limited to warranties of MERCHANTABILITY or
* FITNESS FOR A PARTICULAR PURPOSE.
*/
The libgloss subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source
file. Unless otherwise noted in the body of the source file(s), the following copyright
notices will apply to the contents of the libgloss subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify,
copy, or redistribute it subject to the terms and conditions of the BSD
License.   This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties
of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license
is available at http://www.opensource.org/licenses. Any Red Hat trademarks that
are incorporated in the source code or documentation are not subject to the BSD
License and may only be used or replicated with the express
permission of
Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of the University nor the names of its contributors may
  be used to endorse or promote products derived from this software without
  specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
 LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY
OF SUCH DAMAGE.

(3) DJ Delorie

Copyright (C) 1993 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted
provided that the above copyright notice and following paragraph are
duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
 PURPOSE.

(4) (formerly GPL for fr30)

The GPL is no longer applicable to the fr30 platform. The piece of
code (syscalls.c) referencing the GPL has been officially relicensed.

(5) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which
specifically grants the user the right to modify, use and distribute this
software provided this notice is not removed or altered. All other rights
are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the 29K Technical Support Center at
800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or
0031-11-1129 in
Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(6) - Analog Devices, Inc. (bfin-* targets)

Copyright (C) 2006, 2008, 2009, 2011, 2012 Analog Devices, Inc.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(7) University of Utah and the Computer Systems Laboratory (CSL)
[applies only to hppa*-*-pro* targets]
Copyright (c) 1990,1994
The University of Utah and
the Computer Systems Laboratory (CSL). All rights reserved.

Permission to use, copy, modify and distribute this software is hereby
granted provided that (1) source code retains these copyright, permission,
and disclaimer notices, and (2) redistributions including binaries
reproduce the notices in supporting documentation, and (3) all advertising
materials mentioning features or use of this software display the following
acknowledgement: ``This product includes software developed by the
Computer Systems Laboratory at the University of Utah."

THE UNIVERSITY OF UTAH AND CSL ALLOW FREE USE OF THIS SOFTWARE IN ITS "AS
IS" CONDITION. THE UNIVERSITY OF UTAH AND CSL DISCLAIM ANY LIABILITY OF
ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

CSL requests users of this software to return to csl-dist@cs.utah.edu any
improvements that they make and grant CSL redistribution rights.

(8) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems,
 Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice is preserved.

(9) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:

permission to use, copy, modify, and distribute this file
for any purpose is hereby granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(10) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is
freely granted, provided that
 the above copyright notice, this notice
and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

(11) IBM Corp. spu processor (only spu-* targets)

(C) Copyright IBM Corp. 2005, 2006

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of IBM nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(13) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright (c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

1. Redistributions source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of Xilinx nor the names of its contributors may be
used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS
IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) - National Semiconductor Corporation

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice
 is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(15) - CodeSourcery, Inc. (tic6x-* targets)

Copyright (c) 2010 CodeSourcery, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above copyright
    notice, this list of conditions and the following disclaimer in the
    documentation and/or other materials provided with the distribution.
  * Neither the name of CodeSourcery
 nor the
    names of its contributors may be used to endorse or promote products
    derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CODESOURCERY, INC. ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL CODESOURCERY BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16) - GPL with exception (sparc-*leon*, crx-*, cr16-* targets only)

Copyright (C) 1992 Free Software Foundation,
Inc.
Written By David Vinayak Henkel-Wallace, June 1992

This file is free software; you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by the
Free Software Foundation; either version 2, or (at your option) any
later version.

In addition to the permissions in the GNU General Public License, the
Free Software Foundation gives you unlimited permission to link the
compiled version of this file with other programs, and to distribute
those programs without any restriction coming from the use of this
file. (The General Public License restrictions do apply in other
respects; for example, they cover modification of the file, and
distribution when not linked into another program.)

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a
copy of the GNU General Public License
along with this program; see the file COPYING. If not, write to
the Free Software Foundation, 59 Temple Place - Suite 330,
Boston, MA 02111-1307, USA.

As a special exception, if you link this library with files
compiled with GCC to produce an executable, this does not cause
the resulting executable to be covered by the GNU General Public License.
This exception does not however invalidate any other reasons why
the executable file might be covered by the GNU General Public License.

(17) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,

this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of Adapteva nor the names of its contributors may be used
  to endorse or promote products derived from this software without specific
  prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(18) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* Neither the name of Rolls-Royce Controls and Data Services Limited nor
  the names of its contributors may be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT
HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and
 that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(20) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2) Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names
 of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(21) BSD-2-Clause-FreeBSD (pru-* targets)

SPDX-License-Identifier: BSD-2-Clause-FreeBSD

Copyright (c)
2018-2019 Dimitar Dimitrov <dimitar@dinux.eu>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
/* Copyright (C) 2013-2021 Free Software Foundation, Inc.

  This file is part of GCC.

  modify it under the terms of the GNU Library General Public License
  as published by the Free Software Foundation; either version 2, or
  (at your option) any later version.

  In addition to the permissions in the GNU Library General Public
  License, the Free Software Foundation gives you unlimited
  permission to link the compiled version of this file into
  combinations with other programs, and to distribute those
  combinations without any restriction coming from the use of this
  file.  (The Library Public License restrictions do apply in other
  respects; for example, they cover modification of the file, and
  distribution when not linked into a combined executable.)

  This program is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Library
 General Public License for more details.

  You should have received a copy of the GNU Library General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street - Fifth Floor, Boston, MA
  02110-1301, USA.  */


#ifndef __VTV_H__
#define __VTV_H__

/* We could have used an enumeration here but it just makes it more
  difficult for the compiler to generate a call to this.  These are
  used as arguments to the function __VLTChangePermission, declared
  below.  */
#define __VLTP_READ_ONLY  0
#define __VLTP_READ_WRITE 1

#ifdef __cplusplus
extern "C" void __VLTChangePermission (int);
#else
extern void __VLTChangePermission (int);
#endif
```

```
#ifdef BIG_PAGE_SIZE
/* TODO - Replace '4096' below with correct big page size.  */
#define VTV_PAGE_SIZE 4096
#else
#if defined(__sun__) && defined(__svr4__) && defined(__sparc__)
#define VTV_PAGE_SIZE 8192
#else
#define VTV_PAGE_SIZE 4096
#endif
#endif



#endif /* __VTV_H__ */
/* Definitions for BSD assembler syntax for Intel 386
  (actually AT&T syntax for insns and operands,
  adapted to BSD conventions for symbol names and debugging.)
  Copyright (C) 1988-2021 Free Software Foundation, Inc.

This file is part of GCC.

GCC is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3, or (at your option)
any later version.

GCC is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with GCC; see the file COPYING3.  If not see
<http://www.gnu.org/licenses/>.  */

/* Use the Sequent Symmetry assembler syntax.  */

/* Define the syntax of pseudo-ops, labels and comments.  */

/* Prefix for internally generated assembler
 labels.  If we aren't using
  underscores, we are using prefix `.'s to identify labels that should
  be ignored, as in `i386/gas.h' --karl@cs.umb.edu  */

#define LPREFIX "L"

/* Assembler pseudos to introduce constants of various size.  */
```

```
#define ASM_BYTE "\t.byte\t"
#define ASM_SHORT "\t.word\t"
#define ASM_LONG "\t.long\t"
#define ASM_QUAD "\t.quad\t"  /* Should not be used for 32bit compilation.  */

/* This was suggested, but it shouldn't be right for DBX output. -- RMS
  #define ASM_OUTPUT_SOURCE_FILENAME(FILE, NAME) */


/* Define the syntax of labels and symbol definitions/declarations.  */

/* This is how to output an assembler line
  that says to advance the location counter by SIZE bytes.  */

#define ASM_OUTPUT_SKIP(FILE,SIZE)  \
 fprintf (FILE, "\t.space " HOST_WIDE_INT_PRINT_UNSIGNED"\n", (SIZE))

/* Define the syntax of labels and symbol definitions/declarations.  */

/* This says how to output an assembler line
  to define a global common symbol.  */

#define
 ASM_OUTPUT_COMMON(FILE, NAME, SIZE, ROUNDED)  \
( fputs (".comm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u\n", (int)(ROUNDED)))

/* This says how to output an assembler line
  to define a local common symbol.  */

#define ASM_OUTPUT_LOCAL(FILE, NAME, SIZE, ROUNDED)  \
( fputs (".lcomm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u\n", (int)(ROUNDED)))

#ifdef HAVE_GAS_LCOMM_WITH_ALIGNMENT
#define ASM_OUTPUT_ALIGNED_LOCAL(FILE, NAME, SIZE, ALIGNMENT)  \
( fputs (".lcomm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u,%u\n", (int)(SIZE), (int)(ALIGNMENT) / BITS_PER_UNIT))
#endif

/* This is how to output an assembler line
  that says to advance the location counter
  to a multiple of 2**LOG bytes.  */
```

```
#define ASM_OUTPUT_ALIGN(FILE,LOG) \
 if ((LOG)!=0) fprintf ((FILE), "\t.align %d\n", (LOG))

/* This is how to store into the string BUF
  the symbol_ref name of an internal numbered label
 where
  PREFIX is the class of label and NUM is the number within the class.
  This is suitable for output with `assemble_name'.  */

#define ASM_GENERATE_INTERNAL_LABEL(BUF,PREFIX,NUMBER) \
   sprintf ((BUF), "*%s%ld", (PREFIX), (long)(NUMBER))

/* The prefix to add to user-visible assembler symbols.  */

#define USER_LABEL_PREFIX "_"

/* Sequent has some changes in the format of DBX symbols.  */
#define DBX_NO_XREFS 1

/* Don't split DBX symbols into continuations.  */
#define DBX_CONTIN_LENGTH 0
```

```
================================================================================
compiler_rt License
================================================================================

The compiler_rt library is dual licensed under both the University of Illinois
"BSD-Like" license and the MIT license.  As a user of this code you may choose
to use it under either license.  As a contributor, you agree to allow your code
to be used under both.

Full text of the relevant licenses is included below.

================================================================================

University of Illinois/NCSA
Open Source License

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:

  LLVM Team

  University of Illinois at Urbana-Champaign

  http://llvm.org
```

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal with the Software without restriction,
including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimers.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimers in the documentation and/or other materials provided with the distribution.

* Neither the names of the LLVM Team, University of Illinois at Urbana-Champaign, nor the names of its contributors may be used to endorse or promote products derived from this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

==========

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or
substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

==
Copyrights and Licenses for Third Party Software Distributed with LLVM:
==
The LLVM software contains code written by third parties. Such software will
have its own individual LICENSE.TXT file in the directory in which it appears.
This file will describe the copyrights, license, and restrictions which apply
to that code.

The disclaimer of
warranty in the University of Illinois Open Source License
applies to all code in the LLVM Distribution, and nothing in any of the
other licenses gives permission to use the names of the LLVM Team or the
University of Illinois to endorse or promote products derived from this
Software.

The following pieces of software have additional or alternate copyrights,
licenses, and/or restrictions:

Program Directory
------- ---------
mach_override lib/interception/mach_override
@node Library Copying
@appendixsec GNU LESSER GENERAL PUBLIC LICENSE

@cindex LGPL, Lesser General Public License
@center Version 2.1, February 1999

@display
Copyright @copyright{} 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street - Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]
@end display

@appendixsubsec Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

Licenses are intended to guarantee your freedom to share and change
free software---to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software---typically libraries---of
the Free
Software Foundation and other authors who decide to use it. You can use
it too, but we suggest you first think carefully about whether this
license or the ordinary General Public License is the better strategy to
use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of it
in new free programs; and that you are informed that you can do these
things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems
that might be
introduced by others.

Finally, software patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that

any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library.
The ordinary
General Public License therefore permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the @dfn{Lesser} General Public License because it
does @emph{Less} to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free
libraries. In this
case, there is little to gain by limiting the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
``work based on the library'' and a ``work that uses the library''. The
former contains code derived from the
library, whereas the latter must
be combined with the library in order to run.

@iftex
@appendixsubsec TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
@end iftex
@ifinfo
@center GNU LESSER GENERAL PUBLIC LICENSE
@center TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
@end ifinfo

@enumerate 0
@item
This License Agreement applies to any software library or other program
which contains a notice placed by the copyright holder or other
authorized party saying it may be distributed under the terms of this
Lesser General Public License (also called ``this License''). Each
licensee is addressed as ``you''.

A ``library'' means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The ``Library'', below, refers to any such software library or work
which has been distributed under these terms. A ``work based on the
Library'' means
either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly into another language. (Hereinafter, translation is
included without limitation in the term ``modification''.)

``Source code'' for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control compilation
and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether

that is true depends on what the Library does
and what the program that uses the Library does.

@item
You may copy and distribute verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the
Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a
fee.

@item
You may modify your copy or copies of the Library or any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

@enumerate a
@item
The modified work must itself be a software library.

@item
You must cause
the files modified to carry prominent notices
stating that you changed the files and the date of any change.

@item
You must cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

@item
If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must

be optional: if the application does not supply it, the square
root function must still
 compute square roots.)
@end enumerate

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work
 based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

@item
You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

 Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

 This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

@item
You may copy and distribute the Library
 (or a portion or
derivative of it, under Section 2) in object code or executable form

under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

@item
A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a ``work that uses the Library''. Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However,
linking a ``work that uses the Library'' with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a ``work that uses the library''. The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a ``work that uses the Library'' uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work.
(Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

@item
As an exception to the Sections above, you may also combine or link a ``work that uses the Library'' with the Library to produce a

work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices,
you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of this License. Also, you must do one
of these things:

@enumerate a
@item
Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable ``work that
uses the Library'', as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

@item
Use a suitable shared library mechanism for linking with the Library. A
suitable mechanism is one that (1) uses at run time
a copy of the
library already present on the user's computer system, rather than
copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs
one, as long as the modified version is interface-compatible with the
version that the work was made with.

@item
Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

@item
If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

@item
Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.
@end enumerate

For an executable, the required form of the ``work that uses the
Library" must include any data and utility programs needed for
reproducing
the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies the
executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

@item
You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that
you do these two things:

@enumerate a
@item
Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

@item
Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.
@end enumerate

@item
You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or

distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

@item
You are not required to accept this License, since you have not signed it. However,
nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

@item
Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

@item
If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions
are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims
or to contest validity of any
such claims; this section has the sole purpose of protecting the

integrity of the free software distribution system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

@item
If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded.
  In such case, this License incorporates the limitation as if
written in the body of this License.

@item
The Free Software Foundation may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
``any later version'', you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

@item
If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software
 which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

@center NO WARRANTY

@item
BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY ``AS IS'' WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item
IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED
 TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.
@end enumerate

@iftex
@heading END OF TERMS AND CONDITIONS
@end iftex
@ifinfo
@center END OF TERMS AND CONDITIONS
@end ifinfo

@page
@appendixsubsec How to Apply These Terms to Your New Libraries

 If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively,
 under the terms of the
ordinary General Public License).

 To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
``copyright'' line and a pointer to where the full notice is found.

@smallexample

@var{one line to give the library's name and an idea of what it does.}
Copyright (C) @var{year} @var{name of author}

This library is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 2.1 of the License, or (at
your option) any later version.

This library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should
 have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301,
USA.
@end smallexample

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a ``copyright disclaimer'' for the library, if
necessary. Here is a sample; alter the names:

@smallexample
Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

@var{signature of Ty Coon}, 1 April 1990
Ty Coon, President of Vice
@end smallexample

That's all there is to it!
     GNU GENERAL PUBLIC LICENSE
       Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
   51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

      Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free

software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work
which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim
copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such

interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably
considered independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work
based on it,
under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is

allowed only for noncommercial distribution and only if you
received the program in object code
or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy
the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.
Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version
number of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE
LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the
License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands
`show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org

bzip2/libbzip2 version 1.0.6 of 6 September 2010

MIT License (MIT)

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
 USE OR OTHER DEALINGS IN THE
SOFTWARE.
Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

=-=-=-

*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES
 OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)COPYRIGHT 8.1 (Berkeley) 3/16/94
*/
==========
The LLVM Project is under the Apache License v2.0 with LLVM Exceptions:
==========

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common

control with that entity. For the purposes of this definition,
"control" means (i) the
power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached
to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition,
"submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative
Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work
includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional
attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License
does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,

whether in tort (including
negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such
obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and
limitations under the License.

---- LLVM Exceptions to the Apache 2.0 License ----

As an exception, if, as a result of your compiling your source code, portions
of this Software are embedded into an Object form of such source code, you
may redistribute such embedded portions in such Object form without complying
with the conditions of Sections 4(a), 4(b) and 4(d) of the License.

In addition, if you combine or link compiled
forms of this Software with
software that is licensed under the GPLv2 ("Combined Software") and if a
court of competent jurisdiction determines that the patent provision (Section
3), the indemnity provision (Section 9) or other Section of the License
conflicts with the conditions of the GPLv2, you may retroactively and
prospectively choose to deem waived or otherwise exclude such Section(s) of
the License, but only in their entirety and only with respect to the Combined
Software.

==
Software from third parties included in the LLVM Project:
==
The LLVM Project contains third party software which is under different license
terms. All such code will be identified clearly using at least one of two
mechanisms:
1) It will be in a separate directory tree with its own `LICENSE.txt` or
`LICENSE` file at the top containing the specific
license and restrictions
which apply to that software, or
2) It will contain specific license and restriction terms at the top of every
file.

==
Legacy LLVM License (https://llvm.org/docs/DeveloperPolicy.html#legacy):
==

The software contained in this directory tree is dual licensed under both the
University of Illinois "BSD-Like" license and the MIT license. As a user of
this code you may choose to use it under either license. As a contributor,
you agree to allow your code to be used under both.

Full text of the relevant licenses is included below.

==

University of Illinois/NCSA

Open Source License

Copyright (c) 2017-2019 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:
Threading Runtimes Team
Intel Corporation
http://www.intel.com

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal with the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimers.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimers in the documentation and/or other materials provided with the distribution.

* Neither the names of Intel Corporation Threading Runtimes Team nor the names of its contributors may be used to endorse or promote products derived from
this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

==========

Copyright (c) 2017-2019 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software,

and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
GCC RUNTIME LIBRARY EXCEPTION

Version 3.1, 31 March 2009

Copyright (C) 2009 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this
license document, but changing it is not allowed.

This GCC Runtime Library Exception ("Exception") is an additional
permission under section 7 of the GNU General Public License, version

3 ("GPLv3"). It applies to a given file (the "Runtime Library") that bears a notice placed by the copyright holder of the file stating that the file is governed by GPLv3 along with this Exception.

When you use GCC to compile a program, GCC may combine portions of certain GCC header files and runtime libraries with the compiled program. The purpose of this Exception is to allow compilation of non-GPL (including proprietary) programs to use, in this way, the header files and runtime libraries covered by this Exception.

0. Definitions.

A file is an "Independent Module" if it either requires the Runtime Library
for execution after a Compilation Process, or makes use of an interface provided by the Runtime Library, but is not otherwise based on the Runtime Library.

"GCC" means a version of the GNU Compiler Collection, with or without modifications, governed by version 3 (or a specified later version) of the GNU General Public License (GPL) with the option of using any subsequent versions published by the FSF.

"GPL-compatible Software" is software whose conditions of propagation, modification and use would permit combination with GCC in accord with the license of GCC.

"Target Code" refers to output from any compiler for a real or virtual target processor architecture, in executable form or suitable for input to an assembler, loader, linker and/or execution phase. Notwithstanding that, Target Code does not include data in any format that is used as a compiler intermediate representation, or used for producing a compiler intermediate representation.

The "Compilation Process" transforms code
entirely represented in
non-intermediate languages designed for human-written code, and/or in Java Virtual Machine byte code, into Target Code. Thus, for example, use of source code generators and preprocessors need not be considered part of the Compilation Process, since the Compilation Process can be understood as starting with the output of the generators or preprocessors.

A Compilation Process is "Eligible" if it is done using GCC, alone or with other GPL-compatible software, or if it is done without using any work based on GCC. For example, using non-GPL-compatible Software to optimize any GCC intermediate representations would not qualify as an Eligible Compilation Process.

1. Grant of Additional Permission.

You have permission to propagate a work of Target Code formed by
combining the Runtime Library with Independent Modules, even if such
propagation would otherwise violate the terms of GPLv3, provided that
all Target Code was generated by Eligible Compilation Processes. You
may
 then convey such a combination under terms of your choice,
consistent with the licensing of the Independent Modules.

2. No Weakening of GCC Copyleft.

The availability of this Exception does not imply any general
presumption that third-party software is unaffected by the copyleft
requirements of the license of GCC.
THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESSED OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Unless stated otherwise, the sources under the cygwin subdirectory,
as well as the sources under the cygserver subdirectory linked into
the Cygwin DLL, are licensed under the Lesser Gnu Public License,
version 3 or (at your option) any later version (LGPLv3+). See the
COPYING.LIB file for the exact wording of that license.

Unless stated otherwise, the sources under the cygserver subdir not
linked into the Cygwin DLL, as well as the sources under the lsaauth
and the utils subdirectories are licensed under the Gnu Public License,
version 3 or (at your option) any later version (GPLv3+). See the
COPYING file for the exact wording of that license.

Parts of the sources in any subdirectory are licensed using a BSD-like
license. The affected source files contain explicit copyright notices
to that
 effect.

Linking Exception:

 As a special exception, the copyright holders of the Cygwin library
 grant you additional permission to link libcygwin.a, crt0.o, and
 gcrt0.o with independent modules to produce an executable, and to
 convey the resulting executable under terms of your choice, without
 any need to comply with the conditions of LGPLv3 section 4. An
 independent module is a module which is not itself based on the
 Cygwin library.
This is the file "copying.dj". It does not apply to any sources
copyrighted by UCB Berkeley or the Free Software Foundation.

Copyright Information for sources and executables that are marked
Copyright (C) DJ Delorie
24 Kirsten Ave
Rochester NH 03867-2954

This document is Copyright (C) DJ Delorie and may be distributed
verbatim, but changing it is not allowed.

Source code copyright DJ Delorie is distributed under the terms of the
GNU General Public Licence, with the following exceptions:

* Any existing copyright or authorship information in any given source
file must remain intact. If you modify a source file, a notice to that
effect must be added to the authorship information in the source file.

* binaries provided in djgpp may be distributed without sources ONLY if
the recipient is given sufficient information to obtain a copy of djgpp
themselves. This primarily applies to go32.exe, emu387, stub.exe, and
the graphics drivers.

* modified versions of the binaries provided
in djgpp must be
distributed under the terms of the GPL.

* objects and libraries linked into an application may be distributed
without sources.

Changes to source code copyright BSD or FSF are copyright DJ Delorie, but
fall under the terms of the original copyright.

A copy of the file "COPYING" is included with this document. If you did not
receive a copy of "COPYING", you may obtain one from whence this document
was obtained, or by writing:
Free Software Foundation
675 Mass Ave
Cambridge, MA 02139
USA
libffi - Copyright (c) 1996-2014 Anthony Green, Red Hat, Inc and others.
See source files for details.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
``Software''), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
 CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by
 the Library is deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code

for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic

pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other

parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those

subprograms and other parts of the work.

The Corresponding Source need not include anything that users
can regenerate automatically from other parts of the Corresponding
Source.

The Corresponding Source for a work in source code form is that
same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of
copyright on the Program, and are irrevocable provided the stated
conditions are met. This License explicitly affirms your unlimited
permission to run the unmodified Program. The output from running a
covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or

modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work,

and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)

that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in

ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or

requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed

under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
GNU LIBRARY GENERAL PUBLIC LICENSE
****

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place -- Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble
========

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of

this Library General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or
translated straightforwardly into another language. (Hereinafter,
translation is included without limitation in the term
"modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code
means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the library.

Activities other than copying, distribution and modification are
not covered by this License; they are outside its scope. The act
of running
a program using the Library is not restricted, and
output from such a program is covered only if its contents
constitute a work based on the Library (independent of the use of
the Library in a tool for writing it). Whether that is true
depends on what the Library does and what the program that uses
the Library does.

1. You may copy and distribute verbatim copies of the Library's
complete source code as you receive it, in any medium, provided
that you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep
intact all the notices that refer to this License and to the
absence of any warranty; and distribute a copy of this License
along with the Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange
for a fee.

2. You may modify your copy or copies of the Library or
any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a. The modified work must itself be a software library.

b. You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c. You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d. If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and

performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License,
whose permissions
for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library.
To do this, you must alter all the notices that refer to this
License, so that they refer to the ordinary GNU General Public
License, version 2, instead of to this License. (If a
newer
version than version 2 of the ordinary GNU General Public License
has appeared, then you can specify that version instead if you
wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to
all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable
form under the terms of Sections 1 and 2 above provided that you
accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software
interchange.

If distribution of object code is
made by offering access to copy
from a designated place, then offering equivalent access to copy
the source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being
compiled or linked with it, is called a "work that uses the
Library". Such a work, in isolation, is not a derivative work of
the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because
it contains portions of the Library), rather than a "work that
uses the library". The executable is therefore covered by this
License. Section 6 states terms for distribution of such
executables.

When a "work that uses the Library" uses material from a header
file that is part of the Library, the object code for the work may
be a derivative work of the Library even though the source code is

not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any
executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a.
Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b. Accompany the work with a written offer, valid for at least

three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of

performing this distribution.

c. If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d. Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries
that do not normally
accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a. Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b. Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the

Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License
to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously

your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of

any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO

WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT
UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries
==========

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution
under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

ONE LINE TO GIVE THE LIBRARY'S NAME AND AN IDEA OF WHAT IT DOES.
Copyright (C) YEAR NAME OF AUTHOR

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Library General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper
mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

SIGNATURE OF TY COON, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library is

deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying
Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data
structure
layouts and accessors, or small macros, inline functions and templates

(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide

whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/. Unicode Data Files do not include PDF online code charts under the directory http://www.unicode.org/Public/. Software includes any source code published in the Unicode Standard or under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode, Inc. All rights reserved. Distributed under the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software that the data or software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR

PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.
Copyright (c) 2019 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.74 shadow-utils 2:4.9-15.el9

1.74.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any

patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any

part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium

customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to

these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions

of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
NOTE:
This license has been obsoleted by the change to the BSD-style copyright.
You may continue to use this license if you wish, but you are under no
obligation to do so.

(*
This document is freely plagiarised from the 'Artistic Licence',
distributed as part of the Perl v4.0 kit by Larry Wall, which is
available from most major archive sites. I stole it from CrackLib.

Id
*)

This documents purpose is to state the conditions under which this
Package (See definition below) viz: "Shadow", the Shadow Password Suite
which is held by Julianne Frances Haugh, may be copied, such that the
copyright holder maintains some semblance of artistic control over the
development of the package, while giving the users of the package the
right to use and distribute the Package in a more-or-less customary
fashion, plus the right to make reasonable modifications.

So there.

****

Definitions:

A "Package" refers to the collection
of files distributed by the
Copyright Holder, and derivatives of that collection of files created
through textual modification, or segments thereof.

"Standard Version" refers to such a Package if it has not been modified,
or has been modified in accordance with the wishes of the Copyright
Holder.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You
may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when AND WHY you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version
of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide separate documentation for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names, and clearly
documenting the differences in manual
pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. YOU MAY NOT CHARGE A FEE FOR THIS PACKAGE ITSELF. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that YOU DO NOT ADVERTISE this package as a product of your own.

6. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

7. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

```
/*
* Copyright (c) 1990 - 1994, Julianne Frances Haugh
* Copyright (c) 1996 - 2000, Marek Michakiewicz
* Copyright (c) 2000 - 2006, Tomasz Koczko
* Copyright (c) 2007 - 2011, Nicolas Franois
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
```

* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. The name of the copyright holders or contributors may not be used to
*   endorse or promote products derived from this software without
*   specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
* ``AS IS''
 AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
* LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
* HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
* OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it

in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work
which contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably

considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work
based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code
or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary

form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy
the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.
Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free
redistribution of the Program by
all those who receive copies directly or indirectly through you, then

the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free

Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE
LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

1.75 attr 2.5.1-3.el9

1.75.1 Available under license :

Most components of the "attr" package are licensed under
Version 2.1 of the GNU Lesser General Public License (see below).
below.

Some components (as annotated in the source) are licensed
under Version 2 of the GNU General Public License (see COPYING).

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your
freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions
that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function

must
be optional: if the application does not supply it, the square
root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere
aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library
into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a

medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on

which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further

restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time.

Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs
whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE
COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these
terms (or, alternatively, under the terms of the
ordinary General Public License).

To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License
for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Most components of the "attr" package are licensed under
Version 2.1 of the GNU Lesser General Public License (see COPYING.LGPL).

Some components (as annotated in the source) are licensed

under Version 2 of the GNU General Public License (see below),

---

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that
any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its
scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications
or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if
the Program itself is interactive but
does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works
based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections
1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that
component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation
may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision
will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING

WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts
in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License
does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

1.76 gpg-pubkey 5a6340b3-6229229e

1.76.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to

your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below,

refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but

does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source

code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software

Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this

is what you want to do, use the GNU Lesser General
Public License instead of this License.
The accompanying Red Hat Enterprise Linux @@VERSION@@ release includes
copyrighted software that is licensed under the GNU General Public
License and other licenses. You may obtain the complete
machine-readable source code corresponding to portions of this release
by sending a check or money order in the amount of US $5.00 to:

VP, Legal - Products & Technologies
Red Hat, Inc.
100 East Davie Street
Raleigh, NC 27601 USA

Please write "source for RHEL @@VERSION@@" in the memo line of your
payment.

This offer is valid to anyone in receipt of this information and shall
expire three years following the date of the final distribution of
this release by Red Hat, Inc.
END USER LICENSE AGREEMENT
RED HAT(R) ENTERPRISE LINUX(R) AND RED HAT APPLICATIONS

This end user license agreement ("EULA") governs the use of any Red
Hat software application that includes or refers to this license and
any related updates, source code, appearance, structure and
organization (the "Programs"), regardless of the delivery mechanism.

1. License Grant. Subject to the following terms, Red Hat, Inc. ("Red
Hat") grants to you a perpetual, worldwide license to the Programs
(each of which may include multiple software components) pursuant
to the GNU General Public License v.2
(https://www.gnu.org/licenses/oldlicenses/gpl-2.0.en.html). With
the exception of certain image files identified in Section 2
below, each software component is governed by a license located in
the software component's source code that permits you to run, copy,
modify, and redistribute (subject to certain obligations in some
cases) the software component. The license rights for
the binary
only firmware components are located with the components
themselves. This EULA pertains solely to the Programs and does not
limit your rights under, or grant you rights that supersede, the
license terms of any particular component.

2. Intellectual Property Rights. The Programs and each of their
components are owned by Red Hat and other licensors and are
protected under copyright law and other laws as applicable. Title

to the Programs and any component, or to any copy or modification shall remain with Red Hat and other licensors, subject to the applicable license. The "Red Hat" mark, the individual Program marks, and the "Red Hat" logo are trademarks or registered trademarks of Red Hat and its affiliates in the U.S. and other countries. This EULA does not permit you to distribute the Programs using Red Hat's trademarks, regardless of whether the Programs have been modified. You may make a commercial redistribution of the Programs only if (a) permitted under a separate written agreement with Red Hat authorizing such commercial redistribution or (b) you remove and replace all occurrences of Red Hat trademarks and logos. Modifications to the software may corrupt the Programs. You should read the information found at http://www.redhat.com/about/corporate/trademark/ before distributing a copy of the Programs.

3. Limited Warranty. Except as specifically stated in this Section 3, a separate agreement with Red Hat, or a license for a particular component, to the maximum extent permitted under applicable law, the Programs and the components are provided and licensed "as is" without warranty of any kind, express or implied, including the implied warranties of merchantability, non-infringement or fitness for a particular purpose. Red Hat warrants that the media on which the Programs and the components are provided will be free from defects in materials and manufacture under normal use for a period of 30 days from the date of delivery to you. Neither Red Hat nor its affiliates warrant that the functions contained in the Programs will meet your requirements or that the operation of the Programs will be entirely error free, appear or perform precisely as described in the accompanying documentation, or comply with regulatory requirements. This warranty extends only to the party that purchases subscription services for the Programs from Red Hat and/or its affiliates or a Red Hat authorized distributor.

4. Limitation of Remedies and Liability. To the maximum extent permitted by applicable law, your exclusive remedy under this EULA is to return any defective media within 30 days of delivery along with a copy of your payment receipt and Red Hat, at its option, will replace it or refund the money you paid for the media. To the maximum extent permitted under applicable law, under no circumstances will Red Hat, its affiliates, any Red Hat authorized distributor, or the licensor of any component provided to you under this EULA be liable to you for any incidental or consequential damages, including lost profits or lost savings arising out of the

use or inability to use the Programs or any component, even if Red Hat, its affiliates, an authorized distributor, and/or licensor has been advised of the possibility of such damages. In no event shall Red Hat's or its affiliates' liability, an authorized distributor's liability or the liability of the licensor of a component provided to you under this EULA exceed the amount that you paid to Red Hat for the media under this EULA.

5. Export Control. You understand that countries, including the U.S., may restrict the import, use, export, re-export or transfer of encryption products and other controlled materials (which may include the Programs or related technical information licensed hereunder) ("Controlled Materials"). As required by U.S. law, you represent and warrant that you: (a) understand that certain of the Controlled Materials are of U.S. origin and subject to export controls under the U.S. Export Administration Regulations (the "EAR"); (b) are not located in (or owned or controlled by any person or entity located in) any country listed in Country Group E:1 in Supplement No. 1 to part 740 of the EAR; or by any person or entity listed on the U.S. Department of Treasury Office of Foreign Assets Control ("OFAC") list of Specially Designated Nationals and Blocked Persons ("SDNs") (and are not 50% or more owned or controlled by any one or more persons or entities identified on the SDN list); (c) will not export, re-export or transfer the Controlled Materials to (1) any prohibited destination, (2) anyone who has been prohibited from participating in U.S. export transactions by any federal agency of the U.S. government or (3) any end user who you know or have reason to know will use them in the design, development or production of nuclear, chemical or biological weapons, or rocket systems, space launch vehicles, or sounding rockets, or unmanned air vehicle systems or any other prohibited use under the EAR; and (d) understand and agree that if you are in the United States and export, re-export or transfer the Controlled Materials to eligible end users, you will, to the extent required by EAR Section 740.17(e), submit semi-annual reports to the U.S. Commerce Department's Bureau of Industry and Security, that include the name and address (including country) of each transferee.

6. Third Party Software. The Programs may be provided with third party software that are not part of the Programs. These third party software are not required to run the Programs, are provided as a convenience to you, and are subject to their own license terms. The license terms either accompany the third party software or can be viewed at http://www.redhat.com/licenses/thirdparty/eula.html. If you do not agree to abide by the applicable license terms for the

third party software, then you may not install them. If you wish to install the third party software on more than one system or transfer the third party software to another party, then you must contact the licensor of the applicable third party software.

7. General. If any provision of this EULA is held to be unenforceable, the enforceability of the remaining provisions shall not be affected. Any claim, controversy or dispute arising under or relating to this EULA shall be governed by the laws of the State of New York and of the United States, without regard to any conflict of laws provisions. The rights and obligations of the parties to this EULA shall not be governed by the United Nations Convention on the International Sale of Goods.

Copyright (C) 2019 Red Hat, Inc. All rights reserved. The Program marks, "Red Hat"
mark and the Red Hat logo are trademarks or registered trademarks of Red Hat, Inc. All other trademarks are the property of their respective owners.

1.77 setup 2.13.7-10.el9

1.77.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2761148229_1762982441.4856465/0/setup-2.13.7-10.el9-1.src.rpm-cosi-expand-archive-CCMvEFhU/setup-2.13.7.tar.bz2-cosi-expand-archive-DinyIGjL/setup-2.13.7.tar.bz2# /etc/services: /opt/cola/permits/2761148229_1762982441.4856465/0/setup-2.13.7-10.el9-1.src.rpm-cosi-expand-archive-CCMvEFhU/setup-2.13.7.tar.bz2-cosi-expand-archive-DinyIGjL/setup-2.13.7.tar.bz2Summary: A set of system configuration and setup files
/opt/cola/permits/2761148229_1762982441.4856465/0/setup-2.13.7-10.el9-1.src.rpm-cosi-expand-archive-CCMvEFhU/setup.specSummary: A set of system configuration and setup files

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

Setup package is public domain.

Found in path(s):
* /setup-2.13.7-10.el9-1.src.rpm-cosi-expand-archive-CCMvEFhU/setup-2.13.7.tar.bz2-cosi-expand-archive-DinyIGjL/setup-2.13.7.tar.bz2

1.78 libtool-ltdl 2.4.6-46.el9

1.78.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source

code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into

another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that,

in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of

the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these

materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if

you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR

CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which

gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.

Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that
contains a notice placed by the copyright holder saying it can be
distributed under the terms of this License. Such a notice grants a
world-wide, royalty-free license, unlimited in duration, to use that
work under the conditions stated herein. The ``Document'', below,
refers
to any such manual or work. Any member of the public is a
licensee, and is addressed as ``you''. You accept the license if you
copy, modify or distribute the work in a way requiring permission
under copyright law.

A ``Modified Version'' of the Document means any work containing the
Document or a portion of it, either copied verbatim, or with
modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section
of the Document that deals exclusively with the relationship of the
publishers or authors of the Document to the Document's overall
subject (or to related matters) and contains nothing that could fall
directly within that overall subject. (Thus, if the Document is in
part a textbook of mathematics, a Secondary Section may not explain
any mathematics.) The relationship could be a matter of historical
connection with the subject or with related matters, or of legal,
commercial, philosophical, ethical or political
position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles
are designated, as being those of Invariant Sections, in the notice
that says that the Document is released under this License. If a
section does not fit the above definition of Secondary then it is not
allowed to be designated as Invariant. The Document may contain zero
Invariant Sections. If the Document does not identify any Invariant
Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,
as Front-Cover Texts or Back-Cover Texts, in the notice that says that
the Document is released under this License. A Front-Cover Text may
be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,
represented in a format whose specification is available to the
general public, that is suitable for revising the document
straightforwardly with generic text editors or (for
 images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
ASCII without markup, Texinfo input format, La@TeX{} input
format, SGML or XML using a publicly available
DTD, and standard-conforming simple HTML,
PostScript or PDF designed for human modification. Examples
of transparent image formats include PNG, XCF and
JPG@. Opaque formats include proprietary formats that can be
read and edited only by proprietary word
 processors, SGML or
XML for which the DTD and/or processing tools are
not generally available, and the machine-generated HTML,
PostScript or PDF produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means
the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'',
 or ``History''.)  To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which
states that this License applies to the Document. These Warranty
Disclaimers are considered to be included by reference in this
License, but only as regards disclaiming warranties: any other
implication that these Warranty Disclaimers may have is void and has
no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either
commercially or noncommercially, provided that this License, the
copyright notices, and the license notice saying this License applies
to the Document are reproduced in all copies, and that you add no other
conditions whatsoever to those of this License. You may not use
technical measures to obstruct or control the reading or further
copying of the copies
 you make or distribute. However, you may accept
compensation in exchange for copies. If you distribute a large enough
number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and
you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have
printed covers) of the Document, numbering more than 100, and the
Document's license notice requires Cover Texts, you must enclose the
copies in covers that carry, clearly and legibly, all these Cover
Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on
the back cover. Both covers must also clearly and legibly identify
you as the publisher of these copies. The front cover must present
the full title with all words of the title equally prominent and
visible. You may add other material on the covers in addition.

Copying with changes limited to the covers, as long as they preserve
the
title of the Document and satisfy these conditions, can be treated
as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit
legibly, you should put the first ones listed (as many as fit
reasonably) on the actual cover, and continue the rest onto adjacent
pages.

If you publish or distribute Opaque copies of the Document numbering
more than 100, you must either include a machine-readable Transparent
copy along with each Opaque copy, or state in or with each Opaque copy
a computer-network location from which the general network-using
public has access to download using public-standard network protocols
a complete Transparent copy of the Document, free of added material.
If you use the latter option, you must take reasonably prudent steps,
when you begin distribution of Opaque copies in quantity, to ensure
that this Transparent copy will remain thus accessible at the stated
location until at least one year after the last time you distribute
an
Opaque copy (directly or through your agents or retailers) of that
edition to the public.

It is requested, but not required, that you contact the authors of the
Document well before redistributing any large number of copies, to give
them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under
the conditions of sections 2 and 3 above, provided that you release
the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same
title as a previous version
if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the
Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History'' section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item
For any
section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document, you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant
Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old

one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if
known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License
into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an ``aggregate'' if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'', ``Dedications'', or ``History'', the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and

will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for
any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and
conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'') contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons
 Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License
 in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License''.

@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts."@: line with this:

@smallexample
@group
  with the Invariant Sections being @var{list their titles}, with
  the Front-Cover Texts being @var{list}, and with the Back-Cover Texts
  being @var{list}.
@end group
@end smallexample

If you have Invariant
 Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:

1.79 libsepol 3.6-3.el9

1.79.1 Available under license :

This library (libselinux) is public domain software, i.e. not copyrighted.

Warranty Exclusion

You agree that this software is a
non-commercially developed program that may contain "bugs" (as that
term is used in the industry) and that it may not function as intended.
The software is licensed "as is". NSA makes no, and hereby expressly
disclaims all, warranties, express, implied, statutory, or otherwise
with respect to the software, including noninfringement and the implied
warranties of merchantability and fitness for a particular purpose.

Limitation of Liability

In no event will NSA be liable for any damages, including loss of data,
lost profits, cost of cover, or other special, incidental,

consequential, direct or indirect damages arising from the software or the use thereof, however caused and on any theory of liability. This limitation will apply even if NSA has been advised of the possibility of such damage. You acknowledge that this is
a reasonable allocation of
risk.

1.80 dnf-data 4.14.0-31.el9

1.80.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their

rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the

notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is

void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed

through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS

TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.81 gnutls 3.8.3-9.el9

1.81.1 Available under license :

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons") that the public can reliably and without fear of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or
other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
moral rights retained by the original author(s) and/or performer(s);
publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
rights
protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
rights protecting the extraction, dissemination, use and reuse of data in a Work;
database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and
other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims
and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's
express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will

not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.

Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.

Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without

limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.

Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

The "inih" library is distributed under the New BSD license:

Copyright (c) 2009, Ben Hoyt
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* Neither the name of Ben Hoyt nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY BEN HOYT "AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE
DISCLAIMED. IN NO EVENT SHALL BEN HOYT BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices

stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing

or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For
example, if a patent
license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to
decide if he or she is willing
to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License

may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may

be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

 This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
 decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

 When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that

you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a

combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or

other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary

GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The

threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate

properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the

integrity of the free software distribution system
which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
LICENSING
=========

Since GnuTLS version 3.1.10, the core library is released under
the GNU Lesser General Public License (LGPL) version 2.1 or later
(see doc/COPYING.LESSER for the license terms).

The GNU LGPL applies to the main GnuTLS library, while the
included applications as well as gnutls-openssl
library are under the GNU GPL version 3. The gnutls library is
located in the lib/ and libdane/ directories, while the applications
in src/ and, the gnutls-openssl library is at extra/.

The documentation in doc/ is under the GNU FDL license 1.3.

Note, however, that the nettle and the gmp libraries which are
GnuTLS dependencies, they are distributed under a LGPLv3+ or GPLv2+ dual
license. As such binaries linking to them need to adhere to either LGPLv3+
or the GPLv2+ license.

For any copyright year range specified as YYYY-ZZZZ in this package
note that the range specifies every single year in that closed interval.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of

protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy,
is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require,

such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to

the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent

works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source

may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded
from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,
procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the
Corresponding Source conveyed under this section must be accompanied
by the Installation Information. But this requirement does not apply
if neither you nor any third party retains the ability to install
modified object code on the User Product (for example, the work has

been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty
or limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your
license from a particular copyright holder is reinstated (a)
provisionally, unless and until the copyright holder explicitly and

finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have

permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.
/* Extract the last component (base name) of a file name.

Copyright (C) 1998, 2001, 2003-2006, 2009-2023 Free Software Foundation,
Inc.

This file is free software: you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of the
License, or (at your option) any later version.

This file is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>. */

#ifndef _BASENAME_LGPL_H

```
#define _BASENAME_LGPL_H

#include <stddef.h>

#ifndef DOUBLE_SLASH_IS_DISTINCT_ROOT
# define DOUBLE_SLASH_IS_DISTINCT_ROOT 0
#endif

#ifdef __cplusplus
extern "C" {
#endif


/*
 Return the address of the last file name component of FILENAME.
  If FILENAME has some trailing slash(es), they are considered to be
  part of the last component.
  If FILENAME has no relative file name components because it is a file
  system root, return the empty string.
  Examples:
          FILENAME      RESULT
          "foo.c"       "foo.c"
          "foo/bar.c"   "bar.c"
          "/foo/bar.c"  "bar.c"
          "foo/bar/"    "bar/"
          "foo/bar//"   "bar//"
          "/"           ""
          "//"          ""
          ""            ""
  The return value is a tail of the given FILENAME; do NOT free() it!  */

/* This function was traditionally called 'basename', but we avoid this
  function name because
    * Various platforms have different functions in their libc.
      In particular, the glibc basename(), defined in <string.h>, does
      not consider trailing slashes to be part of the component:

 FILENAME      RESULT
          "foo/bar/"    ""
          "foo/bar//"   ""
    * The 'basename' command eliminates trailing slashes and for a root
      produces a non-empty result:
          FILENAME      RESULT
          "foo/bar/"    "bar"
          "foo/bar//"   "bar"
          "/"           "/"
          "//"          "/"
*/
```

```
extern char *last_component (char const *filename) _GL_ATTRIBUTE_PURE;

/* Return the length of the basename FILENAME.
  Typically FILENAME is the value returned by base_name or last_component.
  Act like strlen (FILENAME), except omit all trailing slashes.  */
extern size_t base_len (char const *filename) _GL_ATTRIBUTE_PURE;



#ifdef __cplusplus
} /* extern "C" */
#endif

#endif /* _BASENAME_LGPL_H */
```

```
========================================================================
Written by Andy Polyakov <appro@fy.chalmers.se> for the OpenSSL
project. The module is, however, dual licensed under OpenSSL and
CRYPTOGAMS licenses depending on where you obtain it. For further
details see https://www.openssl.org/~appro/cryptogams/.
========================================================================

Copyright (c) 2006-2012, CRYPTOGAMS by <appro@openssl.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

    * Redistributions of source code must retain copyright notices,
 this list of conditions and the following disclaimer.

    * Redistributions in binary form must reproduce the above
 copyright notice, this list of conditions and the following
 disclaimer in the documentation and/or other materials
 provided with the distribution.

    * Neither the name of the CRYPTOGAMS nor
 the names of its
 copyright holder and contributors may be used to endorse or
 promote products derived from this software without specific
 prior written permission.

ALTERNATIVELY, provided that this notice is retained in full, this
product may be distributed under the terms of the GNU General Public
License (GPL), in which case the provisions of the GPL apply INSTEAD OF
those given above.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
```

LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

##
Constant-time SSSE3 AES core implementation.
version 0.1
##
By Mike Hamburg (Stanford University), 2009
Public domain.
##
For details see https://shiftleft.org/papers/vector_aes/ and
https://crypto.stanford.edu/vpaes/.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new

free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official

standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product,

doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions.

Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further

restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or

run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor

version. For
purposes of this definition, "control" includes the right to grant
patent sublicenses in a manner consistent with the requirements of
this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free
patent license under the contributor's essential patent claims, to
make, use, sell, offer for sale, import and otherwise run, modify and
propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express
agreement or commitment, however denominated, not to enforce a patent
(such as an express permission to practice a patent or covenant not to
sue for patent infringement). To "grant" such a patent license to a
party means to make such an agreement or commitment not to enforce a
patent against the party.

If you convey a covered work, knowingly relying on a patent license,
and the Corresponding Source of the work is not available for anyone
to copy, free of charge and under the terms of this
License, through a
publicly available network server or other readily accessible means,
then you must either (1) cause the Corresponding Source to be so
available, or (2) arrange to deprive yourself of the benefit of the
patent license for this particular work, or (3) arrange, in a manner
consistent with the requirements of this License, to extend the patent
license to downstream recipients. "Knowingly relying" means you have
actual knowledge that, but for the patent license, your conveying the
covered work in a country, or your recipient's use of the covered work
in a country, would infringe one or more identifiable patents in that
country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or
arrangement, you convey, or propagate by procuring conveyance of, a
covered work, and grant a patent license to some of the parties
receiving the covered work authorizing them to use, propagate, modify
or convey a specific copy of the covered
work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying

the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered

version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library is
deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code
for portions of the Combined Work that, considered in isolation, are
based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the

object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying
Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data
structure
layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse

engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for

software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those

products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is

not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of

technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution

medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the

Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of

rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this

License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS

THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/philosophy/why-not-lgpl.html>.
The MIT License (MIT)

Copyright (c) 2016 Wrymouth Innovation Ltd

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL
THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.82 mpfr 4.1.0-7.el9

1.82.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by
the Library is deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code
for portions of the Combined Work that, considered in isolation, are
based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the
object code and/or source code for the Application, including any data
and utility programs needed for reproducing the Combined Work from the
Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free

software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.

States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the

work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying
the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public
License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),

EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.

1.83 ncurses-libs 6.2-12.20210508.el9

1.83.1 Available under license :

Upstream source https://invisible-island.net/ncurses/ncurses-examples.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2003-2019,2020 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining
a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-
ings in this Software without prior written authorization from the X Consor-
tium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent
`make' implicit rules from creating a file called install from it

when there is no Makefile.

This script is compatible with the BSD install script, but was written
from scratch. It can only install one file at a time, a restriction
shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source https://invisible-island.net/ncurses/ncurses.html
This package is used for testing builds of ncurses.

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 by Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 1996-2020,2021 by Thomas E. Dickey
Licence: X11

Files: doc/html/NCURSES-Programming-HOWTO.html
Copyright: 2001 by Pradeep Padala
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software
is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files:
install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Files: progs/tset.c ncurses/tinfo/read_termcap.c
Copyright: 1980,1991,1992,1993 The Regents of the University of California.
License: BSD

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list

of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

-- vile: txtmode file-encoding=utf-8
Copyright 2018-2020,2021 Thomas E. Dickey
Copyright 1998-2017,2018 Free Software Foundation, Inc.

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

-- vile:txtmode fc=72
-- $Id: COPYING,v 1.10 2021/01/01 09:54:30 tom Exp $
Upstream source https://invisible-island.net/ncurses/Ada95.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 by Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2010-2020,2021 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included

in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a

copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except
as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-
ings in this Software without prior written authorization from the X Consor-
tium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent
`make' implicit rules from creating a file called install from it
when there is no Makefile.

This script is compatible with the BSD install script, but was written
from scratch. It can only install one file at a time, a restriction
shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source https://invisible-island.net/ncurses/ncurses-examples.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package

Copyright: 2003-2020,2021 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-

TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent `make' implicit rules from creating a file called install from it when there is no Makefile.

This script is compatible with the BSD install script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's install programs.

On Debian systems, the complete text of the GNU General Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8

1.84 libksba 1.5.1-7.el9

1.84.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To
"modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate
Legal Notices"
to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than
the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing
those activities but
which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited

permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content,
constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal
Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep
intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License,

in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object

code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute
modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information
does not include a
requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for

unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently

reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time
you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not
impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims

owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is

conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of

warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea
of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY
NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

 You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

 The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But first,
 please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
                GNU LESSER GENERAL PUBLIC LICENSE
                  Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

 This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

 0. Additional Definitions.

 As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

 "The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

 An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by
 the Library is deemed a mode
of using an interface provided by the Library.

 A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters,
data structure
layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation

Information in the manner specified by section 6 of the GNU GPL
for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the
Library side by side in a single library together with other library
facilities that are not Applications and are not covered by this
License, and convey such a combined
library under terms of your
choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based
on the Library, uncombined with any other library facilities,
conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it
is a work based on the Library, and explaining where to find the
accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions
of the GNU Lesser General Public License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the
Library as you received it specifies that a certain numbered version
of the GNU Lesser General Public License "or any later version"
applies to it, you have the option
of following the terms and
conditions either of that published version or of any later version
published by the Free Software Foundation. If the Library as you
received it does not specify a version number of the GNU Lesser
General Public License, you may choose any version of the GNU Lesser
General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide
whether future versions of the GNU Lesser General Public License shall
apply, that proxy's public statement of acceptance of any version is
permanent authorization for you to choose that version for the
Library.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free

program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause

any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the

Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if

necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
KSBA is distributed under mixed GPL and LGPL licenses. Please see the
file AUTHOR for details. The text of the used licenses can be found in
the files:

COPYING.LGPLv3
COPYING.GPLv3
COPYING.GPLv2

1.85 open-ldap 2.6.8-4.el9

1.85.1 Available under license :

Copyright 2011-2021 Howard Chu, Symas Corp.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted only as authorized by the OpenLDAP
Public License.

A copy of this license is available in the file LICENSE in the
top-level directory of the distribution or, alternatively, at
<http://www.OpenLDAP.org/license.html>.

OpenLDAP is a registered trademark of the OpenLDAP Foundation.

Individual files and/or contributed packages may be copyright by
other parties and/or subject to additional restrictions.

This work also contains materials derived from public sources.

Additional information about OpenLDAP can be obtained at
<http://www.openldap.org/>.
OpenLDAP Public License

The OpenLDAP Public License
Version 2.8.1, 25 November 2003

Redistribution and use of this software and associated documentation
("Software"), with or without modification, are permitted provided
that the following conditions are met:

1. Redistributions in source form must retain copyright statements
and notices,

2. Redistributions in binary form must reproduce applicable copyright
statements and notices, this list of conditions, and the following
disclaimer in the documentation and/or other materials provided
with the distribution, and

3. Redistributions must contain a verbatim copy of this document.

The OpenLDAP Foundation may revise this license from time to time.
Each revision is distinguished by a version number. You may use
this Software under terms of this license revision or under the
terms of any subsequent revision of the license.

THIS SOFTWARE IS PROVIDED BY THE OPENLDAP FOUNDATION AND ITS
CONTRIBUTORS ``AS IS'' AND ANY EXPRESSED
OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
SHALL THE OPENLDAP FOUNDATION, ITS CONTRIBUTORS, OR THE AUTHOR(S)
OR OWNER(S) OF THE SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

The names of the authors and copyright holders must not be used in
advertising or otherwise to promote the sale, use or other dealing
in this Software without specific, written prior permission. Title
to copyright in this Software shall at all times remain with copyright
holders.

OpenLDAP
is a registered trademark of the OpenLDAP Foundation.

Copyright 1999-2003 The OpenLDAP Foundation, Redwood City,
California, USA. All rights reserved. Permission to copy and

distribute verbatim copies of this document is granted.
/***
*
* Copyright (C) 2000 Pierangelo Masarati, <ando@sys-net.it>
* All rights reserved.
*
* Permission is granted to anyone to use this software for any purpose
* on any computer system, and to alter it and redistribute it, subject
* to the following restrictions:
*
* 1. The author is not responsible for the consequences of use of this
* software, no matter how awful, even if they arise from flaws in it.
*
* 2. The origin of this software must not be misrepresented, either by
* explicit claim or by omission. Since few users ever read sources,
* credits should appear in the documentation.
*
* 3. Altered versions must be plainly marked as such, and must not be
* misrepresented as being the original software. Since few users
* ever read sources, credits should appear in the documentation.
*
* 4. This notice may not be removed or altered.
*
***/
Copyright 1998-2024 The OpenLDAP Foundation. All rights reserved.

COPYING RESTRICTIONS APPLY.

See COPYRIGHT and LICENSE files in the top-level directory of this
distribution (i.e., ../../COPYRIGHT and ../../LICENSE, respectively).
Copyright 1998-2024 The OpenLDAP Foundation. All rights reserved.

COPYING RESTRICTIONS APPLY.

See COPYRIGHT and LICENSE files in the top-level directory of this
distribution (i.e., ../../COPYRIGHT and ../../LICENSE, respectively).

NeoSoft Tcl client extensions to Lightweight Directory Access Protocol.

Copyright (c) 1998-1999 NeoSoft, Inc.
All Rights Reserved.

This software may be used, modified, copied, distributed, and sold,
in both source and binary form provided that these copyrights are
retained and their terms are followed.

Under no circumstances are the authors or NeoSoft Inc. responsible

for the proper functioning of this software, nor do the authors
assume any liability for damages incurred with its use.

Redistribution and use in source and binary forms are permitted
provided that this notice is preserved and that due credit is given
to NeoSoft, Inc.

NeoSoft, Inc. may not be used to endorse or promote products derived
from this software without specific prior written
permission. This
software is provided ``as is'' without express or implied warranty.

Requests for permission may be sent to NeoSoft Inc, 1770 St. James Place,
Suite 500, Houston, TX, 77056.
Copyright 1998-2024 The OpenLDAP Foundation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted only as authorized by the OpenLDAP
Public License.

A copy of this license is available in the file LICENSE in the
top-level directory of the distribution or, alternatively, at
<http://www.OpenLDAP.org/license.html>.

OpenLDAP is a registered trademark of the OpenLDAP Foundation.

Individual files and/or contributed packages may be copyright by
other parties and/or subject to additional restrictions.

This work is derived from the University of Michigan LDAP v3.3
distribution. Information concerning this software is available
at <http://www.umich.edu/~dirsvcs/ldap/ldap.html>.

This work also contains materials derived from public sources.

Additional information about OpenLDAP can be obtained at
<http://www.openldap.org/>.

Portions Copyright 1998-2013 Kurt D. Zeilenga.
Portions Copyright 1998-2006 Net Boolean Incorporated.
Portions
 Copyright 2001-2006 IBM Corporation.
All rights reserved.

Redistribution and use in source and binary forms, with or without

modification, are permitted only as authorized by the OpenLDAP
Public License.

Portions Copyright 1999-2008 Howard Y.H. Chu.
Portions Copyright 1999-2008 Symas Corporation.
Portions Copyright 1998-2003 Hallvard B. Furuseth.
Portions Copyright 2007-2011 Gavin Henry.
Portions Copyright 2007-2011 Suretec Systems Ltd.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that this notice is preserved.
The names of the copyright holders may not be used to endorse or
promote products derived from this software without their specific
prior written permission. This software is provided ``as is''
without express or implied warranty.

Portions Copyright (c) 1992-1996 Regents of the University of Michigan.
All rights reserved.

Redistribution and use in source and binary forms are
 permitted
provided that this notice is preserved and that due credit is given
to the University of Michigan at Ann Arbor. The name of the
University may not be used to endorse or promote products derived
from this software without specific prior written permission. This
software is provided ``as is'' without express or implied warranty.
The OpenLDAP Public License
 Version 2.8, 17 August 2003

Redistribution and use of this software and associated documentation
("Software"), with or without modification, are permitted provided
that the following conditions are met:

1. Redistributions in source form must retain copyright statements
  and notices,

2. Redistributions in binary form must reproduce applicable copyright
  statements and notices, this list of conditions, and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution, and

3. Redistributions must contain a verbatim copy of this document.

The OpenLDAP Foundation may revise this license from time to time.
Each revision is distinguished by a version number. You may use
this Software under terms of this license revision or under the
terms of any subsequent revision of the license.

THIS SOFTWARE IS PROVIDED BY THE OPENLDAP FOUNDATION AND ITS
CONTRIBUTORS ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES,
INCLUDING,
 BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
SHALL THE OPENLDAP FOUNDATION, ITS CONTRIBUTORS, OR THE AUTHOR(S)
OR OWNER(S) OF THE SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

The names of the authors and copyright holders must not be used in
advertising or otherwise to promote the sale, use or other dealing
in this Software without specific, written prior permission. Title
to copyright in this Software shall at all times remain with copyright
holders.

OpenLDAP is a registered trademark
 of the OpenLDAP Foundation.

Copyright 1999-2003 The OpenLDAP Foundation, Redwood City,
California, USA. All Rights Reserved. Permission to copy and
distribute verbatim copies of this document is granted.

1.86 crypto-policies 20250905-1.git377cc42.el9_7

1.86.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts

as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest
you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients
all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original

author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU

operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without
limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does

and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves,

then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to
a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed
under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot

use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues),

conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people
have made
generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public
License from time to time.
Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and

conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of
all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL
DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
"copyright" line
and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should
also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.87 rpm 4.16.1.3-39.el9

1.87.1 Available under license :

RPM is covered under two separate licenses.

The entire code base may be distributed under the terms of the GNU General
Public License (GPL), which appears immediately below. Alternatively,
all of the source code in the lib and rpmio subdirectories of the RPM source

code distribution as well as any code derived from that code may instead be
distributed under the GNU Library General Public License (LGPL), at the
choice of the distributor. The complete text of the LGPL appears
at the bottom of this file.

This alternative is provided to enable applications to be linked against
the RPM library (commonly called librpm) without forcing such applications
to be distributed under the GPL.

Any questions regarding the licensing of RPM should be addressed to
rpm-maint@lists.rpm.org

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive
source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that
there is no warranty for this free
software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The
"Program", below,
refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not

compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided
under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original
licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy
both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be
a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that
version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY

FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF
ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to
Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY
WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w'
and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991
Free Software Foundation, Inc.
675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is

numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the
freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know
their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software

patents. We wish to avoid the danger that companies distributing free
software will individually obtain patent licenses, thus in effect
transforming the program into proprietary software. To prevent this,
we have made it clear that any patent must be licensed for everyone's
free use or not licensed at all.

 Most GNU software, including some
 libraries, is covered by the ordinary
GNU General Public License, which was designed for utility programs. This
license, the GNU Library General Public License, applies to certain
designated libraries. This license is quite different from the ordinary
one; be sure to read it in full, and don't assume that anything in it is
the same as in the ordinary license.

 The reason we have a separate public license for some libraries is that
they blur the distinction we usually make between modifying or adding to a
program and simply using it. Linking a program with a library, without
changing the library, is in some sense simply using the library, and is
analogous to running a utility program or application program. However, in
a textual and legal sense, the linked executable is a combined work, a
derivative of the original library, and the ordinary General Public License
treats it as such.

 Because of this blurred distinction, using the ordinary General
Public License for libraries did
 not effectively promote software
sharing, because most developers did not use the libraries. We
concluded that weaker conditions might promote sharing better.

 However, unrestricted linking of non-free programs would deprive the
users of those programs of all benefit from the free status of the
libraries themselves. This Library General Public License is intended to
permit developers of non-free programs to use free libraries, while
preserving your freedom as a user of such programs to change the free
libraries that are incorporated in them. (We have not seen how to achieve
this as regards changes in header files, but we have achieved it as regards
changes in the actual functions of the Library.) The hope is that this
will lead to faster development of free libraries.

 The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains
 code derived from the library, while the latter only
works together with the library.

 Note that it is possible for a library to be covered by the ordinary
General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which
contains a notice placed by the copyright holder or other authorized
party saying it may be distributed under the terms of this Library
General Public License (also called "this License"). Each licensee is
addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any
derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly into another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control compilation
and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether that is true depends on what
the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the
Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a

fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root
function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work.
(Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must
include the
copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

d) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the source code distributed need not include anything that is normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other
proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or

distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor to decide if he or she is willing
to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish revised and/or new
versions of the Library General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a
version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED
BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR

PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.88 kerberos 1.21.1-8.el9_6

1.88.1 Available under license :

[NOTE: MIT has only incorporated the mechglue and spnego change, and not the incremental propagation changes. The filenames are different between the Sun and MIT sources. The actual MIT filenames appear in the top-level README file. Original text of Sun's LICENSE file follows.]

Subject to the license set forth below, Sun Microsystems, Inc. donates the attached files to MIT for the purpose of including these modifications and additions in future versions of the Kerberos system.

Many of the files attached are subject to licenses issued by other entities, including OpenVision, MIT, and FundsXpress. See the individual files, and/or related Readme files, for these licenses.

In addition Sun requires that the license set forth below be incorporated into any future version of the Kerberos system which contains portions of the files attached. The following files must be listed, in the top level Readme file, as being provided subject to such license:

cmd/krb5/iprop/iprop.x
cmd/krb5/iprop/iprop_hdr.h
cmd/krb5/kadmin/server/ipropd_svc.c
cmd/krb5/kproplog/kproplog.c
cmd/krb5/slave/kpropd_rpc.c
lib/gss_mechs/mech_krb5/et/kdb5_err.c
lib/gss_mechs/mech_spnego/mech/gssapiP_spnego.h
lib/gss_mechs/mech_spnego/mech/spnego_mech.c
lib/krb5/kadm5/kadm_host_srv_names.c

lib/krb5/kdb/kdb_convert.c
lib/krb5/kdb/kdb_hdr.h
lib/krb5/kdb/kdb_log.c
lib/krb5/kdb/kdb_log.h
lib/libgss/g_accept_sec_context.c
lib/libgss/g_acquire_cred.c
lib/libgss/g_canon_name.c
lib/libgss/g_compare_name.c
lib/libgss/g_context_time.c
lib/libgss/g_delete_sec_context.c
lib/libgss/g_dsp_name.c
lib/libgss/g_dsp_status.c
lib/libgss/g_dup_name.c
lib/libgss/g_exp_sec_context.c
lib/libgss/g_export_name.c
lib/libgss/g_glue.c
lib/libgss/g_imp_name.c
lib/libgss/g_imp_sec_context.c
lib/libgss/g_init_sec_context.c
lib/libgss/g_initialize.c
lib/libgss/g_inquire_context.c
lib/libgss/g_inquire_cred.c
lib/libgss/g_inquire_names.c
lib/libgss/g_process_context.c
lib/libgss/g_rel_buffer.c
lib/libgss/g_rel_cred.c
lib/libgss/g_rel_name.c
lib/libgss/g_rel_oid_set.c
lib/libgss/g_seal.c
lib/libgss/g_sign.c
lib/libgss/g_store_cred.c
lib/libgss/g_unseal.c
lib/libgss/g_userok.c
lib/libgss/g_utils.c
lib/libgss/g_verify.c
lib/libgss/gssd_pname_to_uid.c
uts/common/gssapi/include/gssapi_err_generic.h
uts/common/gssapi/include/mechglueP.h

Sun's
License is as follows:

Copyright (c) 2004 Sun Microsystems, Inc.

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,

distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
 EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright
=========

Copyright |copy| 1985-2023 by the Massachusetts Institute of
Technology and its contributors. All rights reserved.

See :ref:`mitK5license` for additional copyright and license
information.
/* -*- mode: c; c-basic-offset: 4; indent-tabs-mode: nil -*- */
/*

 Copyright 1987 by the Student Information Processing Board
 of the Massachusetts Institute of Technology

 Permission to use, copy, modify, and distribute this software
 and its documentation for any purpose and without fee is
 hereby granted, provided that the above copyright notice
 appear in all copies and that both that copyright notice and
 this permission notice appear in supporting documentation,
 and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
 used in advertising or publicity pertaining to distribution
 of the software without specific, written prior permission.
 Furthermore if you modify this software you must label
 your software as modified software and not distribute it in such a
 fashion that it might be confused with the original M.I.T. software.
 M.I.T. and the M.I.T. S.I.P.B. make no representations about
 the suitability of this software for any purpose. It is
 provided "as
 is" without express or implied warranty.

*/
/* -*- mode: c; c-basic-offset: 4; indent-tabs-mode: nil -*- */
/*

Copyright 1987, 1989 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Furthermore if you modify this software you must label
your software as modified software and not distribute it in such a
fashion that it might be confused with the original M.I.T. software.
M.I.T. and the M.I.T. S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided
"as is" without express or implied warranty.

*/
/* -*- mode: c; c-basic-offset: 4; indent-tabs-mode: nil -*- */
/*
* Copyright (C) 1989-1994 by the Massachusetts Institute of Technology,
* Cambridge, MA, USA. All Rights Reserved.
*
* This software is being provided to you, the LICENSEE, by the
* Massachusetts Institute of Technology (M.I.T.) under the following
* license. By obtaining, using and/or copying this software, you agree
* that you have read, understood, and will comply with these terms and
* conditions:
*
* Export of this software from the United States of America may
* require a specific license from the United States Government.
* It is the responsibility of any person or organization contemplating
* export to obtain such a license before exporting.
*
* WITHIN THAT CONSTRAINT, permission to use, copy, modify and distribute
* this software and its documentation for any purpose and without fee or
* royalty is hereby granted, provided that you agree to comply with the
* following copyright notice and statements,
 including the disclaimer, and
* that the same appear on ALL copies of the software and documentation,
* including modifications that you make for internal use or for
* distribution:
*
* THIS SOFTWARE IS PROVIDED "AS IS", AND M.I.T. MAKES NO REPRESENTATIONS
* OR WARRANTIES, EXPRESS OR IMPLIED. By way of example, but not

* limitation, M.I.T. MAKES NO REPRESENTATIONS OR WARRANTIES OF
* MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF
* THE LICENSED SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY
* PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.
*
* The name of the Massachusetts Institute of Technology or M.I.T. may NOT
* be used in advertising or publicity pertaining to distribution of the
* software. Title to copyright in this software and any associated
* documentation shall at all times remain with M.I.T., and USER agrees to
* preserve same.
*
* Furthermore if you modify this software you must label
* your software as modified
 software and not distribute it in such a
* fashion that it might be confused with the original M.I.T. software.
*/
Copyright (C) 1985-2023 by the Massachusetts Institute of Technology.

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
 notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
 notice, this list of conditions and the following disclaimer in the
 documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT
 OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Downloading of this software may constitute an export of cryptographic
software from the United States of America that is subject to the
United States Export Administration Regulations (EAR), 15 CFR 730-774.
Additional laws or regulations may apply. It is the responsibility of

the person or entity contemplating export to comply with all
applicable export laws and regulations, including obtaining any
required license from the U.S. government.

The U.S. government prohibits export of encryption source code to
certain countries and individuals, including, but not limited to, the
countries of Cuba, Iran, North Korea, Sudan, Syria, and residents and
nationals of
those countries.

Documentation components of this software distribution are licensed
under a Creative Commons Attribution-ShareAlike 3.0 Unported License.
(https://creativecommons.org/licenses/by-sa/3.0/)

Individual source code files are copyright MIT, Cygnus Support,
Novell, OpenVision Technologies, Oracle, Red Hat, Sun Microsystems,
FundsXpress, and others.

Project Athena, Athena, Athena MUSE, Discuss, Hesiod, Kerberos, Moira,
and Zephyr are trademarks of the Massachusetts Institute of Technology
(MIT). No commercial use of these trademarks may be made without
prior written permission of MIT.

"Commercial use" means use of a name in a product or other for-profit
manner. It does NOT prevent a commercial firm from referring to the
MIT trademarks in order to convey information (although in doing so,
recognition of their trademark status should be given).

==========

The following copyright and permission notice applies to
the
OpenVision Kerberos Administration system located in "kadmin/create",
"kadmin/dbutil", "kadmin/passwd", "kadmin/server", "lib/kadm5", and
portions of "lib/rpc":

Copyright, OpenVision Technologies, Inc., 1993-1996, All Rights
Reserved

WARNING: Retrieving the OpenVision Kerberos Administration system
source code, as described below, indicates your acceptance of the
following terms. If you do not agree to the following terms, do
not retrieve the OpenVision Kerberos administration system.

You may freely use and distribute the Source Code and Object Code
compiled from it, with or without modification, but this Source
Code is provided to you "AS IS" EXCLUSIVE OF ANY WARRANTY,
INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY OR

FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED. IN NO EVENT WILL OPENVISION HAVE ANY LIABILITY FOR ANY LOST PROFITS, LOSS OF DATA OR COSTS OF PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES, OR FOR ANY SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THIS AGREEMENT, INCLUDING, WITHOUT LIMITATION, THOSE RESULTING FROM THE USE OF THE SOURCE CODE, OR THE FAILURE OF THE SOURCE CODE TO PERFORM, OR FOR ANY OTHER REASON.

OpenVision retains all copyrights in the donated Source Code. OpenVision also retains copyright to derivative works of the Source Code, whether created by OpenVision or by a third party. The OpenVision copyright notice must be preserved if derivative works are made based on the donated Source Code.

OpenVision Technologies, Inc. has donated this Kerberos Administration system to MIT for inclusion in the standard Kerberos 5 distribution. This donation underscores our commitment to continuing Kerberos technology development and our gratitude for the valuable work which has been performed by MIT and the Kerberos community.

==========

Portions contributed by Matt Crawford "crawdad@fnal.gov" were work performed at Fermi National Accelerator Laboratory, which is operated by Universities Research Association, Inc., under contract DE-AC02-76CHO3000 with the U.S. Department of Energy.

==========

Portions of "src/lib/crypto" have the following copyright:

Copyright (C) 1998 by the FundsXpress, INC.

All rights reserved.

Export of this software from the United States of America may require a specific license from the United States Government. It is the responsibility of any person or organization contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright

notice and
this permission notice appear in supporting documentation, and that
the name of FundsXpress. not be used in advertising or publicity
pertaining to distribution of the software without specific,
written prior permission. FundsXpress makes no representations
about the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

THIS SOFTWARE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

==========

The implementation of the AES encryption algorithm in
"src/lib/crypto/builtin/aes" has the following copyright:

Copyright (C) 1998-2013, Brian Gladman, Worcester, UK. All
rights reserved.

The redistribution and use of this software (with or without
changes) is allowed without the payment of fees
or royalties
provided that:

source code distributions include the above copyright notice,
this list of conditions and the following disclaimer;

binary distributions include the above copyright notice, this
list of conditions and the following disclaimer in their
documentation.

This software is provided 'as is' with no explicit or implied
warranties in respect of its operation, including, but not limited
to, correctness and fitness for purpose.

==========

Portions contributed by Red Hat, including the pre-authentication
plug-in framework and the NSS crypto implementation, contain the
following copyright:

Copyright (C) 2006 Red Hat, Inc.
Portions copyright (C) 2006 Massachusetts Institute of Technology
All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions

are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

* Neither the name of Red Hat, Inc., nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

==========

The bundled verto source code is subject to the following license:

Copyright 2011 Red Hat, Inc.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use, copy,
modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above
copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.

==========

The MS-KKDCP client implementation has the following copyright:

Copyright 2013,2014 Red Hat, Inc.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials
provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE
OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

==========

The implementations of GSSAPI mechglue in GSSAPI-SPNEGO in
"src/lib/gssapi", including the following files:

lib/gssapi/generic/gssapi_err_generic.et
lib/gssapi/mechglue/g_accept_sec_context.c
lib/gssapi/mechglue/g_acquire_cred.c

lib/gssapi/mechglue/g_canon_name.c
lib/gssapi/mechglue/g_compare_name.c
lib/gssapi/mechglue/g_context_time.c
lib/gssapi/mechglue/g_delete_sec_context.c
lib/gssapi/mechglue/g_dsp_name.c
lib/gssapi/mechglue/g_dsp_status.c
lib/gssapi/mechglue/g_dup_name.c
lib/gssapi/mechglue/g_exp_sec_context.c
lib/gssapi/mechglue/g_export_name.c
lib/gssapi/mechglue/g_glue.c
lib/gssapi/mechglue/g_imp_name.c
lib/gssapi/mechglue/g_imp_sec_context.c
lib/gssapi/mechglue/g_init_sec_context.c
lib/gssapi/mechglue/g_initialize.c
lib/gssapi/mechglue/g_inquire_context.c
lib/gssapi/mechglue/g_inquire_cred.c
lib/gssapi/mechglue/g_inquire_names.c
lib/gssapi/mechglue/g_process_context.c
lib/gssapi/mechglue/g_rel_buffer.c
lib/gssapi/mechglue/g_rel_cred.c
lib/gssapi/mechglue/g_rel_name.c
lib/gssapi/mechglue/g_rel_oid_set.c
lib/gssapi/mechglue/g_seal.c
lib/gssapi/mechglue/g_sign.c
lib/gssapi/mechglue/g_store_cred.c
lib/gssapi/mechglue/g_unseal.c
lib/gssapi/mechglue/g_userok.c
lib/gssapi/mechglue/g_utils.c
lib/gssapi/mechglue/g_verify.c
lib/gssapi/mechglue/gssd_pname_to_uid.c
lib/gssapi/mechglue/mglueP.h
lib/gssapi/mechglue/oid_ops.c
lib/gssapi/spnego/gssapiP_spnego.h
lib/gssapi/spnego/spnego_mech.c

and the initial implementation of incremental propagation, including
the following new or changed files:

include/iprop_hdr.h
kadmin/server/ipropd_svc.c
lib/kdb/iprop.x
lib/kdb/kdb_convert.c
lib/kdb/kdb_log.c
lib/kdb/kdb_log.h
lib/krb5/error_tables/kdb5_err.et
kprop/kpropd_rpc.c
kprop/kproplog.c

are subject to the following license:

Copyright (C) 2004 Sun Microsystems, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

==========

Kerberos V5 includes documentation and software developed at the University of California at Berkeley, which includes this copyright notice:

Copyright (C) 1983 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the University nor the names of its

contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH
DAMAGE.

==========

Portions contributed by Novell, Inc., including the LDAP database
backend, are subject to the following license:

Copyright (C) 2004-2005, Novell, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

* The copyright holder's name is not used to endorse or promote
products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR

SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

==========

Portions funded by Sandia National Laboratory and developed by the
University of Michigan's Center for Information Technology
Integration, including the PKINIT implementation, are subject to the
following
license:

COPYRIGHT (C) 2006-2007
THE REGENTS OF THE UNIVERSITY OF MICHIGAN
ALL RIGHTS RESERVED

Permission is granted to use, copy, create derivative works and
redistribute this software and such derivative works for any
purpose, so long as the name of The University of Michigan is not
used in any advertising or publicity pertaining to the use of
distribution of this software without specific, written prior
authorization. If the above copyright notice or any other
identification of the University of Michigan is included in any
copy of any portion of this software, then the disclaimer below
must also be included.

THIS SOFTWARE IS PROVIDED AS IS, WITHOUT REPRESENTATION FROM THE
UNIVERSITY OF MICHIGAN AS TO ITS FITNESS FOR ANY PURPOSE, AND
WITHOUT WARRANTY BY THE UNIVERSITY OF MICHIGAN OF ANY KIND, EITHER
EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE.
THE REGENTS OF THE UNIVERSITY OF MICHIGAN SHALL NOT BE LIABLE FOR
ANY DAMAGES, INCLUDING SPECIAL, INDIRECT, INCIDENTAL, OR
CONSEQUENTIAL DAMAGES, WITH RESPECT TO ANY CLAIM ARISING OUT OF OR
IN CONNECTION WITH THE USE OF THE SOFTWARE, EVEN IF IT HAS BEEN OR
IS HEREAFTER ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

==========

The pkcs11.h file included in the PKINIT code has the following
license:

Copyright 2006 g10 Code GmbH
Copyright 2006 Andreas Jellinghaus

This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE.

==========

Portions
contributed by Apple Inc. are subject to the following
license:

Copyright 2004-2008 Apple Inc. All Rights Reserved.

Export of this software from the United States of America may
require a specific license from the United States Government.
It is the responsibility of any person or organization
contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and
distribute this software and its documentation for any purpose and
without fee is hereby granted, provided that the above copyright
notice appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation, and that
the name of Apple Inc. not be used in advertising or publicity
pertaining to distribution of the software without specific,
written prior permission. Apple Inc. makes no representations
about the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

THIS SOFTWARE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

==========

The implementations of UTF-8 string handling in src/util/support and
src/lib/krb5/unicode are subject to the following copyright and
permission notice:

The OpenLDAP Public License
Version 2.8, 17 August 2003

Redistribution and use of this software and associated
documentation ("Software"), with or without modification, are

permitted provided that the following conditions are met:

1. Redistributions in source form must retain copyright
   statements and notices,

2. Redistributions in binary form must reproduce applicable
   copyright statements and notices, this
list of conditions, and
   the following disclaimer in the documentation and/or other
   materials provided with the distribution, and

3. Redistributions must contain a verbatim copy of this
   document.

The OpenLDAP Foundation may revise this license from time to time.
Each revision is distinguished by a version number. You may use
this Software under terms of this license revision or under the
terms of any subsequent revision of the license.

THIS SOFTWARE IS PROVIDED BY THE OPENLDAP FOUNDATION AND ITS
CONTRIBUTORS "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE OPENLDAP FOUNDATION, ITS
CONTRIBUTORS, OR THE AUTHOR(S) OR OWNER(S) OF THE SOFTWARE BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

The names of the authors and copyright holders must not be used in
advertising or otherwise to promote the sale, use or other dealing
in this Software without specific, written prior permission. Title
to copyright in this Software shall at all times remain with
copyright holders.

OpenLDAP is a registered trademark of the OpenLDAP Foundation.

Copyright 1999-2003 The OpenLDAP Foundation, Redwood City,
California, USA. All Rights Reserved. Permission to copy and
distribute verbatim copies of this document is granted.

==========

Marked test programs in src/lib/krb5/krb
have the following copyright:

Copyright (C) 2006 Kungliga Tekniska Hgskola
(Royal Institute of Technology, Stockholm, Sweden).
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. Neither the name of KTH nor the names of its contributors may
be used to endorse or promote products derived from this
software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY KTH AND ITS CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL KTH OR ITS
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

==========

The KCM Mach RPC definition file used on macOS has the following
copyright:

Copyright (C) 2009 Kungliga Tekniska Hgskola
(Royal Institute of Technology, Stockholm, Sweden).
All rights reserved.

Portions Copyright (C) 2009 Apple Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the Institute nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE INSTITUTE AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE INSTITUTE OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

==========

Portions of the RPC implementation in src/lib/rpc and src/include/gssrpc have the following copyright and permission notice:

Copyright (C) 2010, Oracle America, Inc.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright

notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. Neither the name of the "Oracle America, Inc." nor the names
of its contributors may be used to endorse or promote products
derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

==========

Copyright (C) 2006,2007,2009 NTT (Nippon Telegraph and Telephone
Corporation). All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer as the first lines of this file unmodified.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or
other materials provided
with the distribution.

THIS SOFTWARE IS PROVIDED BY NTT "AS IS" AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES

OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL NTT BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

==========

Copyright 2000 by Carnegie Mellon University

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its
documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Carnegie Mellon University not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

CARNEGIE MELLON UNIVERSITY DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL CARNEGIE MELLON UNIVERSITY BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

==========

Copyright
(C) 2002 Naval Research Laboratory (NRL/CCS)

Permission to use, copy, modify and distribute this software and its documentation is hereby granted, provided that both the copyright notice and this permission notice appear in all copies of the software, derivative works or modified versions, and any portions thereof.

NRL ALLOWS FREE USE OF THIS SOFTWARE IN ITS "AS IS" CONDITION AND DISCLAIMS ANY LIABILITY OF ANY KIND FOR ANY DAMAGES WHATSOEVER

RESULTING FROM THE USE OF THIS SOFTWARE.

==========

Copyright (C) 2022 United States Government as represented by the
Secretary of the Navy. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF
SUCH DAMAGE.

==========

Copyright (C) 1991, 1992, 1994 by Cygnus Support.

Permission to use, copy, modify, and distribute this software and
its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that copyright notice and this permission
notice appear in supporting documentation. Cygnus Support makes no
representations about the suitability of this software for any
purpose. It is provided "as is" without express or implied
warranty.

==========

Copyright (C) 2006 Secure Endpoints Inc.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use, copy,
modify,
merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS
BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

==========

Portions of the implementation of the Fortuna-like PRNG are subject to
the following notice:

Copyright (C) 2005
Marko Kreen
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

Copyright (C) 1994 by the University of Southern California

EXPORT OF THIS SOFTWARE from the United States of America may
require a specific license from the United States Government. It
is the responsibility of any person or organization
contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to copy, modify, and distribute
this software and its documentation in source and binary forms is
hereby granted, provided that any documentation or other materials
related to such distribution or use acknowledge that the software
was developed by the University of Southern California.

DISCLAIMER OF WARRANTY. THIS SOFTWARE IS PROVIDED "AS IS". The
University of Southern California MAKES NO REPRESENTATIONS OR
WARRANTIES, EXPRESS OR IMPLIED. By way of example, but not
limitation, the University of Southern California MAKES NO
REPRESENTATIONS OR WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY
PARTICULAR PURPOSE. The University of Southern California shall not
be held liable for any liability nor for any direct, indirect, or
consequential damages with respect to any claim by the user or
distributor of the ksu software.

==========

Copyright (C) 1995
The President and Fellows of Harvard University

This code is derived from software contributed to Harvard by Jeremy
Rassen.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source

code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. All advertising materials mentioning features or use of this
software must display the following acknowledgement:

This product includes software developed by the University of
California, Berkeley and its contributors.

4. Neither the name of the University nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

==========

Copyright (C) 2008 by the Massachusetts Institute of Technology.
Copyright 1995 by Richard P. Basch. All Rights Reserved.
Copyright 1995 by Lehman Brothers, Inc. All Rights Reserved.

Export of this software from the United States of America may
require a specific license from the United States Government. It
is the responsibility
of any person or organization
contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and
distribute this software and its documentation for any purpose and
without fee is hereby granted, provided that the above copyright
notice appear in all copies and that both that copyright notice and

this permission notice appear in supporting documentation, and that
the name of Richard P. Basch, Lehman Brothers and M.I.T. not be
used in advertising or publicity pertaining to distribution of the
software without specific, written prior permission. Richard P.
Basch, Lehman Brothers and M.I.T. make no representations about the
suitability of this software for any purpose. It is provided "as
is" without express or implied warranty.

==========

The following notice applies to "src/lib/krb5/krb/strptime.c" and
"src/include/k5-queue.h".

Copyright (C) 1997, 1998 The NetBSD Foundation, Inc.
All rights reserved.

This code was contributed to The NetBSD Foundation by Klaus Klein.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. All advertising materials mentioning features or use of this
software must display the following acknowledgement:

This product includes software developed by the NetBSD
Foundation, Inc. and its contributors.

4. Neither the name of The NetBSD Foundation nor the names of
its contributors may be used to endorse or promote products
derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND
CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR

CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

==========

The following notice applies to Unicode library files in "src/lib/krb5/unicode":

Copyright 1997, 1998, 1999 Computing Research Labs,
New Mexico State University

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE COMPUTING RESEARCH LAB OR
NEW MEXICO STATE UNIVERSITY BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

==========

The following notice applies to "src/util/support/strlcpy.c":

Copyright (C) 1998 Todd C. Miller "Todd.Miller@courtesan.com"

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL
WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE
AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR
CONSEQUENTIAL DAMAGES OR ANY
DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT,
NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

==========

The following notice applies to "src/util/profile/argv_parse.c" and
"src/util/profile/argv_parse.h":

Copyright 1999 by Theodore Ts'o.

Permission to use, copy, modify, and distribute this software for
any purpose with or without fee is hereby granted, provided that
the above copyright notice and this permission notice appear in all
copies. THE SOFTWARE IS PROVIDED "AS IS" AND THEODORE TS'O (THE
AUTHOR) DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN
NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER
RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION
OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. (Isn't
it sick that the U.S. culture of lawsuit-happy lawyers requires
this kind of disclaimer?)

==========

The following notice applies to SWIG-generated code in
"src/util/profile/profile_tcl.c":

Copyright (C) 1999-2000, The University of Chicago

This file may be freely redistributed without license or fee
provided this copyright message remains intact.

==========

The following notice applies to portiions of "src/lib/rpc" and
"src/include/gssrpc":

Copyright (C) 2000 The Regents of the University of Michigan. All rights reserved.

Copyright (C) 2000 Dug Song "dugsong@UMICH.EDU". All rights reserved, all wrongs reversed.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

==========

Implementations of the MD4 algorithm are subject to the following notice:

Copyright (C) 1990, RSA Data Security, Inc. All rights reserved.

License to copy and use this software is granted provided that it is identified as the "RSA Data Security, Inc. MD4 Message Digest Algorithm" in all material mentioning or referencing this software

or this function.

License is also granted to make and use derivative works provided
that such works are identified as "derived from the
RSA Data
Security, Inc. MD4 Message Digest Algorithm" in all material
mentioning or referencing the derived work.

RSA Data Security, Inc. makes no representations concerning either
the merchantability of this software or the suitability of this
software for any particular purpose. It is provided "as is"
without express or implied warranty of any kind.

These notices must be retained in any copies of any part of this
documentation and/or software.

==========

Implementations of the MD5 algorithm are subject to the following
notice:

Copyright (C) 1990, RSA Data Security, Inc. All rights reserved.

License to copy and use this software is granted provided that it
is identified as the "RSA Data Security, Inc. MD5 Message- Digest
Algorithm" in all material mentioning or referencing this software
or this function.

License is also granted to make and use derivative works provided
that
such works are identified as "derived from the RSA Data
Security, Inc. MD5 Message-Digest Algorithm" in all material
mentioning or referencing the derived work.

RSA Data Security, Inc. makes no representations concerning either
the merchantability of this software or the suitability of this
software for any particular purpose. It is provided "as is"
without express or implied warranty of any kind.

These notices must be retained in any copies of any part of this
documentation and/or software.

==========

The following notice applies to
"src/lib/crypto/crypto_tests/t_mddriver.c":

Copyright (C) 1990-2, RSA Data Security, Inc. Created 1990. All

rights reserved.

RSA Data Security, Inc. makes no representations concerning either
the merchantability of this software or the suitability of this
software for any particular purpose. It is provided "as is" without
express or implied warranty
of any kind.

These notices must be retained in any copies of any part of this
documentation and/or software.

==========

Portions of "src/lib/krb5" are subject to the following notice:

Copyright (C) 1994 CyberSAFE Corporation.
Copyright 1990,1991,2007,2008 by the Massachusetts
Institute of Technology.
All Rights Reserved.

Export of this software from the United States of America may
require a specific license from the United States Government. It
is the responsibility of any person or organization
contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and
distribute this software and its documentation for any purpose and
without fee is hereby granted, provided that the above copyright
notice appear in all copies and that both that copyright notice and
this permission notice appear in supporting
documentation, and that
the name of M.I.T. not be used in advertising or publicity
pertaining to distribution of the software without specific,
written prior permission. Furthermore if you modify this software
you must label your software as modified software and not
distribute it in such a fashion that it might be confused with the
original M.I.T. software. Neither M.I.T., the Open Computing
Security Group, nor CyberSAFE Corporation make any representations
about the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

==========

Portions contributed by PADL Software are subject to the following
license:

Copyright (c) 2011, PADL Software Pty Ltd. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions
of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

2. Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. Neither the name of PADL Software nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY PADL SOFTWARE AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL PADL SOFTWARE
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

==========

The bundled libev source code is subject to the following license:

All files in libev are Copyright (C)2007,2008,2009 Marc Alexander
Lehmann.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following

disclaimer in the
documentation and/or other materials provided
with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

Alternatively, the contents of this package may be used under the
terms of the GNU General Public License ("GPL") version 2 or
any
later version, in which case the provisions of the GPL are
applicable instead of the above. If you wish to allow the use of
your version of this package only under the terms of the GPL and
not to allow others to use your version of this file under the BSD
license, indicate your decision by deleting the provisions above
and replace them with the notice and other provisions required by
the GPL in this and the other files of this package. If you do not
delete the provisions above, a recipient may use your version of
this file under either the BSD or the GPL.

==========

Files copied from the Intel AESNI Sample Library are subject to the
following license:

Copyright (C) 2010, Intel Corporation All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source
code must retain the above
copyright notice, this list of conditions and the following
disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following

disclaimer in the documentation and/or other materials
provided with the distribution.

* Neither the name of Intel Corporation nor the names of its
contributors may be used to endorse or promote products
derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

==========

The following notice applies to
"src/ccapi/common/win/OldCC/autolock.hxx":

Copyright (C) 1998 by Danilo Almeida. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer
in the documentation and/or other materials provided
with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES

(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

==========

The following notice applies to portions of
"src/plugins/preauth/spake/edwards25519.c"
and
"src/plugins/preauth/spake/edwards25519_tables.h":

The MIT License (MIT)

Copyright (c) 2015-2016 the fiat-crypto authors (see the AUTHORS
file).

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

==========

The following notice applies to portions of
"src/plugins/preauth/spake/edwards25519.c":

Copyright (c) 2015-2016, Google Inc.

Permission to use, copy, modify, and/or distribute this software for
any purpose with or without fee is hereby granted, provided that the

above copyright notice and this permission notice appear in all
copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL
WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE
AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL
DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR
PROFITS, WHETHER IN AN ACTION OF CONTRACT,
 NEGLIGENCE OR OTHER
TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
/* -*- mode: c; c-basic-offset: 4; indent-tabs-mode: nil -*- */
/*

 Copyright 1987, 1988 by the Student Information Processing Board
 of the Massachusetts Institute of Technology

 Permission to use, copy, modify, and distribute this software
 and its documentation for any purpose and without fee is
 hereby granted, provided that the above copyright notice
 appear in all copies and that both that copyright notice and
 this permission notice appear in supporting documentation,
 and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
 used in advertising or publicity pertaining to distribution
 of the software without specific, written prior permission.
 Furthermore if you modify this software you must label
 your software as modified software and not distribute it in such a
 fashion that it might be confused with the original M.I.T. software.
 M.I.T. and the M.I.T. S.I.P.B. make no representations about
 the suitability of this software for any purpose. It is
 provided
 "as is" without express or implied warranty.

*/
.. _mitK5license:

MIT Kerberos License information
================================

.. toctree::
   :hidden:

   copyright.rst

.. include:: notice.rst

1.89 dejavu-sans-fonts 2.37-18.el9

1.89.1 Available under license :

Fonts are (c) Bitstream (see below). DejaVu changes are in public domain.
Glyphs imported from Arev fonts are (c) Tavmjong Bah (see below)

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the
designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE

FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: fonts at gnome dot org.

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font
Software, and to permit
persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT
NOT LIMITED TO ANY WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,

INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: tavmjong @ free . fr.

TeX Gyre DJV Math

Fonts are (c) Bitstream (see below). DejaVu changes are in public domain.

Math extensions done by B. Jackowski, P. Strzelczyk and P. Pianowski (on behalf of TeX users groups) are in public domain.

Letters
imported from Euler Fraktur from AMSfonts are (c) American Mathematical Society (see below).
Bitstream Vera Fonts Copyright
Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license (Fonts) and associated documentation
files (the Font Software), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute,
and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be
included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional
glyphs
or characters may be added to the Fonts, only if the fonts are renamed
to names not containing either the words Bitstream or the word Vera.

This License becomes null and void to the extent applicable to Fonts or

Font Software
that has been modified and is distributed under the Bitstream Vera
names.

The Font Software may be sold as part of a larger software package but
no copy
of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION
BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO
USE
THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.
Except as contained in this notice, the names of GNOME, the GNOME
Foundation,
and Bitstream Inc., shall not be used in advertising or otherwise to promote
the sale, use or other dealings in this Font Software without prior written
authorization from the GNOME Foundation or Bitstream Inc., respectively.
For further information, contact: fonts at gnome dot org.

AMSFonts (v. 2.2) copyright

The PostScript Type 1 implementation of the AMSFonts produced by and
previously distributed by Blue Sky Research and Y&Y, Inc. are now freely
available for general use. This has been accomplished through the
cooperation
of a consortium of scientific publishers with Blue Sky Research and Y&Y.
Members of this consortium include:

Elsevier Science IBM Corporation Society for Industrial and Applied Mathematics (SIAM) Springer-Verlag American Mathematical Society (AMS)

In order to assure the authenticity of these fonts, copyright will be
held
by
the American Mathematical Society. This is not meant to restrict in any way
the legitimate use of the fonts, such as (but not limited to) electronic
distribution of documents containing these fonts, inclusion of these fonts
into other public domain or commercial font collections or computer
applications, use of the outline data to create derivative fonts and/or
faces, etc. However, the AMS does require that the AMS copyright notice be

removed from any derivative versions of the fonts which have been altered in any way. In addition, to ensure the fidelity of TeX documents using Computer Modern fonts, Professor Donald Knuth, creator of the Computer Modern faces, has requested that any alterations which yield different font metrics be given a different name.

Id

1.90 redhatrelease 9.7-0.7.el9

1.90.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the

source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt

otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made

generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.
The accompanying Red Hat Enterprise Linux @@VERSION@@ release includes
copyrighted software that is licensed under the GNU General Public
License and other licenses. You may obtain the complete
machine-readable source code corresponding to portions of this release
by sending a check or money order in the amount of US $5.00 to:

VP, Legal - Products & Technologies
Red Hat, Inc.
100 East Davie Street
Raleigh, NC 27601 USA

Please write "source for RHEL @@VERSION@@" in the memo line of your
payment.

This offer is valid to anyone in receipt of this information and shall
expire three years following the date of the final distribution of
this release by Red Hat, Inc.

END USER LICENSE AGREEMENT
RED HAT(R) ENTERPRISE LINUX(R) AND RED HAT APPLICATIONS

This end user license agreement ("EULA") governs the use of any Red Hat software application that includes or refers to this license and any related updates, source code, appearance, structure and organization (the "Programs"), regardless of the delivery mechanism.

1. License Grant. Subject to the following terms, Red Hat, Inc. ("Red Hat") grants to you a perpetual, worldwide license to the Programs (each of which may include multiple software components) pursuant to the GNU General Public License v.2 (https://www.gnu.org/licenses/oldlicenses/gpl-2.0.en.html). With the exception of certain image files identified in Section 2 below, each software component is governed by a license located in the software component's source code that permits you to run, copy, modify, and redistribute (subject to certain obligations in some cases) the software component. The license rights for the binary only firmware components are located with the components themselves. This EULA pertains solely to the Programs and does not limit your rights under, or grant you rights that supersede, the license terms of any particular component.

2. Intellectual Property Rights. The Programs and each of their components are owned by Red Hat and other licensors and are protected under copyright law and other laws as applicable. Title to the Programs and any component, or to any copy or modification shall remain with Red Hat and other licensors, subject to the applicable license. The "Red Hat" mark, the individual Program marks, and the "Red Hat" logo are trademarks or registered trademarks of Red Hat and its affiliates in the U.S. and other countries. This EULA does not permit you to distribute the Programs using Red Hat's trademarks, regardless of whether the Programs have been modified. You may make a commercial redistribution of the Programs only if (a) permitted under a separate written agreement with Red Hat authorizing such commercial redistribution or (b) you remove and replace all occurrences of Red Hat trademarks and logos. Modifications to the software may corrupt the Programs. You should read the information found at http://www.redhat.com/about/corporate/trademark/ before distributing a copy of the Programs.

3. Limited Warranty. Except as specifically stated in this Section 3,

a separate agreement with Red Hat, or a license for a particular component, to the maximum extent permitted under applicable law, the Programs and the components are provided and licensed "as is" without warranty of any kind, express or implied, including the implied warranties of merchantability, non-infringement or fitness for a particular purpose. Red Hat warrants that the media on which the Programs and the components are provided will be free from defects in materials and manufacture under normal use for a period of 30 days from the date of delivery to you. Neither Red Hat nor its affiliates warrant that the functions contained in the Programs will meet your requirements or that the operation of the Programs will be entirely error free, appear or perform precisely as described in the accompanying documentation, or comply with regulatory requirements. This warranty extends only to the party that purchases subscription services for the Programs from Red Hat and/or its affiliates or a Red Hat authorized distributor.

4. Limitation of Remedies and Liability. To the maximum extent permitted by applicable law, your exclusive remedy under this EULA is to return any defective media within 30 days of delivery along with a copy of your payment receipt and Red Hat, at its option, will replace it or refund the money you paid for the media. To the maximum extent permitted under applicable law, under no circumstances will Red Hat, its affiliates, any Red Hat authorized distributor, or the licensor of any component provided to you under this EULA be liable to you for any incidental or consequential damages, including lost profits or lost savings arising out of the use or inability to use the Programs or any component, even if Red Hat, its affiliates, an authorized distributor, and/or licensor has been advised of the possibility of such damages. In no event shall Red Hat's or its affiliates' liability, an authorized distributor's liability or the liability of the licensor of a component provided to you under this EULA exceed the amount that you paid to Red Hat for the media under this EULA.

5. Export Control. You understand that countries, including the U.S., may restrict the import, use, export, re-export or transfer of encryption products and other controlled materials (which may include the Programs or related technical information licensed hereunder) ("Controlled Materials"). As required by U.S. law, you represent and warrant that you: (a) understand that certain of the Controlled Materials are of U.S. origin and subject to export controls under the U.S. Export Administration Regulations (the "EAR"); (b) are not located in (or owned or controlled by any person or entity located in) any country listed in Country Group

E:1 in Supplement No. 1 to part 740 of the EAR; or by any person or entity listed on the U.S. Department of Treasury Office of Foreign Assets Control ("OFAC") list of Specially Designated Nationals and Blocked Persons ("SDNs") (and are not 50% or more owned or controlled by any one or more persons or entities identified on the SDN list); (c) will not export, re-export or transfer the Controlled Materials to (1) any prohibited destination, (2) anyone who has been prohibited from participating in U.S. export transactions by any federal agency of the U.S. government or (3) any end user who you know or have reason to know will use them in the design, development or production of nuclear, chemical or biological weapons, or rocket systems, space launch vehicles, or sounding rockets, or unmanned air vehicle systems or any other prohibited use under the EAR; and (d) understand and agree that if you are in the United States and export, re-export or transfer the Controlled Materials to eligible end users, you will, to the extent required by EAR Section 740.17(e), submit semi-annual reports to the U.S. Commerce Department's Bureau of Industry and Security, that include the name and address (including country) of each transferee.

6. Third Party Software. The Programs may be provided with third party software that are not part of the Programs. These third party software are not required to run the Programs, are provided as a convenience to you, and are subject to their own license terms. The license terms either accompany the third party software or can be viewed at http://www.redhat.com/licenses/thirdparty/eula.html. If you do not agree to abide by the applicable license terms for the third party software, then you may not install them. If you wish to install the third party software on more than one system or transfer the third party software to another party, then you must contact the licensor of the applicable third party software.

7. General. If any provision of this EULA is held to be unenforceable, the enforceability of the remaining provisions shall not be affected. Any claim, controversy or dispute arising under or relating to this EULA shall be governed by the laws of the State of New York and of the United States, without regard to any conflict of laws provisions. The rights and obligations of the parties to this EULA shall not be governed by the United Nations Convention on the International Sale of Goods.

Copyright (C) 2019 Red Hat, Inc. All rights reserved. The Program marks, "Red Hat" mark and the Red Hat logo are trademarks or registered trademarks of Red Hat, Inc. All other trademarks are the property of their respective owners.

1.91 openssl-fips-provider 3.0.7-8.el9

1.91.1 Available under license :

This software is copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software; you can redistribute it and/or modify it under
the same terms as the Perl 5 programming language system itself.

Terms of the Perl programming language system itself

a) the GNU General Public License as published by the Free
  Software Foundation; either version 1, or (at your option) any
  later version, or
b) the "Artistic License"

--- The GNU General Public License, Version 1, February 1989 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

 The GNU General Public License, Version 1, February 1989

                GNU GENERAL PUBLIC LICENSE
                 Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

                     Preamble

 The license agreements of most software companies try to keep users
at the mercy of those companies. By contrast, our General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. The
General Public License applies to the Free Software Foundation's
software and to any other program whose authors commit to using it.
You can use it for your programs, too.

 When we speak of free software, we are referring to freedom, not
price. Specifically, the General Public License is designed to make
sure that you have the freedom to give away or sell copies of free
software, that you receive source code or can get it if you want it,

that you can change the software or use pieces of it in new free
programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender
the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

The precise terms and conditions
for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which
contains a notice placed by the copyright holder saying it may be
distributed under the terms of this General Public License. The
"Program", below, refers to any such program or work, and a "work based
on the Program" means either the Program or any work containing the
Program or a portion of it, either verbatim or with modifications. Each
licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source
code as you receive it, in any medium, provided that you conspicuously and
appropriately publish on each copy an appropriate copyright notice and
disclaimer of warranty; keep intact all the notices that refer to this
General Public License and to the absence of any warranty; and give any
other recipients of the
Program a copy of this General Public License
along with the Program. You may charge a fee for the physical act of

transferring a copy.

2. You may modify your copy or copies of the Program or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use
in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three years, to give any third party free (except for a nominal charge for the cost of distribution) a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the corresponding source code may be obtained. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making modifications to it. For an executable file, complete source code means all the source code for all modules it contains; but, as a special exception, it need not include source code for modules which are standard libraries that
accompany the operating system on which the executable file runs, or for standard header files or definitions files that accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the Program except as expressly provided under this General Public License. Any attempt otherwise to copy, modify, sublicense, distribute or transfer the Program is void, and will automatically terminate your rights to use the Program under this License. However, parties who have received copies, or rights to use copies, from you under this General Public License will not have their licenses terminated so long as such parties remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based on the Program) you indicate your acceptance of this license to do so, and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original
licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of the license which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to humanity, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 1, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19xx name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the
appropriate parts of the General Public License. Of course, the
commands you use may be called something other than `show w' and `show
c'; they could even be mouse-clicks or menu items--whatever suits your
program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here a sample; alter
the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (a program to direct compilers to make passes
at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

--- The Artistic License 1.0 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The Artistic License 1.0

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

- "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.
- "Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.
- "Copyright Holder" is whoever is named in the copyright or copyrights for the package.
- "You" is you, if you're thinking about copying or distributing this Package.
- "Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)
- "Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as ftp.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified
Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names,
and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6. The scripts and library files supplied as input to or produced as output

from the programs of this Package do not automatically fall under the copyright
of this Package, but belong to whomever generated them, and may be sold
commercially, and may be aggregated with this Package.

7. C or perl subroutines supplied by you and linked into this Package
shall not
be considered part of this Package.

8. The name of the Copyright Holder may not be used to endorse or promote
products derived from this software without specific prior written permission.

9. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF
MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical

transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made,

use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,

or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.92 libgpg-error 1.42-5.el9

1.92.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether

gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work
which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim

copies of the Program's
source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably
considered independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest

your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy

the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.
Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free
redistribution of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any

patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE

LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands
`show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it
becomes a de-facto standard. To achieve this, non-free programs must
be allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting the
free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those

sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the
work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable "work that
uses the Library", as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (1) uses at run time a
copy of the library already present on the user's computer system,
rather than copying library functions into the executable, and (2)
will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least
three years, to give the same user the materials specified in
Subsection 6a, above, for a charge no more than the cost of
performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you

distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or

otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and

conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will
be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE
LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source file to most
effectively
convey the exclusion of warranty; and each file should
have at least the "copyright" line and a pointer to where the full
notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.93 audit 3.1.5-7.el9

1.93.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors
who decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide

complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.
^L
Finally,
software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore
permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to

encourage the widest possible use of a certain library, so that it
becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains code derived from the library, whereas the latter must
be combined with the library
in order to run.
^L
GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other
program which contains a notice placed by the copyright holder or
other authorized party saying it may be distributed under the terms of
this Lesser General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly

into another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control
compilation
and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether that is true depends on what the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's
complete source code as you receive it,
in any medium, provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the
Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a
fee.

2. You may modify your copy or copies of the Library or any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no
charge to all third parties under
the terms of this License.

d) If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility

is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and
can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms
of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6,

whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything
that is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.
^L
7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined
with any other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited

by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License
may add an explicit geographical distribution limitation excluding those
countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

13. The Free Software Foundation
may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.
^L
14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for
this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS

PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with

the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data

prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the

ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object

file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at

least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your

rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE

LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or
executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not

compelled to copy the
source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution
of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY

FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.94 libnghttp2 1.43.0-6.el9

1.94.1 Available under license :

LEGAL NOTICE INFORMATION

All the files in this distribution are covered under the MIT license
(see the file LICENSE) except some files mentioned below:
Copyright (c) 2020 mruby developers

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
The MIT License

Copyright (c) 2012, 2014, 2015, 2016 Tatsuhiro Tsujikawa
Copyright (c) 2012, 2014, 2015, 2016 nghttp2 contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
set yrange [0:]
set terminal pngcairo font 'Sans, 8' lw 1 size 1400,1024
set xtics rotate by -45
set style histogram errorbars gap 2 lw 1
set style fill solid border -1

If not otherwise noted, the extensions in this package are licensed
under the following license.

Copyright (c) 2010 by the contributors (see AUTHORS file).
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
 notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
 notice, this list of conditions and the following disclaimer in the
 documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL,
 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.95 langpacks-core-font-en 3.0-16.el9

1.95.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

Name: langpacks

Found in path(s):
* /langpacks-3.0-16.el9-1.src.rpm-cosi-expand-archive-zF6UNqmj/langpacks.spec

1.96 sed 4.8-9.el9

1.96.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1)
assert copyright on the software, and (2) offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all

the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts,

regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and

only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of

that material) supplement the terms of this License with terms:

a) Disclaiming warranty
or limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an

organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone

to copy, free of charge and under the terms of this
License, through a
publicly available network server or other readily accessible means,
then you must either (1) cause the Corresponding Source to be so
available, or (2) arrange to deprive yourself of the benefit of the
patent license for this particular work, or (3) arrange, in a manner
consistent with the requirements of this License, to extend the patent
license to downstream recipients. "Knowingly relying" means you have
actual knowledge that, but for the patent license, your conveying the
covered work in a country, or your recipient's use of the covered work
in a country, would infringe one or more identifiable patents in that
country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or
arrangement, you convey, or propagate by procuring conveyance of, a
covered work, and grant a patent license to some of the parties
receiving the covered work authorizing them to use, propagate, modify
or convey a specific copy of the covered
work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying
the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY

APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/philosophy/why-not-lgpl.html>.

1.97 gdbm-libs 1:1.23-1.el9

1.97.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007, 2011 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1) assert copyright on the software, and (2)
offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains
that there is no warranty for this free software. For both users' and
authors' sake, the GPL requires that modified versions be marked as
changed, so that their problems will not be attributed erroneously to
authors of previous versions.

Some devices are designed to deny users access to install or run

modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays
"Appropriate Legal Notices"
to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything,
other
than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing
those activities but
which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically

linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content,
constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users'
Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention

is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to

copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the
object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and
execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install

modified object code on the User Product (for example, the work has
been installed in ROM).

The requirement to provide Installation Information
does not include a
requirement to continue to provide support service, warranty, or updates
for a work that has been modified or installed by the recipient, or for
the User Product in which it has been modified or installed. Access to a
network may be denied when the modification itself materially and
adversely affects the operation of the network or violates the rules and
protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided,
in accord with this section must be in a format that is publicly
documented (and with an implementation available to the public in
source code form), and must require no special password or key for
unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this
License by making exceptions from one or more of its conditions.
Additional permissions that are applicable to the entire Program shall
be treated as though they were included
in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the
terms of sections
15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on
those licensors and authors.

All other non-permissive
additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above requirements apply either way.

8. Termination.

You
may not propagate or modify a covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your
license from a particular copyright holder is reinstated (a)

provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have

actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this
License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you have the
option of following the terms and conditions
either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED,
INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer
of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief
idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the

GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes
with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But
first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.98 alternatives 1.24-2.el9

1.98.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your

freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively

when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is

allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

1.99 json-glib 1.6.6-1.el9

1.99.1 Available under license :

Creative Commons Legal Code

CC0 1.0 Universal CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons") that the public can reliably and without fear of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1.
Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;

ii. moral rights retained by the original author(s) and/or performer(s);

iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;

iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;

v. rights protecting the extraction, dissemination, use and reuse of data in a Work;

vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive);
and

vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment
of Affirmer's
heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver

shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future
medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.

b. Affirmer offers the Work as-is and makes no representations
or warranties
of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.

c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.

d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies

of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest
you first think carefully about whether
this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients
all the rights that we gave
you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that

there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free

programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without
limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from

such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If

identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves,
then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to
a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed
under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the

source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables
containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the

copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people
have made
generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License
from time to time.
Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of
all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL
DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that

everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms of the
ordinary General Public License).

 To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
"copyright" line and
 a pointer to where the full notice is found.

  <one line to give the library's name and a brief idea of what it does.>
  Copyright (C) <year> <name of author>

  This library is free software; you can redistribute it and/or
  modify it under the terms of the GNU Lesser General Public
  License as published by the Free Software Foundation; either
  version 2.1 of the License, or (at your option) any later version.

  This library is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this library; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also
 get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the
 library `Frob' (a library for tweaking knobs) written by James Random Hacker.

 <signature of Ty Coon>, 1 April 1990
 Ty Coon, President of Vice

That's all there is to it!
Copyright 2019 Red Hat, Inc.,
with Reserved Font Name Red Hat.

This Font Software is licensed under the SIL Open Font License, Version 1.1.
This license is copied below, and is also available with a FAQ at:
http://scripts.sil.org/OFL

SIL OPEN FONT LICENSE Version 1.1 - 26 February 2007

PREAMBLE
The goals of the Open Font License (OFL) are to stimulate worldwide development of collaborative font projects, to support the font creation efforts of academic and linguistic communities, and to provide a free and open framework in which fonts may be shared and improved in partnership with others.

The OFL allows the licensed fonts to be used, studied, modified and redistributed freely as long as they are not sold by themselves. The fonts, including any derivative works, can be bundled, embedded, redistributed and/or sold with any software provided that any reserved names
are not used by derivative works. The fonts and derivatives, however, cannot be released under any other type of license. The requirement for fonts to remain under this license does not apply to any document created using the fonts or their derivatives.

DEFINITIONS
"Font Software" refers to the set of files released by the Copyright Holder(s) under this license and clearly marked as such. This may include source files, build scripts and documentation.

"Reserved Font Name" refers to any names specified as such after the copyright statement(s).

"Original Version" refers to the collection of Font Software components as distributed by the Copyright Holder(s).

"Modified Version" refers to any derivative made by adding to, deleting, or substituting -- in part or in whole -- any of the components of the Original Version, by changing formats or by porting the Font Software to a new environment.

"Author" refers to any designer, engineer, programmer, technical writer or other person who contributed
to the Font Software.

PERMISSION & CONDITIONS
Permission is hereby granted, free of charge, to any person obtaining a copy of the Font Software, to use, study, copy, merge, embed, modify, redistribute, and sell modified and unmodified copies of the Font Software, subject to the following conditions:

1) Neither the Font Software nor any of its individual components,
in Original or Modified Versions, may be sold by itself.

2) Original or Modified Versions of the Font Software may be bundled,
redistributed and/or sold with any software, provided that each copy
contains the above copyright notice and this license. These can be
included either as stand-alone text files, human-readable headers or
in the appropriate machine-readable metadata fields within text or
binary files as long as those fields can be easily viewed by the user.

3) No Modified Version of the Font Software may use the Reserved Font
Name(s) unless explicit written permission is granted by the corresponding
Copyright
Holder. This restriction only applies to the primary font name as
presented to the users.

4) The name(s) of the Copyright Holder(s) or the Author(s) of the Font
Software shall not be used to promote, endorse or advertise any
Modified Version, except to acknowledge the contribution(s) of the
Copyright Holder(s) and the Author(s) or with their explicit written
permission.

5) The Font Software, modified or unmodified, in part or in whole,
must be distributed entirely under this license, and must not be
distributed under any other license. The requirement for fonts to
remain under this license does not apply to any document created
using the Font Software.

TERMINATION
This license becomes null and void if any of the above conditions are
not met.

DISCLAIMER
THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT
OF COPYRIGHT, PATENT,
TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL THE
COPYRIGHT HOLDER BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL
DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM
OTHER DEALINGS IN THE FONT SOFTWARE.
Creative Commons Legal Code

Attribution-ShareAlike 3.0 Unported

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE

LEGAL SERVICES. DISTRIBUTION OF THIS LICENSE DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE INFORMATION PROVIDED, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM ITS USE.

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. TO THE EXTENT THIS LICENSE MAY BE CONSIDERED TO BE A CONTRACT, THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions

a. "Adaptation" means a work based upon the Work, or upon the Work and other pre-existing works, such as a translation, adaptation, derivative work, arrangement of music or other alterations of a literary or artistic work, or phonogram or performance and includes cinematographic adaptations or any other form in which the Work may be recast, transformed, or adapted including in any form recognizably derived from the original, except that a work that constitutes a Collection will not be considered an Adaptation for the purpose of this License. For the avoidance of doubt, where the Work is a musical work, performance or phonogram, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered an Adaptation for the purpose of this License.
b. "Collection" means a collection of literary or artistic works, such as encyclopedias and anthologies, or performances, phonograms or broadcasts, or other works or subject matter other than works listed in Section 1(f) below, which, by reason of the selection and arrangement of their contents, constitute intellectual creations, in which the Work is included in its entirety in unmodified form along with one or more other contributions, each constituting separate and independent works in themselves, which together are assembled into a collective whole. A work that constitutes a Collection will not be considered an Adaptation (as defined below) for the purposes of this License.
c. "Creative Commons Compatible License" means a license that is listed at https://creativecommons.org/compatiblelicenses that has been

approved by Creative Commons as being essentially equivalent to this License, including, at a minimum, because that license: (i) contains terms that have the same purpose, meaning and effect as the License Elements of this License; and,

(ii) explicitly permits the relicensing of adaptations of works made available under that license under this License or a Creative Commons jurisdiction license with the same License Elements as this License.

d. "Distribute" means to make available to the public the original and copies of the Work or Adaptation, as appropriate, through sale or other transfer of ownership.

e. "License Elements" means the following high-level license attributes as selected by Licensor and indicated in the title of this License: Attribution, ShareAlike.

f. "Licensor" means the individual, individuals, entity or entities that offer(s) the Work under the terms of this License.

g. "Original Author" means, in the case of a literary or artistic work, the individual, individuals, entity or entities who created the Work or if no individual or entity can be identified, the publisher; and in addition (i) in the case of a performance the actors, singers, musicians,

dancers, and other persons who act, sing, deliver, declaim, play in, interpret or otherwise perform literary or artistic works or expressions of folklore; (ii) in the case of a phonogram the producer being the person or legal entity who first fixes the sounds of a performance or other sounds; and, (iii) in the case of broadcasts, the organization that transmits the broadcast.

h. "Work" means the literary and/or artistic work offered under the terms of this License including without limitation any production in the literary, scientific and artistic domain, whatever may be the mode or form of its expression including digital form, such as a book, pamphlet and other writing; a lecture, address, sermon or other work of the same nature; a dramatic or dramatico-musical work; a choreographic work or entertainment in dumb show; a musical composition with or without words; a cinematographic work to which are assimilated works expressed by a

process analogous to cinematography; a work of drawing, painting, architecture, sculpture, engraving or lithography; a photographic work to which are assimilated works expressed by a process analogous to photography; a work of applied art; an illustration, map, plan, sketch or three-dimensional work relative to geography, topography, architecture or science; a performance; a broadcast; a phonogram; a compilation of data to the extent it is protected as a copyrightable work; or a work performed by a variety or circus performer to the extent it is not otherwise considered a literary or artistic work.

i. "You" means an individual or entity exercising rights under this License who has not previously violated the terms of this License with

respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.

j. "Publicly Perform" means to perform public recitations of the Work and to communicate to the public those public recitations, by any means or process, including by wire or wireless means or public digital performances; to make available to the public Works in such a way that members of the public may access these Works from a place and at a place individually chosen by them; to perform the Work to the public by any means or process and the communication to the public of the performances of the Work, including by public digital performance; to broadcast and rebroadcast the Work by any means including signs, sounds or images.

k. "Reproduce" means to make copies of the Work by any means including without limitation by sound or visual recordings and the right of fixation and reproducing fixations of the Work, including storage of a protected performance or phonogram in digital form or other electronic medium.

2. Fair Dealing Rights. Nothing in this License is intended to reduce, limit, or restrict any uses free from copyright or rights arising from limitations or exceptions that are provided for in connection with the copyright protection under copyright law or other applicable laws.

3. License Grant. Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:

a. to Reproduce the Work, to incorporate the Work into one or more Collections, and to Reproduce the Work as incorporated in the Collections;

b. to create and Reproduce Adaptations provided that any such Adaptation, including any translation in any medium, takes reasonable steps to clearly label, demarcate or otherwise identify that changes were made to the original Work. For example, a translation could be marked "The original work was translated from English to Spanish," or a modification could indicate "The original work has been modified.";

c. to Distribute and Publicly Perform the Work including as incorporated in Collections; and,

d. to Distribute and Publicly Perform Adaptations.

e. For the avoidance of doubt:

i. Non-waivable Compulsory License Schemes. In those jurisdictions in which the right to collect royalties through any statutory or

compulsory licensing scheme cannot be waived, the Licensor reserves the exclusive right to collect such royalties for any exercise by You of the rights granted under this License;

ii. Waivable Compulsory License Schemes. In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme can be waived, the Licensor waives the exclusive right to collect such royalties for any exercise by You of the rights granted under this License; and,

iii. Voluntary License Schemes. The Licensor waives the right to collect royalties, whether individually or, in the event that the Licensor is a member of a collecting society that administers voluntary licensing schemes, via that society, from any exercise by You of the rights granted under this License.

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. Subject to Section 8(f), all rights not expressly granted by Licensor are hereby reserved.

4. Restrictions. The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:

a. You may Distribute or Publicly Perform the Work only under the terms of this License. You must include a copy of, or the Uniform Resource Identifier (URI) for, this License with every copy of the Work You Distribute or Publicly Perform. You may not offer or impose any terms on the Work that restrict the terms of this License or the ability of the recipient of the Work to exercise the rights granted to that recipient under the terms of the License. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties with every copy of the Work You Distribute or Publicly Perform. When You Distribute or Publicly Perform the Work, You may not impose any effective technological measures on the Work that restrict the ability of a recipient of the Work from You to exercise the rights granted to that recipient under the terms of the License. This Section 4(a) applies to the Work as incorporated in a Collection, but this does not require the Collection apart from the Work itself to be made subject to the terms of this License. If You create a Collection, upon notice from any Licensor You must, to the extent practicable, remove from the Collection any credit as required by Section 4(c), as requested. If You create an Adaptation, upon notice from any Licensor You must, to the extent practicable, remove from the Adaptation any credit as required by Section 4(c), as requested.

b. You may Distribute or Publicly Perform an Adaptation only under the terms of: (i) this License; (ii) a later version of this License with the same License Elements as this License; (iii) a Creative Commons jurisdiction license (either this or a later license version) that contains the same License Elements as this License (e.g., Attribution-ShareAlike 3.0 US)); (iv) a Creative Commons Compatible License. If you license the Adaptation under one of the licenses mentioned in (iv), you must comply with the terms of that license. If you license the Adaptation under the terms of any of the licenses mentioned in (i), (ii) or (iii) (the "Applicable License"), you must comply with the terms of the
Applicable License generally and the following provisions: (I) You must include a copy of, or the URI for, the Applicable License with every copy of each Adaptation You Distribute or Publicly Perform; (II) You may not offer or impose any terms on the Adaptation that restrict the terms of the Applicable License or the ability of the recipient of the Adaptation to exercise the rights granted to that recipient under the terms of the Applicable License; (III) You must keep intact all notices that refer to the Applicable License and to the disclaimer of warranties with every copy of the Work as included in the Adaptation You Distribute or Publicly Perform; (IV) when You Distribute or Publicly Perform the Adaptation, You may not impose any effective technological measures on the Adaptation that restrict the ability of a recipient of the Adaptation from You to exercise the rights granted to that recipient under the terms of the Applicable
License. This Section 4(b) applies to the Adaptation as incorporated in a Collection, but this does not require the Collection apart from the Adaptation itself to be made subject to the terms of the Applicable License.

c. If You Distribute, or Publicly Perform the Work or any Adaptations or Collections, You must, unless a request has been made pursuant to Section 4(a), keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or if the Original Author and/or Licensor designate another party or parties (e.g., a sponsor institute, publishing entity, journal) for attribution ("Attribution Parties") in Licensor's copyright notice, terms of service or by other reasonable means, the name of such party or parties; (ii) the title of the Work if supplied; (iii) to the extent reasonably practicable, the URI,
if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work; and (iv) , consistent with Ssection 3(b), in the case of an Adaptation, a credit identifying the use of the Work in the Adaptation (e.g., "French translation of the Work by Original Author," or "Screenplay based on original Work by Original Author"). The credit

required by this Section 4(c) may be implemented in any reasonable manner; provided, however, that in the case of a Adaptation or Collection, at a minimum such credit will appear, if a credit for all contributing authors of the Adaptation or Collection appears, then as part of these credits and in a manner at least as prominent as the credits for the other contributing authors. For the avoidance of doubt, You may only use the credit required by this Section for the purpose of attribution in the manner set out above
and, by exercising
Your rights under this License, You may not implicitly or explicitly assert or imply any connection with, sponsorship or endorsement by the Original Author, Licensor and/or Attribution Parties, as appropriate, of You or Your use of the Work, without the separate, express prior written permission of the Original Author, Licensor and/or Attribution Parties.

d. Except as otherwise agreed in writing by the Licensor or as may be otherwise permitted by applicable law, if You Reproduce, Distribute or Publicly Perform the Work either by itself or as part of any Adaptations or Collections, You must not distort, mutilate, modify or take other derogatory action in relation to the Work which would be prejudicial to the Original Author's honor or reputation. Licensor agrees that in those jurisdictions (e.g. Japan), in which any exercise of the right granted in Section 3(b) of this License (the right to make Adaptations) would
be deemed to be a distortion, mutilation,
modification or other derogatory action prejudicial to the Original Author's honor and reputation, the Licensor will waive or not assert, as appropriate, this Section, to the fullest extent permitted by the applicable national law, to enable You to reasonably exercise Your right under Section 3(b) of this License (right to make Adaptations) but not otherwise.

5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED TO BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTIBILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES,
SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. Limitation on Liability. EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS

BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. Termination

a. This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Adaptations or Collections from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.
b. Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work).
Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous

a. Each time You Distribute or Publicly Perform the Work or a Collection, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.
b. Each time You Distribute or Publicly Perform an Adaptation, Licensor offers to the recipient a license to the original Work on the same terms and conditions as the license granted to You under this License.
c. If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.
d. No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.
e. This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You. This License may not be modified without the mutual written agreement of the Licensor and You.
f. The rights granted under, and the subject matter

referenced, in this
License were drafted utilizing the terminology of the Berne Convention
for the Protection of Literary and Artistic Works (as amended on
September 28, 1979), the Rome Convention of 1961, the WIPO Copyright
Treaty of 1996, the WIPO Performances and Phonograms Treaty of 1996
and the Universal Copyright Convention (as revised on July 24, 1971).
These rights and subject matter take effect in the relevant
jurisdiction in which the License terms are sought to be enforced
according to the corresponding provisions of the implementation of
those treaty provisions in the applicable national law. If the
standard suite of rights granted under applicable copyright law
includes additional rights not granted under this License, such
additional rights are deemed to be included in the License; this
License is not intended to restrict the license of any rights under
applicable law.

Creative Commons Notice

Creative Commons
is not a party to this License, and makes no warranty
whatsoever in connection with the Work. Creative Commons will not be
liable to You or any party on any legal theory for any damages
whatsoever, including without limitation any general, special,
incidental or consequential damages arising in connection to this
license. Notwithstanding the foregoing two (2) sentences, if Creative
Commons has expressly identified itself as the Licensor hereunder, it
shall have all rights and obligations of Licensor.

Except for the limited purpose of indicating to the public that the
Work is licensed under the CCPL, Creative Commons does not authorize
the use by either party of the trademark "Creative Commons" or any
related trademark or logo of Creative Commons without the prior
written consent of Creative Commons. Any permitted use will be in
compliance with Creative Commons' then-current trademark usage
guidelines, as may be published on its
website or otherwise made
available upon request from time to time. For the avoidance of doubt,
this trademark restriction does not form part of the License.

Creative Commons may be contacted at https://creativecommons.org/.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic

pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other

parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those

subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or

modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work,

and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)

that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in

ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or

requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have

permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS
THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

The MIT License (MIT)

Copyright (c) 2014 John Hawthorn

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.100 libidn 2.3.0-7.el9

1.100.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters,

data structure
layouts and accessors, or small macros, inline functions and templates
(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the
Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license
document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that,
taken together, effectively do not restrict modification of the
portions of the Library contained in the Combined Work and reverse
engineering for debugging such modifications, if you also do each of
the following:

a) Give prominent notice with each copy of the Combined Work that
the Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license
document.

c) For a Combined Work that
displays copyright notices during
execution, include the copyright notice for the Library among
these notices, as well as a reference directing the user to the
copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this
License, and the Corresponding Application Code in a form
suitable for, and under terms that permit, the user to
recombine or relink the Application with a modified version of
the Linked Version to produce a modified Combined Work, in the
manner specified by section 6 of the GNU GPL for conveying
Corresponding Source.

1) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (a) uses at run time
a copy of the Library already present on the user's computer
system, and (b) will operate properly with a modified version
of the Library that is interface-compatible

with the Linked
Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined
library under terms of your
choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option
of following the terms and
conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser

General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which

gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
Libidn2 COPYING -- Licensing information. -*- outline -*-
Copyright (C) 2011-2016 Simon Josefsson
See the end for copying conditions.

The source code for the C library (libidn2.a or libidn.so) are licensed under the terms of either the GNU General Public License version 2.0 or later (see the file COPYINGv2) or the GNU Lesser General Public License version 3.0 or later (see the file COPYING.LESSERv3), or both in parallel as here.

The command line tool, self tests, examples, and other auxiliary files, are licensed under the GNU General Public License version 3.0 or later.

The license of the Unicode character data files (which are parsed into static storage in the library) are documented in COPYING.unicode.

Other files are licensed as indicated in each file.

There may be exceptions to these general rules, see each file for precise information.

This file is free software: you can redistribute
it and/or modify it
under the terms of the GNU General Public License as published by the
Free Software Foundation, either version 3 of the License, or (at your
option) any later version.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this file. If not, see <http://www.gnu.org/licenses/>.
A. Unicode Copyright.

Copyright 1991-2016 Unicode, Inc. All rights reserved.

Certain documents and files on this website contain a legend indicating that "Modification is permitted." Any person is hereby authorized, without fee, to modify such documents and files to create derivative works conforming to the Unicode Standard, subject to Terms and Conditions herein.

Any person is hereby authorized, without fee, to view, use, reproduce, and distribute all documents and files solely for informational purposes and in the creation of products supporting the Unicode Standard, subject to the Terms and Conditions herein.

Further specifications of rights and restrictions pertaining to the use of the particular set of data files known as the "Unicode Character Database" can be found in the License.

Each version of the Unicode Standard has further specifications of rights and restrictions of use. For the book editions (Unicode 5.0 and earlier), these are found on the back of the
title page. The online code charts carry specific restrictions. All other files, including online documentation of the core specification for Unicode 6.0 and later, are covered under these general Terms of Use.

No license is granted to "mirror" the Unicode website where a fee is charged for access to the "mirror" site.

Modification is not permitted with respect to this document. All copies of this document must be verbatim.

B. Restricted Rights Legend.
Any technical data or software which is licensed to the United States of America, its agencies and/or instrumentalities under this Agreement is commercial technical data or commercial computer software developed exclusively at private expense as defined in FAR 2.101, or DFARS 252.227-7014 (June 1995), as applicable. For technical data, use, duplication, or disclosure by the Government is subject to restrictions as set forth in DFARS 202.227-7015 Technical Data, Commercial and Items (Nov 1995) and this Agreement. For Software,
in accordance with FAR 12-212 or DFARS 227-7202, as applicable, use, duplication or disclosure by the Government is subject to the restrictions set forth in this Agreement.

C. Warranties and Disclaimers.

This publication and/or website may include technical or typographical errors or other inaccuracies . Changes are periodically added to the information herein; these changes will be incorporated in new editions of the publication and/or website. Unicode may make improvements and/or changes in the product(s) and/or program(s) described in this publication and/or website at any time.

If this file has been purchased on magnetic or optical media from Unicode, Inc. the sole and exclusive remedy for any claim will be exchange of the defective media within ninety (90) days of original purchase.

EXCEPT AS PROVIDED IN SECTION C.2, THIS PUBLICATION AND/OR SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND EITHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING, BUT NOT LIMITED TO,
ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. UNICODE AND ITS LICENSORS ASSUME NO RESPONSIBILITY FOR ERRORS OR OMISSIONS IN THIS PUBLICATION AND/OR SOFTWARE OR OTHER DOCUMENTS WHICH ARE REFERENCED BY OR LINKED TO THIS PUBLICATION OR THE UNICODE WEBSITE.

D. Waiver of Damages.
In no event shall Unicode or its licensors be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever, whether or not Unicode was advised of the possibility of the damage, including, without limitation, those resulting from the following: loss of use, data or profits, in connection with the use, modification or distribution of this information or its derivatives.

E. Trademarks & Logos.
The Unicode Word Mark and the Unicode Logo are trademarks of Unicode, Inc. The Unicode Consortium and Unicode, Inc. are trade names of Unicode, Inc. Use of the information and materials found on this website indicates your acknowledgement
of Unicode, Inc.s exclusive worldwide rights in the Unicode Word Mark, the Unicode Logo, and the Unicode trade names.
The Unicode Consortium Name and Trademark Usage Policy (Trademark Policy) are incorporated herein by reference and you agree to abide by the provisions of the Trademark Policy, which may be changed from time to time in the sole discretion of Unicode, Inc.
All third party trademarks referenced herein are the property of their respective owners.

F. Miscellaneous.
Jurisdiction and Venue. This server is operated from a location in the State of California, United States of America. Unicode makes no representation that the materials are appropriate for use in other locations. If you access this server from other locations, you are responsible for compliance with local laws. This Agreement, all use of this site and any claims and damages resulting from use of this site are governed solely by the laws of the State of California without regard to any principles
which would apply the laws of a different jurisdiction. The user agrees that any disputes regarding this site shall be resolved solely in the courts located in Santa Clara County, California. The user agrees said courts have personal jurisdiction and agree to waive any right to transfer the dispute to any other forum.
Modification by Unicode Unicode shall have the right to modify this Agreement at any time by posting it to this site. The user may not assign any part of this Agreement without Unicodes prior written consent.
Taxes. The user agrees to pay any taxes arising from access to this website or use of the information herein, except for those based on Unicodes net income.
Severability. If any provision of this Agreement is declared invalid or unenforceable, the remaining provisions of this Agreement shall remain in effect.
Entire Agreement. This Agreement constitutes the entire agreement between the parties.

EXHIBIT 1
Unicode Data Files include all data files
under the directories
http://www.unicode.org/Public/, http://www.unicode.org/reports/,

http://www.unicode.org/cldr/data/, http://source.icu-project.org/repos/icu/, and
http://www.unicode.org/utility/trac/browser/.

Unicode Data Files do not include PDF online code charts under the
directory http://www.unicode.org/Public/.

Software includes any source code published in the Unicode Standard
or under the directories
http://www.unicode.org/Public/, http://www.unicode.org/reports/,
http://www.unicode.org/cldr/data/, http://source.icu-project.org/repos/icu/, and
http://www.unicode.org/utility/trac/browser/.

NOTICE TO USER: Carefully read the following legal agreement.
BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S
DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"),
YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE
TERMS AND CONDITIONS OF THIS AGREEMENT.
IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE
THE DATA FILES OR SOFTWARE.

COPYRIGHT
AND PERMISSION NOTICE

Copyright 1991-2016 Unicode, Inc. All rights reserved.
Distributed under the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining
a copy of the Unicode data files and any associated documentation
(the "Data Files") or Unicode software and any associated documentation
(the "Software") to deal in the Data Files or Software
without restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, and/or sell copies of
the Data Files or Software, and to permit persons to whom the Data Files
or Software are furnished to do so, provided that either
(a) this copyright and permission notice appear with all copies
of the Data Files or Software, or
(b) this copyright and permission notice appear in associated
Documentation.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF
ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED
TO THE
WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT OF THIRD PARTY RIGHTS.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS
NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL
DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE,
DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER

TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.

1.101 lua 5.4.4-4.el9

1.101.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2761148214_1762986455.8683238/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/lua-5.4.4.tar.gz-cosi-expand-archive-uI2E5jq1/lua-5.4.4/doc/contents.html<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
/opt/cola/permits/2761148214_1762986455.8683238/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/lua-5.4.4.tar.gz-cosi-expand-archive-uI2E5jq1/lua-5.4.4/doc/manual.html<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
/opt/cola/permits/2761148214_1762986455.8683238/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/lua-5.4.4.tar.gz-cosi-expand-archive-uI2E5jq1/lua-5.4.4/doc/readme.html<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
/opt/cola/permits/2761148214_1762986455.8683238/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/lua-5.4.4.tar.gz-cosi-expand-archive-uI2E5jq1/lua-5.4.4/src/lua.h/*
/opt/cola/permits/2761148214_1762986455.8683238/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/lua.spec%global
major_version 5.4
/opt/cola/permits/2761148214_1762986455.8683238/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/mit.txtCopyright (c) 1994-2013 Lua.org, PUC-Rio.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

#!../lua

Found in path(s):
* /lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-sPm7CPlk/lua-5.4.4-tests.tar.gz-cosi-expand-archive-z1tQ2KNs/lua-5.4.4-tests/all.lua

1.102 pcre 8.44-4.el9

1.102.1 Available under license :

PCRE LICENCE

Please see the file LICENCE in the PCRE distribution for licensing details.

End
PCRE LICENCE

PCRE is a library of functions to support regular expressions whose syntax
and semantics are as close as possible to those of the Perl 5 language.

Release 8 of PCRE is distributed under the terms of the "BSD" licence, as
specified below. The documentation for PCRE, supplied in the "doc"
directory, is distributed under the same terms as the software itself. The data
in the testdata directory is not copyrighted and is in the public domain.

The basic library functions are written in C and are freestanding. Also
included in the distribution is a set of C++ wrapper functions, and a
just-in-time compiler that can be used to optimize pattern matching. These
are both optional features that can be omitted when the library is built.

THE BASIC LIBRARY FUNCTIONS

Written by: Philip Hazel
Email local part: ph10
Email domain: cam.ac.uk

University of Cambridge Computing Service,
Cambridge, England.

Copyright (c) 1997-2020 University
of Cambridge
All rights reserved.

PCRE JUST-IN-TIME COMPILATION SUPPORT

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2010-2020 Zoltan Herczeg
All rights reserved.

STACK-LESS JUST-IN-TIME COMPILER

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2009-2020 Zoltan Herczeg
All rights reserved.

THE C++ WRAPPER FUNCTIONS

Contributed by: Google Inc.

Copyright (c) 2007-2012, Google Inc.
All rights reserved.

THE "BSD" LICENCE

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce
the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* Neither the name of the University of Cambridge nor the name of Google
Inc. nor the names of their contributors may be used to endorse or
promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN

CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

End
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.103 coreutils 8.32-39.el9

1.103.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,

the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2)

tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that

same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you

receive it, in any medium, provided that you conspicuously and
appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other

parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided

you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and

adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some

trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that

copyright
holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying
the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public
License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),

EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.

1.104 lua-libs 5.4.4-4.el9

1.104.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2761150957_1762986479.0500312/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/lua-5.4.4.tar.gz-cosi-expand-archive-DJyQ7hvT/lua-5.4.4/doc/contents.html<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
/opt/cola/permits/2761150957_1762986479.0500312/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/lua-5.4.4.tar.gz-cosi-expand-archive-DJyQ7hvT/lua-5.4.4/doc/manual.html<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
/opt/cola/permits/2761150957_1762986479.0500312/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/lua-5.4.4.tar.gz-cosi-expand-archive-DJyQ7hvT/lua-5.4.4/doc/readme.html<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
/opt/cola/permits/2761150957_1762986479.0500312/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/lua-5.4.4.tar.gz-cosi-expand-archive-DJyQ7hvT/lua-5.4.4/src/lua.h/*
/opt/cola/permits/2761150957_1762986479.0500312/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/lua.spec%global
major_version 5.4
/opt/cola/permits/2761150957_1762986479.0500312/0/lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/mit.txtCopyright (c) 1994-2013 Lua.org, PUC-Rio.

Found in path(s):
*

No license file was found, but licenses were detected in source scan.

#!../lua

Found in path(s):
* /lua-5.4.4-4.el9-1.src.rpm-cosi-expand-archive-uGD1stQB/lua-5.4.4-tests.tar.gz-cosi-expand-archive-WGdzZA2w/lua-5.4.4-tests/all.lua

1.105 libsemanage-common 3.6-5.el9_6

1.105.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest
you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid

distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use
the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without
limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish
on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified
Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves,
then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to
a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed
under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this
License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables
containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable
source code for the Library including whatever
changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user
installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing
the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people
have made
generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish revised and/or new
versions of the Lesser General Public
License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of
all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL
DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line
and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should

also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.106 openssl-fips-provider-so 3.0.7-8.el9

1.106.1 Available under license :

This software is copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software; you can redistribute it and/or modify it under
the same terms as the Perl 5 programming language system itself.

Terms of the Perl programming language system itself

a) the GNU General Public License as published by the Free
  Software Foundation; either version 1, or (at your option) any
  later version, or
b) the "Artistic License"

--- The GNU General Public License, Version 1, February 1989 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The GNU General Public License, Version 1, February 1989

GNU GENERAL PUBLIC LICENSE
Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The license agreements of most software companies try to keep users

at the mercy of those companies. By contrast, our General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. The General Public License applies to the Free Software Foundation's software and to any other program whose authors commit to using it. You can use it for your programs, too.

When we speak of free software, we are referring to freedom, not price. Specifically, the General Public License is designed to make sure that you have the freedom to give away or sell copies of free software, that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any work containing the

Program or a portion of it, either verbatim or with modifications. Each licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this General Public License and to the absence of any warranty; and give any other recipients of the
Program a copy of this General Public License
along with the Program. You may charge a fee for the physical act of transferring a copy.

2. You may modify your copy or copies of the Program or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive
use
in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding
machine-readable
source code, which must be distributed under the terms of
Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three
years, to give any third party free (except for a nominal charge
for the cost of distribution) a complete machine-readable copy of the
corresponding source code, to be distributed under the terms of
Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the
corresponding source code may be obtained. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making
modifications to it. For an executable file, complete source code means
all the source code for all modules it contains; but, as a special
exception, it need not include source code for modules which are standard
libraries that
accompany the operating system on which the executable
file runs, or for standard header files or definitions files that
accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the
Program except as expressly provided under this General Public License.
Any attempt otherwise to copy, modify, sublicense, distribute or transfer
the Program is void, and will automatically terminate your rights to use
the Program under this License. However, parties who have received
copies, or rights to use copies, from you under this General Public
License will not have their licenses terminated so long as such parties
remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based
on the Program) you indicate your acceptance of this license to do so,
and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the
Program), the recipient automatically receives a license from the
original
licensor to copy, distribute or modify the Program subject to these
terms and conditions. You may not impose any further restrictions on the
recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will

be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of the license which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest

possible use to humanity, the best way to achieve this is to make it
free software which everyone can redistribute and change under these
terms.

To do so,
attach the following notices to the program. It is safest to
attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 1, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19xx name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the
appropriate parts of the General Public License. Of course, the
commands you use may be called something other than `show w' and `show
c'; they could even be mouse-clicks or menu items--whatever suits your
program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here a sample; alter

the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (a program to direct compilers to make passes
at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

--- The Artistic License 1.0 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The Artistic License 1.0

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package
may be copied, such that the Copyright Holder maintains some semblance of
artistic control over the development of the package, while giving the users of
the package the right to use and distribute the Package in a more-or-less
customary fashion, plus the right to make reasonable modifications.

Definitions:

- "Package" refers to the collection of files distributed by the Copyright
  Holder, and derivatives of that collection
of files created through
  textual modification.
- "Standard Version" refers to such a Package if it has not been modified,
  or has been modified in accordance with the wishes of the Copyright
  Holder.
- "Copyright Holder" is whoever is named in the copyright or copyrights for
  the package.
- "You" is you, if you're thinking about copying or distributing this Package.
- "Reasonable copying fee" is whatever you can justify on the basis of media
  cost, duplication charges, time of people involved, and so on. (You will
  not be required to justify it to the Copyright Holder, but only to the
  computing community at large as a market that must bear the fee.)
- "Freely Available" means that no fee is charged for the item itself, though
  there may be fees involved in handling the item. It also means that

recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as ftp.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names, and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package.

7. C or perl subroutines supplied by you and linked into this Package shall not
be considered part of this Package.

8. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

9. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the

outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed

as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.107 libmodulemd 2.13.0-2.el9

1.107.1 Available under license :

MIT License

Copyright (c) 2017-2018 Stephen Gallagher <sgallagh@redhat.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.108 librepo 1.14.5-3.el9

1.108.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source

code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into

another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that,

in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of

the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these

materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if

you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR

CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.109 audit-lib 3.1.5-7.el9

1.109.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors
who decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.
^L
Finally,
software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore
permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library
in order to run.
^L
GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data

prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices

stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under
the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and
can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms
of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2,

instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the
complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a
"work that uses the
library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline

functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute
the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything
that is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.
^L
7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined
with any other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or

distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited
by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License,
they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software
distribution system which is
implemented by public license practices. Many people have made

generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.
^L
14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS
PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source
file to most
effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper
mail.

You should also get your employer (if you work as a programmer) or
your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into
another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion

of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under

the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a

derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a

copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it

in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered

independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or
executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary

form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then

the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free

Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,

or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.110 libunistring 0.9.10-15.el9

1.110.1 Available under license :

@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
 must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that

contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The ``Document'', below, refers
to any such manual or work. Any member of the public is a licensee, and is addressed as ``you''. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A ``Modified Version'' of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political
position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for
images composed of
pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file

format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain @sc{ascii} without markup, Texinfo input format, La@TeX{} input format, @acronym{SGML} or @acronym{XML} using a publicly available @acronym{DTD}, and standard-conforming simple @acronym{HTML}, PostScript or @acronym{PDF} designed for human modification. Examples of transparent image formats include @acronym{PNG}, @acronym{XCF} and @acronym{JPG}. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, @acronym{SGML} or @acronym{XML} for which the @acronym{DTD} and/or processing tools are not generally available, and the machine-generated @acronym{HTML}, PostScript or @acronym{PDF} produced by some word processors for output purposes only.

The ``Title Page'' means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, ``Title Page'' means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as ``Acknowledgements'', ``Dedications'', ``Endorsements'', or ``History''.) To ``Preserve the Title'' of such a section when you modify the Document means that it remains a section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever
to those of this License. You may not use
technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.
You may add other material on the covers in addition.
Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that
this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that

edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from
those of previous versions
(which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in

the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add
to it an item stating at least the title, year, new authors, and
publisher of the Modified Version as given on the Title Page. If
there is no section Entitled ``History'' in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the ``History'' section.
You may omit a network location for a work that was published at
least
four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item

Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document,
you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf
of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of
each such section unique by
adding at the end of it, in parentheses, the name of the original

author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract
 a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate
and independent documents or works, in or on a volume of a storage or
distribution medium, is called an ``aggregate'' if the copyright
resulting from the compilation is not used to limit the legal rights
of the compilation's users beyond what the individual works permit.
When the Document is included in an aggregate, this License does not
apply to the other works in the aggregate which are not themselves
derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these
copies of the Document, then if the Document is less than one half of
the entire aggregate, the Document's Cover Texts may
 be placed on
covers that bracket the Document within the aggregate, or the
electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole
aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may
distribute translations of the Document under the terms of section 4.
Replacing Invariant Sections with translations requires special
permission from their copyright holders, but you may include
translations of some or all Invariant Sections in addition to the
original versions of these Invariant Sections. You may include a
translation of this License, and all the license notices in the
Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice
or disclaimer, the original
 version will prevail.

If a section in the Document is Entitled ``Acknowledgements'',
``Dedications'', or ``History'', the requirement (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies
 you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that
 a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'')
 contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole

or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the
 MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License".
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts." line with this:

@smallexample
@group
   with the Invariant Sections being @var{list their titles}, with
   the Front-Cover
 Texts being @var{list}, and with the Back-Cover Texts
   being @var{list}.
@end group
@end smallexample

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,

to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the

earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This

License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the

written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object

code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above

requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible

for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a

patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
@c The GNU General Public License.
@center Version 3, 29 June 2007

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2007 Free Software Foundation, Inc. @url{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this
license document, but changing it is not allowed.
@end display

@heading Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom
to share and change all versions of a program---to make sure it remains
free software for all its users. We, the Free Software Foundation,
use the GNU General Public License for most of our software; it
applies also to any other work released this way by its authors. You
can
 apply it to your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you
have certain responsibilities if you distribute copies of the
software, or if you modify it: responsibilities to respect the freedom
of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too,
receive or can get the source code. And you must show them these
terms so they know
 their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1) assert copyright on the software, and (2) offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains

that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice
 for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

@heading TERMS AND CONDITIONS

@enumerate 0
@item Definitions.

``This License'' refers to version 3 of the GNU General Public License.

``Copyright'' also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

``The Program'' refers to any copyrightable work licensed
 under this
License. Each licensee is addressed as ``you''.  ``Licensees'' and ``recipients'' may be individuals or organizations.

To ``modify'' a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy.  The resulting work is called a ``modified version'' of the earlier work or a work ``based on'' the earlier work.

A ``covered work'' means either the unmodified Program or a work based on the Program.

To ``propagate'' a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To ``convey'' a work means any kind of propagation that enables other parties to make or receive copies. Mere
interaction with a user
through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays ``Appropriate Legal Notices'' to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

@item Source Code.

The ``source code'' for a work means the preferred form of the work for making modifications to it. ``Object code'' means any non-source form of a work.

A ``Standard Interface'' means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming
language, one that
is widely used among developers working in that language.

The ``System Libraries'' of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A ``Major Component'', in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The ``Corresponding Source'' for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However,
it does not include the work's
System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

@item Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission
to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is
permitted solely under the
conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

@item Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

@item Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive
it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

@item Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

@enumerate a
@item
The work must carry prominent notices stating that you modified it, and giving a relevant date.

@item
The work must carry prominent notices stating that it is released under this License and any conditions added
under section 7. This
requirement modifies the requirement in section 4 to ``keep intact all notices''.

@item
You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

@item
If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.
@end enumerate

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in
or on a volume of a storage or distribution medium, is called an ``aggregate'' if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

@item Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

@enumerate a
@item
Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

@item
Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer,
valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the

Corresponding Source for all the software in the product that is
covered by this License, on a durable physical medium customarily used
for software interchange, for a price no more than your reasonable
cost of physically performing this conveying of source, or (2) access
to copy the Corresponding Source from a network server at no charge.

@item
Convey individual copies of the object code with a copy of the written
offer to provide the Corresponding Source. This alternative is
allowed only occasionally and noncommercially, and only if you
received the object code with such an offer, in accord with subsection
6b.

@item
Convey the object code by offering access from a designated place
(gratis or for a charge), and offer equivalent access to the
Corresponding Source in the same way through
 the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to copy
the object code is a network server, the Corresponding Source may be
on a different server (operated by you or a third party) that supports
equivalent copying facilities, provided you maintain clear directions
next to the object code saying where to find the Corresponding Source.
Regardless of what server hosts the Corresponding Source, you remain
obligated to ensure that it is available for as long as needed to
satisfy these requirements.

@item
Convey the object code using peer-to-peer transmission, provided you
inform other peers where the object code and Corresponding Source of
the work are being offered to the general public at no charge under
subsection 6d.

@end enumerate

A separable portion of the object code, whose source code is excluded
from the Corresponding Source as a System Library, need not be
included in conveying the
 object code work.

A ``User Product'' is either (1) a ``consumer product'', which means any
tangible personal property which is normally used for personal,
family, or household purposes, or (2) anything designed or sold for
incorporation into a dwelling. In determining whether a product is a
consumer product, doubtful cases shall be resolved in favor of
coverage. For a particular product received by a particular user,
``normally used'' refers to a typical or common use of that class of

product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

``Installation Information'' for a User Product means any methods, procedures, authorization keys, or other information required to install
and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information
does not include a
requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

@item Additional Terms.

``Additional permissions'' are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall

be treated as though they were included
in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders
of that material) supplement the terms of this License with terms:

@enumerate a
@item
Disclaiming warranty or limiting liability differently from the terms
of
sections 15 and 16 of this License; or

@item
Requiring preservation of specified reasonable legal notices or author
attributions in that material or in the Appropriate Legal Notices
displayed by works containing it; or

@item
Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

@item
Limiting the use for publicity purposes of names of licensors or
authors of the material; or

@item
Declining to grant rights under trademark law for use of some trade
names, trademarks, or service marks; or

@item
Requiring indemnification of licensors and authors of that material by
anyone who conveys the material (or modified versions of it) with
contractual assumptions of liability to the recipient, for any
liability that these contractual assumptions directly impose on those
licensors and authors.

@end enumerate

All other non-permissive additional terms are considered
``further
restrictions'' within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions; the
above requirements apply either way.

@item Termination.

You may not propagate or modify a
covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination
of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under

this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

@item Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

@item Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An ``entity transaction'' is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

@item Patents.

A ``contributor'' is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's ``contributor version''.

A contributor's ``essential patent claims'' are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, ``control'' includes the right to grant patent
sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a ``patent license'' is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To ``grant'' such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you
must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. ``Knowingly relying'' means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work
and works based on it.

A patent license is ``discriminatory'' if it does not include within the

scope of its coverage, prohibits the exercise of, or is conditioned on
the non-exercise of one or more of the rights that are specifically
granted under this License. You may not convey a covered work if you
are a party to an arrangement with a third party that is in the
business of distributing software, under which you make payment to the
third party based on the extent of your activity of conveying the
work, and under which the third party grants, to any of the parties
who would receive the covered work from you, a discriminatory patent
license (a) in connection with copies of the covered work conveyed by
you (or copies made from those copies), or (b) primarily for and in
connection with specific products or compilations that contain the
covered work, unless you entered into that arrangement, or that patent
license was granted, prior to 28 March 2007.

Nothing in this License shall
 be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

@item No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey
a covered work so as to satisfy simultaneously your obligations under
this License and any other pertinent obligations, then as a
consequence you may not convey it at all. For example, if you agree
to terms that obligate you to collect a royalty for further conveying
from those to whom you convey the Program, the only way you could
satisfy both those terms and this License would be to refrain entirely
from conveying the Program.

@item Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any
 covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

@item Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions
of the GNU General Public License from time to time. Such new

versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies that a certain numbered version of the GNU General Public
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that numbered version or
of any later version
published by the Free Software Foundation. If
the Program does not specify a version number of the GNU General
Public License, you may choose any version ever published by the Free
Software Foundation.

If the Program specifies that a proxy can decide which future versions
of the GNU General Public License can be used, that proxy's public
statement of acceptance of a version permanently authorizes you to
choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

@item Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM ``AS IS'' WITHOUT
WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND
PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE
DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR
CORRECTION.

@item Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR
CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES
ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT
NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR
LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM
TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER
PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

@item Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above
 cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

@end enumerate

@heading END OF TERMS AND CONDITIONS

@heading How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these
terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the ``copyright'' line and a pointer to where the full notice is found.

@smallexample
@var{one line to give the program's name and a brief idea of what it does.}
Copyright
 (C) @var{year} @var{name of author}

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or (at
your option) any later version.

This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see @url{http://www.gnu.org/licenses/}.
@end smallexample

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short

notice like this when it starts in an interactive mode:

@smallexample
@var{program} Copyright (C) @var{year} @var{name of author}
This program comes with ABSOLUTELY NO WARRANTY;
 for details type @samp{show w}.
This is free software, and you are welcome to redistribute it
under certain conditions; type @samp{show c} for details.
@end smallexample

The hypothetical commands @samp{show w} and @samp{show c} should show
the appropriate parts of the General Public License. Of course, your
program's commands might be different; for a GUI interface, you would
use an ``about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a ``copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
@url{http://www.gnu.org/licenses/}.

The GNU General Public License does not permit incorporating your
program into proprietary programs. If your program is a subroutine
library, you may consider it more useful to permit linking proprietary
applications with the library. If this is what you want to do, use
the GNU Lesser General Public License instead of this License.
  But
first, please read @url{http://www.gnu.org/philosophy/why-not-lgpl.html}.
    GNU LESSER GENERAL PUBLIC LICENSE
                Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

 This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

 0. Additional Definitions.

 As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

 "The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated

material is not limited to numerical parameters, data
structure
layouts and accessors, or small macros, inline functions and templates
(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the
Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license
document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that,
taken together, effectively do not restrict modification of the
portions of the Library contained in the Combined Work and reverse
engineering for debugging such modifications, if you also do each of
the following:

a) Give prominent notice with each copy of the Combined Work that
the Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license
document.

c) For a Combined Work that displays copyright
notices during
execution, include the copyright notice for the Library among
these notices, as well as a reference directing the user to the
copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this
License, and the Corresponding Application Code in a form
suitable for, and under terms that permit, the user to
recombine or relink the Application with a modified version of
the Linked Version to produce a modified Combined Work, in the
manner specified by section 6 of the GNU GPL for conveying
Corresponding Source.

1) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (a) uses at run time
a copy of the Library already present on the user's computer
system, and (b) will operate properly with a modified version
of the Library that is interface-compatible

with the Linked
Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under
terms of your
choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following
the terms and
conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser

General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

1.111 bzip2 1.0.8-10.el9_5

1.111.1 Available under license :

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2019 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@acm.org
bzip2/libbzip2 version 1.0.8 of 13 July 2019

1.112 fonts-filesystem 1:2.0.5-7.el9.1

1.112.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same

freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"

and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is
not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that

Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of

your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section

7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical

medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option

remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating

where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting

any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest

to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

MIT License

Copyright 2019 Nicolas Mailhot <nim@fedoraproject.org>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the Software), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice (including the next paragraph) shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.113 file 5.39-16.el9

1.113.1 Available under license :

Copyright (c) Ian F. Darwin 1986-1995.
Software written by Ian F. Darwin and others;
maintained 1995-present by Christos Zoulas and others.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice immediately at the beginning of the file, without modification,
  this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
$File: COPYING,v 1.2 2018/09/09 20:33:28 christos Exp $
Copyright (c) Ian F. Darwin 1986, 1987, 1989, 1990, 1991, 1992, 1994, 1995.
Software written by Ian F. Darwin and others;
maintained 1994- Christos Zoulas.

This software is not subject to any export provision of the United States
Department of Commerce, and may be exported to any country or planet.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice immediately at the beginning of the file, without modification,
  this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED
 WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

1.114 findutils 1:4.8.0-7.el9

1.114.1 Available under license :

/* Extract the last component (base name) of a file name.

  Copyright (C) 1998, 2001, 2003-2006, 2009-2021 Free Software Foundation,
  Inc.

  This program is free software: you can redistribute it and/or modify
  it under the terms of the GNU General Public License as published by
  the Free Software Foundation; either version 3 of the License, or
  (at your option) any later version.

  This program is distributed in the hope that it will be useful,

```
   but WITHOUT ANY WARRANTY; without even the implied warranty of
   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
   GNU General Public License for more details.

   You should have received a copy of the GNU General Public License
   along with this program.  If not, see <https://www.gnu.org/licenses/>.  */

#ifndef _BASENAME_LGPL_H
#define _BASENAME_LGPL_H

#include <stddef.h>

#ifndef DOUBLE_SLASH_IS_DISTINCT_ROOT
# define DOUBLE_SLASH_IS_DISTINCT_ROOT 0
#endif

#ifdef __cplusplus
extern "C" {
#endif


/*
 Return the address of the last file name component of FILENAME.
  If FILENAME has some trailing slash(es), they are considered to be
  part of the last component.
  If FILENAME has no relative file name components because it is a file
  system root, return the empty string.
  Examples:
          FILENAME      RESULT
          "foo.c"       "foo.c"
          "foo/bar.c"   "bar.c"
          "/foo/bar.c"  "bar.c"
          "foo/bar/"    "bar/"
          "foo/bar//"   "bar//"
          "/"           ""
          "//"          ""
          ""            ""
  The return value is a tail of the given FILENAME; do NOT free() it!  */

/* This function was traditionally called 'basename', but we avoid this
  function name because
    * Various platforms have different functions in their libc.
      In particular, the glibc basename(), defined in <string.h>, does
      not consider trailing slashes to be part of the component:
          FILENAME
      RESULT
          "foo/bar/"    ""
          "foo/bar//"   ""
```

```
   * The 'basename' command eliminates trailing slashes and for a root
     produces a non-empty result:
          FILENAME      RESULT
          "foo/bar/"    "bar"
          "foo/bar//"   "bar"
          "/"           "/"
          "//"          "/"
*/
extern char *last_component (char const *filename) _GL_ATTRIBUTE_PURE;

/* Return the length of the basename FILENAME.
  Typically FILENAME is the value returned by base_name or last_component.
  Act like strlen (FILENAME), except omit all trailing slashes.  */
extern size_t base_len (char const *filename) _GL_ATTRIBUTE_PURE;



#ifdef __cplusplus
} /* extern "C" */
#endif

#endif /* _BASENAME_LGPL_H */
```

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new

free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official

standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product,

doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions.

Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty
or limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further

restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or

run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant

patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory

patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the
option of following the terms and conditions either of that numbered version or of any later version published by the Free Software

Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.

1.115 langpacks-core-en 3.0-16.el9

1.115.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

Name: langpacks

Found in path(s):
* /langpacks-3.0-16.el9.src.rpm-cosi-expand-archive-fhzS60uV/langpacks.spec

1.116 libassuan 2.5.5-3.el9

1.116.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change

free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a

restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it
becomes a de-facto standard. To achieve this, non-free programs must
be allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting the
free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an

appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote

it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked

with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly
with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined

library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will
be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE
LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively

convey the exclusion of warranty; and each file should
have at least the "copyright" line and a pointer to where the full
notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for

software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1) assert copyright on the software, and (2) offer
you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those

products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate
Legal Notices"
to the extent that it includes a convenient and prominently visible
feature that (1) displays an appropriate copyright notice, and (2)
tells the user that there is no warranty for the work (except to the
extent that warranties are provided), that licensees may convey the
work under this License, and how to view a copy of this License. If
the interface presents a list of user commands or options, such as a
menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work
for making modifications to it. "Object code" means any non-source
form of a work.

A "Standard Interface" means an interface that either is an official
standard defined by a recognized standards body, or, in the case of
interfaces specified for a particular programming language, one that
is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other
than
the work as a whole, that (a) is included in the normal form of
packaging a Major Component, but which is not part of that Major
Component, and (b) serves only to enable use of the work with that
Major Component, or to implement a Standard Interface for which an
implementation is available to the public in source code form. A
"Major Component", in this context, means a major essential component
(kernel, window system, and so on) of the specific operating system
(if any) on which the executable work runs, or a compiler used to
produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all
the source code needed to generate, install, and (for an executable
work) run the object code and to modify the work, including scripts to
control those activities. However, it does not include the work's
System Libraries, or general-purpose tools or generally available free
programs which are used unmodified in performing
those activities but
which are not part of the work. For example, Corresponding Source
includes interface definition files associated with source files for
the work, and the source code for shared libraries and dynamically
linked subprograms that the work is specifically designed to require,
such as by intimate data communication or control flow between those
subprograms and other parts of the work.

The Corresponding Source need not include anything that users

can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content,
constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users'
Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and

its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years and valid for as
long as you offer spare parts or customer
support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in the same way through the same place at no
further charge.
You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the

Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information

does not include a
requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included
in this License, to the extent
that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections
15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your
receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time
you convey a covered work, the recipient automatically
receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not

impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that

country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed

under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you have the
option of following the terms and conditions either
of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED,
INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS
THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer
of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief
idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

 If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

  <program> Copyright (C) <year> <name of author>
  This program comes with
 ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

 You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

 The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But first,
 please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.117 libpkit 0.25.3-3.el9_5

1.117.1 Available under license :

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

  * Redistributions of source code must retain the above
    copyright notice, this list of conditions and the
    following disclaimer.
  * Redistributions in binary form must reproduce the
    above copyright notice, this list of conditions and
    the following disclaimer in the documentation and/or
    other materials provided with the distribution.
  * The names of contributors to this software may not be
    used to endorse or promote products derived from this
    software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED
AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF
THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

1.118 libsolv 0.7.24-3.el9

1.118.1 Available under license :

All files for the Windows compatibility layer are taken from musl,
except for unistd.h and fmemopen.c.

MUSL

musl as a whole is licensed under the following standard MIT license:

Copyright 2005-2014 Rich Felker, et al.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

TRE (tre.h, tre-mem.c)

The TRE regular expression implementation (reg* and
tre*) is Copyright 2001-2008 Ville Laurikari and licensed
under a 2-clause BSD license (license text in the source files). The
included version has been heavily modified by Rich Felker in 2012, in
the interests of size, simplicity, and namespace cleanliness.

This is the license, copyright notice, and disclaimer for TRE, a regex
matching package (library and tools) with support for approximate
matching.

Copyright (c) 2001-2009 Ville Laurikari <vl@iki.fi>
All
 rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

 1. Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.

 2. Redistributions in binary form must reproduce the above copyright
    notice, this list of conditions and the following disclaimer in the
    documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA,
 OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of Novell nor the names of its contributors may
be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.119 shadow 2:4.9-15.el9

1.119.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on

the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Program at all. For
example, if a patent
license would not permit royalty-free redistribution of the Program by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under
any particular circumstance, the balance of the section is intended to
apply and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to
decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

NOTE:
 This license has been obsoleted by the change to the BSD-style copyright.
 You may continue to use this license if you wish, but you are under no
 obligation to do so.

(*
This document is freely plagiarised from the 'Artistic Licence',
distributed as part of the Perl v4.0 kit by Larry Wall, which is
available from most major archive sites. I stole it from CrackLib.

 Id
*)

This documents purpose is to state the conditions under which this
Package (See definition below) viz: "Shadow", the Shadow Password Suite
which is held by Julianne Frances Haugh, may be copied, such that the
copyright holder maintains some semblance of artistic control over the
development of the package, while giving the users of the package the
right to use and distribute the Package in a more-or-less customary
fashion, plus the right to make reasonable modifications.

So there.

****

Definitions:

A "Package" refers to the collection
 of files distributed by the
Copyright Holder, and derivatives of that collection of files created
through textual modification, or segments thereof.

"Standard Version" refers to such a Package if it has not been modified,
or has been modified in accordance with the wishes of the Copyright
Holder.

"Copyright Holder" is whoever is named in the copyright or copyrights
for the package.

"You" is you, if you're thinking about copying or distributing this
Package.

"Reasonable copying fee" is whatever you can justify on the basis of
media cost, duplication charges, time of people involved, and so on.
(You will not be required to justify it to the Copyright Holder, but
only to the computing community at large as a market that must bear the
fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when AND WHY you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide separate documentation for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding
Standard Version executables, giving the non-standard executables
non-standard names, and clearly
 documenting the differences in manual
pages (or equivalent), together with instructions on where to get the
Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this
Package. You may charge any fee you choose for support of this Package.
YOU MAY NOT CHARGE A FEE FOR THIS PACKAGE ITSELF. However, you may
distribute this Package in aggregate with other (possibly commercial)
programs as part of a larger (possibly commercial) software distribution
provided that YOU DO NOT ADVERTISE this package as a product of your
own.

6. The name of the Copyright Holder may not be used to endorse or
promote products derived from this software without specific prior
written permission.

7. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF
MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

   The End
/*
* Copyright (c) 1990 - 1994, Julianne Frances Haugh
* Copyright (c) 1996 - 2000, Marek Michakiewicz
* Copyright (c) 2000 - 2006, Tomasz Koczko
* Copyright (c) 2007 - 2011, Nicolas Franois
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. The name of the copyright holders or contributors may not be used to
*   endorse or promote products derived from this software without
*   specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
* ``AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
* LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
* HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
* OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their

rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work
which contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim
copies of the Program's
source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole
or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably
considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work
based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code
or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled to copy
the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.
Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free
redistribution of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through
any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE
LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

1.120 libevent 2.1.12-8.el9_4

1.120.1 Available under license :

Libevent is available for use under the following license, commonly known as the 3-clause (or "modified") BSD license:

==========

Copyright (c) 2000-2007 Niels Provos <provos@citi.umich.edu>
Copyright (c) 2007-2012 Niels Provos and Nick Mathewson

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
==========

Portions of Libevent are based on works by others, also made available by them under the three-clause BSD license above. The copyright notices are available in the corresponding source files; the license is as above. Here's a list:

log.c:
Copyright (c) 2000 Dug Song <dugsong@monkey.org>
Copyright (c) 1993 The Regents of the University of California.

strlcpy.c:
Copyright (c) 1998 Todd C. Miller <Todd.Miller@courtesan.com>

win32select.c:
Copyright (c) 2003 Michael A. Davis <mike@datanerds.net>

evport.c:
Copyright (c) 2007 Sun Microsystems

ht-internal.h:
Copyright (c) 2002 Christopher Clark

minheap-internal.h:
Copyright (c) 2006 Maxim Yegorushkin <maxim.yegorushkin@gmail.com>

==========

The arc4module is available under the following, sometimes called the "OpenBSD" license:

Copyright (c) 1996, David Mazieres <dm@uun.org>
Copyright (c) 2008, Damien Miller <djm@openbsd.org>

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN

ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

==========

The Windows timer code is based on code from libutp, which is
distributed under this license, sometimes called the "MIT" license.

Copyright (c) 2010 BitTorrent, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be
included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
CMake - Cross Platform Makefile Generator
Copyright 2000-2013 Kitware, Inc.
Copyright 2000-2011 Insight Software Consortium
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* Neither the names of Kitware, Inc., the Insight Software Consortium,
nor the names of their contributors may be used to endorse or promote
products derived from this software without specific prior written

permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The above copyright and license notice applies to distributions of
CMake in source and binary form. Some source files contain additional
notices of original copyright by their contributors; see each source
for details. Third-party software packages supplied with CMake under
compatible licenses provide their
own copyright notices documented in
corresponding subdirectories.

CMake was initially developed by Kitware with the following sponsorship:

* National Library of Medicine at the National Institutes of Health
  as part of the Insight Segmentation and Registration Toolkit (ITK).

* US National Labs (Los Alamos, Livermore, Sandia) ASC Parallel
  Visualization Initiative.

* National Alliance for Medical Image Computing (NAMIC) is funded by the
  National Institutes of Health through the NIH Roadmap for Medical Research,
  Grant U54 EB005149.

* Kitware, Inc.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the copyright
  notice, this list of conditions and the following disclaimer in the

documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.121 gobject-introspection 1.68.0-11.el9

1.121.1 Available under license :

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some
specially designated Free Software Foundation software, and to any
other libraries whose authors decide to use it. You can use it for
your libraries, too.

When we speak of free software, we are referring
to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it

if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if
you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link a program with the library, you must provide
complete object files to the recipients so that they can relink them
with the library, after making
changes to the library and recompiling
it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright
the library, and (2) offer you this license which gives you legal
permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain
that everyone understands that there is no warranty for this free
library. If the library is modified by someone else and passed on, we
want its recipients to know that what they have is not the original
version, so that any problems introduced by others will not reflect on
the original authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that companies distributing free
software will individually obtain patent licenses, thus in effect
transforming the program into proprietary software. To prevent this,
we have made it clear that any patent must
be licensed for everyone's
free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary
GNU General Public License, which was designed for utility programs. This
license, the GNU Library General Public License, applies to certain
designated libraries. This license is quite different from the ordinary
one; be sure to read it in full, and don't assume that anything in it is
the same as in the ordinary license.

The reason we have a separate public license for some libraries is that
they blur the distinction we usually make between modifying or adding to a
program and simply using it. Linking a program with a library, without
changing the library, is in some sense simply using the library, and is
analogous to running a utility program or application program. However, in

a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a

portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent
of the use of the Library in a tool for
writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work
must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility

is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code
of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative
work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the
use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,

whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply
a copy of this License. If the work
during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany
the work with a written offer, valid for at
least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major

components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the
executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based
on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions
for copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the

original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not
distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system;
it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new

versions of the Library General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or
concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY
IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE
OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year>
<name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public
License as published by the Free Software Foundation; either
version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Library General Public License for more details.

You should have received a copy of the GNU Library General Public
License along with this library; if not, write to the
Free Software Foundation, Inc., 59 Temple Place - Suite 330,
Boston, MA 02111-1307 USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary.
Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so

that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole
or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by

modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED

TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
gobject-introspection has two licenses; one for the typelib library,
and one for the tools.

* The typelib libraries (girepository/) are licensed under the LGPLv2+.
See the file COPYING.LGPL.

* The remaining code is GPLv2+ compatible (see the file COPYING.GPL) and
consists of a mix of GPLv2+, LGPLv2+ and MIT. See the license headers in
each file for details.

In general where applicable files should have headers denoting their license
status; if they do not, please file a bug at
https://gitlab.gnome.org/GNOME/gobject-introspection/issues.

1.122 keyutils-libs 1.6.3-1.el9

1.122.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. <http://fsf.org/>
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission
to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program
or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish,
that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third

parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can
be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program
(or a work based on it,
under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium

customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program
in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled
to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based
on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to

these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit
royalty-free redistribution of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute
software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions

of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies
a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED
BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY
OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either
version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show
w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc. <http://fsf.org/>
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use
it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these

rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you
must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat
to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits such linking only if the
entire
combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it

does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software
only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL
PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility
in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably considered independent and separate
works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead
of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code,
which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the
library". The executable is therefore
covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish revised and/or new
versions of the Lesser
General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving
the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN

WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL
OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright"
line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your

school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.123 popt 1.18-8.el9

1.123.1 Available under license :

Copyright (c) 1998 Red Hat Software

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be
used in advertising or otherwise to promote the sale, use or other dealings
in this Software without prior written authorization from the X Consortium.

1.124 gawk 5.1.0-6.el9

1.124.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free

program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause

any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the

Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if

necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with

the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data

prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the

ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object

file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at

least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your

rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE

LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Copyright (c) 1983, 1993
The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
* Neither the name of the <ORGANIZATION> nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED.
IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some
specially designated Free Software Foundation software, and to any
other libraries whose authors decide to use it. You can use it for
your libraries, too.

When we speak of free software, we are referring to freedom,
not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if
you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link a program with the library, you must provide
complete object files to the recipients so that they can relink them
with the library, after making
changes to the library and recompiling
it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright
the library, and (2) offer you this license which gives you legal
permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain
that everyone understands that there is no warranty for this free
library. If the library is modified by someone else and passed on, we
want its recipients to know that what they have is not the original
version, so that any problems introduced by others will not reflect on
the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed
under these terms. A "work based on the
Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent
of the use of the Library in a tool for
writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or

collective works based on the Library.

In addition,
mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the
Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative
work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the

library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the

Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Accompany the
work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

d) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the source code distributed need not include anything that is normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the
Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for
copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute
the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is

implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system;
 it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

 12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

 13. The Free Software Foundation may publish revised and/or new
versions of the Library General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each
 version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

 14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

      NO WARRANTY

 15. BECAUSE THE LIBRARY
 IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR

OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR
LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year>
<name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public
License along with this library; if not, write to the Free
Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston,
MA 02110-1301, USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary.
Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that

is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other
than the work as a whole, that (a) is included in the normal form of
packaging a Major Component, but which is not part of that Major
Component, and (b) serves only to enable use of the work with that
Major Component, or to implement a Standard Interface for which an
implementation is available to the public in source code form. A
"Major Component", in this context, means a major essential component
(kernel, window system, and so on) of the specific operating system
(if any) on which the executable work runs, or a compiler used to
produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all
the source code needed to generate, install, and (for an executable
work) run the object code and to modify the work, including scripts to
control those activities. However, it does not include the work's
System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but
which are not part of the work. For example, Corresponding Source
includes interface definition files associated with source files for
the work, and the source code for shared libraries and dynamically
linked subprograms that the work is specifically designed to require,
such as by intimate data communication or control flow between those
subprograms and other parts of the work.

The Corresponding Source need not include anything that users
can regenerate automatically from other parts of the Corresponding
Source.

The Corresponding Source for a work in source code form is that
same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of
copyright on the Program, and are irrevocable provided the stated
conditions are met. This License explicitly affirms your unlimited
permission to run the unmodified Program. The output from running a
covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains

in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the

terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product

(including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a

typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the

entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains

a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work

occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant

patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory

patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
 that patent license was granted, prior to 28 March 2007.

 Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

 12. No Surrender of Others' Freedom.

 If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

 13. Use with the GNU Affero General Public License.

  Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

 14. Revised Versions of this License.

 The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

 Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
 have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the

GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.125 readline 8.1-4.el9

1.125.1 Available under license :

@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the

software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that
contains a notice placed by the copyright holder saying it can be
distributed under the terms of this License. Such a notice grants a
world-wide, royalty-free license, unlimited in duration, to use that
work under the conditions stated herein. The ``Document'', below,
refers
 to any such manual or work. Any member of the public is a
licensee, and is addressed as ``you''. You accept the license if you
copy, modify or distribute the work in a way requiring permission
under copyright law.

A ``Modified Version'' of the Document means any work containing the
Document or a portion of it, either copied verbatim, or with
modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section
of the Document that deals exclusively with the relationship of the
publishers or authors of the Document to the Document's overall
subject (or to related matters) and contains nothing that could fall
directly within that overall subject. (Thus, if the Document is in
part a textbook of mathematics, a Secondary Section may not explain
any mathematics.) The relationship could be a matter of historical
connection with the subject or with related matters, or of legal,
commercial, philosophical, ethical or political
 position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles
are designated, as being those of Invariant Sections, in the notice
that says that the Document is released under this License. If a
section does not fit the above definition of Secondary then it is not
allowed to be designated as Invariant. The Document may contain zero
Invariant Sections. If the Document does not identify any Invariant
Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,
as Front-Cover Texts or Back-Cover Texts, in the notice that says that
the Document is released under this License. A Front-Cover Text may
be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,
represented in a format whose specification is available to the
general public, that is suitable for revising the document
straightforwardly with generic text editors or (for
 images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
@sc{ascii} without markup, Texinfo input format, La@TeX{} input
format, @acronym{SGML} or @acronym{XML} using a publicly available
@acronym{DTD}, and standard-conforming simple @acronym{HTML},
PostScript or @acronym{PDF} designed for human modification. Examples
of transparent image formats include @acronym{PNG}, @acronym{XCF} and
@acronym{JPG}. Opaque formats
 include proprietary formats that can be
read and edited only by proprietary word processors, @acronym{SGML} or
@acronym{XML} for which the @acronym{DTD} and/or processing tools are
not generally available, and the machine-generated @acronym{HTML},
PostScript or @acronym{PDF} produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means
the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in
 another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'', or ``History''.)  To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which

states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever
to those of this License. You may not use
technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.
You may add other material on the covers in addition.
Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy

a computer-network location from which the general network-using
public has access to download using public-standard network protocols
a complete Transparent copy of the Document, free of added material.
If you use the latter option, you must take reasonably prudent steps,
when you begin distribution of Opaque copies in quantity, to ensure
that
this Transparent copy will remain thus accessible at the stated
location until at least one year after the last time you distribute an
Opaque copy (directly or through your agents or retailers) of that
edition to the public.

It is requested, but not required, that you contact the authors of the
Document well before redistributing any large number of copies, to give
them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under
the conditions of sections 2 and 3 above, provided that you release
the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from
those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same title as a previous version
if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities
responsible for authorship of the modifications in the Modified
Version, together with at least five of the principal authors of the
Document (all of its principal authors, if it has fewer than five),
unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the
Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications
adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice
giving the public permission to use the Modified Version under the
terms of this License, in the form shown in
the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add
to it an item stating at least the title, year, new authors, and
publisher of the Modified Version as given on the Title Page. If
there is no section Entitled ``History'' in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the ``History'' section.
You may omit a network location for a work that was published at
least
four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item

Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document,
 you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf
 of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its

license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of
 each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract
 a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate
and independent documents or works, in or on a volume of a storage or
distribution medium, is called an ``aggregate'' if the copyright
resulting from the compilation is not used to limit the legal rights
of the compilation's users beyond what the individual works permit.
When the Document is included in an aggregate, this License does not
apply to the other works in the aggregate which are not themselves
derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these
copies of the Document, then if the Document is less than one half of
the entire aggregate, the Document's Cover Texts may

be placed on
covers that bracket the Document within the aggregate, or the
electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole
aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may
distribute translations of the Document under the terms of section 4.
Replacing Invariant Sections with translations requires special
permission from their copyright holders, but you may include
translations of some or all Invariant Sections in addition to the
original versions of these Invariant Sections. You may include a
translation of this License, and all the license notices in the
Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice
or disclaimer, the original
version will prevail.

If a section in the Document is Entitled ``Acknowledgements'',
``Dedications'', or ``History'', the requirement (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies
you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that

copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that
 a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'')
 contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license

published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the
 MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License''.
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts.'' line with this:

@smallexample
@group
   with the Invariant Sections being @var{list their titles}, with
   the Front-Cover
 Texts being @var{list}, and with the Back-Cover Texts
   being @var{list}.
@end group
@end smallexample

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether

gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this

License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major

Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction

and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or
modification of the work as a means of enforcing, against the work's
users, your or third parties' legal rights to forbid circumvention of
technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you
receive it, in any medium, provided that you conspicuously and
appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

b) The work must carry prominent notices stating that it is

released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the

product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the

additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read

<http://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we

want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and

distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole
or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are

prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING

OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.126 gmp 1:6.2.0-13.el9

1.126.1 Available under license :

No license file was found, but licenses were detected in source scan.

/* Generic x86 gmp-mparam.h -- Compiler/machine parameter header file.

Copyright 1991, 1993, 1994, 1995, 1996, 1997, 1999, 2000, 2001, 2002, 2003,
2004, 2005, 2006, 2007, 2008, 2009 Free Software Foundation, Inc.

This file is part of the GNU MP Library.

The GNU MP Library is free software; you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 3 of the License, or (at your
option) any later version.

The GNU MP Library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public
License for more details.

You should have received a copy of the GNU Lesser General Public License
along with the GNU MP Library. If not, see http://www.gnu.org/licenses/. */

Found in path(s):
*
/gmp-c9s-zip/gmp-c9s/gmp-mparam.h
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2761148612_1762983741.2881236/0/gmp-c9s-zip/gmp-c9s/gmp.h/* Definitions for GNU multiple precision functions.   -*- mode: c -*-
/opt/cola/permits/2761148612_1762983741.2881236/0/gmp-c9s-zip/gmp-c9s/gmp.spec#
/opt/cola/permits/2761148612_1762983741.2881236/0/gmp-c9s-zip/gmp-c9s/ibm_z13_simd_part1.patchCo-authored-by: Stefan Liebler <stli at linux.ibm.com>
/opt/cola/permits/2761148612_1762983741.2881236/0/gmp-c9s-zip/gmp-c9s/ibm_z13_simd_part2.patchCo-authored-by: Stefan Liebler <stli at linux.ibm.com>
/opt/cola/permits/2761148612_1762983741.2881236/0/gmp-c9s-zip/gmp-c9s/ibm_z13_simd_part3.patchCo-authored-by: Stefan Liebler <stli at linux.ibm.com>

Found in path(s):
*

1.127 libcap-ng 0.8.2-7.el9

1.127.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors

who decide to use it. You
can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.
^L
Finally,
software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the

ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore
permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it
becomes
a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The

former contains code derived from the library, whereas the latter must
be combined with the library
 in order to run.
^L
GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other
program which contains a notice placed by the copyright holder or
other authorized party saying it may be distributed under the terms of
this Lesser General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly
 into another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control
compilation
and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether that is true depends on what the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's
complete source code as you receive it,
 in any medium, provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the

Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under
the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and
can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest

your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it

contains portions of the Library), rather than a
"work that uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute
the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified

executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (1) uses at run time a
copy of the library already present on the user's computer system,
rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything
that is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.
^L
7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined
with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited
by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License,
they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then

the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software
distribution system which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation
may publish revised and/or new
versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.
^L
14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is

copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for
this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS
PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms
of the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source
file to most
effectively convey the exclusion of warranty; and each file should
have at least the "copyright" line and a pointer to where the full
notice is found.

<one line to give the library's name and a brief idea of what it
does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper
mail.

You should also get your employer (if you work as a programmer) or
your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively

when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer

to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to

this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it

free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

1.128 sqlite 3.34.1-9.el9_7

1.128.1 Available under license :

The author disclaims copyright to this source code. In place of a legal notice, here is a blessing:

May you do good and not evil.
May you find forgiveness for yourself and forgive others.
May you share freely, never taking more than you give.

The author disclaims copyright to this source code. In place of a legal notice, here is a blessing:

* May you do good and not evil.
* May you find forgiveness for yourself and forgive others.
* May you share freely, never taking more than you give.

1.129 libdnf 0.69.0-16.el9

1.129.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change

free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that

any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact

all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that

uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on

the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.

11. If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent

license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply,
and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system
 which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

 12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

 13. The Free Software Foundation may publish
 revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

 14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,

write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision
will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.130 file-system 3.16-5.el9

1.130.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

Summary: The basic directory layout for a Linux system

Found in path(s):
* /filesystem.3.16-5.el9.os.almalinux.9.5-1.src.rpm-cosi-expand-archive-nagKMg9K/filesystem.spec

1.131 e2fsprogs 1.46.5-8.el9

1.131.1 Available under license :

This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

http://sourceforge.net/projects/e2fsprogs

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2001 by Andries Brouwer
Copyright (C) 1999, 2000, 2003 by Theodore Ts'o

You are free to distribute this software under the terms of the GNU
Lesser (Library) General Public License.

On Debian systems, the complete text of the GNU Lesser (Library)
General Public License can be found in /usr/share/common-licenses/LGPL-2.
This is the Debian GNU/Linux prepackaged version of the static EXT2
file system consistency checker (e2fsck.static). The EXT2 utilities
were written by Theodore Ts'o <tytso@mit.edu> and Remy Card
<card@masi.ibp.fr>.

Sources were obtained from http://sourceforge.net/projects/e2fsprogs

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <http://www.alcove.com/>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU
General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000,
2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General

```
Public License can be found in `/usr/share/common-licenses/GPL-2'.
#
# This is a Makefile stub which handles the creation of BSD shared
# libraries.
#
# In order to use this stub, the following makefile variables must be defined.
#
# BSDLIB_VERSION = 1.0
# BSDLIB_IMAGE = libce
# BSDLIB_MYDIR = et
# BSDLIB_INSTALL_DIR = $(SHLIBDIR)
#

all:: image

real-subdirs:: Makefile
 @echo " MKDIR pic"
 @mkdir -p pic

BSD_LIB = $(BSDLIB_IMAGE).so.$(BSDLIB_VERSION)
BSDLIB_PIC_FLAG = -fpic

image:  $(BSD_LIB)

$(BSD_LIB): $(OBJS)
 (cd pic; ld -Bshareable -o $(BSD_LIB) $(LDFLAGS_SHLIB) $(OBJS))
 $(MV) pic/$(BSD_LIB) .
 $(RM) -f ../$(BSD_LIB)
 (cd ..; $(LN) $(LINK_BUILD_FLAGS) \
  `echo $(my_dir) | sed -e 's;lib/;;'`/$(BSD_LIB) $(BSD_LIB))

install-shlibs install:: $(BSD_LIB)
 @echo " INSTALL_PROGRAM $(BSDLIB_INSTALL_DIR)/$(BSD_LIB)"
 @$(INSTALL_PROGRAM) $(BSD_LIB) \
  $(DESTDIR)$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
 @-$(LDCONFIG)

install-strip: install

install-shlibs-strip:: install-shlibs

uninstall-shlibs uninstall::
 $(RM) -f $(DESTDIR)$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)

clean::
 $(RM)
 -rf pic
 $(RM) -f $(BSD_LIB)
```

$(RM) -f ../$(BSD_LIB)

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, and the entire permission notice in its entirety,
   including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
   products derived from this software without specific prior
   written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
 DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

This is the Debian GNU/Linux prepackaged version of the translation
files of the EXT2 file system utilities. The EXT2 utilities were
written by Theodore Ts'o <tytso@mit.edu> and Remy Card
<card@masi.ibp.fr>.

Sources were obtained from http://sourceforge.net/projects/e2fsprogs

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>
        Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
    Copyright (c) 2001 Alcove <http://www.alcove.com/>
    Copyright (c) 1997 Klee Dienes
    Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU
General Public License.

 Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000,

2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General
Public License can be found in `/usr/share/common-licenses/GPL-2'.
This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Fri Dec 14 22:24:35 EST 2007

It is part of the main e2fsprogs distribution, which can be found at:

http://sourceforge.net/projects/e2fsprogs

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007 by
Theodore Ts'o

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from
this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
/*

Copyright 1987 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
M.I.T. and the M.I.T. S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

*/
Index: tdbsa/tdb.c
===
--- tdbsa.orig/tdb.c
+++ tdbsa/tdb.c
@@ -4,11 +4,11 @@ Rev: 23371
Last Changed Date: 2007-06-06 20:14:06 -0400 (Wed, 06 Jun 2007)
*/
 /*
-   Unix SMB/CIFS implementation.
+   trivial database library - standalone version

-   trivial database library - private includes
-
-   Copyright (C) Andrew Tridgell   2005
+   Copyright (C) Andrew Tridgell   1999-2005
+   Copyright (C) Jeremy Allison   2000-2006
+   Copyright (C) Paul `Rusty' Russell   2000

    ** NOTE! The following LGPL license applies to the tdb
    ** library. This does NOT imply that all of Samba is released
EXT2ED is hereby placed under the terms of the GNU General Public License.
Follows the GNU license.

Gadi Oxman, August 1995

     GNU GENERAL PUBLIC LICENSE
        Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
                    675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the
GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you
must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any

patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for
copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents
constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You
must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program
is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or
with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information
you received as to the offer
to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering
access
to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program
(or any work based on the
Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the

Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously
your obligations under this
License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to
the wide range of software distributed
through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY;
for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider
it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
This package, the EXT2 filesystem utilities, are made available under
the GNU Public License version 2, with the exception of the lib/ext2fs
and lib/e2p libraries, which are made available under the GNU Library
General Public License Version 2, the lib/uuid library which is made
available under a BSD-style license and the lib/et and lib/ss
libraries which are made available under an MIT-style license. Please
see lib/uuid/COPYING for more details for the license for the files
comprising the libuuid library, and the source file headers of the
libet and libss libraries for more information.

The most recent officially distributed version can be found at
http://e2fsprogs.sourceforge.net. If you need to make a distribution,
that's the one you should use. If there is some reason why you'd like
a more recent version that is still in ALPHA testing (i.e., either
using the "WIP" test distributions or one from the hg or git
repository from the development branch, please contact me
(tytso@mit.edu)
before you ship. The release schedules for this
package are flexible, if you give me enough lead time.

Theodore Ts'o
23-June-2007

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms
and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered
only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it
with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made
by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

5. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Program or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying or distributing
the Program (or any work based on the
Program), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the
Program), the recipient automatically receives a license from the
original licensor to copy, distribute or modify the Program subject to
these terms and conditions. You may not impose any further

restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy
simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous
contributions to the wide range of software distributed
through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such

new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software
and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a
subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for
all its users.

This license, the Library General Public License, applies to some
specially designated Free Software Foundation software, and to any
other libraries whose authors decide to use it. You can use it for
your libraries, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.

These restrictions translate to certain responsibilities for you if
you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a
fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link a program with the library, you must provide
complete object files to the recipients so that they can relink them
with the library, after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright
the library, and (2) offer you this license which gives you legal
permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain
that everyone understands that there is no warranty for this free
library. If the library is modified by someone else and passed on, we
want its recipients to know that what they have is not the original
version, so that any problems introduced by others will not reflect on
the original authors' reputations.

Finally, any free program
is threatened constantly by software
patents. We wish to avoid the danger that companies distributing free
software will individually obtain patent licenses, thus in effect
transforming the program into proprietary software. To prevent this,
we have made it clear that any patent must be licensed for everyone's
free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary
GNU General Public License, which was designed for utility programs. This
license, the GNU Library General Public License, applies to certain
designated libraries. This license is quite different from the ordinary
one; be sure to read it in full, and don't assume that anything in it is
the same as in the ordinary license.

The reason we have a separate public license for some libraries is that
they blur the distinction we usually make between modifying or adding to a
program and simply using it. Linking a program with a library, without
changing the library, is
in some sense simply using the library, and is
analogous to running a utility program or application program. However, in
a textual and legal sense, the linked executable is a combined work, a
derivative of the original library, and the ordinary General Public License
treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in
header files, but we have achieved it as regards
changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed
as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for

making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each
and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make
any other change in
these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or

derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled
to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library,
or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or
link a "work that uses the Library" with the Library to produce a
work containing portions of the Library, and distribute that work

under terms of your choice, provided that
the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of this License. Also, you must do one
of these things:

a) Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable "work that
uses the Library", as object code and/or source code, so that the
user can modify the Library and then
relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

d) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as
a special exception,
the source code distributed need not include anything that is normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that

everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms of the
ordinary General Public License).

 To apply these terms, attach the following notices to the library. It is
safest to attach them
 to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

  <one line to give the library's name and a brief idea of what it does.>
  Copyright (C) <year> <name of author>

  This library is free software; you can redistribute it and/or
  modify it under the terms of the GNU Library General Public
  License as published by the Free Software Foundation; either
  version 2 of the License, or (at your option) any later version.

  This library is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  Library General Public License for more details.

  You should have received a copy of the GNU Library General Public
  License along with this library; if not, write to the Free Software
  Foundation, Inc.,
 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the
 library `Frob' (a library for tweaking knobs) written by James Random Hacker.

 <signature of Ty Coon>, 1 April 1990
 Ty Coon, President of Vice

That's all there is to it!
This is the Debian GNU/Linux prepackaged version of the EXT2 file
system utilities (e2fsck, mke2fs, etc.). The EXT2 utilities were
written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from http://sourceforge.net/projects/e2fsprogs

Packaging is Copyright (c) 2003-2007 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <http://www.alcove.com/>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, are made available under the GNU General Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries
which are made available under an MIT-style license.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2'. The complete text of the GNU Library General Public License can be found in '/usr/share/common-licenses/LGPL-2'.

The license used for lib/et and lib/ss libraries is:

Copyright 1987 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose is hereby granted, provided that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T. S.I.P.B. make no representations about the suitability of this
software for any purpose. It is provided "as is" without express or implied warranty.

The license used for lib/uuid is:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety,

including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND
FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

http://sourceforge.net/projects/e2fsprogs

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2003, 2004 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific
prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This is the Debian GNU/Linux prepackaged version of the ss
command-line interface parsing library. It is currently
distributed together with the EXT2 file system utilities, which are
otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>,
from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board
 of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
M.I.T. and
 the M.I.T. S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.
This is the Debian GNU/Linux prepackaged version of the Common Error
Description library. It is currently distributed together with the EXT2 file
system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>,
from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
M.I.T. and the M.I.T.
S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

1.132 libtasn 4.16.0-9.el9

1.132.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,

not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using

a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other

program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be

linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any

such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system
which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO

WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU

Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of

interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not

convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or
modification of the work as a means of enforcing, against the work's
users, your or third parties' legal rights to forbid circumvention of
technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you
receive it, in any medium, provided that you conspicuously and
appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to

produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular

product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the

entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains

a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work

occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant

patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory

patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
 that patent license was granted, prior to 28 March 2007.

 Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

 12. No Surrender of Others' Freedom.

 If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

 13. Use with the GNU Affero General Public License.

  Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

 14. Revised Versions of this License.

 The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

 Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
 have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the

GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The ``Document'', below, refers
to any such manual or work. Any member of the public is a licensee, and is addressed as ``you''. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A ``Modified Version'' of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political
position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for

images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
ASCII without markup, Texinfo input format, La@TeX{} input
format, SGML or XML using a publicly available
DTD, and standard-conforming simple HTML,
PostScript or PDF designed for human modification. Examples
of transparent image formats include PNG, XCF and
JPG@. Opaque formats include proprietary formats that can be
read and edited only by proprietary word
processors, SGML or
XML for which the DTD and/or processing tools are
not generally available, and the machine-generated HTML,
PostScript or PDF produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means
the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'',
or ``History''.) To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which
states that this License applies to the Document. These Warranty
Disclaimers are considered to be included by reference in this
License, but only as regards disclaiming warranties: any other
implication that these Warranty Disclaimers may have is void and has

no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps,

when you begin distribution of Opaque copies in quantity, to ensure
that this Transparent copy will remain thus accessible at the stated
location until at least one year after the last time you distribute
 an
Opaque copy (directly or through your agents or retailers) of that
edition to the public.

It is requested, but not required, that you contact the authors of the
Document well before redistributing any large number of copies, to give
them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under
the conditions of sections 2 and 3 above, provided that you release
the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same
 title as a previous version
if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities
responsible for authorship of the modifications in the Modified
Version, together with at least five of the principal authors of the
Document (all of its principal authors, if it has fewer than five),
unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the
Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications
adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice
giving the public permission to use the Modified Version under the
terms of this License, in the form shown in the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the
Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add
to it an item stating at least the title, year, new authors, and
publisher of the Modified Version as given on the Title Page. If
there is no section Entitled ``History'' in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the ``History'' section.
You may omit a network location for a work that was published at
least four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any
section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item

Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document, you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant
 Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old
 one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single

copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if
 known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License
 into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate
and independent documents or works, in or on a volume of a storage or
distribution medium, is called an ``aggregate'' if the copyright
resulting from the compilation is not used to limit the legal rights
of the compilation's users beyond what the individual works permit.
When the Document is included in an aggregate, this License does not
apply to the other works in the aggregate which are not themselves
derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these
copies of the Document, then if the Document is less than one half of
the entire aggregate, the Document's Cover Texts may be placed on
covers that bracket the Document within the aggregate, or the
electronic equivalent of covers if the Document is in electronic
 form.
Otherwise they must appear on printed covers that bracket the whole

aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may
distribute translations of the Document under the terms of section 4.
Replacing Invariant Sections with translations requires special
permission from their copyright holders, but you may include
translations of some or all Invariant Sections in addition to the
original versions of these Invariant Sections. You may include a
translation of this License, and all the license notices in the
Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice
or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'',
``Dedications'', or ``History'', the requirement
 (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for
 any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the

licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and
 conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'') contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons
 Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License
 in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License''.
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts.''@: line with this:

@smallexample
@group
   with the Invariant Sections being @var{list their titles}, with
   the Front-Cover Texts being @var{list}, and with the Back-Cover Texts
   being @var{list}.
@end group
@end smallexample

If you have Invariant
 Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
LICENSING
=========

The libtasn1 library is released under the GNU Lesser General Public
License (LGPL) version 2.1 or later; see [COPYING.LESSER](doc/COPYING.LESSER)
for the license terms.

The GNU LGPL applies to the main libtasn1 library, while the
included applications library are under the GNU GPL version 3.
The libtasn1 library is located in the lib directory, while the applications
in src/.

The documentation in doc/ is under the GNU FDL license 1.3.

For any copyright year range specified as YYYY-ZZZZ in this package
note that the range specifies every single year in that closed interval.

1.133 librhsm 0.0.3-9.el9

1.133.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be

consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and

modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into
another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any

warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library

creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the

user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise

permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by

all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply,
and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system
 which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

 12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

 13. The Free Software Foundation may publish
 revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

 14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is

copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision
will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.134 rpm-libs 4.16.1.3-39.el9

1.134.1 Available under license :

RPM is covered under two separate licenses.

The entire code base may be distributed under the terms of the GNU General
Public License (GPL), which appears immediately below. Alternatively,
all of the source code in the lib and rpmio subdirectories of the RPM source
code distribution as well as any code derived from that code may instead be
distributed under the GNU Library General Public License (LGPL), at the
choice of the distributor. The complete text of the LGPL appears
at the bottom of this file.

This alternative is provided to enable applications to be linked against
the RPM library (commonly called librpm) without forcing such applications
to be distributed under the GPL.

Any questions regarding the licensing of RPM should be addressed to
rpm-maint@lists.rpm.org

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive
source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,

distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that
there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The
"Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy
an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third

parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute
them as separate works. But when you
distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under

the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under

this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original
licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy
both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing

to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be
a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that
version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF
ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,

REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to
Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY
WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991
Free Software Foundation, Inc.
675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the
freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know
their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some

libraries, is covered by the ordinary
GNU General Public License, which was designed for utility programs. This
license, the GNU Library General Public License, applies to certain
designated libraries. This license is quite different from the ordinary
one; be sure to read it in full, and don't assume that anything in it is
the same as in the ordinary license.

The reason we have a separate public license for some libraries is that
they blur the distinction we usually make between modifying or adding to a
program and simply using it. Linking a program with a library, without
changing the library, is in some sense simply using the library, and is
analogous to running a utility program or application program. However, in
a textual and legal sense, the linked executable is a combined work, a
derivative of the original library, and the ordinary General Public License
treats it as such.

Because of this blurred distinction, using the ordinary General
Public License for libraries did
not effectively promote software
sharing, because most developers did not use the libraries. We
concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the
users of those programs of all benefit from the free status of the
libraries themselves. This Library General Public License is intended to
permit developers of non-free programs to use free libraries, while
preserving your freedom as a user of such programs to change the free
libraries that are incorporated in them. (We have not seen how to achieve
this as regards changes in header files, but we have achieved it as regards
changes in the actual functions of the Library.) The hope is that this
will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains
code derived from the library, while the latter only
works together with the library.

Note that it is possible for a library to be covered by the ordinary
General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which
contains a notice placed by the copyright holder or other authorized
party saying it may be distributed under the terms of this Library

General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any
derivative work under
copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what
the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root
function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with
a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work.
(Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy

from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other
proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or

distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish revised and/or new
versions of the Library General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a
version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED
BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU

FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.135 libnettle6 3.10.1-1.el9

1.135.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the

source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt

otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made

generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.
                GNU GENERAL PUBLIC LICENSE
                 Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

                      Preamble

 The GNU General Public License is a free, copyleft license for
software and other kinds of works.

 The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the

GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of

software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If

the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying
the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF

SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new

free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official

standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product,

doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions.

Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further

restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or

run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor

version. For
purposes of this definition, "control" includes the right to grant
patent sublicenses in a manner consistent with the requirements of
this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free
patent license under the contributor's essential patent claims, to
make, use, sell, offer for sale, import and otherwise run, modify and
propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express
agreement or commitment, however denominated, not to enforce a patent
(such as an express permission to practice a patent or covenant not to
sue for patent infringement). To "grant" such a patent license to a
party means to make such an agreement or commitment not to enforce a
patent against the party.

If you convey a covered work, knowingly relying on a patent license,
and the Corresponding Source of the work is not available for anyone
to copy, free of charge and under the terms of this
License, through a
publicly available network server or other readily accessible means,
then you must either (1) cause the Corresponding Source to be so
available, or (2) arrange to deprive yourself of the benefit of the
patent license for this particular work, or (3) arrange, in a manner
consistent with the requirements of this License, to extend the patent
license to downstream recipients. "Knowingly relying" means you have
actual knowledge that, but for the patent license, your conveying the
covered work in a country, or your recipient's use of the covered work
in a country, would infringe one or more identifiable patents in that
country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or
arrangement, you convey, or propagate by procuring conveyance of, a
covered work, and grant a patent license to some of the parties
receiving the covered work authorizing them to use, propagate, modify
or convey a specific copy of the covered
work, then the patent license
you grant is automatically extended to all recipients of the covered
work and works based on it.

A patent license is "discriminatory" if it does not include within
the scope of its coverage, prohibits the exercise of, or is
conditioned on the non-exercise of one or more of the rights that are
specifically granted under this License. You may not convey a covered
work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying

the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered

version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see

<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <https://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data

and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying
Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure
layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of

the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the

Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

1.136 grep 3.6-5.el9

1.136.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of

protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy,
is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require,

such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to

the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent

works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source

may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded
from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,
procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the
Corresponding Source conveyed under this section must be accompanied
by the Installation Information. But this requirement does not apply
if neither you nor any third party retains the ability to install
modified object code on the User Product (for example, the work has

been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty
or limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your
license from a particular copyright holder is reinstated (a)
provisionally, unless and until the copyright holder explicitly and

finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have

permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS
THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.
/* Extract the last component (base name) of a file name.

Copyright (C) 1998, 2001, 2003-2006, 2009-2020 Free Software Foundation,
Inc.

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>. */

#ifndef _BASENAME_LGPL_H

```
#define _BASENAME_LGPL_H

#include <stddef.h>

#ifndef DOUBLE_SLASH_IS_DISTINCT_ROOT
# define DOUBLE_SLASH_IS_DISTINCT_ROOT 0
#endif

#ifdef __cplusplus
extern "C" {
#endif


/*
 Return the address of the last file name component of FILENAME.
  If FILENAME has some trailing slash(es), they are considered to be
  part of the last component.
  If FILENAME has no relative file name components because it is a file
  system root, return the empty string.
  Examples:
          FILENAME      RESULT
          "foo.c"       "foo.c"
          "foo/bar.c"   "bar.c"
          "/foo/bar.c"  "bar.c"
          "foo/bar/"    "bar/"
          "foo/bar//"   "bar//"
          "/"           ""
          "//"          ""
          ""            ""
  The return value is a tail of the given FILENAME; do NOT free() it!  */

/* This function was traditionally called 'basename', but we avoid this
  function name because
    * Various platforms have different functions in their libc.
      In particular, the glibc basename(), defined in <string.h>, does
      not consider trailing slashes to be part of the component:
          FILENAME
      RESULT
          "foo/bar/"    ""
          "foo/bar//"   ""
    * The 'basename' command eliminates trailing slashes and for a root
      produces a non-empty result:
          FILENAME      RESULT
          "foo/bar/"    "bar"
          "foo/bar//"   "bar"
          "/"           "/"
          "//"          "/"
*/
```

```
extern char *last_component (char const *filename) _GL_ATTRIBUTE_PURE;

/* Return the length of the basename FILENAME.
  Typically FILENAME is the value returned by base_name or last_component.
  Act like strlen (FILENAME), except omit all trailing slashes.  */
extern size_t base_len (char const *filename) _GL_ATTRIBUTE_PURE;


#ifdef __cplusplus
} /* extern "C" */
#endif

#endif /* _BASENAME_LGPL_H */
```

1.137 npth 1.6-8.el9

1.137.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide
to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,

not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using

a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other

program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses
the
library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be

linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object
code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the
work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least
three years, to give the same user the materials specified in
Subsection 6a, above, for a charge no more than the cost of
performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any

patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.138 libusbx 1.0.26-1.el9

1.138.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest
you first think carefully about whether
this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients
all the rights that we gave
you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence
of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits
its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use
the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a

"work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without
limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish
on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to

exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to
a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed
under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the

library". The executable is therefore covered by this
License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables
containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable
source code for the Library including whatever
changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood

that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user
installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to

refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our

decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should
also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.139 libstdc++ 11.5.0-11.el9

1.139.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software

patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it
becomes a de-facto standard. To achieve this, non-free programs must
be allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting the
free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the

users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains code derived from the library, whereas the latter must
be combined with the library in order to
run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other
program which contains a notice placed by the copyright holder or
other authorized party saying it may be distributed under the terms of
this Lesser General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly into another
language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control
compilation and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether that is true depends on what the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's

complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the
Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a
fee.

2. You may modify your copy or copies of the Library or any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no
charge to all third parties under the terms
of this License.

d) If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably
considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based

on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or

linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the

work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not

excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under
any particular circumstance, the balance of the section is intended to
apply, and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system
which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License
may add an explicit geographical distribution limitation excluding those
countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by

the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will
be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE
LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source file to most
effectively
convey the exclusion of warranty; and each file should
have at least the "copyright" line and a pointer to where the full
notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
This file contains a list of individuals who submit their patches to
the Cygwin sources under 2-clause BSD license, as well as a list of
individuals who signed the former Cygwin Copyright Assignment up to 2016.

==========

2-clause BSD:

==========

Copyright (c) <YEAR>, <OWNER>

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS
 OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
==========

Individuals submitting their patches under 2-clause BSD:

David Allsopp David.Allsopp@cl.cam.ac.uk
Erik M. Bray erik.bray@lri.fr
Brian Inglis Brian.Inglis@SystematicSw.ab.ca
Daniel Santos daniel.santos@pobox.com
Sergejs Lukanihins slukanihin@gmail.com
J.H.
 van de Water houder@xs4all.nl

==========

Individuals who signed the former Cygwin Copyright Assignment:

AJ Reins tbisp@qwest.net
Brian E. Dessent brian@dessent.net
Brian Kenneth Ford Brian.Ford@FlightSafety.com
Charles K. Moore keithmo@exmsft.com
Christian Franke franke@computer.org
Christian Lestrade christian.lestrade@free.fr
Christopher Faylor me@cgf.cx

Christopher January chris@atomice.net
Conrad Scott conrad.scott@dsl.pipex.com
Corinna Vinschen corinna@vinschen.de
Craig Iain McGeachie slapdau@yahoo.com.au
David Korn dave.korn.cygwin@gmail.com
Davis Euresti davie@alum.mit.edu
Dennis Vshivkov walrus@amur.ru
Elfyn McBratney elfyn@ubertales.co.uk
Eric Blake eblake@redhat.com
Ernie Coskrey ernie.coskrey@steeleye.com
Gerd Spalink Gerd.Spalink@t-online.de
Hartmut Honisch hhonisch@users.sourceforge.net
Igor Pechtchanski pechtcha@cs.nyu.edu
Jacek Trzcinski jacek@certum.pl
Jeffrey
Eric Altman jaltman@openafs.org
Jerry D. Hedden jerry@hedden.us
Joe Loh joel@pivot3.com
Johan Rydberg johan@rydberg.com
Johannes Schindelin johannes.schindelin@gmx.de
John Hood cgull@glup.org
Jon Turney jon.turney@dronecode.org.uk
Yoni Londner yonihola2@gmail.com
Joseph H. Buehler jbuehler@hekimian.com
Joshua Daniel Franklin joshuadfranklin@yahoo.com
Ken Brown kbrown@cornell.edu
Lapo Luchini lapo@lapo.it
Lev Bishop lev.bishop@gmail.com
Mark Geisert mark@maxrnd.com
Max Kaehn slothman@electric-cloud.com
Micha Nelissen mdvpost@hotmail.com
Michael Haubenwallner michael.haubenwallner@ssi-schaefer.com
Nicholas S. Wourms nwourms@netscape.com
Pavel Yonkov Tsekov ptsekov@gmx.net
Peter Foley pefoley2@pefoley.com
Pierre A. Humblet phumblet@phumblet.no-ip.org
Robert G. Byrnes byrnes@curl.com
Ryan C. Gordon icculus@icculus.org
Sam Steingold sds@gnu.org
Stephen Cleary shammah@spamcop.net
Stephen Osborn bub@io.com
Takashi
Yano takashi.yano@nifty.ne.jp
Thomas Pfaff tpfaff@gmx.net
Vaclav Haisman vhaisman@gmail.com
Yaakov Selkovitz yselkowi@redhat.com
Yitzchak Scott-Thoennes sthoenna@efn.org

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free

library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we
use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without
limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated

interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish
on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified
Library refers to a function or a
table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the

application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves,
 then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

 3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License
 to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

 Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

 This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

 4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which

must be
distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses the
library". The executable is therefore covered
by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6.
Any
executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or
link a "work that uses the Library" with the Library to produce a
work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse

engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is

normally distributed (in either source or binary form) with
the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other library
facilities. This must be distributed
under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying
or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the

Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many
people have made
generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line
and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You
should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade

names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a

file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
/* Copyright (C) 2013-2015 Free Software Foundation, Inc.

This file is part of GCC.

modify it under the terms of the GNU Library General Public License
as published by the Free Software Foundation; either version 2, or
(at your option) any later version.

In addition to the permissions in the GNU Library General Public
License, the Free Software Foundation gives you unlimited
permission to link the compiled version of this file into
combinations with other programs, and to distribute those
combinations without any restriction coming from the use of this
file. (The Library Public License restrictions do apply in other
respects; for example, they cover modification of the file, and
distribution when not linked into a combined executable.)

This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Library
General Public License for more details.

You should have received a copy of the GNU Library General Public
License along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street - Fifth Floor, Boston, MA
02110-1301, USA. */

#ifndef __VTV_H__
#define __VTV_H__

```
/* We could have used an enumeration here but it just makes it more
  difficult for the compiler to generate a call to this.  These are
  used as arguments to the function __VLTChangePermission, declared
  below.  */
#define __VLTP_READ_ONLY  0
#define __VLTP_READ_WRITE 1

#ifdef __cplusplus
extern "C" void __VLTChangePermission (int);
#else
extern void __VLTChangePermission (int);
#endif

#ifdef BIG_PAGE_SIZE
/* TODO - Replace '4096' below with correct big page size.  */
#define VTV_PAGE_SIZE 4096
#else
#if defined(__sun__) && defined(__svr4__) && defined(__sparc__)
#define VTV_PAGE_SIZE 8192
#else
#define VTV_PAGE_SIZE 4096
#endif
#endif



#endif /* __VTV_H__ */
```

DRuntime: Runtime Library for the D Programming Language

==========

Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED

"AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
The newlib subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source file. Unless otherwise noted in the body of the source file(s), the following copyright notices will apply to the contents of the newlib subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the BSD License. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at http://www.opensource.org/licenses. Any Red Hat trademarks that are incorporated in the source code or documentation are not subject to the BSD License and may only be used or replicated with the express permission
of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT

LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY
OF SUCH DAMAGE.

(3) David M. Gay (AT&T 1991, Lucent 1998)

The author of this software is David M. Gay.

Copyright (c) 1991 by AT&T.

Permission to use, copy, modify, and distribute this software for any
purpose without fee is hereby granted, provided that this entire notice
is included in all copies of any software which is or includes a copy
or modification of this software and in
all copies of the supporting
documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR AT&T MAKES ANY REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

The author of this software is David M. Gay.

Copyright (C) 1998-2001 by Lucent Technologies
All Rights Reserved

Permission to use, copy, modify, and distribute this software and
its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that the copyright notice and this
permission notice and warranty disclaimer appear in supporting
documentation, and that the name of Lucent or any of its entities
not be used in advertising or publicity pertaining to
distribution of the software without specific, written prior
permission.

LUCENT
DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS.
IN NO EVENT SHALL LUCENT OR ANY OF ITS ENTITIES BE LIABLE FOR ANY
SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER
IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF
THIS SOFTWARE.

(4) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which
specifically grants the user the right to modify, use and distribute this
software provided this notice is not removed or altered. All other rights
are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS
SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL
DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING,
PERFORMANCE, OR
USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the 29K Technical Support Center at
800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or
0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(5)

(6)

(7) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this

software is freely granted, provided that this notice is preserved.

(8) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:
  permission to use, copy, modify, and distribute this file
for any purpose is hereby
 granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(9) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is
freely granted, provided that the above copyright notice, this notice
and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE.

(10) Stephane Carrez (m68hc11-elf/m68hc12-elf targets only)

Copyright (C) 1999, 2000, 2001, 2002 Stephane Carrez (stcarrez@nerim.fr)

The authors hereby grant permission
 to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(11) Christopher G. Demetriou

Copyright (c) 2001 Christopher G. Demetriou
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice,
 this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) SuperH, Inc.

Copyright
 2002 SuperH, Inc. All rights reserved

This software is the property of SuperH, Inc (SuperH) which specifically
grants the user the right to modify, use and distribute this software
provided this notice is not removed or altered. All other rights are
reserved by SuperH.

SUPERH MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL SUPERH BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the SuperH Support Center via
e-mail at softwaresupport@superh.com .

SuperH, Inc.
405 River Oaks Parkway
San Jose

CA 95134
USA

(13) Royal Institute of Technology

Copyright (c) 1999 Kungliga Tekniska Hgskolan
(Royal Institute of Technology, Stockholm, Sweden).
All rights reserved.

Redistribution and use in source and binary
forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of KTH nor the names of its contributors may be
used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY KTH AND ITS CONTRIBUTORS ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL KTH OR ITS CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) Alexey Zelkin

Copyright (c) 2000, 2001 Alexey Zelkin <phantom@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS
``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(15) Andrey A. Chernov

Copyright (C) 1997 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(16)
FreeBSD

Copyright (c) 1997-2002 FreeBSD Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR
 SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(17) S. L. Moshier

Author: S. L. Moshier.

Copyright (c) 1984,2000 S.L. Moshier

Permission to use, copy, modify, and distribute this software for any
purpose without fee is hereby granted, provided that this entire notice
is included in all copies of any software which is or includes a copy
or modification of this software and in all copies of the supporting
documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
WARRANTY. IN PARTICULAR, THE AUTHOR MAKES NO REPRESENTATION
OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS
SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

(18) Citrus Project

Copyright (c)1999 Citrus Project,
All
 rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions

are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(19) Todd C. Miller

Copyright (c) 1998 Todd C. Miller <Todd.Miller@courtesan.com>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE
IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL
THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(20) DJ Delorie (i386 / arm)
Copyright (C) 1991 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted
provided that the above copyright notice and following paragraph are
duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even
the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(21) Free Software Foundation LGPL License (*-linux* targets only)

Copyright (C) 1990-1999, 2000, 2001 Free Software Foundation, Inc.
This file is part of the GNU C Library.
Contributed by Mark Kettenis <kettenis@phys.uva.nl>, 1997.

The GNU C Library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

The GNU C Library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with the GNU C Library; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA
02110-1301 USA.

(22) Xavier Leroy LGPL License (i[3456]86-*-linux* targets only)

Copyright (C) 1996 Xavier Leroy (Xavier.Leroy@inria.fr)

This program is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public License
as published by the Free Software Foundation; either version 2
of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

(23) Intel (i960)

Copyright (c) 1993 Intel Corporation

Intel hereby grants you permission to copy, modify, and distribute this
software and its documentation. Intel grants this permission provided
that the above copyright notice appears in all copies and that both the
copyright notice and this permission
 notice appear in supporting
documentation. In addition, Intel grants this permission provided that
you prominently mark as "not part of the original" any modifications
made to this software or documentation, and that the name of Intel
Corporation not be used in advertising or publicity pertaining to
distribution of the software or the documentation without specific,
written prior permission.

Intel Corporation provides this AS IS, WITHOUT ANY WARRANTY, EXPRESS OR
IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY
OR FITNESS FOR A PARTICULAR PURPOSE. Intel makes no guarantee or
representations regarding the use of, or the results of the use of,
the software and documentation in terms of correctness, accuracy,
reliability, currentness, or otherwise; and you rely on the software,
documentation and results solely at your own risk.

IN NO EVENT SHALL INTEL BE LIABLE FOR ANY LOSS OF USE, LOSS OF BUSINESS,
LOSS OF PROFITS, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL
 DAMAGES
OF ANY KIND. IN NO EVENT SHALL INTEL'S TOTAL LIABILITY EXCEED THE SUM
PAID TO INTEL FOR THE PRODUCT LICENSED HEREUNDER.

(24) Hewlett-Packard (hppa targets only)

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:
   permission to use, copy, modify, and distribute this file
for any purpose is hereby granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(25) Henry Spencer (only *-linux targets)

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.

This software is not subject to any license of the American Telephone
and Telegraph Company or of the
Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
explicit claim or by omission. Since few users ever read sources,
credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
misrepresented as being the original software. Since few users
ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

(26) Mike Barcroft

Copyright (c) 2001 Mike Barcroft <mike@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(27) Konstantin Chuguev (--enable-newlib-iconv)

Copyright (c) 1999, 2000
  Konstantin Chuguev. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR
 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

  iconv (Charset Conversion Library) v2.0

(28) Artem Bityuckiy (--enable-newlib-iconv)

Copyright (c) 2003, Artem B. Bityuckiy, SoftMine Corporation.
Rights transferred to Franklin Electronic Publishers.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(29) IBM, Sony, Toshiba (only spu-* targets)

(C) Copyright 2001,2006,
International Business Machines Corporation,
Sony Computer Entertainment, Incorporated,
Toshiba Corporation,

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the names of the copyright holders nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(30) - Alex Tatmanjants (targets using libc/posix)

Copyright (c) 1995 Alex Tatmanjants <alex@elvisti.kiev.ua>
at Electronni Visti IA, Kiev, Ukraine.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH
DAMAGE.

(31) - M. Warner Losh (targets using libc/posix)

Copyright (c) 1998, M. Warner Losh <imp@freebsd.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF

SUCH DAMAGE.

(32) - Andrey A. Chernov (targets using libc/posix)

Copyright (C) 1996 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other
materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(33) - Daniel Eischen (targets using libc/posix)

Copyright (c) 2001 Daniel Eischen <deischen@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification,
are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(34) - Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(35) - Arm Ltd

Copyright (c) 2009-2018 Arm Ltd
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer
in the
documentation and/or other materials provided with the distribution.
3. The name of the company may not be used to endorse or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY ARM LTD ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL ARM LTD BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(36) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright
(c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(37) Texas Instruments Incorporated (tic6x-*, *-tirtos targets)

Copyright (c) 1996-2010,2014 Texas Instruments Incorporated
http://www.ti.com/

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Texas Instruments Incorporated nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(38) National Semiconductor (cr16-* and crx-* targets)

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement,

license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(39) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary
forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
* Neither the name of Adapteva nor the names of its contributors may be used
to endorse or promote products derived from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(40) - Altera Corportion (nios2-* targets)

Copyright (c) 2003 Altera Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

- Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the

documentation and/or other materials provided with the distribution.
o Neither
the name of Altera Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ALTERA CORPORATION, THE COPYRIGHT HOLDER,
AND ITS CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL
THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(41) Ed Schouten - Free
BSD

Copyright (c) 2008 Ed Schouten <ed@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(42) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

 * Redistributions of source code must retain the above copyright notice,
   this list of conditions and the following disclaimer.
 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
 * Neither the name of Rolls-Royce Controls
 and Data Services Limited nor
   the names of its contributors may be used to endorse or promote products
   derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(43) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The
 authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(44) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2) Redistributions in binary form
must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE
OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(45) Phoenix Systems - Phoenix-RTOS targets

Copyright (c) 2016 Phoenix Systems
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(46) embedded brains - RTEMS targets

Copyright (c) 2017 embedded brains GmbH
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(47) John Baldwin - RTEMS targets

Copyright (c) 2015 John Baldwin <jhb@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software

without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(48) Jeffrey Roberson - RTEMS targets

Copyright (c) 2008, Jeffrey Roberson <jeff@freebsd.org>
All rights reserved.

Copyright (c) 2008 Nokia Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice unmodified, this list of conditions, and the following
disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED
BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(49) - SiFive Inc. (riscv-* targets)

Copyright (c) 2017 SiFive Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use,
modify, copy, or redistribute it subject to the terms and conditions
of the FreeBSD License.   This program is distributed in the hope that
it will be useful,
 but WITHOUT ANY WARRANTY expressed or implied,
including the implied warranties of MERCHANTABILITY or FITNESS FOR
A PARTICULAR PURPOSE. A copy of this license is available at
http://www.opensource.org/licenses.

(50) Michael R. Neilly (riscv-* targets)

(c) Copyright 2017 Michael R. Neilly
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* Neither the names of the copyright holders nor the names of their
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE
 IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

(51) Mentor Graphics (amdgcn-* targets)

Copyright (c) 2014-2017 Mentor Graphics.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices
 are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(52) BSD-2-Clause-FreeBSD (pru-* targets)

SPDX-License-Identifier: BSD-2-Clause-FreeBSD

Copyright (c) 2018-2019 Dimitar Dimitrov <dimitar@dinux.eu>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation
 and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
/**
* DISCLAIMER
* This file has no copyright assigned and is placed in the Public Domain.
*
* Its code is distributed in the hope that it will be useful but WITHOUT
* ANY WARRANTY. ALL WARRANTIES, EXPRESSED OR IMPLIED ARE HEREBY DISCLAIMED.
* This includes but is not limited to warranties of MERCHANTABILITY or
* FITNESS FOR A PARTICULAR PURPOSE.
*/

The libgloss subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source
file. Unless otherwise noted in the body of the source file(s), the following copyright
notices will apply to the contents of the libgloss subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify,
copy, or redistribute it subject to the terms and conditions of the BSD
License. This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties
of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license
is available at http://www.opensource.org/licenses. Any Red Hat trademarks that
are incorporated in the source code or documentation are not subject to the BSD
License and may only be used or replicated with the express
permission of
Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
* Neither the name of the University nor the names of its contributors may
be used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,

WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY
OF SUCH DAMAGE.

(3) DJ Delorie

Copyright (C) 1993 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted provided that the above copyright notice and following paragraph are duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(4) (formerly GPL for fr30)

The GPL is no longer applicable to the fr30 platform. The piece of code (syscalls.c) referencing the GPL has been officially relicensed.

(5) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the 29K Technical Support Center at 800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or 0031-11-1129 in
Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741

800-292-9263

(6) - Analog Devices, Inc. (bfin-* targets)

Copyright (C) 2006, 2008, 2009, 2011, 2012 Analog Devices, Inc.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(7) University of Utah and the Computer Systems Laboratory (CSL)
  [applies only to hppa*-*-pro* targets]
Copyright (c) 1990,1994
 The University of Utah and
the Computer Systems Laboratory (CSL). All rights reserved.

Permission to use, copy, modify and distribute this software is hereby
granted provided that (1) source code retains these copyright, permission,
and disclaimer notices, and (2) redistributions including binaries
reproduce the notices in supporting documentation, and (3) all advertising
materials mentioning features or use of this software display the following
acknowledgement: ``This product includes software developed by the
Computer Systems Laboratory at the University of Utah."

THE UNIVERSITY OF UTAH AND CSL ALLOW FREE USE OF THIS SOFTWARE IN ITS "AS
IS" CONDITION. THE UNIVERSITY OF UTAH AND CSL DISCLAIM ANY LIABILITY OF
ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

CSL requests users of this software to return to csl-dist@cs.utah.edu any
improvements that they make and grant CSL redistribution rights.

(8) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems,
 Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice is preserved.

(9) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:

permission to use, copy, modify, and distribute this file
for any purpose is hereby granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(10) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is
freely granted, provided that
the above copyright notice, this notice
and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE.

(11) IBM Corp. spu processor (only spu-* targets)

(C) Copyright IBM Corp. 2005, 2006

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
* Neither the name of IBM nor the names of its contributors may be
used to endorse or promote products derived
from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without
modification, are
permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(13) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright (c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

1. Redistributions source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of Xilinx nor the names of its contributors may be
used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) - National Semiconductor Corporation

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice
is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(15) - CodeSourcery, Inc. (tic6x-* targets)

Copyright (c) 2010 CodeSourcery, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
* Neither the name of CodeSourcery
nor the
names of its contributors may be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CODESOURCERY, INC. ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL CODESOURCERY BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16) - GPL with exception (sparc-*leon*, crx-*, cr16-* targets only)

Copyright (C) 1992 Free Software Foundation,
Inc.
Written By David Vinayak Henkel-Wallace, June 1992

This file is free software; you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by the
Free Software Foundation; either version 2, or (at your option) any
later version.

In addition to the permissions in the GNU General Public License, the
Free Software Foundation gives you unlimited permission to link the
compiled version of this file with other programs, and to distribute
those programs without any restriction coming from the use of this
file. (The General Public License restrictions do apply in other
respects; for example, they cover modification of the file, and
distribution when not linked into another program.)

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a
copy of the GNU General Public License
along with this program; see the file COPYING. If not, write to
the Free Software Foundation, 59 Temple Place - Suite 330,

Boston, MA 02111-1307, USA.

As a special exception, if you link this library with files
compiled with GCC to produce an executable, this does not cause
the resulting executable to be covered by the GNU General Public License.
This exception does not however invalidate any other reasons why
the executable file might be covered by the GNU General Public License.

(17) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,

this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
* Neither the name of Adapteva nor the names of its contributors may be used
to endorse or promote products derived from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(18) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,

this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
* Neither the name of Rolls-Royce Controls and Data Services Limited nor
the names of its contributors may be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT
HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and
that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(20) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2) Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names
of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(21) BSD-2-Clause-FreeBSD (pru-* targets)

SPDX-License-Identifier: BSD-2-Clause-FreeBSD

Copyright (c)
2018-2019 Dimitar Dimitrov <dimitar@dinux.eu>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
/* Copyright (C) 2013-2021 Free Software Foundation, Inc.

This file is part of GCC.

modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

In addition to the permissions in the GNU Library General Public License, the Free Software Foundation gives you unlimited permission to link the compiled version of this file into combinations with other programs, and to distribute those combinations without any restriction coming from the use of this file. (The Library Public License restrictions do apply in other respects; for example, they cover modification of the file, and distribution when not linked into a combined executable.)

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library

General Public License for more details.

You should have received a copy of the GNU Library General Public
License along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street - Fifth Floor, Boston, MA
02110-1301, USA. */

```
#ifndef __VTV_H__
#define __VTV_H__

/* We could have used an enumeration here but it just makes it more
  difficult for the compiler to generate a call to this.  These are
  used as arguments to the function __VLTChangePermission, declared
  below.  */
#define __VLTP_READ_ONLY  0
#define __VLTP_READ_WRITE 1

#ifdef __cplusplus
extern "C" void __VLTChangePermission (int);
#else
extern void __VLTChangePermission (int);
#endif

#ifdef BIG_PAGE_SIZE
/* TODO - Replace '4096' below with correct big page size.  */
#define VTV_PAGE_SIZE 4096
#else
#if defined(__sun__) && defined(__svr4__) && defined(__sparc__)
#define VTV_PAGE_SIZE 8192
#else
#define VTV_PAGE_SIZE 4096
#endif
#endif



#endif /* __VTV_H__ */
```

/* Definitions for BSD assembler syntax for Intel 386
  (actually AT&T syntax for insns and operands,
  adapted to BSD conventions for symbol names and debugging.)
  Copyright (C) 1988-2021 Free Software Foundation, Inc.

This file is part of GCC.

GCC is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3, or (at your option)

```
any later version.

GCC is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with GCC; see the file COPYING3.  If not see
<http://www.gnu.org/licenses/>.  */

/* Use the Sequent Symmetry assembler syntax.  */

/* Define the syntax of pseudo-ops, labels and comments.  */

/* Prefix for internally generated assembler
 labels.  If we aren't using
  underscores, we are using prefix `.'s to identify labels that should
  be ignored, as in `i386/gas.h' --karl@cs.umb.edu  */

#define LPREFIX "L"

/* Assembler pseudos to introduce constants of various size.  */

#define ASM_BYTE "\t.byte\t"
#define ASM_SHORT "\t.word\t"
#define ASM_LONG "\t.long\t"
#define ASM_QUAD "\t.quad\t"  /* Should not be used for 32bit compilation.  */

/* This was suggested, but it shouldn't be right for DBX output. -- RMS
  #define ASM_OUTPUT_SOURCE_FILENAME(FILE, NAME) */


/* Define the syntax of labels and symbol definitions/declarations.  */

/* This is how to output an assembler line
  that says to advance the location counter by SIZE bytes.  */

#define ASM_OUTPUT_SKIP(FILE,SIZE)  \
 fprintf (FILE, "\t.space " HOST_WIDE_INT_PRINT_UNSIGNED"\n", (SIZE))

/* Define the syntax of labels and symbol definitions/declarations.  */

/* This says how to output an assembler line
  to define a global common symbol.  */

#define
```

```
 ASM_OUTPUT_COMMON(FILE, NAME, SIZE, ROUNDED)  \
( fputs (".comm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u\n", (int)(ROUNDED)))

/* This says how to output an assembler line
  to define a local common symbol.  */

#define ASM_OUTPUT_LOCAL(FILE, NAME, SIZE, ROUNDED)  \
( fputs (".lcomm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u\n", (int)(ROUNDED)))

#ifdef HAVE_GAS_LCOMM_WITH_ALIGNMENT
#define ASM_OUTPUT_ALIGNED_LOCAL(FILE, NAME, SIZE, ALIGNMENT)  \
( fputs (".lcomm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u,%u\n", (int)(SIZE), (int)(ALIGNMENT) / BITS_PER_UNIT))
#endif

/* This is how to output an assembler line
  that says to advance the location counter
  to a multiple of 2**LOG bytes.  */

#define ASM_OUTPUT_ALIGN(FILE,LOG) \
 if ((LOG)!=0) fprintf ((FILE), "\t.align %d\n", (LOG))

/* This is how to store into the string BUF
  the symbol_ref name of an internal numbered label
 where
  PREFIX is the class of label and NUM is the number within the class.
  This is suitable for output with `assemble_name'.  */

#define ASM_GENERATE_INTERNAL_LABEL(BUF,PREFIX,NUMBER) \
   sprintf ((BUF), "*%s%ld", (PREFIX), (long)(NUMBER))

/* The prefix to add to user-visible assembler symbols.  */

#define USER_LABEL_PREFIX "_"

/* Sequent has some changes in the format of DBX symbols.  */
#define DBX_NO_XREFS 1

/* Don't split DBX symbols into continuations.  */
#define DBX_CONTIN_LENGTH 0
```

```
================================================================================
compiler_rt License
================================================================================
```

The compiler_rt library is dual licensed under both the University of Illinois
"BSD-Like" license and the MIT license. As a user of this code you may choose
to use it under either license. As a contributor, you agree to allow your code
to be used under both.

Full text of the relevant licenses is included below.

==

University of Illinois/NCSA
Open Source License

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:

  LLVM Team

  University of Illinois at Urbana-Champaign

  http://llvm.org

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal with
the Software without restriction,
 including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

  * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the following disclaimers.

  * Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the following disclaimers in the
    documentation and/or other materials provided with the distribution.

  * Neither the names of the LLVM Team, University of Illinois at
    Urbana-Champaign, nor the names of its contributors may be used to
    endorse or promote products derived from this Software without specific
    prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

==========

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or
substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

==========
Copyrights and Licenses for Third Party Software Distributed with LLVM:
==========
The LLVM software contains code written by third parties. Such software will
have its own individual LICENSE.TXT file in the directory in which it appears.
This file will describe the copyrights, license, and restrictions which apply
to that code.

The disclaimer of
warranty in the University of Illinois Open Source License
applies to all code in the LLVM Distribution, and nothing in any of the
other licenses gives permission to use the names of the LLVM Team or the
University of Illinois to endorse or promote products derived from this
Software.

The following pieces of software have additional or alternate copyrights,
licenses, and/or restrictions:

Program Directory
------- ---------
mach_override lib/interception/mach_override
@node Library Copying
@appendixsec GNU LESSER GENERAL PUBLIC LICENSE

@cindex LGPL, Lesser General Public License
@center Version 2.1, February 1999

@display
Copyright @copyright{} 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street - Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]
@end display

@appendixsubsec Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software---to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software---typically libraries---of
the Free
Software Foundation and other authors who decide to use it. You can use
it too, but we suggest you first think carefully about whether this
license or the ordinary General Public License is the better strategy to
use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of it
in new free programs; and that you are informed that you can do these
things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems
that might be
introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library.
The ordinary
General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the @dfn{Lesser} General Public License because it does @emph{Less} to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages

are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free
libraries. In this
case, there is little to gain by limiting the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
``work based on the library'' and a ``work that uses the library''. The
former contains code derived from the
library, whereas the latter must
be combined with the library in order to run.

@iftex
@appendixsubsec TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
@end iftex
@ifinfo
@center GNU LESSER GENERAL PUBLIC LICENSE
@center TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
@end ifinfo

@enumerate 0
@item
This License Agreement applies to any software library or other program
which contains a notice placed by the copyright holder or other
authorized party saying it may be distributed under the terms of this
Lesser General Public License (also called ``this License''). Each
licensee is addressed as ``you''.

A ``library'' means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The ``Library'', below, refers to any such software library or work which has been distributed under these terms. A ``work based on the Library'' means
either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term ``modification''.)

``Source code'' for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether
that is true depends on what the Library does
and what the program that uses the Library does.

@item
You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

@item
You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

@enumerate a

@item
The modified work must itself be a software library.

@item
You must cause
the files modified to carry prominent notices
stating that you changed the files and the date of any change.

@item
You must cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

@item
If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still
compute square roots.)
@end enumerate

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work

based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

@item
You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

@item
You may copy and distribute the Library
(or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

@item
A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a ``work that uses the Library''. Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However,
linking a ``work that uses the Library'' with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a ``work that uses the
library''. The executable is therefore covered by this License.

Section 6 states terms for distribution of such executables.

When a ``work that uses the Library'' uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work.
(Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

@item
As an exception to the Sections above, you may also combine or link a ``work that uses the Library'' with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices,
you must include the
copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

@enumerate a
@item
Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable ``work that uses the Library'', as object code and/or source code, so that the user can modify the Library and then relink to produce a modified

executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

@item
Use a suitable shared library mechanism for linking with the Library. A
suitable mechanism is one that (1) uses at run time
 a copy of the
library already present on the user's computer system, rather than
copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs
one, as long as the modified version is interface-compatible with the
version that the work was made with.

@item
Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

@item
If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

@item
Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.
@end enumerate

 For an executable, the required form of the ``work that uses the
Library'' must include any data and utility programs needed for
reproducing
 the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies the
executable.

 It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

@item

You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that
 you do these two things:

@enumerate a
@item
Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

@item
Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.
@end enumerate

@item
You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

@item
You are not required to accept this License, since you have not
signed it. However,
 nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

@item
Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with

this License.

@item
If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions
 are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims
 or to contest validity of any
such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

@item
If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded.
 In such case, this License incorporates the limitation as if written in the body of this License.

@item
The Free Software Foundation may publish revised and/or new

versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
``any later version'', you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

@item
If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software
which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

@center NO WARRANTY

@item
BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY ``AS IS'' WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item
IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED
TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.

@end enumerate

@iftex
@heading END OF TERMS AND CONDITIONS
@end iftex
@ifinfo
@center END OF TERMS AND CONDITIONS
@end ifinfo

@page
@appendixsubsec How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively,
under the terms of the
ordinary General Public License).

To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
``copyright'' line and a pointer to where the full notice is found.

@smallexample
@var{one line to give the library's name and an idea of what it does.}
Copyright (C) @var{year} @var{name of author}

This library is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 2.1 of the License, or (at
your option) any later version.

This library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should
have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301,
USA.
@end smallexample

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your

school, if any, to sign a ``copyright disclaimer'' for the library, if
necessary. Here is a sample; alter the names:

@smallexample
Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

@var{signature of Ty Coon}, 1 April 1990
Ty Coon, President of Vice
@end smallexample

That's all there is to it!
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the

source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work
which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim
copies of the Program's
source code as you receive it, in any medium, provided that you

conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably
considered independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or

collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.
Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free
redistribution of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the

integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version
number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE
LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES

PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute it
  under certain conditions; type `show c' for details.

The hypothetical commands
 `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

This program, "bzip2", the associated library "libbzip2", and all
documentation, are copyright (C) 1996-2010 Julian R Seward. All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must

not claim that you wrote the original software. If you use this
software in a product, an acknowledgment in the product
documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote
products derived from this software without specific
prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org
bzip2/libbzip2 version 1.0.6 of 6 September 2010

MIT License (MIT)

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
 USE OR OTHER DEALINGS IN THE
SOFTWARE.

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

=-=-=-

* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)COPYRIGHT 8.1 (Berkeley) 3/16/94
*/

==

The LLVM Project is under the Apache License v2.0 with LLVM Exceptions:

==

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the
power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached

to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative
Works of,
publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work
includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional
attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License
does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including
negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such
obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason

of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

---- LLVM Exceptions to the Apache 2.0 License ----

As an exception, if, as a result of your compiling your source code, portions
of this Software are embedded into an Object form of such source code, you
may redistribute such embedded portions in such Object form without complying
with the conditions of Sections 4(a), 4(b) and 4(d) of the License.

In addition, if you combine or link compiled
forms of this Software with
software that is licensed under the GPLv2 ("Combined Software") and if a
court of competent jurisdiction determines that the patent provision (Section
3), the indemnity provision (Section 9) or other Section of the License
conflicts with the conditions of the GPLv2, you may retroactively and
prospectively choose to deem waived or otherwise exclude such Section(s) of
the License, but only in their entirety and only with respect to the Combined
Software.

==========

Software from third parties included in the LLVM Project:
==
The LLVM Project contains third party software which is under different license
terms. All such code will be identified clearly using at least one of two
mechanisms:
1) It will be in a separate directory tree with its own `LICENSE.txt` or
  `LICENSE` file at the top containing the specific
 license and restrictions
  which apply to that software, or
2) It will contain specific license and restriction terms at the top of every
  file.

==
Legacy LLVM License (https://llvm.org/docs/DeveloperPolicy.html#legacy):
==

The software contained in this directory tree is dual licensed under both the
University of Illinois "BSD-Like" license and the MIT license. As a user of
this code you may choose to use it under either license. As a contributor,
you agree to allow your code to be used under both.

Full text of the relevant licenses is included below.

==

University of Illinois/NCSA
Open Source License

Copyright (c) 2017-2019 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:
  Threading Runtimes Team
  Intel Corporation
   http://www.intel.com

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal with
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

  * Redistributions of source code must retain the above copyright notice,
    this list of conditions and the following disclaimers.

  * Redistributions in binary form must reproduce the above copyright notice,

this list of conditions and the following disclaimers in the
documentation and/or other materials provided with the distribution.

* Neither the names of Intel Corporation Threading Runtimes Team nor the
names of its contributors may be used to endorse or promote products
derived from
this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

==========

Copyright (c) 2017-2019 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software,
and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including

the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
GCC RUNTIME LIBRARY EXCEPTION

Version 3.1, 31 March 2009

Copyright (C) 2009 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this
license document, but changing it is not allowed.

This GCC Runtime Library Exception ("Exception") is an additional
permission under section 7 of the GNU General Public License, version
3 ("GPLv3"). It applies to a given file (the "Runtime Library") that
bears a notice placed by the copyright holder of the file stating that
the file is governed by GPLv3 along with this Exception.

When you use GCC to compile a program, GCC may combine portions of
certain GCC header files and runtime libraries with the compiled
program. The purpose of this Exception is to allow compilation of
non-GPL (including proprietary) programs to use, in this way, the
header files and runtime libraries covered by this Exception.

0. Definitions.

A file is an "Independent Module" if it either requires the Runtime
Library
for execution after a Compilation Process, or makes use of an
interface provided by the Runtime Library, but is not otherwise based
on the Runtime Library.

"GCC" means a version of the GNU Compiler Collection, with or without
modifications, governed by version 3 (or a specified later version) of
the GNU General Public License (GPL) with the option of using any
subsequent versions published by the FSF.

"GPL-compatible Software" is software whose conditions of propagation, modification and use would permit combination with GCC in accord with the license of GCC.

"Target Code" refers to output from any compiler for a real or virtual target processor architecture, in executable form or suitable for input to an assembler, loader, linker and/or execution phase. Notwithstanding that, Target Code does not include data in any format that is used as a compiler intermediate representation, or used for producing a compiler intermediate representation.

The "Compilation Process" transforms code entirely represented in non-intermediate languages designed for human-written code, and/or in Java Virtual Machine byte code, into Target Code. Thus, for example, use of source code generators and preprocessors need not be considered part of the Compilation Process, since the Compilation Process can be understood as starting with the output of the generators or preprocessors.

A Compilation Process is "Eligible" if it is done using GCC, alone or with other GPL-compatible software, or if it is done without using any work based on GCC. For example, using non-GPL-compatible Software to optimize any GCC intermediate representations would not qualify as an Eligible Compilation Process.

1. Grant of Additional Permission.

You have permission to propagate a work of Target Code formed by combining the Runtime Library with Independent Modules, even if such propagation would otherwise violate the terms of GPLv3, provided that all Target Code was generated by Eligible Compilation Processes. You may then convey such a combination under terms of your choice, consistent with the licensing of the Independent Modules.

2. No Weakening of GCC Copyleft.

The availability of this Exception does not imply any general presumption that third-party software is unaffected by the copyleft requirements of the license of GCC.
THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Unless stated otherwise, the sources under the cygwin subdirectory, as well as the sources under the cygserver subdirectory linked into the Cygwin DLL, are licensed under the Lesser Gnu Public License,

version 3 or (at your option) any later version (LGPLv3+). See the COPYING.LIB file for the exact wording of that license.

Unless stated otherwise, the sources under the cygserver subdir not linked into the Cygwin DLL, as well as the sources under the lsaauth and the utils subdirectories are licensed under the Gnu Public License, version 3 or (at your option) any later version (GPLv3+). See the COPYING file for the exact wording of that license.

Parts of the sources in any subdirectory are licensed using a BSD-like license. The affected source files contain explicit copyright notices to that
effect.

Linking Exception:

As a special exception, the copyright holders of the Cygwin library grant you additional permission to link libcygwin.a, crt0.o, and gcrt0.o with independent modules to produce an executable, and to convey the resulting executable under terms of your choice, without any need to comply with the conditions of LGPLv3 section 4. An independent module is a module which is not itself based on the Cygwin library.
This is the file "copying.dj". It does not apply to any sources copyrighted by UCB Berkeley or the Free Software Foundation.

Copyright Information for sources and executables that are marked
Copyright (C) DJ Delorie
24 Kirsten Ave
Rochester NH 03867-2954

This document is Copyright (C) DJ Delorie and may be distributed verbatim, but changing it is not allowed.

Source code copyright DJ Delorie is distributed under the terms of the GNU General Public Licence, with the following exceptions:

* Any existing copyright or authorship information in any given source file must remain intact. If you modify a source file, a notice to that effect must be added to the authorship information in the source file.

* binaries provided in djgpp may be distributed without sources ONLY if the recipient is given sufficient information to obtain a copy of djgpp themselves. This primarily applies to go32.exe, emu387, stub.exe, and the graphics drivers.

* modified versions of the binaries provided

in djgpp must be
distributed under the terms of the GPL.

* objects and libraries linked into an application may be distributed
without sources.

Changes to source code copyright BSD or FSF are copyright DJ Delorie, but
fall under the terms of the original copyright.

A copy of the file "COPYING" is included with this document. If you did not
receive a copy of "COPYING", you may obtain one from whence this document
was obtained, or by writing:
    Free Software Foundation
    675 Mass Ave
    Cambridge, MA 02139
    USA
libffi - Copyright (c) 1996-2014 Anthony Green, Red Hat, Inc and others.
See source files for details.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
``Software''), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
                GNU LESSER GENERAL PUBLIC LICENSE
                  Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to

ensure that, in the event an Application does not supply the
function or data, the facility still operates, and performs
whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of
this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from
a header file that is part of the Library. You may convey such object
code under terms of your choice, provided that, if the incorporated
material is not limited to numerical parameters,
data structure
layouts and accessors, or small macros, inline functions and templates
(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the
Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license
document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that,
taken together, effectively do not restrict modification of the
portions of the Library contained in the Combined Work and reverse
engineering for debugging such modifications, if you also do each of
the following:

a) Give prominent notice with each copy of the Combined Work that
the Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license
document.

c) For a Combined Work that
displays copyright notices during
execution, include the copyright notice for the Library among
these notices, as well as a reference directing the user to the
copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this

License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new

versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the
Library as you received it specifies that a certain numbered version
of the GNU Lesser General Public License "or any later version"
applies to it, you have the option
of following the terms and
conditions either of that published version or of any later version
published by the Free Software Foundation. If the Library as you
received it does not specify a version number of the GNU Lesser
General Public License, you may choose any version of the GNU Lesser
General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide
whether future versions of the GNU Lesser General Public License shall
apply, that proxy's public statement of acceptance of any version is
permanent authorization for you to choose that version for the
Library.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that

is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other
than the work as a whole, that (a) is included in the normal form of
packaging a Major Component, but which is not part of that Major
Component, and (b) serves only to enable use of the work with that
Major Component, or to implement a Standard Interface for which an
implementation is available to the public in source code form. A
"Major Component", in this context, means a major essential component
(kernel, window system, and so on) of the specific operating system
(if any) on which the executable work runs, or a compiler used to
produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all
the source code needed to generate, install, and (for an executable
work) run the object code and to modify the work, including scripts to
control those activities. However, it does not include the work's
System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but
which are not part of the work. For example, Corresponding Source
includes interface definition files associated with source files for
the work, and the source code for shared libraries and dynamically
linked subprograms that the work is specifically designed to require,
such as by intimate data communication or control flow between those
subprograms and other parts of the work.

The Corresponding Source need not include anything that users
can regenerate automatically from other parts of the Corresponding
Source.

The Corresponding Source for a work in source code form is that
same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of
copyright on the Program, and are irrevocable provided the stated
conditions are met. This License explicitly affirms your unlimited
permission to run the unmodified Program. The output from running a
covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains

in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the

terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product

(including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a

typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the

entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains

a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work

occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant

patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory

patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
 that patent license was granted, prior to 28 March 2007.

 Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

 12. No Surrender of Others' Freedom.

 If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

 13. Use with the GNU Affero General Public License.

  Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

 14. Revised Versions of this License.

 The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

 Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
 have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the

GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU LIBRARY GENERAL PUBLIC LICENSE

****

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place -- Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

========

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object
files to the recipients so that they can relink them
with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into
proprietary software. To prevent this,
we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative
of the original library,
and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We

concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running
a program using the Library is not restricted, and
output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or
any portion
of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a. The modified work must itself be a software library.

b. You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c. You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d. If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and

performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the

application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable

source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work

under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a.
Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b. Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of

performing this distribution.

c. If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d. Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries
that do not normally
accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a. Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b. Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License
to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the

Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously

your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by
public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software
Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT
UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries
==========

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution
under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

ONE LINE TO GIVE THE LIBRARY'S NAME AND AN IDEA OF WHAT IT DOES.
Copyright (C) YEAR NAME OF AUTHOR

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

SIGNATURE OF TY COON, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying
Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure
layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license

document.

c) For a Combined Work that displays copyright
notices during
execution, include the copyright notice for the Library among
these notices, as well as a reference directing the user to the
copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this
License, and the Corresponding Application Code in a form
suitable for, and under terms that permit, the user to
recombine or relink the Application with a modified version of
the Linked Version to produce a modified Combined Work, in the
manner specified by section 6 of the GNU GPL for conveying
Corresponding Source.

1) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (a) uses at run time
a copy of the Library already present on the user's computer
system, and (b) will operate properly with a modified version
of the Library that is interface-compatible
with the Linked
Version.

e) Provide Installation Information, but only if you would otherwise
be required to provide such information under section 6 of the
GNU GPL, and only to the extent that such information is
necessary to install and execute a modified version of the
Combined Work produced by recombining or relinking the
Application with a modified version of the Linked Version. (If
you use option 4d0, the Installation Information must accompany
the Minimal Corresponding Source and Corresponding Application
Code. If you use option 4d1, you must provide the Installation
Information in the manner specified by section 6 of the GNU GPL
for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the
Library side by side in a single library together with other library
facilities that are not Applications and are not covered by this
License, and convey such a combined library under
terms of your
choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based

on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/. Unicode Data Files do not include PDF online code charts under the directory http://www.unicode.org/Public/. Software includes any source code published in the Unicode Standard or under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode,
Inc. All rights reserved. Distributed under
the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software
that the data or
software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.
Copyright (c) 2019 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from

this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.140 glibc 2.34-231.el9_7.2

1.140.1 Available under license :

@c The GNU Lesser General Public License.
@center Version 2.1, February 1999

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]
@end display

@subheading Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software---to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software---typically
libraries---of the Free
Software Foundation and other authors who decide to use it. You can use

it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library
or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation
will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and

is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative
of the original library. The ordinary
General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the @dfn{Lesser} General Public License because it does @emph{Less} to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the
same job as widely used non-free libraries. In this
case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a ``work based on the library'' and a ``work that uses the library''. The former
contains code derived from the library, whereas the latter must be combined with the library in order to run.

@subheading TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

@enumerate 0
@item
This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called ``this License''). Each licensee is addressed as ``you''.

A ``library'' means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The ``Library'', below, refers to any such software library or work which has been distributed under these terms. A ``work based on the Library'' means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it,
either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term ``modification''.)

``Source code'' for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

@item
You may copy and distribute
verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a
fee.

@item
You may modify your copy or copies of the Library or any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

@enumerate a
@item
The modified work must itself be a software library.

@item
You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

@item
You must
cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

@item
If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)
@end enumerate

These requirements apply to the modified work as a whole. If
identifiable sections
of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of

this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this
License.

@item
You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

@item
You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and
2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

@item

A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a ``work that uses the Library''. Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a ``work that uses the Library'' with the Library
creates an executable that is a derivative of the Library (because
it
contains portions of the Library), rather than a ``work that uses the
library''. The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a ``work that uses the Library'' uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise,
if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

@item
As an exception to the Sections above, you may also combine or
link a ``work that uses the Library'' with the Library to produce a
work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of

this License. Also, you must do one
of these things:

@enumerate a
@item
Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable ``work that
uses the Library'', as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

@item
Use a suitable shared library mechanism for linking with the Library. A
suitable mechanism is one that (1) uses at run time a copy of the
library already present on the user's computer system, rather than
copying library functions into the executable,
and (2) will operate
properly with a modified version of the library, if the user installs
one, as long as the modified version is interface-compatible with the
version that the work was made with.

@item
Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

@item
If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

@item
Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.
@end enumerate

For an executable, the required form of the ``work that uses the
Library'' must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that

is
normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

@item
You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

@enumerate a
@item
Accompany the combined library with a copy of the same work based on the Library,
uncombined with any other library
facilities. This must be distributed under the terms of the Sections above.

@item
Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.
@end enumerate

@item
You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

@item
You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited

by law if you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

@item
Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.

@item
If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License,
 they do not
excuse you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply,
and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software
 distribution system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

@item
If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

@item
The Free Software Foundation
 may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
``any later version'', you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

@item
If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for
 this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

@center @b{NO WARRANTY}

@item
BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY ``AS IS'' WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item
IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
 BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.
@end enumerate

@subheading END OF TERMS AND CONDITIONS

@page
@subheading How to Apply These Terms to Your New Libraries

 If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms of the
ordinary General Public License).

 To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source
 file to most effectively
convey the exclusion of warranty; and each file should have at least the
``copyright'' line and a pointer to where the full notice is found.

@smallexample
@var{one line to give the library's name and an idea of what it does.}
Copyright (C) @var{year} @var{name of author}

This library is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 2.1 of the License, or (at
your option) any later version.

This library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software

Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301,
USA.
@end
smallexample

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a ``copyright disclaimer'' for the library, if
necessary. Here is a sample; alter the names:

@smallexample
Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

@var{signature of Ty Coon}, 1 April 1990
Ty Coon, President of Vice
@end smallexample

That's all there is to it!
Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
explicit claim or by omission. Since few users ever read sources,
credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
misrepresented as being the original software. Since few users
ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third

parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further

restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will

be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program

`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these

rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it

does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the

terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the
 library `Frob' (a library for tweaking knobs) written by James Random Hacker.

 <signature of Ty Coon>, 1 April 1990
 Ty Coon, President of Vice

That's all there is to it!
UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories
http://www.unicode.org/Public/, http://www.unicode.org/reports/, and
http://www.unicode.org/cldr/data/. Unicode Data Files do not include PDF
online code charts under the directory http://www.unicode.org/Public/.
Software includes any source code published in the Unicode Standard or under
the directories http://www.unicode.org/Public/,
http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.

NOTICE TO USER: Carefully read the following legal agreement. BY
DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES
("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND
AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF
YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA
FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode,
Inc. All rights reserved. Distributed under
the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining a
copy of the Unicode data files and any associated documentation (the "Data
Files") or Unicode software and any associated documentation (the "Software")
to deal in the Data Files or Software without restriction, including without
limitation the rights to use, copy, modify, merge, publish, distribute, and/or
sell copies of the Data Files or Software, and to permit persons to whom the
Data Files or Software are furnished to do so, provided that (a) the above
copyright notice(s) and this permission notice appear with all copies of the
Data Files or Software, (b) both the above copyright notice(s) and this
permission notice appear in associated documentation, and (c) there is clear
notice in each modified Data File or in the Software as well as in the
documentation associated with the Data File(s) or Software
 that the data or
software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.
This file contains the copying permission notices for various files in the GNU C Library distribution that have copyright owners other than the Free Software Foundation. These notices all require that a copy of the notice be included in the accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

All code incorporated from 4.4 BSD is distributed under the following license:

Copyright (C) 1991 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. [This condition was removed.]
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF
SUCH DAMAGE.

The DNS resolver code, taken from BIND 4.9.5, is copyrighted by UC Berkeley, by Digital Equipment Corporation and by Internet Software Consortium. The DEC portions are under the following license:

Portions Copyright (C) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies, and that the name of Digital Equipment Corporation not be used in advertising or publicity pertaining to distribution of the document or software without specific, written prior permission.

THE SOFTWARE IS PROVIDED ``AS IS" AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING
FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The ISC portions are under the following license:

Portions Copyright (c) 1996-1999 by Internet Software Consortium.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING

OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The Sun RPC support (from rpcsrc-4.0) is covered by the following license:

Copyright (c) 2010, Oracle America, Inc.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of the "Oracle America, Inc." nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following CMU license covers some of the support code for Mach, derived from Mach 3.0:

Mach Operating System
Copyright (C) 1991,1990,1989 Carnegie Mellon University
All Rights Reserved.

Permission to use, copy, modify and distribute this software and its documentation is hereby granted, provided that
both the copyright
notice and this permission notice appear in all copies of the

software, derivative works or modified versions, and any portions
thereof, and that both notices appear in supporting documentation.

CARNEGIE MELLON ALLOWS FREE USE OF THIS SOFTWARE IN ITS ``AS IS''
CONDITION. CARNEGIE MELLON DISCLAIMS ANY LIABILITY OF ANY KIND FOR
ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

Carnegie Mellon requests users of this software to return to

Software Distribution Coordinator
School of Computer Science
Carnegie Mellon University
Pittsburgh PA 15213-3890

or Software.Distribution@CS.CMU.EDU any improvements or
extensions that they make and grant Carnegie Mellon the rights to
redistribute these changes.

The file if_ppp.h is under the following CMU license:

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the
 above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors
   may be used to endorse or promote products derived from this software
   without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CARNEGIE MELLON UNIVERSITY AND
CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE UNIVERSITY OR CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
 BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN
IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following license covers the files from Intel's "Highly Optimized

Mathematical Functions for Itanium" collection:

Intel License Agreement

Copyright (c) 2000, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* The name of Intel Corporation may not be used to endorse
or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The files inet/getnameinfo.c and sysdeps/posix/getaddrinfo.c are copyright
(C) by Craig Metz and are distributed under the following license:

/* The Inner Net License,
Version 2.00

The author(s) grant permission for redistribution and use in source and
binary forms, with or without modification, of the software and documentation
provided that the following conditions are met:

0. If you receive a version of the software that is specifically labelled
as not being for redistribution (check the version message and/or README),

you are not permitted to redistribute that version of the software in any
way or form.
1. All terms of the all other applicable copyrights and licenses must be
followed.
2. Redistributions of source code must retain the authors' copyright
notice(s), this list of conditions, and the following disclaimer.
3. Redistributions in binary form must reproduce the authors' copyright
notice(s), this list of conditions, and the following disclaimer in the
documentation and/or other materials provided with the distribution.
4. [The copyright holder has authorized the removal of this clause.]
5. Neither the name(s)
of the author(s) nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ITS AUTHORS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

If these license terms cause you a real problem, contact the author. */

The file sunrpc/des_impl.c
is copyright Eric Young:

Copyright (C) 1992 Eric Young
Collected from libdes and modified for SECURE RPC by Martin Kuck 1994
This file is distributed under the terms of the GNU Lesser General
Public License, version 2.1 or later - see the file COPYING.LIB for details.
If you did not receive a copy of the license with this program, please
see <https://www.gnu.org/licenses/> to obtain a copy.

The file inet/rcmd.c is under a UCB copyright and the following:

Copyright (C) 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with
the distribution.
3. Neither the name of the project nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

The file posix/runtests.c is copyright Tom Lord:

Copyright
1995 by Tom Lord

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its
documentation for any purpose and without fee is hereby granted,
provided that the above copyright notice appear in all copies and that
both that copyright notice and this permission notice appear in
supporting documentation, and that the name of the copyright holder not be
used in advertising or publicity pertaining to distribution of the
software without specific, written prior permission.

Tom Lord DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO
EVENT SHALL TOM LORD BE LIABLE FOR ANY SPECIAL, INDIRECT OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF
USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR
OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

The posix/rxspencer tests
are copyright Henry Spencer:

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone

and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

The file posix/PCRE.tests
 is copyright University of Cambridge:

Copyright (c) 1997-2003 University of Cambridge

Permission is granted to anyone to use this software for any purpose on any
computer system, and to redistribute it freely, subject to the following
restrictions:

1. This software is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. In practice, this means that if you use
  PCRE in software that you distribute to others, commercially or
  otherwise, you must put a sentence like this

    Regular expression support is provided by the PCRE library package,
    which is open source software, written by Philip Hazel, and copyright
    by the University of Cambridge, England.

  somewhere reasonably visible in your documentation and in any relevant
  files or online
 help data or similar. A reference to the ftp site for
  the source, that is, to

    ftp://ftp.csx.cam.ac.uk/pub/software/programming/pcre/

should also be given in the documentation. However, this condition is not intended to apply to whole chains of software. If package A includes PCRE, it must acknowledge it, but if package B is software that includes package A, the condition is not imposed on package B (unless it uses PCRE independently).

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. If PCRE is embedded in any software that is released under the GNU General Purpose Licence (GPL), or Lesser General Purpose Licence (LGPL), then the terms of that licence shall supersede any condition above with which it is incompatible.

Files from Sun fdlibm are copyright Sun Microsystems, Inc.:

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems,
Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice
is preserved.

Various long double libm functions are copyright Stephen L. Moshier:

Copyright 2001 by Stephen L. Moshier <moshier@na-net.ornl.gov>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, see
<https://www.gnu.org/licenses/>. */

1.141 libyaml 0.2.5-7.el9

1.141.1 Available under license :

Copyright (c) 2017-2020 Ingy dt Net
Copyright (c) 2006-2016 Kirill Simonov

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.142 libarchive 3.5.3-6.el9_6

1.142.1 Available under license :

The libarchive distribution as a whole is Copyright by Tim Kientzle
and is subject to the copyright notice reproduced at the bottom of
this file.

Each individual file in this distribution should have a clear
copyright/licensing statement at the beginning of the file. If any do
not, please let me know and I will rectify it. The following is
intended to summarize the copyright status of the individual files;
the actual statements in the files are controlling.

* Except as listed below, all C sources (including .c and .h files)
 and documentation files are subject to the copyright notice reproduced
 at the bottom of this file.

* The following source files are also subject in whole or in part to
 a 3-clause UC Regents copyright; please read the individual source
 files for details:
  libarchive/archive_read_support_filter_compress.c
  libarchive/archive_write_add_filter_compress.c
  libarchive/mtree.5

* The following source files are in the public domain:
  libarchive/archive_getdate.c

*
 The following source files are triple-licensed with the ability to choose
 from CC0 1.0 Universal, OpenSSL or Apache 2.0 licenses:
  libarchive/archive_blake2.h
  libarchive/archive_blake2_impl.h
  libarchive/archive_blake2s_ref.c
  libarchive/archive_blake2sp_ref.c

* The build files---including Makefiles, configure scripts,
 and auxiliary scripts used as part of the compile process---have
 widely varying licensing terms. Please check individual files before
 distributing them to see if those restrictions apply to you.

I intend for all new source code to use the license below and hope over
time to replace code with other licenses with new implementations that
do use the license below. The varying licensing of the build scripts
seems to be an unavoidable mess.

Copyright (c) 2003-2018 <author(s)>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1.
 Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer
  in this position and unchanged.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR(S) ``AS IS" AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
 OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.143 keyutils 1.6.3-1.el9

1.143.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. <http://fsf.org/>
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission
to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program
or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and

you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program
(or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program
in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled
to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute

software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies
a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED
BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either
version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show
w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc. <http://fsf.org/>
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You

can use
it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you
must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat
to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser

General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire
combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software
only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL
PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy,

and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore

covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application

to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library

facilities. This must
be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore,
by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.

11. If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License.
If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices.
Many people have made
generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser
General Public License from time to time.
Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving

the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL
OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright"
line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or

modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper
mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.144 ncurses 6.2-12.20210508.el9

1.144.1 Available under license :

Upstream source https://invisible-island.net/ncurses/ncurses-examples.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2003-2019,2020 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining
a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-
ings in this Software without prior written authorization from the X Consor-

tium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent
`make' implicit rules from creating a file called install from it
when there is no Makefile.

This script is compatible with the BSD install script, but was written
from scratch. It can only install one file at a time, a restriction
shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source https://invisible-island.net/ncurses/ncurses.html
This package is used for testing builds of ncurses.

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 by Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 1996-2020,2021 by Thomas E. Dickey
Licence: X11

Files: doc/html/NCURSES-Programming-HOWTO.html
Copyright: 2001 by Pradeep Padala
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software
is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS

OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

Files:
install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-
ings in this Software without prior written authorization from the X Consor-
tium.

Files: progs/tset.c ncurses/tinfo/read_termcap.c
Copyright: 1980,1991,1992,1993 The Regents of the University of California.
License: BSD

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions

are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list
of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

-- vile: txtmode file-encoding=utf-8
Copyright 2018-2020,2021 Thomas E. Dickey
Copyright 1998-2017,2018 Free Software Foundation, Inc.

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

-- vile:txtmode fc=72
-- $Id: COPYING,v 1.10 2021/01/01 09:54:30 tom Exp $
Upstream source https://invisible-island.net/ncurses/Ada95.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 by Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2010-2020,2021 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included

in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

Files: install-sh

Copyright: 1994 X Consortium
Licence: X11

  Permission is hereby granted, free of charge, to any person obtaining a
copy
  of this software and associated documentation files (the "Software"), to
  deal in the Software without restriction, including without limitation the
  rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
  sell copies of the Software, and to permit persons to whom the Software is
  furnished to do so, subject to the following conditions:

  The above copyright notice and this permission notice shall be included in
  all copies or substantial portions of the Software.

  THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
  IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
  FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
  X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
  AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
  TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

  Except
as contained in this notice, the name of the X Consortium shall not
  be used in advertising or otherwise to promote the sale, use or other deal-
  ings in this Software without prior written authorization from the X Consor-
  tium.

  FSF changes to this file are in the public domain.

  Calling this script install-sh is preferred over install.sh, to prevent
  `make' implicit rules from creating a file called install from it
  when there is no Makefile.

  This script is compatible with the BSD install script, but was written
  from scratch. It can only install one file at a time, a restriction
  shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source https://invisible-island.net/ncurses/ncurses-examples.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 Thomas E. Dickey

Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2003-2020,2021 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent `make' implicit rules from creating a file called install from it when there is no Makefile.

This script is compatible with the BSD install script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's install programs.

On Debian systems, the complete text of the GNU General Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8

1.145 gpg-pubkey fd431d51-4ae0493b

1.145.1 Available under license :

Here is a list with collected copyright notices. For details see the description of each individual package. [Compiled by wk 2017-11-07]

GNUPG is

Copyright (C) 1997-2017 Werner Koch
Copyright (C) 1994-2017 Free Software Foundation, Inc.
Copyright (C) 2003-2017 g10 Code GmbH
Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 1995-1997, 2000-2007 Ulrich Drepper <drepper@gnu.ai.mit.edu>
Copyright (C) 1994 X Consortium
Copyright (C) 1998 by The Internet Society.
Copyright (C) 1998-2004 The OpenLDAP Foundation
Copyright (C) 1998-2004 Kurt D. Zeilenga.
Copyright (C) 1998-2004 Net Boolean Incorporated.
Copyright (C) 2001-2004 IBM Corporation.
Copyright (C) 1999-2003 Howard Y.H. Chu.

Copyright (C) 1999-2003 Symas Corporation.
Copyright (C) 1998-2003 Hallvard B. Furuseth.
Copyright (C) 1992-1996 Regents of the University of Michigan.
Copyright (C) 2000 Dimitrios Souflis
Copyright (C) 2008,2009,2010,2012-2016 William Ahern

GnuPG is free software;
you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

GnuPG is distributed in the hope that it will be useful, but WITHOUT
ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public
License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <https://www.gnu.org/licenses/>.

LIBGCRYPT is

Copyright (C) 1989,1991-2017 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 1996 L. Peter Deutsch
Copyright (C) 1997 Werner Koch
Copyright (C) 1998 The Internet Society
Copyright (C) 1996-1999 Peter Gutmann, Paul Kendall, and Chris Wedgwood
Copyright (C) 1996-2006 Peter Gutmann, Matt Thomlinson and Blake Coverett
Copyright (C) 2003 Nikos Mavroyanopoulos
Copyright (C) 2006-2007 NTT (Nippon Telegraph and Telephone Corporation)
Copyright (C) 2012-2017 g10 Code GmbH
Copyright (C) 2012 Simon Josefsson, Niels Mller
Copyright (c) 2012 Intel Corporation
Copyright (C) 2013 Christian Grothoff
Copyright (C) 2013-2017 Jussi Kivilinna
Copyright (C) 2013-2014 Dmitry Eremin-Solenikov
Copyright (C) 2014 Stephan Mueller
Copyright (C) 2017 Bundesamt fr Sicherheit in der Informationstechnik

Libgcrypt is free software; you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

Libgcrypt is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Lesser General Public License for more details.

You should have received a copy of the
GNU Lesser General Public
License along with this program; if not, see <http://www.gnu.org/licenses/>.

LIBGPG-ERROR is

Copyright (C) 2003-2004, 2010, 2013-2017 g10 Code GmbH

libgpg-error is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public License
as published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

libgpg-error is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License
along with this program; if not, see <http://www.gnu.org/licenses/>.

LIBASSUAN is

Copyright (C) 1992-2013 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 2000 Werner Koch (dd9jn)
Copyright (C)
2001-2016 g10 Code GmbH
Copyright (C) 2004 Simon Josefsson

Assuan is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

Assuan is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this program; if not, see <http://www.gnu.org/licenses/>.

LIBKSBA is

Copyright (C) 2001, 2002, 2003, 2004, 2005, 2006, 2010, 2011
2012, 2013, 2014, 2015 g10 Code GmbH
Copyright (C) 2001, 2002, 2003, 2007 Free Software Foundation, Inc.
Copyright (C) 2000, 2001 Fabio Fiorina

The library and the header files are distributed under
the following
terms (LGPLv3+/GPLv2+):

KSBA is free software; you can redistribute it and/or modify
it under the terms of either

- the GNU Lesser General Public License as published by the Free
Software Foundation; either version 3 of the License, or (at
your option) any later version.

or

- the GNU General Public License as published by the Free
Software Foundation; either version 2 of the License, or (at
your option) any later version.

or both in parallel, as here.

KSBA is distributed in the hope that it will be useful, but WITHOUT
ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public
License for more details.

The other parts (e.g. manual, build system, tests) are distributed
under the following terms (GPLv3):

KSBA is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the
Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

KSBA is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

NPTH is

Copyright (C) 2011, 2012, 2014, 2015, 2017 g10 Code GmbH

nPth is free software; you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

nPth is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See
the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this program;
if not, see <https://www.gnu.org/licenses/>.

NTBTLS is

Copyright (C) 2006-2014 Brainspark B.V.
Copyright (C) 2014-2017 g10 Code GmbH

NTBTLS is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

NTBTLS is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <http://www.gnu.org/licenses/>.

PINENTRY is

Copyright (C) 1999 Robert Bihlmeyer <robbe@orcus.priv.at>
Copyright (C) 2001-2004, 2007-2008, 2010, 2015-2016 g10 Code GmbH
Copyright (C) 2002, 2008 Klarlvdalens Datakonsult AB (KDAB)
Copyright (C) 2004 by Albrecht
Dre <albrecht.dress@arcor.de>
Copyright 2007 Ingo Klcker
Copyright (C) 2014 Serge Voilokov
Copyright (C) 2015 Daiki Ueno
Copyright (C) 2015 Daniel Kahn Gillmor <dkg@fifthhorseman.net>

Copyright 2016 Intevation GmbH

PINENTRY is free software; you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

PINENTRY is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <https://www.gnu.org/licenses/>.

GPGME is

Copyright (C) 1991-2013 Free Software Foundation, Inc.
Copyright (C) 2000-2001 Werner Koch
Copyright (C) 2001-2017 g10 Code GmbH

Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 2004-2008 Igor Belyi
Copyright (C) 2002 John Goerzen
Copyright (C) 2014, 2015 Martin Albrecht
Copyright (C) 2015 Ben McGinnes
Copyright (C) 2015-2016 Bundesamt fr Sicherheit in der Informationstechnik
Copyright (C) 2016 Intevation GmbH

GPGME is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

GPGME is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License
along with this program; if not, see <http://www.gnu.org/licenses/>.

NSIS is

Copyright 1999-2009 Nullsoft and Contributors

Copyright 2002-2008 Amir Szekely
Copyright 2003 Ramon

This license applies to everything in the NSIS package, except where otherwise noted.

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

The user interface used with the installer is

Copyright 2002-2009 Joost Verburg

[It is distributed along with NSIS and the same conditions as stated above apply]

TinySCHEME is part of the GnuPG package and is

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED
BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LIBDNS is part of the GnuPG package and is

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"),
to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.

ZLIB is

(C) 1995-2013 Jean-loup Gailly and Mark Adler

This software is provided
'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

BZIP2 is

This program, "bzip2", the associated library "libbzip2", and all
documentation,
are copyright (C) 1996-2010 Julian R Seward. All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must
   not claim that you wrote the original software. If you use this
   software in a product, an acknowledgment in the product
   documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
   not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote
   products derived from this software without specific prior written
   permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS

OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

SQLITE has

been put into the public-domain by its author D. Richard Hipp:
The author disclaims copyright to this source code. In place of
a legal notice, here is a blessing:

May you do good and not evil.
May you find forgiveness for yourself and forgive others.
May you share freely, never taking more than you give.

[Note that only a few files are distributed under this license.]

Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE
LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN
ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS
INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES
REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS
PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM
THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED
HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer
exclusive Copyright and Related Rights (defined below) upon the creator
and subsequent owner(s) (each and all, an "owner") of an original work of
authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for
the purpose of contributing
to a commons of creative, cultural and
scientific works ("Commons") that the public can reliably and without fear

of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
ii. moral rights retained by the original author(s) and/or performer(s);
iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and
vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or

treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.
b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.
c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without

limitation any person's Copyright and Related Rights in the Work.
Further, Affirmer disclaims responsibility for obtaining any necessary
consents, permissions or other rights required for any use of the
Work.
d. Affirmer understands and acknowledges that Creative Commons is
not a
party to this document and has no duty or obligation with respect to
this CC0 or use of the Work.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1) assert copyright on the software, and (2) offer
you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains
that there is no warranty for this free software. For both users' and
authors' sake, the GPL requires that modified versions be marked as
changed, so that their problems will not be attributed erroneously to
authors of previous versions.

Some devices are designed to deny users access to install or run
modified versions of the software inside them, although the manufacturer
can do so. This is fundamentally incompatible with the aim of
protecting users' freedom to change the software. The systematic
pattern of such abuse occurs in the area of products for individuals to
use, which is precisely where it is most unacceptable. Therefore, we
have designed this version of the GPL to prohibit the practice for those
products. If such problems arise substantially in other domains, we
stand ready to extend this provision to those
domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.
States should not allow patents to restrict development and use of
software on general-purpose computers, but in those that do, we wish to
avoid the special danger that patents applied to a free program could
make it effectively proprietary. To prevent this, the GPL assures that
patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and
modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of
works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this
License. Each licensee is addressed as "you". "Licensees" and
"recipients" may be individuals or organizations.

To

"modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate
Legal Notices"
to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than
the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component

(kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under

the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users'
Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep
intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license
the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution medium, is called an
"aggregate" if the compilation and
its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years and valid for as
long as you offer spare parts or customer
support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the

Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge.
You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object
code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute

modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place

additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the
terms of sections
15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on
those licensors and authors.

All other non-permissive additional
terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the

form of a separately written license, or stated as exceptions;
the above requirements apply either way.

8. Termination.

You may
not propagate or modify a covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your
license from a particular copyright holder is reinstated (a)
provisionally, unless and until the copyright holder explicitly and
finally terminates your license, and (b) permanently, if the copyright
holder fails to notify you of the violation by some reasonable means
prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your
receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, you do not qualify to receive new licenses for the same
material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or
run a copy of the Program. Ancillary propagation of a covered work
occurring solely as a consequence of using peer-to-peer transmission
to receive a copy likewise does not require acceptance. However,
nothing other than this License grants you permission to propagate or
modify any covered work. These actions infringe copyright if you do
not accept this License. Therefore, by modifying or propagating a
covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time

you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not
impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control"
includes the right to grant
patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent

(such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different

permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING,
BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS
THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer
of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively

state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

  <one line to give the program's name and a brief idea
of what it does.>
  Copyright (C) <year> <name of author>

  This program is free software: you can redistribute it and/or modify
  it under the terms of the GNU General Public License as published by
  the Free Software Foundation, either version 3 of the License, or
  (at your option) any later version.

  This program is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
  GNU General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

 If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

  <program> Copyright (C) <year> <name of author>
  This program comes with ABSOLUTELY
NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

 You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

 The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But first,
 please read
<https://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so

that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections

1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

5. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Program or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying or distributing the Program (or any work based on the
Program), you indicate your acceptance of this License to do so, and

all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the

original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may

be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.
[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

 This license, the Lesser General Public License, applies to some
specially designated software packages--typically
 libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.
^L
Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.
^L

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion

of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under

the
scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections
1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library
(because it
contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a

derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise,
if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy
of this License. Also, you must do one
of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a

copy of the library already present on the user's computer system, rather than
copying library functions into the executable, and (2)
will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the
materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.
^L
7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library
with a copy of the same work
based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the
Library or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement
or
otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole
 purpose of protecting the
integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

 12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written
 in the body of this License.

 13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.
^L
 14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the
 Free
Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY
OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It
is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either

version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free
Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
LICENSE TERMS

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT

LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright (c) 2010, Matt McInerney (matt@pixelspread.com),
Copyright (c) 2011, Pablo Impallari (www.impallari.com|impallari@gmail.com),
Copyright (c) 2011, Rodrigo Fuenzalida (www.rfuenzalida.com|hello@rfuenzalida.com), with Reserved Font Name Raleway
This Font Software is licensed under the SIL Open Font License, Version 1.1.
This license is copied below, and is also available with a FAQ at:
http://scripts.sil.org/OFL

SIL OPEN FONT LICENSE Version 1.1 - 26 February 2007

PREAMBLE
The goals of the Open Font License (OFL) are to stimulate worldwide development of collaborative font projects, to support the font creation efforts of academic and linguistic communities, and to provide a free and open framework in which fonts may be shared and improved in partnership with others.

The OFL allows the licensed fonts to be used, studied, modified and redistributed freely as
long as they are not sold by themselves. The
fonts, including any derivative works, can be bundled, embedded, redistributed and/or sold with any software provided that any reserved names are not used by derivative works. The fonts and derivatives, however, cannot be released under any other type of license. The requirement for fonts to remain under this license does not apply to any document created using the fonts or their derivatives.

DEFINITIONS
"Font Software" refers to the set of files released by the Copyright Holder(s) under this license and clearly marked as such. This may include source files, build scripts and documentation.

"Reserved Font Name" refers to any names specified as such after the copyright statement(s).

"Original Version" refers to the collection of Font Software components as distributed by the Copyright Holder(s).

"Modified Version" refers to any derivative made by adding to, deleting, or substituting -- in part or in whole -- any of the components of the Original
Version, by changing formats or by porting the Font Software to a new environment.

"Author" refers to any designer, engineer, programmer, technical writer or other person who contributed to the Font Software.

PERMISSION & CONDITIONS
Permission is hereby granted, free of charge, to any person obtaining a copy of the Font Software, to use, study, copy, merge, embed, modify, redistribute, and sell modified and unmodified copies of the Font Software, subject to the following conditions:

1) Neither the Font Software nor any of its individual components, in Original or Modified Versions, may be sold by itself.

2) Original or Modified Versions of the Font Software may be bundled, redistributed and/or sold with any software, provided that each copy contains the above copyright notice and this license. These can be included either as stand-alone text files, human-readable headers or in the appropriate machine-readable metadata fields within text or binary files as long as those fields
can be easily viewed by the user.

3) No Modified Version of the Font Software may use the Reserved Font Name(s) unless explicit written permission is granted by the corresponding Copyright Holder. This restriction only applies to the primary font name as presented to the users.

4) The name(s) of the Copyright Holder(s) or the Author(s) of the Font Software shall not be used to promote, endorse or advertise any Modified Version, except to acknowledge the contribution(s) of the Copyright Holder(s) and the Author(s) or with their explicit written permission.

5) The Font Software, modified or unmodified, in part or in whole, must be distributed entirely under this license, and must not be distributed under any other license. The requirement for fonts to remain under this license does not apply to any document created using the Font Software.

TERMINATION
This license becomes null and void if any of the above conditions are

not met.

DISCLAIMER
THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT
WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL THE COPYRIGHT HOLDER BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.
Copyright 2008 The Bungee Project Authors (david@djr.com)
This Font Software is licensed under the SIL Open Font License, Version 1.1.
This license is copied below, and is also available with a FAQ at:
http://scripts.sil.org/OFL

SIL OPEN FONT LICENSE Version 1.1 - 26 February 2007

PREAMBLE
The goals of the Open Font License (OFL) are to stimulate worldwide development of collaborative font projects, to support the font creation efforts of academic and linguistic communities, and to provide a free and open framework in which fonts may be shared and improved in partnership with others.

The OFL allows the licensed fonts to be used, studied, modified and redistributed freely as long as they are not sold by themselves. The fonts, including any derivative works, can be bundled, embedded, redistributed and/or sold with any software provided that any reserved names are not
used by derivative works. The fonts and derivatives,
however, cannot be released under any other type of license. The requirement for fonts to remain under this license does not apply to any document created using the fonts or their derivatives.

DEFINITIONS
"Font Software" refers to the set of files released by the Copyright Holder(s) under this license and clearly marked as such. This may include source files, build scripts and documentation.

"Reserved Font Name" refers to any names specified as such after the copyright statement(s).

"Original Version" refers to the collection of Font Software components as distributed by the Copyright Holder(s).

"Modified Version" refers to any derivative made by adding to, deleting, or substituting -- in part or in whole -- any of the components of the Original Version, by changing formats or by porting the Font Software to a new environment.

"Author" refers to any designer, engineer, programmer, technical writer or other person who contributed to the Font Software.

PERMISSION & CONDITIONS
Permission is hereby granted, free of charge, to any person obtaining a copy of the Font Software, to use, study, copy, merge, embed, modify, redistribute, and sell modified and unmodified copies of the Font Software, subject to the following conditions:

1) Neither the Font Software nor any of its individual components, in Original or Modified Versions, may be sold by itself.

2) Original or Modified Versions of the Font Software may be bundled, redistributed and/or sold with any software, provided that each copy contains the above copyright notice and this license. These can be included either as stand-alone text files, human-readable headers or in the appropriate machine-readable metadata fields within text or binary files as long as those fields can be easily viewed by the user.

3) No Modified Version of the Font Software may use the Reserved Font Name(s) unless explicit written permission is granted by the corresponding Copyright Holder.
This restriction only applies to the primary font name as presented to the users.

4) The name(s) of the Copyright Holder(s) or the Author(s) of the Font Software shall not be used to promote, endorse or advertise any Modified Version, except to acknowledge the contribution(s) of the Copyright Holder(s) and the Author(s) or with their explicit written permission.

5) The Font Software, modified or unmodified, in part or in whole, must be distributed entirely under this license, and must not be distributed under any other license. The requirement for fonts to remain under this license does not apply to any document created using the Font Software.

TERMINATION
This license becomes null and void if any of the above conditions are

not met.

DISCLAIMER
THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK,
OR OTHER RIGHT. IN NO EVENT SHALL THE
COPYRIGHT HOLDER BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.
[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the
Library.
Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the

Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without
being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material
is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation

Information in the manner specified by section 6 of the GNU GPL
for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the
Library side by side in a single library together with other library
facilities that are not Applications and are not
covered by this
License, and convey such a combined library under terms of your
choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based
on the Library, uncombined with any other library facilities,
conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it
is a work based on the Library, and explaining where to find the
accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions
of the GNU Lesser General Public License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the
Library as you received it specifies that a certain numbered version
of the GNU Lesser General Public License "or
any later version"
applies to it, you have the option of following the terms and
conditions either of that published version or of any later version
published by the Free Software Foundation. If the Library as you
received it does not specify a version number of the GNU Lesser
General Public License, you may choose any version of the GNU Lesser
General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide
whether future versions of the GNU Lesser General Public License shall
apply, that proxy's public statement of acceptance of any version is
permanent authorization for you to choose that version for the
Library.
Unless explicitly stated, all files within Jim repository are released
under following license:

/* Jim - A small embeddable Tcl interpreter
*

* Copyright 2005 Salvatore Sanfilippo <antirez@invece.org>
* Copyright 2005 Clemens Hintze <c.hintze@gmx.net>
* Copyright 2005 patthoyts - Pat Thoyts <patthoyts@users.sf.net>
* Copyright 2008 oharboe - yvind Harboe - oyvind.harboe@zylin.com
* Copyright 2008 Andrew Lunn <andrew@lunn.ch>
* Copyright 2008 Duane Ellis <openocd@duaneellis.com>
* Copyright 2008 Uwe Klein <uklein@klein-messgeraete.de>
* Copyright 2008 Steve Bennett <steveb@workware.net.au>
* Copyright 2009 Nico Coesel <ncoesel@dealogic.nl>
* Copyright 2009 Zachary T Welch zw@superlucidity.net
* Copyright 2009 David Brownell
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions
 and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above
*   copyright notice, this list of conditions and the following
*   disclaimer in the documentation and/or other materials
*   provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE JIM TCL PROJECT ``AS IS'' AND ANY
* EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
* THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
* JIM TCL PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
* INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
* (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
*
 ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* The views and conclusions contained in the software and documentation
* are those of the authors and should not be interpreted as representing
* official policies, either expressed or implied, of the Jim Tcl Project.
*/
COPYING.other   -*- org -*-
#+TITLE: List of code with permissive licenses as used by GnuPG.
#+STARTUP: showall

* DNS resolver (dirmngr/dns.c)

dns.c - Recursive, Reentrant DNS Resolver.

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY
OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.

* TinySCHEME (tests/gpgscm/LICENSE.TinySCHEME)

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided
with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR

A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

* Regular
expression support

regexp/jimregexp.[ch]:

Originally:

Copyright (c) 1986 by University of Toronto.
Written by Henry Spencer. Not derived from licensed software.

Subsequently modified by:

1986 John Gilmore hoptoad!gnu
1987 James A. Woods ames!jaw
1993 Christopher Seiwald seiwald@vix.com
2000, 2002 Christopher Seiwald <seiwald@perforce.com>
2010 Steve Bennett <steveb@workware.net.au>
2020 NIIBE Yutaka <gniibe@fsij.org>

Permission is granted to anyone to use this software for any
purpose on any computer system, and to redistribute it freely,
subject to the following restrictions:

1. The author is not responsible for the consequences of use of
this software, no matter how awful, even if they arise
from defects in it.

2. The origin of this software must not be misrepresented, either
by explicit claim or by omission.

3. Altered versions must be plainly marked as such, and must not
be misrepresented as being the
original software.

regexp/utf8.[ch] (see regexp/LICENSE):

(c) 2010-2016 Steve Bennett <steveb@workware.net.au>

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above
   copyright notice, this list of conditions and the following
   disclaimer in the documentation and/or other materials
   provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE JIM TCL PROJECT ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
JIM TCL PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation
are those of the authors and should not be interpreted as representing
official policies, either expressed or implied, of the Jim Tcl Project.

UnicodeData.txt:

Copyright 1991-2020 Unicode, Inc. All rights reserved.
Distributed under the Terms of Use in https://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining
a copy of the Unicode data files and any associated documentation
(the "Data Files") or Unicode software and any associated documentation
(the "Software")
to deal in the Data Files or Software
without restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, and/or sell copies of
the Data Files or Software, and to permit persons to whom the Data Files
or Software are furnished to do so, provided that either
(a) this copyright and permission notice appear with all copies
of the Data Files or Software, or
(b) this copyright and permission notice appear in associated
Documentation.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF
ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT OF THIRD PARTY RIGHTS.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS
NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL
DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE,
DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT,
NEGLIGENCE OR OTHER
TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder
shall not be used in advertising or otherwise to promote the sale,
use or other dealings in these Data Files or Software without prior
written authorization of the copyright holder.

1.146 gpgme 1.15.1-6.el9

1.146.1 Available under license :

```
#include "qgpgme/importjob.h"
#include "qgpgme/cryptoconfig.h"
/*
 key.h - wraps a gpgme key
 Copyright (C) 2003, 2005 Klarlvdalens Datakonsult AB

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef __GPGMEPP_KEY_H__
```

```
#define __GPGMEPP_KEY_H__

#include "global.h"
#include "notation.h"

#include "gpgmefw.h"

#include
 <memory>
#include <sys/time.h>

#include <vector>
#include <algorithm>
#include <string>

namespace GpgME
{

class Context;

class Subkey;
class UserID;
class TofuInfo;

typedef std::shared_ptr< std::remove_pointer<gpgme_key_t>::type > shared_gpgme_key_t;

//
// class Key
//

class GPGMEPP_EXPORT Key
{
  friend class ::GpgME::Context;
  struct Null {
 Null() {}
 };
public:
  Key();
  /* implicit */ Key(const Null &);
  Key(const shared_gpgme_key_t &key);
  Key(gpgme_key_t key, bool acquireRef);

  static const Null null;

  const Key &operator=(Key other)
  {
     swap(other);
     return *this;
```

```
  }

  const Key &mergeWith(const Key &other);

  void swap(Key &other)
  {
     using std::swap;
     swap(this->key, other.key);
  }

  bool isNull() const
  {
     return !key;
  }

  UserID userID(unsigned int index) const;
  Subkey subkey(unsigned int index) const;

  unsigned int numUserIDs() const;
  unsigned int numSubkeys()
const;

  std::vector<UserID> userIDs() const;
  std::vector<Subkey> subkeys() const;

  bool isRevoked() const;
  bool isExpired() const;
  bool isDisabled() const;
  bool isInvalid() const;

  /*! Shorthand for isNull || isRevoked || isExpired ||
   *                isDisabled || isInvalid */
  bool isBad() const;

  bool canEncrypt() const;
  /*!
    This function contains a workaround for old gpgme's: all secret
    OpenPGP keys canSign() == true, which canReallySign() doesn't
    have. I don't have time to find what breaks when I remove this
    workaround, but since Kleopatra merges secret into public keys,
    the workaround is not necessary there (and actively harms), I've
    added a new function instead.
   */
  bool canSign() const;
  bool canReallySign() const;
  bool canCertify() const;
  bool canAuthenticate() const;
  bool isQualified() const;
```

```
  bool isDeVs() const;

  bool hasSecret() const;
  GPGMEPP_DEPRECATED
 bool isSecret() const
  {
     return hasSecret();
  }

  /*!
    @return true if this is a X.509 root certificate (currently
    equivalent to something like
    strcmp( chainID(), subkey(0).fingerprint() ) == 0 )
  */
  bool isRoot() const;

  enum OwnerTrust { Unknown = 0, Undefined = 1, Never = 2,
                    Marginal = 3, Full = 4, Ultimate = 5
                  };

  OwnerTrust ownerTrust() const;
  char ownerTrustAsString() const;

  Protocol protocol() const;
  const char *protocolAsString() const;

  const char *issuerSerial() const;
  const char *issuerName() const;
  const char *chainID() const;

  const char *keyID() const;
  const char *shortKeyID() const;
  const char *primaryFingerprint() const;

  unsigned int keyListMode() const;

  /*! Update information about this key.
   * Starts a keylisting for this key with validity
   * and tofu information gathering. Blocks for
   * how long the keylisting takes.*/
   void update();

  /**
   * @brief Add a user id to this key.
   *
   * Needs gnupg 2.1.13 and the key needs to be updated
   * afterwards to see the new uid.
   *
```

```
   * @param uid should be fully formatted and UTF-8 encoded.
   *
   * @returns a possible error.
   **/
  Error addUid(const char *uid);

  /**
   * @brief try to locate the best pgp key for a given mailbox.
   *
   * Boils down to gpg --locate-key <mbox>
   * This may take some time if remote sources are also
   * used.
   *
   * @param mbox should be a mail address does not need to be normalized.
   *
   * @returns The best key for a mailbox or a null key.
   */
  static Key locate(const char *mbox);

  /* @enum Origin
   * @brief The Origin of the key. */
  enum Origin : unsigned int {
      OriginUnknown = 0,
      OriginKS = 1,
      OriginDane = 3,
      OriginWKD = 4,
      OriginURL = 5,
      OriginFile = 6,
      OriginSelf = 7,
      OriginOther
 = 31,
  };
  /*! Get the origin of the key.
   *
   * @returns the Origin. */
  Origin origin() const;

  /*! Get the last update time.
   *
   * @returns the last update time. */
  time_t lastUpdate() const;
private:
  gpgme_key_t impl() const
  {
      return key.get();
  }
  shared_gpgme_key_t key;
};
```

```
//
// class Subkey
//

class GPGMEPP_EXPORT Subkey
{
public:
  Subkey();
  Subkey(const shared_gpgme_key_t &key, gpgme_sub_key_t subkey);
  Subkey(const shared_gpgme_key_t &key, unsigned int idx);

  const Subkey &operator=(Subkey other)
  {
    swap(other);
    return *this;
  }

  void swap(Subkey &other)
  {
    using std::swap;
    swap(this->key, other.key);
    swap(this->subkey, other.subkey);
  }

  bool isNull() const
  {
    return !key || !subkey;
  }

  Key parent() const;

  const char *keyID() const;
  const char *fingerprint() const;

  time_t creationTime() const;
  time_t expirationTime()
 const;
  bool neverExpires() const;

  bool isRevoked() const;
  bool isExpired() const;
  bool isInvalid() const;
  bool isDisabled() const;

  /*! Shorthand for isNull || isRevoked || isExpired ||
   *                isDisabled || isInvalid */
  bool isBad() const;
```

```
  bool canEncrypt() const;
  bool canSign() const;
  bool canCertify() const;
  bool canAuthenticate() const;
  bool isQualified() const;
  bool isDeVs() const;
  bool isCardKey() const;

  bool isSecret() const;

  /** Same as gpgme_pubkey_algo_t */
  enum PubkeyAlgo {
     AlgoUnknown = 0,
     AlgoRSA     = 1,
     AlgoRSA_E   = 2,
     AlgoRSA_S   = 3,
     AlgoELG_E   = 16,
     AlgoDSA     = 17,
     AlgoECC     = 18,
     AlgoELG     = 20,
     AlgoECDSA   = 301,
     AlgoECDH    = 302,
     AlgoEDDSA   = 303,
     AlgoMax     = 1 << 31
  };

  PubkeyAlgo publicKeyAlgorithm() const;

  /**
    @brief Get the public
 key algorithm name.

    This only works for the pre 2.1 algorithms for ECC NULL is returned.

    @returns a statically allocated string with the name of the public
             key algorithm, or NULL if that name is not known.
  */
  const char *publicKeyAlgorithmAsString() const;

  /** @brief Same as publicKeyAlgorithmAsString but static. */
  static const char *publicKeyAlgorithmAsString(PubkeyAlgo algo);

  /**
    @brief Get the key algo string like GnuPG 2.1 prints it.

    This returns combinations of size and algorithm. Like
    bp512 or rsa2048. Misnamed because publicKeyAlgorithmAsString
```

```
    already used the older pubkey_algo_name.
    Actually uses gpgme_pubkey_algo_string.

    @returns the key algorithm as string. Empty string on error.
  */
  std::string algoName() const;

  unsigned int length() const;

  const char *cardSerialNumber() const;

  const char *keyGrip() const;

private:
  shared_gpgme_key_t key;
  gpgme_sub_key_t
 subkey;
};

//
// class UserID
//

class GPGMEPP_EXPORT UserID
{
public:
  class Signature;

  UserID();
  UserID(const shared_gpgme_key_t &key, gpgme_user_id_t uid);
  UserID(const shared_gpgme_key_t &key, unsigned int idx);

  const UserID &operator=(UserID other)
  {
    swap(other);
    return *this;
  }

  void swap(UserID &other)
  {
    using std::swap;
    swap(this->key, other.key);
    swap(this->uid, other.uid);
  }

  bool isNull() const
  {
    return !key || !uid;
```

```
}

Key parent() const;

unsigned int numSignatures() const;
Signature signature(unsigned int index) const;
std::vector<Signature> signatures() const;

const char *id() const;
const char *name() const;
const char *email() const;
const char *comment() const;
const char *uidhash() const;

enum Validity { Unknown = 0, Undefined = 1, Never = 2,
                Marginal = 3, Full = 4, Ultimate = 5

};

Validity validity() const;
char validityAsString() const;

bool isRevoked() const;
bool isInvalid() const;

/*! Shorthand for isNull || isRevoked || isInvalid */
bool isBad() const;

/** TOFU info for this userid.
 * @returns The TOFU stats or a null TofuInfo.
 */
GpgME::TofuInfo tofuInfo() const;

/*! Wrapper around gpgme_addrspec_from_uid.
 *
 * The input string should match the format of
 * a user id string.
 *
 * @returns a normalized mail address if found
 * or an empty string. */
static std::string addrSpecFromString(const char *uid);

/*! Wrapper around gpgme_addrspec_from_uid.
 *
 * @returns a normalized mail address for this userid
 * or an empty string. */
std::string addrSpec() const;
```

```
  /*! Revoke the user id.
   *
   * Key needs update afterwards.
   *
   * @returns an error on error.*/
  Error revoke();

  /*! Get the origin of the key.
   *
   * @returns the
 Origin. */
  Key::Origin origin() const;

  /*! Get the last update time.
   *
   * @returns the last update time. */
  time_t lastUpdate() const;

  /*! Get a remark made by the key provided.
   * A remark is a signature notation on
   * this user id made by the key with the
   * name "rem@gnupg.org". Returns an error if the
   * parent key of this user id was not listed with the
   * keylist mode flags for signatures and signature notations.
   *
   * @param key The key for which comments should be searched.
   * @param error Set to GPG_ERR_NO_DATA if the keylist did
   *              not include signature notations.
   *
   * @returns The value of the comment or NULL if none exists.
   **/
  const char *remark(const Key &key,
                     Error &error) const;

  /*! Get multiple remarks made by potentially multiple keys. */
  std::vector <std::string> remarks(std::vector<GpgME::Key> remarkers,

  Error &error) const;

private:
  shared_gpgme_key_t key;
  gpgme_user_id_t uid;
};

//
// class UserID::Signature
//
```

```
class GPGMEPP_EXPORT UserID::Signature
{
public:
  typedef GPGMEPP_DEPRECATED GpgME::Notation Notation;

  Signature();
  Signature(const shared_gpgme_key_t &key, gpgme_user_id_t uid, gpgme_key_sig_t sig);
  Signature(const shared_gpgme_key_t &key, gpgme_user_id_t uid, unsigned int idx);

  const Signature &operator=(Signature other)
  {
     swap(other);
     return *this;
  }

  void swap(Signature &other)
  {
     using std::swap;
     swap(this->key, other.key);
     swap(this->uid, other.uid);
     swap(this->sig, other.sig);
  }

  /*! Defines a canonical sort order for signatures of the same user ID. */
  bool operator<(const Signature &other) const;

  GPGMEPP_DEPRECATED bool operator<(const Signature &other);

  bool isNull() const
  {
     return !sig || !uid || !key ;
  }

  UserID parent() const;

   const char *signerKeyID() const;

  const char *algorithmAsString() const;
  unsigned int algorithm() const;
  time_t creationTime() const;
  time_t expirationTime() const;
  bool neverExpires() const;

  bool isRevokation() const;
  bool isInvalid() const;
  bool isExpired() const;
  bool isExportable() const;
```

```
  /*! Shorthand for isNull || isExpired || isInvalid */
  bool isBad() const;

  const char *signerUserID() const;
  const char *signerName() const;
  const char *signerEmail() const;
  const char *signerComment() const;

  unsigned int certClass() const;

  enum Status { NoError = 0, SigExpired, KeyExpired,
                BadSignature, NoPublicKey, GeneralError
              };
  Status status() const;
  std::string statusAsString() const;

  const char *policyURL() const;

  unsigned int numNotations() const;
  GpgME::Notation notation(unsigned int idx) const;
  std::vector<GpgME::Notation> notations() const;

private:

  shared_gpgme_key_t key;
  gpgme_user_id_t uid;
  gpgme_key_sig_t sig;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const UserID &uid);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Subkey &subkey);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Key &key);

} // namespace GpgME

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Key)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Subkey)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(UserID)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(UserID::Signature)

GPGMEPP_MAKE_STRCMP(ByFingerprint, .primaryFingerprint());
GPGMEPP_MAKE_STRCMP(ByKeyID, .keyID());
GPGMEPP_MAKE_STRCMP(ByShortKeyID, .shortKeyID());
GPGMEPP_MAKE_STRCMP(ByChainID, .chainID());

#endif // __GPGMEPP_KEY_H__
/*
  qgpgmesecretkeyexportjob.h
```

```
  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMESECRETKEYEXPORTJOB_H__
#define __QGPGME_QGPGMESECRETKEYEXPORTJOB_H__

#include "exportjob.h"
#ifdef BUILDING_QGPGME
# include "context.h"
#else
#include "gpgme++/context.h"
#endif
#include <QProcess>

namespace GpgME
{
class Data;
}
```

```
namespace QGpgME
{

class QGpgMESecretKeyExportJob : public ExportJob
{
  Q_OBJECT
public:
  QGpgMESecretKeyExportJob(bool
 armour, const QString &charset);
  ~QGpgMESecretKeyExportJob();

  /* from ExportJob */
  GpgME::Error start(const QStringList &patterns) Q_DECL_OVERRIDE;

private Q_SLOTS:
  /* from Job */
  void slotCancel() Q_DECL_OVERRIDE;

  void slotStdout();
  void slotStderr();
  void slotProcessExited(int exitCode, QProcess::ExitStatus exitStatus);

private:
  QProcess *mProcess;
  QByteArray mKeyData;
  GpgME::Error mError;
  bool mArmour;
  QString mCharset;
};

}

#endif // __QGPGME_QGPGMESECRETKEYEXPORTJOB_H__
/*
 gpgadduserideditinteractor.h - Edit Interactor to add a new UID to an OpenPGP key
 Copyright (C) 2008 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
```

```
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301,
 USA.
*/

#ifndef __GPGMEPP_GPGADDUSERIDEDITINTERACTOR_H__
#define __GPGMEPP_GPGADDUSERIDEDITINTERACTOR_H__

#include <editinteractor.h>

#include <string>

namespace GpgME
{

class GPGMEPP_EXPORT GpgAddUserIDEditInteractor : public EditInteractor
{
public:
  explicit GpgAddUserIDEditInteractor();
  ~GpgAddUserIDEditInteractor();

  void setNameUtf8(const std::string &name);
  const std::string &nameUtf8() const
  {
     return m_name;
  }

  void setEmailUtf8(const std::string &email);
  const std::string &emailUtf8() const
  {
     return m_email;
  }

  void setCommentUtf8(const std::string &comment);
  const std::string &commentUtf8() const
  {
     return m_comment;
  }

private:
  const char *action(Error &err) const override;
  unsigned int nextState(unsigned int statusCode, const char *args, Error &err) const override;
```

```
private:
  std::string m_name, m_email, m_comment;
};

} // namespace GpgME

#endif // __GPGMEPP_GPGADDUSERIDEDITINTERACTOR_H__
/*
  qgpgmesignjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2007,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMESIGNJOB_H__
#define __QGPGME_QGPGMESIGNJOB_H__

#include "signjob.h"
```

```
#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "signingresult.h"
#else
#include <gpgme++/signingresult.h>
#endif
#ifdef BUILDING_QGPGME
# include "key.h"
#else
#include <gpgme++/key.h>
#endif

namespace QGpgME
{

class QGpgMESignJob
#ifdef Q_MOC_RUN
  : public SignJob
#else
   : public _detail::ThreadedJobMixin<SignJob, std::tuple<GpgME::SigningResult, QByteArray, QString,
GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMESignJob(GpgME::Context *context);
  ~QGpgMESignJob();

  /* from SignJob */
  GpgME::Error start(const std::vector<GpgME::Key> &signers,
                     const QByteArray &plainText,
                     GpgME::SignatureMode mode) Q_DECL_OVERRIDE;

  /* from SignJob */
  void start(const std::vector<GpgME::Key> &signers,
             const std::shared_ptr<QIODevice> &plainText,
             const std::shared_ptr<QIODevice> &signature,
             GpgME::SignatureMode mode) Q_DECL_OVERRIDE;

  /* from SignJob */
  GpgME::SigningResult exec(const std::vector<GpgME::Key> &signers,
                            const QByteArray &plainText,
                            GpgME::SignatureMode mode,
```

```
                        QByteArray
 &signature) Q_DECL_OVERRIDE;

  /* from SignJob */
  void setOutputIsBase64Encoded(bool on) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  GpgME::SigningResult mResult;
  bool mOutputIsBase64Encoded;
};

}

#endif // __QGPGME_QGPGMESIGNJOB_H__
/*
 editinteractor.h - Interface for edit interactors
 Copyright (C) 2007 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_EDITINTERACTOR_H__
#define
 __GPGMEPP_EDITINTERACTOR_H__

#include "gpgmepp_export.h"

#include <cstdio>
```

```
namespace GpgME
{

class Error;
class Context;
class CallbackHelper;

class GPGMEPP_EXPORT EditInteractor
{
  friend class ::GpgME::Context;
  friend class ::GpgME::CallbackHelper;
  EditInteractor(const EditInteractor &);
  EditInteractor &operator=(const EditInteractor &);
public:
  EditInteractor();
  virtual ~EditInteractor();

  enum {
     StartState = 0,
     ErrorState = 0xFFFFFFFF
  };

  virtual const char *action(Error &err) const = 0;
  virtual unsigned int nextState(unsigned int statusCode, const char *args, Error &err) const = 0;

  unsigned int state() const;
  Error lastError() const;
  bool needsNoResponse(unsigned int statusCode) const;

  void setDebugChannel(std::FILE *file);

private:
  class Private;
  Private *const d;
};

} // namespace GpgME

#endif // __GPGMEPP_EDITINTERACTOR_H__
/*
 callbacks.h - callback targets for internal use:
 Copyright (C) 2003 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.
```

```
 This is an internal header file, subject to change without
 notice. DO NOT USE.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51
 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_CALLBACKS_H__
#define __GPGMEPP_CALLBACKS_H__

#include <gpgme.h>

extern "C" {

  void progress_callback(void *opaque, const char *what,
                         int type, int current, int total);
  gpgme_error_t passphrase_callback(void *opaque, const char *uid_hint,
                                    const char *desc, int prev_was_bad, int fd);
}

namespace GpgME
{
extern const gpgme_data_cbs data_provider_callbacks;
extern const gpgme_edit_cb_t edit_interactor_callback;
}

#endif // __GPGME_CALLBACKS_H__
#include "qgpgme/protocol.h"
/*
  qgpgmechangeexpiryjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH
```

```
  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMECHANGEEXPIRYJOB_H__
#define __QGPGME_QGPGMECHANGEEXPIRYJOB_H__

#include "changeexpiryjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
{

class QGpgMEChangeExpiryJob
#ifdef Q_MOC_RUN
  : public ChangeExpiryJob
#else
  : public _detail::ThreadedJobMixin<ChangeExpiryJob>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
```

```
  void slotFinished();
#endif
public:
   explicit QGpgMEChangeExpiryJob(GpgME::Context *context);
  ~QGpgMEChangeExpiryJob();

  /* from ChangeExpiryJob */
  GpgME::Error start(const GpgME::Key &key, const QDateTime &expiry) Q_DECL_OVERRIDE;

  /* from ChangeExpiryJob */
  GpgME::Error start(const GpgME::Key &key, const QDateTime &expiry,
                     const std::vector<GpgME::Subkey> &subkeys) Q_DECL_OVERRIDE;

};

}

#endif // __QGPGME_QGPGMECHANGEEXPIRYJOB_H__
/*
  dn.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
```

```
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/
#ifndef QGPGME_DN_H
#define QGPGME_DN_H

#include "qgpgme_export.h"

#include <QString>
#include <QStringList>

#include <QVector>

namespace QGpgME
{

/**
  @short DN parser and reorderer
*/
class QGPGME_EXPORT DN
{
public:
   class Attribute;
   typedef QVector<Attribute> AttributeList;
   typedef AttributeList::const_iterator const_iterator;

   DN();
   explicit DN(const QString &dn);
   explicit
 DN(const char *utf8DN);
   DN(const DN &other);
   ~DN();

   const DN &operator=(const DN &other);

   /** @return the value in rfc-2253-escaped form */
   static QString escape(const QString &value);

   /** @return the DN in a reordered form, according to the settings in
       the [DN] group of the application's config file */
   QString prettyDN() const;
   /** @return the DN in the original form */
   QString dn() const;
   /**
     \overload
     Uses \a sep as separator (default: ,)
   */
```

```
  QString dn(const QString &sep) const;

  QString operator[](const QString &attr) const;

  void append(const Attribute &attr);

  const_iterator begin() const;
  const_iterator end() const;

  /** Set the order in which prettyDN will reorder the Attributes. */
  void setAttributeOrder(const QStringList &order) const;

  /** Get the used attribute order. */
  const QStringList & attributeOrder() const;

private:
  void detach();
private:
  class Private;
   Private *d;
};

class QGPGME_EXPORT DN::Attribute
{
public:
  typedef DN::AttributeList List;

  explicit Attribute(const QString &name = QString(), const QString &value = QString())
     : mName(name.toUpper()), mValue(value) {}
  Attribute(const Attribute &other)
     : mName(other.name()), mValue(other.value()) {}

  const Attribute &operator=(const Attribute &other)
  {
     if (this != &other) {
        mName = other.name();
        mValue = other.value();
     }
     return *this;
  }

  const QString &name() const
  {
     return mName;
  }
  const QString &value() const
  {
     return mValue;
```

```
  }

  void setValue(const QString &value)
  {
     mValue = value;
  }

private:
  QString mName;
  QString mValue;
};
} // namespace QGpgME
#endif // QGPGME_DN_H
{
  "op": "export",
  "keys": "victor@example.org",
  "armor": true
}
#include "qgpgme/hierarchicalkeykistjob.h"
{
  "info": {
     "is_mime":     false,
     "signatures":  [{
        "summary":     {
           "sigsum":      [],
           "valid":       false,
           "green":       false,
           "red":  false,
           "revoked":     false,
           "key-expired":  false,
           "sig-expired":  false,
           "key-missing":  false,
           "crl-missing":  false,
           "crl-too-old":  false,
           "bad-policy":   false,
           "sys-error":    false
        },
        "wrong_key_usage":     false,
        "chain_model":  false,
        "is_de_vs":     false,
        "status_string":       "Success",
        "fingerprint":  "A0FF4590BB6122EDEF6E3C542D727CC768697734",
        "validity_string":     "unknown",
        "pubkey_algo_name":    "DSA",
        "hash_algo_name":      "SHA1",
        "status_code":  0,
        "timestamp":    1542213871,
```

```
        "exp_timestamp":        0,
        "pka_trust":    0,
        "validity":     0,
        "validity_reason":      0,
        "notations":    [{
          "human_readable":       false,
          "critical":     false,
          "value":        "https://www.gnu.org/policy/",
          "flags":        0
        }, {
        "human_readable":       true,
        "critical":     false,
        "name": "laughing@me",
        "value":        "Just Squeeze Me",
        "flags":        1
        }, {
        "human_readable":       true,
        "critical":     true,
        "name": "preferred-email-encoding@pgp.com",
        "value":        "pgpmime",
        "flags":        3
        }]
      }]
  },
  "type": "plaintext",
  "base64":       false,
  "data": "Hallo Leute\n"
}
#include "qgpgme/importfromkeyserverjob.h"
/*  qgpgme_export.h - Export macros for qgpgme

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA
```

```
  In addition, as a special exception, the copyright
 holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef QGPGME_EXPORT_H
#define QGPGME_EXPORT_H

#ifdef QGPGME_STATIC_DEFINE
#  define QGPGME_EXPORT
#  define QGPGME_NO_EXPORT
#else
#  ifndef QGPGME_EXPORT
#    ifdef BUILDING_QGPGME
       /* We are building this library */
#      ifdef WIN32
#        define QGPGME_EXPORT __declspec(dllexport)
#      else
#        define QGPGME_EXPORT __attribute__((visibility("default")))
#      endif
#    else
       /* We are
 using this library */
#      ifdef WIN32
#        define QGPGME_EXPORT __declspec(dllimport)
#      else
#        define QGPGME_EXPORT __attribute__((visibility("default")))
#      endif
#    endif
#  endif

#  ifndef QGPGME_NO_EXPORT
#    ifdef WIN32
#      define QGPGME_NO_EXPORT
#    else
#      define QGPGME_NO_EXPORT __attribute__((visibility("hidden")))
#    endif
#  endif
#endif
```

```
#ifndef QGPGME_DEPRECATED
#  define QGPGME_DEPRECATED __attribute__ ((__deprecated__))
#endif

#ifndef QGPGME_DEPRECATED_EXPORT
#  define QGPGME_DEPRECATED_EXPORT QGPGME_EXPORT QGPGME_DEPRECATED
#endif

#ifndef QGPGME_DEPRECATED_NO_EXPORT
#  define QGPGME_DEPRECATED_NO_EXPORT QGPGME_NO_EXPORT QGPGME_DEPRECATED
#endif

#define DEFINE_NO_DEPRECATED 0
#if DEFINE_NO_DEPRECATED
# define QGPGME_NO_DEPRECATED
#endif

#endif
// This file is autogenerated by CMake: DO NOT EDIT

#ifndef QGPGME_LOG_H
#define QGPGME_LOG_H

#include <QLoggingCategory>

Q_DECLARE_LOGGING_CATEGORY(QGPGME_LOG)


#endif
;;;; gpgme.lisp

;;; Copyright (C) 2006 g10 Code GmbH
;;;
;;; This file is part of GPGME-CL.
;;;
;;; GPGME-CL is free software; you can redistribute it and/or modify it
;;; under the terms of the GNU General Public License as published by
;;; the Free Software Foundation; either version 2 of the License, or
;;; (at your option) any later version.
;;;
;;; GPGME-CL is distributed in the hope that it will be useful, but
;;; WITHOUT ANY WARRANTY; without even the implied warranty of
;;; MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
;;; Lesser General Public License for more details.
;;;
;;; You should have received a copy of the GNU General Public License
;;; along with GPGME; if not, write to the Free Software Foundation,
```

```
;;; Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

;;; TODO

;;; Set up the library.

(in-package :gpgme)

(deftype byte-array ()
 '(simple-array (unsigned-byte 8) (*)))

(deftype character-array ()
 '(simple-array character (*)))

;;;
 Debugging.

(defvar *debug* nil "If debugging output should be given or not.")

;;; Load the foreign library.

(define-foreign-library libgpgme
 (:unix "libgpgme.so")
 (t (:default "libgpgme")))

(use-foreign-library libgpgme)

;;; System dependencies.

; Access to ERRNO.
(defcfun ("strerror" c-strerror) :string
 (err :int))

(defun get-errno ()
 *errno*)

(defun set-errno (errno)
 (setf *errno* errno))

(define-condition system-error (error)
 ((errno :initarg :errno :reader system-error-errno))
 (:report (lambda (c stream)
     (format stream "System error: ~A: ~A"
      (system-error-errno c)
      (c-strerror (system-error-errno c)))))
 (:documentation "Signalled when an errno is encountered."))

; Needed to write passphrases.
```

```
(defcfun ("write" c-write) ssize-t
 (fd :int)
 (buffer :string) ; Actually :pointer, but we only need string.
 (size size-t))

(defun system-write (fd buffer size)
 (let ((res (c-write fd buffer size)))
   (when (< res 0) (error 'system-error
 :errno (get-errno)))
   res))

;;;
;;; C Interface Definitions
;;;

;;; Data Type Interface

;;; Some new data types used for easier translation.

;;; The number of include certs.  Translates to NIL for default.
(defctype cert-int-t
   (:wrapper :int
    :from-c translate-cert-int-t-from-foreign
    :to-c translate-cert-int-t-to-foreign))

;;; A string that may be NIL to indicate a null pointer.
(defctype string-or-nil-t
   (:wrapper :string
    :to-c translate-string-or-nil-t-to-foreign))

;;; Some opaque data types used by GPGME.

(defctype gpgme-ctx-t
   (:wrapper :pointer
    :to-c translate-gpgme-ctx-t-to-foreign)
 "The GPGME context type.")

(defctype gpgme-data-t
   (:wrapper :pointer
    :to-c translate-gpgme-data-t-to-foreign)
 "The GPGME data object type.")

;;; Wrappers for the libgpg-error library.

(defctype gpgme-error-t
   (:wrapper gpg-error::gpg-error-t
    :from-c translate-gpgme-error-t-from-foreign
    :to-c translate-gpgme-error-t-to-foreign)
```

```
 "The
 GPGME error type.")

(defctype gpgme-error-no-signal-t
   (:wrapper gpg-error::gpg-error-t
    :from-c translate-gpgme-error-no-signal-t-from-foreign)
 "The GPGME error type (this version does not signal conditions in translation.")

(defctype gpgme-err-code-t gpg-error::gpg-err-code-t
 "The GPGME error code type.")

(defctype gpgme-err-source-t gpg-error::gpg-err-source-t
 "The GPGME error source type.")

(defun gpgme-err-make (source code)
 "Construct an error value from an error code and source."
 (gpg-err-make source code))

(defun gpgme-error (code)
 "Construct an error value from an error code."
 (gpgme-err-make :gpg-err-source-gpgme code))

(defun gpgme-err-code (err)
 "Retrieve an error code from the error value ERR."
 (gpg-err-code err))

(defun gpgme-err-source (err)
 "Retrieve an error source from the error value ERR."
 (gpg-err-source err))

(defun gpgme-strerror (err)
 "Return a string containing a description of the error code."
 (gpg-strerror err))

(defun
 gpgme-strsource (err)
 "Return a string containing a description of the error source."
 (gpg-strsource err))

(defun gpgme-err-code-from-errno (err)
 "Retrieve the error code for the system error.  If the system error
  is not mapped, :gpg-err-unknown-errno is returned."
 (gpg-err-code-from-errno err))

(defun gpgme-err-code-to-errno (code)
 "Retrieve the system error for the error code.  If this is not a
  system error, 0 is returned."
 (gpg-err-code-to-errno code))
```

```
(defun gpgme-err-make-from-errno (source err)
 (gpg-err-make-from-errno source err))

(defun gpgme-error-from-errno (err)
 (gpg-error-from-errno err))

;;;

(defcenum gpgme-data-encoding-t
 "The possible encoding mode of gpgme-data-t objects."
 (:none 0)
 (:binary 1)
 (:base64 2)
 (:armor 3)
 (:url 4)
 (:urlesc 5)
 (:url0 6)
 (:mime 7))

;;;

(defcenum gpgme-pubkey-algo-t
 "Public key algorithms from libgcrypt."
 (:rsa 1)
 (:rsa-e 2)
 (:rsa-s 3)
 (:elg-e 16)
 (:dsa 17)
 (:ecc 18)
 (:elg 20)
  (:ecdsa 301)
 (:ecdh 302)
 (:eddsa 303))

(defcenum gpgme-hash-algo-t
 "Hash algorithms from libgcrypt."
 (:none 0)
 (:md5 1)
 (:sha1 2)
 (:rmd160 3)
 (:md2 5)
 (:tiger 6)
 (:haval 7)
 (:sha256 8)
 (:sha384 9)
 (:sha512 10)
 (:sha224 11)
```

```
 (:md4 301)
 (:crc32 302)
 (:crc32-rfc1510 303)
 (:crc24-rfc2440 304))

;;;

(defcenum gpgme-sig-mode-t
 "The available signature modes."
 (:none 0)
 (:detach 1)
 (:clear 2))

;;;

(defcenum gpgme-validity-t
 "The available validities for a trust item or key."
 (:unknown 0)
 (:undefined 1)
 (:never 2)
 (:marginal 3)
 (:full 4)
 (:ultimate 5))

;;;

(defcenum gpgme-protocol-t
 "The available protocols."
 (:openpgp 0)
 (:cms 1)
 (:gpgconf 2)
 (:assuan 3)
 (:g13 4)
 (:uiserver 5)
 (:spawn 6)
 (:default 254)
 (:unknown 255))

;;;

(defbitfield (gpgme-keylist-mode-t :unsigned-int)
 "The available keylist mode flags."
 (:local 1)
 (:extern 2)
 (:sigs 4)
 (:sig-notations)
 (:with-secret 16)
 (:with-tofu 32)
```

```
 (:ephemeral
 128)
 (:validate 256))

;;;

(defbitfield (gpgme-sig-notation-flags-t :unsigned-int)
 "The available signature notation flags."
 (:human-readable 1)
 (:critical 2))

(defctype gpgme-sig-notation-t
   (:wrapper :pointer
    :from-c translate-gpgme-sig-notation-t-from-foreign)
 "Signature notation pointer type.")

;; FIXME: Doesn't this depend on endianness?
(defbitfield (gpgme-sig-notation-bitfield :unsigned-int)
 (:human-readable 1)
 (:critical 2))

(defcstruct gpgme-sig-notation
 "Signature notations."
 (next gpgme-sig-notation-t)
 (name :pointer)
 (value :pointer)
 (name-len :int)
 (value-len :int)
 (flags gpgme-sig-notation-flags-t)
 (bitfield gpgme-sig-notation-bitfield))

;;;

(defcenum gpgme-status-code-t
 "The possible status codes for the edit operation."
 (:eof 0)
 (:enter 1)
 (:leave 2)
 (:abort 3)
 (:goodsig 4)
 (:badsig 5)
 (:errsig 6)
 (:badarmor 7)
 (:rsa-or-idea 8)
 (:keyexpired 9)
 (:keyrevoked 10)
 (:trust-undefined 11)
 (:trust-never
```

12)
(:trust-marginal 13)
(:trust-fully 14)
(:trust-ultimate 15)
(:shm-info 16)
(:shm-get 17)
(:shm-get-bool 18)
(:shm-get-hidden 19)
(:need-passphrase 20)
(:validsig 21)
(:sig-id 22)
(:enc-to 23)
(:nodata 24)
(:bad-passphrase 25)
(:no-pubkey 26)
(:no-seckey 27)
(:need-passphrase-sym 28)
(:decryption-failed 29)
(:decryption-okay 30)
(:missing-passphrase 31)
(:good-passphrase 32)
(:goodmdc 33)
(:badmdc 34)
(:errmdc 35)
(:imported 36)
(:import-ok 37)
(:import-problem 38)
(:import-res 39)
(:file-start 40)
(:file-done 41)
(:file-error 42)
(:begin-decryption 43)
(:end-decryption 44)
(:begin-encryption 45)
(:end-encryption 46)
(:delete-problem 47)
(:get-bool 48)
(:get-line 49)
(:get-hidden 50)
(:got-it 51)
(:progress 52)
(:sig-created 53)
(:session-key 54)
(:notation-name 55)
(:notation-data 56)
(:policy-url 57)
(:begin-stream 58)
(:end-stream 59)

```
 (:key-created 60)
 (:userid-hint 61)
 (:unexpected
 62)
 (:inv-recp 63)
 (:no-recp 64)
 (:already-signed 65)
 (:sigexpired 66)
 (:expsig 67)
 (:expkeysig 68)
 (:truncated 69)
 (:error 70)
 (:newsig 71)
 (:revkeysig 72)
 (:sig-subpacket 73)
 (:need-passphrase-pin 74)
 (:sc-op-failure 75)
 (:sc-op-success 76)
 (:cardctrl 77)
 (:backup-key-created 78)
 (:pka-trust-bad 79)
 (:pka-trust-good 80)
 (:plaintext 81)
 (:inv-sgnr 82)
 (:no-sgnr 83)
 (:success 84)
 (:decryption-info 85)
 (:plaintext-length 86)
 (:mountpoint 87)
 (:pinentry-launched 88)
 (:attribute 89)
 (:begin-signing 90)
 (:key-not-created 91)
 (:inquire-maxlen 92)
 (:failure 93)
 (:key-considered 94)
 (:tofu-user 95)
 (:tofu-stats 96)
 (:tofu-stats-long 97)
 (:notation-flags 98)
 (:decryption-compliance-mode 99)
 (:verification-compliance-mode 100))

;;;

(defctype gpgme-engine-info-t
   (:wrapper :pointer
    :from-c translate-gpgme-engine-info-t-to-foreign)
```

```
 "The engine information structure pointer type.")

(defcstruct gpgme-engine-info
  "Engine information."
 (next gpgme-engine-info-t)
 (protocol gpgme-protocol-t)
 (file-name :string)
 (version :string)
 (req-version :string)
 (home-dir :string))

;;;

(defctype gpgme-subkey-t
   (:wrapper :pointer
    :from-c translate-gpgme-subkey-t-from-foreign)
 "A subkey from a key.")

;; FIXME: Doesn't this depend on endianness?
(defbitfield (gpgme-subkey-bitfield :unsigned-int)
 "The subkey bitfield."
 (:revoked 1)
 (:expired 2)
 (:disabled 4)
 (:invalid 8)
 (:can-encrypt 16)
 (:can-sign 32)
 (:can-certify 64)
 (:secret 128)
 (:can-authenticate 256)
 (:is-qualified 512)
 (:is-cardkey 1024)
 (:is-de-vs 2048))

(defcstruct gpgme-subkey
 "Subkey from a key."
 (next gpgme-subkey-t)
 (bitfield gpgme-subkey-bitfield)
 (pubkey-algo gpgme-pubkey-algo-t)
 (length :unsigned-int)
 (keyid :string)
 (-keyid :char :count 17)
 (fpr :string)
 (timestamp :long)
 (expires :long))


(defctype gpgme-key-sig-t
```

```
  (:wrapper :pointer
   :from-c translate-gpgme-key-sig-t-from-foreign)
  "A signature on a user ID.")

;; FIXME: Doesn't this depend on endianness?
(defbitfield (gpgme-key-sig-bitfield :unsigned-int)
 "The key signature bitfield."
 (:revoked 1)
 (:expired 2)
 (:invalid 4)
 (:exportable 16))

(defcstruct gpgme-key-sig
 "A signature on a user ID."
 (next gpgme-key-sig-t)
 (bitfield gpgme-key-sig-bitfield)
 (pubkey-algo gpgme-pubkey-algo-t)
 (keyid :string)
 (-keyid :char :count 17)
 (timestamp :long)
 (expires :long)
 (status gpgme-error-no-signal-t)
 (-class :unsigned-int)
 (uid :string)
 (name :string)
 (email :string)
 (comment :string)
 (sig-class :unsigned-int))


(defctype gpgme-user-id-t
  (:wrapper :pointer
   :from-c translate-gpgme-user-id-t-from-foreign)
 "A user ID from a key.")

;; FIXME: Doesn't this depend on endianness?
(defbitfield (gpgme-user-id-bitfield :unsigned-int)
 "The user ID bitfield."
 (:revoked 1)
 (:invalid 2))

(defcstruct gpgme-user-id
 "A user ID from a key."
 (next
 gpgme-user-id-t)
 (bitfield gpgme-user-id-bitfield)
 (validity gpgme-validity-t)
 (uid :string)
```

```
 (name :string)
 (email :string)
 (comment :string)
 (signatures gpgme-key-sig-t)
 (-last-keysig gpgme-key-sig-t))


(defctype gpgme-key-t
   (:wrapper :pointer
    :from-c translate-gpgme-key-t-from-foreign
    :to-c translate-gpgme-key-t-to-foreign)
 "A key from the keyring.")

;; FIXME: Doesn't this depend on endianness?
(defbitfield (gpgme-key-bitfield :unsigned-int)
 "The key bitfield."
 (:revoked 1)
 (:expired 2)
 (:disabled 4)
 (:invalid 8)
 (:can-encrypt 16)
 (:can-sign 32)
 (:can-certify 64)
 (:secret 128)
 (:can-authenticate 256)
 (:is-qualified 512))

(defcstruct gpgme-key
 "A signature on a user ID."
 (-refs :unsigned-int)
 (bitfield gpgme-key-bitfield)
 (protocol gpgme-protocol-t)
 (issuer-serial :string)
 (issuer-name :string)
 (chain-id :string)
 (owner-trust gpgme-validity-t)
 (subkeys gpgme-subkey-t)
 (uids gpgme-user-id-t)
 (-last-subkey gpgme-subkey-t)
  (-last-uid gpgme-user-id-t)
 (keylist-mode gpgme-keylist-mode-t))

;;;

;;; There is no support in CFFI to define callback C types and have
;;; automatic type checking with the callback definition.

(defctype gpgme-passphrase-cb-t :pointer)
```

```
(defctype gpgme-progress-cb-t :pointer)

(defctype gpgme-edit-cb-t :pointer)



;;;
;;; Function Interface
;;;

;;; Context management functions.

(defcfun ("gpgme_new" c-gpgme-new) gpgme-error-t
 (ctx :pointer))

(defcfun ("gpgme_release" c-gpgme-release) :void
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_set_protocol" c-gpgme-set-protocol) gpgme-error-t
 (ctx gpgme-ctx-t)
 (proto gpgme-protocol-t))

(defcfun ("gpgme_get_protocol" c-gpgme-get-protocol) gpgme-protocol-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_get_protocol_name" c-gpgme-get-protocol-name) :string
 (proto gpgme-protocol-t))

(defcfun ("gpgme_set_armor" c-gpgme-set-armor) :void
 (ctx gpgme-ctx-t)
 (yes :boolean))

(defcfun ("gpgme_get_armor" c-gpgme-get-armor) :boolean
  (ctx gpgme-ctx-t))

(defcfun ("gpgme_set_textmode" c-gpgme-set-textmode) :void
 (ctx gpgme-ctx-t)
 (yes :boolean))

(defcfun ("gpgme_get_textmode" c-gpgme-get-textmode) :boolean
 (ctx gpgme-ctx-t))

(defconstant +include-certs-default+ -256)

(defcfun ("gpgme_set_include_certs" c-gpgme-set-include-certs) :void
 (ctx gpgme-ctx-t)
 (nr-of-certs cert-int-t))
```

```
(defcfun ("gpgme_get_include_certs" c-gpgme-get-include-certs) cert-int-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_set_keylist_mode" c-gpgme-set-keylist-mode) gpgme-error-t
 (ctx gpgme-ctx-t)
 (mode gpgme-keylist-mode-t))

(defcfun ("gpgme_get_keylist_mode" c-gpgme-get-keylist-mode)
   gpgme-keylist-mode-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_set_passphrase_cb" c-gpgme-set-passphrase-cb) :void
 (ctx gpgme-ctx-t)
 (cb gpgme-passphrase-cb-t)
 (hook-value :pointer))

(defcfun ("gpgme_get_passphrase_cb" c-gpgme-get-passphrase-cb) :void
 (ctx gpgme-ctx-t)
 (cb-p :pointer)
 (hook-value-p :pointer))

(defcfun ("gpgme_set_progress_cb"
 c-gpgme-set-progress-cb) :void
 (ctx gpgme-ctx-t)
 (cb gpgme-progress-cb-t)
 (hook-value :pointer))

(defcfun ("gpgme_get_progress_cb" c-gpgme-get-progress-cb) :void
 (ctx gpgme-ctx-t)
 (cb-p :pointer)
 (hook-value-p :pointer))

(defcfun ("gpgme_set_locale" c-gpgme-set-locale) gpgme-error-t
 (ctx gpgme-ctx-t)
 (category :int)
 (value string-or-nil-t))

(defcfun ("gpgme_ctx_get_engine_info" c-gpgme-ctx-get-engine-info)
   gpgme-engine-info-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_ctx_set_engine_info" c-gpgme-ctx-set-engine-info)
   gpgme-error-t
 (ctx gpgme-ctx-t)
 (proto gpgme-protocol-t)
 (file-name string-or-nil-t)
 (home-dir string-or-nil-t))
```

```
;;;

(defcfun ("gpgme_pubkey_algo_name" c-gpgme-pubkey-algo-name) :string
 (algo gpgme-pubkey-algo-t))

(defcfun ("gpgme_hash_algo_name" c-gpgme-hash-algo-name) :string
 (algo gpgme-hash-algo-t))

;;;

(defcfun ("gpgme_signers_clear" c-gpgme-signers-clear) :void
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_signers_add" c-gpgme-signers-add)
 gpgme-error-t
 (ctx gpgme-ctx-t)
 (key gpgme-key-t))

(defcfun ("gpgme_signers_enum" c-gpgme-signers-enum) gpgme-key-t
 (ctx gpgme-ctx-t)
 (seq :int))

;;;

(defcfun ("gpgme_sig_notation_clear" c-gpgme-sig-notation-clear) :void
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_sig_notation_add" c-gpgme-sig-notation-add) gpgme-error-t
 (ctx gpgme-ctx-t)
 (name :string)
 (value string-or-nil-t)
 (flags gpgme-sig-notation-flags-t))

(defcfun ("gpgme_sig_notation_get" c-gpgme-sig-notation-get)
   gpgme-sig-notation-t
 (ctx gpgme-ctx-t))

;;; Run Control.

;;; There is no support in CFFI to define callback C types and have
;;; automatic type checking with the callback definition.

(defctype gpgme-io-cb-t :pointer)

(defctype gpgme-register-io-cb-t :pointer)

(defctype gpgme-remove-io-cb-t :pointer)
```

```
(defcenum gpgme-event-io-t
 "The possible events on I/O event callbacks."
 (:start 0)
 (:done 1)
 (:next-key 2)
 (:next-trustitem 3))

(defctype gpgme-event-io-cb-t :pointer)

(defcstruct
 gpgme-io-cbs
 "I/O callbacks."
 (add gpgme-register-io-cb-t)
 (add-priv :pointer)
 (remove gpgme-remove-io-cb-t)
 (event gpgme-event-io-cb-t)
 (event-priv :pointer))

(defctype gpgme-io-cbs-t :pointer)

(defcfun ("gpgme_set_io_cbs" c-gpgme-set-io-cbs) :void
 (ctx gpgme-ctx-t)
 (io-cbs gpgme-io-cbs-t))

(defcfun ("gpgme_get_io_cbs" c-gpgme-get-io-cbs) :void
 (ctx gpgme-ctx-t)
 (io-cbs gpgme-io-cbs-t))

(defcfun ("gpgme_wait" c-gpgme-wait) gpgme-ctx-t
 (ctx gpgme-ctx-t)
 (status-p :pointer)
 (hang :int))

;;; Functions to handle data objects.

;;; There is no support in CFFI to define callback C types and have
;;; automatic type checking with the callback definition.

(defctype gpgme-data-read-cb-t :pointer)
(defctype gpgme-data-write-cb-t :pointer)
(defctype gpgme-data-seek-cb-t :pointer)
(defctype gpgme-data-release-cb-t :pointer)

(defcstruct gpgme-data-cbs
 "Data callbacks."
 (read gpgme-data-read-cb-t)
 (write gpgme-data-write-cb-t)
 (seek gpgme-data-seek-cb-t)
```

```
  (release gpgme-data-release-cb-t))

(defctype gpgme-data-cbs-t :pointer
 "Data callbacks pointer.")

(defcfun ("gpgme_data_read" c-gpgme-data-read) ssize-t
 (dh gpgme-data-t)
 (buffer :pointer)
 (size size-t))

(defcfun ("gpgme_data_write" c-gpgme-data-write) ssize-t
 (dh gpgme-data-t)
 (buffer :pointer)
 (size size-t))

(defcfun ("gpgme_data_seek" c-gpgme-data-seek) off-t
 (dh gpgme-data-t)
 (offset off-t)
 (whence :int))

(defcfun ("gpgme_data_new" c-gpgme-data-new) gpgme-error-t
 (dh-p :pointer))

(defcfun ("gpgme_data_release" c-gpgme-data-release) :void
 (dh gpgme-data-t))

(defcfun ("gpgme_data_new_from_mem" c-gpgme-data-new-from-mem) gpgme-error-t
 (dh-p :pointer)
 (buffer :pointer)
 (size size-t)
 (copy :int))

(defcfun ("gpgme_data_release_and_get_mem" c-gpgme-data-release-and-get-mem)
   :pointer
 (dh gpgme-data-t)
 (len-p :pointer))

(defcfun ("gpgme_data_new_from_cbs" c-gpgme-data-new-from-cbs) gpgme-error-t
 (dh-p :pointer)
 (cbs gpgme-data-cbs-t)
  (handle :pointer))

(defcfun ("gpgme_data_new_from_fd" c-gpgme-data-new-from-fd) gpgme-error-t
 (dh-p :pointer)
 (fd :int))

(defcfun ("gpgme_data_new_from_stream" c-gpgme-data-new-from-stream)
   gpgme-error-t
```

```
 (dh-p :pointer)
 (stream :pointer))

(defcfun ("gpgme_data_get_encoding" c-gpgme-data-get-encoding)
   gpgme-data-encoding-t
 (dh gpgme-data-t))

(defcfun ("gpgme_data_set_encoding" c-gpgme-data-set-encoding)
   gpgme-error-t
 (dh gpgme-data-t)
 (enc gpgme-data-encoding-t))

(defcfun ("gpgme_data_get_file_name" c-gpgme-data-get-file-name) :string
 (dh gpgme-data-t))

(defcfun ("gpgme_data_set_file_name" c-gpgme-data-set-file-name) gpgme-error-t
 (dh gpgme-data-t)
 (file-name string-or-nil-t))

(defcfun ("gpgme_data_new_from_file" c-gpgme-data-new-from-file) gpgme-error-t
 (dh-p :pointer)
 (fname :string)
 (copy :int))

(defcfun ("gpgme_data_new_from_filepart" c-gpgme-data-new-from-filepart)
   gpgme-error-t
 (dh-p :pointer)
 (fname :string)
 (fp
 :pointer)
 (offset off-t)
 (length size-t))

;;; Key and trust functions.

(defcfun ("gpgme_get_key" c-gpgme-get-key) gpgme-error-t
 (ctx gpgme-ctx-t)
 (fpr :string)
 (key-p :pointer)
 (secret :boolean))

(defcfun ("gpgme_key_ref" c-gpgme-key-ref) :void
 (key gpgme-key-t))

(defcfun ("gpgme_key_unref" c-gpgme-key-unref) :void
 (key gpgme-key-t))

;;; Crypto operations.
```

```
(defcfun ("gpgme_cancel" c-gpgme-cancel) gpgme-error-t
 (ctx gpgme-ctx-t))

;;;

(defctype gpgme-invalid-key-t
   (:wrapper :pointer
    :from-c translate-gpgme-invalid-key-t-from-foreign)
 "An invalid key structure.")

(defcstruct gpgme-invalid-key
 "An invalid key structure."
 (next gpgme-invalid-key-t)
 (fpr :string)
 (reason gpgme-error-no-signal-t))

;;; Encryption.

(defcstruct gpgme-op-encrypt-result
 "Encryption result structure."
 (invalid-recipients gpgme-invalid-key-t))

(defctype gpgme-op-encrypt-result-t
   (:wrapper :pointer
    :from-c translate-gpgme-op-encrypt-result-t-from-foreign)
  "An encryption result structure.")

(defcfun ("gpgme_op_encrypt_result" c-gpgme-op-encrypt-result)
   gpgme-op-encrypt-result-t
 (ctx gpgme-ctx-t))

(defbitfield gpgme-encrypt-flags-t
 (:always-trust 1)
 (:no-encrypt-to 2)
 (:prepare 4)
 (:expect-sign 8)
 (:no-compress 16)
 (:symmetric 32)
 (:throw-keyids 64)
 (:wrap 128)
 (:want-address 256))

(defcfun ("gpgme_op_encrypt_start" c-gpgme-op-encrypt-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (recp :pointer) ; Key array.
 (flags gpgme-encrypt-flags-t)
 (plain gpgme-data-t)
```

```
 (cipher gpgme-data-t))

(defcfun ("gpgme_op_encrypt" c-gpgme-op-encrypt) gpgme-error-t
 (ctx gpgme-ctx-t)
 (recp :pointer) ; Key array.
 (flags gpgme-encrypt-flags-t)
 (plain gpgme-data-t)
 (cipher gpgme-data-t))

(defcfun ("gpgme_op_encrypt_sign_start" c-gpgme-op-encrypt-sign-start)
   gpgme-error-t
 (ctx gpgme-ctx-t)
 (recp :pointer) ; Key array.
 (flags gpgme-encrypt-flags-t)
 (plain gpgme-data-t)
 (cipher gpgme-data-t))

(defcfun ("gpgme_op_encrypt_sign"
 c-gpgme-op-encrypt-sign) gpgme-error-t
 (ctx gpgme-ctx-t)
 (recp :pointer) ; Key array.
 (flags gpgme-encrypt-flags-t)
 (plain gpgme-data-t)
 (cipher gpgme-data-t))

;;; Decryption.

(defctype gpgme-recipient-t
   (:wrapper :pointer
    :from-c translate-gpgme-recipient-t-from-foreign)
 "A recipient structure.")

(defcstruct gpgme-recipient
 "Recipient structure."
 (next gpgme-recipient-t)
 (keyid :string)
 (-keyid :char :count 17)
 (pubkey-algo gpgme-pubkey-algo-t)
 (status gpgme-error-no-signal-t))

(defbitfield gpgme-op-decrypt-result-bitfield
 "Decryption result structure bitfield."
 (:wrong-key-usage 1)
 (:is-de-vs 2)
 (:is-mine 4))

(defcstruct gpgme-op-decrypt-result
 "Decryption result structure."
```

```
 (unsupported-algorithm :string)
 (bitfield gpgme-op-decrypt-result-bitfield)
 (recipients gpgme-recipient-t)
 (file-name :string))

(defctype gpgme-op-decrypt-result-t
   (:wrapper :pointer
    :from-c translate-gpgme-op-decrypt-result-t-from-foreign)
  "A decryption result structure.")

(defcfun ("gpgme_op_decrypt_result" c-gpgme-op-decrypt-result)
   gpgme-op-decrypt-result-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_op_decrypt_start" c-gpgme-op-decrypt-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (cipher gpgme-data-t)
 (plain gpgme-data-t))

(defcfun ("gpgme_op_decrypt" c-gpgme-op-decrypt) gpgme-error-t
 (ctx gpgme-ctx-t)
 (cipher gpgme-data-t)
 (plain gpgme-data-t))

(defcfun ("gpgme_op_decrypt_verify_start" c-gpgme-op-decrypt-verify-start)
   gpgme-error-t
 (ctx gpgme-ctx-t)
 (cipher gpgme-data-t)
 (plain gpgme-data-t))

(defcfun ("gpgme_op_decrypt_verify" c-gpgme-op-decrypt-verify) gpgme-error-t
 (ctx gpgme-ctx-t)
 (cipher gpgme-data-t)
 (plain gpgme-data-t))

;;; Signing.

(defctype gpgme-new-signature-t
   (:wrapper :pointer
    :from-c translate-gpgme-new-signature-t-from-foreign)
 "A new signature structure.")

(defcstruct gpgme-new-signature
 "New signature structure."
 (next gpgme-new-signature-t)
  (type gpgme-sig-mode-t)
 (pubkey-algo gpgme-pubkey-algo-t)
 (hash-algo gpgme-hash-algo-t)
```

```
 (-obsolete-class :unsigned-long)
 (timestamp :long)
 (fpr :string)
 (-obsolete-class-2 :unsigned-int)
 (sig-class :unsigned-int))

(defcstruct gpgme-op-sign-result
 "Signing result structure."
 (invalid-signers gpgme-invalid-key-t)
 (signatures gpgme-new-signature-t))

(defctype gpgme-op-sign-result-t
   (:wrapper :pointer
    :from-c translate-gpgme-op-sign-result-t-from-foreign)
 "A signing result structure.")

(defcfun ("gpgme_op_sign_result" c-gpgme-op-sign-result)
   gpgme-op-sign-result-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_op_sign_start" c-gpgme-op-sign-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (plain gpgme-data-t)
 (sig gpgme-data-t)
 (mode gpgme-sig-mode-t))

(defcfun ("gpgme_op_sign" c-gpgme-op-sign) gpgme-error-t
 (ctx gpgme-ctx-t)
 (plain gpgme-data-t)
 (sig gpgme-data-t)
 (mode gpgme-sig-mode-t))

;;; Verify.

(defbitfield (gpgme-sigsum-t :unsigned-int)
 "Flags
 used for the summary field in a gpgme-signature-t."
 (:valid #x0001)
 (:green #x0002)
 (:red #x0004)
 (:key-revoked #x0010)
 (:key-expired #x0020)
 (:sig-expired #x0040)
 (:key-missing #x0080)
 (:crl-missing #x0100)
 (:crl-too-old #x0200)
 (:bad-policy #x0400)
 (:sys-error #x0800)
```

```
 (:tofu-conflict #x1000))

(defctype gpgme-signature-t
   (:wrapper :pointer
    :from-c translate-gpgme-signature-t-from-foreign)
 "A signature structure.")

;; FIXME: Doesn't this depend on endianness?
(defbitfield (gpgme-signature-bitfield :unsigned-int)
 "The signature bitfield."
 (:wrong-key-usage 1)
 (:pka-trust 2)
 (:chain-model 4)
 (:is-de-vs 8))

(defcstruct gpgme-signature
 "Signature structure."
 (next gpgme-signature-t)
 (summary gpgme-sigsum-t)
 (fpr :string)
 (status gpgme-error-no-signal-t)
 (notations gpgme-sig-notation-t)
 (timestamp :unsigned-long)
 (exp-timestamp :unsigned-long)
 (bitfield gpgme-signature-bitfield)
 (validity gpgme-validity-t)
 (validity-reason
 gpgme-error-no-signal-t)
 (pubkey-algo gpgme-pubkey-algo-t)
 (hash-algo gpgme-hash-algo-t))

(defcstruct gpgme-op-verify-result
 "Verify result structure."
 (signatures gpgme-signature-t)
 (file-name :string))

(defctype gpgme-op-verify-result-t
   (:wrapper :pointer
    :from-c translate-gpgme-op-verify-result-t-from-foreign)
 "A verify result structure.")

(defcfun ("gpgme_op_verify_result" c-gpgme-op-verify-result)
   gpgme-op-verify-result-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_op_verify_start" c-gpgme-op-verify-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (sig gpgme-data-t)
```

```
 (signed-text gpgme-data-t)
 (plaintext gpgme-data-t))

(defcfun ("gpgme_op_verify" c-gpgme-op-verify) gpgme-error-t
 (ctx gpgme-ctx-t)
 (sig gpgme-data-t)
 (signed-text gpgme-data-t)
 (plaintext gpgme-data-t))

;;; Import.

(defbitfield (gpgme-import-flags-t :unsigned-int)
 "Flags used for the import status field."
 (:new #x0001)
 (:uid #x0002)
 (:sig #x0004)
 (:subkey #x0008)
 (:secret
 #x0010))

(defctype gpgme-import-status-t
   (:wrapper :pointer
    :from-c translate-gpgme-import-status-t-from-foreign)
 "An import status structure.")

(defcstruct gpgme-import-status
 "New import status structure."
 (next gpgme-import-status-t)
 (fpr :string)
 (result gpgme-error-no-signal-t)
 (status :unsigned-int))

(defcstruct gpgme-op-import-result
 "Import result structure."
 (considered :int)
 (no-user-id :int)
 (imported :int)
 (imported-rsa :int)
 (unchanged :int)
 (new-user-ids :int)
 (new-sub-keys :int)
 (new-signatures :int)
 (new-revocations :int)
 (secret-read :int)
 (secret-imported :int)
 (secret-unchanged :int)
 (skipped-new-keys :int)
 (not-imported :int)
```

```
 (imports gpgme-import-status-t))

(defctype gpgme-op-import-result-t
   (:wrapper :pointer
    :from-c translate-gpgme-op-import-result-t-from-foreign)
 "An import status result structure.")

(defcfun ("gpgme_op_import_result" c-gpgme-op-import-result)
   gpgme-op-import-result-t
  (ctx gpgme-ctx-t))

(defcfun ("gpgme_op_import_start" c-gpgme-op-import-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (keydata gpgme-data-t))

(defcfun ("gpgme_op_import" c-gpgme-op-import) gpgme-error-t
 (ctx gpgme-ctx-t)
 (keydata gpgme-data-t))

;;; Export.

(defcfun ("gpgme_op_export_start" c-gpgme-op-export-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (pattern :string)
 (reserved :unsigned-int)
 (keydata gpgme-data-t))

(defcfun ("gpgme_op_export" c-gpgme-op-export) gpgme-error-t
 (ctx gpgme-ctx-t)
 (pattern :string)
 (reserved :unsigned-int)
 (keydata gpgme-data-t))

;;; FIXME: Extended export interfaces require array handling.

;;; Key generation.

(defbitfield (gpgme-genkey-flags-t :unsigned-int)
 "Flags used for the key generation result bitfield."
 (:primary #x0001)
 (:sub #x0002)
 (:uid #x0004))

(defcstruct gpgme-op-genkey-result
 "Key generation result structure."
 (bitfield gpgme-genkey-flags-t)
 (fpr :string))
```

```
(defctype gpgme-op-genkey-result-t :pointer
 "A
 key generation result structure.")

(defcfun ("gpgme_op_genkey_result" c-gpgme-op-genkey-result)
   gpgme-op-genkey-result-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_op_genkey_start" c-gpgme-op-genkey-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (parms :string)
 (pubkey gpgme-data-t)
 (seckey gpgme-data-t))

(defcfun ("gpgme_op_genkey" c-gpgme-op-genkey) gpgme-error-t
 (ctx gpgme-ctx-t)
 (parms :string)
 (pubkey gpgme-data-t)
 (seckey gpgme-data-t))

;;; Key deletion.

(defcfun ("gpgme_op_delete_start" c-gpgme-op-delete-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (key gpgme-key-t)
 (allow-secret :int))

(defcfun ("gpgme_op_delete" c-gpgme-op-delete) gpgme-error-t
 (ctx gpgme-ctx-t)
 (key gpgme-key-t)
 (allow-secret :int))

;;; FIXME: Add edit interfaces.

;;; Keylist interface.

(defbitfield (gpgme-keylist-flags-t :unsigned-int)
 "Flags used for the key listing result bitfield."
 (:truncated #x0001))

(defcstruct gpgme-op-keylist-result
 "Key listing result structure."
 (bitfield
 gpgme-keylist-flags-t))

(defctype gpgme-op-keylist-result-t :pointer
 "A key listing result structure.")
```

```
(defcfun ("gpgme_op_keylist_result" c-gpgme-op-keylist-result)
  gpgme-op-keylist-result-t
 (ctx gpgme-ctx-t))

(defcfun ("gpgme_op_keylist_start" c-gpgme-op-keylist-start) gpgme-error-t
 (ctx gpgme-ctx-t)
 (pattern :string)
 (secret_only :boolean))

;;; FIXME: Extended keylisting requires array handling.

(defcfun ("gpgme_op_keylist_next" c-gpgme-op-keylist-next) gpgme-error-t
 (ctx gpgme-ctx-t)
 (r-key :pointer))

(defcfun ("gpgme_op_keylist_end" c-gpgme-op-keylist-end) gpgme-error-t
 (ctx gpgme-ctx-t))

;;; Various functions.

(defcfun ("gpgme_check_version" c-gpgme-check-version) :string
 (req-version string-or-nil-t))

(defcfun ("gpgme_get_engine_info" c-gpgme-get-engine-info) gpgme-error-t
 (engine-info-p :pointer))

(defcfun ("gpgme_set_engine_info" c-gpgme-set-engine-info) gpgme-error-t
 (proto gpgme-protocol-t)
 (file-name string-or-nil-t)
 (home-dir
 string-or-nil-t))

(defcfun ("gpgme_engine_check_version" c-gpgme-engine-check-verson)
  gpgme-error-t
 (proto gpgme-protocol-t))

;;;
;;; L I S P  I N T E R F A C E
;;;

;;;
;;; Lisp type translators.
;;;

;;; Both directions.

;;; cert-int-t is a helper type that takes care of representing the
;;; default number of certs as NIL.
```

```
(defun translate-cert-int-t-from-foreign (value)
 (cond
   ((eql value +include-certs-default+) nil)
   (t value)))

(defun translate-cert-int-t-to-foreign (value)
 (cond
   (value value)
   (t +include-certs-default+)))

;;; string-or-nil-t translates a null pointer to NIL and vice versa.
;;; Translation from foreign null pointer already works as expected.

(defun translate-string-or-nil-t-to-foreign (value)
 (cond
   (value value)
   (t (null-pointer))))

;;; Output only.

;;; These type translators only convert from foreign type, because we
;;; never use these types in the other direction.

;;; Convert gpgme-engine-info-t linked lists into a
 list of property
;;; lists.  Note that this converter will automatically be invoked
;;; recursively.
;;;
;;; FIXME: Should we use a hash table (or struct, or clos) instead of
;;; property list, as recommended by the Lisp FAQ?

(defun translate-gpgme-engine-info-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
   (t (with-foreign-slots
    ((next protocol file-name version req-version home-dir)
     value (:struct gpgme-engine-info))
  (append (list protocol (list
        :file-name file-name
        :version version
        :req-version req-version
        :home-dir home-dir))
   next)))))

(defun translate-gpgme-invalid-key-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
```

```
  (t (with-foreign-slots
   ((next fpr reason)
    value (:struct gpgme-invalid-key))
  (append (list (list :fpr fpr
       :reason reason))
  next)))))

(defun translate-gpgme-op-encrypt-result-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots

  ((invalid-recipients)
    value (:struct gpgme-op-encrypt-result))
  (list :encrypt
       (list :invalid-recipients invalid-recipients))))))

(defun translate-gpgme-recipient-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots
   ((next keyid pubkey-algo status)
    value (:struct gpgme-recipient))
  (append (list (list :keyid keyid
       :pubkey-algo pubkey-algo
       :status status))
  next)))))

(defun translate-gpgme-op-decrypt-result-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots
   ((unsupported-algorithm bitfield recipients file-name)
    value (:struct gpgme-op-decrypt-result))
  (list :decrypt (list :unsupported-algorithm unsupported-algorithm
       :bitfield bitfield
       :recipients recipients
       :file-name file-name))))))

(defun translate-gpgme-new-signature-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots
   ((next
 type pubkey-algo hash-algo timestamp fpr sig-class)
    value (:struct gpgme-new-signature))
  (append (list (list :type type
       :pubkey-algo pubkey-algo
```

```
        :hash-algo hash-algo
        :timestamp timestamp
        :fpr fpr
        :sig-class sig-class))
   next)))))

(defun translate-gpgme-op-sign-result-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
   (t (with-foreign-slots
    ((invalid-signers signatures)
     value (:struct gpgme-op-sign-result))
   (list :sign (list :invalid-signers invalid-signers
      :signatures signatures))))))

(defun translate-gpgme-signature-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
   (t (with-foreign-slots
    ((next summary fpr status notations timestamp
    exp-timestamp bitfield validity validity-reason
    pubkey-algo hash-algo)
     value (:struct gpgme-signature))
   (append (list (list :summary summary
        :fpr fpr
        :status status
        :notations notations
        :timestamp timestamp

     :exp-timestamp exp-timestamp
        :bitfield bitfield
        :validity validity
        :validity-reason validity-reason
        :pubkey-algo pubkey-algo))
   next)))))

(defun translate-gpgme-op-verify-result-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
   (t (with-foreign-slots
    ((signatures file-name)
     value (:struct gpgme-op-verify-result))
   (list :verify (list :signatures signatures
        :file-name file-name))))))

(defun translate-gpgme-import-status-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
```

```
  (t (with-foreign-slots
   ((next fpr result status)
    value (:struct gpgme-import-status))
  (append (list (list :fpr fpr
       :result result
       :status status))
  next)))))

(defun translate-gpgme-op-import-result-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots
   ((considered no-user-id imported imported-rsa unchanged
  new-user-ids new-sub-keys new-signatures
  new-revocations
 secret-read secret-imported
  secret-unchanged skipped-new-keys not-imported
  imports)
    value (:struct gpgme-op-import-result))
  (list :verify (list :considered considered
       :no-user-id no-user-id
       :imported imported
       :imported-rsa imported-rsa
       :unchanged unchanged
       :new-user-ids new-user-ids
       :new-sub-keys new-sub-keys
       :new-signatures new-signatures
       :new-revocations new-revocations
       :secret-read secret-read
       :secret-imported secret-imported
       :secret-unchanged secret-unchanged
       :skipped-new-keys skipped-new-keys
       :not-imported not-imported
       :imports imports))))))

;;; Error handling.

;;; Use gpgme-error-no-signal-t to suppress automatic error handling
;;; at translation time.
;;;
;;; FIXME: Part of this probably should be in gpg-error!

(define-condition gpgme-error (error)
 ((value :initarg :gpgme-error :reader gpgme-error-value))
 (:report (lambda (c stream)

    (format stream "GPGME returned error: ~A (~A)"
      (gpgme-strerror (gpgme-error-value c))
```

```
      (gpgme-strsource (gpgme-error-value c)))))
 (:documentation "Signalled when a GPGME function returns an error."))

(defun translate-gpgme-error-t-from-foreign (value)
 "Raise a GPGME-ERROR if VALUE is non-zero."
 (when (not (eql (gpgme-err-code value) :gpg-err-no-error))
  (error 'gpgme-error :gpgme-error value))
 (gpg-err-canonicalize value))

(defun translate-gpgme-error-t-to-foreign (value)
 "Canonicalize the error value."
 (if (eql (gpgme-err-code value) :gpg-err-no-error)
    0
    (gpg-err-as-value value)))

(defun translate-gpgme-error-no-signal-t-from-foreign (value)
 "Canonicalize the error value."
 (gpg-err-canonicalize value))


;;; *INTERNAL* Lispy Function Interface that is still close to the C
;;; interface.

;;; Passphrase callback management.

;;; Maybe: Instead, use subclassing, and provide a customizable
;;; default implementation for ease-of-use.

(defvar
 *passphrase-handles* (make-hash-table)
 "Hash table with GPGME context address as key and the corresponding
  passphrase callback object as value.")

(defcallback passphrase-cb gpgme-error-t ((handle :pointer)
      (uid-hint :string)
      (passphrase-info :string)
      (prev-was-bad :boolean)
      (fd :int))
 (handler-case
    (let* ((passphrase-cb
      (gethash (pointer-address handle) *passphrase-handles*))
     (passphrase
      (cond
  ((functionp passphrase-cb)
   (concatenate 'string
        (funcall passphrase-cb uid-hint passphrase-info
          prev-was-bad)
        '(#\Newline)))
```

```
 (t (concatenate 'string passphrase-cb '(#\Newline)))))
     (passphrase-len (length passphrase))
     ;; FIXME: Could be more robust.
     (res (system-write fd passphrase passphrase-len)))
(cond
  ((< res passphrase-len) ; FIXME: Blech.  A weak attempt to be robust.
   (gpgme-error :gpg-err-inval))
  (t (gpgme-error :gpg-err-no-error))))
  (gpgme-error (err)
(gpgme-error-value err))
  (system-error (err) (gpgme-error-from-errno (system-error-errno err)))
  ;; FIXME: The original error gets lost here.
  (condition (err) (progn
       (when *debug*
    (format t "DEBUG: passphrase-cb: Unexpressable: ~A~%"
     err))
       (gpgme-error :gpg-err-general)))))

;;; CTX is a C-pointer to the context.
(defun gpgme-set-passphrase-cb (ctx cb)
 "Set the passphrase callback for CTX."
 (let ((handle (pointer-address ctx)))
   (cond
     (cb (setf (gethash handle *passphrase-handles*) cb)
   (c-gpgme-set-passphrase-cb ctx (callback passphrase-cb) ctx))
     (t (c-gpgme-set-passphrase-cb ctx (null-pointer) (null-pointer))
  (remhash handle *passphrase-handles*)))))

;;; Progress callback management.

;;; Maybe: Instead, use subclassing, and provide a customizable
;;; default implementation for ease-of-use.

(defvar *progress-handles* (make-hash-table)
 "Hash table with GPGME context address as key and the corresponding
  progress callback
 object as value.")

(defcallback progress-cb :void ((handle :pointer)
    (what :string)
    (type :int)
    (current :int)
    (total :int))
 (handler-case
     (let* ((progress-cb
       (gethash (pointer-address handle) *progress-handles*)))
 (funcall progress-cb what type current total))
   ;; FIXME: The original error gets lost here.
```

```
  (condition (err) (when *debug*
       (format t "DEBUG: progress-cb: Unexpressable: ~A~%"
        err)))))

;;; CTX is a C-pointer to the context.
(defun gpgme-set-progress-cb (ctx cb)
 "Set the progress callback for CTX."
 (let ((handle (pointer-address ctx)))
  (cond
   (cb (setf (gethash handle *progress-handles*) cb)
  (c-gpgme-set-progress-cb ctx (callback progress-cb) ctx))
   (t (c-gpgme-set-progress-cb ctx (null-pointer) (null-pointer))
  (remhash handle *progress-handles*)))))

;;; Context management.

(defun gpgme-new (&key (protocol :openpgp) armor textmode include-certs
   keylist-mode passphrase progress file-name
 home-dir)
 "Allocate a new GPGME context."
 (with-foreign-object (ctx-p 'gpgme-ctx-t)
  (c-gpgme-new ctx-p)
  (let ((ctx (mem-ref ctx-p 'gpgme-ctx-t)))
   ;;; Set locale?
   (gpgme-set-protocol ctx protocol)
   (gpgme-set-armor ctx armor)
   (gpgme-set-textmode ctx textmode)
   (when include-certs (gpgme-set-include-certs ctx include-certs))
   (when keylist-mode (gpgme-set-keylist-mode ctx keylist-mode))
   (gpgme-set-passphrase-cb ctx passphrase)
   (gpgme-set-progress-cb ctx progress)
   (gpgme-set-engine-info ctx protocol
     :file-name file-name :home-dir home-dir)
   (when *debug* (format t "DEBUG: gpgme-new: ~A~%" ctx))
   ctx)))

(defun gpgme-release (ctx)
 "Release a GPGME context."
 (when *debug* (format t "DEBUG: gpgme-release: ~A~%" ctx))
 (c-gpgme-release ctx))

(defun gpgme-set-protocol (ctx proto)
 "Set the protocol to be used by CTX to PROTO."
 (c-gpgme-set-protocol ctx proto))

(defun gpgme-get-protocol (ctx)
 "Get
```

```
 the protocol used with CTX."
 (c-gpgme-get-protocol ctx))

;;; FIXME: How to do pretty printing?
;;;
;;; gpgme-get-protocol-name

(defun gpgme-set-armor (ctx armor)
 "If ARMOR is true, enable armor mode in CTX, disable it otherwise."
(c-gpgme-set-armor ctx armor))

(defun gpgme-armor-p (ctx)
 "Return true if armor mode is set for CTX."
 (c-gpgme-get-armor ctx))

(defun gpgme-set-textmode (ctx textmode)
 "If TEXTMODE is true, enable text mode mode in CTX, disable it otherwise."
(c-gpgme-set-textmode ctx textmode))

(defun gpgme-textmode-p (ctx)
 "Return true if text mode mode is set for CTX."
 (c-gpgme-get-textmode ctx))

(defun gpgme-set-include-certs (ctx &optional certs)
 "Include up to CERTS certificates in an S/MIME message."
 (c-gpgme-set-include-certs ctx certs))

(defun gpgme-get-include-certs (ctx)
 "Return the number of certs to include in an S/MIME message,
  or NIL if the default is used."
 (c-gpgme-get-include-certs ctx))

(defun gpgme-get-keylist-mode (ctx)
  "Get the keylist mode in CTX."
 (c-gpgme-get-keylist-mode ctx))

(defun gpgme-set-keylist-mode (ctx mode)
 "Set the keylist mode in CTX."
 (c-gpgme-set-keylist-mode ctx mode))


;;; FIXME: How to handle locale?  cffi-grovel?

(defun gpgme-get-engine-info (&optional ctx)
 "Retrieve the engine info for CTX, or the default if CTX is omitted."
 (cond
   (ctx (c-gpgme-ctx-get-engine-info ctx))
   (t (with-foreign-object (info-p 'gpgme-engine-info-t)
```

```
  (c-gpgme-get-engine-info info-p)
  (mem-ref info-p 'gpgme-engine-info-t)))))

(defun gpgme-set-engine-info (ctx proto &key file-name home-dir)
 "Set the engine info for CTX, or the default if CTX is NIL."
 (cond
   (ctx (c-gpgme-ctx-set-engine-info ctx proto file-name home-dir))
   (t (c-gpgme-set-engine-info proto file-name home-dir))))

;;; FIXME: How to do pretty printing?
;;;
;;; gpgme_pubkey_algo_name, gpgme_hash_algo_name

(defun gpgme-set-signers (ctx keys)
 "Set the signers for the context CTX."
 (c-gpgme-signers-clear ctx)
  (dolist (key keys) (c-gpgme-signers-add ctx key)))

;;;

(defun gpgme-set-sig-notation (ctx notations)
 "Set the sig notation for the context CTX."
 (c-gpgme-sig-notation-clear ctx)
 (dolist (notation notations)
   (c-gpgme-sig-notation-add
    ctx (first notation) (second notation) (third notation))))

(defun gpgme-get-sig-notation (ctx)
 "Get the signature notation data for the context CTX."
 (c-gpgme-sig-notation-get ctx))

;;; FIXME: Add I/O callback interface, for integration with clg.

;;; FIXME: Add gpgme_wait?

;;; Streams
;;; -------
;;;
;;; GPGME uses standard streams.  You can define your own streams, or
;;; use the existing file or string streams.
;;;
;;; A stream-spec is either a stream, or a list with a stream as its
;;; first argument followed by keyword parameters: encoding,
;;; file-name.
;;;
;;; FIXME: Eventually, we should provide a class that can be mixed
;;; into stream classes and which provides accessors for encoding and
;;; file-names.  This interface
```

```
 should be provided in addition to the
;;; above sleazy interface, because the sleazy interface is easier to
;;; use (less typing), and is quite sufficient in a number of cases.
;;;
;;; For best results, streams with element type (unsigned-byte 8)
;;; should be used.  Character streams may work if armor mode is used.

;;; Do we need to provide access to GPGME data objects through streams
;;; as well?  It seems to me that specific optimizations, like
;;; directly writing to file descriptors, is better done by extending
;;; the sleazy syntax (stream-spec) instead of customized streams.
;;; Customized streams do buffering, and this may mess up things.  Mmh.

(defvar *data-handles* (make-hash-table)
 "Hash table with GPGME data user callback handle address as key
  and the corresponding stream as value.")

;;; The release callback removes the stream from the *data-handles*
;;; hash and releases the CBS structure that is used as the key in
;;; that hash.  It is implicitly invoked (through
 GPGME) by
;;; gpgme-data-release.
(defcallback data-release-cb :void ((handle :pointer))
 (unwind-protect (remhash (pointer-address handle) *data-handles*)
   (when (not (null-pointer-p handle)) (foreign-free handle))))

(defcallback data-read-cb ssize-t ((handle :pointer) (buffer :pointer)
                                   (size size-t))
 (when *debug* (format t "DEBUG: gpgme-data-read-cb: want ~A~%" size))
 (let ((stream (gethash (pointer-address handle) *data-handles*)))
   (cond
     (stream
      (let* ((stream-type (stream-element-type stream))
             (seq (make-array size :element-type stream-type))
             (read (read-sequence seq stream)))
        (cond
          ((equal stream-type '(unsigned-byte 8))
           (dotimes (i read)
             (setf (mem-aref buffer :unsigned-char i)
                   (aref (the byte-array seq) i))))
          ((eql stream-type 'character)
           (dotimes (i read)
             (setf (mem-aref buffer :unsigned-char
i)
                   (char-code (aref (the character-array seq) i)))))
          (t
           (dotimes (i read)
             (setf (mem-aref buffer :unsigned-char i)
```

```
                (coerce (aref seq i) '(unsigned-byte 8))))))
      (when *debug* (format t "DEBUG: gpgme-data-read-cb: read ~A~%" read))
      read))
    (t
     (set-errno +ebadf+)
     -1))))

(defcallback data-write-cb ssize-t ((handle :pointer) (buffer :pointer)
                                    (size size-t))
 (when *debug* (format t "DEBUG: gpgme-data-write-cb: want ~A~%" size))
 (let ((stream (gethash (pointer-address handle) *data-handles*)))
  (cond
   (stream
    (let* ((stream-type (stream-element-type stream))
           (seq (make-array size :element-type stream-type)))
      (cond
       ((equal stream-type '(unsigned-byte 8))
        (dotimes (i size)
          (setf (aref (the byte-array seq) i)
                (mem-aref buffer :unsigned-char i))))
        ((eql stream-type 'character)
        (dotimes (i size)
          (setf (aref (the character-array seq) i)
                (code-char (mem-aref buffer :unsigned-char i)))))
        (t
         (dotimes (i size)
           (setf (aref seq i)
                 (coerce (mem-aref buffer :unsigned-char i) stream-type)))))
      (write-sequence seq stream)
      size))
    (t
     (set-errno +ebadf+)
     -1))))

;;; This little helper macro allows us to swallow the cbs structure by
;;; simply setting it to a null pointer, but still protect against
;;; conditions.
(defmacro with-cbs-swallowed ((cbs) &body body)
 `(let ((,cbs (foreign-alloc '(:struct gpgme-data-cbs))))
   (unwind-protect (progn ,@body)
     (when (not (null-pointer-p ,cbs)) (foreign-free ,cbs)))))

(defun gpgme-data-new (stream &key encoding file-name)
 "Allocate a new GPGME data object for STREAM."
 (with-foreign-object (dh-p 'gpgme-data-t)
   ;;; We allocate one CBS structure
 for each stream we wrap in a
   ;;; data object.  Although we could also share all these
```

```
  ;;; structures, as they contain the very same callbacks, we need a
  ;;; unique C pointer as handle anyway to look up the stream in the
  ;;; callback.  This is a convenient one to use.
  (with-cbs-swallowed (cbs)
    (setf (foreign-slot-value cbs '(:struct gpgme-data-cbs) 'read)
          (callback data-read-cb))
    (setf (foreign-slot-value cbs '(:struct gpgme-data-cbs) 'write)
          (callback data-write-cb))
    (setf (foreign-slot-value cbs '(:struct gpgme-data-cbs) 'seek)
          (null-pointer))
    (setf (foreign-slot-value cbs '(:struct gpgme-data-cbs) 'release)
          (callback data-release-cb))
    (c-gpgme-data-new-from-cbs dh-p cbs cbs)
    (let ((dh (mem-ref dh-p 'gpgme-data-t)))
 (when encoding (gpgme-data-set-encoding dh encoding))
 (when file-name (gpgme-data-set-file-name dh file-name))
 ;;; Install the stream into the hash table and
 swallow the cbs
       ;;; structure while protecting against any errors.
 (unwind-protect
      (progn
       (setf (gethash (pointer-address cbs) *data-handles*) stream)
       (setf cbs (null-pointer)))
   (when (not (null-pointer-p cbs)) (c-gpgme-data-release dh)))
 (when *debug* (format t "DEBUG: gpgme-data-new: ~A~%" dh))
 dh))))

;;; This function releases a GPGME data object.  It implicitly
;;; invokes the data-release-cb function to clean up associated junk.
(defun gpgme-data-release (dh)
 "Release a GPGME data object."
 (when *debug* (format t "DEBUG: gpgme-data-release: ~A~%" dh))
 (c-gpgme-data-release dh))

(defclass data ()
 (c-data)  ; The C data object pointer
 (:documentation "The GPGME data type."))

(defmethod initialize-instance :after ((data data) &key streamspec
                                       &allow-other-keys)
 (let ((c-data (if (listp streamspec)
                   (apply #'gpgme-data-new streamspec)
                   (gpgme-data-new streamspec)))
       (cleanup t))
   (unwind-protect
        (progn
         (setf (slot-value data 'c-data) c-data)
         (finalize data (lambda () (gpgme-data-release c-data)))
```

```
        (setf cleanup nil))
    (if cleanup (gpgme-data-release c-data)))))

(defun translate-gpgme-data-t-to-foreign (value)
 ;; Allow a pointer to be passed directly for the finalizer to work.
 (cond
   ((null value) (null-pointer))
   ((pointerp value) value)
   (t (slot-value value 'c-data))))

(defmacro with-gpgme-data ((dh streamspec) &body body)
 `(let ((,dh (make-instance 'data :streamspec ,streamspec)))
    ,@body))

(defun gpgme-data-get-encoding (dh)
 "Get the encoding associated with the data object DH."
 (c-gpgme-data-get-encoding dh))

(defun gpgme-data-set-encoding (dh encoding)
 "Set the encoding associated with the data object DH to ENCODING."
 (c-gpgme-data-set-encoding dh encoding))

(defun gpgme-data-get-file-name (dh)
 "Get the file name associated with the data object
 DH."
 (c-gpgme-data-get-file-name dh))

(defun gpgme-data-set-file-name (dh file-name)
 "Set the file name associated with the data object DH to FILE-NAME."
 (c-gpgme-data-set-file-name dh file-name))

;;; FIXME: Add key accessor interfaces.

(defun gpgme-get-key (ctx fpr &optional secret)
 "Get the key with the fingerprint FPR from the context CTX."
 (with-foreign-object (key-p 'gpgme-key-t)
   (c-gpgme-get-key ctx fpr key-p secret)
   (mem-ref key-p 'gpgme-key-t)))

(defun gpgme-key-ref (key)
 "Acquire an additional reference to the key KEY."
 (when *debug* (format t "DEBUG: gpgme-key-ref: ~A~%" key))
 (c-gpgme-key-ref key))

(defun gpgme-key-unref (key)
 "Release a reference to the key KEY."
 (when *debug* (format t "DEBUG: gpgme-key-unref: ~A~%" key))
 (c-gpgme-key-unref key))
```

```
;;; FIXME: We REALLY need pretty printing for keys and all the other
;;; big structs.

;;; Various interfaces.

(defun gpgme-check-version (&optional req-version)
 (c-gpgme-check-version req-version))

;;;
;;;
 The *EXPORTED* CLOS interface.
;;;

;;; The context type.

;;; We wrap the C context pointer into a class object to be able to
;;; stick a finalizer on it.

(defclass context ()
 (c-ctx  ; The C context object pointer.
  signers ; The list of signers.
  sig-notation) ; The list of signers.
 (:documentation "The GPGME context type."))

(defmethod initialize-instance :after ((ctx context) &rest rest
         &key &allow-other-keys)
 (let ((c-ctx (apply #'gpgme-new rest))
 (cleanup t))
   (unwind-protect
  (progn (setf (slot-value ctx 'c-ctx) c-ctx)
  (finalize ctx (lambda () (gpgme-release c-ctx)))
  (setf cleanup nil))
     (if cleanup (gpgme-release c-ctx)))))

(defun translate-gpgme-ctx-t-to-foreign (value)
 ;; Allow a pointer to be passed directly for the finalizer to work.
 (if (pointerp value) value (slot-value value 'c-ctx)))

(defmacro context (&rest rest)
 "Create a new GPGME context."
 `(make-instance 'context ,@rest))

;;; The context type: Accessor
 functions.

;;; The context type: Accessor functions: Protocol.
```

```
(defgeneric protocol (ctx)
 (:documentation "Get the protocol of CONTEXT."))

(defmethod protocol ((ctx context))
 (gpgme-get-protocol ctx))

(defgeneric (setf protocol) (protocol ctx)
 (:documentation "Set the protocol of CONTEXT to PROTOCOL."))

;;; FIXME: Adjust translator to reject invalid protocols.  Currently,
;;; specifying an invalid protocol throws a "NIL is not 32 signed int"
;;; error.  This is suboptimal.
(defmethod (setf protocol) (protocol (ctx context))
 (gpgme-set-protocol ctx protocol))

;;; The context type: Accessor functions: Armor.
;;; FIXME: Is it good style to make foop setf-able?  Or should it be
;;; foo/foop for set/get?

(defgeneric armorp (ctx)
 (:documentation "Get the armor flag of CONTEXT."))

(defmethod armorp ((ctx context))
 (gpgme-armor-p ctx))

(defgeneric (setf armorp) (armor ctx)
 (:documentation "Set the armor flag of CONTEXT to ARMOR."))

(defmethod (setf armorp) (armor (ctx
 context))
 (gpgme-set-armor ctx armor))

;;; The context type: Accessor functions: Textmode.
;;; FIXME: Is it good style to make foop setf-able?  Or should it be
;;; foo/foop for set/get?

(defgeneric textmodep (ctx)
 (:documentation "Get the text mode flag of CONTEXT."))

(defmethod textmodep ((ctx context))
 (gpgme-textmode-p ctx))

(defgeneric (setf textmodep) (textmode ctx)
 (:documentation "Set the text mode flag of CONTEXT to TEXTMODE."))

(defmethod (setf textmodep) (textmode (ctx context))
 (gpgme-set-textmode ctx textmode))
```

```
;;; The context type: Accessor functions: Include Certs.

(defgeneric include-certs (ctx)
 (:documentation "Get the number of included certificates in an
                  S/MIME message, or NIL if the default is used."))

(defmethod include-certs ((ctx context))
 (gpgme-get-include-certs ctx))

(defgeneric (setf include-certs) (certs ctx)
 (:documentation "Return the number of certificates to include in an
                  S/MIME message, or
 NIL if the default is used."))

(defmethod (setf include-certs) (certs (ctx context))
 (gpgme-set-include-certs ctx certs))

;;; The context type: Accessor functions: Engine info.

(defgeneric engine-info (ctx)
 (:documentation "Retrieve the engine info for CTX."))

(defmethod engine-info ((ctx context))
 (gpgme-get-engine-info ctx))

(defgeneric (setf engine-info) (info ctx)
 (:documentation "Set the engine info for CTX."))

(defmethod (setf engine-info) (info (ctx context))
 (dolist (proto '(:openpgp :cms))
   (let ((pinfo (getf info proto)))
     (when pinfo
 (gpgme-set-engine-info ctx proto :file-name (getf pinfo :file-name)
         :home-dir (getf pinfo :home-dir))))))

;;; The context type: Accessor functions: Keylist mode.

(defgeneric keylist-mode (ctx)
 (:documentation "Get the keylist mode of CTX."))

(defmethod keylist-mode ((ctx context))
 (gpgme-get-keylist-mode ctx))

(defgeneric (setf keylist-mode) (mode ctx)
 (:documentation "Set the keylist mode of CTX to MODE."))

(defmethod
```

```
 (setf keylist-mode) (mode (ctx context))
 (gpgme-set-keylist-mode ctx mode))

;;; The context type: Accessor functions: Signers.

(defgeneric signers (ctx)
 (:documentation "Get the signers of CTX."))

(defmethod signers ((ctx context))
 (slot-value ctx 'signers))

(defgeneric (setf signers) (signers ctx)
 (:documentation "Set the signers of CTX to SIGNERS."))

(defmethod (setf keylist-mode) (signers (ctx context))
 (gpgme-set-signers ctx signers)
 (setf (slot-value ctx 'signers) signers))

;;; The context type: Accessor functions: Sig notations.

(defgeneric sig-notations (ctx)
 (:documentation "Get the signature notations of CTX."))

(defmethod sig-notations ((ctx context))
 (slot-value ctx 'signers))

(defgeneric (setf sig-notations) (notations ctx)
 (:documentation "Set the signatire notations of CTX to NOTATIONS."))

(defmethod (setf sig-notations) (notations (ctx context))
 (gpgme-set-signers ctx notations)
 (setf (slot-value ctx 'notations) notations))

;;;
 The context type: Support macros.

(defmacro with-context ((ctx &rest rest) &body body)
 `(let ((,ctx (make-instance 'context ,@rest)))
   ,@body))

;;; The key type.

(defclass key ()
 (c-key)  ; The C key object pointer.
 (:documentation "The GPGME key type."))

;;; In the initializer, we swallow the c-key argument.
(defmethod initialize-instance :after ((key key) &key c-key
```

```
          &allow-other-keys)
 (setf (slot-value key 'c-key) c-key)
 (finalize key (lambda () (gpgme-key-unref c-key))))

(defun translate-gpgme-key-t-from-foreign (value)
 (when *debug* (format t "DEBUG: import key: ~A~%" value))
 (make-instance 'key :c-key value))

(defun translate-gpgme-key-t-to-foreign (value)
 ;; Allow a pointer to be passed directly for the finalizer to work.
 (if (pointerp value) value (slot-value value 'c-key)))

(defmethod print-object ((key key) stream)
 (print-unreadable-object (key stream :type t :identity t)
  (format stream "~s" (fpr key))))

;;; The key type:
 Accessor functions.

;;; FIXME: The bitfield and flags contain redundant information at
;;; this point.  FIXME: Deal nicer with zero-length name (policy url)
;;; and zero length value (omit?) and human-readable (convert to string).
;;; FIXME: Turn binary data into sequence or vector or what it should be.
;;; FIXME: Turn the whole thing into a hash?
(defun translate-gpgme-sig-notation-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots
   ((next name value name-len value-len flags bitfield)
    value (:struct gpgme-sig-notation))
  (append (list (list
  :name name
  :value value
  :name-len name-len
  :value-len value-len
  :flags flags
  :bitfield bitfield))
  next)))))

;;; FIXME: Deal nicer with timestamps.  bitfield field name?
(defun translate-gpgme-subkey-t-from-foreign (value)
 (cond
  ((null-pointer-p value) nil)
  (t (with-foreign-slots
   ((next bitfield pubkey-algo length keyid fpr timestamp expires)
    value (:struct gpgme-subkey))
```

```
 (append (list (list
   :bitfield bitfield
   :pubkey-algo pubkey-algo
   :length length
   :keyid keyid
   :fpr fpr
   :timestamp timestamp
   :expires expires))
   next)))))

(defun translate-gpgme-key-sig-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
   (t (with-foreign-slots
    ((next bitfield pubkey-algo keyid timestamp expires status
    uid name email comment sig-class)
     value (:struct gpgme-key-sig))
  (append (list (list
   :bitfield bitfield
   :pubkey-algo pubkey-algo
   :keyid keyid
   :timestamp timestamp
   :expires expires
   :status status
   :uid uid
   :name name
   :email email
   :comment comment
   :sig-class sig-class))
   next)))))

(defun translate-gpgme-user-id-t-from-foreign (value)
 (cond
   ((null-pointer-p value) nil)
   (t (with-foreign-slots
    ((next bitfield validity uid name email comment signatures)
     value (:struct gpgme-user-id))
  (append (list (list
   :bitfield bitfield
   :validity validity
   :uid uid
   :name
 name
   :email email
   :comment comment
   :signatures signatures))
   next)))))
```

```
(defun key-data (key)
 (with-slots (c-key) key
   (with-foreign-slots
 ((bitfield protocol issuer-serial issuer-name chain-id
     owner-trust subkeys uids keylist-mode)
  c-key (:struct gpgme-key))
     (list
      :bitfield bitfield
      :protocol protocol
      :issuer-serial issuer-serial
      :issuer-name issuer-name
      :chain-id chain-id
      :owner-trust owner-trust
      :subkeys subkeys
      :uids uids
      :keylist-mode keylist-mode))
   ))


(defgeneric fpr (key)
 (:documentation "Get the primary fingerprint of the key."))

(defmethod fpr ((key key))
 (getf (car (getf (key-data key) :subkeys)) :fpr))


;;; The context type: Crypto-Operations.

(defgeneric get-key (ctx fpr &optional secret)
 (:documentation "Get the (secret) key FPR from CTX."))

(defmethod get-key ((ctx context) fpr &optional secret)
 (gpgme-get-key ctx fpr secret))

;;; Encrypt.

(defgeneric
 op-encrypt (ctx recp plain cipher &key always-trust sign)
 (:documentation "Encrypt."))

(defmethod op-encrypt ((ctx context) recp plain cipher
        &key always-trust sign)
 (with-foreign-object (c-recp :pointer (+ 1 (length recp)))
   (dotimes (i (length recp))
     (setf (mem-aref c-recp 'gpgme-key-t i) (elt recp i)))
   (setf (mem-aref c-recp :pointer (length recp)) (null-pointer))
   (with-gpgme-data (in plain)
     (with-gpgme-data (out cipher)
```

```
 (let ((flags))
   (if always-trust (push :always-trust flags))
   (cond
     (sign
      (c-gpgme-op-encrypt-sign ctx c-recp flags in out)
      (append (c-gpgme-op-encrypt-result ctx)
       (c-gpgme-op-sign-result ctx)))
     (t
      (c-gpgme-op-encrypt ctx c-recp flags in out)
      (c-gpgme-op-encrypt-result ctx))))))))

;;; Decrypt.

(defgeneric op-decrypt (ctx cipher plain &key verify)
 (:documentation "Decrypt."))

(defmethod op-decrypt ((ctx context) cipher plain &key verify)
 (with-gpgme-data (in cipher)
   (with-gpgme-data
 (out plain)
     (cond
 (verify
  (c-gpgme-op-decrypt-verify ctx in out)
  (append (c-gpgme-op-decrypt-result ctx)
   (c-gpgme-op-verify-result ctx)))
 (t
  (c-gpgme-op-decrypt ctx in out)
  (c-gpgme-op-decrypt-result ctx))))))

;;; Signing.

(defgeneric op-sign (ctx plain sig &optional mode)
 (:documentation "Sign."))

(defmethod op-sign ((ctx context) plain sig &optional (mode :none))
 (with-gpgme-data (in plain)
   (with-gpgme-data (out sig)
     (c-gpgme-op-sign ctx in out mode)
     (c-gpgme-op-sign-result ctx))))

;;; Verify.

(defgeneric op-verify (ctx sig text &key detached)
 (:documentation "Verify."))

(defmethod op-verify ((ctx context) sig text &key detached)
 (with-gpgme-data (in sig)
   (with-gpgme-data (on text)
```

```
     (c-gpgme-op-verify ctx in (if detached on nil)
    (if detached nil on))
     (c-gpgme-op-verify-result ctx))))

;;; Import.

(defgeneric op-import (ctx keydata)
 (:documentation "Import."))

(defmethod op-import ((ctx context) keydata)
  (with-gpgme-data (in keydata)
   (c-gpgme-op-import ctx in)
   (c-gpgme-op-import-result ctx)))

;;; Export.

(defgeneric op-export (ctx pattern keydata)
 (:documentation "Export public key data matching PATTERN to the
                  stream KEYDATA."))

(defmethod op-export ((ctx context) pattern keydata)
 (with-gpgme-data (dh keydata)
   (c-gpgme-op-export ctx pattern 0 dh)))

;;; Key generation.



;;;
;;; Initialization
;;;

(defun check-version (&optional req-version)
 "Check that the GPGME version requirement is satisfied."
 (gpgme-check-version req-version))

(defparameter *version* (check-version)
 "The version number of GPGME used.")
#include "qgpgme/signencryptjob.h"
{
 "manifest_version": 2,

 "name": "gpgme-json with native Messaging",
 "description": "A simple demo application",
 "version": "0.1",
 "content_security_policy": "default-src 'self' filesystem:",
 "browser_action": {
   "default_icon": "testicon.png",
   "default_title": "gpgme.js",
```

```
  "default_popup": "popup.html"
 },
 "permissions": ["nativeMessaging", "activeTab"]
}
{
 "info": [{
            "protocol":     "OpenPGP"
        }, {
            "protocol":     "spawn",
            "fname":        "/nonexistent",
            "version":      "1.0.0",
            "req_version":  "1.0.0"
        }]
}
/* qgpgmetofupolicyjob.h

  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of this program with any edition of

 the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
#ifndef QGPGME_QGPGMETOFUPOLICYJOB_H
#define QGPGME_QGPGMETOFUPOLICYJOB_H
```

```
#include "tofupolicyjob.h"

#include "threadedjobmixin.h"
namespace GpgME
{
  class Key;
} // namespace GpgME

namespace QGpgME {

class QGpgMETofuPolicyJob
#ifdef Q_MOC_RUN
  : public TofuPolicyJob
#else
  : public _detail::ThreadedJobMixin<TofuPolicyJob, std::tuple<GpgME::Error, QString, GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMETofuPolicyJob(GpgME::Context
 *context);
  ~QGpgMETofuPolicyJob();

  void start(const GpgME::Key &key, GpgME::TofuInfo::Policy policy) Q_DECL_OVERRIDE;
  GpgME::Error exec(const GpgME::Key &key, GpgME::TofuInfo::Policy policy) Q_DECL_OVERRIDE;
};

}

#endif
{
  "op": "keylist",
  "keys": ["alpha@example.net", "bravo@example.net"],
  "chunksize": 64
}
2011-12-02  Werner Koch  <wk@g10code.com>

 NB: ChangeLog files are no longer manually maintained.  Starting
 on December 1st, 2011 we put change information only in the GIT
 commit log, and generate a top-level ChangeLog file from logs at
 "make dist".  See doc/HACKING for details.

2008-11-08  Moritz  <moritz@gnu.org>
```

* gpgme.lisp (size-t): Wrong call to defctype: function accepts
optional, not keyword argument.
(ssize-t): Likewise.
(off-t): Likewise.
(gpgme-data-t, gpgme-ctx-t): Likewise.
(gpgme-error-t): Likewise.
(gpgme-error-no-signal-t): Likewise.
(gpgme-err-code-t): Likewise.
(gpgme-err-source-t): Likewise.
(gpgme-sig-notation-t, gpgme-engine-info-t): Likewise.
(gpgme-subkey-t): Likewise.
(gpgme-key-sig-t): Likewise.
(gpgme-user-id-t): Likewise.
(gpgme-key-t): Likewise.
(gpgme-data-cbs-t): Likewise.
(gpgme-invalid-key-t): Likewise.
(gpgme-op-encrypt-result-t): Likewise.
(gpgme-recipient-t): Likewise.
(gpgme-op-decrypt-result-t): Likewise.
(gpgme-new-signature-t):
Likewise.
(gpgme-op-sign-result-t): Likewise.
(gpgme-signature-t): Likewise.
(gpgme-op-verify-result-t): Likewise.
(gpgme-import-status-t): Likewise.
(gpgme-op-import-result-t): Likewise.
(gpgme-op-genkey-result-t): Likewise.
(gpgme-op-keylist-result-t): Likewise.

2006-07-06 Marcus Brinkmann <marcus@g10code.de>

* Initial release.

Copyright (C) 2006, 2008 g10 Code GmbH

This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
/*
exception.h - exception wrapping a gpgme error
Copyright (C) 2007 Klarlvdalens Datakonsult AB
2016 Bundesamt fr Sicherheit in der Informationstechnik
Software engineering by Intevation GmbH

This file is part of GPGME++.

GPGME++ is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public
License as published by the Free Software Foundation; either
version 2 of the License, or (at your option) any later version.

GPGME++ is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License
along with GPGME++; see the file COPYING.LIB. If not, write to the
Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301, USA.
*/

```
// -*- c++ -*-
#ifndef
 __GPGMEPP_EXCEPTION_H__
#define __GPGMEPP_EXCEPTION_H__

#include "error.h"

#include <stdexcept>
#include <string>

namespace GpgME
{

class GPGMEPP_EXPORT Exception : public std::runtime_error
{
public:
  enum Options {
     NoOptions = 0x0,
     MessageOnly = 0x1,

     AllOptions = MessageOnly
  };

  explicit Exception(const GpgME::Error &err, const std::string &msg = std::string(), Options opt = NoOptions)
     : std::runtime_error(make_message(err, msg, opt)), m_error(err), m_message(msg) {}

  ~Exception() throw();

  Error error() const
  {
```

```
    return m_error;
  }
  const std::string &message() const
  {
    return m_message;
  }
private:
  static std::string make_message(const GpgME::Error &err, const std::string &msg);
  static std::string make_message(const GpgME::Error &err, const std::string &msg, Options opt);
private:
  const GpgME::Error m_error;
  const std::string m_message;
};

} // namespace GpgME

#endif /* __GPGMEPP_EXCEPTION_H__
 */
/*
  qgpgmesignkeyjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
```

```
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __QGPGME_QGPGMESIGNKEYJOB_H__
#define __QGPGME_QGPGMESIGNKEYJOB_H__

#include "signkeyjob.h"

#include "threadedjobmixin.h"

#include <QString>

#ifdef BUILDING_QGPGME
# include "key.h"
#else
#include <gpgme++/key.h>
#endif

namespace QGpgME
{

class QGpgMESignKeyJob
#ifdef Q_MOC_RUN
   : public SignKeyJob
#else
   : public _detail::ThreadedJobMixin<SignKeyJob>
#endif
{
   Q_OBJECT
#ifdef
 Q_MOC_RUN
public Q_SLOTS:
   void slotFinished();
#endif
public:
   explicit QGpgMESignKeyJob(GpgME::Context *context);
   ~QGpgMESignKeyJob();

   /* from SignKeyJob */
   GpgME::Error start(const GpgME::Key &key) Q_DECL_OVERRIDE;

   /* from SignKeyJob */
   void setUserIDsToSign(const std::vector<unsigned int> &idsToSign) Q_DECL_OVERRIDE;

   /* from SignKeyJob */
   void setCheckLevel(unsigned int checkLevel) Q_DECL_OVERRIDE;
```

```
  /* from SignKeyJob */
  void setExportable(bool exportable) Q_DECL_OVERRIDE;

  /* from SignKeyJob */
  void setSigningKey(const GpgME::Key &key) Q_DECL_OVERRIDE;

  /* from SignKeyJob */
  void setNonRevocable(bool nonRevocable) Q_DECL_OVERRIDE;

  /* from SignKeyJob */
  void setRemark(const QString &remark) Q_DECL_OVERRIDE;

  /* from SignKeyJob */
  void setDupeOk(bool value) Q_DECL_OVERRIDE;

private:
  std::vector<unsigned int> m_userIDsToSign;
  GpgME::Key m_signingKey;
  unsigned int m_checkLevel;

 bool m_exportable;
  bool m_nonRevocable;
  bool m_started;
  bool m_dupeOk;
  QString m_remark;
};
}

#endif // __QGPGME_QGPGMESIGNKEYJOB_H__
/*
# Copyright (C) 2016 g10 Code GmbH
# Copyright (C) 2004,2008 Igor Belyi <belyi@users.sourceforge.net>
# Copyright (C) 2002 John Goerzen <jgoerzen@complete.org>
#
#    This library is free software; you can redistribute it and/or
#    modify it under the terms of the GNU Lesser General Public
#    License as published by the Free Software Foundation; either
#    version 2.1 of the License, or (at your option) any later version.
#
#    This library is distributed in the hope that it will be useful,
#    but WITHOUT ANY WARRANTY; without even the implied warranty of
#    MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
#    Lesser General Public License for more details.
#
#    You should have received a copy of the GNU Lesser General Public
#    License along with this library; if not, write to the Free Software
#    Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307  USA
```

```
*/
%module gpgme
%include "cpointer.i"
%include "cstring.i"

/* no need to record
 whether GPGME's c++ bindings were built
  concurrently with the python bindings */
%ignore HAVE_CXX11;

%{
/* We use public symbols (eg. "_obsolete_class") which are marked as
* deprecated but we need to keep them.  Silence the warning.  */
#pragma GCC diagnostic ignored "-Wdeprecated-declarations"
%}

/* Generate doc strings for all methods.

  This will generate docstrings of the form

    gpgme_op_encrypt(ctx, recp, flags, plain, cipher) -> gpgme_error_t

  which we transform into

    ctx.op_encrypt(recp, flags, plain, cipher) -> gpgme_error_t

  for automagically wrapped functions.  */
%feature("autodoc", "0");


/* Allow use of Unicode objects, bytes, and None for strings.  */
%typemap(in) const char *(PyObject *encodedInput = NULL) {
 if ($input == Py_None)
   $1 = NULL;
 else if (PyUnicode_Check($input))
   {
     encodedInput = PyUnicode_AsUTF8String($input);
     if (encodedInput == NULL)
       return NULL;
     $1 = PyBytes_AsString(encodedInput);
   }
 else
 if (PyBytes_Check($input))
   $1 = PyBytes_AsString($input);
 else {
   PyErr_Format(PyExc_TypeError,
                "arg %d: expected str, bytes, or None, got %s",
   $argnum, $input->ob_type->tp_name);
```

```
  return NULL;
 }
}
%typemap(freearg) const char * {
 Py_XDECREF(encodedInput$argnum);
}

/* Likewise for a list of strings.  */
%typemap(in) const char *[] (void *vector = NULL,
                             size_t size,
                             PyObject **pyVector = NULL) {
 /* Check if is a list */
 if (PyList_Check($input)) {
  size_t i, j;
  size = PyList_Size($input);
  $1 = (char **) (vector = malloc((size+1) * sizeof(char *)));
  pyVector = calloc(sizeof *pyVector, size);

  for (i = 0; i < size; i++) {
   PyObject *o = PyList_GetItem($input,i);
   if (PyUnicode_Check(o))
    {
     pyVector[i] = PyUnicode_AsUTF8String(o);
     if (pyVector[i] == NULL)
      {
       free(vector);
       for (j = 0; j < i; j++)
         Py_XDECREF(pyVector[j]);
       return NULL;
      }
     $1[i] = PyBytes_AsString(pyVector[i]);
    }
   else if (PyString_Check(o))
 $1[i] = PyString_AsString(o);
   else {
 PyErr_Format(PyExc_TypeError,
              "arg %d: list must contain only str or bytes, got %s "
              "at position %d",
              $argnum, o->ob_type->tp_name, i);
 free($1);
 return NULL;
   }
  }
  $1[i] = NULL;
 } else {
  PyErr_Format(PyExc_TypeError,
             "arg %d: expected a list of str or bytes, got %s",
             $argnum, $input->ob_type->tp_name);
```

```
  return NULL;
 }
}
%typemap(freearg) const char *[] {
 size_t i;
 free(vector$argnum);
 for (i = 0; i < size$argnum; i++)
  Py_XDECREF(pyVector$argnum[i]);
}

/* Release returned buffers as necessary.  */
%typemap(newfree) char * "gpgme_free($1);";
%newobject gpgme_data_release_and_get_mem;
%newobject gpgme_pubkey_algo_string;
%newobject gpgme_addrspec_from_uid;

%typemap(arginit)
 gpgme_key_t [] {
 $1 = NULL;
}

%typemap(in) gpgme_key_t [] {
 int i, numb = 0;
 if (!PySequence_Check($input)) {
  PyErr_Format(PyExc_ValueError, "arg %d: Expected a list of gpgme_key_t",
  $argnum);
  return NULL;
 }
 if((numb = PySequence_Length($input)) != 0) {
  $1 = (gpgme_key_t*)malloc((numb+1)*sizeof(gpgme_key_t));
  for(i=0; i<numb; i++) {
   PyObject *pypointer = PySequence_GetItem($input, i);

   /* input = $input, 1 = $1, 1_descriptor = $1_descriptor */
   /* &1_descriptor = $&1_descriptor *1_descriptor = $*1_descriptor */

   /* Following code is from swig's python.swg.  */
   if ((SWIG_ConvertPtr(pypointer,(void **) &$1[i], $*1_descriptor,SWIG_POINTER_EXCEPTION | $disown ))
== -1) {
    Py_DECREF(pypointer);
 PyErr_Format(PyExc_TypeError,
              "arg %d: list must contain only gpgme_key_ts, got %s "
              "at position %d",
              $argnum, pypointer->ob_type->tp_name,
 i);
    free($1);
 return NULL;
   }
```

```
    Py_DECREF(pypointer);
  }
  $1[numb] = NULL;
 }
}
%typemap(freearg) gpgme_key_t [] {
 if ($1) free($1);
}

/* Special handling for references to our objects.  */
%typemap(in) gpgme_data_t DATAIN (gpgme_data_t wrapper = NULL,
                                  PyObject *bytesio = NULL,
                                  Py_buffer view, int have_view = 0) {
 /* If we create a temporary wrapper object, we will store it in
    wrapperN, where N is $argnum.  Here in this fragment, SWIG will
    automatically append $argnum.  */
 memset(&view, 0, sizeof view);
 if ($input == Py_None)
  $1 = NULL;
 else {
  PyObject *pypointer;
  pypointer = _gpg_obj2gpgme_data_t($input, $argnum, &wrapper,
                                    &bytesio, &view);
  if (pypointer == NULL)
    return NULL;
  have_view = !! view.obj;

  /* input = $input, 1 = $1, 1_descriptor = $1_descriptor */

  /* Following code is from swig's python.swg.
  */

  if ((SWIG_ConvertPtr(pypointer,(void **) &$1, $1_descriptor,
       SWIG_POINTER_EXCEPTION | $disown )) == -1) {
    Py_DECREF(pypointer);
    return NULL;
  }
  Py_DECREF(pypointer);
 }
}

#if HAVE_DATA_H
/* If we are doing an in-tree build, we can use the internal
  representation of struct gpgme_data for an very efficient check if
  the buffer has been modified.  */
%{
#include "data.h" /* For struct gpgme_data.  */
%}
```

```
#endif

%typemap(freearg) gpgme_data_t DATAIN {
 /* See whether we need to update the Python buffer.  */
 if (resultobj && wrapper$argnum && view$argnum.buf)
   {
     int dirty;
     char *new_data = NULL;
     size_t new_size;

#if HAVE_DATA_H
     new_data = wrapper$argnum->data.mem.buffer;
     new_size = wrapper$argnum->data.mem.length;
     dirty = new_data != NULL;
#else
     new_data = gpgme_data_release_and_get_mem (wrapper$argnum, &new_size);
     wrapper$argnum = NULL;
     dirty = new_size != view$argnum.len

     || memcmp (new_data, view$argnum.buf, view$argnum.len);
#endif

     if (dirty)
       {
         /* The buffer is dirty.  */
         if (view$argnum.readonly)
           {
             Py_XDECREF(resultobj);
             resultobj = NULL;
             PyErr_SetString(PyExc_ValueError,
                             "cannot update read-only buffer");
           }

         /* See if we need to truncate the buffer.  */
         if (resultobj && view$argnum.len != new_size)
           {
             if (bytesio$argnum == NULL)
               {
                 Py_XDECREF(resultobj);
                 resultobj = NULL;
                 PyErr_SetString(PyExc_ValueError, "cannot resize buffer");
               }
             else
               {
                 PyObject *retval;
                 PyBuffer_Release(&view$argnum);
                 assert(view$argnum.obj == NULL);
                 retval = PyObject_CallMethod(bytesio$argnum, "truncate",
```

```
                    "l", (long) new_size);
            if (retval == NULL)
              {
                Py_XDECREF(resultobj);
                resultobj = NULL;
              }
            else
              {
                Py_DECREF(retval);

                retval = PyObject_CallMethod(bytesio$argnum,
                                             "getbuffer", NULL);
                if (retval == NULL
                    || PyObject_GetBuffer(retval, &view$argnum,
                                          PyBUF_SIMPLE|PyBUF_WRITABLE) < 0)
                  {
                    Py_XDECREF(resultobj);
                    resultobj = NULL;
                  }

                Py_XDECREF(retval);

                if (resultobj && view$argnum.len
                    != new_size)
                  {
                    Py_XDECREF(resultobj);

                   resultobj = NULL;
                    PyErr_Format(PyExc_ValueError,
                                 "Expected buffer of length %zu, got %zi",
                                 new_size,
                                 view$argnum.len);
                  }
              }
          }
        }
       if (resultobj)
         memcpy(view$argnum.buf, new_data, new_size);
      }
#if ! HAVE_DATA_H
    free (new_data);
#endif
  }

 /* Free the temporary wrapper, if any.  */
 if (wrapper$argnum)
   gpgme_data_release(wrapper$argnum);
```

```
 Py_XDECREF (bytesio$argnum);
 if (have_view$argnum && view$argnum.buf)
   PyBuffer_Release(&view$argnum);
}

%apply gpgme_data_t DATAIN {gpgme_data_t plain, gpgme_data_t cipher,
   gpgme_data_t sig, gpgme_data_t signed_text,
   gpgme_data_t plaintext, gpgme_data_t keydata,
   gpgme_data_t pubkey, gpgme_data_t seckey,
   gpgme_data_t out, gpgme_data_t data};

/* SWIG has problems
 interpreting ssize_t, off_t or gpgme_error_t in
  gpgme.h.  */
%typemap(out) ssize_t, gpgme_error_t, gpgme_err_code_t, gpgme_err_source_t, gpg_error_t {
 $result = PyLong_FromLong($1);
}

%typemap(in) ssize_t, gpgme_error_t, gpgme_err_code_t, gpgme_err_source_t, gpg_error_t {
 if (PyLong_Check($input))
   $1 = PyLong_AsLong($input);
#if PY_MAJOR_VERSION < 3
 else if (PyInt_Check($input))
   $1 = PyInt_AsLong($input);
#endif
 else
   PyErr_SetString(PyExc_TypeError, "Numeric argument expected");
}

%typemap(out) off_t {
#if _FILE_OFFSET_BITS == 64
 $result = PyLong_FromLongLong($1);
#else
 $result = PyLong_FromLong($1);
#endif
}

%typemap(in) off_t {
 if (PyLong_Check($input))
#if _FILE_OFFSET_BITS == 64
   $1 = PyLong_AsLongLong($input);
#else
   $1 = PyLong_AsLong($input);
#endif
#if PY_MAJOR_VERSION < 3
 else if (PyInt_Check($input))
   $1 = PyInt_AsLong($input);
#endif
```

```
 else
   PyErr_SetString(PyExc_TypeError, "Numeric argument expected");
}

/* Those are for gpgme_data_read()
 and gpgme_strerror_r().  */
%typemap(in) (void *buffer, size_t size), (char *buf, size_t buflen) {
 {
   long tmp$argnum;
   if (PyLong_Check($input))
     tmp$argnum = PyLong_AsLong($input);
#if PY_MAJOR_VERSION < 3
   else if (PyInt_Check($input))
     tmp$argnum = PyInt_AsLong($input);
#endif
   else
     {
       PyErr_SetString(PyExc_TypeError, "Numeric argument expected");
       return NULL;
     }

   if (tmp$argnum < 0) {
     PyErr_SetString(PyExc_ValueError, "Positive integer expected");
     return NULL;
   }
   $2 = (size_t) tmp$argnum;
   $1 = ($1_ltype) malloc($2+1);
 }
}
%typemap(argout) (void *buffer, size_t size), (char *buf, size_t buflen) {
 Py_XDECREF($result);   /* Blow away any previous result */
 if (result < 0) {      /* Check for I/O error */
   free($1);
   return PyErr_SetFromErrno(PyExc_RuntimeError);
 }
 $result = PyBytes_FromStringAndSize($1,result);
 free($1);
}

/* For gpgme_data_write, but should be universal.  */
%typemap(in)
 (const void *buffer, size_t size)(PyObject *encodedInput = NULL) {
 Py_ssize_t ssize;

 if ($input == Py_None)
   $1 = NULL, $2 = 0;
 else if (PyUnicode_Check($input))
   {
```

```
    encodedInput = PyUnicode_AsUTF8String($input);
    if (encodedInput == NULL)
      return NULL;
    if (PyBytes_AsStringAndSize(encodedInput, (char **) &$1, &ssize) == -1)
      {
        Py_DECREF(encodedInput);
        return NULL;
      }
  }
 else if (PyBytes_Check($input))
  PyBytes_AsStringAndSize($input, (char **) &$1, &ssize);
 else {
  PyErr_Format(PyExc_TypeError,
               "arg %d: expected str, bytes, or None, got %s",
  $argnum, $input->ob_type->tp_name);
  return NULL;
 }

 if (! $1)
  $2 = 0;
 else
  {
    assert (ssize >= 0);
    $2 = (size_t) ssize;
  }
}
%typemap(freearg) (const void *buffer, size_t size) {
 Py_XDECREF(encodedInput$argnum);
}

/* Make types containing 'next' field to be lists.  */
%ignore next;
%typemap(out) gpgme_sig_notation_t,
 gpgme_subkey_t,
  gpgme_key_sig_t, gpgme_user_id_t, gpgme_invalid_key_t,
  gpgme_recipient_t, gpgme_new_signature_t, gpgme_signature_t,
  gpgme_import_status_t, gpgme_conf_arg_t, gpgme_conf_opt_t,
  gpgme_conf_comp_t, gpgme_tofu_info_t {
 int i;
 int size = 0;
 $1_ltype curr;
 for (curr = $1; curr != NULL; curr = curr->next) {
  size++;
 }
 $result = PyList_New(size);
 for (i=0,curr=$1; i<size; i++,curr=curr->next) {
  PyObject *o = SWIG_NewPointerObj(SWIG_as_voidptr(curr), $1_descriptor, %newpointer_flags);
  PyList_SetItem($result, i, o);
```

```
 }
}



/* Wrap the fragile result objects into robust Python ones.  */
%define wrapresult(cls, name)
%typemap(out) cls {
 PyObject *fragile;
 fragile = SWIG_NewPointerObj(SWIG_as_voidptr($1), $1_descriptor,
                              %newpointer_flags);
 $result = _gpg_wrap_result(fragile, name);
 Py_DECREF(fragile);
}
%enddef

wrapresult(gpgme_encrypt_result_t, "EncryptResult")
wrapresult(gpgme_decrypt_result_t,
 "DecryptResult")
wrapresult(gpgme_sign_result_t, "SignResult")
wrapresult(gpgme_verify_result_t, "VerifyResult")
wrapresult(gpgme_import_result_t, "ImportResult")
wrapresult(gpgme_genkey_result_t, "GenkeyResult")
wrapresult(gpgme_keylist_result_t, "KeylistResult")
wrapresult(gpgme_vfs_mount_result_t, "VFSMountResult")

%typemap(out) gpgme_engine_info_t {
 int i;
 int size = 0;
 $1_ltype curr;
 for (curr = $1; curr != NULL; curr = curr->next) {
   size++;
 }
 $result = PyList_New(size);
 if ($result == NULL)
   return NULL; /* raise */
 for (i=0,curr=$1; i<size; i++,curr=curr->next) {
   PyObject *fragile, *o;
   fragile = SWIG_NewPointerObj(SWIG_as_voidptr(curr), $1_descriptor,
                                %newpointer_flags);
   if (fragile == NULL)
     {
       Py_DECREF($result);
       return NULL; /* raise */
     }
   o = _gpg_wrap_result(fragile, "EngineInfo");
   Py_DECREF(fragile);
   if (o == NULL)
```

```
    {
      Py_DECREF($result);

 return NULL; /* raise */
    }
  PyList_SetItem($result, i, o);
 }
}



/* Include mapper for interact callbacks.  */
%typemap(in) (gpgme_interact_cb_t fnc, void *fnc_value) {
 if (! PyTuple_Check($input))
  return PyErr_Format(PyExc_TypeError, "interact callback must be a tuple");
 if (PyTuple_Size($input) != 2 && PyTuple_Size($input) != 3)
  return PyErr_Format(PyExc_TypeError,
                      "interact callback must be a tuple of size 2 or 3");

 $1 = (gpgme_interact_cb_t) _gpg_interact_cb;
 $2 = $input;
}



/* The assuan protocol callbacks.  */
%typemap(in) (gpgme_assuan_data_cb_t data_cb, void *data_cb_value) {
 if ($input == Py_None)
  $1 = $2 = NULL;
 else
  {
    if (! PyTuple_Check($input))
      return PyErr_Format(PyExc_TypeError, "callback must be a tuple");
    if (PyTuple_Size($input) != 2)
      return PyErr_Format(PyExc_TypeError,
                          "callback must be a tuple of size 2");
    if (! PyCallable_Check(PyTuple_GetItem($input,
1)))
      return PyErr_Format(PyExc_TypeError, "second item must be callable");
    $1 = _gpg_assuan_data_cb;
    $2 = $input;
  }
}

%typemap(in) (gpgme_assuan_inquire_cb_t inq_cb, void *inq_cb_value) {
 if ($input == Py_None)
  $1 = $2 = NULL;
 else
```

```
  {
    if (! PyTuple_Check($input))
      return PyErr_Format(PyExc_TypeError, "callback must be a tuple");
    if (PyTuple_Size($input) != 2)
      return PyErr_Format(PyExc_TypeError,
                          "callback must be a tuple of size 2");
    if (! PyCallable_Check(PyTuple_GetItem($input, 1)))
      return PyErr_Format(PyExc_TypeError, "second item must be callable");
    $1 = _gpg_assuan_inquire_cb;
    $2 = $input;
  }
}

%typemap(in) (gpgme_assuan_status_cb_t stat_cb, void *stat_cb_value) {
 if ($input == Py_None)
   $1 = $2 = NULL;
 else
   {
    if (! PyTuple_Check($input))
      return PyErr_Format(PyExc_TypeError, "callback must be a tuple");
    if (PyTuple_Size($input)
 != 2)
      return PyErr_Format(PyExc_TypeError,
                          "callback must be a tuple of size 2");
    if (! PyCallable_Check(PyTuple_GetItem($input, 1)))
      return PyErr_Format(PyExc_TypeError, "second item must be callable");
    $1 = _gpg_assuan_status_cb;
    $2 = $input;
  }
}



/* With SWIG, you can define default arguments for parameters.
* While it's legal in C++ it is not in C, so we cannot change the
* already existing gpgme.h. We need, however, to declare the function
* *before* SWIG loads it from gpgme.h. Hence, we define it here.     */
gpgme_error_t gpgme_op_keylist_start (gpgme_ctx_t ctx,
                  const char *pattern="",
                  int secret_only=0);

/* The whence argument is surprising in Python-land,
  because BytesIO or StringIO objects do not require it.
  It defaults to SEEK_SET. Let's do that for Data objects, too */
off_t gpgme_data_seek (gpgme_data_t dh, off_t offset, int whence=SEEK_SET);

/*
 Include the unmodified <gpgme.h> for cc, and the cleaned-up local
  version for SWIG.  We do, however, want to hide certain fields on
```

```
 some structs, which we provide prior to including the version for
 SWIG.  */
%{
#ifdef HAVE_CONFIG_H
#include "config.h"
#endif

#include <gpgme.h>
%}

/* This is for notations, where we want to hide the length fields, and
* the unused bit field block.  We silence the warning.  */
%warnfilter(302) _gpgme_sig_notation;
struct _gpgme_sig_notation
{
 struct _gpgme_sig_notation *next;

 /* If NAME is a null pointer, then VALUE contains a policy URL
    rather than a notation.  */
 char *name;

 /* The value of the notation data.  */
 char *value;

 /* The accumulated flags.  */
 gpgme_sig_notation_flags_t flags;

 /* Notation data is human-readable.  */
 unsigned int human_readable : 1;

 /* Notation data is critical.  */
 unsigned int critical : 1;
};

/* Now include our local modified version.  Any structs defined above
 are ignored.
 */
#ifdef HAVE_CONFIG_H
%include "config.h"
#endif

%include "gpgme.h"

%include "errors.i"

/* Generating and handling pointers-to-pointers.  */

%pointer_functions(gpgme_ctx_t, gpgme_ctx_t_p);
```

```
%pointer_functions(gpgme_data_t, gpgme_data_t_p);
%pointer_functions(gpgme_key_t, gpgme_key_t_p);
%pointer_functions(gpgme_error_t, gpgme_error_t_p);
%pointer_functions(gpgme_trust_item_t, gpgme_trust_item_t_p);
%pointer_functions(gpgme_engine_info_t, gpgme_engine_info_t_p);

/* Helper functions.  */

%{
#include <stdio.h>
%}
FILE *fdopen(int fildes, const char *mode);

/* We include both headers in the generated c code...  */
%{
#include "helpers.h"
#include "private.h"

/* SWIG runtime support for helpers.c  */
PyObject *
_gpg_wrap_gpgme_data_t(gpgme_data_t data)
{
 /*
  * If SWIG is invoked without -builtin, the macro SWIG_NewPointerObj
  * expects a variable named "self".
  *
  * XXX: It is not quite clear why passing NULL as self is okay, but
  * it works with -builtin, and it
 seems to work just fine without
  * it too.
  */
 PyObject* self = NULL;
 (void) self;
 return SWIG_NewPointerObj(data, SWIGTYPE_p_gpgme_data, 0);
}

gpgme_ctx_t
_gpg_unwrap_gpgme_ctx_t(PyObject *wrapped)
{
 gpgme_ctx_t result;
 if (SWIG_ConvertPtr(wrapped,
                     (void **) &result,
                     SWIGTYPE_p_gpgme_context,
                     SWIG_POINTER_EXCEPTION) == -1)
   return NULL;
 return result;
}
%}
```

```
/* ... but only the public definitions here.  They will be exposed to
  the Python world, so let's be careful.  */
%include "helpers.h"


%define genericrepr(cls)
%pythoncode %{
  def __repr__(self):
      names = [name for name in dir(self)
          if not name.startswith("_") and name != "this"]
      props = ", ".join(("{}={!r}".format(name, getattr(self, name))
          for name in names)
      )
      return "cls({})".format(props)
%}

%enddef

%extend _gpgme_key {
 genericrepr(Key)
};


%extend _gpgme_subkey {
 genericrepr(SubKey)
};

%extend
 _gpgme_key_sig {
 genericrepr(KeySig)
};

%extend _gpgme_user_id {
 genericrepr(UID)
};

%extend _gpgme_tofu_info {
 genericrepr(TofuInfo)
};
{
  "name": "gpgmejson",
  "description": "Integration with GnuPG",
  "path": "/usr/bin/gpgme-json",
  "type": "stdio",
  "allowed_extensions": [
      "jid1-AQqSMBYb0a8ADg@jetpack"
  ]
```

```
}
/*
 verificationresult.h - wraps a gpgme verify result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_VERIFICATIONRESULT_H__
#define
 __GPGMEPP_VERIFICATIONRESULT_H__

#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <time.h>

#include <memory>

#include <vector>
#include <iosfwd>

namespace GpgME
{

class Error;
class Signature;
class Notation;
class Key;
```

```
class GPGMEPP_EXPORT VerificationResult : public Result
{
public:
  VerificationResult();
  VerificationResult(gpgme_ctx_t ctx, int error);
  VerificationResult(gpgme_ctx_t ctx, const Error &error);
  explicit VerificationResult(const Error &err);

  const VerificationResult &operator=(VerificationResult other)
  {
    swap(other);
    return *this;
  }

  void swap(VerificationResult &other)
  {
    Result::swap(other);
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  const char *fileName() const;

  unsigned int numSignatures() const;
  Signature signature(unsigned int index) const;
  std::vector<Signature> signatures() const;

   class Private;
private:
  void init(gpgme_ctx_t ctx);
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const VerificationResult &result);

class GPGMEPP_EXPORT Signature
{
  friend class ::GpgME::VerificationResult;
  Signature(const std::shared_ptr<VerificationResult::Private> &parent, unsigned int index);
public:
  typedef GPGMEPP_DEPRECATED GpgME::Notation Notation;

  Signature();

  const Signature &operator=(Signature other)
  {
```

```
    swap(other);
    return *this;
}

void swap(Signature &other)
{
    using std::swap;
    swap(this->d, other.d);
    swap(this->idx, other.idx);
}

bool isNull() const;

enum Summary {
    None       = 0x000,
    Valid      = 0x001,
    Green      = 0x002,
    Red        = 0x004,
    KeyRevoked = 0x008,
    KeyExpired = 0x010,
    SigExpired = 0x020,
    KeyMissing = 0x040,
    CrlMissing = 0x080,

CrlTooOld  = 0x100,
    BadPolicy  = 0x200,
    SysError   = 0x400,
    TofuConflict= 0x800
};
Summary summary() const;

const char *fingerprint() const;

Error status() const;

time_t creationTime() const;
time_t expirationTime() const;
bool neverExpires() const;

GPGMEPP_DEPRECATED bool wrongKeyUsage() const
{
    return isWrongKeyUsage();
}
bool isWrongKeyUsage() const;
bool isVerifiedUsingChainModel() const;
bool isDeVs() const;

enum PKAStatus {
```

```
    UnknownPKAStatus, PKAVerificationFailed, PKAVerificationSucceeded
  };
  PKAStatus pkaStatus() const;
  const char *pkaAddress() const;

  enum Validity {
    Unknown, Undefined, Never, Marginal, Full, Ultimate
  };
  Validity validity() const;
  char validityAsString() const;
  Error nonValidityReason() const;

  unsigned int publicKeyAlgorithm() const;
  const char *publicKeyAlgorithmAsString() const;

  unsigned int hashAlgorithm()
const;
  const char *hashAlgorithmAsString() const;

  const char *policyURL() const;
  GpgME::Notation notation(unsigned int index) const;
  std::vector<GpgME::Notation> notations() const;

  /** Returns the key object associated with this signature.
   * May be incomplete but will have at least the fingerprint
   * set or the associated TOFU Information if applicable. */
  GpgME::Key key() const;

  /* Search / Update the key of this signature.
   *
   * Same as above but if search is set to true this will
   * either update the key provided by the engine or search
   * the key in the engine. The key is cached.
   *
   * As this involves an engine call it might take some time
   * to finish so it should be avoided to do this in a UI
   * thread. The result will be cached and no engine call
   * will be done if update is set to false and a key is
   * already cached.
   *
   * If no key was provided by the engine this will look
   * up the
key so this call might block while the engine
   * is called to obtain the key.
   *
   * If both search and update are false this is the same
   * as calling key()
   */
```

```
  GpgME::Key key(bool search, bool update) const;

private:
  std::shared_ptr<VerificationResult::Private> d;
  unsigned int idx;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Signature &sig);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Signature::PKAStatus pkaStatus);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Signature::Summary summary);

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(VerificationResult)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Signature)

#endif // __GPGMEPP_VERIFICATIONRESULT_H__
/*
 statusconsumerassuantransaction.h - Assuan transaction that forwards status lines to a consumer
 Copyright (c) 2020 g10 Code GmbH
 Software engineering by Ingo Klcker <dev@ingo-kloecker.de>

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_STATUSCONSUMERASSUANTRANSACTION_H__
#define
 __GPGMEPP_STATUSCONSUMERASSUANTRANSACTION_H__

#include <interfaces/assuantransaction.h>

namespace GpgME
{
```

```
class StatusConsumer;

class GPGMEPP_EXPORT StatusConsumerAssuanTransaction: public AssuanTransaction
{
public:
  explicit StatusConsumerAssuanTransaction(StatusConsumer *statusConsumer);
  ~StatusConsumerAssuanTransaction();

private:
  Error data(const char *data, size_t datalen) override;
  Data inquire(const char *name, const char *args, Error &err) override;
  Error status(const char *status, const char *args) override;

private:
  StatusConsumer *m_consumer;
};

} // namespace GpgME

#endif // __GPGMEPP_STATUSCONSUMERASSUANTRANSACTION_H__
#include "qgpgme/gpgcardjob.h"
/* util.h
  Copyright (C) 2000 Werner Koch (dd9jn)
  Copyright (C) 2001, 2002, 2003, 2004, 2005 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef UTIL_H
#define UTIL_H

#ifdef HAVE_W32_SYSTEM
# include "winsock2.h"
```

```
# include "windows.h"
#endif

/* For pid_t.  */
#ifdef
 HAVE_SYS_TYPES_H
# include <sys/types.h>
#endif
/* We must see the symbol ttyname_r before a redefinition. */
#ifdef HAVE_UNISTD_H
# include <unistd.h>
#endif

#include "gpgme.h"


#define DIM(v) (sizeof(v)/sizeof((v)[0]))



/*-- {posix,w32}-util.c --*/
int _gpgme_get_conf_int (const char *key, int *value);
void _gpgme_allow_set_foreground_window (pid_t pid);

/*-- dirinfo.c --*/
void _gpgme_dirinfo_disable_gpgconf (void);

const char *_gpgme_get_default_homedir (void);
const char *_gpgme_get_default_agent_socket (void);
const char *_gpgme_get_default_gpg_name (void);
const char *_gpgme_get_default_gpgsm_name (void);
const char *_gpgme_get_default_g13_name (void);
const char *_gpgme_get_default_gpgconf_name (void);
const char *_gpgme_get_default_uisrv_socket (void);
int _gpgme_in_gpg_one_mode (void);

const char *_gpgme_get_basename (const char *name);



/*-- replacement functions in <funcname>.c --*/
#ifdef HAVE_CONFIG_H

#ifndef HAVE_STPCPY
static _GPGME_INLINE char *
_gpgme_stpcpy
 (char *a, const char *b)
{
```

```
 while (*b)
   *a++ = *b++;
 *a = 0;
 return a;
}
#define stpcpy(a,b) _gpgme_stpcpy ((a), (b))
#endif /*!HAVE_STPCPY*/


/* Due to a bug in mingw32's snprintf related to the 'l' modifier and
  for increased portability we use our snprintf on all systems. */
#undef snprintf
#define snprintf gpgrt_snprintf


#if REPLACE_TTYNAME_R
int _gpgme_ttyname_r (int fd, char *buf, size_t buflen);
#undef  ttyname_r
#define ttyname_r(a,b,c) _gpgme_ttyname_r ((a), (b), (c))
#endif

#endif /*HAVE_CONFIG_H*/


/*-- conversion.c --*/

/* Concatenate the string S1 with all the following strings up to a
  NULL.  Returns a malloced buffer with the new string or NULL on a
  malloc error or if too many arguments are given.  */
char *_gpgme_strconcat (const char *s1, ...) GPGRT_ATTR_SENTINEL(0);

/* Convert two hexadecimal digits from STR to the value they
  represent.  Returns -1 if one of the characters is not a
  hexadecimal digit.  */
int _gpgme_hextobyte (const char
 *str);

/* Decode the C formatted string SRC and store the result in the
  buffer *DESTP which is LEN bytes long.  If LEN is zero, then a
  large enough buffer is allocated with malloc and *DESTP is set to
  the result.  Currently, LEN is only used to specify if allocation
  is desired or not, the caller is expected to make sure that *DESTP
  is large enough if LEN is not zero.  */
gpgme_error_t _gpgme_decode_c_string (const char *src, char **destp,
        size_t len);

/* Decode the percent escaped string SRC and store the result in the
  buffer *DESTP which is LEN bytes long.  If LEN is zero, then a
```

```
  large enough buffer is allocated with malloc and *DESTP is set to
  the result.  Currently, LEN is only used to specify if allocation
  is desired or not, the caller is expected to make sure that *DESTP
  is large enough if LEN is not zero.  If BINARY is 1, then '\0'
  characters are allowed in the output.  */
gpgme_error_t _gpgme_decode_percent_string (const char *src, char
 **destp,
        size_t len, int binary);

gpgme_error_t _gpgme_encode_percent_string (const char *src, char **destp,
        size_t len);

/* Split a string into space delimited fields and remove leading and
* trailing spaces from each field.  A pointer to the each field is
* stored in ARRAY.  Stop splitting at ARRAYSIZE fields.  The function
* modifies STRING.  The number of parsed fields is returned.  */
int _gpgme_split_fields (char *string, char **array, int arraysize);

/* Convert the field STRING into an unsigned long value.  Check for
* trailing garbage.  */
gpgme_error_t _gpgme_strtoul_field (const char *string, unsigned long *result);

/* Convert STRING into an offset value similar to atoi().  */
gpgme_off_t _gpgme_string_to_off (const char *string);

/* Parse the string TIMESTAMP into a time_t.  The string may either be
  seconds since Epoch or in the ISO 8601 format like
  "20390815T143012".  Returns 0 for an empty string or seconds since
  Epoch. Leading spaces
 are skipped. If ENDP is not NULL, it will
  point to the next non-parsed character in TIMESTRING. */
time_t _gpgme_parse_timestamp (const char *timestamp, char **endp);

/* Variant of _gpgme_parse_timestamp to return an unsigned long or 0
* on error or missing timestamp.  */
unsigned long _gpgme_parse_timestamp_ul (const char *timestamp);

int _gpgme_map_pk_algo (int algo, gpgme_protocol_t protocol);

const char *_gpgme_cipher_algo_name (int algo, gpgme_protocol_t protocol);
const char *_gpgme_cipher_mode_name (int algo, gpgme_protocol_t protocol);


/*-- b64dec.c --*/

struct b64state
{
 int idx;
```

```
 int quad_count;
 char *title;
 unsigned char radbuf[4];
 int stop_seen:1;
 int invalid_encoding:1;
 gpg_error_t lasterr;
};

gpg_error_t _gpgme_b64dec_start (struct b64state *state, const char *title);
gpg_error_t _gpgme_b64dec_proc (struct b64state *state,
                                void *buffer, size_t length, size_t *r_nbytes);
gpg_error_t _gpgme_b64dec_finish (struct b64state
 *state);



/* Retrieve the environment variable NAME and return a copy of it in a
  malloc()'ed buffer in *VALUE.  If the environment variable is not
  set, return NULL in *VALUE.  */
gpgme_error_t _gpgme_getenv (const char *name, char **value);


/*-- status-table.c --*/
/* Convert a status string to a status code.  */
void _gpgme_status_init (void);
gpgme_status_code_t _gpgme_parse_status (const char *name);
const char *_gpgme_status_to_string (gpgme_status_code_t code);


#ifdef HAVE_W32_SYSTEM
int _gpgme_mkstemp (int *fd, char **name);
const char *_gpgme_get_w32spawn_path (void);
#endif /*HAVE_W32_SYSTEM*/



#include <assuan.h>
/* System hooks for assuan integration.  */
extern struct assuan_system_hooks _gpgme_assuan_system_hooks;
extern struct assuan_malloc_hooks _gpgme_assuan_malloc_hooks;
int _gpgme_assuan_log_cb (assuan_context_t ctx, void *hook,
    unsigned int cat, const char *msg);



/* Parse the compliance field.  */
#define PARSE_COMPLIANCE_FLAGS(flags, result)    \
```

```
 do {        \
  char *comp_p, *comp_endp;      \
  unsigned long comp_ul;      \
        \
  for (comp_p = (flags);      \
 comp_p        \
   && (comp_ul = strtoul (comp_p, &comp_endp, 10))  \
   && comp_p != comp_endp;     \
 comp_p = comp_endp)      \
    {        \
 switch (comp_ul)      \
  {       \
  case 23: (result)->is_de_vs = 1; break;   \
  }       \
    }        \
 } while (0)


#endif /* UTIL_H */
/*
 gpgsetexpirytimeeditinteractor.h - Edit Interactor to change the expiry time of an OpenPGP key
 Copyright (C) 2007 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston,
 MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_GPGSETEXPIRYTIMEEDITINTERACTOR_H__
#define __GPGMEPP_GPGSETEXPIRYTIMEEDITINTERACTOR_H__

#include <editinteractor.h>
```

```
#include <string>

namespace GpgME
{

class GPGMEPP_EXPORT GpgSetExpiryTimeEditInteractor : public EditInteractor
{
public:
  explicit GpgSetExpiryTimeEditInteractor(const std::string &timeString = "0");
  ~GpgSetExpiryTimeEditInteractor();

private:
  const char *action(Error &err) const override;
  unsigned int nextState(unsigned int statusCode, const char *args, Error &err) const override;

private:
  const std::string m_strtime;
};

} // namespace GpgME

#endif // __GPGMEPP_GPGSETEXPIRYTIMEEDITINTERACTOR_H___
{
  "type": "ciphertext",
  "base64":       true
}
{
  "op": "config_opt",
  "component": "gpg",
  "option": "default-key"
}
1603972630
##Sketch 1 2
document()
layout('A4',1)
fp((0,0,0))
ft(1)
Fn('Helvetica-Bold')
Fs(18)
dstyle('Text')
fp((0,1,0.498))
ft(1)
lp((0,0,0))
lw(0.283465)
lc(1)
lj(0)
ld(())
```

la1()
la2()
dstyle('Application Box')
layer('Layer 1',1,1,0,0,(0,0,0))
lw(1)
r(0,0,0,0,688.145,44.1554)
lw(1)
r(0,0,0,0,682.363,85.0359)
lp((0.392,0.584,0.929))
lw(4.25197)
b()
bs(605.383,329.758,0)
bs(605.383,230.546,0)
lw(1)
r(0,0,0,0,807.414,53.6148)
lp((0.392,0.584,0.929))
lw(4.25)
b()
bs(480.134,240.945,0)
bs(480.358,325.277,0)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(474.803,432.284,0)
bs(475.334,360.243,0)
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(354.331,432.284,0)
bs(352.806,361.417,0)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(212.598,432.284,0)
bs(212.598,361.417,0)
fp((0.999,1,0.4))
lw(0.283465)
r(70.5968,0,0,-56.6929,191.608,488.976,0.0603744,0.151107)
lw(1)
r(0,0,0,0,88.5492,390.805)
lp((0.392,0.584,0.929))
lw(4.25197)
b()

bs(226.772,524.409,0)
bs(226.772,488.976,0)
lp((0.392,0.584,0.929))
lw(4.25)
b()
bs(403.937,528.718,0)
bs(403.937,488.976,0)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1,
 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(240.945,432.284,0)
bs(240.574,394.994,0)
bs(595.276,396.85,0)
bs(595.276,361.417,0)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(333.071,432.284,0)
bs(333.07,425.196,0)
bs(333.07,382.677,0)
bs(240.945,382.677,0)
bs(240.945,361.417,0)
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-28.347,318.897,354.331,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica-Bold')
Fs(10)
txt('GPG',(1,0,0,0.905764,344.004,335.686))
G_()
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-28.3464,446.763,354.33,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')

txt('GpgConf',(0.552654,0,0,0.500564,481.802,340.184),1,1)
G_()
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-28.347,191.338,354.331,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('GpgSM',(0.552654,0,0,0.500574,226.376,340.185),1,1)
G_()
lp((0.392,0.584,0.929))
lw(4.25)
b()
bs(347.244,325.984,0)
bs(347.244,325.984,0)
bs(347.244,255.118,0)
bs(304.724,255.118,0)
bs(304.724,226.771,0)
lp((0.392,0.584,0.929))
lw(4.25)
b()
bs(233.858,325.984,0)
bs(233.858,255.118,0)
bs(276.378,255.118,0)
bs(276.378,226.771,0)
fp((0,0,0))
le()
lw(1)
Fn('Palatino-Roman')
txt('2008-07-17',(0.608301,0,0,0.608301,708.661,65.8308))
lw(1)
r(0,0,0,0,750.427,153.265)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1,
 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(219.685,325.984,0)
bs(219.685,198.425,0)
bs(219.685,162.992,0)
G()
fp((1,1,1))
lw(0.283465)

r(113.386,0,0,-42.5196,35.4333,162.992,0.0670228,0.151107)
fp((0,0,0))
lw(0.283465)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('LDAP
 Server',(0.552654,0,0,0.552654,92.1261,148.819),1,1)
fp((0,0,0))
lw(0.283465)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('(CRLs, Certificates)',(0.552654,0,0,0.552654,92.1261,134.646),1,1)
G_()
G()
fp((1,1,1))
lw(0.283465)
r(113.386,0,0,-42.5196,35.4331,99.2125,0.0670228,0.151107)
fp((0,0,0))
lw(0.283465)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('HTTP Server',(0.552654,0,0,0.552654,92.1259,85.0394),1,1)
fp((0,0,0))
lw(0.283465)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('(CRLs)',(0.552654,0,0,0.552654,92.1259,70.8662),1,1)
G_()
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.866,0,0,-31.2962,191.338,158.855,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')

```
Fs(14)
style('Text')
txt('DirMngr',(0.552654,0,0,0.552654,224.02,142.978),1,1)
G_()
lw(2)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(219.15,126.18,0)
bs(219.685,77.9528,0)
bs(155.906,77.9528,0)
lp((0.392,0.584,0.929))
lw(3)
b()
bs(233.858,127.559,0)
bs(233.858,99.2125,0)
bs(276.378,99.2125,0)
bs(276.378,85.0393,0)
lp((0.392,0.584,0.929))
lw(3)
b()
bs(248.031,127.559,0)
bs(248.031,113.386,0)
bs(375.59,113.386,0)
bs(375.59,85.0393,0)
G()
fp((1,0.647,0.31))
lw(0.283465)
r(99.2124,0,0,-28.3464,333.07,85.0393,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Certificate
 Cache',(0.552654,0,0,0.552654,382.606,69.8548),1,1)
fp((1,0.647,0.31))
lw(0.283465)
r(70.5589,0,0,-28.3464,248.031,85.0393,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
```

txt('CRL Cache',(0.552654,0,0,0.552654,284.147,70.6936),1,1)
G_()
lw(1)
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(503.149,240.945,0)
bs(503.149,283.464,0)
bs(588.189,283.465,0)
bs(588.189,325.984,0)
lw(1)
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(503.149,283.464,0)
bs(503.149,283.464,0)
bs(361.417,283.464,0)
bs(361.417,325.984,0)
lw(1)
la2(([(-4.0,
 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(361.417,283.464,0)
bs(205.512,283.465,0)
bs(205.512,325.984,0)
lw(1)
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(574.015,85.0393,0)
bs(574.015,141.732,0)
bs(262.204,141.732,0)
lw(1)
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(602.361,85.0393,0)
bs(602.361,170.079,0)
bs(439.37,170.079,0)
bs(439.37,311.811,0)
bs(460.629,311.811,0)
bs(460.629,325.984,0)
lw(1)
ld((5, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(389.763,240.945,0)
bs(389.763,269.291,0)
bs(290.551,269.291,0)
bs(290.551,340.157,0)
bs(262.204,340.157,0)
lw(1)

ld((5, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(389.763,269.291,0)
bs(559.843,269.291,0)
bs(559.843,333.071,0)
bs(574.016,333.071,0)
lw(1)
ld((5, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(488.976,85.0393,0)
bs(488.976,127.559,0)
bs(389.763,127.559,0)
bs(389.763,212.598,0)
lw(2)
ld((1,
 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(205.512,127.559,0)
bs(205.512,113.386,0)
bs(170.079,113.386,0)
bs(170.079,141.732,0)
bs(155.906,141.732,0)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(622.961,356.76,0)
bs(622.961,518.503,0)
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-28.3459,573.199,354.33,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('GpgAgent',(0.552654,0,0,0.500554,608.238,340.185),1,1)
G_()
lp((0.392,0.584,0.929))
lw(4.25)
b()
bs(721.712,467.717,0)

bs(721.712,297.838,0)
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-28.3464,686.278,297.637,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('SCdaemon',(0.552654,0,0,0.500564,721.316,283.492),1,1)
G_()
fp((1,0.647,0.31))
lw(0.283465)
lj(1)
r(86.162,0,0,-117.493,679.192,566.929,0.181818,0.333333)
G()
fp((0,0,0))
le()
lw(1)
Fn('Helvetica-Bold')
Fs(18)
txt('Smartcard',(0.552654,0,0,0.552654,698.127,491.036))
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-31.2962,686.279,557.593,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('Card
 Reader',(0.552654,0,0,0.552654,721.318,541.975),1,1)
G_()
G()
fp((0.999,1,0.4))
lw(0.283465)
r(73.6353,0,0,-41.2944,587.066,565.703,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('PIN Entry',(0.57675,0,0,0.729211,623.632,545.097),1,1)
G_()

lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(643.758,340.157,0)
bs(643.758,340.157,0)
bs(707.539,340.158,0)
bs(707.539,304.724,0)
lw(1)
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(574.016,283.465,0)
bs(587.066,283.464,0)
bs(686.278,283.464,0)
G()
lp((0.392,0.584,0.929))
lw(4.25197)
b()
bs(98.9053,325.985,0)
bs(98.9053,240.945,0)
G()
fp((0.999,1,0.4))
lw(0.283465)
r(70.5589,0,0,-28.3464,63.7795,354.331,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('WatchGnuPG',(0.552654,0,0,0.552654,98.8185,338.713),1,1)
G_()
G()
fp((1,0.647,0.31))
lw(0.283465)
r(70.5589,0,0,-28.1194,63.7795,240.718,0.0670228,0.168178)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('Log
 Socket',(0.552654,0,0,0.552654,98.8175,225.1),1,1)
G_()
G_()
G()

fp((1,0.647,0.31))
lw(0.283465)
r(85.0392,0,0,-28.3464,446.457,240.945,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Config Files',(0.552654,0,0,0.552654,485.621,226.772),1,1)
G_()
G()
fp((1,0.647,0.31))
lw(0.283465)
r(85.0392,0,0,-28.3464,545.669,85.0394,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Config Files',(0.552654,0,0,0.552654,584.834,70.8662),1,1)
G_()
G()
fp((1,0.647,0.31))
lw(0.283465)
r(84.6546,0,0,-27.3609,347.245,239.959,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Help
 Files',(0.552654,0,0,0.552654,388.252,224.705),1,1)
G_()
G()
fp((1,0.647,0.31))
lw(0.283465)
r(84.6546,0,0,-27.3609,446.457,85.0394,0.0670228,0.151107)
fp((0,0,0))
le()

```
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Help Files',(0.552654,0,0,0.552654,487.464,69.7854),1,1)
G_()
G()
fp((1,0.647,0.31))
lw(0.283465)
r(85.0392,0,0,-28.3464,248.032,240.945,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Keybox Files',(0.552654,0,0,0.552654,289.59,226.322),1,1)
G_()
G()
fp((1,0.647,0.31))
lw(0.283465)
r(70.866,0,0,-28.3464,574.016,240.945,0.0670228,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(18)
txt('Private Keys',(0.552654,0,0,0.552654,609.449,226.772),1,1)
G_()
G()
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(24)
txt('Scute',(0.552654,0,0,0.599958,224.978,465.775),1,1)
fp((0,0,0))
le()
```

lw(1)
Fn('Times-Roman')
Fs(10)
txt('(pkcs#11)',(1,0,0,1.08559,206.081,445.011))
G_()
G()
fp((0.999,1,0.4))
lw(0.283465)
r(198.827,0,0,-56.6929,304.322,488.976,0.0603744,0.151107)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
Fn('Helvetica-Bold')
Fs(36)
txt('GPGME
 Library',(0.552654,0,0,0.552654,404.952,457.853),1,1)
G_()
G()
lw(1)
style('Application Box')
r(197.598,0,0,-42.5187,304.724,566.928,0.0152672,0.0677968)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
txt('GPGME aware Application',(0.98062,0,0,0.937018,334.892,540.985))
G_()
G()
lw(1)
style('Application Box')
r(127.829,0,0,-41.7496,162.992,566.159,0.0152672,0.0677968)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
txt('Legacy Application',(174.688,540.01))
G_()
G()
G()
lp((0.392,0.584,0.929))
lw(4.25197)
b()
bs(749.296,162.296,0)
bs(705.89,162.296,0)
lw(3.25)

ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0,
 -3.0), (-4.0, 3.0)], 1))
b()
bs(705.89,100.083,0)
bs(744.472,100.083,0)
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(705.89,131.189,0)
bs(744.472,131.189,0)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('execute/access',(0.31891,0,0,0.280771,726.951,87.3768),1,1)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('closely linked',(0.31891,0,0,0.280771,724.715,149.589),1,1)
fp((0,0,0))
le()
lw(1)
Fn('Helvetica')
Fs(14)
style('Text')
txt('Assuan protocol',(0.31891,0,0,0.280771,728.535,118.483),1,1)
G_()
lw(1)
r(56.6929,0,0,-92.126,701.575,170.079)
G_()
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(248.031,325.984,0)
bs(248.031,297.638,0)
bs(538.583,297.638,0)
bs(538.583,340.157,0)
bs(566.929,340.157,0)

```
lp((0.392,0.584,0.929))
lw(3.25)
ld((1, 1))
la2(([(-4.0, 3.0), (2.0, 0.0), (-4.0, -3.0), (-4.0, 3.0)], 1))
b()
bs(375.591,325.984,0)
bs(375.591,304.724,0)
bs(531.496,304.724,0)
bs(531.496,347.244,0)
bs(566.929,347.244,0)
guidelayer('Guide
 Lines',1,0,0,1,(0,0,1))
grid((0,0,7.08661,7.08661),1,(0,0,1),'Grid')
/*
 assuantransaction.h - Interface for ASSUAN transactions
 Copyright (C) 2009 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH <info@kdab.com>
 Author: Marc Mutz <marc@kdab.com>

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
  Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_INTERFACES_ASSUANTRANSACTION_H__
#define __GPGMEPP_INTERFACES_ASSUANTRANSACTION_H__

#include "gpgmepp_export.h"

#include <stddef.h>

namespace GpgME
{
```

```
class Error;
class Data;

class GPGMEPP_EXPORT AssuanTransaction
{
public:
  virtual ~AssuanTransaction() {}

  virtual Error data(const char *data, size_t datalen) = 0;
  virtual Data  inquire(const char *name, const char *args, Error &err) = 0;
  virtual Error status(const char *status, const char *args) = 0;
};

} // namespace GpgME

#endif // __GPGMEPP_INTERFACES_ASSUANTRANSACTION_H__
/*
 util.h - some inline helper functions
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef __GPGMEPP_UTIL_H__
#define
 __GPGMEPP_UTIL_H__

#include "global.h"
#include "notation.h"
```

```
#include <gpgme.h>

#ifndef NDEBUG
#include <iostream>
#endif
#include <sstream>
#include <string>

static inline const char *protect(const char *s)
{
  return s ? s : "<null>" ;
}

static inline gpgme_error_t make_error(gpgme_err_code_t code)
{
  return gpgme_err_make((gpgme_err_source_t)22, code);
}

static inline unsigned long to_pid(const std::string &s)
{
  std::stringstream ss(s);
  unsigned int result;
  if (ss >> result) {
     return result;
  } else {
     return 0U;
  }
}

static inline gpgme_keylist_mode_t add_to_gpgme_keylist_mode_t(unsigned int oldmode, unsigned int newmodes)
{
  if (newmodes & GpgME::Local) {
     oldmode |= GPGME_KEYLIST_MODE_LOCAL;
  }
  if (newmodes & GpgME::Extern) {
     oldmode |= GPGME_KEYLIST_MODE_EXTERN;
  }
  if (newmodes & GpgME::Signatures) {
     oldmode |= GPGME_KEYLIST_MODE_SIGS;
  }
  if (newmodes & GpgME::SignatureNotations)
 {
     oldmode |= GPGME_KEYLIST_MODE_SIG_NOTATIONS;
  }
  if (newmodes & GpgME::Validate) {
     oldmode |= GPGME_KEYLIST_MODE_VALIDATE;
  }
  if (newmodes & GpgME::Ephemeral) {
```

```
    oldmode |= GPGME_KEYLIST_MODE_EPHEMERAL;
  }
  if (newmodes & GpgME::WithTofu) {
    oldmode |= GPGME_KEYLIST_MODE_WITH_TOFU;
  }
  if (newmodes & GpgME::WithKeygrip) {
    oldmode |= GPGME_KEYLIST_MODE_WITH_KEYGRIP;
  }
  if (newmodes & GpgME::WithSecret) {
    oldmode |= GPGME_KEYLIST_MODE_WITH_SECRET;
  }
#ifndef NDEBUG
  if (newmodes & ~(GpgME::Local |
                   GpgME::Extern |
                   GpgME::Signatures |
                   GpgME::SignatureNotations |
                   GpgME::Validate |
                   GpgME::Ephemeral |
                   GpgME::WithTofu |
                   GpgME::WithKeygrip |
                   GpgME::WithSecret)) {
    //std::cerr << "GpgME::Context: keylist mode must be one of Local,
 "
    //"Extern, Signatures, SignatureNotations, Validate, Ephemeral, WithTofu, "
    //"WithKeygrip, WithSecret, or a combination thereof!" << std::endl;
  }
#endif
  return static_cast<gpgme_keylist_mode_t>(oldmode);
}

static inline unsigned int convert_from_gpgme_keylist_mode_t(unsigned int mode)
{
  unsigned int result = 0;
  if (mode & GPGME_KEYLIST_MODE_LOCAL) {
    result |= GpgME::Local;
  }
  if (mode & GPGME_KEYLIST_MODE_EXTERN) {
    result |= GpgME::Extern;
  }
  if (mode & GPGME_KEYLIST_MODE_SIGS) {
    result |= GpgME::Signatures;
  }
  if (mode & GPGME_KEYLIST_MODE_SIG_NOTATIONS) {
    result |= GpgME::SignatureNotations;
  }
  if (mode & GPGME_KEYLIST_MODE_WITH_SECRET) {
    result |= GpgME::WithSecret;
  }
```

```
  if (mode & GPGME_KEYLIST_MODE_WITH_TOFU) {
     result |= GpgME::WithTofu;
  }
  if (mode & GPGME_KEYLIST_MODE_WITH_KEYGRIP) {
     result |= GpgME::WithKeygrip;
  }
  if (mode & GPGME_KEYLIST_MODE_EPHEMERAL)
 {
     result |= GpgME::Ephemeral;
  }
  if (mode & GPGME_KEYLIST_MODE_VALIDATE) {
     result |= GpgME::Validate;
  }
#ifndef NDEBUG
  if (mode & ~(GPGME_KEYLIST_MODE_LOCAL |
               GPGME_KEYLIST_MODE_EXTERN |
               GPGME_KEYLIST_MODE_SIGS |
               GPGME_KEYLIST_MODE_SIG_NOTATIONS |
               GPGME_KEYLIST_MODE_WITH_SECRET |
               GPGME_KEYLIST_MODE_WITH_TOFU |
               GPGME_KEYLIST_MODE_WITH_KEYGRIP |
               GPGME_KEYLIST_MODE_EPHEMERAL |
               GPGME_KEYLIST_MODE_VALIDATE)) {
     //std::cerr << "GpgME: WARNING: gpgme_get_keylist_mode() returned an unknown flag!" << std::endl;
  }
#endif // NDEBUG
  return result;
}

static inline GpgME::Notation::Flags convert_from_gpgme_sig_notation_flags_t(unsigned int flags)
{
  unsigned int result = 0;
  if (flags & GPGME_SIG_NOTATION_HUMAN_READABLE) {
     result |= GpgME::Notation::HumanReadable ;
  }
  if (flags &
 GPGME_SIG_NOTATION_CRITICAL) {
     result |= GpgME::Notation::Critical ;
  }
  return static_cast<GpgME::Notation::Flags>(result);
}

static inline gpgme_sig_notation_flags_t  add_to_gpgme_sig_notation_flags_t(unsigned int oldflags, unsigned int
newflags)
{
  unsigned int result = oldflags;
  if (newflags & GpgME::Notation::HumanReadable) {
     result |= GPGME_SIG_NOTATION_HUMAN_READABLE;
```

```
  }
  if (newflags & GpgME::Notation::Critical) {
     result |= GPGME_SIG_NOTATION_CRITICAL;
  }
  return static_cast<gpgme_sig_notation_flags_t>(result);
}

#endif // __GPGMEPP_UTIL_H__
/*
 interface/dataprovider.h - Interface for data sources
 Copyright (C) 2003 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_INTERFACES_DATAPROVIDER_H__
#define
 __GPGMEPP_INTERFACES_DATAPROVIDER_H__

#include <sys/types.h>

#include "gpgmepp_export.h"

#include <gpg-error.h>

namespace GpgME
{

class GPGMEPP_EXPORT DataProvider
{
public:
```

```
  virtual ~DataProvider() {}

  enum Operation {
     Read, Write, Seek, Release
  };
  virtual bool isSupported(Operation op) const = 0;

  virtual ssize_t read(void   *buffer, size_t bufSize) = 0;
  virtual ssize_t write(const void *buffer, size_t bufSize) = 0;
  virtual off_t seek(off_t offset, int whence) = 0;
  virtual void release() = 0;
};

} // namespace GpgME

#endif // __GPGMEPP_INTERFACES_DATAPROVIDER_H__
/*
  qgpgmekeyformailboxjob.h

  This file is part of libkleopatra, the KDE keymanagement library
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin
Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
```

```
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __QGPGME_QGPGMEKEYFORMAILBOXJOB_H__
#define __QGPGME_QGPGMEKEYFORMAILBOXJOB_H__
#include "keyformailboxjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "keylistresult.h"
# include "key.h"
#else
# include <gpgme++/keylistresult.h>
# include <gpgme++/key.h>
#endif

namespace QGpgME
{

class
 QGpgMEKeyForMailboxJob
#ifdef Q_MOC_RUN
   : public KeyForMailboxJob
#else
   : public _detail::ThreadedJobMixin<KeyForMailboxJob, std::tuple<GpgME::KeyListResult, GpgME::Key,
GpgME::UserID, QString, GpgME::Error> >
#endif
{
   Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
   void slotFinished();
#endif
public:
   explicit QGpgMEKeyForMailboxJob(GpgME::Context *context);
   ~QGpgMEKeyForMailboxJob();

   /**
     Starts the operation. \a mailbox is the mailbox to
     look for.

     The result is the same as for the LocateKeysJob.

     If \a canEncrypt is true, only keys that have a subkey for encryption
     usage are returned. Use this if you need to select a
     key for signing.
```

```
  */
  GpgME::Error start(const QString &mailbox, bool canEncrypt = true) Q_DECL_OVERRIDE;

  GpgME::KeyListResult exec(const QString &mailbox, bool canEncrypt, GpgME::Key &key, GpgME::UserID
&uid) Q_DECL_OVERRIDE;
};

}
#endif
/*
  protocol_p.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2005 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
#ifndef __QGPGME_PROTOCOL_P_H__
#define __QGPGME_PROTOCOL_P_H__
#include "qgpgmenewcryptoconfig.h"

#include "qgpgmekeygenerationjob.h"
```

```
#include "qgpgmekeylistjob.h"
#include "qgpgmelistallkeysjob.h"
#include "qgpgmedecryptjob.h"
#include "qgpgmedecryptverifyjob.h"
#include "qgpgmerefreshkeysjob.h"
#include "qgpgmedeletejob.h"
#include "qgpgmesecretkeyexportjob.h"
#include "qgpgmedownloadjob.h"
#include
 "qgpgmesignencryptjob.h"
#include "qgpgmeencryptjob.h"
#include "qgpgmesignjob.h"
#include "qgpgmesignkeyjob.h"
#include "qgpgmeexportjob.h"
#include "qgpgmeverifydetachedjob.h"
#include "qgpgmeimportjob.h"
#include "qgpgmeimportfromkeyserverjob.h"
#include "qgpgmeverifyopaquejob.h"
#include "qgpgmechangeexpiryjob.h"
#include "qgpgmechangeownertrustjob.h"
#include "qgpgmechangepasswdjob.h"
#include "qgpgmeadduseridjob.h"
#include "qgpgmekeyformailboxjob.h"
#include "qgpgmewkspublishjob.h"
#include "qgpgmetofupolicyjob.h"
#include "qgpgmequickjob.h"

namespace
{

class Protocol : public QGpgME::Protocol
{
  GpgME::Protocol mProtocol;
public:
  explicit Protocol(GpgME::Protocol proto) : mProtocol(proto) {}

  QString name() const Q_DECL_OVERRIDE
  {
     switch (mProtocol) {
     case GpgME::OpenPGP: return QStringLiteral("OpenPGP");
     case GpgME::CMS:     return QStringLiteral("SMIME");
     default:             return QString();
     }
  }

   QString displayName() const Q_DECL_OVERRIDE
  {
     // ah (2.4.16): Where is this used and isn't this inverted
```

```
    // with name
    switch (mProtocol) {
    case GpgME::OpenPGP: return QStringLiteral("gpg");
    case GpgME::CMS:     return QStringLiteral("gpgsm");
    default:             return QStringLiteral("unknown");
    }
  }

  QGpgME::SpecialJob *specialJob(const char *, const QMap<QString, QVariant> &) const
Q_DECL_OVERRIDE
  {
    return nullptr;
  }

  QGpgME::KeyListJob *keyListJob(bool remote, bool includeSigs, bool validate) const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }

    unsigned int mode = context->keyListMode();
    if (remote) {
      mode |= GpgME::Extern;
      mode &= ~GpgME::Local;
    } else {
      mode |= GpgME::Local;
      mode &= ~GpgME::Extern;

  }
    if (includeSigs) {
      mode |= GpgME::Signatures;
    }
    if (validate) {
      mode |= GpgME::Validate;
    }
    context->setKeyListMode(mode);
    return new QGpgME::QGpgMEKeyListJob(context);
  }

  QGpgME::ListAllKeysJob *listAllKeysJob(bool includeSigs, bool validate) const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }

    unsigned int mode = context->keyListMode();
```

```
    mode |= GpgME::Local;
    mode &= ~GpgME::Extern;
    if (includeSigs) {
        mode |= GpgME::Signatures;
    }
    if (validate) {
        mode |= GpgME::Validate;
        /* Setting the context to offline mode disables CRL / OCSP checks in
           this Job. Otherwise we would try to fetch the CRL's for all CMS
           keys in the users keyring because GpgME::Validate includes remote

  resources by default in the validity check.
           This setting only has any effect if gpgsm >= 2.1.6 is used.
           */
        context->setOffline(true);
    }
    context->setKeyListMode(mode);
    return new QGpgME::QGpgMEListAllKeysJob(context);
}

QGpgME::EncryptJob *encryptJob(bool armor, bool textmode) const Q_DECL_OVERRIDE
{
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
        return nullptr;
    }

    context->setArmor(armor);
    context->setTextMode(textmode);
    return new QGpgME::QGpgMEEncryptJob(context);
}

QGpgME::DecryptJob *decryptJob() const Q_DECL_OVERRIDE
{
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
        return nullptr;
    }
    return new QGpgME::QGpgMEDecryptJob(context);
}

QGpgME::SignJob *signJob(bool armor, bool textMode) const Q_DECL_OVERRIDE
 {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
        return nullptr;
    }
```

```
    context->setArmor(armor);
    context->setTextMode(textMode);
    return new QGpgME::QGpgMESignJob(context);
  }

  QGpgME::VerifyDetachedJob *verifyDetachedJob(bool textMode) const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }

    context->setTextMode(textMode);
    return new QGpgME::QGpgMEVerifyDetachedJob(context);
  }

  QGpgME::VerifyOpaqueJob *verifyOpaqueJob(bool textMode) const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }

    context->setTextMode(textMode);
    return new QGpgME::QGpgMEVerifyOpaqueJob(context);
  }

  QGpgME::KeyGenerationJob *keyGenerationJob()
 const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }
    return new QGpgME::QGpgMEKeyGenerationJob(context);
  }

  QGpgME::ImportJob *importJob() const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }
    return new QGpgME::QGpgMEImportJob(context);
  }

  QGpgME::ImportFromKeyserverJob *importFromKeyserverJob() const Q_DECL_OVERRIDE
  {
```

```
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
        return nullptr;
    }
    return new QGpgME::QGpgMEImportFromKeyserverJob(context);
}

QGpgME::ExportJob *publicKeyExportJob(bool armor) const Q_DECL_OVERRIDE
{
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context)
{
        return nullptr;
    }

    context->setArmor(armor);
    return new QGpgME::QGpgMEExportJob(context);
}

QGpgME::ExportJob *secretKeyExportJob(bool armor, const QString &charset) const Q_DECL_OVERRIDE
{
    if (mProtocol != GpgME::CMS) { // fixme: add support for gpg, too
        return nullptr;
    }

    // this operation is not supported by gpgme, so we have to call gpgsm ourselves:
    return new QGpgME::QGpgMESecretKeyExportJob(armor, charset);
}

QGpgME::RefreshKeysJob *refreshKeysJob() const Q_DECL_OVERRIDE
{
    if (mProtocol != GpgME::CMS) { // fixme: add support for gpg, too
        return nullptr;
    }

    // this operation is not supported by gpgme, so we have to call gpgsm ourselves:
    return new QGpgME::QGpgMERefreshKeysJob();
}

QGpgME::DownloadJob *downloadJob(bool armor) const Q_DECL_OVERRIDE
{
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
     if (!context) {
        return nullptr;
    }

    context->setArmor(armor);
    // this is the hackish interface for downloading from keyserers currently:
```

```
    context->setKeyListMode(GpgME::Extern);
    return new QGpgME::QGpgMEDownloadJob(context);
  }

  QGpgME::DeleteJob *deleteJob() const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }
    return new QGpgME::QGpgMEDeleteJob(context);
  }

  QGpgME::SignEncryptJob *signEncryptJob(bool armor, bool textMode) const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }

    context->setArmor(armor);
    context->setTextMode(textMode);
    return new QGpgME::QGpgMESignEncryptJob(context);
  }

  QGpgME::DecryptVerifyJob *decryptVerifyJob(bool
textMode) const Q_DECL_OVERRIDE
  {
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }

    context->setTextMode(textMode);
    return new QGpgME::QGpgMEDecryptVerifyJob(context);
  }

  QGpgME::ChangeExpiryJob *changeExpiryJob() const Q_DECL_OVERRIDE
  {
    if (mProtocol != GpgME::OpenPGP) {
      return nullptr;    // only supported by gpg
    }

    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
      return nullptr;
    }
    return new QGpgME::QGpgMEChangeExpiryJob(context);
```

```
}

QGpgME::ChangePasswdJob *changePasswdJob() const Q_DECL_OVERRIDE
{
   if (!GpgME::hasFeature(GpgME::PasswdFeature, 0)) {
      return nullptr;
   }
   GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
   if (!context) {
      return nullptr;
   }
    return new QGpgME::QGpgMEChangePasswdJob(context);
}

QGpgME::SignKeyJob *signKeyJob() const Q_DECL_OVERRIDE
{
   if (mProtocol != GpgME::OpenPGP) {
      return nullptr;    // only supported by gpg
   }

   GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
   if (!context) {
      return nullptr;
   }
   return new QGpgME::QGpgMESignKeyJob(context);
}

QGpgME::ChangeOwnerTrustJob *changeOwnerTrustJob() const Q_DECL_OVERRIDE
{
   if (mProtocol != GpgME::OpenPGP) {
      return nullptr;    // only supported by gpg
   }

   GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
   if (!context) {
      return nullptr;
   }
   return new QGpgME::QGpgMEChangeOwnerTrustJob(context);
}

QGpgME::AddUserIDJob *addUserIDJob() const Q_DECL_OVERRIDE
{
   if (mProtocol != GpgME::OpenPGP) {
      return nullptr;    // only
supported by gpg
   }

   GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
```

```
    if (!context) {
        return nullptr;
    }
    return new QGpgME::QGpgMEAddUserIDJob(context);
}

QGpgME::KeyListJob *locateKeysJob() const Q_DECL_OVERRIDE
{
    if (mProtocol != GpgME::OpenPGP) {
        return nullptr;
    }
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
        return nullptr;
    }
    context->setKeyListMode(GpgME::Extern | GpgME::Local | GpgME::Signatures | GpgME::Validate);
    return new QGpgME::QGpgMEKeyListJob(context);
}

QGpgME::KeyForMailboxJob *keyForMailboxJob() const Q_DECL_OVERRIDE
{
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
        return nullptr;
    }
    return new QGpgME::QGpgMEKeyForMailboxJob(context);
}

QGpgME::WKSPublishJob *wksPublishJob()
const Q_DECL_OVERRIDE
{
    if (mProtocol != GpgME::OpenPGP) {
        return nullptr;
    }
    auto context = GpgME::Context::createForEngine(GpgME::SpawnEngine);
    if (!context) {
        return nullptr;
    }
    return new QGpgME::QGpgMEWKSPublishJob(context.release());
}

QGpgME::TofuPolicyJob *tofuPolicyJob() const Q_DECL_OVERRIDE
{
    if (mProtocol != GpgME::OpenPGP) {
        return nullptr;
    }
    GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
    if (!context) {
```

```
        return nullptr;
      }
      return new QGpgME::QGpgMETofuPolicyJob(context);
    }

    QGpgME::QuickJob *quickJob() const Q_DECL_OVERRIDE
    {
      if (mProtocol != GpgME::OpenPGP) {
        return nullptr;
      }
      GpgME::Context *context = GpgME::Context::createForProtocol(mProtocol);
      if (!context) {
        return nullptr;
      }
      return new QGpgME::QGpgMEQuickJob(context);
    }
};

}
#endif
/*
  qgpgmelistallkeysjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
```

```
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __QGPGME_QGPGMELISTALLKEYSJOB_H__
#define __QGPGME_QGPGMELISTALLKEYSJOB_H__

#include "listallkeysjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "keylistresult.h"
#else
#include <gpgme++/keylistresult.h>
#endif
#ifdef BUILDING_QGPGME
# include "key.h"
#else
#include <gpgme++/key.h>
#endif

namespace QGpgME
{

class QGpgMEListAllKeysJob
#ifdef Q_MOC_RUN
    : public ListAllKeysJob
#else
   : public _detail::ThreadedJobMixin<ListAllKeysJob, std::tuple<GpgME::KeyListResult,
std::vector<GpgME::Key>, std::vector<GpgME::Key>, QString, GpgME::Error> >
#endif
{
   Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
   void slotFinished();
#endif
public:
   explicit QGpgMEListAllKeysJob(GpgME::Context *context);
   ~QGpgMEListAllKeysJob();

   /* from ListAllKeysJob */
   GpgME::Error start(bool mergeKeys) Q_DECL_OVERRIDE;
```

```
  /* from ListAllKeysJob */
  GpgME::KeyListResult exec(std::vector<GpgME::Key> &pub, std::vector<GpgME::Key> &sec, bool
mergeKeys) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &result) Q_DECL_OVERRIDE;

private:
  GpgME::KeyListResult mResult;
};

}

#endif // __QGPGME_QGPGMELISTALLKEYSJOB_H__
/*
  importjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
```

```
#ifndef __KLEO_IMPORTJOB_H__
#define __KLEO_IMPORTJOB_H__

#include "abstractimportjob.h"
#include "qgpgme_export.h"

#include <QtCore/QByteArray>

namespace GpgME
{
class Error;
class ImportResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous importers

  To use a ImportJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress()
 and result()
  signals to suitable slots and then start the import with a call
  to start(). This call might fail, in which case the ImportJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the ImportJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT ImportJob : public AbstractImportJob
{
  Q_OBJECT
protected:
  explicit ImportJob(QObject *parent);
public:
  ~ImportJob();

  /**
    Starts the importing operation. \a keyData contains the data to
    import from.
  */
  virtual GpgME::Error start(const QByteArray &keyData) = 0;

  virtual GpgME::ImportResult exec(const QByteArray &keyData) = 0;
};
```

```
}

#endif // __KLEO_IMPORTJOB_H__
/* t-support.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link
 the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
#ifndef T_SUPPORT_H
#define T_SUPPORT_H

#include "interfaces/passphraseprovider.h"
#include <QObject>

#include <gpg-error.h>

namespace GpgME
{
class TestPassphraseProvider : public PassphraseProvider
{
```

```
public:
  char *getPassphrase(const char * /*useridHint*/, const char * /*description*/,
                      bool /*previousWasBad*/, bool &/*canceled*/) Q_DECL_OVERRIDE
  {
     char *ret;
     gpgrt_asprintf(&ret, "abc");
     return
 ret;
  }
};
} // namespace GpgME

void killAgent(const QString &dir = qgetenv("GNUPGHOME"));
/* Is the passphrase Provider / loopback Supported */
bool loopbackSupported();

class QGpgMETest : public QObject
{
  Q_OBJECT
protected:
  bool copyKeyrings(const QString &from, const QString& to);

public Q_SLOTS:
  void initTestCase();
  void cleanupTestCase();
};

/* Timeout, in milliseconds, for use with QSignalSpy to wait on
  signals.  */
#define QSIGNALSPY_TIMEOUT 60000

#endif // T_SUPPORT_H
/*
 statusconsumer.h - Interface for status callbacks
 Copyright (c) 2020 g10 Code GmbH
 Software engineering by Ingo Klcker <dev@ingo-kloecker.de>

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.
```

```
 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_INTERFACES_STATUSCONSUMER_H__
#define __GPGMEPP_INTERFACES_STATUSCONSUMER_H__

#include
 "gpgmepp_export.h"

namespace GpgME
{

class GPGMEPP_EXPORT StatusConsumer
{
public:
  virtual ~StatusConsumer() {}

  virtual void status(const char *status, const char *details) = 0;
};

} // namespace GpgME

#endif // __GPGMEPP_INTERFACES_STATUSCONSUMER_H__
{
  "op": "version"
}
/*
 data_p.h - wraps a gpgme data object, private part -*- c++ -*-
 Copyright (C) 2003,2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.
```

```
 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef
 __GPGMEPP_DATA_P_H__
#define __GPGMEPP_DATA_P_H__

#include <data.h>
#include "callbacks.h"

class GpgME::Data::Private
{
public:
   explicit Private(gpgme_data_t d = nullptr)
      : data(d), cbs(data_provider_callbacks) {}
   ~Private();

   gpgme_data_t data;
   gpgme_data_cbs cbs;
};

#endif // __GPGMEPP_DATA_P_H__
/* context.h - Definitions for a GPGME context.
  Copyright (C) 2000 Werner Koch (dd9jn)
  Copyright (C) 2001, 2002, 2003, 2004, 2005, 2010 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, see <https://www.gnu.org/licenses/>.
*/

#ifndef CONTEXT_H
#define CONTEXT_H
```

```
#include "gpgme.h"
#include "engine.h"
#include "wait.h"
#include "sema.h"


extern gpgme_error_t _gpgme_selftest;

/*
 Operations might require to remember arbitrary information and data
  objects during invocations of the status handler.  The
  ctx_op_data structure provides a generic framework to hook in
  such additional data.  */
typedef enum
 {
   OPDATA_DECRYPT, OPDATA_SIGN, OPDATA_ENCRYPT, OPDATA_PASSPHRASE,
   OPDATA_IMPORT, OPDATA_GENKEY, OPDATA_KEYLIST, OPDATA_EDIT,
   OPDATA_VERIFY, OPDATA_TRUSTLIST, OPDATA_ASSUAN, OPDATA_VFS_MOUNT,
   OPDATA_PASSWD, OPDATA_EXPORT, OPDATA_KEYSIGN, OPDATA_TOFU_POLICY,
   OPDATA_QUERY_SWDB, OPDATA_SETEXPIRE, OPDATA_REVSIG
 } ctx_op_data_id_t;


/* "gpgmeres" in ASCII.  */
#define CTX_OP_DATA_MAGIC 0x736572656d677067ULL
struct ctx_op_data
{
 /* A magic word just to make sure people don't deallocate something
    that ain't a result structure.  */
 unsigned long long magic;

 /* The next element in the linked list, or NULL if this is the last
    element.  Used by op data structures linked into a context.  */
 struct ctx_op_data *next;

 /* The
 type of the hook data, which can be used by a routine to
    lookup the hook data.  */
 ctx_op_data_id_t type;

 /* The function to release HOOK and all its associated resources.
    Can be NULL if no special deallocation routine is necessary.  */
 void (*cleanup) (void *hook);

 /* The hook that points to the operation data.  */
 void *hook;

 /* The number of outstanding references.  */
```

```
 int references;
};
typedef struct ctx_op_data *ctx_op_data_t;


/* The context defines an environment in which crypto operations can
  be performed (sequentially).  */
struct gpgme_context
{
 DECLARE_LOCK (lock);

 /* True if the context was canceled asynchronously.  */
 int canceled;

 /* The engine info for this context.  */
 gpgme_engine_info_t engine_info;

 /* The protocol used by this context.  */
 gpgme_protocol_t protocol;

 /* The running engine process.  */
 engine_t engine;

 /* Engine's sub protocol.  */
 gpgme_protocol_t sub_protocol;

 /* True if armor mode should
 be used.  */
 unsigned int use_armor : 1;

 /* True if text mode should be used.  */
 unsigned int use_textmode : 1;

 /* True if offline mode should be used.  */
 unsigned int offline : 1;

 /* True if a status callback shall be called for nearly all status
  * lines.  */
 unsigned int full_status : 1;

 /* The Tofu info has a human readable string which is presented to
  * the user in a directly usable format.  By enabling this flag the
  * unmodified string, as received form gpg, will be returned.  */
 unsigned int raw_description : 1;

 /* True if session keys should be exported upon decryption.  */
 unsigned int export_session_keys : 1;
```

```
/* True if a Pinentry was launched during the last operation.  This
 * flag is cleared with each operation.  */
unsigned int redraw_suggested : 1;

/* True if the option --include-key-block shall be passed to gpg.  */
unsigned int include_key_block : 1;

/* True if the option --auto-key-import shall be passed to gpg.  */
 unsigned int auto_key_import : 1;

/* True if the option --auto-key-retrieve shall be passed to gpg.  */
unsigned int auto_key_retrieve : 1;

/* Do not use the symmtric encryption passphrase cache.  */
unsigned int no_symkey_cache : 1;

/* Pass --ignore-mdc-error to gpg.  Note that this flag is reset
 * after the operation.  */
unsigned int ignore_mdc_error : 1;

/* Pass --expert to gpg edit key. */
unsigned int extended_edit : 1;

/* Flags for keylist mode.  */
gpgme_keylist_mode_t keylist_mode;

/* The current pinentry mode.  */
gpgme_pinentry_mode_t pinentry_mode;

/* Number of certs to be included.  */
unsigned int include_certs;

/* The actual number of keys in SIGNERS, the allocated size of the
 * array, and the array with the signing keys.  */
unsigned int signers_len;
unsigned int signers_size;
gpgme_key_t *signers;

/* The signature notations for this context.  */
gpgme_sig_notation_t sig_notations;

/* The sender's addr-spec or
NULL.  */
char *sender;

/* The gpg specific override session key or NULL. */
char *override_session_key;
```

```
  /* The optional request origin.  */
  char *request_origin;

  /* The optional auto key locate options.  */
  char *auto_key_locate;

  /* The locale for the pinentry.  */
  char *lc_ctype;
  char *lc_messages;

  /* The optional trust-model override.  */
  char *trust_model;

  /* The operation data hooked into the context.  */
  ctx_op_data_t op_data;

  /* The user provided passphrase callback and its hook value.  */
  gpgme_passphrase_cb_t passphrase_cb;
  void *passphrase_cb_value;

  /* The user provided progress callback and its hook value.  */
  gpgme_progress_cb_t progress_cb;
  void *progress_cb_value;

  /* The user provided status callback and its hook value.  */
  gpgme_status_cb_t status_cb;
  void *status_cb_value;

  /* A list of file descriptors in active use by the current
     operation.  */
  struct fd_table fdt;
  struct gpgme_io_cbs io_cbs;
};

#endif /*
  CONTEXT_H */
/* sema.h - Definitions for semaphores.
   Copyright (C) 2000 Werner Koch (dd9jn)
   Copyright (C) 2001, 2003, 2004, 2007 g10 Code GmbH

   This file is part of GPGME.

   GPGME is free software; you can redistribute it and/or modify it
   under the terms of the GNU Lesser General Public License as
   published by the Free Software Foundation; either version 2.1 of
   the License, or (at your option) any later version.

   GPGME is distributed in the hope that it will be useful, but
```

```
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef SEMA_H
#define SEMA_H

#include <gpg-error.h>

#define DEFINE_GLOBAL_LOCK(name) \
 gpgrt_lock_t
 name  = GPGRT_LOCK_INITIALIZER

#define DEFINE_STATIC_LOCK(name) \
 static gpgrt_lock_t name = GPGRT_LOCK_INITIALIZER

#define INIT_LOCK(name) \
 name = (gpgrt_lock_t) GPGRT_LOCK_INITIALIZER

#define DECLARE_LOCK(name) gpgrt_lock_t name

#define DESTROY_LOCK(name) gpgrt_lock_destroy(&name)

#define LOCK(name) gpgrt_lock_lock(&name)

#define UNLOCK(name) gpgrt_lock_unlock(&name)

#endif /* SEMA_H */
# This is a template.  The dist target uses it to create the real file.
Summary: GPGME - GnuPG Made Easy
Name: gpgme
Version: 1.15.1
Release: 1
URL: https://gnupg.org/gpgme.html
Source: https://www.gnupg.org/ftp/gcrypt/gpgme/%{name}-%{version}.tar.gz
Group: Development/Libraries
Copyright: GPL
BuildRoot: %{_tmppath}/%{name}-%{version}
BuildRequires: make
Prereq: /sbin/ldconfig /sbin/install-info
Requires: gnupg

%description
```

```
GnuPG Made Easy (GPGME) is a library designed to make access to GnuPG easier
for applications. It provides a High-Level Crypto API for encryption,
decryption, signing, signature verification and key management.

%prep
%setup -q

%build
CFLAGS="$RPM_OPT_FLAGS"; export CFLAGS
./configure --prefix=/usr
make

%install
rm -fr $RPM_BUILD_ROOT
mkdir -p $RPM_BUILD_ROOT
make install prefix=$RPM_BUILD_ROOT/usr infodir=$RPM_BUILD_ROOT%{_infodir}
rm -f $RPM_BUILD_ROOT%{_infodir}/dir

%clean
rm -fr $RPM_BUILD_ROOT
make distclean

%post
/sbin/ldconfig
/sbin/install-info %{_infodir}/gpgme.info.gz
 %{_infodir}/dir
/sbin/install-info %{_infodir}/gpgme-python-howto.info.gz %{_infodir}/dir

%preun
if [ "$1" = 0 ]; then
/sbin/install-info --delete %{_infodir}/gpgme.info.gz %{_infodir}/dir
/sbin/install-info --delete %{_infodir}/gpgme-python-howto.info.gz %{_infodir}/dir
fi

%postun
/sbin/ldconfig

%files
%defattr(-,root,root)
%doc COPYING COPYING.LESSER AUTHORS README INSTALL NEWS ChangeLog TODO THANKS
%attr(0755,root,root) %{_bindir}/gpgme-config
%attr(0755,root,root) %{_libdir}/*gpgme.so*
%attr(0755,root,root) %{_libdir}/*gpgme.la
%attr(0644,root,root) %{_libdir}/*gpgme.a
%{_includedir}/gpgme.h
%{_datadir}/aclocal/gpgme.m4
%{_infodir}/gpgme.info*
%{_infodir}/gpgme-python-howto.info*
```

```
%changelog
* Sat Aug 30 2003 Robert Schiele <rschiele@uni-mannheim.de>
- %{_infodir}/dir is not packaged, remove to prevent checking failure
* Mon Jul 01 2002 Wojciech Polak <polak@lodz.pdi.net>
- initial specfile release for GPGME.

# EOF
/*
  threadedjobmixin.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_THREADEDJOBMIXING_H__
#define __QGPGME_THREADEDJOBMIXING_H__

#include <QMutex>
#include <QMutexLocker>
```

```
#include <QThread>
#include <QString>
#include <QIODevice>

#ifdef BUILDING_QGPGME
# include "context.h"
# include "interfaces/progressprovider.h"
#else
# include <gpgme++/context.h>
# include <gpgme++/interfaces/progressprovider.h>
#endif

#include "job.h"

#include
 <cassert>
#include <functional>

namespace QGpgME
{
namespace _detail
{

QString audit_log_as_html(GpgME::Context *ctx, GpgME::Error &err);

class PatternConverter
{
  const QList<QByteArray> m_list;
  mutable const char **m_patterns;
public:
  explicit PatternConverter(const QByteArray &ba);
  explicit PatternConverter(const QString &s);
  explicit PatternConverter(const QList<QByteArray> &lba);
  explicit PatternConverter(const QStringList &sl);
  ~PatternConverter();

  const char **patterns() const;
};

class ToThreadMover
{
  QObject *const m_object;
  QThread *const m_thread;
public:
  ToThreadMover(QObject *o, QThread *t) : m_object(o), m_thread(t) {}
  ToThreadMover(QObject &o, QThread *t) : m_object(&o), m_thread(t) {}
  ToThreadMover(const std::shared_ptr<QObject> &o, QThread *t) : m_object(o.get()), m_thread(t) {}
  ~ToThreadMover()
```

```
  {
    if (m_object && m_thread) {
      m_object->moveToThread(m_thread);
    }
  }
};

template
 <typename T_result>
class Thread : public QThread
{
public:
  explicit Thread(QObject *parent = Q_NULLPTR) : QThread(parent) {}

  void setFunction(const std::function<T_result()> &function)
  {
    const QMutexLocker locker(&m_mutex);
    m_function = function;
  }

  T_result result() const
  {
    const QMutexLocker locker(&m_mutex);
    return m_result;
  }

private:
  void run() Q_DECL_OVERRIDE {
    const QMutexLocker locker(&m_mutex);
    m_result = m_function();
  }
private:
  mutable QMutex m_mutex;
  std::function<T_result()> m_function;
  T_result m_result;
};

template <typename T_base, typename T_result = std::tuple<GpgME::Error, QString, GpgME::Error> >
class ThreadedJobMixin : public T_base, public GpgME::ProgressProvider
{
public:
  typedef ThreadedJobMixin<T_base, T_result> mixin_type;
  typedef T_result result_type;

protected:
  static_assert(std::tuple_size<T_result>::value > 2,
                "Result tuple too
```

```
small");
  static_assert(std::is_same <
                typename std::tuple_element <
                std::tuple_size<T_result>::value - 2,
                T_result
                >::type,
                QString
                >::value,
                "Second to last result type not a QString");
  static_assert(std::is_same <
                typename std::tuple_element <
                std::tuple_size<T_result>::value - 1,
                T_result
                >::type,
                GpgME::Error
                >::value,
                "Last result type not a GpgME::Error");

  explicit ThreadedJobMixin(GpgME::Context *ctx)
     : T_base(nullptr), m_ctx(ctx), m_thread(), m_auditLog(), m_auditLogError()
  {
  }

  void lateInitialization()
  {
     assert(m_ctx);
     QObject::connect(&m_thread, &QThread::finished, this,
                      &mixin_type::slotFinished);
     m_ctx->setProgressProvider(this);

QGpgME::g_context_map.insert(this, m_ctx.get());
  }

  ~ThreadedJobMixin()
  {
     QGpgME::g_context_map.remove(this);
  }

  template <typename T_binder>
  void run(const T_binder &func)
  {
     m_thread.setFunction(std::bind(func, this->context()));
     m_thread.start();
  }
  template <typename T_binder>
  void run(const T_binder &func, const std::shared_ptr<QIODevice> &io)
  {
     if (io) {
```

```
        io->moveToThread(&m_thread);
    }
    // the arguments passed here to the functor are stored in a QThread, and are not
    // necessarily destroyed (living outside the UI thread) at the time the result signal
    // is emitted and the signal receiver wants to clean up IO devices.
    // To avoid such races, we pass std::weak_ptr's to the functor.
    m_thread.setFunction(std::bind(func, this->context(), this->thread(), std::weak_ptr<QIODevice>(io)));
    m_thread.start();
  }
  template <typename T_binder>
  void
 run(const T_binder &func, const std::shared_ptr<QIODevice> &io1, const std::shared_ptr<QIODevice> &io2)
  {
    if (io1) {
        io1->moveToThread(&m_thread);
    }
    if (io2) {
        io2->moveToThread(&m_thread);
    }
    // the arguments passed here to the functor are stored in a QThread, and are not
    // necessarily destroyed (living outside the UI thread) at the time the result signal
    // is emitted and the signal receiver wants to clean up IO devices.
    // To avoid such races, we pass std::weak_ptr's to the functor.
    m_thread.setFunction(std::bind(func, this->context(), this->thread(), std::weak_ptr<QIODevice>(io1),
std::weak_ptr<QIODevice>(io2)));
    m_thread.start();
  }
  GpgME::Context *context() const
  {
    return m_ctx.get();
  }

  virtual void resultHook(const result_type &) {}

  void slotFinished()
  {
    const T_result r = m_thread.result();
    m_auditLog = std::get < std::tuple_size<T_result>::value
 - 2 > (r);
    m_auditLogError = std::get < std::tuple_size<T_result>::value - 1 > (r);
    resultHook(r);
    Q_EMIT this->done();
    doEmitResult(r);
    this->deleteLater();
  }
  void slotCancel() Q_DECL_OVERRIDE {
    if (m_ctx)
    {
```

```
            m_ctx->cancelPendingOperation();
        }
    }
    QString auditLogAsHtml() const Q_DECL_OVERRIDE
    {
        return m_auditLog;
    }
    GpgME::Error auditLogError() const Q_DECL_OVERRIDE
    {
        return m_auditLogError;
    }
    void showProgress(const char * /*what*/,
                      int /*type*/, int current, int total) Q_DECL_OVERRIDE {
        // will be called from the thread exec'ing the operation, so
        // just bounce everything to the owning thread:
        // ### hope this is thread-safe (meta obj is const, and
        // ### portEvent is thread-safe, so should be ok)
        QMetaObject::invokeMethod(this, "progress", Qt::QueuedConnection,

        // TODO port
        Q_ARG(QString, QString()),
        Q_ARG(int, current),
        Q_ARG(int, total));
    }
  private:
    template <typename T1, typename T2>
    void doEmitResult(const std::tuple<T1, T2> &tuple)
    {
        Q_EMIT this->result(std::get<0>(tuple), std::get<1>(tuple));
    }

    template <typename T1, typename T2, typename T3>
    void doEmitResult(const std::tuple<T1, T2, T3> &tuple)
    {
        Q_EMIT this->result(std::get<0>(tuple), std::get<1>(tuple), std::get<2>(tuple));
    }

    template <typename T1, typename T2, typename T3, typename T4>
    void doEmitResult(const std::tuple<T1, T2, T3, T4> &tuple)
    {
        Q_EMIT this->result(std::get<0>(tuple), std::get<1>(tuple), std::get<2>(tuple), std::get<3>(tuple));
    }

    template <typename T1, typename T2, typename T3, typename T4, typename T5>
    void doEmitResult(const std::tuple<T1, T2, T3, T4, T5> &tuple)
    {
        Q_EMIT this->result(std::get<0>(tuple), std::get<1>(tuple), std::get<2>(tuple),
```

```
 std::get<3>(tuple), std::get<4>(tuple));
  }

private:
  std::shared_ptr<GpgME::Context> m_ctx;
  Thread<T_result> m_thread;
  QString m_auditLog;
  GpgME::Error m_auditLogError;
};

}
}

#endif /* __QGPGME_THREADEDJOBMIXING_H__ */
/*
  deletejob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
```

```
#ifndef __KLEO_DELETEJOB_H__
#define __KLEO_DELETEJOB_H__

#include "qgpgme_export.h"
#include "job.h"

namespace GpgME
{
class Error;
class Key;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous deleters

  To use a DeleteJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then
 start the delete with a call
  to start(). This call might fail, in which case the DeleteJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the DeleteJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT DeleteJob : public Job
{
  Q_OBJECT
protected:
  explicit DeleteJob(QObject *parent);
public:
  ~DeleteJob();

  /**
    Starts the delete operation. \a key represents the key to
    delete, \a allowSecretKeyDeletion specifies if a key may also
    be deleted if the secret key part is available, too.
  */
  virtual GpgME::Error start(const GpgME::Key &key, bool allowSecretKeyDeletion = false) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &result, const QString &auditLogAsHtml = QString(), const GpgME::Error
&auditLogError = GpgME::Error());
```

```
};

}

#endif // __KLEO_DELETEJOB_H__
/*
  qgpgmedownloadjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEDOWNLOADJOB_H__
#define __QGPGME_QGPGMEDOWNLOADJOB_H__

#include "downloadjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
```

```
{

class QGpgMEDownloadJob
#ifdef Q_MOC_RUN
  : public DownloadJob
#else
  : public _detail::ThreadedJobMixin<DownloadJob, std::tuple<GpgME::Error, QByteArray, QString,
GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public
 Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEDownloadJob(GpgME::Context *context);
  ~QGpgMEDownloadJob();

  /* from DownloadJob */
  GpgME::Error start(const QStringList &fingerprints) Q_DECL_OVERRIDE;

  /* from DownloadJob */
  GpgME::Error start(const QByteArray &fingerprint, const std::shared_ptr<QIODevice> &keyData)
Q_DECL_OVERRIDE;
};

}

#endif // __QGPGME_QGPGMEDOWNLOADJOB_H__
#include "qgpgme/signkeyjob.h"
/*
  keyformailboxjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.
```

```
   You should have received a copy of the GNU General Public License
   along with this program; if not, write to the Free Software
   Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a special exception, the copyright holders give
   permission
  to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/
#ifndef __KLEO_KEYFORMAILBOX_H__
#define __KLEO_KEYFORMAILBOX_H__

#include <QString>

#include "job.h"

#ifdef BUILDING_QGPGME
# include "key.h"
#else
# include <gpgme++/key.h>
#endif

namespace GpgME
{
class Error;
class KeyListResult;
}

namespace QGpgME
{

/**
   @short Get the best key to use for a Mailbox

   To use the keyformailboxjob, first obtain an instance from the
   CryptoBackend and either exec it or start and
   conncet the
  result() signals to a suitable slot.
   The job will be automatically deleted in which
   case the KeylistJob instance will have schedules it's own
```

```
  destruction with a call to QObject::deleteLater().

  The best key is defined as the key with a UID that has an
  E-Mail that matches the mailbox provided. If multiple
  keys are found the one with the highest validity is returned.

  After result() is emitted, the
  KeyListJob will schedule it's own destruction by calling
  QObject::deleteLater().
*/
class QGPGME_EXPORT KeyForMailboxJob: public Job
{
  Q_OBJECT
protected:
  explicit KeyForMailboxJob(QObject *parent);

public:
  ~KeyForMailboxJob();

  /**
    Starts the operation. \a mailbox is the mailbox to
    look for.

    The result is the same as for the LocateKeysJob.

    If \a canEncrypt is true, only keys that have a subkey for encryption
    usage are returned. Use this if you need to select a
    key for signing.
  */
  virtual GpgME::Error
 start(const QString &mailbox, bool canEncrypt = true) = 0;

  virtual GpgME::KeyListResult exec(const QString &mailbox, bool canEncrypt, GpgME::Key &key,
GpgME::UserID &uid) = 0;

Q_SIGNALS:
  /** The result. \a Key is the key found or a Null key.
   *
   * The userid is the uid where the mailbox matches.
   *
   * The auditlog params are always null / empty.
   */
  void result(const GpgME::KeyListResult &result, const GpgME::Key &key, const GpgME::UserID &uid, const
QString &auditLogAsHtml = QString(), const GpgME::Error &auditLogError = GpgME::Error());
};

}
#endif
```

```
/*
  hierarchicalkeylistjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_HIERARCHICALKEYLISTJOB_H__
#define __KLEO_HIERARCHICALKEYLISTJOB_H__

#include "qgpgme_export.h"
#include "keylistjob.h"
#include "cryptobackend.h"

#ifdef BUILDING_QGPGME
# include "keylistresult.h"
#else
#include <gpgme++/keylistresult.h>
#endif
```

```
#include <QPointer>

#include <set>

namespace GpgME
{
class Error;
class Key;
}

namespace QGpgME
{
class KeyListJob;
}

namespace
 QGpgME
{

/**
  @short A convenience job that additionally fetches all available issuers.

  To use a HierarchicalKeyListJob, pass it a CryptoBackend
  implementation, connect the progress() and result() signals to
  suitable slots and then start the keylisting with a call to
  start(). This call might fail, in which case the
  HierarchicalKeyListJob instance will have scheduled it's own
  destruction with a call to QObject::deleteLater().

  After result() is emitted, the HierarchicalKeyListJob will
  schedule its own destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT HierarchicalKeyListJob : public KeyListJob
{
  Q_OBJECT
public:
  explicit HierarchicalKeyListJob(const Protocol *protocol,
                                  bool remote = false, bool includeSigs = false,
                                  bool validating = false);
  ~HierarchicalKeyListJob();

  /**
    Starts the keylist operation. \a patterns is a list of patterns
     used to restrict the list of keys returned. Empty patterns are
    ignored. \a patterns must not be empty or contain only empty
    patterns; use the normal KeyListJob for a full listing.

    The \a secretOnly parameter is ignored by
```

```
    HierarchicalKeyListJob and must be set to false.
  */
  GpgME::Error start(const QStringList &patterns, bool secretOnly = false) Q_DECL_OVERRIDE;

  GpgME::KeyListResult exec(const QStringList &patterns, bool secretOnly,
                            std::vector<GpgME::Key> &keys) Q_DECL_OVERRIDE;

private Q_SLOTS:
  void slotResult(const GpgME::KeyListResult &);
  void slotNextKey(const GpgME::Key &key);
  /* from Job */
  void slotCancel() Q_DECL_OVERRIDE;

private:
  GpgME::Error startAJob();

private:
  const Protocol *const mProtocol;
  const bool mRemote;
  const bool mIncludeSigs;
  const bool mValidating;
  bool mTruncated;
  std::set<QString> mSentSet; // keys already sent (prevent duplicates even
 if the backend should return them)
  std::set<QString> mScheduledSet; // keys already scheduled (by starting a job for them)
  std::set<QString> mNextSet; // keys to schedule for the next iteraton
  GpgME::KeyListResult mIntermediateResult;
  QPointer<KeyListJob> mJob;
};

}

#endif // __KLEO_HIERARCHICALKEYLISTJOB_H__
/*
  qgpgmeadduseridjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
```

```
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEADDUSERIDJOB_H__
#define __QGPGME_QGPGMEADDUSERIDJOB_H__

#include "adduseridjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
{

class QGpgMEAddUserIDJob
#ifdef Q_MOC_RUN
  : public AddUserIDJob
#else
  : public _detail::ThreadedJobMixin<AddUserIDJob>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit
 QGpgMEAddUserIDJob(GpgME::Context *context);
  ~QGpgMEAddUserIDJob();

  /* from AddUserIDJob */
```

```
  GpgME::Error start(const GpgME::Key &key, const QString &name, const QString &email, const QString
&comment) Q_DECL_OVERRIDE;
};
}

#endif // __QGPGME_QGPGMEADDUSERIDJOB_H__
/*  qgpgmegpgcardjob.h

  This file is part of libkleopatra, the KDE keymanagement library
  Copyright (c) 2020 g10 Code GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by
 Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEGPGCARDJOB_H__
#define __QGPGME_QGPGMEGPGCARDJOB_H__
#include "gpgcardjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
{

class QGpgMEGpgCardJob
```

```
#ifdef Q_MOC_RUN
  : public GpgCardJob
#else
  : public _detail::ThreadedJobMixin<GpgCardJob, std::tuple<QString, QString, int, QString, GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEGpgCardJob();
  ~QGpgMEGpgCardJob();

  GpgME::Error start(const QStringList
 &cmds) Q_DECL_OVERRIDE;

  GpgME::Error exec(const QStringList &cmds, QString &std_out, QString &std_err, int &exitCode)
Q_DECL_OVERRIDE;
};

}
#endif
{
  "op": "encrypt",
  "keys": ["bravo@example.net", "alpha@example.net"],
  "data": "Hello world",
  "file_name": "test.txt",
  "armor": false,
  "always-trust": true
}
/*
 swdbresult.h - wraps a gpgme swdb query / rsult
 Copyright (C) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.
```

```
 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/
#ifndef __GPGMEPP_SWDB_H__
#define __GPGMEPP_SWDB_H__

#include
 "gpgmepp_export.h"

#include "global.h"
#include "engineinfo.h"

#include <vector>
#include <string>
#include <iostream>
#include <ostream>

namespace GpgME
{

class GPGMEPP_EXPORT SwdbResult
{
public:
  /* Obtain swdb results through query() */
  SwdbResult();
  explicit SwdbResult(gpgme_query_swdb_result_t result);

  /** Query the swdb to get information about updates.
   *
   * Runs gpgconf --query-swdb through gpgme and
   * returns a list of results.
   * If iversion is given as NULL a check is only done if GPGME
   * can figure out the version by itself (for example when using
   * "gpgme" or "gnupg").
   *
   * If NULL is used for name the current gpgme version is
   * checked.
   *
   * @param name: Name of the component to query.
   * @param iversion: Optionally the installed version.
   * @param err: Optional error.
   */
  static std::vector<SwdbResult> query(const char *name,
                                       const char
```

```
*iversion = NULL,
                                Error *err = NULL);

  const SwdbResult &operator=(SwdbResult other)
  {
     swap(other);
     return *this;
  }

  void swap(SwdbResult &other)
  {
     using std::swap;
     swap(this->d, other.d);
  }
  bool isNull() const;

  /* The name of the package (e.g. "gpgme", "gnupg") */
  std::string name() const;

  /* The version of the installed version.  */
  EngineInfo::Version installedVersion() const;

  /* The time the online info was created.  */
  unsigned long created() const;

  /* The time the online info was retrieved.  */
  unsigned long retrieved() const;

  /* This bit is set if an error occurred or some of the information
   * in this structure may not be set.  */
  bool warning() const;

  /* An update is available.  */
  bool update() const;

  /* The update is important.  */
  bool urgent() const;

  /* No information at all available.  */
  bool noinfo()
const;

  /* The package name is not known. */
  bool unknown() const;

  /* The information here is too old.  */
  bool tooOld() const;
```

```
  /* Other error.  */
  bool error() const;

  /* The version of the latest released version.  */
  EngineInfo::Version version() const;

  /* The release date of that version.  */
  unsigned long releaseDate() const;

private:
  class Private;
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const SwdbResult &info);

} // namespace GpgME

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(SwdbResult)

#endif
/* priv-io.h - Interface to the private I/O functions.
  Copyright (C) 2000 Werner Koch (dd9jn)
  Copyright (C) 2001, 2002, 2003, 2004, 2005 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef IO_H
#define IO_H

#ifdef HAVE_W32_SYSTEM
# include <winsock2.h>
# include <windows.h>
```

```
#else
#
 include <sys/socket.h>
#endif

/* For pid_t.  */
#ifdef HAVE_SYS_TYPES_H
# include <sys/types.h>
#endif


/* A single file descriptor passed to spawn.  For child fds, dup_to
  specifies the fd it should become in the child, but only 0, 1 and 2
  are valid values (due to a limitation in the W32 code).  As return
  value, the PEER_NAME fields specify the name of the file
  descriptor in the spawned process, or -1 if no change.  If ARG_LOC
  is not 0, it specifies the index in the argument vector of the
  program which contains a numerical representation of the file
  descriptor for translation purposes.  */
struct spawn_fd_item_s
{
 int fd;
 int dup_to;
 int peer_name;
 int arg_loc;
};

struct io_select_fd_s
{
 int fd;
 int for_read;
 int for_write;
 int signaled;
 void *opaque;
};

/* These function are either defined in posix-io.c or w32-io.c.  */
void _gpgme_io_subsystem_init (void);
int _gpgme_io_socket (int namespace, int style, int protocol);
int
 _gpgme_io_connect (int fd, struct sockaddr *addr, int addrlen);
int _gpgme_io_read (int fd, void *buffer, size_t count);
int _gpgme_io_write (int fd, const void *buffer, size_t count);
int _gpgme_io_pipe (int filedes[2], int inherit_idx);
int _gpgme_io_close (int fd);
typedef void (*_gpgme_close_notify_handler_t) (int,void*);
int _gpgme_io_set_close_notify (int fd, _gpgme_close_notify_handler_t handler,
    void *value);
```

```
int _gpgme_io_set_nonblocking (int fd);

/* Under Windows do not allocate a console.  */
#define IOSPAWN_FLAG_DETACHED 1
/* A flag to tell the spawn function to allow the child process to set
  the foreground window. */
#define IOSPAWN_FLAG_ALLOW_SET_FG 2
/* Don't close any child FDs.  */
#define IOSPAWN_FLAG_NOCLOSE 4
/* Set show window to true for windows */
#define IOSPAWN_FLAG_SHOW_WINDOW 8

/* Spawn the executable PATH with ARGV as arguments.  After forking
  close all fds except for those in FD_LIST in the child, then
  optionally dup() the child fds.  Finally,
 all fds in the list are
  closed in the parent.  */
int _gpgme_io_spawn (const char *path, char *const argv[], unsigned int flags,
       struct spawn_fd_item_s *fd_list,
       void (*atfork) (void *opaque, int reserved),
       void *atforkvalue, pid_t *r_pid);

int _gpgme_io_select (struct io_select_fd_s *fds, size_t nfds, int nonblock);

/* Write the printable version of FD to the buffer BUF of length
  BUFLEN.  The printable version is the representation on the command
  line that the child process expects.  */
int _gpgme_io_fd2str (char *buf, int buflen, int fd);

/* Duplicate a file descriptor.  This is more restrictive than dup():
  it assumes that the resulting file descriptors are essentially
  co-equal (for example, no private offset), which is true for pipes
  and sockets (but not files) under Unix with the standard dup()
  function.  Basically, this function is used to reference count the
  status output file descriptor shared between GPGME and libassuan
  (in engine-gpgsm.c).
  */
int _gpgme_io_dup (int fd);

#ifndef HAVE_W32_SYSTEM
int _gpgme_io_recvmsg (int fd, struct msghdr *msg, int flags);
int _gpgme_io_sendmsg (int fd, const struct msghdr *msg, int flags);
int _gpgme_io_waitpid (int pid, int hang, int *r_status, int *r_signal);
#endif

#endif /* IO_H */
/*
 context_p.h - wraps a gpgme context (private part)
```

```
 Copyright (C) 2003, 2007 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++
 -*-
#ifndef __GPGMEPP_CONTEXT_P_H__
#define __GPGMEPP_CONTEXT_P_H__

#include <context.h>
#include <data.h>

#include <gpgme.h>

namespace GpgME
{

class Context::Private
{
public:
  enum Operation {
      None = 0,

      Encrypt   = 0x001,
      Decrypt   = 0x002,
      Sign      = 0x004,
      Verify    = 0x008,
      DecryptAndVerify = Decrypt | Verify,
      SignAndEncrypt   = Sign | Encrypt,
```

```
    Import    = 0x010,
    Export    = 0x020, // no gpgme_export_result_t, but nevertheless...
    Delete    = 0x040, // no gpgme_delete_result_t, but nevertheless...

    KeyGen    = 0x080,
    KeyList   = 0x100,
    TrustList = 0x200, // no gpgme_trustlist_result_t, but nevertheless...

    Edit      = 0x400, // no gpgme_edit_result_t, but nevertheless...
    CardEdit  = 0x800, // no gpgme_card_edit_result_t, but nevertheless...

    GetAuditLog = 0x1000, // no gpgme_getauditlog_result_t, but nevertheless...

    AssuanTransact = 0x2000,
     Passwd    = 0x4000, // no gpgme_passwd_result_t, but nevertheless...

    CreateVFS = 0x4000,
    MountVFS = 0x8000,

    EndMarker
  };

  Private(gpgme_ctx_t c = nullptr);
  ~Private();

  gpgme_ctx_t ctx;
  gpgme_io_cbs *iocbs;
  Operation lastop;
  gpgme_error_t lasterr;
  Data lastAssuanInquireData;
  std::unique_ptr<AssuanTransaction> lastAssuanTransaction;
  std::unique_ptr<EditInteractor> lastEditInteractor, lastCardEditInteractor;
  DecryptionFlags decryptFlags;
};

} // namespace GpgME

#endif // __GPGMEPP_CONTEXT_P_H__
/*
  qgpgmedecryptjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
```

```
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEDECRYPTJOB_H__
#define __QGPGME_QGPGMEDECRYPTJOB_H__

#include "decryptjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "decryptionresult.h"
#else
#include <gpgme++/decryptionresult.h>
#endif

namespace QGpgME
{

class QGpgMEDecryptJob
#ifdef Q_MOC_RUN
  : public DecryptJob
#else
  : public _detail::ThreadedJobMixin<DecryptJob, std::tuple<GpgME::DecryptionResult,
 QByteArray, QString, GpgME::Error> >
#endif
```

```
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEDecryptJob(GpgME::Context *context);
  ~QGpgMEDecryptJob();

  /* from DecryptJob */
  GpgME::Error start(const QByteArray &cipherText) Q_DECL_OVERRIDE;

  /* from DecryptJob */
  void start(const std::shared_ptr<QIODevice> &cipherText, const std::shared_ptr<QIODevice> &plainText)
Q_DECL_OVERRIDE;

  /* from DecryptJob */
  GpgME::DecryptionResult exec(const QByteArray &cipherText,
                               QByteArray &plainText) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  GpgME::DecryptionResult mResult;
};

}
#endif // __QGPGME_QGPGMEDECRYPTJOB_H__
/* engine-backend.h - A crypto backend for the engine interface.
  Copyright (C) 2002, 2003, 2004, 2009 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, see <https://www.gnu.org/licenses/>.
*/
```

```
#ifndef ENGINE_BACKEND_H
#define ENGINE_BACKEND_H

#include "engine.h"

struct engine_ops
{
 /* Static functions.  */

 /* Return the default file name for the binary of this engine.  */
 const
 char *(*get_file_name) (void);

 /* Return the default home dir for the binary of this engine.  If
    this function pointer is not set, the standard default home dir
    of the engine is used. */
 const char *(*get_home_dir) (void);

 /* Returns a malloced string containing the version of the engine
    with the given binary file name (or the default if FILE_NAME is
    NULL.  */
 char *(*get_version) (const char *file_name);

 /* Returns a statically allocated string containing the required
    version.  */
 const char *(*get_req_version) (void);

 gpgme_error_t (*new) (void **r_engine,
   const char *file_name, const char *home_dir,
                       const char *version);

 /* Member functions.  */
 void (*release) (void *engine);
 gpgme_error_t (*reset) (void *engine);
 void (*set_status_cb) (void *engine, gpgme_status_cb_t cb, void *cb_value);
 void (*set_status_handler) (void *engine, engine_status_handler_t fnc,
         void *fnc_value);
 gpgme_error_t
 (*set_command_handler) (void *engine,
     engine_command_handler_t fnc,
     void *fnc_value);
 gpgme_error_t (*set_colon_line_handler) (void *engine,
        engine_colon_line_handler_t fnc,
        void *fnc_value);
 gpgme_error_t (*set_locale) (void *engine, int category, const char *value);
 gpgme_error_t (*set_protocol) (void *engine, gpgme_protocol_t protocol);
 void (*set_engine_flags) (void *engine, gpgme_ctx_t ctx);
```

```
gpgme_error_t (*decrypt) (void *engine,
                          gpgme_decrypt_flags_t flags,
                          gpgme_data_t ciph,
      gpgme_data_t plain, int export_session_key,
                          const char *override_session_key,
                          int auto_key_retrieve);
gpgme_error_t (*delete) (void *engine, gpgme_key_t key, unsigned int flags);
gpgme_error_t (*edit) (void *engine, int type, gpgme_key_t key,
   gpgme_data_t out, gpgme_ctx_t ctx /* FIXME */);
gpgme_error_t (*encrypt) (void *engine, gpgme_key_t recp[],
                          const char *recpstring,
      gpgme_encrypt_flags_t flags,
      gpgme_data_t plain, gpgme_data_t ciph,
      int use_armor);
gpgme_error_t (*encrypt_sign) (void *engine, gpgme_key_t recp[],
                               const char *recpstring,
    gpgme_encrypt_flags_t flags,
    gpgme_data_t plain, gpgme_data_t ciph,
    int use_armor, gpgme_ctx_t ctx /* FIXME */);
gpgme_error_t (*export) (void *engine, const char *pattern,
     gpgme_export_mode_t mode, gpgme_data_t keydata,
     int use_armor);
gpgme_error_t (*export_ext) (void *engine, const char *pattern[],
        gpgme_export_mode_t mode, gpgme_data_t keydata,
        int use_armor);
gpgme_error_t (*genkey) (void *engine,
                         const char *userid, const char *algo,
                         unsigned long reserved, unsigned long expires,
                         gpgme_key_t key, unsigned int flags,
                         gpgme_data_t help_data,
                          unsigned int extraflags,
     gpgme_data_t pubkey, gpgme_data_t seckey);
gpgme_error_t (*import) (void *engine, gpgme_data_t keydata,
                         gpgme_key_t *keyarray);
gpgme_error_t (*keylist) (void *engine, const char *pattern,
      int secret_only, gpgme_keylist_mode_t mode,
      int engine_flags);
gpgme_error_t (*keylist_ext) (void *engine, const char *pattern[],
   int secret_only, int reserved,
   gpgme_keylist_mode_t mode,
   int engine_flags);
gpgme_error_t (*keylist_data) (void *engine, gpgme_data_t data);
gpgme_error_t (*keysign) (void *engine,
                          gpgme_key_t key, const char *userid,
                          unsigned long expires, unsigned int flags,
                          gpgme_ctx_t ctx);
gpgme_error_t (*revsig) (void *engine,
                         gpgme_key_t key, gpgme_key_t signing_key,
```

```
                    const char *userid, unsigned int flags);
gpgme_error_t (*tofu_policy)
(void *engine,
                        gpgme_key_t key,
                        gpgme_tofu_policy_t policy);
gpgme_error_t (*sign) (void *engine, gpgme_data_t in, gpgme_data_t out,
  gpgme_sig_mode_t mode, int use_armor,
  int use_textmode, int include_certs,
  gpgme_ctx_t ctx /* FIXME */);
gpgme_error_t (*verify) (void *engine, gpgme_data_t sig,
    gpgme_data_t signed_text, gpgme_data_t plaintext,
                   gpgme_ctx_t ctx);
gpgme_error_t  (*getauditlog) (void *engine, gpgme_data_t output,
                       unsigned int flags);
gpgme_error_t (*setexpire) (void *engine, gpgme_key_t key,
                      unsigned long expires, const char *subfprs,
                      unsigned int reserved);
gpgme_error_t  (*opassuan_transact) (void *engine,
                            const char *command,
                            gpgme_assuan_data_cb_t data_cb,

                    void *data_cb_value,
                            gpgme_assuan_inquire_cb_t inq_cb,
                            void *inq_cb_value,
                            gpgme_assuan_status_cb_t status_cb,
                            void *status_cb_value);

gpgme_error_t  (*conf_load) (void *engine, gpgme_conf_comp_t *conf_p);
gpgme_error_t  (*conf_save) (void *engine, gpgme_conf_comp_t conf);
gpgme_error_t  (*conf_dir) (void *engine, const char *what, char **result);

gpgme_error_t  (*query_swdb) (void *engine,
                        const char *name, const char *iversion,
                        gpgme_query_swdb_result_t result);

void (*set_io_cbs) (void *engine, gpgme_io_cbs_t io_cbs);
void (*io_event) (void *engine, gpgme_event_io_t type, void *type_data);

/* Cancel the whole engine session.  */
gpgme_error_t (*cancel) (void *engine);

/* Cancel only the current operation, not the whole session.
 */
gpgme_error_t (*cancel_op) (void *engine);

/* Change the passphrase for KEY. */
gpgme_error_t (*passwd) (void *engine, gpgme_key_t key, unsigned int flags);
```

```
 /* Set the pinentry mode.  */
 gpgme_error_t (*set_pinentry_mode) (void *engine, gpgme_pinentry_mode_t mode);

 /* The spawn command.  */
 gpgme_error_t (*opspawn) (void * engine,
                           const char *file, const char *argv[],
                           gpgme_data_t datain,
                           gpgme_data_t dataout,
                           gpgme_data_t dataerr, unsigned int flags);

};


extern struct engine_ops _gpgme_engine_ops_gpg;  /* OpenPGP.  */
extern struct engine_ops _gpgme_engine_ops_gpgsm; /* CMS.  */
extern struct engine_ops _gpgme_engine_ops_gpgconf; /* gpg-conf.  */
extern struct engine_ops _gpgme_engine_ops_assuan; /* Low-level Assuan. */
extern struct engine_ops _gpgme_engine_ops_g13;         /* Crypto VFS. */
#ifdef ENABLE_UISERVER
extern struct engine_ops _gpgme_engine_ops_uiserver;
#endif
extern
 struct engine_ops _gpgme_engine_ops_spawn;       /* Spawn engine. */


/* Prototypes for extra functions in engine-gpgconf.c  */
gpgme_error_t _gpgme_conf_arg_new (gpgme_conf_arg_t *arg_p,
                                   gpgme_conf_type_t type, const void *value);
void _gpgme_conf_arg_release (gpgme_conf_arg_t arg, gpgme_conf_type_t type);
gpgme_error_t _gpgme_conf_opt_change (gpgme_conf_opt_t opt, int reset,
        gpgme_conf_arg_t arg);
void _gpgme_conf_release (gpgme_conf_comp_t conf);
gpgme_error_t _gpgme_conf_load (void *engine, gpgme_conf_comp_t *conf_p);



#endif /* ENGINE_BACKEND_H */
/* wkspublishjob.h

  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
```

```
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt
 library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
#ifndef QGPGME_WKSPUBLISHJOB_H
#define QGPGME_WKSPUBLISHJOB_H

#include "job.h"

#include "qgpgme_export.h"

namespace GpgME
{
  class Key;
} // namespace GpgME

namespace QGpgME {

/**
* Handles Web Key Service Publishing. Needs WKS tools installed and
* server support.
*
* Remember that after a result is emitted the job is auto deleted
* so you can only use it for a single action.
*
* The workflow is to call startCreate, check for errors and then
* send the RFC822 mail returned in returnedData.
 *
* When the response is received start a startRecieve with the
* RFC822 mail received as parameter response. Check for errors
* and then send again send the result from returnedData back to
* the server.
```

```
*
*/
class QGPGME_EXPORT WKSPublishJob: public Job
{
  Q_OBJECT
protected:
  explicit WKSPublishJob(QObject *parent);
public:
  ~WKSPublishJob();


  /** Start a check if WKS Publishing is supported. As this involves
   * an HTTP Query it might take a while. Returns GPG_ERR_NOT_SUPPORED
   * result if GnuPG is too old or the required tools are not installed.
   *
   * The error GPG_ERR_NOT_ENABLED indicates that wks-tools failed to
   * detect a working wks service for this.
   *
   * @param the mailbox to check for.
   **/
  virtual void startCheck(const QString &mailbox) = 0;

  /** Create a publish request.
   * The returnedData from the result signal will contain
   * the full Request as returned by gpg-wks-client --create
   *
   * @param
 fpr the fingerprint of the key to create the request for.
   * @param mailbox A simple mail address without a Name.
   */
  virtual void startCreate(const char *fpr, const QString &mailbox) = 0;

  /** Handle a submission response. The returnedData in the result singnal
   * will contain the confirmation response as returned by gpg-wks-client --receive
   *
   * @param response The response of the server.
   **/
  virtual void startReceive(const QByteArray &response) = 0;

Q_SIGNALS:
  /* Result of the operation returned Data and returned Error are
   * the results from gpg-wks-client's stdout or stderr respectively.
   *
   * As usual auditLogAsHtml and auditLogError can be ignored.
   **/
  void result(const GpgME::Error &error, const QByteArray &returnedData,
              const QByteArray &returnedError,
              const QString &auditLogAsHtml = QString(),
```

```
            const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif
/*gpgmepp_export.h - Export macros for gpgmepp
 Copyright (C) 2016, by Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef GPGMEPP_EXPORT_H
#define GPGMEPP_EXPORT_H

#ifdef
 GPGMEPP_STATIC_DEFINE
#  define GPGMEPP_EXPORT
#  define GPGMEPP_NO_EXPORT
#else
#  ifndef GPGMEPP_EXPORT
#    ifdef BUILDING_GPGMEPP
       /* We are building this library */
#      ifdef WIN32
#        define GPGMEPP_EXPORT __declspec(dllexport)
#      else
#        define GPGMEPP_EXPORT __attribute__((visibility("default")))
#      endif
#    else
       /* We are using this library */
#      ifdef WIN32
#        define GPGMEPP_EXPORT __declspec(dllimport)
```

```
#      else
#       define GPGMEPP_EXPORT __attribute__((visibility("default")))
#      endif
#    endif
#  endif

#  ifndef GPGMEPP_NO_EXPORT
#    ifdef WIN32
#     define GPGMEPP_NO_EXPORT
#    else
#     define GPGMEPP_NO_EXPORT __attribute__((visibility("hidden")))
#    endif
#  endif
#endif

#ifndef GPGMEPP_DEPRECATED
#  define GPGMEPP_DEPRECATED __attribute__ ((__deprecated__))
#endif

#ifndef GPGMEPP_DEPRECATED_EXPORT
#  define GPGMEPP_DEPRECATED_EXPORT GPGMEPP_EXPORT GPGMEPP_DEPRECATED
#endif

#ifndef GPGMEPP_DEPRECATED_NO_EXPORT
#
  define GPGMEPP_DEPRECATED_NO_EXPORT GPGMEPP_NO_EXPORT GPGMEPP_DEPRECATED
#endif

#define DEFINE_NO_DEPRECATED 0
#if DEFINE_NO_DEPRECATED
# define GPGMEPP_NO_DEPRECATED
#endif

#endif
/*
 defaultassuantransaction.h - default Assuan Transaction that just stores data and status lines
 Copyright (C) 2009 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
```

```
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston,
 MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_DEFAULTASSUANTRANSACTION_H__
#define __GPGMEPP_DEFAULTASSUANTRANSACTION_H__

#include <interfaces/assuantransaction.h>

#include <string>
#include <vector>
#include <utility>

namespace GpgME
{

class GPGMEPP_EXPORT DefaultAssuanTransaction : public AssuanTransaction
{
public:
  explicit DefaultAssuanTransaction();
  ~DefaultAssuanTransaction();

  const std::vector< std::pair<std::string, std::string> > &statusLines() const
  {
     return m_status;
  }
  std::vector<std::string> statusLine(const char *tag) const;
  std::string firstStatusLine(const char *tag) const;

  const std::string &data() const
  {
     return m_data;
  }

private:
  Error data(const char *data, size_t datalen) override;
  Data inquire(const char *name, const char *args, Error &err) override;
  Error status(const char *status, const char *args) override;

private:
  std::vector< std::pair<std::string, std::string> > m_status;
```

```
  std::string
 m_data;
};

} // namespace GpgME

#endif // __GPGMEPP_DEFAULTASSUANTRANSACTION_H__
/* engine.h - GPGME engine interface.
  Copyright (C) 2000 Werner Koch (dd9jn)
  Copyright (C) 2001, 2002, 2003, 2004, 2010 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef ENGINE_H
#define ENGINE_H

#include "gpgme.h"

/* Flags used by the EXTRAFLAGS arg of _gpgme_engine_op_genkey.
  */
#define GENKEY_EXTRAFLAG_ARMOR      1
#define GENKEY_EXTRAFLAG_REVOKE     2
#define GENKEY_EXTRAFLAG_SETPRIMARY 4



struct engine;
typedef struct engine *engine_t;

typedef gpgme_error_t (*engine_status_handler_t) (void *priv,
       gpgme_status_code_t code,
       char *args);
typedef gpgme_error_t (*engine_colon_line_handler_t) (void *priv, char *line);
typedef gpgme_error_t (*engine_command_handler_t) (void *priv,
```

```
        gpgme_status_code_t code,
        const char *keyword,
        int fd, int *processed);
typedef gpgme_error_t (*engine_assuan_result_cb_t) (void *priv,
                                        gpgme_error_t result);

/* Helper for gpgme_set_global_flag.  */
int _gpgme_set_engine_minimal_version (const char *value);

/* Get a deep copy of the engine info and return it in INFO.  */
gpgme_error_t _gpgme_engine_info_copy (gpgme_engine_info_t *r_info);

/* Release the engine info INFO.  */
void _gpgme_engine_info_release (gpgme_engine_info_t
 info);

/* Set the engine info for the info list INFO, protocol PROTO, to the
  file name FILE_NAME and the home directory HOME_DIR.  */
gpgme_error_t _gpgme_set_engine_info (gpgme_engine_info_t info,
         gpgme_protocol_t praoto,
         const char *file_name,
         const char *home_dir);



gpgme_error_t _gpgme_engine_new (gpgme_engine_info_t info,
    engine_t *r_engine);
gpgme_error_t _gpgme_engine_reset (engine_t engine);

gpgme_error_t _gpgme_engine_set_locale (engine_t engine, int category,
    const char *value);
gpgme_error_t _gpgme_engine_set_protocol (engine_t engine,
      gpgme_protocol_t protocol);
void _gpgme_engine_set_engine_flags (engine_t engine, gpgme_ctx_t ctx);
void _gpgme_engine_release (engine_t engine);
void _gpgme_engine_set_status_cb (engine_t engine,
                          gpgme_status_cb_t cb, void *cb_value);
void _gpgme_engine_set_status_handler (engine_t engine,
          engine_status_handler_t fnc,
          void *fnc_value);
gpgme_error_t
 _gpgme_engine_set_command_handler (engine_t engine,
      engine_command_handler_t fnc,
      void *fnc_value);
gpgme_error_t
_gpgme_engine_set_colon_line_handler (engine_t engine,
         engine_colon_line_handler_t fnc,
         void *fnc_value);
gpgme_error_t _gpgme_engine_op_decrypt (engine_t engine,
```

```
                            gpgme_decrypt_flags_t flags,
                            gpgme_data_t ciph,
    gpgme_data_t plain,
                            int export_session_key,
                            const char *override_session_key,
                            int auto_key_retrieve);
gpgme_error_t _gpgme_engine_op_delete (engine_t engine, gpgme_key_t key,
        unsigned int flags);
gpgme_error_t _gpgme_engine_op_edit (engine_t engine, int type,
       gpgme_key_t key, gpgme_data_t out,
       gpgme_ctx_t ctx /* FIXME */);
gpgme_error_t _gpgme_engine_op_encrypt (engine_t engine,
    gpgme_key_t
 recp[],
                            const char *recpstring,
    gpgme_encrypt_flags_t flags,
    gpgme_data_t plain, gpgme_data_t ciph,
    int use_armor);
gpgme_error_t _gpgme_engine_op_encrypt_sign (engine_t engine,
        gpgme_key_t recp[],
                                const char *recpstring,
        gpgme_encrypt_flags_t flags,
        gpgme_data_t plain,
        gpgme_data_t ciph,
        int use_armor,
        gpgme_ctx_t ctx /* FIXME */);
gpgme_error_t _gpgme_engine_op_export (engine_t engine, const char *pattern,
         gpgme_export_mode_t mode,
         gpgme_data_t keydata, int use_armor);
gpgme_error_t _gpgme_engine_op_export_ext (engine_t engine,
       const char *pattern[],
       gpgme_export_mode_t mode,
       gpgme_data_t keydata,
       int use_armor);
gpgme_error_t _gpgme_engine_op_genkey (engine_t engine,
                            const char *userid, const char *algo,

                      unsigned long reserved,
                            unsigned long expires,
                            gpgme_key_t key, unsigned int flags,
         gpgme_data_t help_data,
         unsigned int extraflags,
                            gpgme_data_t pubkey,
         gpgme_data_t seckey);
gpgme_error_t _gpgme_engine_op_keysign (engine_t engine,
                            gpgme_key_t key, const char *userid,
                            unsigned long expires,
                            unsigned int flags,
```

```
                            gpgme_ctx_t ctx);
gpgme_error_t _gpgme_engine_op_revsig (engine_t engine,
                            gpgme_key_t key,
                            gpgme_key_t signing_key,
                            const char *userid,
                            unsigned int flags);
gpgme_error_t _gpgme_engine_op_tofu_policy
 (engine_t engine,
                                gpgme_key_t key,
                                gpgme_tofu_policy_t policy);
gpgme_error_t _gpgme_engine_op_import (engine_t engine,
          gpgme_data_t keydata,
                            gpgme_key_t *keyarray);
gpgme_error_t _gpgme_engine_op_keylist (engine_t engine,
     const char *pattern,
     int secret_only,
     gpgme_keylist_mode_t mode,
     int engine_flags);
gpgme_error_t _gpgme_engine_op_keylist_ext (engine_t engine,
         const char *pattern[],
         int secret_only,
         int reserved,
         gpgme_keylist_mode_t mode,
         int engine_flags);
gpgme_error_t _gpgme_engine_op_keylist_data (engine_t engine,
          gpgme_data_t data);
gpgme_error_t _gpgme_engine_op_sign (engine_t engine, gpgme_data_t in,
         gpgme_data_t out, gpgme_sig_mode_t mode,
         int use_armor, int use_textmode,
         int include_certs,
         gpgme_ctx_t ctx /* FIXME */);
gpgme_error_t
 _gpgme_engine_op_trustlist (engine_t engine,
       const char *pattern);
gpgme_error_t _gpgme_engine_op_verify (engine_t engine, gpgme_data_t sig,
          gpgme_data_t signed_text,
          gpgme_data_t plaintext,
                            gpgme_ctx_t ctx);

gpgme_error_t _gpgme_engine_op_getauditlog (engine_t engine,
                                gpgme_data_t output,
                                unsigned int flags);
gpgme_error_t _gpgme_engine_op_assuan_transact
              (engine_t engine,
               const char *command,
               gpgme_assuan_data_cb_t data_cb,
               void *data_cb_value,
               gpgme_assuan_inquire_cb_t inq_cb,
```

```
            void *inq_cb_value,
            gpgme_assuan_status_cb_t status_cb,
            void *status_cb_value);

gpgme_error_t _gpgme_engine_op_conf_load (engine_t engine,
      gpgme_conf_comp_t *conf_p);
gpgme_error_t _gpgme_engine_op_conf_save
 (engine_t engine,
      gpgme_conf_comp_t conf);
gpgme_error_t _gpgme_engine_op_conf_dir (engine_t engine,
     const char *what,
     char **result);

gpgme_error_t _gpgme_engine_op_query_swdb (engine_t engine,
                                 const char *name,
                                 const char *iversion,
                                 gpgme_query_swdb_result_t result);


void _gpgme_engine_set_io_cbs (engine_t engine,
        gpgme_io_cbs_t io_cbs);
void _gpgme_engine_io_event (engine_t engine,
       gpgme_event_io_t type, void *type_data);

gpgme_error_t _gpgme_engine_cancel (engine_t engine);

gpgme_error_t _gpgme_engine_cancel_op (engine_t engine);

gpgme_error_t _gpgme_engine_op_passwd (engine_t engine, gpgme_key_t key,
                             unsigned int flags);

gpgme_error_t _gpgme_engine_set_pinentry_mode (engine_t engine,
                                   gpgme_pinentry_mode_t mode);

gpgme_error_t
 _gpgme_engine_op_spawn (engine_t engine,
                         const char *file, const char *argv[],
                         gpgme_data_t datain,
                         gpgme_data_t dataout,
                         gpgme_data_t dataerr,
                         unsigned int flags);
gpgme_error_t _gpgme_engine_op_setexpire (engine_t engine,
                              gpgme_key_t key,
                              unsigned long expires,
                              const char *subfprs,
                              unsigned int reserved);

/* The available engine option flags.  */
```

```
#define GPGME_ENGINE_FLAG_OFFLINE       1


#endif /* ENGINE_H */
/*
 vfsmountresult.h - wraps a gpgme vfs mount result
 Copyright (C) 2009 Klarlvdalens Datakonsult AB <info@kdab.com>
 Author: Marc Mutz <marc@kdab.com>, Volker Krause <volker@kdab.com>

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_VFSMOUNTRESULT_H__
#define
 __GPGMEPP_VFSMOUNTRESULT_H__

#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <memory>

#include <vector>
#include <iosfwd>

namespace GpgME
{

class Error;

class GPGMEPP_EXPORT VfsMountResult : public Result
{
public:
```

```
  VfsMountResult();
  VfsMountResult(gpgme_ctx_t ctx, const Error &error, const Error &opError);
  explicit VfsMountResult(const Error &err);

  const VfsMountResult &operator=(VfsMountResult other)
  {
     swap(other);
     return *this;
  }

  void swap(VfsMountResult &other)
  {
     Result::swap(other);
     using std::swap;
     swap(this->d, other.d);
  }

  bool isNull() const;
  const char *mountDir() const;

  class Private;
private:
  void init(gpgme_ctx_t ctx);
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const VfsMountResult &result);

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(VfsMountResult)

#endif // __GPGMEPP_VFSMOUNTRESULT_H__
/*
 keylistresult.h - wraps a gpgme keylist result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
```

```
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_KEYLISTRESULT_H__
#define
 __GPGMEPP_KEYLISTRESULT_H__

#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <memory>

namespace GpgME
{

class Error;

class GPGMEPP_EXPORT KeyListResult : public Result
{
public:
  KeyListResult();
  KeyListResult(gpgme_ctx_t ctx, int error);
  KeyListResult(gpgme_ctx_t ctx, const Error &error);
  explicit KeyListResult(const Error &err);
  KeyListResult(const Error &err, const _gpgme_op_keylist_result &res);

  const KeyListResult &operator=(KeyListResult other)
  {
     swap(other);
     return *this;
  }
  void swap(KeyListResult &other)
  {
     Result::swap(other);
     using std::swap;
     swap(this->d, other.d);
  }

  const KeyListResult &operator+=(const KeyListResult &other)
  {
     mergeWith(other);
```

```
    return *this;
  }

  void mergeWith(const KeyListResult &other);

  bool isNull() const;

  bool isTruncated() const;

private:
  void detach();
  void init(gpgme_ctx_t
 ctx);
  class Private;
  std::shared_ptr<Private> d;
};

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(KeyListResult)

#endif // __GPGMEPP_KEYLISTRESULT_H__
#include "qgpgme/keygenerationjob.h"
from __future__ import absolute_import

import cython
import gpg

c = gpg.Context()
seckeys = c.keylist(pattern=None, secret=True)
pubkeys = c.keylist(pattern=None, secret=False)

seclist = list(seckeys)
secnum = len(seclist)

publist = list(pubkeys)
pubnum = len(publist)

if cython.compiled is True:
  cc = "Powered by Cython compiled C code."
else:
  cc = "Powered by Python."

print("""
  Number of secret keys:  {0}
  Number of public keys:  {1}

 {2}
```

""".format(secnum, pubnum, cc))
/*
  exportjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two. You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt. If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so. If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_EXPORTJOB_H__
#define __QGPGME_EXPORTJOB_H__

#include "qgpgme_export.h"
#include "job.h"

#include <QtCore/QByteArray>

namespace GpgME
{
class Error;
}

```
class QStringList;

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous exporters

  To use a ExportJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
   signals to suitable slots and then start the export with a call
  to start(). This call might fail, in which case the ExportJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the ExportJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT ExportJob : public Job
{
   Q_OBJECT
protected:
   explicit ExportJob(QObject *parent);
public:
   ~ExportJob();

   /**
      Starts the export operation. \a patterns is a list of patterns
      used to restrict the list of keys exported. Empty patterns are
      ignored. If \a patterns is empty or contains only empty
      strings, all available keys are exported.
   */
   virtual GpgME::Error start(const QStringList &patterns) = 0;

   virtual void setExportFlags (unsigned int flags);

Q_SIGNALS:
   void result(const GpgME::Error &result, const QByteArray &keyData, const QString &auditLogAsHtml =
QString(),
 const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif // __QGPGME_EXPORTJOB_H__
/*
* Copyright (C) 2016 g10 Code GmbH
```

```
*
* This file is part of GPGME.
*
* GPGME is free software; you can redistribute it and/or modify it
* under the terms of the GNU Lesser General Public License as
* published by the Free Software Foundation; either version 2.1 of
* the License, or (at your option) any later version.
*
* GPGME is distributed in the hope that it will be useful, but
* WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
* Lesser General Public License for more details.
*
* You should have received a copy of the GNU Lesser General Public
* License along with this program; if not, see <https://www.gnu.org/licenses/>.
*/

#include <gpgme.h>

#ifndef _GPG_PRIVATE_H_
#define _GPG_PRIVATE_H_

/* GPGME glue.  Implemented in helpers.c.  */

void _gpg_exception_init(void);
gpgme_error_t _gpg_exception2code(void);

PyObject *_gpg_obj2gpgme_t(PyObject *input, const char *objtype, int argnum);
PyObject
 *_gpg_obj2gpgme_data_t(PyObject *input, int argnum,
    gpgme_data_t *wrapper,
    PyObject **bytesio, Py_buffer *view);

PyObject *_gpg_wrap_result(PyObject *fragile, const char *classname);

gpgme_error_t _gpg_interact_cb(void *opaque, const char *keyword,
   const char *args, int fd);
gpgme_error_t _gpg_assuan_data_cb (void *hook,
       const void *data, size_t datalen);
gpgme_error_t _gpg_assuan_inquire_cb (void *hook,
         const char *name, const char *args,
         gpgme_data_t *r_data);
gpgme_error_t _gpg_assuan_status_cb (void *hook,
        const char *status, const char *args);



/* SWIG runtime support.  Implemented in gpgme.i.  */
```

```
PyObject *_gpg_wrap_gpgme_data_t(gpgme_data_t data);
gpgme_ctx_t _gpg_unwrap_gpgme_ctx_t(PyObject *wrapped);

#endif /* _GPG_PRIVATE_H_ */
/*
 configuration.h - wraps gpgme configuration components
 Copyright (C) 2010 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef
 __GPGMEPP_CONFIGURATION_H__
#define __GPGMEPP_CONFIGURATION_H__

#include "global.h"

#include "gpgmefw.h"

#include <iosfwd>
#include <vector>
#include <string>
#include <algorithm>
#include <memory>

namespace GpgME
{
namespace Configuration
{
```

```
typedef std::shared_ptr< std::remove_pointer<gpgme_conf_comp_t>::type > shared_gpgme_conf_comp_t;
typedef std::weak_ptr< std::remove_pointer<gpgme_conf_comp_t>::type > weak_gpgme_conf_comp_t;

class Argument;
class Option;
class Component;

enum Level {
  Basic,
  Advanced,
  Expert,
  Invisible,
  Internal,

  NumLevels
};

enum Type {
  NoType,
  StringType,
  IntegerType,
  UnsignedIntegerType,

  FilenameType = 32,
  LdapServerType,
  KeyFingerprintType,
  PublicKeyType,
  SecretKeyType,
  AliasListType,

  MaxType
};

enum Flag {
  Group    = (1 << 0),
  Optional = (1 << 1),
  List     = (1 << 2),
  Runtime  = (1 << 3),
  Default  = (1 << 4),
  DefaultDescription = (1 << 5),
  NoArgumentDescription
 = (1 << 6),
  NoChange = (1 << 7),

  LastFlag = NoChange
};
```

```
//
// class Component
//

class GPGMEPP_EXPORT Component
{
public:
  Component() : comp() {}
  explicit Component(const shared_gpgme_conf_comp_t &gpgme_comp)
     : comp(gpgme_comp) {}

  // copy ctor is ok

  const Component &operator=(const Component &other)
  {
     if (this != &other) {
        Component(other).swap(*this);
     }
     return *this;
  }

  void swap(Component &other)
  {
     using std::swap;
     swap(this->comp, other.comp);
  }

  bool isNull() const
  {
     return !comp;
  }

  static std::vector<Component> load(Error &err);
  Error save() const;

  const char *name() const;
  const char *description() const;
  const char *programName() const;

  Option option(unsigned int index) const;
  Option option(const char *name) const;

  unsigned int numOptions() const;

  std::vector<Option> options() const;

  GPGMEPP_MAKE_SAFE_BOOL_OPERATOR(!isNull())
private:
```

```
    shared_gpgme_conf_comp_t comp;
};

//
// class Option
//

class GPGMEPP_EXPORT Option
{
public:
  Option() : comp(), opt(nullptr) {}
  Option(const shared_gpgme_conf_comp_t &gpgme_comp, gpgme_conf_opt_t gpgme_opt)
      : comp(gpgme_comp), opt(gpgme_opt) {}

  const Option &operator=(const Option &other)
  {
      if (this != &other) {
          Option(other).swap(*this);
      }
      return *this;
  }

  void swap(Option &other)
  {
      using std::swap;
      swap(this->comp, other.comp);
      swap(this->opt,  other.opt);
  }

  bool isNull() const
  {
      return comp.expired() || !opt;
  }

  Component parent() const;

  unsigned int flags() const;

  Level level() const;

  const char *name() const;
  const char *description() const;
  const char *argumentName() const;

  Type type() const;
  Type alternateType() const;

  Argument defaultValue() const;
```

```
  const char *defaultDescription()
 const;

  Argument noArgumentValue() const;
  const char *noArgumentDescription() const;

  /*! The value that is in the config file (or null, if it's not set). */
  Argument activeValue() const;
  /*! The value that is in this object, ie. either activeValue(), newValue(), or defaultValue() */
  Argument currentValue() const;

  Argument newValue() const;
  bool set() const;
  bool dirty() const;

  Error setNewValue(const Argument &argument);
  Error resetToDefaultValue();
  Error resetToActiveValue();

  Argument createNoneArgument(bool set) const;
  Argument createStringArgument(const char *value) const;
  Argument createStringArgument(const std::string &value) const;
  Argument createIntArgument(int value) const;
  Argument createUIntArgument(unsigned int value) const;

  Argument createNoneListArgument(unsigned int count) const;
  Argument createStringListArgument(const std::vector<const char *> &value) const;
  Argument
 createStringListArgument(const std::vector<std::string> &value) const;
  Argument createIntListArgument(const std::vector<int> &values) const;
  Argument createUIntListArgument(const std::vector<unsigned int> &values) const;

  GPGMEPP_MAKE_SAFE_BOOL_OPERATOR(!isNull())
private:
  weak_gpgme_conf_comp_t  comp;
  gpgme_conf_opt_t opt;
};

//
// class Argument
//

class GPGMEPP_EXPORT Argument
{
  friend class ::GpgME::Configuration::Option;
  Argument(const shared_gpgme_conf_comp_t &comp, gpgme_conf_opt_t opt, gpgme_conf_arg_t arg, bool owns);
public:
  Argument() : comp(), opt(nullptr), arg(nullptr) {}
```

```
  //Argument( const shared_gpgme_conf_comp_t & comp, gpgme_conf_opt_t opt, gpgme_conf_arg_t arg );
  Argument(const Argument &other);
  ~Argument();

  const Argument &operator=(const Argument &other)
  {
     if (this != &other) {
        Argument(other).swap(*this);
     }
     return *this;
  }

  void swap(Argument &other)
  {
     using
 std::swap;
     swap(this->comp, other.comp);
     swap(this->opt,  other.opt);
     swap(this->arg,  other.arg);
  }

  bool isNull() const
  {
     return comp.expired() || !opt || !arg;
  }

  Option parent() const;

  unsigned int numElements() const;

  bool boolValue() const;
  const char *stringValue(unsigned int index = 0) const;
  int         intValue(unsigned int index = 0) const;
  unsigned int uintValue(unsigned int index = 0) const;

  unsigned int numberOfTimesSet() const;
  std::vector<const char *> stringValues() const;
  std::vector<int>          intValues() const;
  std::vector<unsigned int> uintValues() const;

  GPGMEPP_MAKE_SAFE_BOOL_OPERATOR(!isNull())
private:
  weak_gpgme_conf_comp_t comp;
  gpgme_conf_opt_t opt;
  gpgme_conf_arg_t arg;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Level level);
```

```
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Type type);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream
 &os, Flag flag);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Component &component);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Option &option);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Argument &argument);

} // namespace Configuration
} // namespace GpgME

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Configuration::Component)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Configuration::Option)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Configuration::Argument)

#endif // __GPGMEPP_CONFIGURATION_H__
{
  "dec_info":    {
     "symkey_algo":  "TWOFISH.CFB",
     "wrong_key_usage":     false,
     "is_de_vs":    false,
     "is_mime":     false,
     "legacy_cipher_nomdc":  false,
     "recipients":   [{
        "keyid":       "6AE6D7EE46A871F8",
        "pubkey_algo_name":    "ELG-E",
        "status_string":       "Success",
        "status_code":  0
     }]
  },
  "info": {
     "is_mime":     false,
     "signatures":   [{
        "summary":     {
           "sigsum":      [],
           "valid":       false,
           "green":       false,
           "red":  false,
           "revoked":     false,
           "key-expired":  false,
           "sig-expired":  false,
           "key-missing":  false,
           "crl-missing":  false,
           "crl-too-old":  false,
           "bad-policy":   false,
           "sys-error":    false
        },
```

```
  "wrong_key_usage":      false,
        "chain_model":  false,
        "is_de_vs":     false,
        "status_string":        "Success",
        "fingerprint":  "A0FF4590BB6122EDEF6E3C542D727CC768697734",
        "validity_string":      "unknown",
        "pubkey_algo_name":     "DSA",
        "hash_algo_name":       "RIPEMD160",
        "status_code":  0,
        "timestamp":    1542200353,
        "exp_timestamp":        0,
        "pka_trust":    0,
        "validity":     0,
        "validity_reason":      0
     }]
  },
  "type": "plaintext",
  "base64":       false,
  "data": "Hello world"
}
-----BEGIN PGP PUBLIC KEY BLOCK-----

mQENBFsMHecBCACqdJgqa+CeNYwPCK+MpOwAV6uFVjDyO2LmOs6+XfDWRBU/Zjtz
8zdYNKSbLjkWN4ujV5aiyA7MtEofszzYLEoKUt1wiDScHMpW8qmEFDvl9g26MeAV
rTno9D5KodHvEIs8wnrqBs8ix0WLbh6J1Dtt8HQgIbN+v3gaRQrgBFe6z2ZYpHHx
ZfOu3iFKlm2WE/NekRkvvFIo3ApGvRhGIYw6JMmugBlo7s5xosJK0I9dkPGlEEtt
aF1RkcMj8sWG9vHAXcjlGgFfXSN9YLppydXpkuZGm4+gjLB2a3rbQCZVFnxCyG4O
ybjkP8Jw6Udm89bK2ucYFfjdrmYn/nJqRxeNABEBAAG0I1Rlc3QgTm9Qcml2S2V5
IDxub2JvZHlAZXhhbXBsZS5vcmc+iQFOBBMBCAA4FiEE4Fmh4IZtMa4TEXCITZou
EzBBU9EFAlsMHecCGwMFCwkIBwIGFQoJCAsCBBYCAwECHgECF4AACgkQTZouEzBB
U9F+qwf/SHj4uRnTWgyJ71FBxQDYCBq3jbi6e7hMkRPbJyJdnPIMAb2p0PJjBgjW
0pp4+kDPZans3UDHbma1u/SFI4/y6isJiK94Bk5xp5YliLGnUceTjgDFe6lBhfQ1
zVWZC/NF3tPgbziIxXQTNt34nS+9dbV/QFDLW0POcN7C0jR/hgkBjMEH2PezWhSj
mL/yLfLfUYAoxVpXjfC5aPJKqw0tR7m5ibznjCphE+FUMRg8EOmJcg6soeJ5QspU
k2dPN3+Y0zCTNRgAHEI+yIQbM6pio6v2c+UCtT1QhW4xSI38/kcEG8QiM55r1TUy
FcWAY5n5t1nNZtMxxse3LqEon3rKiLkBDQRbDB3nAQgAqfAjSjcngERtM+ZYOwN0
QF2v2FuEuMe8mhju7Met7SN2zGv1LnjhTNshEa9IABEfjZirE2Tqx4xCWDwDedK4
u1ToFvcnuAMnq2O47Sh+eTypsf6WPFtPBWf6ctKY31hFXjgoyDBULBvl43XU/D9C
Mt7nsKDPYHVrrnge/qWPYVcb+cO0sSwNImMcwQSdTQ3VBq7MeNS9ZeBcXi+XCjhN
kjNum2AQqpkHHDQV7871yQ8RIILvZSSfkLb0/SNDU+bGaw2G3lcyKdIfZi2EWWZT
oCbH38I/+LV7nAEe4zFpHwW8X0Dkx2aLgxe6UszDH9L3eGhTLpJhOSiaanG+zZKm
+QARAQABiQE2BBgBCAAgFiEE4Fmh4IZtMa4TEXCITZouEzBBU9EFAlsMHecCGwwA
CgkQTZouEzBBU9H5TQgAolWvIsez/WW8N2tmZEnX0LOFNB+1S4L4X983njwNdoVI
w19pbj+8RIHF/H9kcPGi7jK96gvlykQn3uez/95D2AiRFW5KYdOouFisKgHpv8Ay
BrhclHv11yK+X/0iTD0scYaG7np5162xLkaxSO9hsz2fGv20RKaXCWkI69fWw0BR
XlI5pZh2YFei2ZhH/tIMIW65h3w0gtgaZBBdpZTOOW4zvghyN+0MSObqkI1BvUJu
caDFI4d6ZTmp5SY+pZyktZ4bg/vMH5VFxdIKgbLx9uVeTvOupvbAW0TNulYGUBQE
nm+S0zr3W18t64e4sS3oHse8zCqo1iiImpba6F1Oaw==
```

```
=y6DD
-----END
 PGP PUBLIC KEY BLOCK-----
/*
   gpgcardjob.h

   This file is part of qgpgme, the Qt API binding for gpgme
   Copyright (c) 2020 g10 Code GmbH

   QGpgME is free software; you can redistribute it and/or
   modify it under the terms of the GNU General Public License as
   published by the Free Software Foundation; either version 2 of the
   License, or (at your option) any later version.

   QGpgME is distributed in the hope that it will be useful,
   but WITHOUT ANY WARRANTY; without even the implied warranty of
   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
   General Public License for more details.

   You should have received a copy of the GNU General Public License
   along with this program; if not, write to the Free Software
   Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a special exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech
 AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/
#ifndef __KLEO_GPGCARDJOB_H__
#define __KLEO_GPGCARDJOB_H__

#include <QStringList>

#include "job.h"

namespace GpgME
{
class Error;
}

namespace QGpgME
```

```
{

/**
  @short Get the best key to use for a Mailbox

  To use the keyformailboxjob, first obtain an instance from the
  CryptoBackend and either exec it or start and
  conncet the result() signals to a suitable slot.
  The job will be automatically deleted in which
  case the KeylistJob instance will have schedules it's own
  destruction with a call to QObject::deleteLater().

   The best key is defined as the key with a UID that has an
  E-Mail that matches the mailbox provided. If multiple
  keys are found the one with the highest validity is returned.

  After result() is emitted, the
  KeyListJob will schedule it's own destruction by calling
  QObject::deleteLater().
*/
class QGPGME_EXPORT GpgCardJob: public Job
{
  Q_OBJECT
protected:
  explicit GpgCardJob(QObject *parent);

public:
  ~GpgCardJob();

  /**
    Starts the operation. \a cmds are the commands to
    execute.
  */
  virtual GpgME::Error start(const QStringList &cmds) = 0;

  virtual GpgME::Error exec(const QStringList &cmds, QString &std_out, QString &std_err, int &exitCode) = 0;

Q_SIGNALS:
  /** The resulting stdout and stderr of gpgcard and the exitCode
   *
   * The auditlog params are always null / empty.
   */
  void result(const QString &std_out, const QString &std_err, int exitCode,
              const QString &auditLogAsHtml = QString(),
 const GpgME::Error &auditLogError = GpgME::Error());
};

}
```

#endif
-*- mode: org -*-
#+TITLE: A Short History of the GPGME bindings for Python
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}

* Overview
 :PROPERTIES:
 :CUSTOM_ID: overview
 :END:

Version:	0.0.1
GPGME Version:	1.13.0
Author:	Ben McGinnes <ben@gnupg.org>
Author GPG Key:	DB4724E6FA4286C92B4E55C4321E4E2373590E5D
Language:	Australian English, British English
xml:lang:	en-AU, en-GB, en

The GPGME Python bindings passed through many hands and numerous
phases before, after a fifteen year journey, coming full circle to
return to the source. This is a short explanation of that journey.

** In the beginning
  :PROPERTIES:
  :CUSTOM_ID: in-the-begining
   :END:

  In 2002 John Goerzen released PyME; Python bindings for the GPGME
  module which utilised the current release of Python of the time and
  SWIG.[fn:1] Shortly after creating it and ensuring it worked he stopped
  supporting it, though he left his work available on his Gopher
  site.

** Keeping the flame alive
  :PROPERTIES:
  :CUSTOM_ID: keeping-the-flame-alive
  :END:

  A couple of years later the project was picked up by Igor Belyi and
  actively developed and maintained by him from 2004 to 2008. Igor's
  whereabouts at the time of this document's creation are unknown,
  but the current authors do hope he is well. We're assuming (or
  hoping) that life did what life does and made continuing untenable.

** Passing the torch
:PROPERTIES:
:CUSTOM_ID: passing-the-torch
:END:

In 2014 Martin Albrecht wanted to patch a bug in the PyME code and discovered the absence of Igor. Following a discussion on the PyME mailing list he
became the new maintainer for PyME, releasing
version 0.9.0 in May of that year. He remains the maintainer of the original PyME release in Python 2.6 and 2.7 (available via PyPI).

** Coming full circle
:PROPERTIES:
:CUSTOM_ID: ouroboros
:END:

In 2015 Ben McGinnes approached Martin about a Python 3 version, while investigating how complex a task this would be the task ended up being completed. A subsequent discussion with Werner Koch led to the decision to fold the Python 3 port back into the original GPGME release in the languages subdirectory for non-C bindings under the module name of =pyme3=.

In 2016 this PyME module was integrated back into the GPGME project by Justus Winter. During the course of this work Justus adjusted the port to restore limited support for Python 2, but not as many minor point releases as the original PyME package supports. During the course of this integration the package was renamed to more accurately
reflect its status as a component of GPGME. The =pyme3= module was renamed to =gpg= and adopted by the upstream GnuPG team.

In 2017 Justus departed G10code and the GnuPG team. Following this Ben returned to maintain of gpgme Python bindings and continue building them from that point.

* Relics of the past
:PROPERTIES:
:CUSTOM_ID: relics-past
:END:

There are a few things, in addition to code specific factors, such as

SWIG itself, which are worth noting here.

** The Annoyances of Git
:PROPERTIES:
:CUSTOM_ID: the-annoyances-of-git
:END:

As anyone who has ever worked with git knows, submodules are horrible way to deal with pretty much anything. In the interests of avoiding migraines, that was skipped with addition of the PyME code to GPGME.

Instead the files were added to a subdirectory of the =lang/= directory, along with a copy of the entire git log up to that point as a separate file within the =lang/python/docs/= directory.[fn:2] As the log for PyME is nearly 100KB and the log for GPGME is approximately 1MB, this would cause considerable bloat, as well as some confusion, should the two be merged.

Hence the unfortunate, but necessary, step to simply move the files. A regular repository version has been maintained should it be possible to implement this better in the future.

** The Perils of PyPI
:PROPERTIES:
:CUSTOM_ID: the-perils-of-pypi
:END:

The early port of the Python 2 =pyme= module as =pyme3= was never added to PyPI while the focus remained on development and testing during 2015 and early 2016. Later in 2016, however, when Justus completed his major integration work and subsequently renamed the module from =pyme3= to =gpg=, some prior releases were also provided through PyPI.

Since these bindings require a matching release of the GPGME libraries in order to function, it was determined that there was little benefit in also providing a copy
through PyPI since anyone
obtaining the GPGME source code would obtain the Python bindings source code at the same time. Whereas there was the potential to sew confusion amongst Python users installing the module from PyPI, only to discover that without the relevant C files, header files or SWIG compiled binaries, the Python module did them little good.

There are only two files on PyPI which might turn up in a search for this module or a sample of its content:

1. gpg (1.8.0) - Python bindings for GPGME GnuPG cryptography library
2. pyme (0.9.0) - Python support for GPGME GnuPG cryptography library

*** GPG 180 - Python bindings for GPGME GnuPG cryptography library
:PROPERTIES:
:CUSTOM_ID: pypi-gpgme-180
:END:

This is the most recent version to reach PyPI and is the version of the official Pyhon bindings which shipped with GPGME 1.8.0. If you have GPGME 1.8.0 installed and /only/ 1.8.0 installed, then it is probably safe to use this copy from PyPI.

As there have been a lot of changes since the release of GPGME 1.8.0, the GnuPG Project recommends not using this version of the module and instead installing the current version of GPGME along with the Python bindings included with that package.

*** PyME 090 - Python support for GPGME GnuPG cryptography library
:PROPERTIES:
:CUSTOM_ID: pypi-gpgme-90
:END:

This is the last release of the PyME bindings maintained by Martin Albrecht and is only compatible with Python 2, it will not work with Python 3. This is the version of the software from which the port from Python 2 to Python 3 code was made in 2015.

Users of the more recent Python bindings will recognise numerous points of similarity, but also significant differences. It is likely that the more recent official bindings will feel "more pythonic."

For those using Python 2, there is essentially no harm in using this module, but it may lack a number of more recent features added to GPGME.

* Footnotes

[fn:1] In all likelihood this would have been Python 2.2 or possibly Python 2.3.

[fn:2] The entire PyME git log and other preceding VCS logs are

located in the =gpgme/lang/python/docs/old-commits.log= file.
#include "qgpgme/debug.h"
#include "qgpgme/keylistjob.h"
1.15.1
000
 *H
010 UDE1!0U
Deutsches Forschungsnetz10UDFN-PCA1.0,U%DFN Top Level Certification Authority1!0 *H
 certify@pca.dfn.de0
981029180310Z
011231180310Z010 UDE1!0U
Deutsches Forschungsnetz10UDFN-PCA1.0,U%DFN Top Level Certification Authority1!0 *H
 certify@pca.dfn.de0"0
 *H
0
nskvS2r#iA4H|*/
:Sd;v
tD}L+~IWWD|eP&qH)
!1\p%,1.tIsmnQ,g-W)@\(t<kvm5j(d)9M_KGQJ0:qTE 00 `HB0) `HBhttps://mystic.pca.dfn.de/0A
`HB42http://www.pca.dfn.de/dfnpca/policy/wwwpolicy.html08 `HB
+)The DFN Top Level Certification Authority0! `HBcgi/check-rev.cgi?0 `HB
dfnpca.crl0U00U0
 *H
`^[:8\e7*%QC?:/JVgwPUB
OgGqjGVxl50%<`Pb18 z;t~r0U<A%3#l'8b"<iX"V!k"*Q8&hAPI"3 00KUb&Qq'46_{D[JZ!i<=T
/OF

```
{
  "info": {
    "is_mime":     false,
    "signatures":  [{
      "summary":     {
        "sigsum":      [],
        "valid":       false,
        "green":       false,
        "red":  false,
        "revoked":     false,
        "key-expired":  false,
        "sig-expired":  false,
        "key-missing":  false,
        "crl-missing":  false,
        "crl-too-old":  false,
        "bad-policy":   false,
        "sys-error":    false
      },
      "wrong_key_usage":     false,
      "chain_model":  false,
      "is_de_vs":     false,
      "status_string":       "Success",
```

```
        "fingerprint":  "A0FF4590BB6122EDEF6E3C542D727CC768697734",
        "validity_string":      "unknown",
        "pubkey_algo_name":     "DSA",
        "hash_algo_name":       "SHA1",
        "status_code":  0,
        "timestamp":    1542201053,
         "exp_timestamp":        0,
        "pka_trust":    0,
        "validity":     0,
        "validity_reason":      0
      }]
  }
}
#include "qgpgme/changeownertrustjob.h"
/*
  signkeyjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
```

```
#ifndef __KLEO_SIGNKEYJOB_H__
#define __KLEO_SIGNKEYJOB_H__

#include "job.h"

#include <vector>

namespace GpgME
{
class Error;
class Key;
}

class QString;

namespace QGpgME
{

/**
  @short An abstract base class to sign keys asynchronously

  To use a SignKeyJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable
 slots and then start the job with a call
  to start(). This call might fail, in which case the ChangeExpiryJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the SignKeyJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT SignKeyJob : public Job
{
   Q_OBJECT
protected:
   explicit SignKeyJob(QObject *parent);
public:
   ~SignKeyJob();

   /**
      Starts the key signing operation. \a key is the key to sign.
      @param keyToSign the key to be signed
      @param idsToSign the user IDs to sign
      @param signingKey the secret key to use for signing
      @param option the signing mode, either local or exportable
    */
```

```
  virtual GpgME::Error start(const GpgME::Key &keyToSign) = 0;

  /**
   * If explicitly specified, only the listed user IDs will be signed. Otherwise all user IDs
   * are signed.
   * @param list of user ID indexes (of the
key to be signed).
   */
  virtual void setUserIDsToSign(const std::vector<unsigned int> &idsToSign) = 0;

  /**
   * sets the check level
   * @param the check level, ranges from 0 (no claim) and 3 (extensively checked),
   * default is 0
   */
  virtual void setCheckLevel(unsigned int checkLevel) = 0;

  /**
   * sets whether the signature should be exportable, or local only.
   * default is local.
   */
  virtual void setExportable(bool exportable) = 0;

  /**
   * sets an alternate signing key
   */
  virtual void setSigningKey(const GpgME::Key &key) = 0;

  /**
   * if set, the created signature won't be revocable. By default signatures
   * can be revoked.
   */
  virtual void setNonRevocable(bool nonRevocable) = 0;

  /**
   * Set this if it is ok to overwrite an existing signature. In that
   * case the context has to have the flag "extended-edit" set to 1 through
   * Context::setFlag before calling edit.
   *
   * Not
pure virtual for ABI compatibility.
   **/
  virtual void setDupeOk(bool) {};

  /**
   * Add a remark to the signature. This uses rem@gnupg.org as a notation.
   *
   * Not pure virtual for ABI compatibility.
```

```
   **/
  virtual void setRemark(const QString &) {};

Q_SIGNALS:
  void result(const GpgME::Error &result, const QString &auditLogAsHtml = QString(), const GpgME::Error
&auditLogError = GpgME::Error());
};

}

#endif // __KLEO_SIGNKEYJOB_H__
# -*- mode: org -*-
#+TITLE: Maintenance Mode
#+AUTHOR: Ben McGinnes
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}
#+LATEX_HEADER: \author{Ben McGinnes <ben@gnupg.org>}


* Maintenance Mode from 2019
 :PROPERTIES:
 :CUSTOM_ID: maintenance-mode
 :END:

| Version:        | 0.0.1                                |
| GPGME Version:  | 1.13.0                               |
| Author:         | Ben McGinnes <ben@gnupg.org>         |
| Author GPG Key: | DB4724E6FA4286C92B4E55C4321E4E2373590E5D |
| Language:       | Australian English, British English  |
| xml:lang:       | en-AU, en-GB, en                     |

From the beginning of 2019 the Python bindings to GPGME will enter
maintenance mode, meaning that new features will not be added and only
bug fixes and security fixes will be made.
  This also means that
documentation beyond that existing at the end of 2018 will not be
developed further except to correct errors.

Though use of these bindings appears to have been quite well received,
there has been no indication of what demand there is, if any for
either financial backing of the current Python bindings development or
support contracts with g10code GmbH citing the necessity of including
the bindings.
```

** Maintainer from 2019 onward
:PROPERTIES:
:CUSTOM_ID: maintenance-mode-bm
:END:

How does this affect the position of GnuPG Python Bindings Maintainer?

Well, I will remain as maintainer of the bindings; but without funding
for that position, the amount of time I will be able to dedicate
solely to this task will be limited and reduced to volunteered time.
As with all volunteered time and effort in free software projects,
this will be subject to numerous external imperatives.

** Using the Python Bindings from 2019 and beyond
:PROPERTIES:
:CUSTOM_ID:
maintenance-mode-blade-runner
:END:

For most, if not all, Python developers using these bindings; they
will continue to just work the same as they always have. Expansions
of GPGME itself are usually handled by SWIG with the existing code and
thus bindings are generated properly when the bindings are installed
alongside GPGME and when the latter is built from source.

In the rare circumstances where that is not enough to address some new
addition to GPGME, then that is a bug and thus subject to the
maintenance mode provisions (i.e. it will be fixed following a bug
report being raised and your humble author will need to remember where
the timesheet template was filed, depending on how many years off such
an event is).

All the GPGME functionality will continue to be accessible via the
lower level, dynamically generated methods which match the GPGME C
documentation. While the more intuitively Pythonic higher level layer
already covers the vast majority of functionality people require
with
key generation, signatures, certifications (key signing), encryption,
decryption, verification, validation, trust levels and so on.

Any wanted features lacking in the Python bindings are usually lacking
because they are missing from GPGME itself (e.g. revoking keys via the
API) and in such cases they are usually deliberately excluded. More
discussion of these issues can be found in the archives of the
[[https://lists.gnupg.org/mailman/listinfo/gnupg-devel][gnupg-devel mailing list]].

Any features existing in the dynamically generated layer for which
people want a specific, higher level function included to make it more
Pythonic (e.g. to avoid needing to learn or memorise cryptographic
mode values or GnuPG status code numbers), would be a feature request
and /not/ a bug.

It is still worthwhile requesting it, but the addition of such a
feature would not be guaranteed and provided on a purely volunteer
basis. Expediting such a request would require funding that request.

Those
 with a commercial interest in expediting such a feature request
already know how to [[https://gnupg.org/cgi-bin/procdonate.cgi?mode=preset][expedite it]] (use the message field to state what
feature is being requested).

** Documentation formats
 :PROPERTIES:
 :CUSTOM_ID: docs
 :END:

The documentation has been written in Org mode for GNU Emacs, with
both Texinfo and reStructuredText formats generated from that. The
Texinfo files are intended for use with the rest of the GnuPG
documentation; while the reStructuredText files are intended for use
with Docutils and Sphinx, as with other Python projects.

*** Cautionary Notes regarding Sphinx and EPUB
  :PROPERTIES:
  :CUSTOM_ID: sphinx-made-epubs-suck
  :END:

Though Python's Docutils in conjunction with Sphinx is capable of
generating some very useful HTML sites, as proven by [[https://readthedocs.org/][Read the Docs]] and
the [[https://docs.python.org/][Python documentation]], there are a number of output formats it does not
 handle well. At the top of the list of things it manages to break
so atrociously as to be embarassing is the [[http://idpf.org/epub][EPUB 3]] format.

The automatically generated EPUB of the CPython documentation always
contains hundreds of validation errors and even the modest amount of
documentation here [[https://files.au.adversary.org.s3.amazonaws.com/crypto/gpgme-python/rst/epub/GPGMEPythonBindings.epub][produced a file]] with approximately thirty
validation errors. As the volume of documentation content increases,
so does the induced errors. Whereas Texinfo doesn't produce EPUB
output at all, nor does Org-mode.

Should there ever be genuine demand for this format, lodge a
[[https://dev.gnupg.org/maniphest/task/edit/form/4/][feature
request]] case marked for [[https://dev.gnupg.org/p/BenM/][my]] attention. The means of generating such files flawlessly is already available, but is not yet part of the
GnuPG build system. Nor is it integrated with a means of converting
Org
 mode input files to the relevant base format automatically, as can
already be done when converting Org to reStructuredText or Org to
Texinfo. As a certain amount of work would be required to get it
done, there would need to be clear demand for that work to be done.

```
# libgpgme.vers - List of symbols to export.
# Copyright (C) 2002, 2004, 2005, 2009, 2012 g10 Code GmbH
#
# This file is part of GPGME.
#
# GPGME is free software; you can redistribute it and/or modify
# it under the terms of the GNU Lesser general Public License as
# published by the Free Software Foundation; either version 2.1 of
# the License, or (at your option) any later version.
#
# GPGME is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
# GNU Lesser General Public License for more details.
#
# You should have received a copy of the GNU Lesser General Public
# License along with this program; if not, see <https://www.gnu.org/licenses/>.

#-----------------------------------------------------
# Please remember to add new functions also to gpgme.def
#-----------------------------------------------------

GPGME_1.1 {
 global:
   gpgme_set_engine_info;

    gpgme_ctx_get_engine_info;
   gpgme_ctx_set_engine_info;

   gpgme_data_set_file_name;
   gpgme_data_get_file_name;
   gpgme_data_identify;

   gpgme_sig_notation_clear;
   gpgme_sig_notation_add;
   gpgme_sig_notation_get;
```

gpgme_free;

gpgme_op_getauditlog_start;
gpgme_op_getauditlog;

gpgme_conf_release;
gpgme_conf_arg_new;
gpgme_conf_arg_release;
gpgme_conf_opt_change;
gpgme_op_conf_load;
gpgme_op_conf_save;
gpgme_op_conf_dir;

gpgme_cancel_async;

gpgme_op_assuan_result;
gpgme_op_assuan_transact;
gpgme_op_assuan_transact_start;

gpgme_check_version_internal;

gpgme_io_read;
gpgme_io_write;

gpgme_result_ref;
gpgme_result_unref;

gpgme_op_import_keys;
gpgme_op_import_keys_start;
gpgme_op_export_keys;
gpgme_op_export_keys_start;

gpgme_op_assuan_transact_ext;

gpgme_wait_ext;

gpgme_op_vfs_mount_result;
gpgme_op_vfs_mount;
gpgme_op_vfs_create;

gpgme_key_from_uid;
gpgme_set_sub_protocol;
gpgme_get_sub_protocol;

gpgme_op_passwd_start;
gpgme_op_passwd;

gpgme_set_global_flag;

gpgme_io_writen;

gpgme_set_pinentry_mode;
gpgme_get_pinentry_mode;

gpgme_get_dirinfo;

gpgme_op_spawn_start;
gpgme_op_spawn;

gpgme_set_offline;
gpgme_get_offline;

gpgme_set_status_cb;
gpgme_get_status_cb;

gpgme_pubkey_algo_string;
gpgme_set_ctx_flag;
gpgme_get_ctx_flag;
gpgme_data_set_flag;

gpgme_op_createkey_start;
gpgme_op_createkey;
gpgme_op_createsubkey_start;
gpgme_op_createsubkey;
gpgme_op_adduid_start;
gpgme_op_adduid;
gpgme_op_revuid_start;
gpgme_op_revuid;
gpgme_op_keysign_start;
gpgme_op_keysign;
gpgme_op_tofu_policy_start;
gpgme_op_tofu_policy;
gpgme_op_interact_start;
gpgme_op_interact;

gpgme_addrspec_from_uid;

gpgme_set_sender;
gpgme_get_sender;

gpgme_op_query_swdb;
gpgme_op_query_swdb_result;

gpgme_op_set_uid_flag_start;
gpgme_op_set_uid_flag;

```
  gpgme_op_decrypt_ext;
  gpgme_op_decrypt_ext_start;

  gpgme_data_new_from_estream;

};


GPGME_1.0 {
 global:
  gpgme_check_version;
  gpgme_get_engine_info;
  gpgme_engine_check_version;

  gpgme_err_code_from_errno;
  gpgme_err_code_to_errno;
  gpgme_err_make_from_errno;
  gpgme_error_from_errno;
  gpgme_strerror;
  gpgme_strerror_r;
  gpgme_strsource;

  gpgme_data_get_encoding;
  gpgme_data_new;
  gpgme_data_new_from_cbs;
  gpgme_data_new_from_fd;
  gpgme_data_new_from_file;
  gpgme_data_new_from_filepart;
  gpgme_data_new_from_mem;
  gpgme_data_new_from_stream;
  gpgme_data_read;
  gpgme_data_release;
  gpgme_data_release_and_get_mem;
  gpgme_data_seek;
  gpgme_data_set_encoding;
  gpgme_data_write;

  gpgme_get_protocol_name;
  gpgme_hash_algo_name;
  gpgme_pubkey_algo_name;

  gpgme_new;
  gpgme_get_armor;
  gpgme_get_include_certs;
  gpgme_get_io_cbs;
   gpgme_get_keylist_mode;
  gpgme_get_passphrase_cb;
  gpgme_get_progress_cb;
```

gpgme_get_protocol;
gpgme_get_textmode;
gpgme_release;
gpgme_set_armor;
gpgme_set_include_certs;
gpgme_set_io_cbs;
gpgme_set_keylist_mode;
gpgme_set_locale;
gpgme_set_passphrase_cb;
gpgme_set_progress_cb;
gpgme_set_protocol;
gpgme_set_textmode;
gpgme_signers_add;
gpgme_signers_clear;
gpgme_signers_count;
gpgme_signers_enum;

gpgme_key_ref;
gpgme_key_unref;
gpgme_key_release;

gpgme_trust_item_ref;
gpgme_trust_item_unref;

gpgme_cancel;
gpgme_op_card_edit;
gpgme_op_card_edit_start;
gpgme_op_decrypt;
gpgme_op_decrypt_result;
gpgme_op_decrypt_start;
gpgme_op_decrypt_verify;
gpgme_op_decrypt_verify_start;
gpgme_op_delete;
gpgme_op_delete_start;
gpgme_op_delete_ext;
gpgme_op_delete_ext_start;
gpgme_op_edit;
gpgme_op_edit_start;
gpgme_op_encrypt;
gpgme_op_encrypt_start;
gpgme_op_encrypt_ext;
gpgme_op_encrypt_ext_start;
gpgme_op_encrypt_sign;
gpgme_op_encrypt_sign_ext;
gpgme_op_encrypt_sign_start;
gpgme_op_encrypt_sign_ext_start;
gpgme_op_encrypt_result;

gpgme_op_export;
gpgme_op_export_ext;
gpgme_op_export_ext_start;
gpgme_op_export_start;
gpgme_op_genkey;
gpgme_op_genkey_result;
gpgme_op_genkey_start;
gpgme_get_key;
gpgme_op_import;
gpgme_op_import_result;
gpgme_op_import_start;
gpgme_op_keylist_end;
gpgme_op_keylist_ext_start;
gpgme_op_keylist_from_data_start;
gpgme_op_keylist_next;
gpgme_op_keylist_result;
gpgme_op_keylist_start;
gpgme_op_sign;
gpgme_op_sign_result;
gpgme_op_sign_start;
gpgme_op_trustlist_end;
gpgme_op_trustlist_next;
gpgme_op_trustlist_start;
gpgme_op_verify;
gpgme_op_verify_result;
gpgme_op_verify_start;
gpgme_wait;

gpgme_data_new_with_read_cb;
gpgme_data_rewind;
gpgme_get_sig_status;
gpgme_get_sig_string_attr;
gpgme_get_sig_ulong_attr;
gpgme_get_sig_key;
gpgme_key_get_string_attr;
gpgme_key_get_ulong_attr;
gpgme_key_sig_get_string_attr;
gpgme_key_sig_get_ulong_attr;
gpgme_op_import_ext;
gpgme_trust_item_get_int_attr;
gpgme_trust_item_get_string_attr;
gpgme_trust_item_release;

gpgme_err_code_from_syserror;
gpgme_err_set_errno;

gpgme_op_setexpire;
gpgme_op_setexpire_start;

```
  gpgme_op_revsig;
  gpgme_op_revsig_start;

 local:
  *;

};
# -*- mode: org -*-
#+TITLE: What's New in the GPGME Python Bindings and Documentation
#+AUTHOR: Ben McGinnes
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}
#+LATEX_HEADER: \author{Ben McGinnes <ben@gnupg.org>}


* What's New
 :PROPERTIES:
 :CUSTOM_ID: new-stuff
 :END:

| Version:        | 0.0.1                                |
| GPGME Version:  | 1.13.0                               |
| Author:         | Ben McGinnes <ben@gnupg.org>         |
| Author GPG Key: | DB4724E6FA4286C92B4E55C4321E4E2373590E5D |
| Language:       | Australian English, British English  |
| xml:lang:       | en-AU, en-GB, en                     |

Last time the most obviously new thing was adding the /What's New/
section to the HOWTO.  Now it's moving it out of the HOWTO.


** New in GPGME 1130
  :PROPERTIES:
   :CUSTOM_ID: new-stuff-1-13-0
  :END:

Additions since GPGME 1.12.0 include:

- Moving the /What's New/ section out of the basic [[file:gpgme-python-howto.org][HOWTO]] document and
 into its own file so as to more readily include other documents
 beyond that HOWTO.
- Moving the preceding, archival, segments into [[file:what-was-new.org][another file]].
- Added =gpg.version.versionintlist= to make it easier for Python
```

developers to check for a specific version number, even with beta
versions (it will drop the "-betaN" part).
- Added expanded detail on issues pertaining to installing for Windows
users.
- Bindings enter [[file:maintenance-mode][maintenance mode]] from January, 2019.
- Added documentation on maintenance mode and what changes can be made
to the code when in that status. Essentially that boils down to bug
fixes only and no feature requests.
- The import-keys-hkp.py example script, which uses the =hkp4py=
module to search the SKS servers for a key, has been
tightened up to
search for both hexadecimal key IDs and user ID strings with reduced
chance of unnecessary repitition. There may still be some
repetition if a key includes a user ID matching the hexadecimal
value of a key ID.
/*
global.h - global gpgme functions and enums
Copyright (C) 2003, 2007 Klarlvdalens Datakonsult AB
2016 Bundesamt fr Sicherheit in der Informationstechnik
Software engineering by Intevation GmbH

This file is part of GPGME++.

GPGME++ is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public
License as published by the Free Software Foundation; either
version 2 of the License, or (at your option) any later version.

GPGME++ is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License
along with GPGME++; see the file COPYING.LIB. If not, write to the
Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef
__GPGMEPP_GLOBAL_H__
#define __GPGMEPP_GLOBAL_H__

#include "gpgmefw.h"
#include "gpgmepp_export.h"

#include <iosfwd>

```
#include <cstring>

namespace GpgME
{
class Error;
class EngineInfo;
class Context;
}

struct _GIOChannel;
typedef struct _GIOChannel      GIOChannel;
class QIODevice;

namespace GpgME
{

GPGMEPP_EXPORT void initializeLibrary();
/*!
 Initializes the library, returns Error::code() ==
 GPG_ERR_USER_1 if underlying gpgme is too old.
*/
GPGMEPP_EXPORT Error initializeLibrary(int);

enum Protocol { OpenPGP, CMS, UnknownProtocol };

enum Engine { GpgEngine, GpgSMEngine, GpgConfEngine, UnknownEngine, AssuanEngine, G13Engine,
SpawnEngine };

enum KeyListMode {
  Local = 0x1,
  Extern = 0x2,
  Locate = 0x3,
  Signatures = 0x4,
  SignatureNotations = 0x8,
  Validate = 0x10,
  Ephemeral = 0x20,
  WithTofu = 0x40,
  WithKeygrip = 0x80,
  WithSecret = 0x100
};

enum SignatureMode { NormalSignatureMode, Detached, Clearsigned };

GPGMEPP_EXPORT std::ostream
 &operator<<(std::ostream &os, Protocol proto);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Engine eng);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, KeyListMode mode);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, SignatureMode mode);
```

```
GPGMEPP_EXPORT Error setDefaultLocale(int category, const char *value);

GPGMEPP_EXPORT Context *wait(Error &e, bool hang = true);
typedef void (*IdleFunction)(void);
GPGMEPP_EXPORT IdleFunction registerIdleFunction(IdleFunction idleFunction);

typedef void (*IOCallback)(void *data, int fd);

GPGMEPP_EXPORT EngineInfo engineInfo(Protocol proto);
GPGMEPP_EXPORT EngineInfo engineInfo(Engine engine);
/** Wrapper around gpgme_get_dirinfo. What can be:
homedir, sysconfdir, bindir, libexecdir, libdir,
datadir, localedir, agent-socket, agent-ssh-socket,
dirmngr-socket, uiserver-socket, gpgconf-name, gpg-name,
gpgsm-name, g13-name

This may be extended in the future.
*/
GPGMEPP_EXPORT const char *dirInfo(const char *what);

GPGMEPP_EXPORT
 Error checkEngine(Protocol proto);
GPGMEPP_EXPORT Error checkEngine(Engine engine);

/* Wrapper for gpgme_set_global_flag */
GPGMEPP_EXPORT int setGlobalFlag(const char *name, const char *value);

GPGMEPP_EXPORT GIOChannel *getGIOChannel(int fd);
GPGMEPP_EXPORT QIODevice   *getQIODevice(int fd);

enum Feature {
  ValidatingKeylistModeFeature            = 0x00000001,
  CancelOperationFeature                  = 0x00000002,
  WrongKeyUsageFeature                    = 0x00000004,
  DefaultCertificateInclusionFeature      = 0x00000008,

  GetSetEngineInfoFeature                 = 0x00000010,
  EngineInfoHomeDirFeature                = 0x00000020,
  NoEncryptToEncryptionFlagFeature        = 0x00000040,
  EphemeralKeylistModeFeature             = 0x00000080,

  SetDataFileNameFeeature                 = 0x00000100,
  VerificationResultFileNameFeature       = 0x00000200,
  DecryptionResultFileNameFeature         = 0x00000400,
   DecryptionResultRecipientsFeature      = 0x00000800,

  AuditLogFeature                         = 0x00001000,
```

```
  GpgConfEngineFeature                    = 0x00002000,
  CancelOperationAsyncFeature             = 0x00004000,
  AssuanEngineFeature                     = 0x00008000,

  ClearAddGetSignatureNotationsFeature    = 0x00010000,
  SignatureNotationsKeylistModeFeature    = 0x00020000,
  KeySignatureNotationsFeature            = 0x00040000,
  SignatureNotationsFlagsFeature          = 0x00080000,
  SignatureNotationsCriticalFlagFeature   = 0x00100000,
  SignatureNotationsHumanReadableFlagFeature = 0x00200000,
  CardKeyFeature                          = 0x00400000,
  ImportFromKeyserverFeature              = 0x00800000,

  KeyIsQualifiedFeature                   = 0x01000200,
  SubkeyIsQualifiedFeature                = 0x02000000,
  SignaturePkaFieldsFeature               = 0x04000000,
  SignatureAlgorithmFieldsFeature
        = 0x08000000,

  FdPointerFeature                        = 0x10000000,
  G13VFSFeature                           = 0x20000000,
  PasswdFeature                           = 0x40000000, // gpgme >= 1.3.0
  // unusable (max value)

  FeatureMaxValue                         = 0x80000000
};
enum Feature2 {
  BinaryAndFineGrainedIdentify            = 0x00000001, // gpgme >= 1.7.0
  Feature2MaxValue                        = 0x80000000
};

// use hasFeature( unsigned long, unsigned long ) instead
GPGMEPP_DEPRECATED_EXPORT bool hasFeature(unsigned long feature);
GPGMEPP_EXPORT bool hasFeature(unsigned long feature, unsigned long feature2);

} // namespace GpgME

# ifndef GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION
#  define GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION( Class ) \
  namespace std { template <> inline void swap< GpgME::Class >( GpgME::Class & lhs, GpgME::Class & rhs ) {
lhs.swap( rhs ); } }
# endif

# ifndef GPGMEPP_MAKE_SAFE_BOOL_OPERATOR
#
 define GPGMEPP_MAKE_SAFE_BOOL_OPERATOR( Cond ) \
  private: \
  struct __safe_bool_dummy__ { void nonnull() {} }; \
```

```
  typedef void ( __safe_bool_dummy__::*unspecified_bool_type )(); \
  public: \
  operator unspecified_bool_type() const { return ( Cond ) ? &__safe_bool_dummy__::nonnull : nullptr; }
# endif

inline int _gpgmepp_strcmp(const char *s1, const char *s2)
{
  return s1 ? s2 ? std::strcmp(s1, s2) : 1 : s2 ? -1 : 0;
}

#define _GPGMEPP_MAKE_STRCMP( Name, expr, cmp )                 \
  template <template <typename U> class Op>                     \
  struct Name {                                                 \
    typedef bool result_type;                                   \
    \
    bool operator()( const char * lhs, const char * rhs ) const {   \
      return Op<int>()( cmp, 0 );                               \
    }                                                           \
    \
    bool operator()(
 const std::string & lhs, const std::string & rhs ) const { \
      return operator()( lhs.c_str(), rhs.c_str() );            \
    }                                                           \
    bool operator()( const char * lhs, const std::string & rhs ) const { \
      return operator()( lhs, rhs.c_str() );                    \
    }                                                           \
    bool operator()( const std::string & lhs, const char * rhs ) const { \
      return operator()( lhs.c_str(), rhs );                    \
    }                                                           \
    \
    template <typename T>                                       \
    bool operator()( const T & lhs, const T & rhs ) const {     \
      return operator()( (lhs expr), (rhs expr) );              \
    }                                                           \
    template <typename
 T>                                     \
    bool operator()( const T & lhs, const char * rhs ) const {  \
      return operator()( (lhs expr), rhs );                     \
    }                                                           \
    template <typename T>                                       \
    bool operator()( const char * lhs, const T & rhs ) const {  \
      return operator()( lhs, (rhs expr) );                     \
    }                                                           \
    template <typename T>                                       \
    bool operator()( const T & lhs, const std::string & rhs ) const { \
      return operator()( (lhs expr), rhs );                     \
    }                                                           \
    template <typename T>                                       \
```

```
    bool operator()( const std::string & lhs, const
 T & rhs ) const {    \
        return operator()( lhs, (rhs expr) );                    \
    }                                                  \
  }

#define GPGMEPP_MAKE_STRCMP( Name, expr )                        \
  _GPGMEPP_MAKE_STRCMP( Name, expr, _gpgmepp_strcmp( lhs, rhs ) )


#endif // __GPGMEPP_GLOBAL_H__
/* mbox-util.h - Defs for mail address helper functions
* Copyright (C) 2015 Werner Koch
*
* This file is part of GnuPG.
*
* This file is free software; you can redistribute it and/or modify
* it under the terms of the GNU Lesser General Public License as
* published by the Free Software Foundation; either version 2.1 of
* the License, or (at your option) any later version.
*
* This file is distributed in the hope that it will be useful,
* but WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
* GNU Lesser General Public License for more details.
*
* You should have received a copy of the GNU Lesser General Public License
* along with this program; if not, see <https://www.gnu.org/licenses/>.
*/
#ifndef GNUPG_COMMON_MBOX_UTIL_H
#define GNUPG_COMMON_MBOX_UTIL_H

/* int has_invalid_email_chars (const void *buffer, size_t length); */
int _gpgme_is_valid_mailbox (const char *name);
/* int _gpgme_is_valid_mailbox_mem
 (const void *buffer, size_t length); */
char *_gpgme_mailbox_from_userid (const char *userid);
/* int is_valid_user_id (const char *uid); */


#endif /*GNUPG_COMMON_MBOX_UTIL_H*/
/*
  downloadjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH
```

```
  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_DOWNLOADJOB_H__
#define __KLEO_DOWNLOADJOB_H__

#include "job.h"

#include <QtCore/QByteArray>

#include <memory>

namespace GpgME
{
class Error;
}

class QStringList;
class QIODevice;
class QByteArray;

namespace QGpgME
{
```

```
/**
  @short An abstract base class for asynchronous downloaders

  To use a DownloadJob, first obtain an instance from the
  CryptoBackend implementation,
 connect the progress() and result()
  signals to suitable slots and then start the download with a call
  to start(). This call might fail, in which case the DownloadJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the DownloadJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT DownloadJob : public Job
{
  Q_OBJECT
protected:
  explicit DownloadJob(QObject *parent);
public:
  ~DownloadJob();

  /**
    Starts the download operation. \a fingerprint is the
    fingerprint of the key to download. If \a fingerprint is empty,
    contains only whitespace or anything other than a fingerprint,
    the result is undefined.

    Output is written to \a keyData, if given. Otherwise, it is
    passed as the second argument of result().
  */
  virtual GpgME::Error start(const QByteArray &fingerprint,
                             const
 std::shared_ptr<QIODevice> &keyData) = 0;

  /**
    Starts the download operation. \a fingerprints is a list of
    fingerprints used to specify the list of keys downloaded. Empty
    patterns are ignored. If \a fingerprints is empty, contains
    only empty strings or anything other than fingerprints, the
    result is undefined.
  */
  virtual QGPGME_DEPRECATED_EXPORT GpgME::Error start(const QStringList &fingerprints) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &result, const QByteArray &keyData, const QString &auditLogAsHtml =
QString(), const GpgME::Error &auditLogError = GpgME::Error());
```

```
};

}

#endif // __KLEO_DOWNLOADJOB_H__
{
  "base64": true,
  "more": true,
  "response": "*"
}
/*
  job.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_JOB_H__
#define __KLEO_JOB_H__
```

```
#include "qgpgme_export.h"

#include <QObject>
#include <QString>
#include <QMap>

#ifdef BUILDING_QGPGME
# include "error.h"
#else
# include <gpgme++/error.h>
#endif

class QWidget;

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous crypto operations

  During the operation, you might receive progress updates through
  the progress()
 signal as they arrive, but an implementation is
  free to not send progress information. You should show a busy
  progressbar until the first progress() signal is received.

  The done() signal is emitted _before_ the result() signals of
  subclasses and should be used to hide and/or reset progress bars,
  not to learn of the end of the operation. Use the result()
  signals for that.

  To cancel the operation, simply call slotCancel(). The result()
  signal of subclasses will still be emitted, though, and will
  carry the information that the operation was canceled.
*/
class QGPGME_EXPORT Job : public QObject
{
   Q_OBJECT
protected:
   explicit Job(QObject *parent);
public:
   ~Job();

   virtual QString auditLogAsHtml() const;
   virtual GpgME::Error auditLogError() const;
   bool isAuditLogSupported() const;

   /** Get the underlying context to set some additional options for a job.
```

```
   *
   * This is intended to provide more flexibility on configuring jobs
 before
   * they are started.
   * The context is still owned by the thread, do not delete it.
   *
   * This is a static method that takes the job as argument.
   *
   * This function may not be called for running jobs.
   *
   * @returns the context used by the job job or null.
   */
  static GpgME::Context *context(Job *job);

public Q_SLOTS:
  virtual void slotCancel() = 0;

Q_SIGNALS:
  void progress(const QString &what, int current, int total);
  void done();
};

extern QMap <Job *, GpgME::Context *> g_context_map;
}

#endif // __KLEO_JOB_H__
/*
 importresult.h - wraps a gpgme import result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
```

```
*/

#ifndef __GPGMEPP_IMPORTRESULT_H__
#define
 __GPGMEPP_IMPORTRESULT_H__

#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <memory>

#include <vector>

namespace GpgME
{

class Error;
class Import;

class GPGMEPP_EXPORT ImportResult : public Result
{
public:
  ImportResult();
  ImportResult(gpgme_ctx_t ctx, int error);
  ImportResult(gpgme_ctx_t ctx, const Error &error);
  explicit ImportResult(const Error &error);

  const ImportResult &operator=(ImportResult other)
  {
     swap(other);
     return *this;
  }

  void swap(ImportResult &other)
  {
     Result::swap(other);
     using std::swap;
     swap(this->d, other.d);
  }

  bool isNull() const;

  int numConsidered() const;
  int numKeysWithoutUserID() const;
  int numImported() const;
  int numRSAImported() const;
  int numUnchanged() const;
```

```
  int newUserIDs() const;
  int newSubkeys() const;
  int newSignatures() const;
  int newRevocations() const;

  int numSecretKeysConsidered()
 const;
  int numSecretKeysImported() const;
  int numSecretKeysUnchanged() const;

  int notImported() const;
  int numV3KeysSkipped() const;

  Import import(unsigned int idx) const;
  std::vector<Import> imports() const;

  class Private;
private:
  void init(gpgme_ctx_t ctx);
  std::shared_ptr<Private> d;
};

class GPGMEPP_EXPORT Import
{
  friend class ::GpgME::ImportResult;
  Import(const std::shared_ptr<ImportResult::Private> &parent, unsigned int idx);
public:
  Import();

  const Import &operator=(Import other)
  {
    swap(other);
    return *this;
  }

  void swap(Import &other)
  {
    using std::swap;
    swap(this->d, other.d);
    swap(this->idx, other.idx);
  }

  bool isNull() const;

  const char *fingerprint() const;
  Error error() const;
```

```
  enum Status {
     Unknown = 0x0,
     NewKey = 0x1,
     NewUserIDs = 0x2,
     NewSignatures = 0x4,
     NewSubkeys = 0x8,

 ContainedSecretKey = 0x10
  };
  Status status() const;

private:
  std::shared_ptr<ImportResult::Private> d;
  unsigned int idx;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const ImportResult &irs);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Import &imp);

} // namespace GpgME

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(ImportResult)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Import)

#endif // __GPGMEPP_IMPORTRESULT_H__
{
  "op": "delete",
  "key": "E8143C489C8D41124DC40D0B47AF4B6961F04784"
}
{
 "fingerprint":  "*"
}
;;; -*- Mode: lisp -*-

;;; Copyright (C) 2006 g10 Code GmbH
;;;
;;; This file is part of GPGME.
;;;
;;; GPGME is free software; you can redistribute it and/or
;;; modify it under the terms of the GNU Lesser General Public License
;;; as published by the Free Software Foundation; either version 2.1 of
;;; the License, or (at your option) any later version.
;;;
;;; GPGME is distributed in the hope that it will be useful, but
;;; WITHOUT ANY WARRANTY; without even the implied warranty of
;;; MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
;;; Lesser General Public License for more details.
;;;
```

```
;;; You should have received a copy of the GNU Lesser General Public
;;; License along with GPGME; if not, write to the Free
;;; Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
;;; 02111-1307, USA.

(defpackage #:gpgme-system
 (:use #:common-lisp #:asdf))

(in-package #:gpgme-system)

(defsystem gpgme
 :description "GnuPG Made Easy."
 :author "g10 Code GmbH"
  :version "1.15.1"
 :licence "GPL"
 :defsystem-depends-on ("cffi-grovel")
 :depends-on ("cffi" "gpg-error" "trivial-garbage")
 :components ((:file "gpgme-package")
              (:cffi-grovel-file "gpgme-grovel"
               :depends-on ("gpgme-package"))
       (:file "gpgme"
  :depends-on ("gpgme-package" "gpgme-grovel"))))
# -*- mode: org -*-
#+TITLE: GNU Privacy Guard (GnuPG) Made Easy Python Bindings
#+AUTHOR: Ben McGinnes
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}
#+LATEX_HEADER: \author{Ben McGinnes <ben@gnupg.org>}


* GPGME Python Bindings
 :PROPERTIES:
 :CUSTOM_ID: top
 :END:


** Contents
  :PROPERTIES:
  :CUSTOM_ID: contents
  :END:


- [[file:short-history][A short history of the project]]
- [[file:what-is-new][What's New]]
```

- [[file:maintenance-mode][Maintenance Mode]] (from January, 2019)
- [[file:what-was-new][What Was New]]
- [[file:gpgme-python-howto][GPGME Python Bindings HOWTO]]


```
{
  "components":   [{
     "name": "gpg",
        "description":  "OpenPGP",
        "options":     [{
           "name": "Monitor",
           "flags":       1,
           "level":       0,
           "type": 0,
           "alt_type":     0
        }, {
           "name": "verbose",
           "description":  "verbose",
           "level":       0,
           "type": 0,
           "alt_type":     0
        }]
  }]
}
{
  "keys": [{
     "revoked":      false,
        "expired":      false,
        "disabled":     false,
        "invalid":      false,
        "can_encrypt":  true,
        "can_sign":     true,
        "can_certify":  true,
        "can_authenticate":     true,
        "secret":       false,
        "is_qualified": false,
        "protocol":     "OpenPGP",
        "fingerprint":  "23FD347A419429BACCD5E72D6BC4778054ACD246",
        "subkeys":      [{
           "revoked":      false,
           "expired":      false,
           "disabled":     false,
           "invalid":      false,
           "can_encrypt":  false,
           "can_sign":     true,
           "can_certify":  true,
           "can_authenticate":     true,
           "secret":       false,
           "is_qualified": false,
           "is_cardkey":   false,
```

```
            "is_de_vs":     false,
            "pubkey_algo_name":
    "DSA",
            "pubkey_algo_string":   "dsa1024",
            "pubkey_algo":  17,
            "length":       1024,
            "timestamp":    920892875,
            "expires":      0
          }, {
            "revoked":      false,
              "expired":      false,
              "disabled":     false,
              "invalid":      false,
              "can_encrypt":  true,
              "can_sign":     false,
              "can_certify":  false,
              "can_authenticate":     false,
              "secret":       false,
              "is_qualified": false,
              "is_cardkey":   false,
              "is_de_vs":     false,
              "pubkey_algo_name":     "ELG-E",
              "pubkey_algo_string":   "elg1024",
              "pubkey_algo":  16,
              "length":       1024,
              "timestamp":    920892914,
               "expires":      0
          }],
          "userids":     [{
            "revoked":      false,
            "invalid":      false,
            "validity":     "unknown",
            "uid":  "Zulu Test (demo key) <zulu@example.net>",
            "name": "Zulu Test",
            "email":        "zulu@example.net",
            "comment":      "demo key",
            "address":      "zulu@example.net"
          }]
    }]
}
/*
 notation.h - wraps a gpgme verify result
 Copyright (C) 2004, 2007 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.
```

```
 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_NOTATION_H__
#define
 __GPGMEPP_NOTATION_H__

#include "gpgmefw.h"
#include "verificationresult.h"
#include "gpgmepp_export.h"

#include <memory>

#include <iosfwd>

namespace GpgME
{

class GPGMEPP_EXPORT Notation
{
  friend class ::GpgME::Signature;
  Notation(const std::shared_ptr<VerificationResult::Private> &parent, unsigned int sindex, unsigned int nindex);
public:
  Notation();
  explicit Notation(gpgme_sig_notation_t nota);

  const Notation &operator=(Notation other)
  {
     swap(other);
     return *this;
  }

  void swap(Notation &other)
  {
     using std::swap;
```

```
    swap(this->d, other.d);
  }

  bool isNull() const;

  const char *name() const;
  const char *value() const;

  enum Flags {
    NoFlags = 0,
    HumanReadable = 1,
    Critical = 2
  };
  Flags flags() const;

  bool isHumanReadable() const;
  bool isCritical() const;

private:
  class Private;
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream
 &operator<<(std::ostream &os, const Notation &nota);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Notation::Flags flags);

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Notation)

#endif // __GPGMEPP_NOTATION_H__
/*
  qgpgmesignencryptjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2007,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
```

```
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMESIGNENCRYPTJOB_H__
#define __QGPGME_QGPGMESIGNENCRYPTJOB_H__

#include "signencryptjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "signingresult.h"
#else
#include <gpgme++/signingresult.h>
#endif
#ifdef BUILDING_QGPGME
# include "encryptionresult.h"
#else
#include <gpgme++/encryptionresult.h>
#endif
#ifdef BUILDING_QGPGME
# include
 "key.h"
#else
#include <gpgme++/key.h>
#endif

#include <utility>

namespace QGpgME
{
```

```
class QGpgMESignEncryptJob
#ifdef Q_MOC_RUN
  : public SignEncryptJob
#else
  : public _detail::ThreadedJobMixin<SignEncryptJob, std::tuple<GpgME::SigningResult,
GpgME::EncryptionResult, QByteArray, QString, GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMESignEncryptJob(GpgME::Context *context);
  ~QGpgMESignEncryptJob();

  /* from SignEncryptJob */
  GpgME::Error start(const std::vector<GpgME::Key> &signers,
                     const std::vector<GpgME::Key> &recipients,
                     const QByteArray &plainText, bool alwaysTrust) Q_DECL_OVERRIDE;

  /* from SignEncryptJob */
  void start(const std::vector<GpgME::Key> &signers,
             const std::vector<GpgME::Key> &recipients,
             const std::shared_ptr<QIODevice> &plainText,
             const std::shared_ptr<QIODevice>
 &cipherText,
             bool alwaysTrust) Q_DECL_OVERRIDE;

  void start(const std::vector<GpgME::Key> &signers,
             const std::vector<GpgME::Key> &recipients,
             const std::shared_ptr<QIODevice> &plainText,
             const std::shared_ptr<QIODevice> &cipherText,
             const GpgME::Context::EncryptionFlags flags) Q_DECL_OVERRIDE;

  std::pair<GpgME::SigningResult, GpgME::EncryptionResult>
  exec(const std::vector<GpgME::Key> &signers,
       const std::vector<GpgME::Key> &recipients,
       const QByteArray &plainText, bool alwaysTrust,
       QByteArray &cipherText) Q_DECL_OVERRIDE;

  std::pair<GpgME::SigningResult, GpgME::EncryptionResult>
  exec(const std::vector<GpgME::Key> &signers,
       const std::vector<GpgME::Key> &recipients,
       const QByteArray &plainText, const GpgME::Context::EncryptionFlags flags,
       QByteArray &cipherText) Q_DECL_OVERRIDE;
```

```
  /* from SignEncryptJob */
  void setOutputIsBase64Encoded(bool
on) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  bool mOutputIsBase64Encoded;
  std::pair<GpgME::SigningResult, GpgME::EncryptionResult> mResult;
};

}

#endif // __QGPGME_QGPGMESIGNENCRYPTJOB_H__
```

```
    GNU GENERAL PUBLIC LICENSE
      Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
  59 Temple Place, Suite 330, Boston, MA  02111-1307  USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

     Preamble

 The licenses for most software are designed to take away your
freedom to share and change it.  By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users.  This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it.  (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.)  You can apply it to
your programs, too.

 When we speak of free software, we are referring to freedom, not
price.  Our General Public Licenses are designed
 to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

 To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.
```

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or
executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not

compelled to copy the
source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution
of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY

FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.


```
{
  "keys": [{
     "revoked":      false,
        "expired":      false,
        "disabled":     false,
        "invalid":      false,
        "can_encrypt":  true,
        "can_sign":     true,
        "can_certify":  true,
        "can_authenticate":     true,
        "secret":       true,
        "is_qualified": false,
```

```
    "protocol":     "OpenPGP",
    "fingerprint":  "A0FF4590BB6122EDEF6E3C542D727CC768697734",
    "subkeys":      [{
       "revoked":      false,
       "expired":      false,
       "disabled":     false,
       "invalid":      false,
       "can_encrypt":  false,
       "can_sign":     true,
       "can_certify":  true,
       "can_authenticate":     true,
       "is_qualified": false,
       "is_cardkey":   false,
       "is_de_vs":     false,
       "pubkey_algo_name":     "DSA",

"pubkey_algo_string":   "dsa1024",
       "keyid":        "2D727CC768697734",
       "keygrip":      "76F7E2B35832976B50A27A282D9B87E44577EB66",
       "pubkey_algo":  17,
       "length":       1024,
       "timestamp":    920882846,
       "expires":      0
    }, {
       "revoked":      false,
          "expired":      false,
          "disabled":     false,
          "invalid":      false,
          "can_encrypt":  true,
          "can_sign":     false,
          "can_certify":  false,
          "can_authenticate":     false,
          "is_qualified": false,
          "is_cardkey":   false,
          "is_de_vs":     false,
          "pubkey_algo_name":     "ELG-E",
          "pubkey_algo_string":   "elg1024",
          "keyid":        "6AE6D7EE46A871F8",
          "keygrip":
 "A0747D5F9425E6664F4FFBEED20FBCA79FDED2BD",
          "pubkey_algo":  16,
          "length":       1024,
          "timestamp":    920882959,
          "expires":      0
    }],
    "userids":      [{
       "revoked":      false,
       "invalid":      false,
```

```
          "validity":     "unknown",
          "uid":  "Alfa Test (demo key) <alfa@example.net>",
          "name": "Alfa Test",
          "email":        "alfa@example.net",
          "comment":      "demo key",
          "address":      "alfa@example.net"
        }, {
          "revoked":      false,
          "invalid":      false,
          "validity":     "unknown",
          "uid":  "Alpha Test (demo key) <alpha@example.net>",
          "name": "Alpha Test",
          "email":        "alpha@example.net",
          "comment":      "demo key",
          "address":
    "alpha@example.net"
        }, {
          "revoked":      false,
            "invalid":      false,
            "validity":     "unknown",
            "uid":  "Alice (demo key)",
            "name": "Alice",
            "email":        "",
            "comment":      "demo key",
            "origin":       0,
            "last_update":  0
        }]
  }, {
     "revoked":      false,
        "expired":      false,
        "disabled":     false,
        "invalid":      false,
        "can_encrypt":  true,
        "can_sign":     true,
        "can_certify":  true,
        "can_authenticate":     true,
        "is_qualified": false,
        "protocol":     "OpenPGP",
        "fingerprint":  "D695676BDCEDCC2CDD6152BCFE180B1DA9E3B0B2",
        "owner_trust":  "unknown",
        "origin":       0,
        "last_update":  0,
        "subkeys":
    [{
          "revoked":      false,
          "expired":      false,
          "disabled":     false,
          "invalid":      false,
```

```
      "can_encrypt":  false,
      "can_sign":     true,
      "can_certify":  true,
      "can_authenticate":     true,
      "secret":       false,
      "is_qualified": false,
      "is_cardkey":   false,
      "is_de_vs":     false,
      "pubkey_algo_name":     "DSA",
      "pubkey_algo_string":   "dsa1024",
      "keyid":        "FE180B1DA9E3B0B2",
      "pubkey_algo":  17,
      "length":       1024,
      "timestamp":    920888034,
      "expires":      0
    }, {
      "revoked":      false,
        "expired":      false,
        "disabled":     false,
        "invalid":      false,
        "can_encrypt":
true,
        "can_sign":     false,
        "can_certify":  false,
        "can_authenticate":     false,
        "secret":       false,
        "is_qualified": false,
        "is_cardkey":   false,
        "is_de_vs":     false,
        "pubkey_algo_name":     "ELG-E",
        "pubkey_algo_string":   "elg1024",
        "keyid":        "5381EA4EE29BA37F",
        "pubkey_algo":  16,
        "length":       1024,
        "timestamp":    920888071,
        "expires":      0
    }],
    "userids":      [{
      "revoked":      false,
      "invalid":      false,
      "validity":     "unknown",
      "uid":  "Bob (demo key)",
      "name": "Bob",
      "email":        "",
      "comment":      "demo key"
    }, {
```

```
      "revoked":      false,
           "invalid":      false,
           "validity":     "unknown",
           "uid":  "Bravo Test (demo key) <bravo@example.net>",
           "name": "Bravo Test",
           "email":        "bravo@example.net",
           "comment":      "demo key",
           "address":      "bravo@example.net"
        }]
  }]
}
/*
  verifydetachedjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_VERIFYDETACHEDJOB_H__
#define __KLEO_VERIFYDETACHEDJOB_H__
```

```
#include "job.h"
#include "qgpgme_export.h"

#include <memory>

class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class VerificationResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous verification of detached signatures

  To use a VerifyDetachedJob, first
 obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then start the verification with a
  call to start(). This call might fail, in which case the
  VerifyDetachedJob instance will have scheduled it's own
  destruction with a call to QObject::deleteLater().

  After result() is emitted, the VerifyDetachedJob will schedule
  it's own destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT VerifyDetachedJob : public Job
{
  Q_OBJECT
protected:
  explicit VerifyDetachedJob(QObject *parent);
public:
  ~VerifyDetachedJob();

  /**
    Starts the verification operation. \a signature contains the
    signature data, while \a signedData contains the data over
    which the signature was made.
  */
  virtual GpgME::Error start(const QByteArray &signature,
        const QByteArray &signedData) = 0;
```

```
  /*!
    \overload

    \throws GpgME::Exception if starting fails.

  */
  virtual void start(const std::shared_ptr<QIODevice> &signature, const std::shared_ptr<QIODevice>
&signedData) = 0;

  virtual GpgME::VerificationResult exec(const QByteArray &signature,
                                         const QByteArray &signedData) = 0;

Q_SIGNALS:
  void result(const GpgME::VerificationResult &result, const QString &auditLogAsHtml = QString(), const
GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif // __KLEO_VERIFYDETACHEDJOB_H__
/*
 decryptionresult.h - wraps a gpgme keygen result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_DECRYPTIONRESULT_H__
#define
 __GPGMEPP_DECRYPTIONRESULT_H__
```

```
#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <vector>
#include <algorithm>
#include <iosfwd>
#include <memory>

namespace GpgME
{

class Error;

class GPGMEPP_EXPORT DecryptionResult : public Result
{
public:
  DecryptionResult();
  DecryptionResult(gpgme_ctx_t ctx, int error);
  DecryptionResult(gpgme_ctx_t ctx, const Error &err);
  explicit DecryptionResult(const Error &err);

  const DecryptionResult &operator=(DecryptionResult other)
  {
     swap(other);
     return *this;
  }

  void swap(DecryptionResult &other)
  {
     Result::swap(other);
     using std::swap;
     swap(this->d, other.d);
  }

  bool isNull() const;

  GPGMEPP_DEPRECATED const char *unsupportedAlgortihm() const
  {
     return unsupportedAlgorithm();
  }
  const char *unsupportedAlgorithm() const;

  GPGMEPP_DEPRECATED bool wrongKeyUsage() const
  {
     return isWrongKeyUsage();
   }
  bool isWrongKeyUsage() const;
```

```
  bool isDeVs() const;

  const char *fileName() const;

  const char *sessionKey() const;

  const char *symkeyAlgo() const;

  class Recipient;

  unsigned int numRecipients() const;
  Recipient recipient(unsigned int idx) const;
  std::vector<Recipient> recipients() const;

  bool isLegacyCipherNoMDC() const;

private:
  class Private;
  void init(gpgme_ctx_t ctx);
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const DecryptionResult &result);

class GPGMEPP_EXPORT DecryptionResult::Recipient
{
public:
  Recipient();
  explicit Recipient(gpgme_recipient_t reci);

  const Recipient &operator=(Recipient other)
  {
    swap(other);
    return *this;
  }

  void swap(Recipient &other)
  {
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  const char *keyID() const;
  const char *shortKeyID() const;
```

```
    unsigned int publicKeyAlgorithm() const;
   const char *publicKeyAlgorithmAsString() const;

   Error status() const;

private:
   class Private;
   std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const DecryptionResult::Recipient &reci);

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(DecryptionResult)

#endif // __GPGMEPP_DECRYPTIONRESULT_H__
{
   "name": "gpgmejson",
   "description": "Integration with GnuPG",
   "path": "/usr/bin/gpgme-json",
   "type": "stdio",
   "allowed_origins": [
      "chrome-extension://kajibbejlbohfaggdiogboambcijhkke/"
   ]
}
-----BEGIN PGP PUBLIC KEY BLOCK-----

mQENBFrsKEkBCADKw4Wt8J6M/88qD8PO6lSMCxH1cpwH8iK0uPaFFYsJkkXo7kWf
PTAtrV+REqF/o80dvYcdLvRsV21pvncZz/HXLu1yQ18mC3XObrKokbdgrTTKA5XE
BZkNsqyaMMJauT18H4hYkSg62/tTdO1cu/zWv/LFf7Xyn6+uA74ovXCJlO1s0N2c
PShtr98QRzPMf2owgVk37JnDNp4gGVDGHxSZOuUwxgYAZYnA8SFc+c+3ZrQfY870
+O4j3Mz4p7yD13AwP4buQLBsb/icxekeQCqpRJhLH9f7MdEcGXa1x36RcEkHdu+M
yJ392eMgD+dKNfRCtyTPhjZTxvbNELIBYICfABEBAAG0EHRlc3RAZXhhbXBsZS5v
cmeJAVQEEwEIAD4WIQTUFzW5Ejb9uIIEjFojAWNe7/DLBQUCWuwoSQIbAwUJA8Jn
AAULCQgHAgYVCgkICwIEFgIDAQIeAQIXgAAKCRAjAWNe7/DLBf9kB/wOQ/S60HGw
Fq07W9N01HWULyhHKoMmcHL6rfZ64oDqLxolPSasz7WAMW1jN4qtWJ0mFzwO83V6
kaBe+wF6Kqir6udFSBW9rPcFg6/VZXPltT0a6uacIHq6DyQ5iMW4YQWbVy9OR2rN
GkYo1JCBR0XdRJYCSX3yB4TWv/eXnZ37/WjmiTOIZh35rjs+NuU/S5JPDfAp2/k7
0DevQeBsv+UjVXjWpNTZmPbvDnd995uSmC6UY4hzyP84ORYMYn9n1QAR0goxDN6U
unOf9Rlp1oMzdxMool/d1MlCxg2h3jheuhv7lgUF4KpvHOuEPXQ7UO417E0TYcDZ
1J8Nsv87SZeEuQENBFrsKEkBCADjoEBhG/QPqZHg8VyoD1xYRAWGxyDJkX/GrSs6
yE+x2hk5FoQCajxKa/d4AVxOnJpdwhAfeXeSNaql5Ejgzax+Tdj9BV6vtGVJVv0p
O7bgAiZxkA6RHxtNqhpPnPQoXvUzkzpRgpuL+Nj4yIg7z1ITH6KQH4u5SI9vd+j/
8i9Taz67pdZwuJjac8qBuJHjzAo1bjYctFYUSG5pbmMQyNLySzgiNkFa4DajODlt
3RuqVGP316Fk+Sy2+60tC/HlX8jgMyMONfOGBQx6jk8tvAphS/LAqrrNepnagIyL
UGKU+L8cB2g1PGGp2biBFWqZbudZoyRBet/0yH/zirBdQJw1ABEBAAGJATwEGAEI
ACYWIQTUFzW5Ejb9uIIEjFojAWNe7/DLBQUCWuwoSQIbDAUJA8JnAAAKCRAjAWNe
```

```
7/DLBf0pCACPp5hBuUWngu2Hqvg+tNiujfsiYzId3MffFxEk3CbXeHcJ5F32NDJ9
PYCnra4L8wSv+NZt9gIa8lFwoFSFQCjzH7KE86XcV3MhfdJTNb/+9CR7Jq3e/4Iy
0N5ip7PNYMCyakcAsxvsNCJKrSaDuYe/OAoTXRBtgRWE2uyT315em02Lkr+2Cc/Q
k6H+vlNOHGRgnpI/OZZjnUuUfBUvMGHr1phW+y7aeymC9PnUGdViRdJe23nntMSD
A+0/I7ESO9JsWvJbyBmuiZpu9JjScOjYH9xpQLqRNyw4WHpZriN69F0t9Mmd7bM1
+UyPgbPEr0iWMeyctYsuOLeUyQKMscDT
=QyY6
-----END
 PGP PUBLIC KEY BLOCK-----
/*
# Copyright (C) 2016 g10 Code GmbH
# Copyright (C) 2004 Igor Belyi <belyi@users.sourceforge.net>
# Copyright (C) 2002 John Goerzen <jgoerzen@complete.org>
#
#    This library is free software; you can redistribute it and/or
#    modify it under the terms of the GNU Lesser General Public
#    License as published by the Free Software Foundation; either
#    version 2.1 of the License, or (at your option) any later version.
#
#    This library is distributed in the hope that it will be useful,
#    but WITHOUT ANY WARRANTY; without even the implied warranty of
#    MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
#    Lesser General Public License for more details.
#
#    You should have received a copy of the GNU Lesser General Public
#    License along with this library; if not, write to the Free Software
#    Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307  USA
*/

#ifdef HAVE_CONFIG_H
#include "config.h"
#endif

#include <gpgme.h>
#include "Python.h"

#ifdef
 _WIN32
#include <windows.h>
#define write(fd, str, sz) {DWORD written; WriteFile((HANDLE) fd, str, sz, &written, 0);}
#endif

/* Flag specifying whether this is an in-tree build.  */
extern int gpg_in_tree_build;

PyObject *gpg_raise_callback_exception(PyObject *self);

PyObject *gpg_set_passphrase_cb(PyObject *self, PyObject *cb);
```

```
PyObject *gpg_set_progress_cb(PyObject *self, PyObject *cb);
PyObject *gpg_set_status_cb(PyObject *self, PyObject *cb);

PyObject *gpg_data_new_from_cbs(PyObject *self, PyObject *pycbs,
    gpgme_data_t *r_data);
#include "qgpgme/changepasswdjob.h"
;;;; gpgme-grovel.lisp

;;; This file is part of GPGME-CL.
;;;
;;; GPGME-CL is free software; you can redistribute it and/or modify it
;;; under the terms of the GNU General Public License as published by
;;; the Free Software Foundation; either version 2 of the License, or
;;; (at your option) any later version.
;;;
;;; GPGME-CL is distributed in the hope that it will be useful, but
;;; WITHOUT ANY WARRANTY; without even the implied warranty of
;;; MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
;;; Lesser General Public License for more details.
;;;
;;; You should have received a copy of the GNU General Public License
;;; along with GPGME; if not, write to the Free Software Foundation,
;;; Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.


(in-package :gpgme)


(include "errno.h" "sys/types.h")

(constant (+ebadf+ "EBADF"))

(ctype off-t "off_t")
(ctype size-t "size_t")
(ctype ssize-t "ssize_t")

(cvar ("errno" *errno*) :int)
/*
 result.h - base class for results
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
```

```
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_RESULT_H__
#define
 __GPGMEPP_RESULT_H__

#include "gpgmefw.h"
#include "error.h"

#include <algorithm> // std::swap

namespace GpgME
{

class GPGMEPP_EXPORT Result
{
protected:
  explicit Result() : mError() {}
  explicit Result(int err) : mError(err) {}
  explicit Result(const Error &err) : mError(err) {}

  void swap(Result &other)
  {
     std::swap(other.mError, mError);
  }

public:
  const Error &error() const
  {
     return mError;
  }

protected:
  Error mError;
};

}
```

#endif // __GPGMEPP_RESULT_H__
(21:protected-private-key(3:dsa(1:p129:_d8|po3s@!WGUOAXRC$_[8SN:y|o?2[.pVxn(kOc\Bk0zu&FnK)(1:q21:vBeOP\P)(1:g129:fU/e(2hp@hjc2uE=Sg GO;ZkIyFnGM!GsG@
= _SZklI)(1:y128:K:9tA]4SU1 }sG`nZpx/imV^>A;V%?5!!sS{!=-6@|
=d
)(9:protected25:openpgp-s2k3-sha1-aes-cbc((4:sha18:Li7:6452224)16:,kO{,)80:z7OCG/sB48(H9%*ojSO
OGSma`YUs1h<_)(12:protected-at15:20130812T105134)))
For a list of the authors of the source code of GPGME, please see the
file AUTHORS. The following people supported GPGME development in
various ways (for example by finding bugs or giving advice), and we
want to thank them for their help. If we forgot you, please let us
know.

Adriaan de Groot adridg@cs.kun.nl
Albrecht Dre albrecht.dress@arcor.de
Alfons Hoogervorst alfons@proteus.demon.nl
Daniel Mueller daniel@danm.de
Enno Cramer uebergeek@web.de
Frank Heckenbach frank@g-n-u.de
Igor Belyi gpgme@katehok.ac93.org
Jan-Oliver Wagner jan@intevation.de
Johannes Poehlmann jhp@caldera.de
Jose C. Garca Sogo jose@jaimedelamo.eu.org
Leo Gaspard ekleog@gmail.com
Mark Mutz mutz@kde.org
Miguel Coca mcoca@gnu.org
Noel Torres envite@rolamasao.org
Patrick Spendrin patrick.spendrin@kdab.com
Stphane Corthsy stephane@sente.ch
Timo Schulz twoaday@freakmail.de
Tommy Reynolds reynolds@redhat.com
W.
Trevor King wking@tremily.us

Copyright 2001, 2002, 2004, 2010, 2012 g10 Code GmbH

This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
#include "qgpgme/quickjob.h"
/*
specialjob.h

```
  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_SPECIALJOB_H__
#define __KLEO_SPECIALJOB_H__

#include "job.h"
#include "qgpgme_export.h"

namespace GpgME
{
class Error;
}

namespace QGpgME
{

/**
  @short An abstract base class for protocol-specific jobs
```

```
  To use a SpecialJob, first obtain an instance from the
  CryptoBackend implementation, connect progress() and result()
  signals to suitable slots and then start the
 job with a call to
  start(). This call might fail, in which case the SpecialJob
  instance will have schedules its own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the SpecialJob will schedule its own
  destruction by calling QObject::deleteLater().

  Parameters are set using the Qt property system. More general, or
  constructor parameters are given in the call to
  QGpgME::Protocol::specialJob().

  The result is made available through the result signal, and
  through the read-only result property, the latter of which needs
  to be defined in each SpecialJob subclass.
*/
class QGPGME_EXPORT SpecialJob : public Job
{
  Q_OBJECT
protected:
  explicit SpecialJob(QObject *parent);

public:
  ~SpecialJob();

  /**
    Starts the special operation.
  */
  virtual GpgME::Error start() = 0;

  virtual GpgME::Error exec() = 0;

Q_SIGNALS:
  void result(const GpgME::Error &result, const QVariant &data);
};

}

#endif // __KLEO_SPECIALJOB_H__
/*
  signencryptjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
```

  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

  In addition, as a
 special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two. You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt. If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so. If
  you do not wish to do so, delete this exception statement from
  your version.
*/

```
#ifndef __KLEO_SIGNENCRYPTJOB_H__
#define __KLEO_SIGNENCRYPTJOB_H__

#include "job.h"
#include "qgpgme_export.h"

#ifdef BUILDING_QGPGME
# include "global.h"
# include "context.h"
#else
# include <gpgme++/global.h>
# include <gpgme++/context.h>
#endif

#include <memory>
#include <vector>
#include <utility>
```

```
class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class Key;
class
 SigningResult;
class EncryptionResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous combined signing and encrypting

  To use a SignEncryptJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then start the operation with a
  call to start(). This call might fail, in which case the
  SignEncryptJob instance will have scheduled it's own destruction
  with a call to QObject::deleteLater().

  After result() is emitted, the SignEncryptJob will schedule it's
  own destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT SignEncryptJob : public Job
{
  Q_OBJECT
protected:
  explicit SignEncryptJob(QObject *parent);
public:
  ~SignEncryptJob();

  /**
    Starts the combined signing and encrypting operation. \a signers
    is the list of keys to sign \a plainText with. \a recipients is
    a list of keys to encrypt the signed \a plainText
 to. In both
    lists, empty (null) keys are ignored.

    If \a alwaysTrust is true, validity checking for the
    \em recipient keys will not be performed, but full validity
    assumed for all \em recipient keys without further checks.
  */
  virtual GpgME::Error start(const std::vector<GpgME::Key> &signers,
```

```
        const std::vector<GpgME::Key> &recipients,
        const QByteArray &plainText,
        bool alwaysTrust = false) = 0;

    /*!
      \overload

      If \a cipherText is non-null, the ciphertext is written
      there. Otherwise, it will be delivered in the third argument of
      result().

      \throws GpgME::Exception if starting fails
    */
    virtual void start(const std::vector<GpgME::Key> &signers,
                       const std::vector<GpgME::Key> &recipients,
                       const std::shared_ptr<QIODevice> &plainText,
                       const std::shared_ptr<QIODevice> &cipherText = std::shared_ptr<QIODevice>(),
                        bool alwaysTrust = false) = 0;

    virtual std::pair<GpgME::SigningResult, GpgME::EncryptionResult>
    exec(const std::vector<GpgME::Key> &signers,
         const std::vector<GpgME::Key> &recipients,
         const QByteArray &plainText,
         bool alwaysTrust, QByteArray &cipherText) = 0;

    /*!
      This is a hack to request BASE64 output (instead of whatever
      comes out normally).
    */
    virtual void setOutputIsBase64Encoded(bool) = 0;

    /** Like start but with an additional argument for EncryptionFlags for
     * more flexibility. */
    virtual void start(const std::vector<GpgME::Key> &signers,
                       const std::vector<GpgME::Key> &recipients,
                       const std::shared_ptr<QIODevice> &plainText,
                       const std::shared_ptr<QIODevice> &cipherText = std::shared_ptr<QIODevice>(),
                       const GpgME::Context::EncryptionFlags flags = GpgME::Context::None) = 0;

    /** Like exec
   but with an additional argument for EncryptionFlags for
     * more flexibility. */
    virtual std::pair<GpgME::SigningResult, GpgME::EncryptionResult>
    exec(const std::vector<GpgME::Key> &signers,
         const std::vector<GpgME::Key> &recipients,
         const QByteArray &plainText,
         const GpgME::Context::EncryptionFlags flags, QByteArray &cipherText) = 0;
  Q_SIGNALS:
```

```
    void result(const GpgME::SigningResult &signingresult,
                const GpgME::EncryptionResult &encryptionresult,
                const QByteArray &cipherText, const QString &auditLogAsHtml = QString(),
                const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif // __KLEO_SIGNENCRYPTJOB_H__
/*
    cryptoconfig.h

    This file is part of qgpgme, the Qt API binding for gpgme
    Copyright (c) 2004 Klarlvdalens Datakonsult AB
    Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
    Software engineering by Intevation GmbH

    QGpgME is free software; you can redistribute it and/or
    modify it under the terms of the GNU General Public License as
    published by the Free Software Foundation; either version 2 of the
    License, or (at your option) any later version.

    QGpgME is distributed in the hope that it will be useful,
    but WITHOUT ANY WARRANTY; without even the implied warranty of
    MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
    General Public License for more details.

    You should have received a copy of the GNU General Public License
    along with this program; if not, write to the Free Software
    Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

    In addition, as a special
   exception, the copyright holders give
    permission to link the code of this program with any edition of
    the Qt library by Trolltech AS, Norway (or with modified versions
    of Qt that use the same license as Qt), and distribute linked
    combinations including the two.  You must obey the GNU General
    Public License in all respects for all of the code used other than
    Qt.  If you modify this file, you may extend this exception to
    your version of the file, but you are not obligated to do so.  If
    you do not wish to do so, delete this exception statement from
    your version.
*/

#ifndef CRYPTOCONFIG_H
#define CRYPTOCONFIG_H

#include "qgpgme_export.h"
```

```
#ifdef __cplusplus
/* we read this file from a C compiler, and are only interested in the
* enums... */

#include <QUrl>

#include <vector>

/* Start reading this file from the bottom up :) */

namespace QGpgME
{

/**
* Description of a single option
*/
class QGPGME_EXPORT CryptoConfigEntry
{

public:
#endif /* __cplusplus
 */
  /**
    @li basic       This option should always be offered to the user.
    @li advanced       This option may be offered to advanced users.
    @li expert       This option should only be offered to expert users.
    */
  enum Level { Level_Basic = 0,
               Level_Advanced = 1,
               Level_Expert = 2
             };

  /**
    Type of the argument
    @li ArgType_None       The option is set or not set, but no argument.
    @li ArgType_String       An unformatted string.
    @li ArgType_Int          A signed integer number.
    @li ArgType_UInt       An unsigned integer number.
    @li ArgType_Path       A string that describes the pathname of a file.
    The file does not necessarily need to exist.
    Separated from string so that e.g. a FileDialog can be used.
    @li ArgType_DirPath       A string that describes the pathname of a directory.
    The directory does not necessarily need
 to exist.
    Separated from path so that e.g. a FileDialog can be used which only
    allows directories to be selected.
    @li ArgType_LDAPURL       A LDAP URL
    Separated from URL so that a more specific widget can be shown, hiding the url syntax
```

```
  */
  enum ArgType { ArgType_None = 0,
                 ArgType_String = 1,
                 ArgType_Int = 2,
                 ArgType_UInt = 3,
                 ArgType_Path = 4,
                 /* Nr. 5 was URL historically. */
                 ArgType_LDAPURL = 6,
                 ArgType_DirPath = 7,

                 NumArgType
               };

#ifdef __cplusplus
  virtual ~CryptoConfigEntry() {}

  /**
   * Return the internal name of this entry
   */
  virtual QString name() const = 0;

  /**
   * @return user-visible description of this entry
   */
  virtual QString description() const = 0;

  /**
   * @return "component/group/name"
   */
  virtual QString path()
 const = 0;

  /**
   * @return true if the argument is optional
   */
  virtual bool isOptional() const = 0;

  /**
   * @return true if the entry is readonly
   */
  virtual bool isReadOnly() const = 0;

  /**
   * @return true if the argument can be given multiple times
   */
  virtual bool isList() const = 0;

  /**
```

```
     * @return true if the argument can be changed at runtime
     */
    virtual bool isRuntime() const = 0;

    /**
     * User level
     */
    virtual Level level() const = 0;

    /**
     * Argument type
     */
    virtual ArgType argType() const = 0;

    /**
     * Return true if the option is set, i.e. different from default
     */
    virtual bool isSet() const = 0;

    /**
     * Return value as a bool (only allowed for ArgType_None)
     */
    virtual bool boolValue() const = 0;

    /**
     * Return value as a string (available for all argtypes)
     * The returned string can be empty (explicitly set to empty) or null (not set).
      */
    virtual QString stringValue() const = 0;

    /**
     * Return value as a signed int
     */
    virtual int intValue() const = 0;

    /**
     * Return value as an unsigned int
     */
    virtual unsigned int uintValue() const = 0;

    /**
     * Return value as a URL (only meaningful for Path and URL argtypes)
     */
    virtual QUrl urlValue() const = 0;

    /**
     * Return number of times the option is set (only valid for ArgType_None, if isList())
     */
```

```
  virtual unsigned int numberOfTimesSet() const = 0;

  /**
   * Return value as a list of signed ints
   */
  virtual std::vector<int> intValueList() const = 0;

  /**
   * Return value as a list of unsigned ints
   */
  virtual std::vector<unsigned int> uintValueList() const = 0;

  /**
   * Return value as a list of URLs (only meaningful for Path and URL argtypes, if isList())
   */
  virtual QList<QUrl> urlValueList() const = 0;

  /**
   * Reset an option to its default
value
   */
  virtual void resetToDefault() = 0;

  /**
   * Define whether the option is set or not (only allowed for ArgType_None)
   * #### TODO: and for options with optional args
   */
  virtual void setBoolValue(bool) = 0;

  /**
   * Set string value (allowed for all argtypes)
   */
  virtual void setStringValue(const QString &) = 0;

  /**
   * Set a new signed int value
   */
  virtual void setIntValue(int) = 0;

  /**
   * Set a new unsigned int value
   */
  virtual void setUIntValue(unsigned int) = 0;

  /**
   * Set value as a URL (only meaningful for Path (if local) and URL argtypes)
   */
  virtual void setURLValue(const QUrl &) = 0;
```

```
  /**
   * Set the number of times the option is set (only valid for ArgType_None, if isList())
   */
  virtual void setNumberOfTimesSet(unsigned int) = 0;

  /**
   * Set a new list of signed int values
   */
  virtual void setIntValueList(const std::vector<int> &) = 0;

  /**
    * Set a new list of unsigned int values
   */
  virtual void setUIntValueList(const std::vector<unsigned int> &) = 0;

  /**
   * Set value as a URL list (only meaningful for Path (if all URLs are local) and URL argtypes, if isList())
   */
  virtual void setURLValueList(const QList<QUrl> &) = 0;

  /**
   * @return true if the value was changed
   */
  virtual bool isDirty() const = 0;

  // Design change from here on we are closely bound to one implementation
  // of cryptoconfig. To avoid ABI breaks with every new function we
  // add real functions from now on.

  /**
   * @return a stringValueList.
   */
  QStringList stringValueList() const;
};

/**
* Group containing a set of config options
*/
class QGPGME_EXPORT CryptoConfigGroup
{

public:
  virtual ~CryptoConfigGroup() {}

  /**
   * Return the internal name of this group
   */
```

```
  virtual QString name() const = 0;

  /**
   * Return the name of the icon for this group

  */
  virtual QString iconName() const = 0;

  /**
   * @return user-visible description of this group
   */
  virtual QString description() const = 0;

  /**
   * @return "component/group"
   */
  virtual QString path() const = 0;

  /**
   * User level
   */
  virtual CryptoConfigEntry::Level level() const = 0;

  /**
   * Returns the list of entries that are known by this group.
   *
   * @return list of group entry names.
   **/
  virtual QStringList entryList() const = 0;

  /**
   * @return the configuration object for a given entry in this group
   * The object is owned by CryptoConfigGroup, don't delete it.
   * Groups cannot be nested, so all entries returned here are pure entries, no groups.
   */
  virtual CryptoConfigEntry *entry(const QString &name) const = 0;
};

/**
* Crypto config for one component (e.g. gpg-agent, dirmngr etc.)
*/
class QGPGME_EXPORT CryptoConfigComponent
{

public:
  virtual ~CryptoConfigComponent()
 {}
```

```
  /**
   * Return the internal name of this component
   */
  virtual QString name() const = 0;

  /**
   * Return the name of the icon for this component
   */
  virtual QString iconName() const = 0;

  /**
   * Return user-visible description of this component
   */
  virtual QString description() const = 0;

  /**
   * Returns the list of groups that are known about.
   *
   * @return list of group names. One of them can be "<nogroup>", which is the group where all
   * "toplevel" options (belonging to no group) are.
   */
  virtual QStringList groupList() const = 0;

  /**
   * @return the configuration object for a given group
   * The object is owned by CryptoConfigComponent, don't delete it.
   */
  virtual CryptoConfigGroup *group(const QString &name) const = 0;

};

/**
* Main interface to crypto configuration.
*/
class QGPGME_EXPORT CryptoConfig
{

public:
  virtual ~CryptoConfig() {}

  /**
   * Returns the list
 of known components (e.g. "gpg-agent", "dirmngr" etc.).
   * Use @ref component() to retrieve more information about each one.
   * @return list of component names.
   **/
  virtual QStringList componentList() const = 0;
```

```
  /**
   * @return the configuration object for a given component
   * The object is owned by CryptoConfig, don't delete it.
   */
  virtual CryptoConfigComponent *component(const QString &name) const = 0;

  /**
   * Convenience method to get hold of a single configuration entry when
   * its component, group and name are known. This can be used to read
   * the value and/or to set a value to it.
   *
   * @return the configuration object for a single configuration entry, 0 if not found.
   * The object is owned by CryptoConfig, don't delete it.
   */
  CryptoConfigEntry *entry(const QString &componentName, const QString &groupName, const QString
&entryName) const
  {
     const QGpgME::CryptoConfigComponent *comp = component(componentName);
      const QGpgME::CryptoConfigGroup *group = comp ? comp->group(groupName) : nullptr;
     return group ? group->entry(entryName) : nullptr;
  }

  /**
   * Write back changes
   *
   * @param runtime this parameter is ignored. Changes will always
   * be made with --runtime set.
   */
  virtual void sync(bool runtime) = 0;

  /**
   * Tells the CryptoConfig to discard any cached information, including
   * all components, groups and entries.
   * Call this to free some memory when you won't be using the object
   * for some time.
   * DON'T call this if you're holding pointers to components, groups or entries.
   */
  virtual void clear() = 0;
};

}
#endif /* __cplusplus */
#endif /* CRYPTOCONFIG_H */
/* debug.h - interface to debugging functions
  Copyright (C) 2002, 2004, 2005, 2007 g10 Code GmbH

  This file is part of GPGME.
```

```
  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef DEBUG_H
#define DEBUG_H

#include <string.h>
#ifdef HAVE_STDINT_H
#include <stdint.h>
#endif
#include <errno.h>

#include "gpgme.h"
 /* Required for gpgme_error stuff.  */


/* Indirect stringification, requires __STDC__ to work.  */
#define STRINGIFY(v) #v
#define XSTRINGIFY(v) STRINGIFY(v)


/*
* The debug levels.
*
* Note that TRACE_LOGBUFX uses the current debug level + 1.
*/

#define DEBUG_INIT 1
#define DEBUG_GLOBAL    2
#define DEBUG_CTX 3
#define DEBUG_ENGINE 4
#define DEBUG_DATA 5
#define DEBUG_ASSUAN 6
#define DEBUG_SYSIO 7
```

```
/* Remove path components from filenames (i.e. __FILE__) for cleaner
  logs. */
static inline const char *_gpgme_debug_srcname (const char *file)
                                    GPGME_GCC_A_PURE;

static inline const char *
_gpgme_debug_srcname (const char *file)
{
 const char *s = strrchr (file, '/');
 return s? s+1:file;
}

/* Initialization helper function; see debug.c.  */
int _gpgme_debug_set_debug_envvar (const char *value);

/* Called early to initialize the logging.  */
void _gpgme_debug_subsystem_init (void);

/* Log the formatted string FORMAT at debug
 level LEVEL or higher.  */
int  _gpgme_debug (void **line, int level, int mode,
                const char *func, const char *tagname, const char *tagvalue,
                const char *format, ...) GPGRT_ATTR_PRINTF(7,8);


/* Add the formatted string FORMAT to the debug line *LINE.  */
void _gpgme_debug_add (void **helper, const char *format, ...);

/* Finish construction of *LINE and send it to the debug output
  stream.  */
void _gpgme_debug_end (void **helper);

void _gpgme_debug_buffer (int lvl, const char *const fmt,
    const char *const func, const char *const buffer,
    size_t len);

void _gpgme_debug_frame_begin (void);
int  _gpgme_debug_frame_end (void);

static inline gpgme_error_t
_gpgme_trace_gpgme_error (gpgme_error_t err, const char *file, int line)
{
 _gpgme_debug (NULL, DEBUG_ENGINE, -1, NULL, NULL, NULL,
             "%s:%d: returning error: %s\n",
             _gpgme_debug_srcname (file), line, gpgme_strerror (err));
 return err;
}
```

```
/* Trace support.
  */

/* FIXME: For now.  */
#define _gpgme_debug_trace() 1

#define _TRACE(lvl, name, tag)     \
 int _gpgme_trace_level = lvl;     \
 const char *const _gpgme_trace_func = name;   \
 const char *const _gpgme_trace_tagname = STRINGIFY (tag); \
 void *_gpgme_trace_tag = (void *) (uintptr_t) tag; \
 _gpgme_debug_frame_begin ()

/* Note: We can't protect this with a do-while block.  */
#define TRACE_BEG(lvl, name, tag, ...)                              \
 _TRACE (lvl, name, tag);      \
 _gpgme_debug (NULL, _gpgme_trace_level, 1,                         \
               _gpgme_trace_func, _gpgme_trace_tagname, _gpgme_trace_tag, \
               __VA_ARGS__)

#define TRACE(lvl, name, tag, ...) do {                             \
   _gpgme_debug_frame_begin ();     \
   _gpgme_debug (NULL, lvl, 0, name, STRINGIFY (tag), (void *)(uintptr_t)tag, \
                 __VA_ARGS__);                                      \
   _gpgme_debug_frame_end ();
                         \
 } while (0)


/* Trace a gpg-error and return it.  */
#define TRACE_ERR(err) \
   _trace_err ((err), _gpgme_trace_level, _gpgme_trace_func, __LINE__)
static inline gpg_error_t
_trace_err (gpg_error_t err, int lvl, const char *func, int line)
{
 if (!err)
   _gpgme_debug (NULL, lvl, 3, func, NULL, NULL, "");
 else
   _gpgme_debug (NULL, lvl, -1, NULL, NULL, NULL,
                 "%s:%d: error: %s <%s>\n",
                 func, line,  gpgme_strerror (err), gpgme_strsource (err));
 _gpgme_debug_frame_end ();
 return err;
}

/* Trace a system call result and return it.  */
#define TRACE_SYSRES(res) \
```

```
  _trace_sysres ((res), _gpgme_trace_level, _gpgme_trace_func, __LINE__)
static inline int
_trace_sysres (int res, int lvl, const char *func, int line)
{
 if (res >= 0)
   _gpgme_debug (NULL, lvl, 3, func, NULL, NULL, "result=%d", res);
 else
   _gpgme_debug (NULL, lvl, -1, NULL, NULL, NULL,
                 "%s:%d: error: %s (%d)\n",

       func, line,  strerror (errno), errno);
 _gpgme_debug_frame_end ();
 return res;
}

/* Trace a system call error and return it.  */
#define TRACE_SYSERR(rc) \
  _trace_syserr ((rc), _gpgme_trace_level, _gpgme_trace_func, __LINE__)
static inline int
_trace_syserr (int rc, int lvl, const char *func, int line)
{
 if (!rc)
   _gpgme_debug (NULL, lvl, 3, func, NULL, NULL, "result=0");
 else
   _gpgme_debug (NULL, lvl, -1, NULL, NULL, NULL,
                 "%s:%d: error: %s (%d)\n",
                 func, line, strerror (rc), rc);
 _gpgme_debug_frame_end ();
 return rc;
}

#define TRACE_SUC(...) do {                                     \
   _gpgme_debug (NULL, _gpgme_trace_level, 3, _gpgme_trace_func, NULL, NULL, \
                 __VA_ARGS__);                                  \
   _gpgme_debug_frame_end ();                                   \
 } while (0)

#define TRACE_LOG(...) do {                                     \
   _gpgme_debug
 (NULL, _gpgme_trace_level, 2,                          \
                 _gpgme_trace_func, _gpgme_trace_tagname, _gpgme_trace_tag, \
                 __VA_ARGS__);                                  \
 } while (0)

#define TRACE_LOGBUF(buf, len) do {                             \
   _gpgme_debug_buffer (_gpgme_trace_level, "%s: check: %s", \
                        _gpgme_trace_func, buf, len);          \
 } while (0)
```

```
#define TRACE_LOGBUFX(buf, len) do {                                    \
  _gpgme_debug_buffer (_gpgme_trace_level+1, "%s: check: %s",       \
                       _gpgme_trace_func, buf, len); \
 } while (0)

#define TRACE_SEQ(hlp,...) do {           \
  _gpgme_debug (&(hlp), _gpgme_trace_level, 2, _gpgme_trace_func,          \
                       _gpgme_trace_tagname, _gpgme_trace_tag, __VA_ARGS__); \
 } while (0)

#define TRACE_ADD0(hlp,fmt) \
 _gpgme_debug_add (&(hlp), fmt)
#define TRACE_ADD1(hlp,fmt,a) \
 _gpgme_debug_add (&(hlp),
 fmt, (a))
#define TRACE_ADD2(hlp,fmt,a,b) \
 _gpgme_debug_add (&(hlp), fmt, (a), (b))
#define TRACE_ADD3(hlp,fmt,a,b,c) \
 _gpgme_debug_add (&(hlp), fmt, (a), (b), (c))
#define TRACE_END(hlp,fmt) \
 _gpgme_debug_add (&(hlp), fmt); \
 _gpgme_debug_end (&(hlp))

#define TRACE_ENABLED(hlp) (!!(hlp))

/* And finally a simple macro to trace the location of an error code.
  This macro is independent of the other trace macros and may be used
  without any preconditions.  */
#define trace_gpg_error(e) \
 _gpgme_trace_gpgme_error (gpg_error (e), __FILE__, __LINE__)


#endif /* DEBUG_H */
#include "qgpgme/abstractimportjob.h"
/*
  qgpgmechangeexpiryjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.
```

```
  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMECHANGEOWNERTRUSTJOB_H__
#define __QGPGME_QGPGMECHANGEOWNERTRUSTJOB_H__

#include "changeownertrustjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
{

class QGpgMEChangeOwnerTrustJob
#ifdef Q_MOC_RUN
  : public ChangeOwnerTrustJob
#else
  : public _detail::ThreadedJobMixin<ChangeOwnerTrustJob>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
   void slotFinished();
#endif
public:
  explicit QGpgMEChangeOwnerTrustJob(GpgME::Context *context);
  ~QGpgMEChangeOwnerTrustJob();
```

```
  /* from ChangeOwnerTrustJob */
  GpgME::Error start(const GpgME::Key &key, GpgME::Key::OwnerTrust trust) Q_DECL_OVERRIDE;
};
}

#endif // __QGPGME_QGPGMECHANGEOWNERTRUSTJOB_H__
cython
/* parsetlv.h -  TLV functions definitions
* Copyright (C) 2012 g10 Code GmbH
*
* This file is free software; you can redistribute it and/or modify
* it under the terms of the GNU Lesser General Public License as
* published by the Free Software Foundation; either version 2.1 of
* the License, or (at your option) any later version.
*
* This file is distributed in the hope that it will be useful,
* but WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
* GNU Lesser General Public License for more details.
*
* You should have received a copy of the GNU Lesser General Public License
* along with this program; if not, see <https://www.gnu.org/licenses/>.
*/

#ifndef PARSETLV_H
#define PARSETLV_H

/* ASN.1 constants.  */
#define ASN1_CLASS_UNIVERSAL   0
#define ASN1_CLASS_APPLICATION 1
#define ASN1_CLASS_CONTEXT     2
#define ASN1_CLASS_PRIVATE     3
#define ASN1_TAG_INTEGER       2
#define ASN1_TAG_OBJECT_ID
    6
#define ASN1_TAG_SEQUENCE     16


/* Object used with parse_tlv.  */
struct tlvinfo_s
{
 int cls;           /* The class of the tag.  */
 int tag;           /* The tag.  */
 int is_cons;       /* True if it is a constructed object.  */
 int is_ndef;       /* True if the object has an indefinite length.  */
 size_t length;     /* The length of the value.  */
 size_t nhdr;       /* The number of octets in the header (tag,length). */
};
```

```
typedef struct tlvinfo_s tlvinfo_t;

/*-- parsetlv.c --*/
int _gpgme_parse_tlv (char const **buffer, size_t *size, tlvinfo_t *ti);
#define parse_tlv(a,b,c) _gpgme_parse_tlv ((a), (b), (c))



#endif /*PARSETLV_H*/
/*
  decryptjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_DECRYPTJOB_H__
#define __KLEO_DECRYPTJOB_H__

#include "job.h"
```

```
#include <memory>

class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class DecryptionResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous decrypters

  To use a DecryptJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress()
 and result()
  signals to suitable slots and then start the decryption with a
  call to start(). This call might fail, in which case the
  DecryptJob instance will have scheduled it's own destruction with
  a call to QObject::deleteLater().

  After result() is emitted, the DecryptJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT DecryptJob : public Job
{
   Q_OBJECT
protected:
   explicit DecryptJob(QObject *parent);
public:
   ~DecryptJob();

   /**
     Starts the decryption operation. \a cipherText is the data to
     decrypt.
   */
   virtual GpgME::Error start(const QByteArray &cipherText) = 0;

   /*!
     \overload

     If \a plainText is non-null, the plaintext is written
     there. Otherwise, it will be delivered in the second argument
     of result().
```

```
    \throws GpgME::Exception if starting fails
  */
  virtual void start(const std::shared_ptr<QIODevice> &cipherText, const std::shared_ptr<QIODevice>
 &plainText = std::shared_ptr<QIODevice>()) = 0;

  virtual GpgME::DecryptionResult exec(const QByteArray &cipherText,
                                       QByteArray &plainText) = 0;

Q_SIGNALS:
  void result(const GpgME::DecryptionResult &result, const QByteArray &plainText, const QString
&auditLogAsHtml = QString(), const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif // __KLEO_DECRYPTJOB_H__
/*
 data.h - wraps a gpgme data object
 Copyright (C) 2003,2004 Klarlvdalens Datakonsult AB

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_DATA_H__
#define __GPGMEPP_DATA_H__

#include "global.h"
#include "key.h"

#include <sys/types.h> // for size_t,
 off_t
#include <cstdio> // FILE
```

```
#include <algorithm>
#include <memory>

namespace GpgME
{

class DataProvider;
class Error;

class GPGMEPP_EXPORT Data
{
  struct Null {
 Null() {}
 };
public:
  /* implicit */ Data(const Null &);
  Data();
  explicit Data(gpgme_data_t data);

  // Memory-Based Data Buffers:
  Data(const char *buffer, size_t size, bool copy = true);
  explicit Data(const char *filename);
  Data(const char *filename, off_t offset, size_t length);
  Data(std::FILE *fp, off_t offset, size_t length);
  // File-Based Data Buffers:
  explicit Data(std::FILE *fp);
  explicit Data(int fd);
  // Callback-Based Data Buffers:
  explicit Data(DataProvider *provider);

  static const Null null;

  const Data &operator=(Data other)
  {
     swap(other);
     return *this;
  }

  void swap(Data &other)
  {
     using std::swap;
     swap(this->d, other.d);
  }

  bool isNull() const;

  enum Encoding {
     AutoEncoding,
```

```
    BinaryEncoding,
    Base64Encoding,
    ArmorEncoding,
    MimeEncoding,
    UrlEncoding,
    UrlEscEncoding,
    Url0Encoding,
};
Encoding encoding() const;
Error setEncoding(Encoding encoding);

enum Type {
    Invalid,
    Unknown,
    PGPSigned,
    PGPOther,
    PGPKey,
    CMSSigned,
    CMSEncrypted,
    CMSOther,
    X509Cert,
    PKCS12,
    PGPEncrypted,
    PGPSignature,
};
Type type() const;

char *fileName() const;
Error setFileName(const char *name);

ssize_t read(void *buffer, size_t length);
ssize_t write(const void *buffer, size_t length);
off_t seek(off_t offset, int whence);

/* Convenience function to do a seek (0, SEEK_SET).  */
Error rewind();

/** Try to parse the data to a key object using the
 * Protocol proto. Returns an empty list on error.*/
std::vector<Key> toKeys(const Protocol proto = Protocol::OpenPGP) const;


/** Return a copy of the data as std::string. Sets seek pos to 0 */
std::string toString();

class Private;
Private *impl()
{
```

```
    return d.get();
  }
  const Private *impl() const
  {
    return d.get();
  }
private:
  std::shared_ptr<Private> d;
};

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(Data)

#endif // __GPGMEPP_DATA_H__
/*
  keylistjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception,
 the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
```

```
*/

#ifndef __KLEO_KEYLISTJOB_H__
#define __KLEO_KEYLISTJOB_H__

#include "job.h"
#include "qgpgme_export.h"

#ifdef BUILDING_QGPGME
# include "key.h"
#else
# include <gpgme++/key.h>
#endif

#include <vector>

namespace GpgME
{
class Error;
class KeyListResult;
}

class QStringList;

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous key listers

  To use a KeyListJob, first
 obtain an instance from the
  CryptoBackend implementation, connect the nextKey(), progress()
  and result() signals to suitable slots and then start the key
  listing with a call to start(). This call might fail, in which
  case the KeylistJob instance will have schedules it's own
  destruction with a call to QObject::deleteLater().

  During keylisting, you will receive new key objects through the
  nextKey() signal as they arrive. After result() is emitted, the
  KeyListJob will schedule it's own destruction by calling
  QObject::deleteLater().
*/
class QGPGME_EXPORT KeyListJob : public Job
{
   Q_OBJECT
protected:
   explicit KeyListJob(QObject *parent);
```

```
public:
  ~KeyListJob();

  /**
    Starts the keylist operation. \a pattern is a list of patterns
    used to restrict the list of keys returned. Empty patterns are
    ignored. If \a pattern is empty or contains only empty strings,
    all keys are returned (however, the backend is free to truncate

  the result and should do so; when this happens, it will be
    reported by the reult object).

    If \a secretOnly is true, only keys for which the secret key is
    also available are returned. Use this if you need to select a
    key for signing.
  */
  virtual GpgME::Error start(const QStringList &patterns, bool secretOnly = false) = 0;

  virtual GpgME::KeyListResult exec(const QStringList &patterns, bool secretOnly, std::vector<GpgME::Key>
&keys) = 0;

  /** Add a flag to the keylistmode used. */
  virtual void addMode(GpgME::KeyListMode mode) = 0;

Q_SIGNALS:
  void nextKey(const GpgME::Key &key);
  void result(const GpgME::KeyListResult &result, const std::vector<GpgME::Key> &keys =
std::vector<GpgME::Key>(), const QString &auditLogAsHtml = QString(), const GpgME::Error &auditLogError =
GpgME::Error());
};

}

#endif // __KLEO_KEYLISTJOB_H__
/*
 gpgsignkeyeditinteractor.h - Edit Interactor to change the owner trust of an OpenPGP key
 Copyright (C) 2008 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.
```

```
 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA
 02110-1301, USA.
*/

#ifndef __GPGMEPP_GPGSIGNKEYEDITINTERACTOR_H__
#define __GPGMEPP_GPGSIGNKEYEDITINTERACTOR_H__

#include <editinteractor.h>

#include <string>
#include <vector>

namespace GpgME
{

class Key;
class UserID;

class GPGMEPP_EXPORT GpgSignKeyEditInteractor : public EditInteractor
{
public:
  enum SignOption {
     Exportable = 0x1,
     NonRevocable = 0x2,
     Trust = 0x4
  };

  GpgSignKeyEditInteractor();
  ~GpgSignKeyEditInteractor();

  void setCheckLevel(unsigned int checkLevel);
  void setUserIDsToSign(const std::vector<unsigned int> &userIDsToSign);
  void setKey(const Key &key);
  void setSigningOptions(int options);

  /* Set this if it is ok to overwrite an existing signature. In that
   * case the context has to have the flag "extended-edit" set to 1 through
   * Context::setFlag before calling edit.*/
  void setDupeOk(bool value);
```

```
private:
  const char *action(Error &err) const override;
  unsigned int nextState(unsigned
 int statusCode, const char *args, Error &err) const override;

private:
  class Private;
  Private *const d;
};

} // namespace GpgME

#endif // __GPGMEPP_GPGSIGNKEYEDITINTERACTOR_H__
#include "qgpgme/adduseridjob.h"
{
  "type": "signature",
  "base64":       false,
  "data": "*"
}
/*
 gpggencardkeyinteractor.h - Edit Interactor to generate a key on a card
 Copyright (C) 2017 by Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_GPGGENCARDKEYEDITINTERACTOR_H__
#define
 __GPGMEPP_GPGGENCARDKEYEDITINTERACTOR_H__

#include <editinteractor.h>
```

```
#include <string>
#include <memory>

namespace GpgME
{

class GPGMEPP_EXPORT GpgGenCardKeyInteractor: public EditInteractor
{
public:
  /** Edit interactor to generate a key on a smartcard.
   *
   * The \a serialnumber argument is intended to safeguard
   * against accidentally working on the wrong smartcard.
   *
   * The edit interactor will fail if the card did not match.
   *
   * @param serialnumber: Serialnumber of the intended card.
   **/
  explicit GpgGenCardKeyInteractor(const std::string &serialnumber);
  ~GpgGenCardKeyInteractor();

  /** Set the key sizes for the subkeys (default 2048) */
  void setKeySize(int size);

  void setNameUtf8(const std::string &name);
  void setEmailUtf8(const std::string &email);

  void setDoBackup(bool value);
  void setExpiry(const std::string &timeString);

  enum Algo {
     RSA = 1,
     ECC = 2
   };
  void setAlgo(Algo algo);

  std::string backupFileName() const;

private:
  const char *action(Error &err) const override;
  unsigned int nextState(unsigned int statusCode, const char *args, Error &err) const override;

private:
  class Private;
  std::shared_ptr<Private> d;
};

} // namespace GpgME
```

```
#endif // __GPGMEPP_GPGGENCARDKEYEDITINTERACTOR_H__
/* sys-util.h - System utilities not generally used.
* Copyright (C) 2013 g10 Code GmbH
*
* This file is part of GPGME.
*
* GPGME is free software; you can redistribute it and/or modify it
* under the terms of the GNU Lesser General Public License as
* published by the Free Software Foundation; either version 2.1 of
* the License, or (at your option) any later version.
*
* GPGME is distributed in the hope that it will be useful, but
* WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
* Lesser General Public License for more details.
*
* You should have received a copy of the GNU Lesser General Public
* License along with this program; if not, see <https://www.gnu.org/licenses/>.
*/

#ifndef SYS_UTIL_H
#define SYS_UTIL_H

/*-- {posix,w32}-util.c --*/
int _gpgme_set_default_gpg_name (const char *name);
int _gpgme_set_default_gpgconf_name (const char *name);
int _gpgme_set_override_inst_dir (const
 char *dir);

char *_gpgme_get_gpg_path (void);
char *_gpgme_get_gpgconf_path (void);

int _gpgme_access (const char *path_utf8, int mode);

#ifdef HAVE_W32_SYSTEM
const char *_gpgme_get_inst_dir (void);
void _gpgme_w32_cancel_synchronous_io (HANDLE thread);
/* See CreateProcessA returns true on success */
int _gpgme_create_process_utf8 (const char *application_name_utf8,
                                char *command_line_utf8,
                                LPSECURITY_ATTRIBUTES lpProcessAttributes,
                                LPSECURITY_ATTRIBUTES lpThreadAttributes,
                                BOOL bInheritHandles,
                                DWORD dwCreationFlags,
                                void *lpEnvironment,
                                char *working_directory_utf8,
                                LPSTARTUPINFOA lpStartupInfo,
```

LPPROCESS_INFORMATION lpProcessInformation);
#endif

#endif /* SYS_UTIL_H */
2011-12-02 Werner Koch <wk@g10code.com>

NB: ChangeLog files are no longer manually maintained. Starting
on December 1st, 2011 we put change information only in the GIT
commit log, and generate a top-level ChangeLog file from logs at
"make dist". See doc/HACKING for details.

2011-05-12 Marcus Brinkmann <marcus@g10code.com>

* gpgme.texi (I/O Callback Example): Fix example code.

* gpgme.texi (Generating Keys): Fix OpenPGP parameters and reference
GPG and GPGSM manual.

2010-01-05 Werner Koch <wk@g10code.com>

* gpgme.texi (Changing Passphrases): New.

2009-07-21 Werner Koch <wk@g10code.com>

* uiserver.texi (UI Server Encrypt): Add --expect-sign option to
PREP_ENCRYPT.

2009-06-16 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Result Management): New section.

2009-06-16 Werner Koch <wk@g10code.com>

* gpgme.texi (Exporting Keys): Document gpgme_op_export_keys.
(Importing Keys): Document gpgme_op_import_keys.
(Data Buffer Meta-Data): Document URL encodings.

2009-05-28
 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Library Version Check): Document selftest error.
(Creating Contexts): Likewise.

2009-05-18 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Encrypting a Plaintext): Document
GPGME_ENCRYPT_NO_ENCRYPT_TO.

2009-05-05 Marcus Brinkmann <marcus@g10code.de>

 * gpgme.texi (Engine Information): Replace path by file_name.

2008-11-28 Werner Koch <wk@g10code.com>

 * gpgme.texi (Listing Keys): Change description of the return
 value to match the code. Spotted by Colin Leroy.

2008-10-15 Werner Koch <wk@g10code.com>

 * uiserver.texi (Miscellaneous UI Server Commands): Add option
 --protocol to the SENDER command.

2008-07-17 Werner Koch <wk@g10code.com>

 * module-overview.sk: New.

2008-07-04 Werner Koch <wk@g10code.com>

 * gpgme.texi (Algorithms): Add a hint on symmetric only encryption.

2008-06-27 Marcus Brinkmann <marcus@g10code.de>

 * gpgme.texi (Cancellation): Document gpgme_cancel_async.

2008-06-25
 Werner Koch <wk@g10code.com>

 * gpgme.texi (Listing Keys): Updated example to the current API.
 Noted by Nico Schottelius.

2008-06-05 Werner Koch <wk@g10code.com>

 * uiserver.texi (Miscellaneous UI Server Commands): Describe
 START_CONFDIALOG.

2008-06-04 Werner Koch <wk@g10code.com>

 * gpgme.texi: Use @copying command. Change license to
 GPLv3. Include protocol specis from GpgOL and GPGEx. Minor
 cleanups.

2008-03-11 Marcus Brinkmann <marcus@g10code.de>

 * gpgme.texi (File Based Data Buffers): Document the need for
 blocking operations.
 (Callback Based Data Buffers): Likewise.

2008-03-05 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Library Version Check): Rename snippet function to
init_gpgme.
(I/O Callback Example): Call it here.

2008-01-28 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Document that data encoding affects some output data
objects now.

2007-09-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Protocols and Engines):
Document GPGME_PROTOCOL_UNKNOWN.

2007-09-11 Werner Koch <wk@g10code.com>

* gpgme.texi (I/O Callback Example): Typo fix.

2007-08-07 Werner Koch <wk@g10code.com>

* gpgme.texi (Verify): Describe chain_model.

2007-07-12 Werner Koch <wk@g10code.com>

* gpgme.texi (Library Version Check): Add remark that the socket
layer will get initialized.

2007-06-05 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Advanced Key Editing): New section.

2007-05-21 Werner Koch <wk@g10code.com>

* Makefile.am (online): New target.

2007-05-18 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Error Strings): Fix documentation of
gpgme_strerror_r.

2006-11-01 Moritz Schulte <moritz@g10code.com>

* gpgme.texi (Data Buffer I/O Operations): Fixed entry for
gpgme_data_seek: OFFSET is not a pointer; some s/whence/offset/.

2006-09-25 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Destroying Data Buffers): Clarify that
gpgme_data_release_and_get_mem destroys DH unconditionally.

2005-03-24
Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Library Version Check): Make example code compatible
to W32 systems.

2006-06-21 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Passphrase Callback): Fix inverted condition in
description.

2005-12-20 Werner Koch <wk@g10code.com>

* gpgme.texi (Verify): Document pka_trust.

2005-12-06 Werner Koch <wk@g10code.com>

* gpgme.texi (Key Management): Updated to match the fixes for
subkey fingerprints and theg secret flag.

2005-10-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Destroying Data Buffers): Document gpgme_free.

2005-10-02 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Management): Add the new member notations of
gpgme_sig_key_t.
(Key Listing Mode): Document GPGME_KEYLIST_MODE_SIG_NOTATIONS.

2005-10-01 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Enclose all return parameters of deftypefuns in
curly brackets.

* gpgme.texi (Signature Notation Data): New
section.
(Verify): Added more about the notation data structure.

2005-09-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Data Buffer I/O Operations, Data Buffer Meta-Data):
New subsections.

* gpgme.texi: Replace plaintext_filename with file_name.

* gpgme.texi (Key Management): Document is_qualified.

2005-07-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Decrypt): Add plaintext_filename to
gpgme_decrypt_result_t.
(Verify): Likewise for gpgme_verify_result_t.

2005-06-03 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Add information about new fields in
gpgme_signature_t.

* gpgme.texi (Decrypt): Add gpgme_recipient_t.

2005-05-28 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Listing Mode): Fix return type of
gpgme_set_keylist_mode.
Reported by "Sergio" <ml_sergico@virgilio.it>.

2005-04-28 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Included Certificates): Document
GPGME_INCLUDE_CERTS_DEFAULT.

2005-01-12 Marcus
Brinkmann <marcus@g10code.de>

* gpgme.texi (Engine Configuration): New section.
(Crypto Engine): New subsection.

2004-12-07 Marcus Brinkmann <marcus@g10code.de>

* lesser.texi (Library Copying): Change from @appendixsec to
@appendix.
* gpgme.texi (Features): Change reference to GPL to one to LGPL.

* Makefile.am: Change license to LGPL.
(gpgme_TEXINFOS): Replace gpl.texi with lesser.texi.

* gpgme.texi: Change license to LGPL (also for documentation of
GPGME's license).
* lesser.texi: New file.
* gpl.texi: File removed.

* gpgme.texi (Creating Contexts): Fix cut&paste error. Reported
by Noel Torres <envite@rolamasao.org>.

2004-09-30 Marcus Brinkmann <marcus@g10code.de>

* Makefile.am (gpgme_TEXINFOS): Remove fdl.texi.
* gpgme.texi: Do not include fdl.texi. Change license to GPL.
* fdl.texi: File removed.

2004-09-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Management): Change type of keylist_mode in
gpgme_key_t to gpgme_keylist_mode_t.

2004-09-28
Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Passphrase Callback): Fix last change.

2004-09-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Passphrase Callback): Document
GPG_ERR_NOT_IMPLEMENTED.

* gpgme.texi: Update copyright year for tex version.

2004-07-29 Moritz Schulte <moritz@g10code.com>

* gpgme.texi (Verify): Fix gpgme_get_key example (ancient
force_update argument was still there).

2004-06-08 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Listing Keys): Elaborate on the length restrictions
on search patterns.

* gpgme.texi (Decrypt and Verify): Document the NO_DATA error
code.
(Verify): Document the relationship between gpgme_op_verify_result
and the decrypt and verify operations.

2004-05-21 Marcus Brinkmann <marcus@g10code.de>

* gpgme.text (Verify): Document GPG_ERR_CERT_REVOKED status.

* gpgme.texi (Decrypt): Add note about new field wrong_key_usage
of gpgme_decrypt_result_t.

* gpgme.texi (Key Management): Add
note about new field
keylist_mode of gpgme_key_t.

2004-04-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Correct type of member wrong_key_usage.

2004-03-29 Moritz Schulte <moritz@duesseldorf.ccc.de>

* gpgme.texi (Verify): Fix type of gpgme_op_verify_result.
* gpgme.texi (Key Listing Mode): Typo fix.

2004-03-23 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Library Version Check): Fix the instruction when to
set the locale.

2004-03-03 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (I/O Callback Example Qt): New section by Marc Mutz.

2004-02-24 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (cancellation): New section.

2004-02-17 Werner Koch <wk@gnupg.org>

* gpgme.texi (Key Listing Mode): Doc KEYLIST_MODE_VALIDATE.

2004-02-06 Moritz Schulte <mo@g10code.com>

* gpgme.texi: A couple of small fixes regarding the Largfile
Support section.

2004-02-01 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Largefile Support): New
section.

2004-01-13 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Management): Fix exportable field.

2003-12-25 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Management): Rename member class in

gpgme_key_sig_t to sig_class.
(Creating a Signature): Likewise for gpgme_signature_t.

2003-12-23 Moritz Schulte <mo@g10code.com>

* gpgme.texi (Listing Keys): Minor clarification for
gpgme_get_key.

2003-10-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Signal Handling): New section.

2003-09-14 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Multi Threading): Correct documentation on memory
synchronization requirement.

* gpgme.texi (Locale): New section.
(Multi Threading): Set locale in example.

2003-09-13 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Error Strings): Add gpgme_strerror_r.

2003-09-13 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Multi Threading): Update documentation.

2003-09-03 Marcus Brinkmann <marcus@g10code.de>

*
gpgme.texi (Header): We don't use the assuan namespace anymore.
Document new thread options.

2003-08-14 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Creating a Signature): Change type of member class
to unsigned int.

2003-08-04 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Get error code from SIG->status in the code
for gpgme_get_sig_status.

2003-07-31 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Management): Add can_authenticate flag.

* gpgme.texi (Listing Keys): Document GPG_ERR_AMBIGUOUS_NAME for
gpgme_get_key.

2003-07-29 Marcus Brinkmann <marcus@g10code.de>

* Makefile.am (EXTRA_DIST): Remove variable.

* gpgme.texi (Encrypting a Plaintext): Bad passphrase is only
possible with symmetric encryption, change the wording to reflect
that.

* gpgme.texi (Creating a Signature): Document
GPG_ERR_UNUSABLE_SECKEY.

* gpgme.texi (Encrypting a Plaintext): Mention encrypt and sign
operations in result function.
(Creating
a Signature): Likewise.

2003-07-23 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Listing Mode): Remove word duplication.
(Listing Keys): Remove mentioning of force argument.
(Verify): Don't mention r_stat. Fix some typos.
(Decrypt and Verify): Correct info how to get the result. Don't
mention r_stat.
(Manipulating Data Buffers): Fix documentation of return value.
(Listing Keys): Update examples.
(Decrypt): Result might also be available when operation failed.
(Verify): Result might also be available when operation failed.
All spotted by Stphane Corthsy.

2003-07-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Error Sources): Fix cut and paste error.

2003-07-09 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Management): Clarify difference between can_sign
and can_certify.
(Information About Keys): Likewise for GPGME_ATTR_CAN_SIGN and
GPGME_ATTR_CAN_CERTIFY.

2003-07-08 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Progress
Meter Callback): Change return type of
gpgme_progress_cb_t to void.

2003-06-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Add 2003 to copyright notice.

* gpgme.texi (Header): Fix name space documentation on
libgpg-error.

2003-06-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Multi Threading): Remove reference to
gpgme_recipients_t.

2003-06-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Crypto Operations): Rename gpgme_invalid_user_id_t
to gpgme_invalid_key_t.

2003-06-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Change error codes to GPG_ERR_* variants.
(Error Handling): Rewritten.

2003-05-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Exporting Keys): Change and document prototypes.
Add new gpgme_op_export_ext and gpgme_op_export_ext_start
variants.
(Selecting Recipients): Section removed.
(Encrypting a Plaintext): Change prototypes and document the
changes.

2003-05-28 Marcus Brinkmann <marcus@g10code.de>

*
gpgme.texi (Exporting Keys): Change argument type from
gpgme_recipient_t to gpgme_user_id_t.
(Encrypting a Plaintext): Likewise.
(Selecting Recipients): Rewritten.

2003-05-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Protocol Selection): Do not use @acronym in @node
because that breaks texi2dvi.

* gpgme.texi (Passphrase Callback): Document new prototype.

2003-05-18 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Header): Remove Gpgme as namespace prefix. Add
_GPGME to namespace prefix.
* gpgme.texi (Multi Threading): Add note about link order.

2003-05-04 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Listing Keys): Document what happens if key is not
found.

* gpgme.texi (Importing Keys): Fix cut and paste error.

2003-04-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Encrypting a Plaintext): Remove reference to
gpgme_get_op_info.
(Detailed Results): Subsection removed.

* gpgme.texi (Key Listing Mode): Add GPGME_KEYLIST_MODE_SIGS.
(Manipulating
Keys): Add obsoleteness note.
(Key Signatures): Likewise.
(Information About Keys): Likewise.
(Key Management): Add new data types GpgmeSubkey, GpgmeKeySig,
GpgmeUserID, and all the information about GpgmeKey.

2003-04-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Listing Keys): Remove force_update argument from
gpgme_get_key.

* gpgme.texi (Trust Item Management): Add data members of
GpgmeTrustItem type.
(Information About Trust Items): Add note about obsoleteness.
(Manipulating Trust Items): Add gpgme_trust_item_ref and
gpgme_trust_item_unref.

2003-04-28 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Rewritten to take into account new and
deprecated functions and data types.

* gpgme.texi (Decrypt): Descript gpgme_op_decrypt_result and
GpgmeDecryptResult.

2003-04-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Encrypting a Plaintext): Add info about

GpgmeEncryptResult and gpgme_op_encrypt_result.

* gpgme.texi
(Creating a Signature): Add info about
GpgmeNewSignature, GpgmeSignResult and gpgme_op_sign_result.
(Crypto Operations): Add GpgmeInvalidUserID.
(Algorithms): New chapter.

* gpgme.texi (Deleting Keys): Document
GPGME_Ambiguous_Specification.
(Error Values): Remove GPGME_Invalid_Type and GPGME_Invalid_Mode.
Add GPGME_Unknown_Reason, GPGME_Not_Found,
GPGME_Ambiguous_Specification, GPGME_Wrong_Key_Usage,
GPGME_Key_Revoked, GPGME_Key_Expired, GPGME_No_CRL_Known,
GPGME_CRL_Too_Old, GPGME_Policy_Mismatch, GPGME_No_Secret_Key,
GPGME_Key_Not_Trusted, GPGME_Issuer_Missing, GPGME_Chain_Too_Long,
GPGME_Unsupported_Algorithm, GPGME_Sig_Expired,
GPGME_Bad_Signature, GPGME_No_Public_Key.

2003-04-25 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Importing Keys): Change GPGME_IMPORT_PRIVATE to
GPGME_IMPORT_SECRET.

* gpgme.texi (Importing Keys): Remove note about gpgme_get_op_info.
(Detailed Results): Remove note about import.

* gpgme.texi (Importing Keys): Add documentation
for
GpgmeImportStatus, GpgmeImportResult and gpgme_op_import_result.

* gpgme.texi (Generating Keys): Fix documentation of public and
secret arguments.

2003-04-24 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Generating Keys): Document changed gpgme_op_genkey
and new gpgme_op_genkey_result function. Document
GpgmeGenKeyResult data type.

* gpgme.texi (Error Values): Rename GPGME_No_Passphrase to
GPGME_Bad_Passphrase.
* gpgme.texi (Decrypt): Likewise.
(Decrypt and Verify): Likewise.
(Creating a Signature): Likewise.
(Encrypting a Plaintext): Likewise.

* gpgme.texi (Error Values): Rename GPGME_No_Recipients to

GPGME_No_UserID and GPGME_Invalid_Recipient to
GPGME_Invalid_UserID.
(Encrypting a Plaintext): Likewise.

* gpgme.texi (Error Values): Remove GPGME_Busy and GPGME_No_Request.
(Listing Keys): Likewise.
(Listing Trust Items): Likewise.

2003-02-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Cancelling an Operation): Removed.
(Passphrase
Callback): Document new type for GpgmePassphraseCb.

2003-01-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Engine Information): Rename member part to
file_name.

* gpgme.texi (Protocols and Engines): Document
gpgme_get_protocol_name.

* gpgme.texi (Engine Information): Rewritten.

2003-01-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (I/O Callback Interface): Document new even
GPGME_EVENT_START.
(Waiting For Completion): Document new possible return values.
(I/O Callback Interface): Document return type of GpgmeIOCb.

2003-01-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Hooking Up Into Idle Time): Section removed.

2002-12-24 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Drop R_STAT argument in gpgme_op_verify.
* gpgme.texi (Decrypt and Verify): Likewise for
gpgme_op_decrypt_verify.

2002-12-23 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Information About Keys): Document that
GPGME_ATTR_IS_SECRET is not representable
as a string anymore.

2002-12-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Signatures): New section.
(Listing Keys): Add gpgme_get_key.

2002-12-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Memory Based Data Buffers): New subsection.
(File Based Data Buffers): Likewise.
(Callback Based Data Buffers): Likewise.
(Manipulating Data Buffers): Update interfaces. Add
gpgme_data_seek.
* gpgme.texi (Engine Version Check): Remove gpgme_check_engine.

2002-11-21 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Document the new interface.

2002-11-19 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Generating Keys): Document new argument to
gpgme_op_genkey.

2002-11-05 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Fix prototype of gpgme_get_sig_key.
Reported by Miguel Coca <e970095@zipi.fi.upm.es>.

2002-08-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Selecting Signers): Fix reference count.

2002-08-21
Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Header): Document name space.

2002-08-20 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Importing Keys): Document gpgme_op_import_ext.

* gpgme.texi (Importing Keys): Undocument EOF.

2002-08-14 Werner Koch <wk@gnupg.org>

* gpgme.texi (Information About Keys): Changed GPGME_ATTR_TYPE.

2002-07-25 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Deleting Keys): Say that secret keys might not be deleted.

2002-07-25 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Information About Keys): Document (badly) the new key attributes.

* gpgme.texi (Manipulating Data Buffers): Mention that backend tries to detect encoding automatically.

2002-07-03 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Run Control): Update this section.
(Waiting For Completion): Likewise for this subsection.
(Cancelling an Operation): Likewise for this subsection.
(Using External Event Loops): New subsection with several subsubsections.

2002-06-28
Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Multi Threading): Remove item about the need to synchronize anything against gpgme_wait (except gpgme_wait itself).

2002-06-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Information About Keys): Fix documentation for IDX.
(Information About Trust Items): Likewise.

2002-06-26 Werner Koch <wk@gnupg.org>

* gpgme.texi (Importing Keys): Document the return value -1 of gpgme_op_import.

2002-06-20 Werner Koch <wk@gnupg.org>

* gpgme.texi (Verify): Explain the new whatidx variable.

2002-06-10 Werner Koch <wk@gnupg.org>

* gpgme.texi (Verify): Document attribute GPGME_ATTR_ERRTOK.

2002-06-04 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Multi Threading): Document new autodetection.

2002-06-04 Marcus Brinkmann <marcus@g10code.de>

* Makefile.am (DISTCLEANFILES): New variable.

2002-05-26 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Some typographical corrections
throughout.

2002-05-09 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Using Automake): New section.

2002-05-09 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Multi Threading): Escape { and }.

2002-05-09 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Overview): Replace note about thread-safeness.
(Multi Threading): New section.

2002-05-03 Werner Koch <wk@gnupg.org>

* gpgme.texi (Manipulating Data Buffers): Changed some data types
to void*.
(Protocol Selection): Added gpgme_get_protocol.
(Verify): Updated to include the new attribute functions and
status codes.

2002-04-27 Werner Koch <wk@gnupg.org>

* gpgme.texi (Manipulating Data Buffers): New type GpgmeDataEncoding.

2002-04-23 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Passphrase Callback): Document that either return
argument can be NULL.
(Progress Meter Callback): Likewise.

2002-04-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Passphrase Callback): Fix small
typo. Document the
new function gpgme_get_passphrase_cb.
(Progress Meter Callback): Document the new function
gpgme_get_progress_cb.

2002-04-16 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Creating a Signature): Fix function name. Reported
by Wichert Ackerman <wichert@debian.org>.

2002-03-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (direntry): End index entry with a full stop.
Patch submitted by Jose Carlos Garcia Sogo <jsogo@debian.org>.

2002-03-17 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Detailed Results): Fix syntax error in last change.

2002-03-08 Werner Koch <wk@gnupg.org>

* gpgme.texi (Detailed Results): Import does also return info.

2002-03-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Encrypting a Plaintext): Document symmetric
encryption.

2002-03-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Error Strings): Add example.
* gpgme.texi (Listing Keys): Likewise.

2002-03-03 Marcus Brinkmann <marcus@g10code.de>

*
gpgme.texi (Information About Keys): Document GPGME_ATTR_EXPIRE.

2002-03-03 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Verify): Document verification of normal and
cleartext signatures.

2002-02-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Listing Keys): Document gpgme_op_keylist_ext_start.

2002-02-27 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Encrypting a Plaintext): Document
GPGME_Invalid_Recipients.
(Error Values): Likewise.

2002-02-26 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Encrypting a Plaintext): Document
gpgme_op_encrypt_sign and gpgme_op_encrypt_sign_start.

2002-02-25 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Creating a Signature): Add a note about
certificates to include.
(Included Certificates): New section.

2002-02-09 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Detailed Results): Remove literal tags.
(Generating Keys): Update documentation.

* gpgme.texi (Generating Keys):
Fix syntax error.

2002-02-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Waiting For Completion): Adjust doc to changes in
the code.

2002-02-06 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Key Listing Mode): Update documentation.

2002-01-31 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Generating Keys): Document error at creation
failure.

2002-01-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Deleting Keys): Document new error values.

2002-01-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Importing Keys): Add reference to gpgme_get_op_info.

2002-01-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Some spell checking.

2002-01-30 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: Add all the gpgme_op_*_start functions.

Fill the concept index with many, many entries.

2002-01-29 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Run Control): New section.
(Verify): Document gpgme_get_notation.
(More Information):
New section describing gpgme_get_op_info.

2002-01-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Passphrase callback): Change GpgmePassphraseCb's
R_HD type from void* to void**.

2002-01-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Creating data buffers): Change
gpgme_data_new_from_filepart's LENGTH type from off_t to size_t.

2002-01-22 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi (Generating keys): New subsection.
(Exporting keys): Likewise.
(Importing keys): Likewise.
(Deleting keys): Likewise.

2002-01-16 Marcus Brinkmann <marcus@g10code.de>

* gpgme.texi: g10Code -> g10 Code

* gpgme.texi (Top): Complete detailmenu.

* gpgme.texi: Convert embarrassing cruft to the real thing.

2002-01-16 Marcus Brinkmann <marcus@g10code.de>

* ChangeLog: New file.
* gpgme.texi: Likewise.
* gpl.texi: Likewise.
* fdl.texi: Likewise.
* Makefile.am (info_TEXINFOS): New variable.
(gpgme_TEXINFOS): Likewise.

Copyright (C) 2002, 2003, 2004, 2005,
2006, 2007, 2008, 2009, 2010,
2011 g10 Code GmbH

This file is free software; as a special exception the author gives

unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
/* data.h - Internal data object abstraction interface.
  Copyright (C) 2002, 2004, 2005 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA. */

#ifndef DATA_H
#define DATA_H

#if HAVE_CONFIG_H
#include <config.h>
#endif

#ifdef HAVE_SYS_TYPES_H
include <sys/types.h>
#endif
#include
 <limits.h>
#include <stdint.h>

#include "gpgme.h"

/* Read up to SIZE bytes into buffer BUFFER from the data object with
  the handle DH. Return the number of characters read, 0 on EOF and
  -1 on error. If an error occurs, errno is set. */
typedef gpgme_ssize_t (*gpgme_data_read_cb) (gpgme_data_t dh,
                                             void *buffer,

```
                                size_t size);

/* Write up to SIZE bytes from buffer BUFFER to the data object with
  the handle DH.  Return the number of characters written, or -1 on
  error.  If an error occurs, errno is set.  */
typedef gpgme_ssize_t (*gpgme_data_write_cb) (gpgme_data_t dh,
                                const void *buffer,
                                size_t size);

/* Set the current position from where the next read or write starts
  in the data object with the handle DH to OFFSET, relative to
  WHENCE.  */
typedef gpgme_off_t (*gpgme_data_seek_cb)
 (gpgme_data_t dh,
                                gpgme_off_t offset,
                                int whence);

/* Release the data object with the handle DH.  */
typedef void (*gpgme_data_release_cb) (gpgme_data_t dh);

/* Get the FD associated with the handle DH, or -1.  */
typedef int (*gpgme_data_get_fd_cb) (gpgme_data_t dh);

struct _gpgme_data_cbs
{
 gpgme_data_read_cb read;
 gpgme_data_write_cb write;
 gpgme_data_seek_cb seek;
 gpgme_data_release_cb release;
 gpgme_data_get_fd_cb get_fd;
};

struct gpgme_data
{
 struct _gpgme_data_cbs *cbs;
 gpgme_data_encoding_t encoding;
 unsigned int propidx;  /* Index into the property table.  */

#ifdef PIPE_BUF
#define BUFFER_SIZE PIPE_BUF
#else
#ifdef _POSIX_PIPE_BUF
#define BUFFER_SIZE _POSIX_PIPE_BUF
#else
#define BUFFER_SIZE 512
#endif
#endif
 char pending[BUFFER_SIZE];
```

```
int pending_len;

/* File name of the data object.  */
char *file_name;

/* Hint on the to be expected total size of the data.
 */
gpgme_off_t size_hint;

union
{
  /* For gpgme_data_new_from_fd.  */
  int fd;

  /* For gpgme_data_new_from_stream.  */
  FILE *stream;

  /* For gpgme_data_new_from_estream.  */
  gpgrt_stream_t e_stream;

  /* For gpgme_data_new_from_cbs.  */
  struct
  {
    gpgme_data_cbs_t cbs;
    void *handle;
  } user;

  /* For gpgme_data_new_from_mem.  */
  struct
  {
    char *buffer;
    const char *orig_buffer;
    /* Allocated size of BUFFER.  */
    size_t size;
    size_t length;
    gpgme_off_t offset;
  } mem;

  /* For gpgme_data_new_from_read_cb.  */
  struct
  {
    int (*cb) (void *, char *, size_t, size_t *);
    void *handle;
  } old_user;
 } data;
};
```

```
/* The data property types.  */
typedef enum
 {
   DATA_PROP_NONE = 0,   /* Dummy property. */
   DATA_PROP_BLANKOUT    /* Do not return the held data.  */
 } data_prop_t;



/* Return the data object's serial number for handle DH.  */
uint64_t _gpgme_data_get_dserial
 (gpgme_data_t dh);

/* Set an internal property of a data object.  */
gpg_error_t _gpgme_data_set_prop (gpgme_data_t dh, uint64_t dserial,
                                  data_prop_t name, int value);

/* Get an internal property of a data object.  */
gpg_error_t _gpgme_data_get_prop (gpgme_data_t dh, uint64_t dserial,
                                  data_prop_t name, int *r_value);

/* Create a new data object.  */
gpgme_error_t _gpgme_data_new (gpgme_data_t *r_dh,
         struct _gpgme_data_cbs *cbs);

void _gpgme_data_release (gpgme_data_t dh);

/* Get the file descriptor associated with DH, if possible.  Otherwise
   return -1.  */
int _gpgme_data_get_fd (gpgme_data_t dh);

/* Get the size-hint value for DH or 0 if not available.  */
gpgme_off_t _gpgme_data_get_size_hint (gpgme_data_t dh);



#endif /* DATA_H */
-----BEGIN PGP PRIVATE KEY BLOCK-----

lQOYBFrsKEkBCADKw4Wt8J6M/88qD8PO6lSMCxH1cpwH8iK0uPaFFYsJkkXo7kWf
PTAtrV+REqF/o80dvYcdLvRsV21pvncZz/HXLu1yQ18mC3XObrKokbdgrTTKA5XE
BZkNsqyaMMJauT18H4hYkSg62/tTdO1cu/zWv/LFf7Xyn6+uA74ovXCJlO1s0N2c
PShtr98QRzPMf2owgVk37JnDNp4gGVDGHxSZOuUwxgYAZYnA8SFc+c+3ZrQfY870
+O4j3Mz4p7yD13AwP4buQLBsb/icxekeQCqpRJhLH9f7MdEcGXa1x36RcEkHdu+M
yJ392eMgD+dKNfRCtyTPhjZTxvbNELIBYICfABEBAAEAB/wLJ0gyMjs2fFfT83wM
5Lzz2yQIwV4t3bblBAujdHTqeN5Zmsm/oakFyjSokULK96Kv0R4ej9eoIgMFvxFk
HRkrggxTrbsNJ7I6QcKYHTPeIIj318ykNL6fj0WJUcdPIENukXl5jbqNyk3/4D2y
TTDySyq6jHTgvMH4K4KJUSpglvSJPntTk9RhuFGHAF+sNR9atygDYctAaERMRtSg
LCoSt/AoX5GRMlQjXT9oqQjwSQoZyF4s8HMC8wdTFIE/E0L4IVdHVp8sz2UszNtT
```

W/evmCA+KVruKjRH/Fhrq4hHkEamW28+j4L6uAyagONP7BONs+S5Oo2zTT9+tV2R
ILTZBADdgLuAgF6C5Lu9jCF6DfFgaT/uafMyQNkEGNlxOHMWHTgLHe475V2eG9gA
amd4yXKyEFKU1PWnvlGuicQSGdzVcwmq61msvXgYD0FK3LP3yWzKnE4X1tzrC9Vp
/uHJxKjewCuyt1f5in919v+T8TbUxBYKC0zX/qWtX+10cTx77QQA6leqhToJ95Yc
u4UBrKMEO+y2v8Svb3LG7yI5oY8tkw0EkJ/kpZ8xTAfZYCe6fXdvVE3PHg2lrxyc
Wv/EU3QY/qA3G82mbXYeJ2jNZaTNYo4MylMrt4Mx25x4ke7JlsE8SVrQ+4CrHkqp
OjSIa7fppLrQ78uW980AtN8NNQGrlTsD/A9aoA60Igxy1Q3K2uSyDCyjLknv57ym
ZSBD3/t7m0l6Q6gbdfhNGosT+Hd4y3actqEqzXZHW2VG4dKZ/wRNkxtSm9adU9vs
EHyzxjb6mKIH32zAG5TaFT20hC+NK6lsyHr9UE2ZrS6ma2sLxGW2O40hqNsdD+5m
NrqeBc2I/js1PMK0EHRlc3RAZXhhbXBsZS5vcmeJAVQEEwEIAD4WIQTUFzW5Ejb9
uIIEjFojAWNe7/DLBQUCWuwoSQIbAwUJA8JnAAULCQgHAgYVCgkICwIEFgIDAQIe
AQIXgAAKCRAjAWNe7/DLBf9kB/wOQ/S60HGwFq07W9N01HWULyhHKoMmcHL6rfZ6
4oDqLxolPSasz7WAMW1jN4qtWJ0mFzwO83V6kaBe+wF6Kqir6udFSBW9rPcFg6/V
ZXPltT0a6uacIHq6DyQ5iMW4YQWbVy9OR2rNGkYo1JCBR0XdRJYCSX3yB4TWv/eX
nZ37/WjmiTOIZh35rjs+NuU/S5JPDfAp2/k70DevQeBsv+UjVXjWpNTZmPbvDnd9
95uSmC6UY4hzyP84ORYMYn9n1QAR0goxDN6UunOf9Rlp1oMzdxMool/d1MlCxg2h
3jheuhv7lgUF4KpvHOuEPXQ7UO417E0TYcDZ1J8Nsv87SZeEnQOYBFrsKEkBCADj
oEBhG/QPqZHg8VyoD1xYRAWGxyDJkX/GrSs6yE+x2hk5FoQCajxKa/d4AVxOnJpd
whAfeXeSNaql5Ejgzax+Tdj9BV6vtGVJVv0pO7bgAiZxkA6RHxtNqhpPnPQoXvUz
kzpRgpuL+Nj4yIg7z1ITH6KQH4u5SI9vd+j/8i9Taz67pdZwuJjac8qBuJHjzAo1
bjYctFYUSG5pbmMQyNLySzgiNkFa4DajODlt3RuqVGP316Fk+Sy2+60tC/HlX8jg
MyMONfOGBQx6jk8tvAphS/LAqrrNepnagIyLUGKU+L8cB2g1PGGp2biBFWqZbudZ
oyRBet/0yH/zirBdQJw1ABEBAAEAB/4lN3gXOI4OuoOcsvHak4pebx61Mt0YP9cT
qZASIBqxok5x8E28pFh/tYfkYdqRCtdNYZOnxcEoUWh5j6nfwZkEnJ9P/T8GPNk7
pMKnKXmExi05b5uGHD8nU1rSbf/YkvAF0vpbxd4/RDxbbtQhbUwGzusSI+pBLM0w
5TreEB+vRGBc2gOvXXOtKLNEa7M9rH2EwbAkP3jOGGwgk6adxbQdBcRxq4merqhL
YrVz73bCj8TDc0fsNJyIaZZJ++ejfBFYavsF1pvx9z7FNFi8rSXoiB3SBtaWGfhr
bwNaMZrDc7TRIq/fgGaL6g//bzcWrr1YaHXZ10Bgx6UymDOlYkCpBADm0Hv46sPw
07SO8+IACcaQliOto1pndOPwTimCeo58/7rf8I2a5uuJloGrnPwAX65bKDnUALp6
X3lnXRNMhnB3Uewx4i00LQmjsxhJfQiGLpMv0j58tn64s7GqQzGVV1JKcQm992RV
jFOydyjZ+K4LGWEOITG/bZrMEVNGCM+OnQQA/Haz8xN0NFSlq7tyfFc0pkx/TiCX
xGfBqbO0wU2b5GMnZbY/06HENpidIzpa231VQaw5/nPTvfhlLKW1iGAkc148cX1q
lL9w2ksXuaHR3LXud2VcfVTIdxU/7h7u1dD/85+c0+7jlGObD9cXKxlM6OjpIJz1
l5/1h3C5S0TuxHkEAL/3BGihkhNfv1Xx0rWu0/732usX/nE/A9C26hGu41FUf3fp
0ilonKpKZUEwWt5hWSEFCSrznNVekiO0rxvuu3RVegvzThPNU4Pf4JZtJpRVhvUQ
d9ulxJw7V9rs75uNBatTNC0kXuGoXhehw4Bn93xa67gYGd3LfrH+oT0GCDpTSHCJ
ATwEGAEIACYWIQTUFzW5Ejb9uIIEjFojAWNe7/DLBQUCWuwoSQIbDAUJA8JnAAAK
CRAjAWNe7/DLBf0pCACPp5hBuUWngu2Hqvg+tNiujfsiYzId3MffFxEk3CbXeHcJ
5F32NDJ9PYCnra4L8wSv+NZt9gIa8lFwoFSFQCjzH7KE86XcV3MhfdJTNb/+9CR7
Jq3e/4Iy0N5ip7PNYMCyakcAsxvsNCJKrSaDuYe/OAoTXRBtgRWE2uyT315em02L
kr+2Cc/Qk6H+vlNOHGRgnpI/OZZjnUuUfBUvMGHr1phW+y7aeymC9PnUGdViRdJe
23nntMSDA+0/I7ESO9JsWvJbyBmuiZpu9JjScOjYH9xpQLqRNyw4WHpZriN69F0t
9Mmd7bM1+UyPgbPEr0iWMeyctYsuOLeUyQKMscDT
=hkUm
-----END
 PGP PRIVATE KEY BLOCK-----
{
  "manifest_version": 2,

```
  "name": "Browsertests for gpgmejs",
  "description": "Run the browsertests.",
  "version": "0.1",
  "content_security_policy": "default-src 'self' filesystem:",
  "browser_action": {
   "default_icon": "testicon.png",
   "default_popup": "popup.html"
  },
  "permissions": ["nativeMessaging", "activeTab"]
 }
/* cJSON.h
* Copyright (c) 2009 Dave Gamble
*
* Permission is hereby granted, free of charge, to any person obtaining a copy
* of this software and associated documentation files (the "Software"), to deal
* in the Software without restriction, including without limitation the rights
* to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
* copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in
* all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
* IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
* FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
* AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
* LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
 OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
* THE SOFTWARE.
*
* SPDX-License-Identifier: MIT
*
* Note that this code has been modified from the original code taken
* from cjson-code-58.zip.
*/

#ifndef cJSON_h
#define cJSON_h

#ifdef __cplusplus
extern "C"
{
#if 0 /*(to make Emacs auto-indent happy)*/
}
#endif
```

```
#endif

/* cJSON Types: */
#define cJSON_False  0
#define cJSON_True   1
#define cJSON_NULL   2
#define cJSON_Number 3
#define cJSON_String 4
#define cJSON_Array  5
#define cJSON_Object 6

#define cJSON_IsReference 256

/* The cJSON structure: */
typedef struct cJSON
{
 /* next/prev allow you to walk array/object chains. Alternatively,
    use GetArraySize/GetArrayItem/GetObjectItem */
 struct cJSON *next, *prev;

 /* An array or object item will have a child pointer pointing to a
    chain of the items in the array/object. */
 struct cJSON *child;

 int type;  /* The type of the item, as above. */

 char *valuestring; /*
 The item's string, if type==cJSON_String */
 int valueint;  /* The item's number, if type==cJSON_Number */
 double valuedouble; /* The item's number, if type==cJSON_Number */

 /* The item's name string, if this item is the child of, or is in
    the list of subitems of an object. */
 char *string;
} cJSON;

typedef struct cJSON *cjson_t;

/* Macros to test the type of an object.  */
#define cjson_is_boolean(a) (!((a)->type & ~1))
#define cjson_is_false(a)   ((a)->type == cJSON_False)
#define cjson_is_true(a)    ((a)->type == cJSON_True)
#define cjson_is_null(a)    ((a)->type == cJSON_NULL)
#define cjson_is_number(a)  ((a)->type == cJSON_Number)
#define cjson_is_string(a)  ((a)->type == cJSON_String)
#define cjson_is_array(a)   ((a)->type == cJSON_Array)
#define cjson_is_object(a)  ((a)->type == cJSON_Object)
```

```
/* Supply a block of JSON, and this returns a cJSON object you can
  interrogate. Call cJSON_Delete when finished. */
extern cJSON *cJSON_Parse(const char *value,
 size_t *r_erroff);

/* Render a cJSON entity to text for transfer/storage. Free the char*
  when finished. */
extern char  *cJSON_Print(cJSON *item);

/* Render a cJSON entity to text for transfer/storage without any
  formatting. Free the char* when finished. */
extern char  *cJSON_PrintUnformatted(cJSON *item);

/* Delete a cJSON entity and all subentities. */
extern void   cJSON_Delete(cJSON *c);

/* Returns the number of items in an array (or object). */
extern int    cJSON_GetArraySize(cJSON *array);

/* Retrieve item number "item" from array "array". Returns NULL if
  unsuccessful. */
extern cJSON *cJSON_GetArrayItem(cJSON *array,int item);

/* Get item "string" from object. Case insensitive. */
extern cJSON *cJSON_GetObjectItem(cJSON *object,const char *string);

/* These calls create a cJSON item of the appropriate type. */
extern cJSON *cJSON_CreateNull(void);
extern cJSON *cJSON_CreateTrue(void);
extern cJSON *cJSON_CreateFalse(void);
extern cJSON *cJSON_CreateBool(int
 b);
extern cJSON *cJSON_CreateNumber(double num);
extern cJSON *cJSON_CreateString(const char *string);
extern cJSON *cJSON_CreateStringConvey (char *string);
extern cJSON *cJSON_CreateArray(void);
extern cJSON *cJSON_CreateObject(void);

/* These utilities create an Array of count items. */
extern cJSON *cJSON_CreateIntArray(const int *numbers,int count);
extern cJSON *cJSON_CreateFloatArray(const float *numbers,int count);
extern cJSON *cJSON_CreateDoubleArray(const double *numbers,int count);
extern cJSON *cJSON_CreateStringArray(const char **strings,int count);

/* Append item to the specified array. */
extern void cJSON_AddItemToArray(cJSON *array, cJSON *item);

/* Append item to the specified object. */
```

```
extern cJSON *cJSON_AddItemToObject(cJSON *object, const char *name,
                            cJSON *item);
extern cJSON *cJSON_AddNullToObject (cJSON *object, const char *name);
extern cJSON *cJSON_AddTrueToObject (cJSON *object, const char *name);
extern cJSON *cJSON_AddFalseToObject
 (cJSON *object, const char *name);
extern cJSON *cJSON_AddBoolToObject (cJSON *object, const char *name, int b);
extern cJSON *cJSON_AddNumberToObject (cJSON *object, const char *name,
                              double num);
extern cJSON *cJSON_AddStringToObject (cJSON *object, const char *name,
                              const char *string);

/* Append reference to item to the specified array/object. Use this
  when you want to add an existing cJSON to a new cJSON, but don't
  want to corrupt your existing cJSON. */
extern void cJSON_AddItemReferenceToArray(cJSON *array, cJSON *item);
extern void cJSON_AddItemReferenceToObject(cJSON *object,
                                  const char *string,cJSON *item);

/* Remove/Detach items from Arrays/Objects. */
extern cJSON *cJSON_DetachItemFromArray(cJSON *array,int which);
extern void   cJSON_DeleteItemFromArray(cJSON *array,int which);
extern cJSON *cJSON_DetachItemFromObject(cJSON *object,const
 char *string);
extern void   cJSON_DeleteItemFromObject(cJSON *object,const char *string);

/* Update array items. */
extern void cJSON_ReplaceItemInArray(cJSON *array,int which,cJSON *newitem);
extern void cJSON_ReplaceItemInObject(cJSON *object,
                               const char *string, cJSON *newitem);

/* Duplicate a cJSON item */
extern cJSON *cJSON_Duplicate(cJSON *item,int recurse);

/* Duplicate will create a new, identical cJSON item to the one you
  pass, in new memory that will need to be released. With recurse!=0,
  it will duplicate any children connected to the item.  The
  item->next and ->prev pointers are always zero on return from
  Duplicate. */

/* ParseWithOpts allows you to require (and check) that the JSON is
  null terminated, and to retrieve the pointer to the final byte
  parsed. */
extern cJSON *cJSON_ParseWithOpts(const char *value,
                            const char **return_parse_end,

        int require_null_terminated,
                            size_t *r_erroff);
```

```
extern void cJSON_Minify(char *json);

/* When assigning an integer value, it needs to be propagated to
  valuedouble too. */
#define cJSON_SetIntValue(object,val) \
 ((object)?(object)->valueint=(object)->valuedouble=(val):(val))

#ifdef __cplusplus
}
#endif

#endif /* cJSON_h */
#include "qgpgme/dataprovider.h"
#include "qgpgme/defaultkeygenerationjob.h"
#include "qgpgme/listallkeysjob.h"
/*  qgpgmequickjob.h

   This file is part of qgpgme, the Qt API binding for gpgme
   Copyright (c) 2017 Intevation GmbH
   Copyright (c) 2020 g10 Code GmbH
   Software engineering by Ingo Klcker <dev@ingo-kloecker.de>

   QGpgME is free software; you can redistribute it and/or
   modify it under the terms of the GNU General Public License as
   published by the Free Software Foundation; either version 2 of the
   License, or (at your option) any later version.

   QGpgME is distributed in the hope that it will be useful,
   but WITHOUT ANY WARRANTY; without even the implied warranty of
   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
   General Public License for more details.

   You should have received a copy of the GNU General Public License along
   with this program; if not, write to the Free Software Foundation, Inc.,
   51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a special exception, the copyright holders
  give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
```

```
*/
#ifndef QGPGME_QGPGMEQUICKJOB_H
#define QGPGME_QGPGMEQUICKJOB_H

#include "quickjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
{

/**
* Interface to the modern key manipulation functions.
*/
class QGpgMEQuickJob
#ifdef Q_MOC_RUN
  : public QuickJob
#else
  : public _detail::ThreadedJobMixin<QuickJob>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEQuickJob(GpgME::Context
 *context);
  ~QGpgMEQuickJob();

  void startCreate(const QString &uid,
                   const char *algo,
                   const QDateTime &expires = QDateTime(),
                   const GpgME::Key &key = GpgME::Key(),
                   unsigned int flags = 0) Q_DECL_OVERRIDE;
  void startAddUid(const GpgME::Key &key, const QString &uid) Q_DECL_OVERRIDE;
  void startRevUid(const GpgME::Key &key, const QString &uid) Q_DECL_OVERRIDE;
  void startAddSubkey(const GpgME::Key &key, const char *algo,
                      const QDateTime &expires = QDateTime(),
                      unsigned int flags = 0) Q_DECL_OVERRIDE;
  void startRevokeSignature(const GpgME::Key &key, const GpgME::Key &signingKey,
                            const std::vector<GpgME::UserID> &userIds = std::vector<GpgME::UserID>())
Q_DECL_OVERRIDE;
};

}
#endif
```

```
{
  "type": "ciphertext",
  "base64":       false
}
/*
 keygenerationresult.h - wraps a gpgme keygen result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_KEYGENERATIONRESULT_H__
#define
 __GPGMEPP_KEYGENERATIONRESULT_H__

#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <memory>

namespace GpgME
{

class Error;

class GPGMEPP_EXPORT KeyGenerationResult : public Result
{
public:
  KeyGenerationResult();
  KeyGenerationResult(gpgme_ctx_t ctx, int error);
```

```
  KeyGenerationResult(gpgme_ctx_t ctx, const Error &error);
  explicit KeyGenerationResult(const Error &err);

  const KeyGenerationResult &operator=(KeyGenerationResult other)
  {
    swap(other);
    return *this;
  }

  void swap(KeyGenerationResult &other)
  {
    Result::swap(other);
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  GPGMEPP_DEPRECATED bool primaryKeyGenerated() const
  {
    return isPrimaryKeyGenerated();
  }
  GPGMEPP_DEPRECATED bool subkeyGenerated() const
  {
    return isSubkeyGenerated();
  }
  bool isPrimaryKeyGenerated() const;
  bool
 isSubkeyGenerated() const;
  const char *fingerprint() const;

private:
  class Private;
  void init(gpgme_ctx_t ctx);
  std::shared_ptr<Private> d;
};

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(KeyGenerationResult)

#endif // __GPGMEPP_KEYGENERATIONRESULT_H__
/*
  adduseridjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
```

```
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_ADDUSERIDJOB_H__
#define __KLEO_ADDUSERIDJOB_H__

#include "job.h"

#include <QtCore/QString>

namespace GpgME
{
class Error;
class Key;
}

namespace QGpgME
{

/**
  @short An abstract base class to asynchronously add UIDs to OpenPGP keys
```

```
  To use a AddUserIDJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals
 to suitable slots and then start the job with a call
  to start(). This call might fail, in which case the AddUserIDJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the AddUserIDJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT AddUserIDJob : public Job
{
  Q_OBJECT
protected:
  explicit AddUserIDJob(QObject *parent);
public:
  ~AddUserIDJob();

  /**
    Starts the operation. \a key is the key to add the UID to. \a
    name, \a email and \a comment are the components of the user id.
  */
  virtual GpgME::Error start(const GpgME::Key &key, const QString &name,
                             const QString &email, const QString &comment = QString()) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &result, const QString &auditLogAsHtml = QString(), const GpgME::Error
&auditLogError = GpgME::Error());
};

}

#endif // __KLEO_ADDUSERIDJOB_H__
/* wait.h - Definitions for the wait queue interface.
  Copyright (C) 2000 Werner Koch (dd9jn)
  Copyright (C) 2001, 2002, 2003, 2004 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
```

```
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef WAIT_H
#define WAIT_H

#include "gpgme.h"
#include "sema.h"

struct fd_table
{
 struct
 io_select_fd_s *fds;
 size_t size;
};
typedef struct fd_table *fd_table_t;

/* Wait items are hooked into the io_select_fd_s to connect an fd with
  a callback handler.  */
struct wait_item_s
{
 gpgme_ctx_t ctx;
 gpgme_io_cb_t handler;
 void *handler_value;
 int dir;
};

/* A registered fd handler is removed later using the tag that
  identifies it.  */
struct tag
{
 /* The context for which the fd was registered.  */
 gpgme_ctx_t ctx;

 /* The index into the fd table for this context.  */
 int idx;

 /* This is used by the wrappers for the user event loop.  */
 void *user_tag;
};


void _gpgme_fd_table_init (fd_table_t fdt);
void _gpgme_fd_table_deinit (fd_table_t fdt);
```

```
gpgme_error_t _gpgme_add_io_cb (void *data, int fd, int dir,
        gpgme_io_cb_t fnc, void *fnc_data, void **r_tag);
void _gpgme_remove_io_cb (void *tag);
void _gpgme_wait_private_event_cb (void *data, gpgme_event_io_t type,
       void *type_data);
void _gpgme_wait_global_event_cb (void *data, gpgme_event_io_t
 type,
      void *type_data);

gpgme_error_t _gpgme_wait_user_add_io_cb (void *data, int fd, int dir,
       gpgme_io_cb_t fnc, void *fnc_data,
       void **r_tag);
void _gpgme_wait_user_remove_io_cb (void *tag);
void _gpgme_wait_user_event_cb (void *data, gpgme_event_io_t type,
    void *type_data);

gpgme_error_t _gpgme_run_io_cb (struct io_select_fd_s *an_fds, int checked,
    gpgme_error_t *err);


/* Session based interfaces require to make a distinction between IPC
  errors and operational errors.  To glue this into the old
  interface, I/O handlers (esp. the status handler) are called with a
  struct as the opaque value that contains the handlers opaque value
  but also a field for the operational error to be returned.  */
struct io_cb_data
{
 /* If this is the first field, the old internal code will still work.  */
 void *handler_value;

 /* The I/O callback can pass an operational error here.  */
 gpgme_error_t op_err;
};

#endif /* WAIT_H */
{
   "op": "verify",
   "data": "-----BEGIN PGP MESSAGE-----
\n\nowGbwMvMwCSoW1RzPCOz3ITxtFASQ/SbgPceiTk5+Qo+qaUlqVwd51kYBJkY+sUU\nWRb8d52wO1Hp7
fs8mxCYHlYmkAaDKQ0MQKDAwF5QlJqWWlSUmqKbmpuYmaObmpec\nn5KZl+5QkF6gl5yfC6RyM3NTlU
XAGrgZ+HMSS9MzQApyU71Ki0sUggtLU1OrUhV8\nU2WkMkpKCoqt9PXLy8v10vNK9fKL0vUL8nMykyv1G
bg4BWBuYP7OMN9VdOep8HTD\nKQLOd+7+Cshs6jVTfsMwT3sje7Pmui779IU/657Lb575u9z/LgA=\n=iqJ/\n--
---END PGP MESSAGE-----\n\n"
}
/*
   qgpgmebackend.h
```

```
  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2005 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEBACKEND_H__
#define __QGPGME_QGPGMEBACKEND_H__

#include <QString>

#include "protocol.h"

class QString;
template <typename T_Key, typename T_Value> class QMap;

namespace QGpgME
{
class CryptoConfig;
class Protocol;
class GpgCardJob;
```

```
class QGpgMEBackend
{
public:
  QGpgMEBackend();
  ~QGpgMEBackend();

  QString name() const;
  QString displayName()
 const;

  CryptoConfig *config() const;
  GpgCardJob *gpgCardJob() const;

  Protocol *openpgp() const;
  Protocol *smime() const;
  Protocol *protocol(const char *name) const;

  static const char OpenPGP[];
  static const char SMIME[];

  bool checkForOpenPGP(QString *reason = Q_NULLPTR) const;
  bool checkForSMIME(QString *reason = Q_NULLPTR) const;
  bool checkForProtocol(const char *name, QString *reason) const;

  bool supportsOpenPGP() const
  {
     return true;
  }
  bool supportsSMIME() const
  {
     return true;
  }
  bool supportsProtocol(const char *name) const;

  const char *enumerateProtocols(int i) const;

private:
  mutable QGpgME::CryptoConfig *mCryptoConfig;
  mutable Protocol *mOpenPGPProtocol;
  mutable Protocol *mSMIMEProtocol;
};

}

#endif // __QGPGME_QGPGMEBACKEND_H__
2011-12-02  Werner Koch  <wk@g10code.com>
```

NB: ChangeLog files are no longer manually maintained. Starting
on December 1st, 2011 we put change information only in the GIT
commit log, and generate a top-level ChangeLog file from logs at
"make dist". See doc/HACKING for details.

2011-04-06 Werner Koch <wk@g10code.com>

* gpg-error.m4: Update from current libgpg-error repo.

2010-05-07 Werner Koch <wk@g10code.com>

* libassuan.m4: Update from libassuan svn.

2009-11-10 Marcus Brinkmann <marcus@g10code.de>

* libassuan.m4: Fix LIBASSUAN_VERSION.

2006-06-08 Marcus Brinkmann <marcus@g10code.de>

* pth.m4: Add --all to pth-config invocation.

2006-02-22 Marcus Brinkmann <marcus@g10code.de>

* pth.m4: Fix code generation (required for Max OS X).
Submitted by Emanuele Giaquinta <exg@gentoo.org>.

2005-11-17 Marcus Brinkmann <marcus@g10code.de>

* glib-2.0.m4: New file.

2004-12-28 Werner Koch <wk@g10code.com>

* pth.m4: Changed quoting for use with automake 1.9.

2004-09-14
 Marcus Brinkmann <marcus@g10code.de>

* pth.m4: Disable _ac_pth_line, and don't fail if Pth is not
found.

* glibc21.m4: New file.
* gpg-error.m4: New file.
* pth.m4: New file.

Copyright (C) 2004, 2005, 2009, 2010, 2011 g10 Code GmbH

This file is free software; as a special exception the author gives

unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
#include "qgpgme/qgpgmenewcryptoconfig.h"
/*
  qgpgmechangepasswdjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2010 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two. You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt. If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so. If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMECHANGEPASSWDJOB_H__
#define __QGPGME_QGPGMECHANGEPASSWDJOB_H__

#include "changepasswdjob.h"

#include "threadedjobmixin.h"

```
namespace QGpgME
{

class QGpgMEChangePasswdJob
#ifdef Q_MOC_RUN
  : public ChangePasswdJob
#else
  : public _detail::ThreadedJobMixin<ChangePasswdJob>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
  void slotFinished();
#endif
public:
   explicit QGpgMEChangePasswdJob(GpgME::Context *context);
  ~QGpgMEChangePasswdJob();

  /* from ChangePasswdJob */
  GpgME::Error start(const GpgME::Key &key) Q_DECL_OVERRIDE;
};

}

#endif // __QGPGME_QGPGMECHANGEPASSWDJOB_H__
{
  "op": "encrypt",
  "keys": ["alpha@example.net", "victor@example.org"],
  "signing_keys": ["A0FF4590BB6122EDEF6E3C542D727CC768697734"],
  "data": "Hello world",
  "armor": true,
  "always-trust": true
}
{
 "option":      {
        "name": "default-key",
        "argname":      "NAME"
 }
}
# -*- mode: org -*-
#+TITLE: What Was New in the GPGME Python Bindings and Documentation
#+AUTHOR: Ben McGinnes
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
```

#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}
#+LATEX_HEADER: \author{Ben McGinnes <ben@gnupg.org>}

* What Was New
 :PROPERTIES:
 :CUSTOM_ID: new-stuff
 :END:

Version:	0.0.1
GPGME Version:	1.13.0
Author:	Ben McGinnes <ben@gnupg.org>
Author GPG Key:	DB4724E6FA4286C92B4E55C4321E4E2373590E5D
Language:	Australian English, British English
xml:lang:	en-AU, en-GB, en

The following are all the past /What's New/ sections for the Python
Bindings HOWTO and other documentation.

** What Was New in GPGME 1120
  :PROPERTIES:

 :CUSTOM_ID: gpgme-1-12-0
  :END:

The most obviously new point for those reading this guide is this
section on other new things, but thats hardly important. Not given
all the other things which spurred the need for adding this section
and its subsections.

*** New in GPGME 1120
   :PROPERTIES:
   :CUSTOM_ID: new-stuff-1-12-0
   :END:

There have been quite a number of additions to GPGME and the Python
bindings to it since the last release of GPGME with versions 1.11.0
and 1.11.1 in April, 2018.

The bullet points of new additiions are:

- an expanded section on [[file:gpgme-python-howto#installation][installing]] and [[file:gpgme-python-howto#snafu][troubleshooting]] the Python
 bindings.
- The release of Python 3.7.0; which appears to be working just fine

with our bindings, in spite of intermittent reports of problems for
many other Python projects with that new release.
- Python 3.7 has been moved to the head of the specified python
versions list in the build process.
- In
order to fix some other issues, there are certain underlying
functions which are more exposed through the [[file:gpgme-python-howto#howto-get-context][gpg.Context()]], but
ongoing documentation ought to clarify that or otherwise provide the
best means of using the bindings. Some additions to =gpg.core= and
the =Context()=, however, were intended (see below).
- Continuing work in identifying and confirming the cause of
oft-reported [[file:gpgme-python-howto#snafu-runtime-not-funtime][problems installing the Python bindings on Windows]].
- GSOC: Google's Surreptitiously Ordered Conscription ... erm ... oh,
right; Google's Summer of Code. Though there were two hopeful
candidates this year; only one ended up involved with the GnuPG
Project directly, the other concentrated on an unrelated third party
project with closer ties to one of the GNU/Linux distributions than
to the GnuPG Project. Thus the Python bindings benefited from GSOC
participant Jacob Adams, who added
the key_import function; building
on prior work by Tobias Mueller.
- Several new methods functions were added to the gpg.Context(),
including: [[file:gpgme-python-howto#howto-import-key][key_import]], [[file:gpgme-python-howto#howto-export-key][key_export]], [[file:gpgme-python-howto#howto-export-public-key][key_export_minimal]] and
[[file:gpgme-python-howto#howto-export-secret-key][key_export_secret]].
- Importing and exporting examples include versions integrated with
Marcel Fest's recently released [[https://github.com/Selfnet/hkp4py][HKP for Python]] module. Some
[[file:gpgme-python-howto#hkp4py][additional notes on this module]] are included at the end of the HOWTO.
- Instructions for dealing with semi-walled garden implementations
like ProtonMail are also included. This is intended to make things
a little easier when communicating with users of ProtonMail's
services and should not be construed as an endorsement of said
service. The GnuPG Project neither favours,
nor disfavours
ProtonMail and the majority of this deals with interacting with the
ProtonMail keyserver.
- Semi-formalised the location where [[file:gpgme-python-howto#draft-editions][draft versions]] of this HOWTO may
periodically be accessible. This is both for the reference of
others and testing the publishing of the document itself. Renamed
this file at around the same time.
- The Texinfo documentation build configuration has been replicated
from the parent project in order to make to maintain consistency
with that project (and actually ship with each release).
- a reStructuredText (=.rst=) version is also generated for Python
developers more used to and comfortable with that format as it is
the standard Python documentation format and Python developers may

wish to use it with Sphinx. Please note that there has been no
testing of the reStructuredText version with Sphinx at all. The
reST file was generated by the simple expedient of using [[https://pandoc.org/][Pandoc]].
-
Added a new section for [[file:gpgme-python-howto#advanced-use][advanced or experimental use]].
- Began the advanced use cases with [[file:gpgme-python-howto#cython][a section]] on using the module with
[[https://cython.org/][Cython]].
- Added a number of new scripts to the =example/howto/= directory;
some of which may be in advance of their planned sections of the
HOWTO (and some are just there because it seemed like a good idea at
the time).
- Cleaned up a lot of things under the hood.
hkp4py
requests
Additional license notices for GPGME. -*- org -*-

This file contains the copying permission notices for various files in
the GPGME distribution which are not covered by the GNU Lesser
General Public License (LGPL) or the GNU General Public License (GPL).

These notices all require that a copy of the notice be included
in the accompanying documentation and be distributed with binary
distributions of the code, so be sure to include this file along
with any binary distributions derived from the GNU C Library.

* MIT License

For files:
- cJSON.c, cJSON.h

#+begin_quote
Copyright (c) 2009 Dave Gamble

Permission is hereby granted, free of charge, to any person obtaining
a opy of this software and associated documentation files (the
"Software"), to eal in the Software without restriction, including
without limitation the ights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the
Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND

NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING ROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
#+end_quote
/*
  qgpgmenewcryptoconfig.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2010 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two. You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt. If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so. If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef QGPGME_QGPGMENEWCRYPTOCONFIG_H
#define QGPGME_QGPGMENEWCRYPTOCONFIG_H

#include "qgpgme_export.h"
#include "cryptoconfig.h"

#include <QHash>
#include <QStringList>

```
#include <QVariant>

#ifdef BUILDING_QGPGME
# include "configuration.h"
#else
# include <gpgme++/configuration.h>
#endif


#include <vector>
#include <utility>

class QGpgMENewCryptoConfig;
class QGpgMENewCryptoConfigComponent;
class
 QGpgMENewCryptoConfigGroup;
class QGpgMENewCryptoConfigEntry;

class QGpgMENewCryptoConfigEntry : public QGpgME::CryptoConfigEntry
{
public:
  QGpgMENewCryptoConfigEntry(const std::shared_ptr<QGpgMENewCryptoConfigGroup> &group, const
GpgME::Configuration::Option &option);
  ~QGpgMENewCryptoConfigEntry();

  QString name() const Q_DECL_OVERRIDE;
  QString description() const Q_DECL_OVERRIDE;
  QString path() const Q_DECL_OVERRIDE;
  bool isOptional() const Q_DECL_OVERRIDE;
  bool isReadOnly() const Q_DECL_OVERRIDE;
  bool isList() const Q_DECL_OVERRIDE;
  bool isRuntime() const Q_DECL_OVERRIDE;
  Level level() const Q_DECL_OVERRIDE;
  ArgType argType() const Q_DECL_OVERRIDE;
  bool isSet() const Q_DECL_OVERRIDE;
  bool boolValue() const Q_DECL_OVERRIDE;
  QString stringValue() const Q_DECL_OVERRIDE;
  int intValue() const Q_DECL_OVERRIDE;
  unsigned int uintValue() const Q_DECL_OVERRIDE;
  QUrl urlValue() const Q_DECL_OVERRIDE;

  unsigned int numberOfTimesSet() const Q_DECL_OVERRIDE;
  std::vector<int> intValueList() const Q_DECL_OVERRIDE;
  std::vector<unsigned int> uintValueList() const Q_DECL_OVERRIDE;
  QList<QUrl> urlValueList() const Q_DECL_OVERRIDE;
  void resetToDefault() Q_DECL_OVERRIDE;
  void setBoolValue(bool) Q_DECL_OVERRIDE;
  void setStringValue(const QString &) Q_DECL_OVERRIDE;
```

```
  void setIntValue(int) Q_DECL_OVERRIDE;
  void setUIntValue(unsigned int) Q_DECL_OVERRIDE;
  void setURLValue(const QUrl &) Q_DECL_OVERRIDE;
  void setNumberOfTimesSet(unsigned int) Q_DECL_OVERRIDE;
  void setIntValueList(const std::vector<int> &) Q_DECL_OVERRIDE;
  void setUIntValueList(const std::vector<unsigned int> &) Q_DECL_OVERRIDE;
  void setURLValueList(const QList<QUrl> &) Q_DECL_OVERRIDE;
  bool isDirty() const Q_DECL_OVERRIDE;

  QStringList stringValueList() const;

#if 0
  void setDirty(bool b);
  QString outputString() const;

protected:
  bool isStringType() const;

  QVariant stringToValue(const QString &value, bool unescape) const;
  QString toString(bool escape) const;
#endif
private:
  std::weak_ptr<QGpgMENewCryptoConfigGroup> m_group;
  GpgME::Configuration::Option m_option;
};

class QGpgMENewCryptoConfigGroup : public QGpgME::CryptoConfigGroup
{
public:
  QGpgMENewCryptoConfigGroup(const std::shared_ptr<QGpgMENewCryptoConfigComponent> &parent, const
GpgME::Configuration::Option &option);
  ~QGpgMENewCryptoConfigGroup();

  QString name() const Q_DECL_OVERRIDE;
  QString iconName() const Q_DECL_OVERRIDE
  {
     return QString();
  }
  QString description() const Q_DECL_OVERRIDE;
  QString path() const Q_DECL_OVERRIDE;
  QGpgME::CryptoConfigEntry::Level level() const Q_DECL_OVERRIDE;
  QStringList entryList() const Q_DECL_OVERRIDE;
  QGpgMENewCryptoConfigEntry *entry(const QString &name) const Q_DECL_OVERRIDE;

private:
  friend class QGpgMENewCryptoConfigComponent; // it adds the entries
  std::weak_ptr<QGpgMENewCryptoConfigComponent>
```

```
 m_component;
  GpgME::Configuration::Option m_option;
  QStringList m_entryNames;
  QHash< QString, std::shared_ptr<QGpgMENewCryptoConfigEntry> > m_entriesByName;
};

/// For docu, see kleo/cryptoconfig.h
class QGpgMENewCryptoConfigComponent : public QGpgME::CryptoConfigComponent, public
std::enable_shared_from_this<QGpgMENewCryptoConfigComponent>
{
public:
  QGpgMENewCryptoConfigComponent();
  ~QGpgMENewCryptoConfigComponent();

  void setComponent(const GpgME::Configuration::Component &component);

  QString name() const Q_DECL_OVERRIDE;
  QString iconName() const Q_DECL_OVERRIDE
  {
     return name();
  }
  QString description() const Q_DECL_OVERRIDE;
  QStringList groupList() const Q_DECL_OVERRIDE;
  QGpgMENewCryptoConfigGroup *group(const QString &name) const Q_DECL_OVERRIDE;

  void sync(bool runtime);

private:
  GpgME::Configuration::Component m_component;
  QHash< QString, std::shared_ptr<QGpgMENewCryptoConfigGroup>
 > m_groupsByName;
};

/**
* CryptoConfig implementation around the gpgconf command-line tool
* For method docu, see kleo/cryptoconfig.h
*/
class QGPGME_EXPORT QGpgMENewCryptoConfig : public QGpgME::CryptoConfig
{
public:
  /**
   * Constructor
   */
  QGpgMENewCryptoConfig();
  ~QGpgMENewCryptoConfig();

  QStringList componentList() const Q_DECL_OVERRIDE;
```

```
  QGpgMENewCryptoConfigComponent *component(const QString &name) const Q_DECL_OVERRIDE;

  void clear() Q_DECL_OVERRIDE;
  void sync(bool runtime) Q_DECL_OVERRIDE;

private:
  /// @param showErrors if true, a messagebox will be shown if e.g. gpgconf wasn't found
  void reloadConfiguration(bool showErrors);

private:
  QHash< QString, std::shared_ptr<QGpgMENewCryptoConfigComponent> > m_componentsByName;
  bool m_parsed;
};

#endif /* QGPGME_QGPGMENEWCRYPTOCONFIG_H */
/*
  qgpgmerefreshkeysjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a
 special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
```

```
*/

#ifndef __QGPGME_QGPGMEREFRESHKEYSJOB_H__
#define __QGPGME_QGPGMEREFRESHKEYSJOB_H__

#include "refreshkeysjob.h"
#ifdef BUILDING_QGPGME
# include "context.h"
#else
#include "gpgme++/context.h"
#endif

#include <QStringList>
#include <QProcess>

namespace QGpgME
{

class QGpgMERefreshKeysJob : public RefreshKeysJob
{
  Q_OBJECT
public:
  QGpgMERefreshKeysJob();
  ~QGpgMERefreshKeysJob();

   /* from RefreshKeysJob */
  GpgME::Error start(const QStringList &patterns) Q_DECL_OVERRIDE;

private Q_SLOTS:
  /* from Job */
  void slotCancel() Q_DECL_OVERRIDE;

  void slotStatus(QProcess *, const QString &, const QStringList &);
  void slotStderr();
  void slotProcessExited(int exitCode, QProcess::ExitStatus exitStatus);

private:
  GpgME::Error startAProcess();

private:
  QProcess *mProcess;
  GpgME::Error mError;
  QStringList mPatternsToDo;
};

}

#endif // __QGPGME_QGPGMEREFRESHKEYSJOB_H__
```

```
/*
  signjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_SIGNJOB_H__
#define __KLEO_SIGNJOB_H__

#include "job.h"

#ifdef BUILDING_QGPGME
# include "global.h"
#else
# include <gpgme++/global.h>
#endif


#include <vector>
```

```
#include <memory>

class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class Key;
class SigningResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous signing

  To use
 a SignJob, first obtain an instance from the CryptoBackend
  implementation, connect the progress() and result() signals to
  suitable slots and then start the signing with a call to
  start(). This call might fail, in which case the SignJob instance
  will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the SignJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT SignJob : public Job
{
  Q_OBJECT
protected:
  explicit SignJob(QObject *parent);
public:
  ~SignJob();

  /**
    Starts the signing operation. \a signers is the list of keys to
    sign \a plainText with. Empty (null) keys are ignored.
  */
  virtual GpgME::Error start(const std::vector<GpgME::Key> &signers,
        const QByteArray &plainText,
        GpgME::SignatureMode mode) = 0;

  /*!
    \overload
```

```
    If \a signature is non-null the signature is written
    there. Otherwise,
  it will be delivered in the second argument of
    result().

    \throws GpgME::Exception if starting fails
  */
  virtual void start(const std::vector<GpgME::Key> &signers,
                     const std::shared_ptr<QIODevice> &plainText,
                     const std::shared_ptr<QIODevice> &signature,
                     GpgME::SignatureMode mode) = 0;

  virtual GpgME::SigningResult exec(const std::vector<GpgME::Key> &signers,
                                    const QByteArray &plainText,
                                    GpgME::SignatureMode mode,
                                    QByteArray &signature) = 0;

  /*!
    This is a hack to request BASE64 output (instead of whatever
    comes out normally).
  */
  virtual void setOutputIsBase64Encoded(bool) = 0;

Q_SIGNALS:
  void result(const GpgME::SigningResult &result, const QByteArray &signature, const QString &auditLogAsHtml
= QString(), const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif
 // __KLEO_SIGNJOB_H__
/* ops.h - Internal operation support.
  Copyright (C) 2000 Werner Koch (dd9jn)
  Copyright (C) 2001, 2002, 2003, 2004, 2005 g10 Code GmbH

  This file is part of GPGME.

  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.
```

```
  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef OPS_H
#define OPS_H

#include "gpgme.h"
#include "context.h"


/* From gpgme.c.  */
gpgme_error_t
 _gpgme_cancel_with_err (gpgme_ctx_t ctx, gpg_error_t ctx_err,
        gpg_error_t op_err);
/* Clear all notation data from the context.  */
void _gpgme_sig_notation_clear (gpgme_ctx_t ctx);

void _gpgme_release_result (gpgme_ctx_t ctx);


/* From wait.c.  */
gpgme_error_t _gpgme_wait_one (gpgme_ctx_t ctx);
gpgme_error_t _gpgme_wait_one_ext (gpgme_ctx_t ctx, gpgme_error_t *op_err);
gpgme_error_t _gpgme_wait_on_condition (gpgme_ctx_t ctx, volatile int *cond,
    gpgme_error_t *op_err);


/* From data.c.  */
gpgme_error_t _gpgme_data_inbound_handler (void *opaque, int fd);
gpgme_error_t _gpgme_data_outbound_handler (void *opaque, int fd);


/* From op-support.c.  */

/* Find or create the op data object of type TYPE.  */
gpgme_error_t _gpgme_op_data_lookup (gpgme_ctx_t ctx, ctx_op_data_id_t type,
        void **hook, int size,
        void (*cleanup) (void *));

/* Prepare a new operation on CTX.  */
gpgme_error_t _gpgme_op_reset (gpgme_ctx_t ctx, int synchronous);

/* Parse the
 KEY_CONSIDERED status line.  */
gpgme_error_t _gpgme_parse_key_considered (const char *args,
                                   char **r_fpr, unsigned int *r_flags);
```

```
/* Parse the INV_RECP status line in ARGS and return the result in
  KEY.  */
gpgme_error_t _gpgme_parse_inv_recp (char *args, int for_signing,
                                     const char *kc_fpr, unsigned int kc_flags,
                                     gpgme_invalid_key_t *key);

/* Parse the PLAINTEXT status line in ARGS and return the result in
  FILENAMEP and R_MIME.  */
gpgme_error_t _gpgme_parse_plaintext (char *args, char **filenamep,int *r_mime);

/* Parse a FAILURE status line and return the error code.  ARGS is
  modified to contain the location part.  */
gpgme_error_t _gpgme_parse_failure (char *args);



/* From verify.c.  */
gpgme_error_t _gpgme_op_verify_init_result (gpgme_ctx_t ctx);
gpgme_error_t _gpgme_verify_status_handler (void *priv,
        gpgme_status_code_t code,
        char
 *args);


/* From decrypt.c.  */
gpgme_error_t _gpgme_op_decrypt_init_result (gpgme_ctx_t ctx,
                                     gpgme_data_t plaintext);
gpgme_error_t _gpgme_decrypt_status_handler (void *priv,
         gpgme_status_code_t code,
         char *args);
gpgme_error_t _gpgme_decrypt_start (gpgme_ctx_t ctx, int synchronous,
                                    gpgme_decrypt_flags_t flags,
                                    gpgme_data_t cipher, gpgme_data_t plain);


/* From signers.c.  */
void _gpgme_signers_clear (gpgme_ctx_t ctx);

/* From sign.c.  */

/* Create an initial op data object for signing.  Needs to be called
  once before calling _gpgme_sign_status_handler.  */
gpgme_error_t _gpgme_op_sign_init_result (gpgme_ctx_t ctx);

/* Process a status line for signing operations.  */
gpgme_error_t _gpgme_sign_status_handler (void *priv,
      gpgme_status_code_t code,
```

```
      char *args);


/* From encrypt.c.  */

/* Create an initial op data object for encrypt.
  Needs to be called
  once before calling _gpgme_encrypt_status_handler.  */
gpgme_error_t _gpgme_op_encrypt_init_result (gpgme_ctx_t ctx);

/* Process a status line for encryption operations.  */
gpgme_error_t _gpgme_encrypt_status_handler (void *priv,
         gpgme_status_code_t code,
         char *args);


/* From passphrase.c.  */
gpgme_error_t _gpgme_passphrase_status_handler (void *priv,
     gpgme_status_code_t code,
     char *args);
gpgme_error_t _gpgme_passphrase_command_handler (void *opaque,
      gpgme_status_code_t code,
      const char *key, int fd,
      int *processed);


/* From progress.c.  */
gpgme_error_t _gpgme_progress_status_handler (void *priv,
          gpgme_status_code_t code,
          char *args);


/* From key.c.  */
gpgme_error_t _gpgme_key_new (gpgme_key_t *r_key);
gpgme_error_t _gpgme_key_add_subkey (gpgme_key_t key,
        gpgme_subkey_t *r_subkey);
gpgme_error_t _gpgme_key_append_name (gpgme_key_t key,

           const char *src, int convert);
gpgme_key_sig_t _gpgme_key_add_sig (gpgme_key_t key, char *src);



/* From keylist.c.  */
void _gpgme_op_keylist_event_cb (void *data, gpgme_event_io_t type,
    void *type_data);
```

```
/* From trust-item.c.  */

/* Create a new trust item.  */
gpgme_error_t _gpgme_trust_item_new (gpgme_trust_item_t *r_item);


/* From trustlist.c.  */
void _gpgme_op_trustlist_event_cb (void *data, gpgme_event_io_t type,
      void *type_data);


/* From version.c.  */

/* Return true if MY_VERSION is at least REQ_VERSION, and false
  otherwise.  */
int _gpgme_compare_versions (const char *my_version,
       const char *req_version);
char *_gpgme_get_program_version (const char *const path);


/* From sig-notation.c.  */

/* Create a new, empty signature notation data object.  */
gpgme_error_t _gpgme_sig_notation_create (gpgme_sig_notation_t *notationp,
      const char *name, int name_len,
      const char *value, int value_len,
      gpgme_sig_notation_flags_t
 flags);

/* Free the signature notation object and all associated resources.
  The object must already be removed from any linked list as the next
  pointer is ignored.  */
void _gpgme_sig_notation_free (gpgme_sig_notation_t notation);

/* Parse a notation or policy URL subpacket.  If the packet type is
  not known, return no error but NULL in NOTATION.  */
gpgme_error_t _gpgme_parse_notation (gpgme_sig_notation_t *notationp,
        int type, int pkflags, int len,
        char *data);

#endif /* OPS_H */
2011-12-02  Werner Koch  <wk@g10code.com>

 NB: ChangeLog files are no longer manually maintained.  Starting
 on December 1st, 2011 we put change information only in the GIT
 commit log, and generate a top-level ChangeLog file from logs at
 "make dist".  See doc/HACKING for details.
```

2011-10-25 Marcus Brinkmann <marcus@g10code.com>

 * m4/pth.m4: Removed.
 * configure.ac: Remove check for pth and automake conditional
 HAVE_PTH.

2011-06-16 Marcus Brinkmann <marcus@g10code.com>

 Release 1.3.1

 * configure.ac: Set LT version to C19/A8/R0.

2011-05-06 Marcus Brinkmann <marcus@g10code.com>

 * Makefile.am (SUBDIRS): Remove complus.

 * configure.ac (AC_CONFIG_FILES): Remove complus/Makefile.
 (BUILD_COMPLUS): Remove AM_CONDITIONAL.
 * complus/: Remove very old and stale component.

 * acinclude.m4 (GNUPG_FIX_HDR_VERSION): Remove.

2011-04-14 Werner Koch <wk@g10code.com>

 * configure.ac: Require automake 1.11.

2011-04-06 Werner Koch <wk@g10code.com>

 * autogen.sh (--build-w32):
 Support option --build-w64.
 * configure.ac (HAVE_W64_SYSTEM): Define.
 (INSERT__TYPEDEFS_FOR_GPGME_H): New.
 (GPGME_CONFIG_HOST): New.

2011-02-02 Marcus Brinkmann <mb@g10code.com>

 * configure.ac (NEED_LIBASSUAN_VERSION): Bump to 2.0.2 for system hooks.

2010-12-30 Werner Koch <wk@g10code.com>

 * configure.ac: Support a git revision.

2010-11-03 Werner Koch <wk@g10code.com>

 * configure.ac (AC_CHECK_HEADERS): Check for sys/types.h and
 sys.stat.h.

2010-11-02 Werner Koch <wk@g10code.com>

* configure.ac (AC_CHECK_HEADERS): Check for sys.time.h.

2010-08-19 Werner Koch <wk@g10code.com>

* configure.ac (AH_BOTTOM): Define GPG_ERR_ENABLE_ERRNO_MACROS.

2010-05-12 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Check for setlocale.

2010-05-07 Werner Koch <wk@g10code.com>

* configure.ac: Change checks to always require libassuan.

2010-05-07 Marcus Brinkmann <marcus@g10code.de>

* autogen.sh: Update the thing.

* configure.ac: Check for locale.h.

2010-05-06
Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Detect Windows CE.
(HAVE_W32CE_SYSTEM): New symbol and automake conditional.
* ltmain.sh, m4/libtool.m4: Patch so that it works for Windows CE.

* configure.ac: Require libgpg-error 1.8.

2010-03-15 Werner Koch <wk@g10code.com>

* configure.ac (emacs_local_vars_begin)
(emacs_local_vars_read_only, emacs_local_vars_end): New.

2010-01-22 Werner Koch <wk@g10code.com>

* autogen.sh (--build-w32): Add --with-libassuan-prefix.

2010-01-11 Marcus Brinkmann <marcus@g10code.de>

Release 1.3.0.

2009-12-22 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Do not use echo -n. Test for __thread.

2009-12-17 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Make largefile check more robust.

2009-12-10 Werner Koch <wk@g10code.com>

* configure.ac: Check for getgid and getegid.

2009-12-08 Marcus Brinkmann <marcus@g10code.de>

Update to libtool 2.2.6a.
* configure.ac: Invoke AC_CONFIG_MACRO_DIR.
(AC_LIBTOOL_WIN32_DLL,
AC_LIBTOOL_RC): Replace by ...
(LT_PREREQ, LT_INIT, LT_LANG): ... these.
* config.guess, config.sub, install-sh, ltmain.sh, m4/libtool.m4:
Updated to libtool 2.2.6a.
* m4/ltoptions.m4, m4/ltsugar.m4, m4/ltversion.m4,
m4/lt~obsolete.m4: New files from libtool 2.2.6a.

2009-11-10 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Activate UIServer if FD passing is enabled and
Assuan is available.

2009-10-30 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Check for argp.h and error_t.

2009-10-26 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (NEED_GPG_VERSION_DEFAULT): Bump to 1.4.0 as 1.3.0
was development versions only.

2009-10-22 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add support for G13.

2009-10-20 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (AC_CONFIG_FILES): Remove assuan/Makefile.

2009-10-20 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Replace internal libassuan by external libassuan.
* m4/libassuan.m4:
New file.
* Makefile.am (assuan): Remove variable.
(SUBDIRS): Remove ${assuan}.

* assuan/: Removed.

2009-06-22 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add AC_TYPE_UINTPTR_T.

* assuan/assuan.h [_ASSUAN_IN_GPGME_BUILD_ASSUAN]: Declare
_gpgme_io_connect.

2009-06-18 Marcus Brinkmann <marcus@g10code.de>

Released GPGME 1.2.0.

* configure.ac (my_version): Set to 1.2.0.
(LIBGPGME_LT_CURRENT, LIBGPGME_LT_AGE): Bump.
(LIBGPGME_LT_REVISION): Reset.

2009-05-05 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add infrastructure for compile time check of
_FILE_OFFSET_BITS.

2009-04-19 Moritz <moritz@gnu.org>

* Makefile.am (DISTCHECK_CONFIGURE_FLAGS): Specify --with-gpg.

2009-03-06 Marcus Brinkmann <marcus@g10code.de>

* assuan/: Update to libassuan SVN 2009-03-06.

2009-01-26 Werner Koch <wk@g10code.com>

* configure.ac (AC_CONFIG_FILES): Add tests/opassuan/Makefile.

2008-12-08 Marcus Brinkmann <marcus@g10code.de>

Release GPGME
1.1.8.

* configure.ac: Bump API revision.

2008-11-03 Marcus Brinkmann <marcus@g10code.com>

* configure.ac: Replace gpgme paths with src.
* gpgme: Move to ...
* src: ... this new directory.

2008-10-20 Werner Koch <wk@g10code.com>

* configure.ac (AC_CONFIG_FILES): Add gpgme.h.
(GNUPG_FIX_HDR_VERSION): Remove.

2008-10-17 Marcus Brinkmann <marcus@g10code.com>

Release GPGME 1.1.7.

* configure.ac (LIBGPGME_LT_REVISION): Bump for release.

2008-09-19 Moritz <moritz@gnu.org>

* configure.ac: Remove bogus "esac".

2008-09-16 Marcus Brinkmann <marcus@g10code.com>

* configure.ac (_XOPEN_SOURCE) [apple-darwin]: Define it.

2008-07-04 Werner Koch <wk@g10code.com>

* config.guess, config.sub: Update to 2007-11-19. Also update
missing et al scripts.

2008-04-01 Werner Koch <wk@g10code.com>

* configure.ac (AC_INIT): Fix quoting.

2008-01-30 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Bump required version of automake up to 1.10.
* autogen.sh: Fix
aclocal check.

2008-01-04 Marcus Brinkmann <marcus@g10code.de>

Release GPGME 1.1.6.

* configure.ac: Support gpgconf.

2007-09-27 Marcus Brinkmann <marcus@g10code.de>

* assuan-pipe-connect.c (pipe_connect_gpgme): Do not close process
handle here. Use this function also on Unix systems.

* assuan-pipe-connect.c (pipe_connect_gpgme): Fix last change.

* assuan-pipe-connect.c (pipe_connect_gpgme): New function, use it
if _ASSUAN_IN_GPGME_BUILD_ASSUAN.

2007-09-17 Werner Koch <wk@g10code.com>

 * configure.ac: Use the svn version magic.

2007-09-07 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac: Check for C++, Qt and support --enable-w32-qt.
 * m4/pkg.m4: New file.

2007-08-21 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (--enable-w32-glib): Use --enableval, not
 --withval.

2007-07-16 Marcus Brinkmann <marcus@g10code.de>

 * assuan/assuan-socket.c (_assuan_close): Always use close().
 * assuan/assuan.h (_gpgme_io_close): New prototype.
 (close): New
 macro, define as _gpgme_io_close.

2007-07-13 Marcus Brinkmann <marcus@g10code.de>

 * assuan/assuan-io.c (_assuan_simple_read, _assuan_simple_write):
 Always use read/write (which means _gpgme_io_read and
 _gpgme_io_write).

2007-07-09 Marcus Brinkmann <marcus@g10code.de>

 Released 1.1.5.

 * configure.ac (LIBGPGME_LT_REVISION): Bump for release.

2007-07-08 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (GPGSM_DEFAULT) [*-mingw32*]: Initialize it.
 (HAVE_ASSUAN_H): Set to 1 if we have it.
 (funopen): Use AC_REPLACE_FUNCS.
 (USE_DESCRIPTOR_PASSING): Define to 1 if we have it. Do not
 define it at all if we don't.
 (NETLIBS) [have_w32_system]: Add -lws2_32.
 (DIRSEP_C, DIRSEP_S, EXPSEP_C, EXPSEP_S, PATHSEP_S)
 [HAVE_DOSISH_SYSTEM]: Remove definitions.

 * assuan/assuan.h (_assuan_funopen): Define to _gpgme_funopen.
 * assuan/funopen.c: Move to ../gpgme/funopen.c.
 * assuan/Makefile.am (libassuan_la_SOURCES): Remove funopen.c.

2007-07-04 Marcus Brinkmann <marcus@g10code.de>

*
assuan/Makefile.am (INCLUDES): Include $(top_srcdir)/gpgme.
* assuan/assuan.h: Include <ath.h> instead of trying to duplicate
the definitions.

* assuan/: Update files to 2007-07-04 version of assuan.

* autogen.sh: Use = not == in test.

2007-03-05 Werner Koch <wk@g10code.com>

Released 1.1.4.

* configure.ac (LIBGPGME_LT_REVISION): Bump for release.

* autogen.sh: New option --force.

2007-01-29 Marcus Brinkmann <marcus@g10code.de>

Released 1.1.3.

* configure.ac (LIBGPGME_LT_REVISION): Bump for release.

2007-01-26 Werner Koch <wk@g10code.com>

* configure.ac: Changed gpg and gpgsm version checks to work with
arbitrary names of the gpg binary. New option --disable-gpg-test
and --disable-gpgsm-test.

2007-01-09 Werner Koch <wk@g10code.com>

* configure.ac (NEED_GPG_VERSION, NEED_GPGSM_VERSION): Must define
after it may have been changed by an option.

2007-01-08 Werner Koch <wk@g10code.com>

* configure.ac: Require gpg-error 1.4 due to the use of
gpg_error_from_syserror.
(HAVE_ASSUAN_H):
New.

2007-01-05 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add options --with-gpg-version and
--with-gpgsm-version to allow overriding the minimum version

requirements.

2006-12-17 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Fix two typos in last change.

2006-12-03 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Use descriptor passing only if --enable-fd-passing
is provided.

* configure.ac: Add check for use of descriptor passing.

2006-11-29 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (NEED_GPG_VERSION): Bump to 1.3.0.

2006-09-19 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Turn stpcpy into a replacement function.
Check for unistd.h and add setenv as replacement function.

2006-07-29 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Check for network libraries and set NETLIBS.

2006-07-06 Marcus Brinkmann <marcus@g10code.de>

* lang, lang/cl: New subdirectories.
*
lang/Makefile.am, lang/README: New files.
* configure.ac (AC_CONFIG_FILES): Add lang/Makefile,
lang/cl/Makefile and lang/cl/gpgme.asd.
* Makefile.am (SUBDIRS): Add lang.

2006-03-02 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (LIBGPGME_LT_REVISION): Bump for release.

2006-02-22 Marcus Brinkmann <marcus@g10code.de>

Released 1.1.1.

* configure.ac (LIBGPGME_LT_CURRENT, LIBGPGME_LT_AGE): Bump for
release.
(LIBGPGME_LT_REVISION): Reset to 0 for release.

2006-01-05 Werner Koch <wk@g10code.com>

* configure.ac: Test for inline feature.
(AH_BOTTOM): New to define the pure attribute.

2006-01-03 Werner Koch <wk@g10code.com>

* configure.ac: Append SVN revision to the version.

2005-11-18 Werner Koch <wk@g10code.com>

* configure.ac (BUILD_REVISION): New.

2005-11-17 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add support for --enable-w32-glib (disabled by
default). Invoke AM_PATH_GLIB_2_0.

2005-11-16 Werner Koch <wk@g10code.com>

* configure.ac
(CFLAGS) [W32]: Make sure that -mms-bitfields are used.

2005-11-15 Werner Koch <wk@g10code.com>

* configure.ac: Create BUILD_FILEVERSION from SVN Revision.

* autogen.sh [W32]: Build shared and static versions of the library.

2005-10-20 Marcus Brinkmann <marcus@g10code.de>

* w32-dll/ChangeLog, w32-dll/build-dll, w32-dll/gpgme.def: Remove
files.

* configure.ac: Instead checking for windres and dlltool, invoke
AC_LIBTOOL_WIN32_DLL and AC_LIBTOOL_RC.
* src/Makefile.am [HAVE_W32_SYSTEM]: Use libtool, which simplifies
the rules.

2005-10-01 Marcus Brinkmann <marcus@g10code.de>

Released 1.1.0.

* configure.ac (LIBGPGME_LT_CURRENT, LIBGPGME_LT_AGE): Bump for
release.
(LIBGPGME_LT_REVISION): Reset to 0 for release.

2005-09-12 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (HAVE_PTH): Don't add $PTH_CFLAGS to $CFLAGS here.

2005-08-26 Werner Koch <wk@g10code.com>

* configure.ac (SEPCONSTANTS): New to define DIRSEP_C et al.

2005-08-19 Werner Koch <wk@g10code.com>

*
configure.ac [W32]: Create values for versioninfo.rc and list
substuture versioninfo.rc.
* configure.ac: Define ENABLE_GPGSM.

2005-08-08 Werner Koch <wk@g10code.com>

* configure.ac (stpcpy): Changed from replace to test.

2005-03-24 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (AH_BOTTOM): Removed.

2005-03-09 Werner Koch <wk@g10code.com>

* acinclude.m4 (GNUPG_CHECK_VA_COPY): Assume no when cross-compiling.

* Makefile.am (EXTRA_DIST): Include autogen.sh

* autogen.sh: Added the usual code to build for W32 (--build-w32).

* configure.ac: Fixed the mingw32 host string, removed OS/2 stuff.
(HAVE_DRIVE_LETTERS): Removed.
(HAVE_W32_SYSTEM): Added.
(AC_GNU_SOURCE): New to replace the identical AH_VERBATIM.
(AH_BOTTOM): Added.

2004-12-28 Werner Koch <wk@g10code.com>

Released 1.0.2.

* Makefile.am (AUTOMAKE_OPTIONS): Build bzip 2 version.
(ACLOCAL_AMFLAGS): Add -I m4.
* configure.ac: Require automake 1.9.3 and autoconf 2.59.
* acinclude.m4:
Changed quoting for automake 1.9.
* README: Use SHA1 instead of MD5.

2004-12-11 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Replace ttyname_r if it doesn't exist (and warn in
that case).

2004-12-07 Marcus Brinkmann <marcus@g10code.de>

* README: Refer to COPYING.LESSER and "each file" instead of
COPYING.
* COPYING.LESSER: New file.
* gpgme.spec.in (%doc): Add COPYING.LESSER.
* acinclude.m4, configure.ac, Makefile.am: Change license to LGPL
2.1 or later.
* TODO: Add copyright notice.
* README.CVS: Likewise.

* configure.ac (GPGSM_VERSION): Fix filter to get it.

2004-10-22 Marcus Brinkmann <marcus@g10code.de>

Released 1.0.1.

* configure.ac (LIBGPGME_LT_REVISION): Bump up to 2.
(AC_INIT): Set version to 1.0.1.

* configure.ac: Set HAVE_GPGSM to true only if $GPGSM is not "no".

2004-09-30 Marcus Brinkmann <marcus@g10code.de>

Released 1.0.0.

* configure.ac (LIBGPGME_LT_REVISION): Bump up to 1.
(AC_INIT): Set version to 1.0.0.

* Makefile.am
(EXTRA_DIST): Remove README-alpha.
* README-alpha: Remove file.

2004-09-17 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Disable AC_CONFIG_MACRO_DIR for now.

2004-09-14 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Improve diagnostics with version check.

* configure.ac: Print diagnostics about found thread libraries at
the end. Check for the versions of GPG and GPGSM and print the
found versions at the end.
(HAVE_GPGSM): Do not require GPGSM to exist and be readable.

(AC_CONFIG_MACRO_DIR): Invoke with argument m4.

* acinclude.m4: Add copyright notice.
(jm_GLIBC21, AM_PATH_GPG_ERROR, _AC_PTH_ERROR, _AC_PTH_VERBOSE,
AC_CHECK_PTH): Removed.

2004-06-23 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Check for <sys/uio.h>.

2004-06-08 Marcus Brinkmann <marcus@g10code.de>

Released 0.9.0.

* configure.ac (AC_INIT): Set version number to 0.9.0.
(LIBGPGME_LT_CURRENT, LIBGPGME_LT_AGE): Bump up by one.
(LIBGPGME_LT_REVISION): Reset to zero.

2004-05-21
Marcus Brinkmann <marcus@g10code.de>

* configure.ac (GPGME_CONFIG_API_VERSION): New variable,
substitute it.

2004-04-29 Marcus Brinkmann <marcus@g10code.de>

Released 0.4.7.

* configure.ac (LIBGPGME_LT_REVISION): Bump it up.

2004-04-02 Thomas Schwinge <schwinge@nic-nac-project.de>

* autogen.sh: Added ACLOCAL_FLAGS.

2004-04-06 Werner Koch <wk@gnupg.org>

Released 0.4.6.

* config.guess, config.sub, ltmain.sh: Updated to those from
libtools 1.5.4.

2004-03-07 Marcus Brinkmann <marcus@g10code.de>

Released 0.4.5.

* configure.ac (NEED_GPGSM_VERSION): Bump up to 1.9.6.

* Makefile.am (EXTRA_DIST): Remove autogen.sh and README.CVS.

2004-02-18 Werner Koch <wk@gnupg.org>

* configure.ac: Make the check for funopen fail with just a
warning.

2004-02-11 Werner Koch <wk@gnupg.org>

* autogen.sh (check_version): Removed bashism and simplified.

2004-02-10 Werner Koch <wk@gnupg.org>

* configure.ac: Fixed funopen test change.

2004-02-06 Moritz Schulte
<mo@g10code.com>

* configure.ac: Fix funopen replacement mechanism.

2004-01-31 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add invocation of AC_SYS_LARGEFILE, AC_TYPE_OFF_T
and AC_FUNC_FSEEKO.

2004-01-12 Werner Koch <wk@gnupg.org>

Released 0.4.4.

* configure.ac: Bumbed LT_Revision; now at C12/A1/R1.
(NEED_GPGSM_VERSION): Set to 1.9.3.
(min_automake_version): Added.
* README.CVS: New.
* Makefile.am (EXTRA_DIST): Added README.CVS.
* autogen.sh: Updated.

2003-11-19 Werner Koch <wk@gnupg.org>

* acinclude.m4: Add AM_PATH_GPG_ERROR.
* configure.ac: Check for timegm. Made warning messages more
prominent.

2003-10-06 Marcus Brinkmann <marcus@g10code.de>

Released 0.4.3.

* configure.ac (LIBGPGME_LT_CURRENT, LIBGPGME_LT_AGE): Bump up by 1.
(LIBGPGME_LT_REVISION): Set to 0.

2003-09-13 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Require libgpg-error 0.5.

* acinclude.m4: Remove libtool cruft, add jm_GLIBC21.
* configure.ac: Add check for
getenv_r, and call jm_GLIBC21.
Define HAVE_THREAD_SAFE_GETENV if appropriate.

2003-09-03 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Remove GPGME_CONFIG_LIBS and GPGME_CONFIG_CFLAGS.

2003-09-02 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Move invocation of AC_CANONICAL_HOST up to
suppress warning by autoconf.

2003-08-30 Robert Schiele <rschiele@uni-mannheim.de>

* gpgme.spec.in: %{_infodir}/dir is not packaged,
remove to prevent checking failure.

2003-08-18 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: If building Assuan, check for funopen and
fopencookie, and make isascii, putc_unlocked and memrchr
replacement functions.
(AM_PATH_GPG_ERROR): Require 0.3.

2003-07-31 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (AC_INIT): Bump version to 0.4.3.

2003-07-30 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (LIBGPGME_LT_REVISION): Bump up to 1.

Released 0.4.2.

2003-07-08 Marcus Brinkmann <marcus@g10code.de>

* configure.ac:
Complain if libgpg-error is not found.

2003-06-22 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (AC_INIT): Bump version to 0.4.2.

2003-06-06 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (LIBGPGME_LT_CURRENT): Bump up to 11.

* configure.ac: Use AM_PATH_GPG_ERROR.

* configure.ac: Check for libgpg-error. Define
GPG_ERR_SOURCE_DEFAULT.

2003-05-26 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (NEED_GPG_VERSION): Bump up to 1.2.2.

2003-05-18 Marcus Brinkmann <marcus@g10code.de>

In all files, replace the Gpgme* type names with the new gpgme_*
type names.

2003-02-01 Marcus Brinkmann <marcus@g10code.de>

* assuan/: Update files to 2002-11-10 version of assuan.

2003-01-29 Marcus Brinkmann <marcus@g10code.de>

* bonobo/gpgme.c, bonobo/main.c, bonobo/main.h, bonobo/Makefile,
bonobo/Makefile.am, bonobo/Makefile.in: Dead files removed.
* configure.ac: Remove automake conditional BUILD_BONOBO
(AC_CONFIG_FILES): Remove bonobo/Makefile.
*
Makefile.am (bonobo): Remove variable.
(SUBDIRS): Remove ${bonobo}.

* configure.ac: Remove all uses of GNUPG_CHECK_TYPEDEF, for byte,
ushort, ulong, u16 and u32.
* acinclude.m4 (GNUPG_CHECK_TYPEDEF): Remove macro.

2002-12-24 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: New conditional HAVE_LD_VERSION_SCRIPT.
Call AC_CANONICAL_HOST, use host instead target.

2002-12-23 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Bump up to 0.4.1.

Released 0.4.0.

2002-12-23 Marcus Brinkmann <marcus@g10code.de>

* autogen.sh (automake_vers): Require 1.7 (really 1.7.1) for the
conditional source distribution bug fix.

2002-12-08 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (LIBGPGME_LT_CURRENT): Increase by one.
(LIBGPGME_LT_AGE, LIBGPGME_LT_REVISION): Set to 0.

2002-11-28 Marcus Brinkmann <marcus@g10code.de>

* NEWS: Add note about moving "gpgmeplug" to the "cryptplug"
package.
* README: Remove instructions related to "gpgmeplug".
* configure.ac:
Remove enable option "gpgmeplug" and automake
conditional BUILD_GPGMEPLUG, as well as the status info about it.
(GPGMEPLUG): Remove variable.
* Makefile.am (gpgmeplug): Remove variable.
(SUBDIRS): Remove ${gpgmeplug}.
* cryptplug.h, gpgme-openpgp.c, gpgmeplug.dox, gpgme-smime.c,
Makefile.am, gpgmeplug.c, ChangeLog: Files removed.

2002-11-22 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Disable GPGSM for all dosish systems.

2002-10-12 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add automake conditional HAVE_GPGSM.

2002-10-08 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (AC_INIT): Bump version up to 0.4.0.
(NEED_GPG_VERSION): Bump up to 1.2.0.
(NEED_GPGSM_VERSION): Bump up to 0.9.0.
* README: Update version numbers.
* NEWS: Start entry for 0.4.0.

2002-09-20 Werner Koch <wk@gnupg.org>

Released 0.3.11.

* configure.ac: Bump up LIBGPGME_LT_REVISION.

* configure.ac (AC_CHECK_HEADERS): Check for sys/select.h.

2002-09-04 Marcus Brinkmann
  <marcus@g10code.de>

 * autogen.sh (autoconf_vers): Bump up to 2.53 to get the @&t@
 quadrigraph. Always cutting the edge!

2002-09-02 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac: Create and substitute LTLIBOBJS.

2002-09-02 Marcus Brinkmann <marcus@g10code.de>

 Released 0.3.10.

 * NEWS: Update for 0.3.9 release.
 * configure.ac: Bump up LIBGPGME_LT_REVISION.

2002-08-29 Marcus Brinkmann <marcus@g10code.de>

 * gpgme.spec.in: Changed user name in Wojciech Polak's email
 address from ghostface to polak per request by himself.

2002-08-28 Werner Koch <wk@gnupg.org>

 * acinclude.m4 (GNUPG_CHECK_VA_COPY): New.
 * configure.ac: Use it.

2002-08-23 Werner Koch <wk@gnupg.org>

 * configure.ac (GPGME_CONFIG_CFLAGS): Renamed from GPGME_CFLAGS
 and removed the libpath because it is set by the config script.

2002-08-21 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac: Bump version number to 0.3.10.

 * NEWS: Add template for development version.

2002-08-21
  Marcus Brinkmann <marcus@g10code.de>

 Released 0.3.9.

 * NEWS: Update for 0.3.9 release.
 * Makefile.am (EXTRA_DIST): Add gpgme.spec.in.

2002-08-21 Marcus Brinkmann <marcus@g10code.de>

* jnlib/argparse.c, jnlib/argparse.h, jnlib/ChangeLog,
jnlib/dotlock.c, jnlib/dotlock.h, jnlib/libjnlib-config.h,
jnlib/logging.c, jnlib/logging.h,jnlib/Makefile.am,
jnlib/mischelp.h, jnlib/README, jnlib/stringhelp.c,
jnlib/stringhelp.h, jnlib/strlist.c, jnlib/strlist.h,
jnlib/types.h, jnlib/xmalloc.c, jnlib/xmalloc.h: Remove files.

2002-08-21 Marcus Brinkmann <marcus@g10code.de>

* Makefile.am (SUBDIRS): Remove jnlib.
* configure.ac: Don't check for unsigned short or unsigned long.
Don't check for memicmp, strlwr, strtoul, memmove, stricmp.
Make stpcpy a replaced function.
Don't define HAVE_JNLIB_LOGGING.
Don't generate jnlib/Makefile.

2002-07-02 Werner Koch <wk@gnupg.org>

* configure.ac: Bumbed version number to 0.3.9; add a comment on
when to change it.

* gpgme.spec.in:
New. Contributed by Wojciech Polak.
* Makefile.am (dist-hook): New.

* AUTHORS: Added Wojciech and bug reporting addresses.

2002-06-25 Werner Koch <wk@gnupg.org>

Released 0.3.8.

* configure.ac: Bumbed LT version to 9/3/0.
(NEED_GPGSM_VERSION): Need 0.3.8 due to fixed export command.

2002-06-04 Marcus Brinkmann <marcus@g10code.de>

Released 0.3.7.

* configure.ac (AC_INIT): Set version to 0.3.7.
(LIBGPGME_LT_REVISION): Add one.

* README: Document version requirement correctly.

2002-06-02 Marcus Brinkmann <marcus@g10code.de>

* acinclude.m4: Fix Pth check so that it doesn't error out if pth
is not found.

2002-06-02 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add checks for Pth and pthreads.
* acinclude.m4: Add slightly hacked check for pth (seems to be an
autoconf version problem).

2002-05-21 Werner Koch <wk@gnupg.org>

* configure.ac (NEED_GPGSM_VERSION): We need gpgsm 0.3.7.

2002-05-03 Werner Koch <wk@gnupg.org>

Released 0.3.6.

2002-04-05
Marcus Brinkmann <marcus@g10code.de>

* acconfig.h: File removed.
* configure.ac (NEED_GPG_VERSION): Add description.
(NEED_GPGSM_VERSION): Likewise.
(HAVE_DOSISH_SYSTEM): Likewise.
(HAVE_DRIVE_LETTERS): Likewise.
(GPG_PATH): Likewise.
(GPGSM_PATH): Likewise.
* acinclude.m4 (GNUPG_CHECK_TYPEDEF): Likewise.

2002-04-01 Werner Koch <wk@gnupg.org>

Released 0.3.5.

2002-03-17 Marcus Brinkmann <marcus@g10code.de>

* configure.ac: Add automake conditional HAVE_DOSISH_SYSTEM.

2002-03-04 Werner Koch <wk@gnupg.org>

* configure.ac: Bumbed version to 0.3.4-cvs to continue development.

Released 0.3.4.

* configure.ac: Bumbed LT version numbers to (7,1,0), requires
gpgsm 0.3.1.

2002-03-03 Marcus Brinkmann <marcus@g10code.de>

* configure.ac (AC_INIT): Change version number to snapshot CVS
version.

2002-02-13 Werner Koch <wk@gnupg.org>

 * configure.ac (vasprintf,fopencookie): Add checks.

2002-02-12 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (AC_INIT):
 Bump version to 0.3.3.
 * jnlib/Makefile.am: Rever to older version that includes xmalloc
 but not dotlock and some other files. Reported by Stphane
 Corthsy.

2002-02-10 Marcus Brinkmann <marcus@g10code.de>

 * Released 0.3.2.

 * configure.ac (AC_INIT): Bump version to 0.3.2.
 * jnlib/libjnlibconfig.h: Revert to older version that doesn't
 expect libgcrypt. Reported by Jose Carlos Garcia Sogo
 <jsogo@debian.org>.

2002-02-09 Marcus Brinkmann <marcus@g10code.de>

 * Released 0.3.1.

 * configure.ac (LIBGPGME_LT_CURRENT): Bump it up to 6!
 (NEED_GPGSM_VERSION): Bump it up to 0.3.0!
 (AC_INIT): Bump version to 0.3.1

2002-01-22 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (HAVE_JNLIB_LOGGING): Define always for assuan.

2001-12-19 Werner Koch <wk@gnupg.org>

 * configure.ac (VERSION,PACKAGE): Defined and subst. Used for
 AM_INIT_AUTOMAKE and moved all version number more to the top.

2001-12-18 Marcus Brinkmann <marcus@g10code.de>

 * autogen.sh (libtool_vers):
 Bump to 1.4.

 * configure.ac (LIBGPGME_LT_CURRENT): Increment.
 (LIBGPGME_LT_AGE): Reset.
 Improve comment.
 Fix wrong comment character.

2001-12-18 Werner Koch <wk@gnupg.org>

 * acinclude.m4 (GNUPG_FIX_HDR_VERSION): Fixed for new automake.

2001-12-14 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (GPG): Substitute this variable.
(GPGSM): Likewise.

2001-11-22 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (AC_CONFIG_FILES): Add tests/gpg/Makefile and
tests/gpgsm/Makefile.

2001-11-21 Marcus Brinkmann <marcus@g10code.de>

 * Makefile.am (gpgmeplug): New variable, set to gpgmeplug if
[BUILD_GPGMEPLUG].
 * configure.ac (AC_CONFIG_FILES): Add gpgmeplug/Makefile.
Support --enable-gpgmeplug.

2001-11-21 Marcus Brinkmann <marcus@g10code.de>

 * autogen.sh: Tighten version dependencies.

2001-11-20 Marcus Brinkmann <marcus@g10code.de>

 * Makefile.am (SUBDIRS): Support building the assuan library
(currently if GPGSM_PATH is set)..
 * configure.ac: Support building
the assuan library.
 * assuan: New directory, populated with the Assuan library
(copied from the newpg repository).

2001-11-20 Marcus Brinkmann <marcus@g10code.de>

 * configure.ac (NEED_GPGSM_VERSION): New variable. Treat it
similarly to NEED_GPG_VERSION.
 * acconfig.h: Likewise.

2001-11-18 Marcus Brinkmann <marcus@g10code.de>

 * configure.in: Renamed to ...
 * configure.ac: ... this. Update to autoconf 2.52. Lots of small
changes in the transition. Support --with-gpg=PATH and
--with-gpgsm=PATH options. Check if test suites can be run.
 * acconfig.h: Add GPGSM_PATH.
 * Makefile.am: New variable `tests', set to `tests' if

RUN_GPG_TESTS.
(SUBDIRS): Replace string `tests' with variable `tests'.

2001-10-22 Marcus Brinkmann <marcus@g10code.de>

* autogen.sh: Invoke automake with `-a' (add missing files).
Do not invoke configure.

2001-09-17 Werner Koch <wk@gnupg.org>

Released 0.2.3.

* configure.in (NEED_GPG_VERSION): Set to 1.0.6. Incremented LT
current
and age.

* Makefile.am (SUBDIRS): Add doc

2001-06-12 Werner Koch <wk@gnupg.org>

Released 0.2.2.

2001-04-05 Werner Koch <wk@gnupg.org>

* configure.in (NEED_GPG_VERSION): Set to 1.0.4g

2001-04-02 Werner Koch <wk@gnupg.org>

Released 0.2.1.

Changed the copyright notices all over the place.

2001-02-28 Werner Koch <wk@gnupg.org>

Released 0.2.0.

2001-01-18 Werner Koch <wk@gnupg.org>

* autogen.sh: Added option --build-w32.

Copyright (C) 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2010,
2011 g10 Code GmbH

This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
(11:private-key(3:dsa(1:p129:eC_L&$2,6tx.gh1VirlqI9
,^g3.$DveUvX1'oIj)(1:q21: #UFK2z(tuVG)(1:g128:zu^Rab;qeQQA B?/6/aspfE/
gx!Mr0YY*oMrJc2xWG:.r6)(1:y128:Uf]j^@oEn4j#QrRq" RcEa E/}4C[3A
5+~~.#!+
)W&5d)ij)(1:x21:`)))
/*
 error.h - wraps a gpgme error
 Copyright (C) 2003, 2007 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB. If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef __GPGMEPP_ERROR_H__
#define
 __GPGMEPP_ERROR_H__

#include "global.h"

#include <string>
#include <iosfwd>

#include <gpg-error.h>

#ifndef GPGMEPP_ERR_SOURCE_DEFAULT
define GPGMEPP_ERR_SOURCE_DEFAULT GPG_ERR_SOURCE_USER_1
#endif

```
namespace GpgME
{

class GPGMEPP_EXPORT Error
{
public:
  Error() : mErr(0), mMessage() {}
  explicit Error(unsigned int e) : mErr(e), mMessage() {}

  const char *source() const;
  const char *asString() const;

  int code() const;
  int sourceID() const;

  bool isCanceled() const;

  unsigned int encodedError() const
  {
     return mErr;
  }
  int toErrno() const;

  static bool hasSystemError();
  static Error fromSystemError(unsigned int src = GPGMEPP_ERR_SOURCE_DEFAULT);
  static void setSystemError(gpg_err_code_t err);
  static void setErrno(int err);
  static Error fromErrno(int err, unsigned int src = GPGMEPP_ERR_SOURCE_DEFAULT);
  static Error fromCode(unsigned int err, unsigned int src = GPGMEPP_ERR_SOURCE_DEFAULT);

   GPGMEPP_MAKE_SAFE_BOOL_OPERATOR(mErr  &&!isCanceled())
private:
  unsigned int mErr;
  mutable std::string mMessage;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const Error &err);

} // namespace GpgME

#endif /* __GPGMEPP_ERROR_H__ */
/*
  protocol.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2005 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH
```

```
  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
#ifndef __QGPGME_PROTOCOL_H__
#define __QGPGME_PROTOCOL_H__

#include <QString>
#include <QVariant>

#include "qgpgme_export.h"

namespace QGpgME {
class CryptoConfig;
class KeyListJob;
class ListAllKeysJob;
class KeyGenerationJob;
class ImportJob;
class ImportFromKeyserverJob;
class ExportJob;
class DownloadJob;
class DeleteJob;
class EncryptJob;
class DecryptJob;
class SignJob;
```

```
class SignKeyJob;
class
 VerifyDetachedJob;
class VerifyOpaqueJob;
class SignEncryptJob;
class DecryptVerifyJob;
class RefreshKeysJob;
class ChangeExpiryJob;
class ChangeOwnerTrustJob;
class ChangePasswdJob;
class AddUserIDJob;
class SpecialJob;
class KeyForMailboxJob;
class WKSPublishJob;
class TofuPolicyJob;
class QuickJob;
class GpgCardJob;

/** The main entry point for QGpgME Comes in OpenPGP and SMIME(CMS) flavors.
*
* Use the proctocol class to obtain an instance of a job. Jobs
* provide async API for GnuPG that can be connected to signals / slots.
*
* A job is usually started with start() and emits a result signal.
* The parameters of the result signal depend on the job but the last
* two are always a QString for the auditlog and an GpgME::Error for
* an eventual error.
*
* In case async API is used and the result signal is emitted a
* job schedules its own deletion.
*
* Most jobs also provide a synchronous call exec in which case
* you have to explicitly delete the job if you
 don't need it anymore.
*
* \code
* // Async example:
* KeyListJob *job = openpgp()->keyListJob();
* connect(job, &KeyListJob::result, job, [this, job](KeyListResult, std::vector<Key> keys, QString, Error)
* {
*    // keys and resuls can now be used.
* });
* \endcode
*
* \code
* // Sync eaxmple:
* KeyListJob *job = openpgp()->keyListJob(false, false, false);
* std::vector<GpgME::Key> keys;
```

```
* GpgME::KeyListResult result = job->exec(QStringList() <<
*                                 QStringLiteral("alfa@example.net"),
*                                 false, keys);
* delete job;
* \endcode
*/
class QGPGME_EXPORT Protocol
{
public:
  virtual ~Protocol() {}

  virtual QString name() const = 0;

  virtual QString displayName() const = 0;

  virtual KeyListJob          *keyListJob(bool remote = false, bool includeSigs = false, bool validate = false) const =
0;
  virtual ListAllKeysJob      *listAllKeysJob(bool includeSigs = false, bool validate
 = false) const = 0;
  virtual EncryptJob          *encryptJob(bool armor = false, bool textmode = false) const = 0;
  virtual DecryptJob          *decryptJob() const = 0;
  virtual SignJob             *signJob(bool armor = false, bool textMode = false) const = 0;
  virtual VerifyDetachedJob    *verifyDetachedJob(bool textmode = false) const = 0;
  virtual VerifyOpaqueJob      *verifyOpaqueJob(bool textmode = false) const = 0;
  virtual KeyGenerationJob     *keyGenerationJob() const = 0;
  virtual ImportJob           *importJob() const = 0;
  virtual ImportFromKeyserverJob *importFromKeyserverJob() const = 0;
  virtual ExportJob           *publicKeyExportJob(bool armor = false) const = 0;
  // @param charset the encoding of the passphrase in the exported file
  virtual ExportJob           *secretKeyExportJob(bool armor = false, const QString &charset = QString()) const = 0;
  virtual DownloadJob          *downloadJob(bool armor = false) const = 0;
  virtual
 DeleteJob           *deleteJob() const = 0;
  virtual SignEncryptJob       *signEncryptJob(bool armor = false, bool textMode = false) const = 0;
  virtual DecryptVerifyJob     *decryptVerifyJob(bool textmode = false) const = 0;
  virtual RefreshKeysJob       *refreshKeysJob() const = 0;
  virtual ChangeExpiryJob      *changeExpiryJob() const = 0;
  virtual SignKeyJob           *signKeyJob() const = 0;
  virtual ChangePasswdJob      *changePasswdJob() const = 0;
  virtual ChangeOwnerTrustJob  *changeOwnerTrustJob() const = 0;
  virtual AddUserIDJob         *addUserIDJob() const = 0;
  virtual SpecialJob          *specialJob(const char *type, const QMap<QString, QVariant> &args) const = 0;

  /** A key locate job.
   *
   * This tries to find a key in local
   * and remote sources, if the key was remote it is imported
   * by GnuPG. Same as KeyListJob but intended to be used
```

```
   * to locate keys automatically. This ends up calling --locate-keys.
   *
    * Only available for OpenPGP
   *
   * Results are validated. As if keyListJob was called
   * with both includeSigs and validate options.
   */
  virtual KeyListJob *locateKeysJob() const = 0;
  /** Find the best key to use for a mailbox. */
  virtual KeyForMailboxJob *keyForMailboxJob() const = 0;

  /** A Job for interacting with gnupg's wks tools. */
  virtual WKSPublishJob *wksPublishJob() const = 0;

  /** A Job to set tofu policy */
  virtual TofuPolicyJob *tofuPolicyJob() const = 0;

  /** A Job for the quick commands */
  virtual QuickJob *quickJob() const = 0;
};

/** Obtain a reference to the OpenPGP Protocol.
*
* The reference is to a static object.
* @returns Reference to the OpenPGP Protocol.
*/
QGPGME_EXPORT Protocol *openpgp();

/** Obtain a reference to the smime Protocol.
*
* The reference is to a static object.
* @returns Reference to the smime Protocol.
*/
QGPGME_EXPORT Protocol *smime();

/** Obtain a reference to a cryptoConfig
 object.
*
* The reference is to a static object.
* @returns reference to cryptoConfig object.
*/
QGPGME_EXPORT CryptoConfig *cryptoConfig();

/** Obtain a reference to a protocol agnostic GpgCardJob.
*
* The reference is to a static object.
* @returns reference to a GpgCardJob following the job pattern.
*/
```

```
QGPGME_EXPORT GpgCardJob *gpgCardJob();

}
#endif
```

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,

whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.
^L
Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many

libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

^L

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a

portion of it, either verbatim or with modifications and/or translated straightforwardly into
another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any
medium, provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under
the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses

the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can
be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the
ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.
^L
Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute

the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or
link a "work that uses the Library" with the Library to produce a
work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of this License. Also, you must do one
of these things:

a)
Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable "work that
uses the Library", as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (1) uses at run time a
copy of the library already present on the user's computer system,
rather than copying library functions into the executable, and (2)
will
operate properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least
three years, to give the same user the materials specified in
Subsection 6a, above, for a charge no more than the cost of
performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above

specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that
is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.
^L
7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined
with any other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or

distribute the Library or its derivative works. These actions are prohibited
by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution
system which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to

be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.
^L
14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY

AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED
ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms
of the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source file
to most
effectively convey the exclusion of warranty; and each file should
have at least the "copyright" line and a pointer to where the full
notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston,
MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the
 library `Frob' (a library for tweaking knobs) written by James
 Random Hacker.

 <signature of Ty Coon>, 1 April 1990
 Ty Coon, President of Vice

That's all there is to it!

{
  "type": "keys",
  "base64":   false,
  "data": "-----BEGIN PGP PUBLIC KEY BLOCK-----
\n\nmQGiBDbjjp4RBAC2ZbFDX0wmJI8yLDYQdIiZeAuHLmfyHsqXaLGUMZtWiAvn/hNp\nctwahmzKm5oXin
HUvUkLOQ0s8rOlu15nhw4azc30rTP1LsIkn5zORNnFdgYC6RKy\nhOeim/63+/yGtdnTm49lVfaCqwsEmBCEkXa
eWDGq+ie1b89J89T6n/JquwCgoQkj\nVeVGG+B/SzJ6+yifdHWQVkcD/RXDyLXX4+WHGP2aet51XlKojWGws
Zmc9LPPYhwU\n/RcUO7ce1QQb0XFlUVFBhY0JQpM/ty/kNi+aGWFzigbQ+HAWZkUvA8+VIAVneN+p\n+SH
hGIyLTXKpAYTq46AwvllZ5Cpvf02Cp/+W1aVyA0qnBWMyeIxXmR9HOi6lxxn5\ncjajA/9VZufOXWqCXkBvz
4Oy3Q5FbjQQ0/+ty8rDn8OTaiPi41FyUnEi6LO+qyBS\n09FjnZj++PkcRcXW99SNxmEJRY7MuNHt5wIvEH2jN
EOJ9lszzZFBDbuwsjXHK35+\nlPbGEy69xCP26iEafysKKbRXJhE1C+tk8SnK+Gm62sivmK/5arQpQWxwaGEgV
GVz\ndCAoZGVtbyBrZXkpIDxhbHBoYUBleGFtcGxlLm5ldD6IVQQTEQIAFQUCNuOOngML\nCgMDFQMC
AxYCAQIXgAAKCRAtcnzHaGl3NDl4AKCBLmRplv/8ZfSqep5IjqEAuaXv\nWwCgl6NEzT+/WewPTGcwZY+p
LkycLv2IVQQTEQIAFQUCNuOOngMLCgMDFQMCAxYC\nAQIXgAAKCRAtcnzHaGl3NDl4AJ4rouHB+LpC
kNi5C59jHEa1kbANzACgmddtrNSj\n1yPyTCwUwRghPUomECS0EEFsaWNlIChkZW1vIGtleSmIVQQTEQIAF
QUCNuO2qwML\nCgMDFQMCAxYCAQIXgAAKCRAtcnzHaGl3NCeMAJ9MeUVrago5Jc6PdwdeN5OMwby3\
n7QCghW65cZTQlD1bBlIq/QM8bz9AN4G0J0FsZmEgVGVzdCAoZGVtbyBrZXkpIDxh\nbGZhQGV4YW1wbG
UubmV0PohVBBMRAgAVBQI247hYAwsKAwMVAwIDFgIBAheAAAoJ\nEC1yfMdoaXc0t8IAoJPwa6j+Vm5V
i3Nvuo8JZri4PJ/DAJ9dqbmaJdB8FdJnHfGh\n1rXK3y/JcrkBDQQ2448PEAQAnI3XH1f0uyN9fZnw72zsHMw706
g7EW29nD4UDQG4\nOzRZViSrUa5n39eI7QrfTO+1meVvs0y8F/PvFst5jH68rPLnGSrXz4sTl1T4cop1\nFBkquvC
AKwPLy0lE7jjtCyItOSwIOo8xoTfY4JEEXmcqsbm+KHv9yYSF/YK4Cf7b\nIzcAAwcD/Rnl5jKxoucDA96pD282
9TKsLFQSau+Xiy8bvOSSDdlyABsOkNBSaeKO\n3eAQEKgDM7dzjVNTnAlpQ0EQ8Y9Z8pxOWYEQYlaMrnR
BC4DZ2IadzEhLlIOz5BVp\n/jfhrr8oVVBwKZXsrz9PZLz+e4Yn+siUUvlei9boD9L2ZgSOHakPiEYEGBECAAY
F\nAjbjjw8ACgkQLXJ8x2hpdzQgqQCfcDXmD8uNVdKg/C9vqI3JSndqknsAnRxzVeHi\n/iJ73OCKtvFrHbV9Gog
q\n=6f6v\n-----END
 PGP PUBLIC KEY BLOCK-----\n",
  "sec-fprs":   ["A0FF4590BB6122EDEF6E3C542D727CC768697734"]
}

#include "qgpgme/verifyopaquejob.h"
#include "qgpgme/dn.h"
/*
  verifyopaquejob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik

```
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_VERIFYOPAQUEJOB_H__
#define __KLEO_VERIFYOPAQUEJOB_H__

#include "job.h"

#include <memory>

class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class VerificationResult;
}

namespace QGpgME
{
```

```
/**
  @short An abstract base class for asynchronous verification of opaque signatures

  To use a VerifyOpaqueJob, first obtain an instance from the
  CryptoBackend
 implementation, connect the progress() and result()
  signals to suitable slots and then start the verification with a
  call to start(). This call might fail, in which case the
  VerifyOpaqueJob instance will have scheduled it's own
  destruction with a call to QObject::deleteLater().

  After result() is emitted, the VerifyOpaqueJob will schedule
  it's own destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT VerifyOpaqueJob : public Job
{
  Q_OBJECT
protected:
  explicit VerifyOpaqueJob(QObject *parent);
public:
  ~VerifyOpaqueJob();

  /**
    Starts the verification operation. \a signature contains the
    signature data, while \a signedData contains the data over
    which the signature was made.
  */
  virtual GpgME::Error start(const QByteArray &signedData) = 0;

  /*!
    \overload

    If \a plainText is non-null, the plaintext is written
    there. Otherwise, it will be delivered in the second argument
    of result().

    \throws GpgME::Exception if starting fails
  */
  virtual void start(const std::shared_ptr<QIODevice> &signedData, const std::shared_ptr<QIODevice> &plainText
= std::shared_ptr<QIODevice>()) = 0;

  /** Synchronous version of @ref start */
  virtual GpgME::VerificationResult exec(const QByteArray &signedData, QByteArray &plainText) = 0;

Q_SIGNALS:
  void result(const GpgME::VerificationResult &result, const QByteArray &plainText, const QString
&auditLogAsHtml = QString(), const GpgME::Error &auditLogError = GpgME::Error());
};
```

```
}

#endif // __KLEO_VERIFYOPAQUEJOB_H__
/*
  changepasswdjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2010 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_CHANGEPASSWDJOB_H__
#define __KLEO_CHANGEPASSWDJOB_H__

#include "job.h"

namespace GpgME
{
class Error;
class Key;
```

```
}

namespace QGpgME
{

/**
  @short An abstract base class to change a key's passphrase asynchronously

  To use a ChangePasswdJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable
 slots and then start the job with a call
  to start(). This call might fail, in which case the ChangePasswdJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the ChangePasswdJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT ChangePasswdJob : public Job
{
  Q_OBJECT
protected:
  explicit ChangePasswdJob(QObject *parent);
public:
  ~ChangePasswdJob();

  /**
    Starts the passphrase-change operation. \a key is the key to
    change the passphrase of. The passphrase is queried by the
    backend directly, you cannot give it to the job beforehand.
  */
  virtual GpgME::Error start(const GpgME::Key &key) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &result, const QString &auditLogAsHtml = QString(), const GpgME::Error
&auditLogError = GpgME::Error());
};

}

#endif // __KLEO_CHANGEPASSWDJOB_H__
{
  "op": "sign",
  "keys": "A0FF4590BB6122EDEF6E3C542D727CC768697734",
  "sender": "alpha@example.net",
  "data": "Hello world",
  "armor": true,
```

```
  "base64": false
}
/*
  qgpgmeencryptjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2007,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEENCRYPTJOB_H__
#define __QGPGME_QGPGMEENCRYPTJOB_H__

#include "encryptjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "encryptionresult.h"
#else
#include <gpgme++/encryptionresult.h>
```

```
#endif
#ifdef BUILDING_QGPGME
# include "key.h"
#else
#include <gpgme++/key.h>
#endif

namespace QGpgME
{

class QGpgMEEncryptJob
#ifdef Q_MOC_RUN
   : public EncryptJob
#else
  : public _detail::ThreadedJobMixin<EncryptJob, std::tuple<GpgME::EncryptionResult, QByteArray, QString,
GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEEncryptJob(GpgME::Context *context);
  ~QGpgMEEncryptJob();

  /* from EncryptJob */
  GpgME::Error start(const std::vector<GpgME::Key> &recipients,
                const QByteArray &plainText, bool alwaysTrust) Q_DECL_OVERRIDE;

  /* from EncryptJob */
  void start(const std::vector<GpgME::Key> &recipients,
           const std::shared_ptr<QIODevice> &plainText,
           const std::shared_ptr<QIODevice> &cipherText,
           bool alwaysTrust) Q_DECL_OVERRIDE;

  /* from EncryptJob */
  GpgME::EncryptionResult exec(const std::vector<GpgME::Key> &recipients,
                        const QByteArray &plainText, bool alwaysTrust,
                        QByteArray &cipherText)
 Q_DECL_OVERRIDE;
  /* from EncryptJob */
  void start(const std::vector<GpgME::Key> &recipients,
           const std::shared_ptr<QIODevice> &plainText,
           const std::shared_ptr<QIODevice> &cipherText,
           const GpgME::Context::EncryptionFlags flags) Q_DECL_OVERRIDE;
```

```
  /* from EncryptJob */
  GpgME::EncryptionResult exec(const std::vector<GpgME::Key> &recipients,
                               const QByteArray &plainText, const GpgME::Context::EncryptionFlags flags,
                               QByteArray &cipherText) Q_DECL_OVERRIDE;

  /* from EncryptJob */
  void setOutputIsBase64Encoded(bool on) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  bool mOutputIsBase64Encoded;
  GpgME::EncryptionResult mResult;
};

}

#endif // __QGPGME_QGPGMEENCRYPTJOB_H__
Just GNU it!
Just GNU it!
Just GNU it!
{
  "op": "verify",
  "data": "Hello world",
  "signature": "-----BEGIN PGP SIGNATURE-----
\n\niHAEABECADAWIQSg/0WQu2Ei7e9uPFQtcnzHaGl3NAUCW+we3RIcYWxwaGFAZXhh\nbXBsZS5uZXQ
ACgkQLXJ8x2hpdzSwIgCfdfk+n6SsYwa9SYfBwr/o4FmWsa8Anj3V\n8p3ahr3rxNbK7cDbSk/p1zD0\n=oS5d\n---
--END PGP SIGNATURE-----"
}
{
 "result":      {
        "considered":   1,
        "no_user_id":   0,
        "imported_rsa": 0,
        "new_user_ids": 0,
        "new_sub_keys": 0,
        "new_signatures":      0,
        "new_revocations":     0,
        "secret_read":  0,
        "secret_imported":     0,
        "secret_unchanged":    0,
        "skipped_new_keys":    0,
        "not_imported": 0,
        "skipped_v3_keys":     0,
        "imports":     [{
                "fingerprint":  "E8143C489C8D41124DC40D0B47AF4B6961F04784",
                "error_string": "Success",
```

```
                "status":       1
            }]
  }
}
/*
 encryptionresult.h - wraps a gpgme sign result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_ENCRYPTIONRESULT_H__
#define
 __GPGMEPP_ENCRYPTIONRESULT_H__

#include "gpgmefw.h"
#include "result.h"
#include "gpgmepp_export.h"

#include <memory>

#include <vector>
#include <iosfwd>

namespace GpgME
{

class Error;
class InvalidRecipient;

class GPGMEPP_EXPORT EncryptionResult : public Result
```

```
{
public:
  EncryptionResult();
  EncryptionResult(gpgme_ctx_t ctx, int error);
  EncryptionResult(gpgme_ctx_t ctx, const Error &error);
  EncryptionResult(const Error &err);

  const EncryptionResult &operator=(EncryptionResult other)
  {
    swap(other);
    return *this;
  }

  void swap(EncryptionResult &other)
  {
    Result::swap(other);
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  unsigned int numInvalidRecipients() const;

  InvalidRecipient invalidEncryptionKey(unsigned int index) const;
  std::vector<InvalidRecipient> invalidEncryptionKeys() const;

  class Private;
private:
  void init(gpgme_ctx_t ctx);
   std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const EncryptionResult &result);

class GPGMEPP_EXPORT InvalidRecipient
{
  friend class ::GpgME::EncryptionResult;
  InvalidRecipient(const std::shared_ptr<EncryptionResult::Private> &parent, unsigned int index);
public:
  InvalidRecipient();

  const InvalidRecipient &operator=(InvalidRecipient other)
  {
    swap(other);
    return *this;
  }
```

```
  void swap(InvalidRecipient &other)
  {
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  const char *fingerprint() const;
  Error reason() const;

private:
  std::shared_ptr<EncryptionResult::Private> d;
  unsigned int idx;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const InvalidRecipient &recipient);

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(EncryptionResult)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(InvalidRecipient)

#endif // __GPGMEPP_ENCRYPTIONRESULT_H__
/*
  qgpgmeimportjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a
```

```
 special exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __QGPGME_QGPGMEIMPORTJOB_H__
#define __QGPGME_QGPGMEIMPORTJOB_H__

#include "importjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "importresult.h"
#else
#include <gpgme++/importresult.h>
#endif

namespace QGpgME
{

class QGpgMEImportJob
#ifdef Q_MOC_RUN
   : public ImportJob
#else
   : public _detail::ThreadedJobMixin<ImportJob, std::tuple<GpgME::ImportResult,
 QString, GpgME::Error> >
#endif
{
   Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
   void slotFinished();
#endif
public:
   explicit QGpgMEImportJob(GpgME::Context *context);
   ~QGpgMEImportJob();

   /* from ImportJob */
   GpgME::Error start(const QByteArray &keyData) Q_DECL_OVERRIDE;
```

```
  /* from ImportJob */
  GpgME::ImportResult exec(const QByteArray &keyData) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  GpgME::ImportResult mResult;
};

}

#endif // __QGPGME_QGPGMEIMPORTJOB_H__
/* tofupolicyjob.h

  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt
 library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/
#ifndef QGPGME_TOFUPOLICYJOB_H
#define QGPGME_TOFUPOLICYJOB_H

#include "job.h"
```

```
#include "qgpgme_export.h"

#ifdef BUILDING_QGPGME
# include "tofuinfo.h"
#else
# include <gpgme++/tofuinfo.h>
#endif

namespace GpgME
{
  class Key;
} // namespace GpgME

namespace QGpgME {

/**
* Set the TOFU Policy for a key
*/
class QGPGME_EXPORT TofuPolicyJob: public Job
{
  Q_OBJECT
protected:
  explicit TofuPolicyJob(QObject *parent);
public:
  ~TofuPolicyJob();


  /* Set the policy to \a policy see the gpgme
 manual for
   * policy explanations. */
  virtual void start(const GpgME::Key &key, GpgME::TofuInfo::Policy policy) = 0;

  virtual GpgME::Error exec(const GpgME::Key &key, GpgME::TofuInfo::Policy policy) = 0;

Q_SIGNALS:
  /* Result of the operation
   *
   * As usual auditLogAsHtml and auditLogError can be ignored.
   **/
  void result(const GpgME::Error &error,
              const QString &auditLogAsHtml = QString(),
              const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif
```

#include "qgpgme/keyformailboxjob.h"
Using gpgme.js

At first, make sure that the environment you want to use gpgme.js in has access
and permissions for nativeMessaging, and gpgme-json installed. For details,
see the README.

The library itself is started via the {@link init} method. This will test the
nativeMessaging connection, and then resolve into an Object offering
the top level API:

* [encrypt]{@link GpgME#encrypt}
* [decrypt]{@link GpgME#decrypt}
* [sign]{@link GpgME#sign}
* [verify]{@link GpgME#verify}
* [Keyring]{@link GPGME_Keyring}

```
gpgmejs.init()
  .then(function(GPGME) {
     // using GPGME
  }, function(error){
     // error handling;
  })
```

All methods that require communication with nativeMessaging are asynchronous,
using Promises. Rejections will be instances of {@link GPGME_Error}.

An exaeption are Keys, which can be initialized in a 'sync' mode, allowing them
to be cached and used synchronously until manually refreshed.

Keyring and Keys

The gnupg keys
 can be accessed via the [Keyring]{@link GPGME_Keyring}.

The Keyring offers the methods for accessing information on all Keys known to
gnupg.

**Due to security constraints, the javascript-binding currently only offers
limited support for secret-Key interaction.**

The existence of secret Keys is not secret, and those secret Keys can be used
for signing, but Operations that may expose, modify or delete secret Keys are
not supported.

* [getKeysArmored]{@link GPGME_Keyring#getKeysArmored}

* [getKeys]{@link GPGME_Keyring#getKeys}
* [getDefaultKey]{@link GPGME_Keyring#getDefaultKey}
* [generateKey]{@link GPGME_Keyring#generateKey}
* [deleteKey]{@link GPGME_Keyring#deleteKey}
{
  "op": "decrypt",
  "data":
"hQEOA2rm1+5GqHH4EAQAhzzu7VYpE9vFVdqkAALRHSyz8698b8MES7j5ldzXGVnGSWmN0+YXGyWyeB
5tnAXAvUiV10tzoiNaPXoNeOFrHQOWrDsQ1vYukdtblDc3FW/Ywf7aelcFIGh9qydmkPX/EPeULsbgdZp6sybGo
PpEuxzb4CYeRjogB9VvPCRAPb4D/1hRdpoVgWI78JvaeI+xwrP71RuHggZEsM8FSYFBD8c5dY+iAHbPSBI6Q
SZMvMHCu8YVlV40rHFjjoKQ1ox9DHHyvaZkwAZbI/U7+CYZoPoXMAARjCCCW4TIB3VrM70QLjnLSVfW
aCtTnYp2KWaRae0Ze7yPt/h1dYe4ofn/O3UH0kEBqJ99Srtrmr9UWdgikgrWCz5TAV27g2vsZubfMe8vC1QnqAS
azyBy74ibvrXrIvHnhHQvPCkZFRdbgYhV/+KQIQ==",
  "base64": true
}
#include "qgpgme/encryptjob.h"
/*
 context.h - wraps a gpgme key context
 Copyright (C) 2003, 2007 Klarlvdalens Datakonsult AB

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB. If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef __GPGMEPP_CONTEXT_H__
#define __GPGMEPP_CONTEXT_H__

#include "global.h"

#include "error.h"
#include
 "key.h"
#include "verificationresult.h" // for Signature::Notation

```
#include <memory>
#include <vector>
#include <utility>
#include <iosfwd>

namespace GpgME
{

class Data;
class TrustItem;
class ProgressProvider;
class PassphraseProvider;
class EventLoopInteractor;
class EditInteractor;
class AssuanTransaction;

class KeyListResult;
class KeyGenerationResult;
class ImportResult;
class DecryptionResult;
class VerificationResult;
class SigningResult;
class EncryptionResult;
class VfsMountResult;

class EngineInfo;

class GPGMEPP_EXPORT Context
{
  explicit Context(gpgme_ctx_t);
public:
  //using GpgME::Protocol;

  //
  // Creation and destruction:
  //

  static Context *createForProtocol(Protocol proto);
  /** Same as above but returning a unique ptr. */
  static std::unique_ptr<Context> create(Protocol proto);
  static std::unique_ptr<Context> createForEngine(Engine engine, Error *err = nullptr);
  virtual ~Context();

  //
  // Context Attributes
  //
```

```
 Protocol protocol() const;

  void setArmor(bool useArmor);
  bool armor() const;

  void setTextMode(bool useTextMode);
  bool textMode() const;

  void setOffline(bool useOfflineMode);
  bool offline() const;

  const char *getFlag(const char *name) const;
  Error setFlag(const char *name, const char *value);

  enum CertificateInclusion {
     DefaultCertificates = -256,
     AllCertificatesExceptRoot = -2,
     AllCertificates = -1,
     NoCertificates = 0,
     OnlySenderCertificate = 1
  };
  void setIncludeCertificates(int which);
  int includeCertificates() const;

  //using GpgME::KeyListMode;
  void setKeyListMode(unsigned int keyListMode);
  void addKeyListMode(unsigned int keyListMode);
  unsigned int keyListMode() const;

  /** Set the passphrase provider
   *
   * To avoid problems where a class using a context registers
   * itself as the provider the Context does not take ownership
   * of the provider and the caller
must ensure that the provider
   * is deleted if it is no longer needed.
   */
  void setPassphraseProvider(PassphraseProvider *provider);
  PassphraseProvider *passphraseProvider() const;

  /** Set the progress provider
   *
   * To avoid problems where a class using a context registers
   * itself as the provider the Context does not take ownership
   * of the provider and the caller must ensure that the provider
   * is deleted if it is no longer needed.
   */
```

```
  void setProgressProvider(ProgressProvider *provider);
  ProgressProvider *progressProvider() const;

  void setManagedByEventLoopInteractor(bool managed);
  bool managedByEventLoopInteractor() const;

  GpgME::Error setLocale(int category, const char *value);

  EngineInfo engineInfo() const;
  GpgME::Error setEngineFileName(const char *filename);
  GpgME::Error setEngineHomeDirectory(const char *filename);

  enum PinentryMode{
     PinentryDefault = 0,
     PinentryAsk =
 1,
     PinentryCancel = 2,
     PinentryError = 3,
     PinentryLoopback = 4
  };
  GpgME::Error setPinentryMode(PinentryMode which);
  PinentryMode pinentryMode() const;

private:
  friend class ::GpgME::EventLoopInteractor;
  void installIOCallbacks(gpgme_io_cbs *iocbs);
  void uninstallIOCallbacks();

public:
  //
  //
  // Key Management
  //
  //

  //
  // Key Listing
  //

  GpgME::Error startKeyListing(const char *pattern = nullptr, bool secretOnly = false);
  GpgME::Error startKeyListing(const char *patterns[], bool secretOnly = false);

  Key nextKey(GpgME::Error &e);

  KeyListResult endKeyListing();
  KeyListResult keyListResult() const;

  Key key(const char *fingerprint, GpgME::Error &e, bool secret = false);
```

```
  //
  // Key Generation
  //

  KeyGenerationResult generateKey(const char *parameters, Data &pubKey);
  GpgME::Error startKeyGeneration(const char *parameters, Data &pubkey);
  KeyGenerationResult keyGenerationResult()
const;

  //
  // Key Export
  //
  enum ExportMode {
     ExportDefault = 0,
     ExportExtern = 2,
     ExportMinimal = 4,
     ExportSecret = 16,
     ExportRaw = 32,
     ExportPKCS12 = 64,
     ExportNoUID = 128,
     ExportSSH = 256,
  };

  GpgME::Error exportPublicKeys(const char *pattern, Data &keyData);
  GpgME::Error exportPublicKeys(const char *pattern, Data &keyData, unsigned int flags);
  GpgME::Error exportPublicKeys(const char *pattern[], Data &keyData);
  GpgME::Error exportPublicKeys(const char *pattern[], Data &keyData, unsigned int export_mode);
  GpgME::Error startPublicKeyExport(const char *pattern, Data &keyData);
  GpgME::Error startPublicKeyExport(const char *pattern, Data &keyData, unsigned int flags);
  GpgME::Error startPublicKeyExport(const char *pattern[], Data &keyData);
  GpgME::Error startPublicKeyExport(const char *pattern[], Data &keyData, unsigned int export_mode);

  //
  // Key
Import
  //

  ImportResult importKeys(const Data &data);
  ImportResult importKeys(const std::vector<Key> &keys);
  GpgME::Error startKeyImport(const Data &data);
  GpgME::Error startKeyImport(const std::vector<Key> &keys);
  ImportResult importResult() const;

  //
  // Key Deletion
  //
```

```
GpgME::Error deleteKey(const Key &key, bool allowSecretKeyDeletion = false);
GpgME::Error startKeyDeletion(const Key &key, bool allowSecretKeyDeletion = false);

//
// Passphrase changing
//

GpgME::Error passwd(const Key &key);
GpgME::Error startPasswd(const Key &key);

//
// Key Editing
//

GpgME::Error edit(const Key &key, std::unique_ptr<EditInteractor> function, Data &out);
GpgME::Error startEditing(const Key &key, std::unique_ptr<EditInteractor> function, Data &out);



//
// Modern Interface actions. Require 2.1.x
//
Error startCreateKey (const char *userid,
                      const char *algo,

              unsigned long reserved,
                      unsigned long expires,
                      const Key &certkey,
                      unsigned int flags);
Error createKey (const char *userid,
                 const char *algo,
                 unsigned long reserved,
                 unsigned long expires,
                 const Key &certkey,
                 unsigned int flags);

// Same as create key but returning a result
GpgME::KeyGenerationResult createKeyEx (const char *userid,
                                        const char *algo,
                                        unsigned long reserved,
                                        unsigned long expires,
                                        const Key &certkey,
                                        unsigned int flags);

Error addUid(const Key &key, const char *userid);
Error startAddUid(const Key &key, const char *userid);

Error revUid(const
```

```
Key &key, const char *userid);
  Error startRevUid(const Key &key, const char *userid);

  Error createSubkey(const Key &key, const char *algo,
                     unsigned long reserved = 0,
                     unsigned long expires = 0,
                     unsigned int flags = 0);
  Error startCreateSubkey(const Key &key, const char *algo,
                          unsigned long reserved = 0,
                          unsigned long expires = 0,
                          unsigned int flags = 0);

  enum SetExpireFlags {
     SetExpireDefault = 0,
     SetExpireAllSubkeys = 1
  };

  Error setExpire(const Key &k, unsigned long expires,
                  const std::vector<Subkey> &subkeys = std::vector<Subkey>(),
                  const SetExpireFlags flags = SetExpireDefault);
  Error startSetExpire(const Key &k, unsigned long expires,
                       const std::vector<Subkey> &subkeys = std::vector<Subkey>(),

       const SetExpireFlags flags = SetExpireDefault);

  Error revokeSignature(const Key &key, const Key &signingKey,
                        const std::vector<UserID> &userIds = std::vector<UserID>());
  Error startRevokeSignature(const Key &key, const Key &signingKey,
                             const std::vector<UserID> &userIds = std::vector<UserID>());

  // using TofuInfo::Policy
  Error setTofuPolicy(const Key &k, unsigned int policy);
  Error setTofuPolicyStart(const Key &k, unsigned int policy);

  EditInteractor *lastEditInteractor() const;
  std::unique_ptr<EditInteractor> takeLastEditInteractor();

  //
  // SmartCard Editing
  //

  GpgME::Error cardEdit(const Key &key, std::unique_ptr<EditInteractor> function, Data &out);
  GpgME::Error startCardEditing(const Key &key, std::unique_ptr<EditInteractor> function, Data &out);

  EditInteractor *lastCardEditInteractor() const;
  std::unique_ptr<EditInteractor> takeLastCardEditInteractor();
```

```
  //
  // Trust Item Management
  //

  GpgME::Error startTrustItemListing(const char *pattern, int maxLevel);
  TrustItem nextTrustItem(GpgME::Error &e);
  GpgME::Error endTrustItemListing();

  //
  // Assuan Transactions
  //

  GpgME::Error assuanTransact(const char *command, std::unique_ptr<AssuanTransaction> transaction);
  GpgME::Error assuanTransact(const char *command);
  GpgME::Error startAssuanTransaction(const char *command, std::unique_ptr<AssuanTransaction> transaction);
  GpgME::Error startAssuanTransaction(const char *command);

  AssuanTransaction *lastAssuanTransaction() const;
  std::unique_ptr<AssuanTransaction> takeLastAssuanTransaction();

  //
  //
  // Crypto Operations
  //

  enum DecryptionFlags {
     // Keep in line with core's flags
     DecryptNone = 0,
     DecryptVerify = 1,
     DecryptUnwrap = 128,
     DecryptMaxValue = 0x80000000
  };

  //
  // Decryption
  //

  // Alternative way to
set decryption flags as they were added only in
  // 1.9.0 and so other API can still be used but with 1.9.0 additionally
  // flags can be set.
  void setDecryptionFlags (const DecryptionFlags flags);

  DecryptionResult decrypt(const Data &cipherText, Data &plainText);
  GpgME::Error startDecryption(const Data &cipherText, Data &plainText);
  DecryptionResult decrypt(const Data &cipherText, Data &plainText, const DecryptionFlags flags);
  GpgME::Error startDecryption(const Data &cipherText, Data &plainText, const DecryptionFlags flags);
  DecryptionResult decryptionResult() const;
```

```
  //
  // Signature Verification
  //

  VerificationResult verifyDetachedSignature(const Data &signature, const Data &signedText);
  VerificationResult verifyOpaqueSignature(const Data &signedData, Data &plainText);
  GpgME::Error startDetachedSignatureVerification(const Data &signature, const Data &signedText);
  GpgME::Error startOpaqueSignatureVerification(const Data &signedData,
 Data &plainText);
  VerificationResult verificationResult() const;

  //
  // Combined Decryption and Signature Verification
  //

  std::pair<DecryptionResult, VerificationResult> decryptAndVerify(const Data &cipherText, Data &plainText);
  std::pair<DecryptionResult, VerificationResult> decryptAndVerify(const Data &cipherText, Data &plainText,
const DecryptionFlags flags);
  GpgME::Error startCombinedDecryptionAndVerification(const Data &cipherText, Data &plainText);
  GpgME::Error startCombinedDecryptionAndVerification(const Data &cipherText, Data &plainText, const
DecryptionFlags flags);
  // use verificationResult() and decryptionResult() to retrieve the result objects...

  //
  // Signing
  //

  void clearSigningKeys();
  GpgME::Error addSigningKey(const Key &signer);
  Key signingKey(unsigned int index) const;
  std::vector<Key> signingKeys() const;

  void clearSignatureNotations();
  GpgME::Error addSignatureNotation(const char *name,
 const char *value, unsigned int flags = 0);
  GpgME::Error addSignaturePolicyURL(const char *url, bool critical = false);
  const char *signaturePolicyURL() const;
  Notation signatureNotation(unsigned int index) const;
  std::vector<Notation> signatureNotations() const;

  //using GpgME::SignatureMode;
  SigningResult sign(const Data &plainText, Data &signature, SignatureMode mode);
  GpgME::Error startSigning(const Data &plainText, Data &signature, SignatureMode mode);
  SigningResult signingResult() const;

  // wrapper for gpgme_set_sender
  const char *getSender();
```

```
  GpgME::Error setSender(const char *sender);

  //
  // Encryption
  //

  enum EncryptionFlags {
     None = 0,
     AlwaysTrust = 1,
     NoEncryptTo = 2,
     Prepare = 4,
     ExpectSign = 8,
     NoCompress = 16,
     Symmetric = 32,
     ThrowKeyIds = 64,
     EncryptWrap = 128
  };
  EncryptionResult encrypt(const std::vector<Key> &recipients, const
 Data &plainText, Data &cipherText, EncryptionFlags flags);
  GpgME::Error encryptSymmetrically(const Data &plainText, Data &cipherText);
  GpgME::Error startEncryption(const std::vector<Key> &recipients, const Data &plainText, Data &cipherText,
EncryptionFlags flags);
  EncryptionResult encryptionResult() const;

  //
  // Combined Signing and Encryption
  //

  std::pair<SigningResult, EncryptionResult> signAndEncrypt(const std::vector<Key> &recipients, const Data
&plainText, Data &cipherText, EncryptionFlags flags);
  GpgME::Error startCombinedSigningAndEncryption(const std::vector<Key> &recipients, const Data &plainText,
Data &cipherText, EncryptionFlags flags);
  // use encryptionResult() and signingResult() to retrieve the result objects...

  //
  //
  // Audit Log
  //
  //
  enum AuditLogFlags {
     DefaultAuditLog = 0,
     HtmlAuditLog = 1,
     DiagnosticAuditLog = 2,
     AuditLogWithHelp = 128
  };
  GpgME::Error startGetAuditLog(Data
 &output, unsigned int flags = 0);
  GpgME::Error getAuditLog(Data &output, unsigned int flags = 0);
```

```
  //
  //
  // G13 crypto container operations
  //
  //
  GpgME::Error createVFS(const char *containerFile, const std::vector<Key> &recipients);
  VfsMountResult mountVFS(const char *containerFile, const char *mountDir);

  // Spawn Engine
  enum SpawnFlags {
     SpawnNone = 0,
     SpawnDetached = 1,
     SpawnAllowSetFg = 2,
     SpawnShowWindow = 4
  };
  /** Spwan the process \a file with arguments \a argv.
   *
   *  If a data parameter is null the /dev/null will be
   *  used. (Or other platform stuff).
   *
   * @param file The executable to start.
   * @param argv list of arguments file should be argv[0].
   * @param input The data to be sent through stdin.
   * @param output The data to be receive the stdout.
   * @param err The data to receive stderr.
   * @param flags Additional flags.
   *
   * @returns
An error or empty error.
   */
  GpgME::Error spawn(const char *file, const char *argv[],
                     Data &input, Data &output, Data &err,
                     SpawnFlags flags);
  /** Async variant of spawn. Immediately returns after starting the
   * process. */
  GpgME::Error spawnAsync(const char *file, const char *argv[],
                          Data &input, Data &output,
                          Data &err, SpawnFlags flags);
  //
  //
  // Run Control
  //
  //

  bool poll();
  GpgME::Error wait();
  GpgME::Error lastError() const;
```

```
  GpgME::Error cancelPendingOperation();
  GpgME::Error cancelPendingOperationImmediately();

  class Private;
  const Private *impl() const
  {
     return d;
  }
  Private *impl()
  {
     return d;
  }

private:
  // Helper functions that need to be context because they rely
  // on the "Friendlyness" of context to access the gpgme types.
  gpgme_key_t *getKeysFromRecipients(const
 std::vector<Key> &recipients);

private:
  Private *const d;

private: // disable...
  Context(const Context &);
  const Context &operator=(const Context &);
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Context::CertificateInclusion incl);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Context::EncryptionFlags flags);
GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, Context::AuditLogFlags flags);

} // namespace GpgME

#endif // __GPGMEPP_CONTEXT_H__
#include "qgpgme/deletejob.h"
/*
 interface/progressprovider.h - Interface for progress reports
 Copyright (C) 2003 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.
```

```
 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef
 __GPGMEPP_INTERFACES_PROGRESSPROVIDER_H__
#define __GPGMEPP_INTERFACES_PROGRESSPROVIDER_H__

namespace GpgME
{

class ProgressProvider
{
public:
  virtual ~ProgressProvider() {}

  virtual void showProgress(const char *what, int type,
                            int current, int total) = 0;
};

} // namespace GpgME

#endif // __GPGMEPP_INTERFACES_PROGRESSPROVIDER_H__
/*
  multideletejob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.
```

```
  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_MULTIDELETEJOB_H__
#define __KLEO_MULTIDELETEJOB_H__

#include "qgpgme_export.h"
#include "job.h"
#include "protocol.h"

#include <QPointer>

#include <vector>

namespace GpgME
{
class Error;
class Key;
}

namespace QGpgME
{
class DeleteJob;
}

namespace QGpgME
{

/**
  @short A convenience class bundling together multiple DeleteJobs.

  To use a MultiDeleteJob, pass it a
 CryptoBackend implementation,
  connect the progress() and result() signals to suitable slots and
```

```
  then start the delete with a call to start(). This call might
  fail, in which case the MultiDeleteJob instance will have scheduled
  it's own destruction with a call to QObject::deleteLater().

  After result() is emitted, the MultiDeleteJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT MultiDeleteJob : public Job
{
  Q_OBJECT
public:
  explicit MultiDeleteJob(const Protocol *protocol);
  ~MultiDeleteJob();

  /**
    Starts the delete operation. \a keys is the list of keys to
    delete, \a allowSecretKeyDeletion specifies if a key may also
    be deleted if the secret key part is available, too.
  */
  GpgME::Error start(const std::vector<GpgME::Key> &keys, bool allowSecretKeyDeletion = false);

  /* from Job */
  void slotCancel() Q_DECL_OVERRIDE;

Q_SIGNALS:
  void result(const GpgME::Error &result, const
 GpgME::Key &errorKey);

private Q_SLOTS:
  void slotResult(const GpgME::Error &);

private:
  GpgME::Error startAJob();

private:
  const Protocol *mProtocol;
  QPointer<DeleteJob> mJob;
  std::vector<GpgME::Key> mKeys;
  std::vector<GpgME::Key>::const_iterator mIt;
  bool mAllowSecretKeyDeletion;
};

}

#endif // __KLEO_MULTIDELETEJOB_H__
{
  "op": "keylist",
  "keys": [ "bravo@example.net", "alpha@example.net" ],
```

```
  "with-secret": true
}
#include "qgpgme/signjob.h"
#+TITLE: GPGME Python Bindings HOWTO Examples
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}
#+LATEX_HEADER: \author{Ben McGinnes <ben@gnupg.org>}


* Examples
 :PROPERTIES:
 :CUSTOM_ID: gpgme-python3-examples
 :END:

 The contents of this directory are the examples included in the /GNU
 Privacy Guard (GnuPG) Made Easy Python Bindings HOWTO/ file.  Each
 script is explicitly for Python 3 and specifically for Python 3.4 or
 later.

 Some of these scripts may work with Python 2.7, but there are no
 guarantees.  They will include the relevant imports from the
 =__future__= module to facilitate that if possible.


* Copyright and Licensing
 :PROPERTIES:
 :CUSTOM_ID: copyright-and-license
 :END:

 Unless otherwise stated, all the examples in this directory are
 released under the same terms as GPGME
 itself; that is they are dual
 licensed under the terms of both the GNU General Public License
 version 2.0 (or any later version) *and* the GNU Lesser General
 Public License version 2.1 (or any later version).


** Copyright (C) The GnuPG Project, 2018
  :PROPERTIES:
  :CUSTOM_ID: copyright
  :END:

  Copyright  The GnuPG Project, 2018.
```

** License GPL compatible
:PROPERTIES:
:CUSTOM_ID: license
:END:

This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE.
/* qgpgmewkspublishjob.h

Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
Software engineering by Intevation GmbH

QGpgME is free software; you can redistribute it and/or
modify it under the terms of the GNU General Public License as
published by the Free Software Foundation; either version 2 of the
License, or (at your option) any later version.

QGpgME is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

In addition, as a special exception, the copyright holders give
permission to link the code of this program with any edition of

the Qt library by Trolltech AS, Norway (or with modified versions
of Qt that use the same license as Qt), and distribute linked
combinations including the two. You must obey the GNU General
Public License in all respects for all of the code used other than
Qt. If you modify this file, you may extend this exception to
your version of the file, but you are not obligated to do so. If
you do not wish to do so, delete this exception statement from
your version.
*/
#ifndef QGPGME_QGPGMEWKSPUBLISHJOB_H
#define QGPGME_QGPGMEWKSPUBLISHJOB_H

```
#include "wkspublishjob.h"

#include "threadedjobmixin.h"
namespace GpgME
{
  class Key;
} // namespace GpgME

namespace QGpgME {

/**
* Handles Web Key Service Publishing. Needs WKS tools installed and
* server support.
*/
class QGpgMEWKSPublishJob
#ifdef Q_MOC_RUN
  : public WKSPublishJob
#else
  : public _detail::ThreadedJobMixin<WKSPublishJob, std::tuple<GpgME::Error, QByteArray, QByteArray,
QString, GpgME::Error>
 >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEWKSPublishJob(GpgME::Context *context);
  ~QGpgMEWKSPublishJob();

  void startCheck(const QString &mailbox) Q_DECL_OVERRIDE;
  void startCreate(const char *fpr, const QString &mailbox) Q_DECL_OVERRIDE;
  void startReceive(const QByteArray &response) Q_DECL_OVERRIDE;
};

}

#endif
/*
 gpgmefw.h - Forwards declarations for gpgme (0.3 and 0.4)
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.
```

GPGME++ is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public
License as published by the Free Software Foundation; either
version 2 of the License, or (at your option) any later version.

GPGME++ is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License
along with GPGME++; see the file COPYING.LIB. If not, write to the
Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_GPGMEFW_H__
#define
__GPGMEPP_GPGMEFW_H__

struct gpgme_context;
typedef gpgme_context *gpgme_ctx_t;

struct gpgme_data;
typedef gpgme_data *gpgme_data_t;

struct gpgme_io_cbs;

struct _gpgme_key;
typedef struct _gpgme_key *gpgme_key_t;

struct _gpgme_trust_item;
typedef struct _gpgme_trust_item *gpgme_trust_item_t;

struct _gpgme_subkey;
typedef struct _gpgme_subkey *gpgme_sub_key_t;

struct _gpgme_user_id;
typedef struct _gpgme_user_id *gpgme_user_id_t;

struct _gpgme_key_sig;
typedef struct _gpgme_key_sig *gpgme_key_sig_t;

struct _gpgme_sig_notation;
typedef struct _gpgme_sig_notation *gpgme_sig_notation_t;

struct _gpgme_engine_info;
typedef struct _gpgme_engine_info *gpgme_engine_info_t;

```
struct _gpgme_op_keylist_result;
typedef struct _gpgme_op_keylist_result *gpgme_keylist_result_t;

struct _gpgme_recipient;
typedef struct _gpgme_recipient *gpgme_recipient_t;

struct gpgme_conf_opt;
typedef struct gpgme_conf_opt *gpgme_conf_opt_t;

struct gpgme_conf_comp;
typedef struct
 gpgme_conf_comp *gpgme_conf_comp_t;

struct gpgme_conf_arg;
typedef struct gpgme_conf_arg *gpgme_conf_arg_t;

struct _gpgme_tofu_info;
typedef struct _gpgme_tofu_info *gpgme_tofu_info_t;

struct _gpgme_op_query_swdb_result;
typedef struct _gpgme_op_query_swdb_result *gpgme_query_swdb_result_t;

#endif // __GPGMEPP_GPGMEFW_H__
{
  "op": "config",
  "component": "gpg"
}
/*
  importfromkeyserverjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
```

```
   Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as
 a special exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_IMPORTFROMKEYSERVERJOB_H__
#define __KLEO_IMPORTFROMKEYSERVERJOB_H__

#include "abstractimportjob.h"
#include "qgpgme_export.h"

namespace GpgME
{
class Key;
class Error;
class ImportResult;
}

#include <vector>

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous keyserver-importers

  To use a ImportJob, first obtain an instance from the

 CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then start the import with a call
  to start(). This call might fail, in which case the ImportJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the ImportJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT ImportFromKeyserverJob : public AbstractImportJob
```

```
{
  Q_OBJECT
protected:
  explicit ImportFromKeyserverJob(QObject *parent);
public:
  ~ImportFromKeyserverJob();

  /**
    Starts the importing operation. \a keyData contains the data to
    import from.
  */
  virtual GpgME::Error start(const std::vector<GpgME::Key> &keys) = 0;

  virtual GpgME::ImportResult exec(const std::vector<GpgME::Key> &keys) = 0;
};

}

#endif // __KLEO_IMPORTFROMKEYSERVERJOB_H__
;;;; gpgme-package.lisp

;;; Copyright (C) 2006 g10 Code GmbH
;;;
;;; This file is part of GPGME-CL.
;;;
;;; GPGME-CL is free software; you can redistribute it and/or modify
;;; it under the terms of the GNU General Public License as published
;;; by the Free Software Foundation; either version 2 of the License,
;;; or (at your option) any later version.
;;;
;;; GPGME-CL is distributed in the hope that it will be useful, but
;;; WITHOUT ANY WARRANTY; without even the implied warranty of
;;; MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
;;; Lesser General Public License for more details.
;;;
;;; You should have received a copy of the GNU General Public License
;;; along with GPGME; if not, write to the Free Software Foundation,
;;; Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

;;; Conventions:
;;;
;;; gpg-error is used for error handling.
;;;
;;; Standard I/O streams are used for input and output.

(defpackage #:gpgme
 (:use #:common-lisp #:cffi #:gpg-error)
```

```
 (:import-from #:trivial-garbage
               #:finalize)
 (:export #:check-version
   #:*version*
   #:context
   #:protocol
   #:armorp
   #:textmodep
   #:+include-certs-default+
   #:include-certs
   #:keylist-mode
   #:signers
   #:sig-notations
   #:with-context
   #:key-data
   #:get-key
   #:op-encrypt
   #:op-decrypt
   #:op-sign
   #:op-verify
   #:op-import
   #:op-export))
```

UNRECOGNIZED LICENSE; MD5 sum: d97206d060321451439b7c122cd4e699

```
/*
 engineinfo.h
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_ENGINEINFO_H__
```

```
#define __GPGMEPP_ENGINEINFO_H__

#include
 "global.h"

#include <memory>

#include <algorithm>
#include <string>
#include <iostream>

namespace GpgME
{

class GPGMEPP_EXPORT EngineInfo
{
public:
  struct Version
  {
    int major, minor, patch;
    Version()
    {
      major = 0;
      minor = 0;
      patch = 0;
    }

    Version(const std::string& version)
    {
      if (version.empty() ||
          std::sscanf(version.c_str(), "%d.%d.%d", &major, &minor, &patch) != 3) {
          major = 0;
          minor = 0;
          patch = 0;
      }
    }

    Version(const char *version)
    {
      if (!version ||
          std::sscanf(version, "%d.%d.%d", &major, &minor, &patch) != 3) {
          major = 0;
          minor = 0;
          patch = 0;
      }
    }

    bool operator < (const Version& other)
```

```
    {
        if (major > other.major ||
            (major ==
other.major && minor > other.minor) ||
            (major == other.major && minor == other.minor && patch > other.patch) ||
            (major >= other.major && minor >= other.minor && patch >= other.patch)) {
            return false;
        }
        return true;
    }

    bool operator < (const char* other)
    {
        return operator<(Version(other));
    }

    bool operator <= (const Version &other)
    {
        return !operator>(other);
    }

    bool operator <= (const char *other)
    {
        return operator<=(Version(other));
    }

    bool operator > (const char* other)
    {
        return operator>(Version(other));
    }

    bool operator > (const Version & other)
    {
        return !operator<(other) && !operator==(other);
    }

    bool operator >= (const Version &other)
    {
        return !operator<(other);
    }

    bool operator >=
(const char *other)
    {
        return operator>=(Version(other));
    }

    bool operator == (const Version& other)
```

```
    {
        return major == other.major
            && minor == other.minor
            && patch == other.patch;
    }

    bool operator == (const char* other)
    {
        return operator==(Version(other));
    }

    bool operator != (const Version &other)
    {
        return !operator==(other);
    }

    bool operator != (const char *other)
    {
        return operator!=(Version(other));
    }

    friend std::ostream& operator << (std::ostream& stream, const Version& ver)
    {
        stream << ver.major;
        stream << '.';
        stream << ver.minor;
        stream << '.';
        stream << ver.patch;
        return stream;
    }
  };

  EngineInfo();
  explicit EngineInfo(gpgme_engine_info_t engine);

  const EngineInfo &operator=(EngineInfo
other)
  {
    swap(other);
    return *this;
  }

  void swap(EngineInfo &other)
  {
    using std::swap;
    swap(this->d, other.d);
  }
```

```
  bool isNull() const;

  Protocol protocol() const;
  const char *fileName() const;
  const char *version() const;
  Version engineVersion() const;
  const char *requiredVersion() const;
  const char *homeDirectory() const;

private:
  class Private;
  std::shared_ptr<Private> d;
};

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(EngineInfo)

#endif // __GPGMEPP_ENGINEINFO_H__
/*
  refreshkeysjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
```

```
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_REFRESHKEYSJOB_H__
#define __KLEO_REFRESHKEYSJOB_H__

#include "job.h"
#include "qgpgme_export.h"

#include <vector>

namespace GpgME
{
class Error;
class Key;
}

class QStringList;

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous key refreshers.

  To use a RefreshKeysJob, first obtain an instance from the
  CryptoBackend implementation, connect
 the progress() and result()
  signals to suitable slots and then start the key refresh with a
  call to start(). This call might fail, in which case the
  RefreshKeysJob instance will have scheduled its own destruction
  with a call to QObject::deleteLater().

  After result() is emitted, the KeyListJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT RefreshKeysJob : public Job
{
   Q_OBJECT
protected:
   explicit RefreshKeysJob(QObject *parent);
public:
   ~RefreshKeysJob();

   /**
```

```
    Starts the keylist operation. \a pattern is a list of patterns
    used to restrict the list of keys returned. Empty patterns are
    ignored. If \a pattern is empty or contains only empty strings,
    all keys are returned (however, the backend is free to truncate
    the result and should do so; when this happens, it will be
    reported by the reult object).

    If \a secretOnly is true, only keys for which the secret key is

    also available are returned. Use this if you need to select a
    key for signing.
  */
  virtual GpgME::Error start(const QStringList &patterns) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &error);
};

}

#endif // __KLEO_REFRESHKEYSJOB_H__
/*
 gpgagentgetinfoassuantransaction.h - Assuan Transaction to get information from gpg-agent
 Copyright (C) 2009 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA
 02110-1301, USA.
*/

#ifndef __GPGMEPP_GPGAGENTGETINFOASSUANTRANSACTION_H__
#define __GPGMEPP_GPGAGENTGETINFOASSUANTRANSACTION_H__
```

```
#include <interfaces/assuantransaction.h>

#include <string>
#include <vector>

namespace GpgME
{

class GPGMEPP_EXPORT GpgAgentGetInfoAssuanTransaction : public AssuanTransaction
{
public:
  enum InfoItem {
     Version,        // string
     Pid,            // unsigned long
     SocketName,     // string (path)
     SshSocketName,  // string (path)
     ScdRunning,     // (none, returns GPG_ERR_GENERAL when scdaemon isn't running)
     //CommandHasOption, // not supported

     LastInfoItem
  };

  explicit GpgAgentGetInfoAssuanTransaction(InfoItem item);
  ~GpgAgentGetInfoAssuanTransaction();

  std::string version() const;
  unsigned int pid() const;
  std::string socketName() const;
  std::string sshSocketName() const;

private:
  const char *command() const;
  Error data(const char *data, size_t datalen)
 override;
  Data inquire(const char *name, const char *args, Error &err) override;
  Error status(const char *status, const char *args) override;

private:
  void makeCommand() const;

private:
  InfoItem m_item;
  mutable std::string m_command;
  std::string m_data;
};

} // namespace GpgME
```

```
#endif // __GPGMEPP_GPGAGENTGETINFOASSUANTRANSACTION_H__
/*
  debug.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2020 g10 Code GmbH
  Software engineering by Ingo Klcker <dev@ingo-kloecker.de>

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of this
 program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef QGPGME_DEBUG_H
#define QGPGME_DEBUG_H

#include "qgpgme_export.h"

namespace GpgME
{
class Error;
}

class QDebug;
```

```
QGPGME_EXPORT QDebug operator<<(QDebug debug, const GpgME::Error &err);

#endif // QGPGME_DEBUG_H
#include "qgpgme/tofupolicyjob.h"
/*
 eventloopinteractor.h
 Copyright (C) 2003,2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef __GPGMEPP_EVENTLOOPINTERACTOR_H__
#define
 __GPGMEPP_EVENTLOOPINTERACTOR_H__

#include "gpgmepp_export.h"

namespace GpgME
{

class Context;
class Error;
class TrustItem;
class Key;

/*! \file eventloopinteractor.h
   \brief Abstract base class for gpgme's external event loop support

   This class does most of the work involved with hooking GpgME++
   up with external event loops, such as the GTK or Qt ones.
```

It actually provides two interfaces: An interface to the gpgme
IO Callback handling and one for gpgme events. The IO Callback
interface consists of the three methods \c actOn(), \c
registerWatcher() and \c unregisterWatcher(). The event
interface consists of the three methods \c nextTrustItemEvent(),
\c nextKeyEvent() and \c operationDoneEvent().

\sect General Usage

\c EventLoopInteractor is designed to be used as a
singleton. However, in order to make any use of it, you have to
subclass it and reimplement it's pure virtual methods (see
below). We suggest
you keep the constructor protected and
provide a static \c instance() method that returns the single
instance. Alternatively, you can create an instance on the
stack, e.g. in \c main().

If you want \c EventLoopInteractor to manage a particular \c
Context, just call \c manage() on the \c Context. OTOH, if you
want to disable IO callbacks for a \c Context, use \c unmanage().

\sect IO Callback Interface

One part of this interface is represented by \c
registerWatcher() and \c unregisterWatcher(), both of which are
pure virtual. \c registerWatcher() should do anything necessary
to hook up watching of file descriptor \c fd for reading (\c dir
= \c Read) or writing (\c dir = Write) to the event loop you use
and return a tag identifying that particular watching process
uniquely. This could be the index into an array of objects you
use for that purpose or the address of such an object. E.g. in
Qt, you'd essentially just create
a new \c QSocketNotifier:

\verbatim
void * registerWatcher(int fd, Direction dir) {
  return new QSocketNotifier(fd, dir == Read ? QSocketNotifier::Read : QSocketNotifier::Write);
  // misses connecting to the activated() signal...
}
\endverbatim

which uses the address of the created object as unique tag. The
tag returned by \c registerWatcher is stored by \c
EventLoopInteractor and passed as argument to \c
unregisterWatcher(). So, in the picture above, you'd implement \c
unregisterWatcher() like this:

```
  \verbatim
  void unregisterWatcher( void * tag ) {
    delete static_cast<QSocketNotifier*>( tag );
  }
  \endverbatim

  The other part of the IO callback interface is \c actOn(), which
  you should call if you receive notification from your event loop
  about activity on file descriptor \c fd in direction \c dir. In
  the picture above, you'd call this from the slot connected to
  the socket notifier's \c activated()
 signal.

  \note \c registerWatcher() as well as \c unregisterWatcher() may
  be called from within \c actOn(), so be careful with
  e.g. locking in threaded environments and keep in mind that the
  object you used to find the \c fd and \c dir fo the \c actOn()
  call might be deleted when \c actOn() returns!

  \sect Event Handler Interface

*/
class GPGMEPP_EXPORT EventLoopInteractor
{
protected:
  EventLoopInteractor();
public:
  virtual ~EventLoopInteractor();

  static EventLoopInteractor *instance()
  {
     return mSelf;
  }

  void manage(Context *context);
  void unmanage(Context *context);

  enum Direction { Read, Write };
protected:
  //
  // IO Notification Interface
  //

  /** Call this if your event loop detected activity on file
     descriptor fd, with direction dir */
  void actOn(int fd, Direction dir);
```

```
  virtual void *registerWatcher(int fd, Direction dir, bool &ok) = 0;
  virtual void unregisterWatcher(void
 *tag) = 0;

  //
  // Event Handler Interface
  //

  virtual void operationStartEvent(Context *context) = 0;
  virtual void nextTrustItemEvent(Context *context, const TrustItem &item) = 0;
  virtual void nextKeyEvent(Context *context, const Key &key) = 0;
  virtual void operationDoneEvent(Context *context, const Error &e) = 0;

private:
  class Private;
  friend class Private;
  Private *const d;
  static EventLoopInteractor *mSelf;
};

}

#endif // __GPGMEPP_EVENTLOOPINTERACTOR_H__
/*
 interface/passphraseprovider.h - Interface for passphrase callbacks
 Copyright (C) 2003,2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef
```

```
 __GPGMEPP_INTERFACES_PASSPHRASEPROVIDER_H__
#define __GPGMEPP_INTERFACES_PASSPHRASEPROVIDER_H__

namespace GpgME
{

class PassphraseProvider
{
public:
  virtual ~PassphraseProvider() {}

  virtual char *getPassphrase(const char *useridHint, const char *description,
                              bool previousWasBad, bool &canceled) = 0;
};

} // namespace GpgME

#endif // __GPGMEPP_INTERFACES_PASSPHRASEPROVIDER_H__
#include "qgpgme/refreshkeysjob.h"
/*
  abstractimportjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2009 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
```

```
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_ABSTRACTIMPORTJOB_H__
#define __KLEO_ABSTRACTIMPORTJOB_H__

#include "job.h"

#include "qgpgme_export.h"

namespace GpgME
{
class Error;
class ImportResult;
}

namespace QGpgME
{

class QGPGME_EXPORT AbstractImportJob : public Job
{
  Q_OBJECT
protected:
  explicit AbstractImportJob(QObject *parent);
public:
  ~AbstractImportJob();

Q_SIGNALS:
  void result(const
 GpgME::ImportResult &result, const QString &auditLogAsHtml = QString(), const GpgME::Error &auditLogError
= GpgME::Error());
};

}

#endif // __KLEO_IMPORTJOB_H__
/*  quickjob.h

   This file is part of qgpgme, the Qt API binding for gpgme
   Copyright (c) 2017 Intevation GmbH
   Copyright (c) 2020 g10 Code GmbH
   Software engineering by Ingo Klcker <dev@ingo-kloecker.de>

   QGpgME is free software; you can redistribute it and/or
   modify it under the terms of the GNU General Public License as
```

```
   published by the Free Software Foundation; either version 2 of the
   License, or (at your option) any later version.

   QGpgME is distributed in the hope that it will be useful,
   but WITHOUT ANY WARRANTY; without even the implied warranty of
   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
   General Public License for more details.

   You should have received a copy of the GNU General Public License along
   with this program; if not, write to the Free Software Foundation, Inc.,
   51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a special exception, the copyright holders give
    permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/
#ifndef QGPGME_QUICKJOB_H
#define QGPGME_QUICKJOB_H

#include "job.h"

#include "qgpgme_export.h"

#include <QDateTime>

#ifdef BUILDING_QGPGME
# include "key.h"
#else
# include <gpgme++/key.h>
#endif

class QString;

namespace QGpgME{

/**
* Interface to the modern key manipulation functions.
*/
class QGPGME_EXPORT QuickJob : public Job
{
  Q_OBJECT
```

```
public:
  explicit QuickJob(QObject *parent = Q_NULLPTR);
  ~QuickJob();

   /** Start --quick-gen-key */
  virtual void startCreate(const QString &uid,
                           const char *algo,
                           const QDateTime &expires = QDateTime(),
                           const GpgME::Key &key = GpgME::Key(),
                           unsigned int flags = 0) = 0;

  /** Start --quick-adduid */
  virtual void startAddUid(const GpgME::Key &key, const QString &uid) = 0;

  /** Start --quick-revuid */
  virtual void startRevUid(const GpgME::Key &key, const QString &uid) = 0;

  /** Start --quick-add-key */
  virtual void startAddSubkey(const GpgME::Key &key, const char *algo,
                              const QDateTime &expires = QDateTime(),
                              unsigned int flags = 0) = 0;

  /**
     Starts the operation to revoke the signatures made with the key \a signingKey on the
     user IDs \a userIds of the key \a key. If \a userIds is an empty list, then all
     signatures made with
 \a signingKey on the user IDs of \a key will be revoked.
  */
  virtual void startRevokeSignature(const GpgME::Key &key, const GpgME::Key &signingKey,
                                    const std::vector<GpgME::UserID> &userIds = std::vector<GpgME::UserID>()) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &error,
              const QString &auditLogAsHtml = QString(), const GpgME::Error &auditLogError = GpgME::Error());
};

}
#endif
/* argparse.h - Argument parser for option handling.
* Copyright (C) 1998,1999,2000,2001,2006 Free Software Foundation, Inc.
*
* This file is part of GnuPG.
*
* GnuPG is free software; you can redistribute it and/or modify it
* under the terms of either
*
*   - the GNU Lesser General Public License as published by the Free
*     Software Foundation; either version 3 of the License, or (at
```

```
*     your option) any later version.
*
* or
*
*   - the GNU General Public License as published by the Free
*     Software Foundation; either version 2 of the License, or (at
*     your option) any later version.
*
* or both in parallel, as here.
*
* GnuPG is distributed in the hope that it will be useful, but
* WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
* General Public License for more details.
*
* You should have received a copies of the GNU General Public License
* and the GNU Lesser General
 Public License along with this program;
* if not, see <https://www.gnu.org/licenses/>.
*/

#ifndef GNUPG_COMMON_ARGPARSE_H
#define GNUPG_COMMON_ARGPARSE_H

#include <stdio.h>

typedef struct
{
 int  *argc;       /* Pointer to ARGC (value subject to change). */
 char ***argv;       /* Pointer to ARGV (value subject to change). */
 unsigned int flags; /* Global flags.  May be set prior to calling the
                        parser.  The parser may change the value.  */
 int err;            /* Print error description for last option.
                        Either 0,  ARGPARSE_PRINT_WARNING or
                        ARGPARSE_PRINT_ERROR.  */

 int r_opt;        /* Returns option code. */
 int r_type;       /* Returns type of option value.  */
 union {
   int   ret_int;
   long  ret_long;
   unsigned long ret_ulong;
   char *ret_str;
 } r;        /* Return values */

 struct {
   int idx;
   int inarg;
```

```
  int stopped;
  const char *last;
  void *aliases;
  const
 void *cur_alias;
  void *iio_list;
 } internal;     /* Private - do not change. */
} ARGPARSE_ARGS;

typedef struct
{
 int         short_opt;
 const char  *long_opt;
 unsigned int flags;
 const char  *description; /* Optional option description. */
} ARGPARSE_OPTS;


/* Global flags (ARGPARSE_ARGS).  */
#define ARGPARSE_FLAG_KEEP       1   /* Do not remove options form argv.     */
#define ARGPARSE_FLAG_ALL        2   /* Do not stop at last option but return
                                remaining args with R_OPT set to -1. */
#define ARGPARSE_FLAG_MIXED      4   /* Assume options and args are mixed.   */
#define ARGPARSE_FLAG_NOSTOP     8   /* Do not stop processing at "--".      */
#define ARGPARSE_FLAG_ARG0      16   /* Do not skip the first arg.           */
#define ARGPARSE_FLAG_ONEDASH   32   /* Allow long options with one dash.    */
#define ARGPARSE_FLAG_NOVERSION 64   /* No output for "--version".           */

#define ARGPARSE_FLAG_STOP_SEEN 256  /* Set
 to true if a "--" has been seen. */

/* Flags for each option (ARGPARSE_OPTS).  The type code may be
  ORed with the OPT flags.  */
#define ARGPARSE_TYPE_NONE        0  /* Does not take an argument.        */
#define ARGPARSE_TYPE_INT         1  /* Takes an int argument.            */
#define ARGPARSE_TYPE_STRING      2  /* Takes a string argument.          */
#define ARGPARSE_TYPE_LONG        3  /* Takes a long argument.            */
#define ARGPARSE_TYPE_ULONG       4  /* Takes an unsigned long argument.  */
#define ARGPARSE_OPT_OPTIONAL (1<<3) /* Argument is optional.             */
#define ARGPARSE_OPT_PREFIX   (1<<4) /* Allow 0x etc. prefixed values.    */
#define ARGPARSE_OPT_IGNORE   (1<<6) /* Ignore command or option.         */
#define ARGPARSE_OPT_COMMAND  (1<<7) /* The argument is a command.        */

#define ARGPARSE_TYPE_MASK  7  /* Mask for the type values (internal).  */

/* A set of macros to make option definitions easier to read.  */
#define ARGPARSE_x(s,l,t,f,d) \
```

```
    { (s), (l), ARGPARSE_TYPE_ ## t | (f), (d) }

#define ARGPARSE_s(s,l,t,d) \
    { (s), (l), ARGPARSE_TYPE_ ## t, (d) }
#define ARGPARSE_s_n(s,l,d) \
    { (s), (l), ARGPARSE_TYPE_NONE, (d) }
#define ARGPARSE_s_i(s,l,d) \
    { (s), (l), ARGPARSE_TYPE_INT, (d) }
#define ARGPARSE_s_s(s,l,d) \
    { (s), (l), ARGPARSE_TYPE_STRING, (d) }
#define ARGPARSE_s_l(s,l,d) \
    { (s), (l), ARGPARSE_TYPE_LONG, (d) }
#define ARGPARSE_s_u(s,l,d) \
    { (s), (l), ARGPARSE_TYPE_ULONG, (d) }

#define ARGPARSE_o(s,l,t,d) \
    { (s), (l), (ARGPARSE_TYPE_ ## t  | ARGPARSE_OPT_OPTIONAL), (d) }
#define ARGPARSE_o_n(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_NONE   | ARGPARSE_OPT_OPTIONAL), (d) }
#define ARGPARSE_o_i(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_INT    | ARGPARSE_OPT_OPTIONAL), (d) }
#define ARGPARSE_o_s(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_STRING | ARGPARSE_OPT_OPTIONAL), (d) }
#define ARGPARSE_o_l(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_LONG   | ARGPARSE_OPT_OPTIONAL), (d) }
#define
 ARGPARSE_o_u(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_ULONG  | ARGPARSE_OPT_OPTIONAL), (d) }

#define ARGPARSE_p(s,l,t,d) \
    { (s), (l), (ARGPARSE_TYPE_ ## t  | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_p_n(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_NONE   | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_p_i(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_INT    | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_p_s(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_STRING | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_p_l(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_LONG   | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_p_u(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_ULONG  | ARGPARSE_OPT_PREFIX), (d) }

#define ARGPARSE_op(s,l,t,d) \
    { (s), (l), (ARGPARSE_TYPE_ ## t \
            | ARGPARSE_OPT_OPTIONAL | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_op_n(s,l,d) \
    { (s), (l), (ARGPARSE_TYPE_NONE \
            | ARGPARSE_OPT_OPTIONAL | ARGPARSE_OPT_PREFIX), (d) }
```

```
#define ARGPARSE_op_i(s,l,d)
 \
   { (s), (l), (ARGPARSE_TYPE_INT \
            | ARGPARSE_OPT_OPTIONAL | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_op_s(s,l,d) \
   { (s), (l), (ARGPARSE_TYPE_STRING \
            | ARGPARSE_OPT_OPTIONAL | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_op_l(s,l,d) \
   { (s), (l), (ARGPARSE_TYPE_LONG \
            | ARGPARSE_OPT_OPTIONAL | ARGPARSE_OPT_PREFIX), (d) }
#define ARGPARSE_op_u(s,l,d) \
   { (s), (l), (ARGPARSE_TYPE_ULONG \
            | ARGPARSE_OPT_OPTIONAL | ARGPARSE_OPT_PREFIX), (d) }

#define ARGPARSE_c(s,l,d) \
   { (s), (l), (ARGPARSE_TYPE_NONE | ARGPARSE_OPT_COMMAND), (d) }

#define ARGPARSE_ignore(s,l) \
   { (s), (l), (ARGPARSE_OPT_IGNORE), "@" }

#define ARGPARSE_group(s,d) \
   { (s), NULL, 0, (d) }

#define ARGPARSE_end()  { 0, NULL, 0, NULL }


/* Other constants.  */
#define ARGPARSE_PRINT_WARNING  1
#define ARGPARSE_PRINT_ERROR    2


/* Error values.  */
#define ARGPARSE_IS_ARG          (-1)
#define ARGPARSE_INVALID_OPTION
   (-2)
#define ARGPARSE_MISSING_ARG      (-3)
#define ARGPARSE_KEYWORD_TOO_LONG  (-4)
#define ARGPARSE_READ_ERROR       (-5)
#define ARGPARSE_UNEXPECTED_ARG    (-6)
#define ARGPARSE_INVALID_COMMAND   (-7)
#define ARGPARSE_AMBIGUOUS_OPTION  (-8)
#define ARGPARSE_AMBIGUOUS_COMMAND (-9)
#define ARGPARSE_INVALID_ALIAS     (-10)
#define ARGPARSE_OUT_OF_CORE       (-11)
#define ARGPARSE_INVALID_ARG       (-12)


int arg_parse (ARGPARSE_ARGS *arg, ARGPARSE_OPTS *opts);
```

```
int optfile_parse (FILE *fp, const char *filename, unsigned *lineno,
    ARGPARSE_ARGS *arg, ARGPARSE_OPTS *opts);
void usage (int level);
const char *strusage (int level);
void set_strusage (const char *(*f)( int ));
void argparse_register_outfnc (int (*fnc)(int, const char *));

#endif /*GNUPG_COMMON_ARGPARSE_H*/
/*
  qgpgmedecryptverifyjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEDECRYPTVERIFYJOB_H__
#define __QGPGME_QGPGMEDECRYPTVERIFYJOB_H__

#include "decryptverifyjob.h"
```

```
#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "decryptionresult.h"
#else
#include <gpgme++/decryptionresult.h>
#endif
#ifdef BUILDING_QGPGME
# include "verificationresult.h"
#else
#include <gpgme++/verificationresult.h>
#endif

namespace QGpgME
{

class
 QGpgMEDecryptVerifyJob
#ifdef Q_MOC_RUN
  : public DecryptVerifyJob
#else
  : public _detail::ThreadedJobMixin<DecryptVerifyJob, std::tuple<GpgME::DecryptionResult,
GpgME::VerificationResult, QByteArray, QString, GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEDecryptVerifyJob(GpgME::Context *context);
  ~QGpgMEDecryptVerifyJob();

  /* from DecryptVerifyJob */
  GpgME::Error start(const QByteArray &cipherText) Q_DECL_OVERRIDE;

  /* from DecryptVerifyJob */
  void start(const std::shared_ptr<QIODevice> &cipherText, const std::shared_ptr<QIODevice> &plainText)
Q_DECL_OVERRIDE;

  /* from DecryptVerifyJob */
  std::pair<GpgME::DecryptionResult, GpgME::VerificationResult>
  exec(const QByteArray &cipherText, QByteArray &plainText) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;
```

```
private:
  std::pair<GpgME::DecryptionResult,
 GpgME::VerificationResult> mResult;
};

}
#endif // __QGPGME_QGPGMEDECRYPTVERIFYJOB_H__
/*
  qgpgmeverifyopaquejob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2007,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEVERIFYOPAQUEJOB_H__
#define __QGPGME_QGPGMEVERIFYOPAQUEJOB_H__

#include "verifyopaquejob.h"

#include "threadedjobmixin.h"
```

```
#ifdef BUILDING_QGPGME
# include "verificationresult.h"
#else
#include <gpgme++/verificationresult.h>
#endif

namespace QGpgME
{

class QGpgMEVerifyOpaqueJob
#ifdef Q_MOC_RUN
  : public VerifyOpaqueJob
#else
  : public _detail::ThreadedJobMixin<VerifyOpaqueJob,
 std::tuple<GpgME::VerificationResult, QByteArray, QString, GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEVerifyOpaqueJob(GpgME::Context *context);
  ~QGpgMEVerifyOpaqueJob();

  /* from VerifyOpaqueJob */
  GpgME::Error start(const QByteArray &signedData) Q_DECL_OVERRIDE;

  /* from VerifyOpaqueJob */
  void start(const std::shared_ptr<QIODevice> &signedData, const std::shared_ptr<QIODevice> &plainText)
Q_DECL_OVERRIDE;

  /* form VerifyOpaqueJob */
  GpgME::VerificationResult exec(const QByteArray &signedData, QByteArray &plainData)
Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  GpgME::VerificationResult mResult;
};

}

#endif // __QGPGME_QGPGMEVERIFYOPAQUEJOB_H__
```

```
#include "qgpgme/wkspublishjob.h"
/*
  qgpgmekeygenerationjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEKEYGENERATIONJOB_H__
#define __QGPGME_QGPGMEKEYGENERATIONJOB_H__

#include "keygenerationjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "keygenerationresult.h"
#else
#include <gpgme++/keygenerationresult.h>
#endif
```

```
namespace QGpgME
{

class QGpgMEKeyGenerationJob
#ifdef Q_MOC_RUN
  : public KeyGenerationJob
#else
  : public
 _detail::ThreadedJobMixin<KeyGenerationJob, std::tuple<GpgME::KeyGenerationResult, QByteArray, QString,
GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
private Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEKeyGenerationJob(GpgME::Context *context);
  ~QGpgMEKeyGenerationJob();

  /* from KeygenerationJob */
  GpgME::Error start(const QString &parameters) Q_DECL_OVERRIDE;
};

}

#endif // __QGPGME_QGPGMEKEYGENERATIONJOB_H__
This is gpgme.info, produced by makeinfo version 6.5 from gpgme.texi.

Copyright  20022008, 2010, 20122018 g10 Code GmbH.

   Permission is granted to copy, distribute and/or modify this
   document under the terms of the GNU General Public License as
   published by the Free Software Foundation; either version 3 of the
   License, or (at your option) any later version.  The text of the
   license can be found in the section entitled Copying.

  This document is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General
Public License for more details.
INFO-DIR-SECTION GNU Libraries
START-INFO-DIR-ENTRY
* GPGME: (gpgme).         Adding support for cryptography to your program.
END-INFO-DIR-ENTRY
```

This file documents the GPGME library.

This is Edition 1.14.1-beta35, last updated 13 December 2019, of The GnuPG Made Easy Reference Manual, for Version 1.14.1-beta35.

Copyright 20022008, 2010, 20122018 g10 Code GmbH.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. The text of the license can be found in the section entitled Copying.

This document is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

Indirect:
gpgme.info-1: 1688
gpgme.info-2: 301751

Tag Table:
(Indirect)
Node: Top1688
Node: Introduction9067
Node: Getting Started9857
Node: Features11318
Node: Overview12630
Node: Preparation13739
Node: Header14736
Node: Building the Source15483
Node: Largefile Support (LFS)17627
Node: Using Automake23043
Node: Using Libtool25596
Node: Library Version Check25958
Node: Signal Handling32018
Node: Multi-Threading33288
Ref: Multi-Threading-Footnote-134704
Node: Protocols and Engines35127
Node: Engine Version Check37878
Node: Engine Information40401
Node: Engine Configuration44261
Node: OpenPGP45565
Node: Cryptographic Message Syntax45905

Node: Assuan46218
Node: Algorithms46592
Ref: Algorithms-Footnote-147071
Node: Public Key Algorithms47199
Node: Hash Algorithms49801
Node: Error Handling51015
Node: Error Values52889
Node: Error Sources58092
Node: Error Codes60532
Node: Error Strings65325
Node: Exchanging Data67132
Node: Creating Data Buffers69017
Node: Memory Based Data Buffers69533
Node: File Based Data Buffers72966
Node: Callback Based Data Buffers76079
Node: Destroying Data Buffers80270
Node: Manipulating Data Buffers81777
Node: Data Buffer I/O Operations82269
Node: Data Buffer Meta-Data84642
Node: Data Buffer Convenience89161
Node: Contexts91381
Node: Creating Contexts92500
Node: Destroying Contexts93347
Node: Result Management93686
Node:
Context Attributes95267
Node: Protocol Selection96434
Node: Crypto Engine97480
Node: Setting the Sender99369
Node: ASCII Armor100882
Node: Text Mode101511
Node: Offline Mode102445
Node: Pinentry Mode103943
Node: Included Certificates105837
Node: Key Listing Mode107283
Node: Passphrase Callback112407
Node: Progress Meter Callback115969
Node: Status Message Callback117954
Node: Context Flags119719
Node: Locale126330
Node: Additional Logs127922
Node: Key Management130120
Node: Key objects131344
Node: Listing Keys145918
Node: Information About Keys154571
Node: Manipulating Keys155879
Node: Generating Keys158777
Node: Signing Keys177097

Node: Exporting Keys182611
Node: Importing Keys189891
Ref: Importing Keys-Footnote-1197294
Node: Deleting Keys197422
Node: Changing Passphrases199702
Node: Changing TOFU Data201029
Node: Advanced Key Editing203137
Node: Crypto Operations205870
Node: Decrypt207127
Node: Verify214407
Node: Decrypt and Verify227500
Node: Sign230355
Node: Selecting Signers230919
Node:
Creating a Signature232325
Node: Signature Notation Data237095
Node: Encrypt239380
Node: Encrypting a Plaintext239736
Node: Miscellaneous254148
Node: Running other Programs254560
Node: Using the Assuan protocol256723
Node: Checking for updates259521
Node: Run Control264338
Node: Waiting For Completion265082
Node: Using External Event Loops267207
Node: I/O Callback Interface269179
Node: Registering I/O Callbacks274107
Node: I/O Callback Example276146
Node: I/O Callback Example GTK+282771
Node: I/O Callback Example GDK284560
Node: I/O Callback Example Qt286202
Node: Cancellation288490
Node: UI Server Protocol290798
Ref: UI Server Protocol-Footnote-1292233
Node: UI Server Encrypt292352
Node: UI Server Sign297710
Node: UI Server Decrypt301751
Node: UI Server Verify303406
Node: UI Server Set Input Files306978
Node: UI Server Sign/Encrypt Files308048
Node: UI Server Verify/Decrypt Files309856
Node: UI Server Import/Export Keys311732
Node: UI Server Checksum Files312794
Node:
Miscellaneous UI Server Commands315012
Ref: command SENDER316943
Node: Debugging318645
Node: Deprecated Functions320394

Node: Library Copying343403
Node: Copying371623
Node: Concept Index409373
Node: Function and Data Index424085

End Tag Table

Local Variables:
coding: utf-8
End:
/*
  decryptverifyjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two. You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt. If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so. If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_DECRYPTVERIFYJOB_H__
#define __KLEO_DECRYPTVERIFYJOB_H__

```
#include "job.h"

#include <memory>

class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class DecryptionResult;
class VerificationResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous combined decrypters and verifiers

  To use a DecryptVerifyJob, first obtain an
 instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then start the operation with a
  call to start(). This call might fail, in which case the
  DecryptVerifyJob instance will have scheduled it's own destruction with
  a call to QObject::deleteLater().

  After result() is emitted, the DecryptVerifyJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT DecryptVerifyJob : public Job
{
  Q_OBJECT
protected:
  explicit DecryptVerifyJob(QObject *parent);
public:
  ~DecryptVerifyJob();

  /**
    Starts the combined decryption and verification operation.
    \a cipherText is the data to decrypt and later verify.
  */
  virtual GpgME::Error start(const QByteArray &cipherText) = 0;

  /*!
    \overload
```

```
    If \a plainText is non-null, the plaintext is written
    there. Otherwise, it will be delivered in the third argument
    of result().


 \throws GpgME::Exception if starting fails
   */
   virtual void start(const std::shared_ptr<QIODevice> &cipherText, const std::shared_ptr<QIODevice> &plainText
= std::shared_ptr<QIODevice>()) = 0;

   /** Synchronous equivalent of start() */
   virtual std::pair<GpgME::DecryptionResult, GpgME::VerificationResult>
   exec(const QByteArray &cipherText, QByteArray &plainText) = 0;

Q_SIGNALS:
   void result(const GpgME::DecryptionResult &decryptionresult,
               const GpgME::VerificationResult &verificationresult,
               const QByteArray &plainText, const QString &auditLogAsHtml = QString(),
               const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif // __KLEO_DECRYPTVERIFYJOB_H__
000
 *H
010 UDE1!0U
Deutsches Forschungsnetz10UDFN-PCA1.0,U%DFN Top Level Certification Authority1!0 *H
 certify@pca.dfn.de0
001102164724Z
011230180000Z010 UDE1!0U
Deutsches Forschungsnetz10UDFN-PCA1+0)U"DFN Server Certification Authority1!0 *H
 certify@pca.dfn.de0"0
 *H
0
W`r;wXu)QYHm1t]4?|-.B(iw6G01N>[mQSwC'muw~E'l-M
+<[A|F)F%
ZiRaW=OC,,meKW@J-*<,L}:Bnm-kv
EYBmu tt[-%,R+n0j0U00U0U{upz*D\
v0Ux0v09753http://www.pca.dfn.de/dfnpca/certify/ssl/dfnpca.crx09753http://www.pca.dfn.de/dfnpca/certify/ssl/dfn
pca.crl0 `HB0) `HBhttps://mystic.pca.dfn.de/0A `HB42http://www.pca.dfn.de/dfnpca/policy/wwwpolicy.html0 `HB
This certificate was issued by the DFN-PCA, the Top
Level Certification Authority of the German Research
Network (Deutsches Forschungsnetz, DFN).
The key owner's identity was authenticated in
accordance with the DFN World Wide Web Policy, v1.00! `HBcgi/check-rev.cgi?0
 *H
```

\C)2
+ZYG| UCA|PzYFnTj@SA)/<HU+4t?@g?pb5w'Z;dqLi9\(d=
,}h?c(MeM44=Qe/_^^JyYN/61&jPFXifP&#;/KZ
1 xOK?ps
```
/*
 gpgsetownertrusteditinteractor.h - Edit Interactor to change the owner trust of an OpenPGP key
 Copyright (C) 2007 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston,
 MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_GPGSETOWNERTRUSTEDITINTERACTOR_H__
#define __GPGMEPP_GPGSETOWNERTRUSTEDITINTERACTOR_H__

#include <editinteractor.h>
#include <key.h>

#include <string>

namespace GpgME
{

class GPGMEPP_EXPORT GpgSetOwnerTrustEditInteractor : public EditInteractor
{
public:
  explicit GpgSetOwnerTrustEditInteractor(Key::OwnerTrust ownertrust);
  ~GpgSetOwnerTrustEditInteractor();

private:
  const char *action(Error &err) const override;
```

```
  unsigned int nextState(unsigned int statusCode, const char *args, Error &err) const override;

private:
  const Key::OwnerTrust m_ownertrust;
};

} // namespace GpgME

#endif // __GPGMEPP_GPGSETOWNERTRUSTEDITINTERACTOR_H__
/* run-support.h - Helper routines for run-* test programs.
* Copyright (C) 2000 Werner Koch (dd9jn)
* Copyright (C) 2001, 2002, 2003, 2004, 2009 g10 Code GmbH
*
* This file is part of GPGME.
*
* GPGME is free software; you can redistribute it and/or modify it
* under the terms of the GNU Lesser General Public License as
* published by the Free Software Foundation; either version 2.1 of
* the License, or (at your option) any later version.
*
* GPGME is distributed in the hope that it will be useful, but
* WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
* Lesser General Public License for more details.
*
* You should have received a copy of the GNU Lesser General Public
* License along with this program; if not, see <https://gnu.org/licenses/>.
* SPDX-License-Identifier: LGPL-2.1-or-later
*/

#include <unistd.h>
#include <errno.h>
#include <stdlib.h>
#include <locale.h>

#ifdef HAVE_W32_SYSTEM
#include
 <windows.h>
#endif

#include <gpgme.h>

#ifndef DIM
#define DIM(v)       (sizeof(v)/sizeof((v)[0]))
#endif

#define fail_if_err(err)     \
 do       \
```

```
  {       \
    if (err)      \
      {       \
        fprintf (stderr, PGM": file %s line %d: <%s> %s\n", \
                 __FILE__, __LINE__, gpgme_strsource (err), \
    gpgme_strerror (err));   \
        exit (1);      \
      }       \
  }       \
 while (0)


static const char *
nonnull (const char *s)
{
 return s? s :"[none]";
}


void
print_data (gpgme_data_t dh)
{
#define BUF_SIZE 512
 char buf[BUF_SIZE + 1];
 int ret;

 ret = gpgme_data_seek (dh, 0, SEEK_SET);
 if (ret)
   fail_if_err (gpgme_err_code_from_errno (errno));
 while ((ret = gpgme_data_read (dh, buf, BUF_SIZE)) > 0)
   fwrite (buf, ret, 1, stdout);
 if (ret < 0)
   fail_if_err (gpgme_err_code_from_errno (errno));
}


gpgme_error_t
passphrase_cb (void *opaque, const char *uid_hint, const char *passphrase_info,
        int
 last_was_bad, int fd)
{
 int res;
 char pass[] = "abc\n";
 int passlen = strlen (pass);
 int off = 0;

 (void)opaque;
 (void)uid_hint;
```

```
 (void)passphrase_info;
 (void)last_was_bad;

 do
   {
     res = gpgme_io_write (fd, &pass[off], passlen - off);
     if (res > 0)
 off += res;
   }
 while (res > 0 && off != passlen);

 return off == passlen ? 0 : gpgme_error_from_errno (errno);
}


char *
make_filename (const char *fname)
{
 const char *srcdir = getenv ("srcdir");
 char *buf;

 if (!srcdir)
   srcdir = ".";
 buf = malloc (strlen(srcdir) + strlen(fname) + 2);
 if (!buf)
   {
     fprintf (stderr, "%s:%d: could not allocate string: %s\n",
        __FILE__, __LINE__, strerror (errno));
     exit (8);
   }
 strcpy (buf, srcdir);
 strcat (buf, "/");
 strcat (buf, fname);
 return buf;
}


void
init_gpgme_basic (void)
{
 gpgme_check_version (NULL);
 setlocale (LC_ALL, "");
 gpgme_set_locale (NULL, LC_CTYPE, setlocale (LC_CTYPE, NULL));
#ifndef HAVE_W32_SYSTEM
  gpgme_set_locale (NULL, LC_MESSAGES, setlocale (LC_MESSAGES, NULL));
#endif
}
```

```
void
init_gpgme (gpgme_protocol_t proto)
{
 gpg_error_t err;

 init_gpgme_basic ();
 err = gpgme_engine_check_version (proto);
 fail_if_err (err);
}


void
print_import_result (gpgme_import_result_t r)
{
 gpgme_import_status_t st;

 for (st=r->imports; st; st = st->next)
   {
    printf ("  fpr: %s err: %d (%s) status:", nonnull (st->fpr),
            st->result, gpgme_strerror (st->result));
    if (st->status & GPGME_IMPORT_NEW)
      fputs (" new", stdout);
    if (st->status & GPGME_IMPORT_UID)
      fputs (" uid", stdout);
    if (st->status & GPGME_IMPORT_SIG)
      fputs (" sig", stdout);
    if (st->status & GPGME_IMPORT_SUBKEY)
      fputs (" subkey", stdout);
    if (st->status & GPGME_IMPORT_SECRET)
      fputs (" secret", stdout);
    putchar ('\n');
   }
 printf ("key import summary:\n"
         "        considered: %d\n"
         "        no user id: %d\n"
          "          imported: %d\n"
         "      imported_rsa: %d\n"
         "         unchanged: %d\n"
         "      new user ids: %d\n"
         "       new subkeys: %d\n"
         "    new signatures: %d\n"
         "   new revocations: %d\n"
         "       secret read: %d\n"
         "   secret imported: %d\n"
         "  secret unchanged: %d\n"
         "  skipped new keys: %d\n"
         "      not imported: %d\n"
```

```
        "   skipped v3 keys: %d\n",
        r->considered,
        r->no_user_id,
        r->imported,
        r->imported_rsa,
        r->unchanged,
        r->new_user_ids,
        r->new_sub_keys,
        r->new_signatures,
        r->new_revocations,
        r->secret_read,
        r->secret_imported,
        r->secret_unchanged,
        r->skipped_new_keys,
        r->not_imported,
        r->skipped_v3_keys);
}
/*
  qgpgmeverifydetachedjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2007,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
```

```
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __QGPGME_QGPGMEVERIFYDETACHEDJOB_H__
#define __QGPGME_QGPGMEVERIFYDETACHEDJOB_H__

#include "verifydetachedjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "verificationresult.h"
#else
#include <gpgme++/verificationresult.h>
#endif

namespace QGpgME
{

class QGpgMEVerifyDetachedJob
#ifdef Q_MOC_RUN
  : public VerifyDetachedJob
#else

 : public _detail::ThreadedJobMixin<VerifyDetachedJob, std::tuple<GpgME::VerificationResult, QString,
GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEVerifyDetachedJob(GpgME::Context *context);
  ~QGpgMEVerifyDetachedJob();

  /* from VerifyDetachedJob */
  GpgME::Error start(const QByteArray &signature, const QByteArray &signedData) Q_DECL_OVERRIDE;

  /* from VerifyDetachedJob */
  void start(const std::shared_ptr<QIODevice> &signature, const std::shared_ptr<QIODevice> &signedData)
Q_DECL_OVERRIDE;

  /* from VerifyDetachedJob */
  GpgME::VerificationResult exec(const QByteArray &signature,
                                 const QByteArray &signedData) Q_DECL_OVERRIDE;
```

```
  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  GpgME::VerificationResult mResult;
};

}

#endif // __QGPGME_QGPGMEVERIFYDETACHEDJOB_H__
/*
  qgpgmeimportfromkeyserverjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition,
 as a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEIMPORTFROMKEYSERVERJOB_H__
#define __QGPGME_QGPGMEIMPORTFROMKEYSERVERJOB_H__
```

```
#include "importfromkeyserverjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "importresult.h"
#else
#include <gpgme++/importresult.h>
#endif

namespace QGpgME
{

class QGpgMEImportFromKeyserverJob
#ifdef Q_MOC_RUN
  : public ImportFromKeyserverJob
#else
   : public _detail::ThreadedJobMixin<ImportFromKeyserverJob, std::tuple<GpgME::ImportResult, QString,
GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEImportFromKeyserverJob(GpgME::Context *context);
  ~QGpgMEImportFromKeyserverJob();

  /* from ImportFromKeyserverJob */
  GpgME::Error start(const std::vector<GpgME::Key> &keys) Q_DECL_OVERRIDE;

  /* from ImportFromKeyserverJob */
  GpgME::ImportResult exec(const std::vector<GpgME::Key> &keys) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &r) Q_DECL_OVERRIDE;

private:
  GpgME::ImportResult mResult;
};

}

#endif // __QGPGME_QGPGMEIMPORTFROMKEYSERVERJOB_H__
```

{
  "op": "import",
  "data": "-----BEGIN PGP PUBLIC KEY BLOCK-----
\n\nmQGiBDbjs5oRBACjAxqGzA6j190iiN/1vJvS5jYLQ1H3xxhzXdZ6ZxjPJkslX1ox\nFqBINhjzBJnV9/7b1FFe5
089NiCcGUVZa2xD3Vu+niLTAGNTQeNy6Y0E6wEfvplQ\nLJbpVGOmuVeZyShHNCKjrsZFtS1mr7o19SUb5Q
WS3gZHabFTbmhibcFBXwCg36qG\nVAnGcZzvnUTGpRy3xjp+zuED/2qTJNpnPhicKSksVwb6EJFXH7mQSZly
blAnOAVF\nMx19GUijW4MWP5FUdcTd5KzIDgkenRLBrpCLIFVkQ4/baP/hOiCLOmCoRu3xnFyo\nRPM/Jn94
Qy3Jo2wigwkhQU+zyOU5C85QBD9ctkbYp/0mu9bpxmYTchHwD1v3dXUX\nEVajA/9lnEz1GiI0bwKpm8VKXp
0YYP5hea8Jh5fNVb1QW2QqGd+XNHnRGSqX5smG\nyrs+xoYxD8+jv1FhmGaSv+6+n+JBVK4TuWrQpZ0cgZ
L5jZnX27TOYXeY4d5YKgE+\n7ZO57TwCIfF/P6puflGm+t5GcFwj4kkfohMEaeNhm1S+xf29q7QrVmljdG9yIFR
l\nc3QgKGRlbW8ga2V5KSA8dmljdG9yQGV4YW1wbGUub3JnPohVBBMRAgAVBQI247Oa\nAwsKAwMVAw
IDFgIBAheAAAoJEEevS2lh8EeEzEkAoMA+KfY9bA8EdfvWwa8zUM1S\nMs5rAKDS+6X3HVuCaLtVxzXOob
+DKbB7b7kBDQQ247O+EAQAh5FAgdvaTJL3jBGc\njYiiJosxeTWf3L/dUY99fZN8R39DSVoUKf9Rt/EsS5Dyw
XVnKAeJiUTYw8lbMRVF\n70VhSDHpMC9KtbB0lk3CcAqULPiyirT5g9ywN24W7k0naWIJisttUh+Hqbm6gc5P
\nz9Nfd5ll8x4Ehi3lKE6Nze3gUNMAAwUD/AtUN1hqwWTTphVZctHq3JaUEb9agmu/\nOcsf24/bq9i8R8FaMwB
F4fI5qIimcqAM+2BZ6dvZEdqrVaZR9aHjzchcHmaiI7Zm\nW4gmk+LHFFWf9y7mG8YDKFBXkaBuJpxFb1FIfJp
maLzJmRa76dLqI3A7H2E8dFQa\n/MGsYCa4NmILiEUEGBECAAYFAjbjs74ACgkQR69LaWHwR4RT3QCgn
MlRAiGtvL5l\nD4Gdo5F0KEP5zZEAlA6Ri9WmZ9Xiqw5R3Bsg+As8sJ4=\n=FRd4\n-----END
 PGP PUBLIC KEY BLOCK-----\n"
}
/* dataprovider.h
  Copyright (C) 2004 Klarlvdalens Datakonsult AB
   Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
   Software engineering by Intevation GmbH

  This file is part of QGPGME.

  QGPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Library General Public License as published
  by the Free Software Foundation; either version 2 of the License, or
  (at your option) any later version.

  QGPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
  GNU Library General Public License for more details.

  You should have received a copy of the GNU Library General Public License
  along with QGPGME; see the file COPYING.LIB. If not, write to the
  Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
  Boston, MA 02110-1301, USA. */

// -*- c++ -*-
#ifndef __QGPGME_DATAPROVIDER_H__
#define
 __QGPGME_DATAPROVIDER_H__

#include "qgpgme_export.h"

```
#include <interfaces/dataprovider.h>
#include <memory>

#include <QtCore/QByteArray>


class QIODevice;

namespace QGpgME
{

class QGPGME_EXPORT QByteArrayDataProvider : public GpgME::DataProvider
{
public:
  QByteArrayDataProvider();
  explicit QByteArrayDataProvider(const QByteArray &initialData);
  ~QByteArrayDataProvider();

  const QByteArray &data() const
  {
     return mArray;
  }

private:
  // these shall only be accessed through the dataprovider
  // interface, where they're public:
  bool isSupported(Operation) const override
  {
     return true;
  }
  ssize_t read(void *buffer, size_t bufSize) override;
  ssize_t write(const void *buffer, size_t bufSize) override;
  off_t seek(off_t offset, int whence) override;
  void release() override;

private:
  QByteArray mArray;
  off_t mOff;
};

class QGPGME_EXPORT QIODeviceDataProvider : public GpgME::DataProvider
{
public:
   explicit QIODeviceDataProvider(const std::shared_ptr<QIODevice> &initialData);
  ~QIODeviceDataProvider();

  const std::shared_ptr<QIODevice> &ioDevice() const
  {
```

```
    return mIO;
  }

private:
  // these shall only be accessed through the dataprovider
  // interface, where they're public:
  bool isSupported(Operation) const override;
  ssize_t read(void *buffer, size_t bufSize) override;
  ssize_t write(const void *buffer, size_t bufSize) override;
  off_t seek(off_t offset, int whence) override;
  void release() override;

private:
  const std::shared_ptr<QIODevice> mIO;
  bool mErrorOccurred : 1;
  bool mHaveQProcess  : 1;
};

} // namespace QGpgME

#endif
/*
  qgpgmeexportjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a
 special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
```

```
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEEXPORTJOB_H__
#define __QGPGME_QGPGMEEXPORTJOB_H__

#include "exportjob.h"

#include "threadedjobmixin.h"

namespace QGpgME
{

class QGpgMEExportJob
#ifdef Q_MOC_RUN
  : public ExportJob
#else
  : public _detail::ThreadedJobMixin<ExportJob, std::tuple<GpgME::Error, QByteArray, QString, GpgME::Error>
>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
   void slotFinished();
#endif
public:
  explicit QGpgMEExportJob(GpgME::Context *context);
  ~QGpgMEExportJob();

  /* from ExportJob */
  void setExportFlags (unsigned int flags) Q_DECL_OVERRIDE;

  /* from ExportJob */
  GpgME::Error start(const QStringList &patterns) Q_DECL_OVERRIDE;
private:
  unsigned int m_flags;
};

}

#endif // __QGPGME_QGPGMEEXPORTJOB_H__
```

HACKING -*- org -*-
#+TITLE: Hacking notes for GPGME
#+STARTUP: showall

* How to contribute
** No more ChangeLog files

Do not modify any of the ChangeLog files in GPGME. Starting
on December 1st, 2011 we put change information only in the GIT
commit log, and generate a top-level ChangeLog file from logs at
"make dist" time. As such, there are strict requirements on the
form of the commit log messages. The old ChangeLog files have all
be renamed to ChangeLog-2011

** Commit log requirements

Your commit log should always start with a one-line summary, the
second line should be blank, and the remaining lines are usually
ChangeLog-style entries for all affected files. However, it's fine
-- even recommended -- to write a few lines of prose describing the
change, when the summary and ChangeLog entries don't give enough of
the big picture. Omit the leading TABs that you're used to seeing
in a "real" ChangeLog
file, but keep the maximum line length at 72
or smaller, so that the generated ChangeLog lines, each with its
leading TAB, will not exceed 80 columns. If you want to add text
which shall not be copied to the ChangeLog, separate it by a line
consisting of two dashes at the begin of a line.

Note that ./autogen.sh installs a git hook to do some basic syntax
checking on the commit log message.

Typo fixes and documentation updates don't need a ChangeLog entry;
thus you would use a commit message like

#+begin_example
Fix typo in a comment

--
#+end_example

The marker line here is important; without it the first line would
appear in the ChangeLog.

If you exceptionally need to have longer lines in a commit log you may
do this after this scissor line:
#+begin_example

------------------------ >8 ------------------------
#+end_example
(hash, blank, 24 dashes, blank, scissor, blank, 24 dashes).
Note that such a comment will be removed if the
git commit option
=--cleanup-scissor= is used.

** License policy

GPGME is currently licensed under the LGPLv2.1+ with tools and the
manual being under the GPLv3+. We may eventually update to a newer
version of the licenses or a combination of them. It is thus
important, that all contributed code allows for an update of the
license; for example we can't accept code under the LGPLv2(only).

If you want to contribute code or documentation to GPGME you are
asked to assert that the contribution is in accordance to the "GPGME
Developer's Certificate of Origin" as found in the file "DCO".
Except for a slight wording change, this DCO is identical to the one
used by the Linux kernel. Please take these simple steps:

- Decide which mail address you want to use. Please have your real
  name in the address and not a pseudonym. Anonymous contributions
  can only be done if you find a proxy who certifies for you.

- If your employer or school might claim ownership
of code written
  by you; you need to talk to them to make sure that you have the
  right to contribute under the DCO.

- Send an OpenPGP signed mail to the gnupg-devel@gnupg.org public
  mailing list from your mail address. Include a copy of the DCO as
  found in the official master branch. Insert your name and email
  address into the DCO in the same way you want to use it later.
  Example:

    Signed-off-by: Joe R. Hacker <joe@example.org>

  If you need it, you may perform simple transformations on the mail
  address: Replacing "@" by " at " or "." by " dot ".)

- That's it. From now on you only need to add a "Signed-off-by:"
  line with your name and mail address to the GIT commit message.
  It is recommended to send the patches using a PGP/MIME signed
  mail.

** Coding standards

Please follow the GNU coding standards. If you are in doubt consult
the existing code as an example. Do no re-indent code without a
need. If you really need to
do it, use a separate commit for such a
change.

- C99 syntax should not be used; stick to C90.
- Please do not use C++ =//= style comments.
- Try to fit lines into 80 columns.
- Ignore signed/unsigned pointer mismatches
- No arithmetic on void pointers; cast to char* first.

** Commit log keywords

- GnuPG-bug-id :: Values are comma or space delimited bug numbers
        from bug.gnupg.org pertaining to this commit.
- Debian-bug-id :: Same as above but from the Debian bug tracker.
- CVE-id :: CVE id number pertaining to this commit.
- Regression-due-to :: Commit id of the regression fixed by this commit.
- Fixes-commit :: Commit id this commit fixes.
- Reported-by :: Value is a name or mail address of a bug reporte.
- Suggested-by :: Value is a name or mail address of someone how
        suggested this change.
- Co-authored-by :: Name or mail address of a co-author
- Some-comments-by :: Name or mail address of the author of

        additional comments (commit log or code).
- Proofread-by :: Sometimes used by translation commits.
- Signed-off-by :: Name or mail address of the developer

* Debug hints

- Use gpgme-tool for manual tests.
- The envvar GPGME_DEBUG enables debugging; see debug.[ch] for
  details.
#include "qgpgme/specialjob.h"
Configuration files may go here. Note that config.h.in is
auto-generated so that this file is not in git.
GPGME Developer's Certificate of Origin. Version 1.0
==

By making a contribution to the GPGME project, I certify that:

(a) The contribution was created in whole or in part by me and I
  have the right to submit it under the free software license
  indicated in the file; or

(b) The contribution is based upon previous work that, to the

best of my knowledge, is covered under an appropriate free
software license and I have the right under that license to
submit that work with modifications, whether created in whole
or in part by me, under the same free software license
(unless I am permitted to submit under a different license),
as indicated in the file; or

(c) The contribution was provided directly to me by some other
person who certified (a), (b) or (c) and I have not modified
it.

(d) I understand and agree that this project and the contribution
are public and that a record of the contribution
(including
all personal information I submit with it, including my
sign-off) is maintained indefinitely and may be redistributed
consistent with this project or the free software license(s)
involved.

Signed-off-by: [Your name and mail address]
{
"op": "keylist",
"keys": ["zulu@example.net"],
"with-secret": false
}
{
"type": "keys",
"base64": false,
"data": "-----BEGIN PGP PUBLIC KEY BLOCK-----
\n\nmQGiBDbjs5oRBACjAxqGzA6j190iiN/1vJvS5jYLQ1H3xxhzXdZ6ZxjPJkslX1ox\nFqBINhjzBJnV9/7b1FFe5
089NiCcGUVZa2xD3Vu+niLTAGNTQeNy6Y0E6wEfvplQ\nLJbpVGOmuVeZyShHNCKjrsZFtS1mr7o19SUb5Q
WS3gZHabFTbmhibcFBXwCg36qG\nVAnGcZzvnUTGpRy3xjp+zuED/2qTJNpnPhicKSksVwb6EJFXH7mQSZly
blAnOAVF\nMx19GUijW4MWP5FUdcTd5KzIDgkenRLBrpCLIFVkQ4/baP/hOiCLOmCoRu3xnFyo\nRPM/Jn94
Qy3Jo2wigwkhQU+zyOU5C85QBD9ctkbYp/0mu9bpxmYTchHwD1v3dXUX\nEVajA/9lnEz1GiI0bwKpm8VKXp
0YYP5hea8Jh5fNVb1QW2QqGd+XNHnRGSqX5smG\nyrs+xoYxD8+jv1FhmGaSv+6+n+JBVK4TuWrQpZ0cgZ
L5jZnX27TOYXeY4d5YKgE+\n7ZO57TwCIfF/P6puflGm+t5GcFwj4kkfohMEaeNhm1S+xf29q7QrVmljdG9yIFR
l\nc3QgKGRlbW8ga2V5KSA8dmljdG9yQGV4YW1wbGUub3JnPohVBBMRAgAVBQI247Oa\nAwsKAwMVAw
IDFgIBAheAAAoJEEevS2lh8EeEzEkAoMA+KfY9bA8EdfvWwa8zUM1S\nMs5rAKDS+6X3HVuCaLtVxzXOob
+DKbB7b7kBDQQ247O+EAQAh5FAgdvaTJL3jBGc\njYiiJosxeTWf3L/dUY99fZN8R39DSVoUKf9Rt/EsS5Dyw
XVnKAeJiUTYw8lbMRVF\n70VhSDHpMC9KtbB0lk3CcAqULPiyirT5g9ywN24W7k0naWIJisttUh+Hqbm6gc5P
\nz9Nfd5ll8x4Ehi3lKE6Nze3gUNMAAwUD/AtUN1hqwWTTphVZctHq3JaUEb9agmu/\nOcsf24/bq9i8R8FaMwB
F4fI5qIimcqAM+2BZ6dvZEdqrVaZR9aHjzchcHmaiI7Zm\nW4gmk+LHFFWf9y7mG8YDKFBXkaBuJpxFb1FIfJp
maLzJmRa76dLqI3A7H2E8dFQa\n/MGsYCa4NmILiEUEGBECAAYFAjbjs74ACgkQR69LaWHwR4RT3QCgn
MlRAiGtvL5l\nD4Gdo5F0KEP5zZEAlA6Ri9WmZ9Xiqw5R3Bsg+As8sJ4=\n=FRd4\n-----END
PGP PUBLIC KEY BLOCK-----\n"
}
#include "qgpgme/changeexpiryjob.h"

This is gpgme.info, produced by makeinfo version 6.5 from gpgme.texi.

Copyright 20022008, 2010, 20122018 g10 Code GmbH.

Permission is granted to copy, distribute and/or modify this
document under the terms of the GNU General Public License as
published by the Free Software Foundation; either version 3 of the
License, or (at your option) any later version. The text of the
license can be found in the section entitled Copying.

This document is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General
Public License for more details.
INFO-DIR-SECTION GNU Libraries
START-INFO-DIR-ENTRY
* GPGME: (gpgme). Adding support for cryptography to your program.
END-INFO-DIR-ENTRY

This file documents the GPGME library.

This is Edition 1.14.1-beta35, last updated 13 December 2019, of The
GnuPG Made Easy Reference Manual, for Version
1.14.1-beta35.

Copyright 20022008, 2010, 20122018 g10 Code GmbH.

Permission is granted to copy, distribute and/or modify this
document under the terms of the GNU General Public License as
published by the Free Software Foundation; either version 3 of the
License, or (at your option) any later version. The text of the
license can be found in the section entitled Copying.

This document is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General
Public License for more details.

File: gpgme.info, Node: UI Server Decrypt, Next: UI Server Verify, Prev: UI Server Sign, Up: UI Server Protocol

A.3 UI Server: Decrypt a Message

Decryption may include the verification of OpenPGP messages. This is
due to the often used combined signing/encryption modus of OpenPGP. The
client may pass an option

to the server to inhibit the signature
verification. The following two commands are required to set the input
and output file descriptors:

-- Command: INPUT FD=N
Set the file descriptor for the message to be decrypted to N. The
message send to the server is either binary encoded or in the
case of OpenPGP ASCII armored. For details on the file
descriptor, see the description of INPUT in the ENCRYPT
section.

-- Command: OUTPUT FD=N
Set the file descriptor to be used for the output. The output is
binary encoded. For details on the file descriptor, see the
description of INPUT in the ENCRYPT section.

The decryption is started with the command:

-- Command: DECRYPT --protocol=NAME [--no-verify]
[--export-session-key]
NAME is the encryption protocol used for the message. For a
description of the allowed protocols see the ENCRYPT command.
This argument is mandatory. If the option --no-verify is given,
the server
should not try to verify a signature, in case the input
data is an OpenPGP combined message. If the option
--export-session-key is given and the underlying engine knows how
to export the session key, it will appear on a status line

File: gpgme.info, Node: UI Server Verify, Next: UI Server Set Input Files, Prev: UI Server Decrypt, Up: UI Server Protocol

A.4 UI Server: Verify a Message
==========

The server needs to support the verification of opaque signatures as
well as detached signatures. The kind of input sources controls what
kind message is to be verified.

-- Command: MESSAGE FD=N
This command is used with detached signatures to set the file
descriptor for the signed data to N. The data is binary encoded
(used verbatim). For details on the file descriptor, see the
description of INPUT in the ENCRYPT section.

-- Command: INPUT FD=N
Set the file descriptor for the opaque message or the signature

part
of a detached signature to N. The message send to the server
is either binary encoded or in the case of OpenPGP ASCII
armored. For details on the file descriptor, see the description
of INPUT in the ENCRYPT section.

-- Command: OUTPUT FD=N
Set the file descriptor to be used for the output. The output is
binary encoded and only used for opaque signatures. For details on
the file descriptor, see the description of INPUT in the
ENCRYPT section.

The verification is then started using:

-- Command: VERIFY --protocol=NAME [--silent]
NAME is the signing protocol used for the message. For a
description of the allowed protocols see the ENCRYPT command.
This argument is mandatory. Depending on the combination of
MESSAGE INPUT and OUTPUT commands, the server needs to select
the appropriate verification mode:

MESSAGE and INPUT
This indicates a detached signature. Output data is not
applicable.

INPUT
This indicates an opaque signature. As no output command has
been given, the server is only required to check the
signature.
INPUT and OUTPUT
This indicates an opaque signature. The server shall write
the signed data to the file descriptor set by the output
command. This data shall even be written if the signatures
cant be verified.

With --silent the server shall not display any dialog; this is for
example used by the client to get the content of opaque signed messages.
The client expects the server to send at least this status information
before the final OK response:

-- Status line: SIGSTATUS FLAG DISPLAYSTRING
Returns the status for the signature and a short string explaining
the status. Valid values for FLAG are:

none
The message has a signature but it could not not be verified
due to a missing key.
green

The signature is fully valid.

yellow
The signature is valid but additional information was shown regarding the validity of the key.

red
The signature is not valid.

DISPLAYSTRING is a percent-and-plus-encoded string with a short human readable description of the status. For example

S SIGSTATUS green Good+signature+from+Keith+Moon+<keith@example.net>

Note that this string needs to fit into an Assuan line and should be short enough to be displayed as short one-liner on the clients window. As usual the encoding of this string is UTF-8 and it should be send in its translated form.

The server shall send one status line for every signature found on the message.

File: gpgme.info, Node: UI Server Set Input Files, Next: UI Server Sign/Encrypt Files, Prev: UI Server Verify, Up: UI Server Protocol

A.5 UI Server: Specifying the input files to operate on.
==========

All file related UI server commands operate on a number of input files or directories, specified by one or more FILE commands:

-- Command: FILE [--clear] NAME
Add the file or directory NAME to the list of pathnames to be processed by the server. The parameter NAME must be an absolute path name (including the drive letter) and is percent espaced (in particular, the characters %, = and white space characters are always escaped). If the option --clear is given, the list of files is cleared before adding NAME.

Historical note: The original spec did not define --clear but the keyword --continued after the file name to indicate that more files are to be expected. However, this has never been used and thus removed from the specs.

File: gpgme.info, Node: UI Server Sign/Encrypt Files, Next: UI Server Verify/Decrypt Files, Prev: UI Server Set Input Files, Up: UI Server Protocol

A.6 UI Server: Encrypting and signing files.
==========

First,
 the input files need to be specified by one or more FILE
commands. Afterwards, the actual operation is requested:

-- Command: ENCRYPT_FILES --nohup
-- Command: SIGN_FILES --nohup
-- Command: ENCRYPT_SIGN_FILES --nohup
   Request that the files specified by FILE are encrypted and/or
   signed. The command selects the default action. The UI server may
   allow the user to change this default afterwards interactively, and
   even abort the operation or complete it only on some of the
   selected files and directories.

   What it means to encrypt or sign a file or directory is specific to
   the preferences of the user, the functionality the UI server
   provides, and the selected protocol. Typically, for each input
   file a new file is created under the original filename plus a
   protocol specific extension (like .gpg or .sig), which contain
   the encrypted/signed file or a detached signature. For
   directories, the server may offer
 multiple options to the user (for
   example ignore or process recursively).

   The ENCRYPT_SIGN_FILES command requests a combined sign and
   encrypt operation. It may not be available for all protocols (for
   example, it is available for OpenPGP but not for CMS).

   The option --nohup is mandatory. It is currently unspecified
   what should happen if --nohup is not present. Because --nohup
   is present, the server always returns OK promptly, and completes
   the operation asynchronously.

File: gpgme.info, Node: UI Server Verify/Decrypt Files, Next: UI Server Import/Export Keys, Prev: UI Server Sign/Encrypt Files, Up: UI Server Protocol

A.7 UI Server: Decrypting and verifying files.
==========

First, the input files need to be specified by one or more FILE
commands. Afterwards, the actual operation is requested:

-- Command: DECRYPT_FILES --nohup
-- Command: VERIFY_FILES --nohup

-- Command: DECRYPT_VERIFY_FILES
--nohup
Request that the files specified by FILE are decrypted and/or verified. The command selects the default action. The UI server may allow the user to change this default afterwards interactively, and even abort the operation or complete it only on some of the selected files and directories.

What it means to decrypt or verify a file or directory is specific to the preferences of the user, the functionality the UI server provides, and the selected protocol. Typically, for decryption, a new file is created for each input file under the original filename minus a protocol specific extension (like .gpg) which contains the original plaintext. For verification a status is displayed for each signed input file, indicating if it is signed, and if yes, if the signature is valid. For files that are signed and encrypted, the VERIFY command transiently decrypts the file to verify the enclosed signature. For directories,
the server may offer multiple
options to the user (for example ignore or process recursively).

The option --nohup is mandatory. It is currently unspecified what should happen if --nohup is not present. Because --nohup is present, the server always returns OK promptly, and completes the operation asynchronously.

File: gpgme.info, Node: UI Server Import/Export Keys, Next: UI Server Checksum Files, Prev: UI Server Verify/Decrypt Files, Up: UI Server Protocol

A.8 UI Server: Managing certificates.
=====================================

First, the input files need to be specified by one or more FILE commands. Afterwards, the actual operation is requested:

-- Command: IMPORT_FILES --nohup
Request that the certificates contained in the files specified by FILE are imported into the local certificate databases.

For directories, the server may offer multiple options to the user (for example ignore or process recursively).

The
option --nohup is mandatory. It is currently unspecified
what should happen if --nohup is not present. Because --nohup is present, the server always returns OK promptly, and completes the operation asynchronously.

FIXME: It may be nice to support an EXPORT command as well, which
is enabled by the context menu of the background of a directory.

File: gpgme.info, Node: UI Server Checksum Files, Next: Miscellaneous UI Server Commands, Prev: UI Server Import/Export Keys, Up: UI Server Protocol

A.9 UI Server: Create and verify checksums for files.
==========

First, the input files need to be specified by one or more FILE
commands. Afterwards, the actual operation is requested:

-- Command: CHECKSUM_CREATE_FILES --nohup
Request that checksums are created for the files specified by
FILE. The choice of checksum algorithm and the destination
storage and format for the created checksums depend on the

preferences of the user and the functionality provided by the UI
server. For directories, the server may offer multiple options to
the user (for example ignore or process recursively).

The option --nohup is mandatory. It is currently unspecified
what should happen if --nohup is not present. Because --nohup
is present, the server always returns OK promptly, and completes
the operation asynchronously.

-- Command: CHECKSUM_VERIFY_FILES --nohup
Request that checksums are created for the files specified by
FILE and verified against previously created and stored
checksums. The choice of checksum algorithm and the source storage
and format for previously created checksums depend on the
preferences of the user and the functionality provided by the UI
server. For directories, the server may offer multiple options to
the user (for example ignore or process recursively).

If the source storage of previously created checksums
is available
to the user through the Windows shell, this command may also accept
such checksum files as FILE arguments. In this case, the UI
server should instead verify the checksum of the referenced files
as if they were given as INPUT files.

The option --nohup is mandatory. It is currently unspecified
what should happen if --nohup is not present. Because --nohup
is present, the server always returns OK promptly, and completes
the operation asynchronously.

File: gpgme.info, Node: Miscellaneous UI Server Commands, Prev: UI Server Checksum Files, Up: UI Server Protocol

A.10 Miscellaneous UI Server Commands

The server needs to implement the following commands which are not related to a specific command:

-- Command: GETINFO WHAT
   This is a multi purpose command, commonly used to return a variety of information. The required subcommands as described by the WHAT parameter are:

    pid
      Return the process id of the server in decimal notation using an Assuan data line.

To allow the server to pop up the windows in the correct relation to the client, the client is advised to tell the server by sending the option:

-- Command option: window-id NUMBER
   The NUMBER represents the native window ID of the clients current window. On Windows systems this is a windows handle (HWND) and on X11 systems it is the X Window ID. The number needs to be given as a hexadecimal value so that it is easier to convey pointer values (e.g. HWND).

A client may want to fire up the certificate manager of the server. To do this it uses the Assuan command:

-- Command: START_KEYMANAGER
   The server shall pop up the main window of the key manager (aka certificate manager). The client expects that the key manager is brought into the foregound and that this command immediately returns (does not wait until the key manager has
been fully brought
   up).

A client may want to fire up the configuration dialog of the server. To do this it uses the Assuan command:

-- Command: START_CONFDIALOG
   The server shall pop up its configuration dialog. The client expects that this dialog is brought into the foregound and that this command immediately returns (i.e. it does not wait until the

dialog has been fully brought up).

When doing an operation on a mail, it is useful to let the server know the address of the sender:

-- Command: SENDER [--info] [--protocol=NAME] EMAIL
EMAIL is the plain ASCII encoded address ("addr-spec" as per RFC-2822) enclosed in angle brackets. The address set with this command is valid until a successful completion of the operation or until a RESET command. A second command overrides the effect of the first one; if EMAIL is not given and --info is not used, the server shall use the default signing key.

If option --info is not given, the server shall also suggest a protocol to use for signing. The client may use this suggested protocol on its own discretion. The same status line as with PREP_ENCRYPT is used for this.

The option --protocol may be used to give the server a hint on which signing protocol should be preferred.

To allow the UI-server to visually identify a running operation or to associate operations the server MAY support the command:

-- Command: SESSION NUMBER [STRING]
The NUMBER is an arbitrary value, a server may use to associate simultaneous running sessions. It is a 32 bit unsigned integer with 0 as a special value indicating that no session association shall be done.

If STRING is given, the server may use this as the title of a window or, in the case of an email operation, to extract the senders address. The string may contain spaces; thus no plus-escaping is used.

This command may be used at any time and overrides the effect of the last command. A RESET undoes the effect of this command.

File: gpgme.info, Node: Debugging, Next: Deprecated Functions, Prev: UI Server Protocol, Up: Top

Appendix B How to solve problems
****

Everyone knows that software often does not do what it should do and thus there is a need to track down problems. This is in particular true

for applications using a complex library like GPGME and of course also for the library itself. Here we give a few hints on how to solve such problems.

First of all you should make sure that the keys you want to use are installed in the GnuPG engine and are usable. Thus the first test is to run the desired operation using gpg or gpgsm on the command line. If you cant figure out why things dont work, you may use GPGMEs built in trace feature. This feature is either enabled using the environment variable GPGME_DEBUG or, if this is not possible, by calling the function gpgme_set_global_flag. The value is the trace level and an optional file name. If no file name is given the trace output is printed to stderr.

For example

```
GPGME_DEBUG=9:/home/user/mygpgme.log
```

(Note that under Windows you use a semicolon in place of the colon to separate the fields.)

A trace level of 9 is pretty verbose and thus you may want to start off with a lower level. The exact definition of the trace levels and the output format may change with any release; you need to check the source code for details. In any case the trace log should be helpful to understand what is going going on. Warning: The trace log may reveal sensitive details like passphrases or other data you use in your application. If you are asked to send a log file, make sure that you run your tests only with play data.

Appendix C Deprecated Functions

For backward compatibility GPGME has a number of functions, data types and constants which are deprecated and should not be used anymore. We document here those which are really old to help understanding old code and to allow migration to their modern counterparts.

Warning: These interfaces will be removed in a future version of GPGME.

-- Function: void gpgme_key_release (gpgme_key_t KEY)
The function gpgme_key_release is equivalent to gpgme_key_unref.

-- Function: gpgme_error_t gpgme_op_import_ext (gpgme_ctx_t CTX,
gpgme_data_t KEYDATA, int *NR)
SINCE: 0.3.9

The function gpgme_op_import_ext is equivalent to:

```
gpgme_error_t err = gpgme_op_import (ctx, keydata);
if (!err)
  {
    gpgme_import_result_t result = gpgme_op_import_result (ctx);
    *nr = result->considered;
  }
```

-- Data type: gpgme_error_t (*gpgme_edit_cb_t) (void *HANDLE,
gpgme_status_code_t STATUS, const char *ARGS, int FD)
The gpgme_edit_cb_t
type is the type of functions which GPGME
calls if it a key edit operation is on-going. The status code
STATUS and the argument line ARGS are passed through by GPGME from
the crypto engine. The file descriptor FD is -1 for normal status
messages. If STATUS indicates a command rather than a status
message, the response to the command should be written to FD. The
HANDLE is provided by the user at start of operation.

The function should return GPG_ERR_FALSE if it did not handle the
status code, 0 for success, or any other error value.

-- Function: gpgme_error_t gpgme_op_edit (gpgme_ctx_t CTX,
gpgme_key_t KEY, gpgme_edit_cb_t FNC, void *HANDLE,
gpgme_data_t OUT)
SINCE: 0.3.9

Note: This function is deprecated, please use gpgme_op_interact
instead.

The function gpgme_op_edit processes the key KEY interactively,
using the edit callback function FNC with the handle HANDLE. The
callback is
invoked for every status and command request from the
crypto engine. The output of the crypto engine is written to the
data object OUT.

Note that the protocol between the callback function and the crypto
engine is specific to the crypto engine and no further support in
implementing this protocol correctly is provided by GPGME.

The function returns the error code GPG_ERR_NO_ERROR if the edit
operation completes successfully, GPG_ERR_INV_VALUE if CTX or KEY

is not a valid pointer, and any error returned by the crypto engine or the edit callback handler.

-- Function: gpgme_error_t gpgme_op_edit_start (gpgme_ctx_t CTX, gpgme_key_t KEY, gpgme_edit_cb_t FNC, void *HANDLE, gpgme_data_t OUT)

SINCE: 0.3.9

Note: This function is deprecated, please use gpgme_op_interact_start instead.

The function gpgme_op_edit_start initiates a gpgme_op_edit operation. It can be completed by calling gpgme_wait on the context. *Note Waiting For Completion::.

The function returns the error code GPG_ERR_NO_ERROR if the operation was started successfully, and GPG_ERR_INV_VALUE if CTX or KEY is not a valid pointer.

-- Function: gpgme_error_t gpgme_op_card_edit (gpgme_ctx_t CTX, gpgme_key_t KEY, gpgme_edit_cb_t FNC, void *HANDLE, gpgme_data_t OUT)

Note: This function is deprecated, please use gpgme_op_interact with the flag GPGME_INTERACT_CARD instead.

The function gpgme_op_card_edit is analogous to gpgme_op_edit, but should be used to process the smart card corresponding to the key KEY.

-- Function: gpgme_error_t gpgme_op_card_edit_start (gpgme_ctx_t CTX, gpgme_key_t KEY, gpgme_edit_cb_t FNC, void *HANDLE, gpgme_data_t OUT)

Note: This function is deprecated, please use gpgme_op_interact_start with the flag GPGME_INTERACT_CARD instead.

The function gpgme_op_card_edit_start initiates a

gpgme_op_card_edit operation. It can be completed by calling gpgme_wait on the context. *Note Waiting For Completion::.

The function returns the error code GPG_ERR_NO_ERROR if the operation was started successfully, and GPG_ERR_INV_VALUE if CTX or KEY is not a valid pointer.

-- Function: gpgme_error_t gpgme_data_new_with_read_cb

(gpgme_data_t *DH, int (*READFUNC) (void *HOOK, char *BUFFER,
size_t COUNT, size_t *NREAD), void *HOOK_VALUE)

The function gpgme_data_new_with_read_cb creates a new gpgme_data_t object and uses the callback function READFUNC to retrieve the data on demand. As the callback function can supply the data in any way it wants, this is the most flexible data type GPGME provides. However, it can not be used to write data.

The callback function receives HOOK_VALUE as its first argument whenever it is invoked. It should return up to COUNT bytes in BUFFER, and return the number of bytes actually read in NREAD. It may return 0 in NREAD if no data is currently available. To indicate EOF the function should return with an error code of -1 and set NREAD to 0. The callback function may support to reset its internal read pointer if it is invoked with BUFFER and NREAD being NULL and COUNT being 0.

The function returns the error code GPG_ERR_NO_ERROR if the data object was successfully created, GPG_ERR_INV_VALUE if DH or READFUNC is not a valid pointer, and GPG_ERR_ENOMEM if not enough memory is available.

-- Function: gpgme_error_t gpgme_data_rewind (gpgme_data_t DH)

The function gpgme_data_rewind is equivalent to:

```
return (gpgme_data_seek (dh, 0, SEEK_SET) == -1)
  ? gpgme_error_from_errno (errno) : 0;
```

-- Data type: gpgme_attr_t

The gpgme_attr_t type is used to specify a key or trust item attribute. The following attributes are defined:

GPGME_ATTR_KEYID

This is the key ID of a sub key. It is representable as a string.

GPGME_ATTR_FPR

This is the fingerprint of a sub key. It is representable as a string.

GPGME_ATTR_ALGO

This is the crypto algorithm for which the sub key can be used. It is representable as a string and as a number. The numbers correspond to the enum gcry_pk_algos values in the gcrypt library.

GPGME_ATTR_LEN
This is the key length of a sub key. It is representable as a number.

GPGME_ATTR_CREATED
This is the timestamp at creation time of a sub key. It is representable as a number.

GPGME_ATTR_EXPIRE
This is the expiration time of a sub key. It is representable as a number.

GPGME_ATTR_USERID
This is a user ID. There can be more than one user IDs in a GPGME_KEY_T object. The first one (with index 0) is the primary user ID. The user ID
is representable as a number.

GPGME_ATTR_NAME
This is the name belonging to a user ID. It is representable as a string.

GPGME_ATTR_EMAIL
This is the email address belonging to a user ID. It is representable as a string.

GPGME_ATTR_COMMENT
This is the comment belonging to a user ID. It is representable as a string.

GPGME_ATTR_VALIDITY
This is the validity belonging to a user ID. It is representable as a string and as a number. See below for a list of available validities.

GPGME_ATTR_UID_REVOKED
This specifies if a user ID is revoked. It is representable as a number, and is 1 if the user ID is revoked, and 0 otherwise.

GPGME_ATTR_UID_INVALID
This specifies if a user ID is invalid. It is representable as a number, and is 1 if the user ID is invalid, and 0 otherwise.

GPGME_ATTR_TYPE
This

returns information about the type of key. For the
string function this will eother be "PGP" or "X.509". The
integer function returns 0 for PGP and 1 for X.509.

GPGME_ATTR_IS_SECRET
This specifies if the key is a secret key. It is
representable as a number, and is 1 if the key is revoked,
and 0 otherwise.

GPGME_ATTR_KEY_REVOKED
This specifies if a sub key is revoked. It is representable
as a number, and is 1 if the key is revoked, and 0
otherwise.

GPGME_ATTR_KEY_INVALID
This specifies if a sub key is invalid. It is representable
as a number, and is 1 if the key is invalid, and 0
otherwise.

GPGME_ATTR_KEY_EXPIRED
This specifies if a sub key is expired. It is representable
as a number, and is 1 if the key is expired, and 0
otherwise.

GPGME_ATTR_KEY_DISABLED
This specifies if a sub key is disabled. It is
representable
as a number, and is 1 if the key is disabled, and 0
otherwise.

GPGME_ATTR_KEY_CAPS
This is a description of the capabilities of a sub key. It is
representable as a string. The string contains the letter e
if the key can be used for encryption, s if the key can be
used for signatures, and c if the key can be used for
certifications.

GPGME_ATTR_CAN_ENCRYPT
This specifies if a sub key can be used for encryption. It is
representable as a number, and is 1 if the sub key can be
used for encryption, and 0 otherwise.

GPGME_ATTR_CAN_SIGN
This specifies if a sub key can be used to create data
signatures. It is representable as a number, and is 1 if
the sub key can be used for signatures, and 0 otherwise.

GPGME_ATTR_CAN_CERTIFY

This specifies if a sub key can be used to create key
certificates. It is representable
as a number, and is 1 if
the sub key can be used for certifications, and 0 otherwise.

GPGME_ATTR_SERIAL
The X.509 issuer serial attribute of the key. It is
representable as a string.

GPGME_ATTR_ISSUE
The X.509 issuer name attribute of the key. It is
representable as a string.

GPGME_ATTR_CHAINID
The X.509 chain ID can be used to build the certification
chain. It is representable as a string.

-- Function: const char * gpgme_key_get_string_attr (gpgme_key_t KEY,
gpgme_attr_t WHAT, const void *RESERVED, int IDX)
The function gpgme_key_get_string_attr returns the value of the
string-representable attribute WHAT of key KEY. If the attribute
is an attribute of a sub key or an user ID, IDX specifies the sub
key or user ID of which the attribute value is returned. The
argument RESERVED is reserved for later use and should be NULL.

The string returned is
only valid as long as the key is valid.

The function returns 0 if an attribute cant be returned as a
string, KEY is not a valid pointer, IDX out of range, or RESERVED
not NULL.

-- Function: unsigned long gpgme_key_get_ulong_attr (gpgme_key_t KEY,
gpgme_attr_t WHAT, const void *RESERVED, int IDX)
The function gpgme_key_get_ulong_attr returns the value of the
number-representable attribute WHAT of key KEY. If the attribute
is an attribute of a sub key or an user ID, IDX specifies the sub
key or user ID of which the attribute value is returned. The
argument RESERVED is reserved for later use and should be NULL.

The function returns 0 if the attribute cant be returned as a
number, KEY is not a valid pointer, IDX out of range, or RESERVED
not NULL.

The signatures on a key are only available if the key was retrieved
via a listing operation with the GPGME_KEYLIST_MODE_SIGS mode enabled,
because it is expensive to retrieve

all signatures of a key.

So, before using the below interfaces to retrieve the signatures on a key, you have to make sure that the key was listed with signatures enabled. One convenient, but blocking, way to do this is to use the function gpgme_get_key.

-- Data type: gpgme_attr_t
The gpgme_attr_t type is used to specify a key signature attribute. The following attributes are defined:

GPGME_ATTR_KEYID
This is the key ID of the key which was used for the signature. It is representable as a string.

GPGME_ATTR_ALGO
This is the crypto algorithm used to create the signature. It is representable as a string and as a number. The numbers correspond to the enum gcry_pk_algos values in the gcrypt library.

GPGME_ATTR_CREATED
This is the timestamp at creation time of the signature. It is representable as a number.

GPGME_ATTR_EXPIRE
This is the expiration time
of the signature. It is
representable as a number.

GPGME_ATTR_USERID
This is the user ID associated with the signing key. The user ID is representable as a number.

GPGME_ATTR_NAME
This is the name belonging to a user ID. It is representable as a string.

GPGME_ATTR_EMAIL
This is the email address belonging to a user ID. It is representable as a string.

GPGME_ATTR_COMMENT
This is the comment belonging to a user ID. It is representable as a string.

GPGME_ATTR_KEY_REVOKED
This specifies if a key signature is a revocation signature.

It is representable as a number, and is 1 if the key is
revoked, and 0 otherwise.

GPGME_ATTR_SIG_CLASS
This specifies the signature class of a key signature. It is
representable as a number. The meaning is specific to the
crypto engine.

GPGME_ATTR_SIG_CLASS
This
specifies the signature class of a key signature. It is
representable as a number. The meaning is specific to the
crypto engine.

GPGME_ATTR_SIG_STATUS
This is the same value as returned by gpgme_get_sig_status.

-- Function: const char * gpgme_key_sig_get_string_attr
(gpgme_key_t KEY, int UID_IDX, gpgme_attr_t WHAT,
const void *RESERVED, int IDX)
The function gpgme_key_sig_get_string_attr returns the value of
the string-representable attribute WHAT of the signature IDX on the
user ID UID_IDX in the key KEY. The argument RESERVED is reserved
for later use and should be NULL.

The string returned is only valid as long as the key is valid.

The function returns 0 if an attribute cant be returned as a
string, KEY is not a valid pointer, UID_IDX or IDX out of range, or
RESERVED not NULL.

-- Function: unsigned long gpgme_key_sig_get_ulong_attr
(gpgme_key_t KEY, int UID_IDX, gpgme_attr_t
WHAT,
const void *RESERVED, int IDX)
The function gpgme_key_sig_get_ulong_attr returns the value of
the number-representable attribute WHAT of the signature IDX on the
user ID UID_IDX in the key KEY. The argument RESERVED is reserved
for later use and should be NULL.

The function returns 0 if an attribute cant be returned as a
string, KEY is not a valid pointer, UID_IDX or IDX out of range, or
RESERVED not NULL.

-- Data type: enum gpgme_sig_stat_t
The gpgme_sig_stat_t type holds the result of a signature check,
or the combined result of all signatures. The following results
are possible:

GPGME_SIG_STAT_NONE
This status should not occur in normal operation.

GPGME_SIG_STAT_GOOD
This status indicates that the signature is valid. For the combined result this status means that all signatures are valid.

GPGME_SIG_STAT_GOOD_EXP
This status indicates that
the signature is valid but expired.
For the combined result this status means that all signatures are valid and expired.

GPGME_SIG_STAT_GOOD_EXPKEY
This status indicates that the signature is valid but the key used to verify the signature has expired. For the combined result this status means that all signatures are valid and all keys are expired.

GPGME_SIG_STAT_BAD
This status indicates that the signature is invalid. For the combined result this status means that all signatures are invalid.

GPGME_SIG_STAT_NOKEY
This status indicates that the signature could not be verified due to a missing key. For the combined result this status means that all signatures could not be checked due to missing keys.

GPGME_SIG_STAT_NOSIG
This status indicates that the signature data provided was not a real signature.

GPGME_SIG_STAT_ERROR
This status indicates that there was some other error which prevented the signature verification.

GPGME_SIG_STAT_DIFF
For the combined result this status means that at least two signatures have a different status. You can get each keys status with gpgme_get_sig_status.

-- Function: const char * gpgme_get_sig_status (gpgme_ctx_t CTX, int IDX, gpgme_sig_stat_t *R_STAT, time_t *R_CREATED)
The function gpgme_get_sig_status is equivalent to:

```
 gpgme_verify_result_t result;
 gpgme_signature_t sig;

 result = gpgme_op_verify_result (ctx);
 sig = result->signatures;

 while (sig && idx)
   {
     sig = sig->next;
     idx--;
   }
 if (!sig || idx)
   return NULL;

 if (r_stat)
   {
     switch (gpg_err_code (sig->status))
{
case GPG_ERR_NO_ERROR:
   *r_stat = GPGME_SIG_STAT_GOOD;
  break;

case GPG_ERR_BAD_SIGNATURE:
  *r_stat = GPGME_SIG_STAT_BAD;
  break;

case GPG_ERR_NO_PUBKEY:
  *r_stat = GPGME_SIG_STAT_NOKEY;
  break;

case GPG_ERR_NO_DATA:
  *r_stat = GPGME_SIG_STAT_NOSIG;
  break;

case GPG_ERR_SIG_EXPIRED:
  *r_stat = GPGME_SIG_STAT_GOOD_EXP;
  break;

case GPG_ERR_KEY_EXPIRED:
  *r_stat = GPGME_SIG_STAT_GOOD_EXPKEY;
  break;

default:
  *r_stat = GPGME_SIG_STAT_ERROR;
  break;
}
   }
```

```
        if (r_created)
          *r_created = sig->timestamp;
        return sig->fpr;
```

-- Function: const char * gpgme_get_sig_string_attr (gpgme_ctx_t CTX, int IDX, gpgme_attr_t WHAT, int WHATIDX)

The function gpgme_get_sig_string_attr is equivalent to:

```
        gpgme_verify_result_t result;
        gpgme_signature_t sig;

        result = gpgme_op_verify_result (ctx);
        sig = result->signatures;

        while (sig && idx)
          {
            sig = sig->next;
            idx--;
          }
        if (!sig || idx)
          return NULL;

        switch (what)
          {
          case GPGME_ATTR_FPR:
            return sig->fpr;

          case GPGME_ATTR_ERRTOK:
            if (whatidx == 1)
              return sig->wrong_key_usage ? "Wrong_Key_Usage" : "";
            else
          return "";
            default:
              break;
            }

        return NULL;
```

-- Function: const char * gpgme_get_sig_ulong_attr (gpgme_ctx_t CTX, int IDX, gpgme_attr_t WHAT, int WHATIDX)

The function gpgme_get_sig_ulong_attr is equivalent to:

```
        gpgme_verify_result_t result;
        gpgme_signature_t sig;
```

```
result = gpgme_op_verify_result (ctx);
        sig = result->signatures;

        while (sig && idx)
          {
            sig = sig->next;
            idx--;
          }
        if (!sig || idx)
          return 0;

        switch (what)
          {
          case GPGME_ATTR_CREATED:
            return sig->timestamp;

          case GPGME_ATTR_EXPIRE:
            return sig->exp_timestamp;

          case GPGME_ATTR_VALIDITY:
            return (unsigned long) sig->validity;

          case GPGME_ATTR_SIG_STATUS:
            switch (sig->status)
        {
        case GPG_ERR_NO_ERROR:
          return GPGME_SIG_STAT_GOOD;

        case GPG_ERR_BAD_SIGNATURE:
          return GPGME_SIG_STAT_BAD;

        case GPG_ERR_NO_PUBKEY:
          return GPGME_SIG_STAT_NOKEY;

        case GPG_ERR_NO_DATA:
          return GPGME_SIG_STAT_NOSIG;

        case GPG_ERR_SIG_EXPIRED:

      return GPGME_SIG_STAT_GOOD_EXP;

        case GPG_ERR_KEY_EXPIRED:
          return GPGME_SIG_STAT_GOOD_EXPKEY;

        default:
          return GPGME_SIG_STAT_ERROR;
        }
```

```
          case GPGME_ATTR_SIG_SUMMARY:
            return sig->summary;

          default:
            break;
          }
        return 0;
```

-- Function: const char * gpgme_get_sig_key (gpgme_ctx_t CTX, int IDX,
gpgme_key_t *R_KEY)

The function gpgme_get_sig_key is equivalent to:

```
        gpgme_verify_result_t result;
        gpgme_signature_t sig;

        result = gpgme_op_verify_result (ctx);
        sig = result->signatures;

        while (sig && idx)
          {
            sig = sig->next;
            idx--;
          }
        if (!sig || idx)
          return gpg_error (GPG_ERR_EOF);

        return gpgme_get_key (ctx, sig->fpr, r_key, 0);
```

File: gpgme.info, Node: Library Copying, Next: Copying,
Prev: Deprecated Functions, Up: Top

GNU Lesser General Public License
****

Version 2.1, February 1999

Copyright 1991, 1999 Free Software Foundation, Inc.
59 Temple Place Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]

Preamble

========

The licenses for most software are designed to take away your freedom to
share and change it. By contrast, the GNU General Public Licenses are
intended to guarantee your freedom to share and change free softwareto
make sure the software is free for all its users.

  This license, the Lesser General Public License, applies to some
specially designated softwaretypically librariesof the
 Free Software
Foundation and other authors who decide to use it. You can use it too,
but we suggest you first think carefully about whether this license or
the ordinary General Public License is the better strategy to use in any
particular case, based on the explanations below.

  When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of it
in new free programs; and that you are informed that you can do these
things.

  To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

  For example,
 if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling it.
And you must show them these terms so they know their rights.

  We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

  To protect each distributor, we want to make it very clear that there
is no warranty for the free library. Also, if the library is modified
by someone else and passed on, the recipients should know that what they
have is not the original version, so that the original authors
reputation will not be affected by problems that
 might be introduced by
others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the Lesser General Public License because it does _Less_ to protect the users freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the

users freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a work based on the library and a work that uses the library. The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called this License). Each licensee is addressed as you.

A library means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The Library, below, refers to any such software library or work which has been distributed under these terms. A work based on the Library means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term modification.)

Source code for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Librarys
complete source code as you receive it, in any medium, provided
that you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep
intact all the notices that refer to this License and to the
absence of any warranty; and distribute a copy of this License
along with the Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange
for a fee.

2. You may modify your copy or copies of the Library or any portion of
it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a. The modified work must itself be a software library.

b. You
must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

c. You must cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

d. If a facility in the modified Library refers to a function or
a table of data to be supplied by an application program that
uses the facility, other than as an argument passed when the
facility is invoked, then you must make a good faith effort to
ensure that, in the event an application does not supply such
function or table, the facility still operates, and performs
whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots
has a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied
function or table used by this function
must be optional: if the application does not supply it, the
square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the
Library, and can be reasonably considered independent and separate
works in themselves, then this License, and its terms, do not apply
to those sections when you distribute them as separate works. But

when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is
to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so
the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a work that uses the Library. Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a work that uses the Library with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a work that uses the library. The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a work that uses the Library uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the
Library, or if the work is itself a
library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a work that uses the Library with the Library to produce a work containing portions of the Library,
and distribute that work under
terms of your choice, provided that the terms permit modification of the work for the customers own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a. Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable work that uses the Library, as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b. Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the users computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c. Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d. If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e. Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the work that uses the Library must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally

accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a. Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed
under the terms of the
Sections above.

b. Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or
other property right claims or to contest validity of
any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only
in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and any later version, you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY AS IS WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries
==========

If
you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms of
the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source file to most
effectively convey the exclusion of warranty; and each file should have
at least the copyright line and a pointer to where the full notice is
found.

ONE LINE TO GIVE THE LIBRARY'S NAME AND AN IDEA OF WHAT IT DOES.
Copyright (C) YEAR NAME OF AUTHOR

This library is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 2.1 of the License, or (at
your option) any later version.

This library
is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307,
USA.

Also add information on how to contact you by electronic and paper
mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a copyright disclaimer for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

SIGNATURE OF TY COON, 1 April 1990
Ty Coon, President of Vice

Thats all there is to it!

File:
gpgme.info, Node: Copying, Next: Concept Index, Prev: Library Copying, Up: Top

GNU General Public License
****

Version 3, 29 June 2007

Copyright 2007 Free Software Foundation, Inc. <https://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this
license document, but changing it is not allowed.

Preamble
========

The GNU General Public License is a free, copyleft license for software
and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a programto make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can
apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know

their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers and authors protection, the GPL clearly explains that there is no warranty for this free software. For both users and authors sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

This License refers to version 3 of the GNU General Public License.

Copyright also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

The Program refers to any copyrightable work licensed under this License. Each licensee is addressed as you. Licensees and recipients may be individuals or organizations.

To modify a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a modified version of the earlier work or a work based on the earlier work.

A covered work means either the unmodified Program or a work based on the Program.

To propagate a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To convey a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays Appropriate Legal Notices to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The source code for a work means the preferred form of the work for making modifications to it. Object code means any non-source form of a work.

A Standard Interface means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The System Libraries of an executable work include anything, other than the work as a whole, that (a) is included in the normal

form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A Major Component, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The Corresponding Source for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the works System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you,

or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the works users, your or third parties legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Programs source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the

terms of section 4, provided that you also meet all of these conditions:

a. The work must carry prominent notices stating that you modified it, and giving a relevant date.

b. The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to keep intact all notices.

c. You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d. If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an aggregate if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilations users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c. Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d. Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e. Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A User Product is either (1) a consumer product, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for

incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, normally used refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

Installation Information for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

Additional
permissions are terms that supplement the terms of
this License by making exceptions from one or more of its
conditions. Additional permissions that are applicable to the
entire Program shall be treated as though they were included in
this License, to the extent that they are valid under applicable
law. If additional permissions apply only to part of the Program,
that part may be used separately under those permissions, but the
entire Program remains governed by this License without regard to
the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part
of it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material
you add to a covered work, you may (if authorized by the copyright
holders of that material) supplement the terms of this License with
terms:

a. Disclaiming warranty or limiting liability differently from
the terms of sections 15 and 16 of this License; or

b. Requiring preservation of specified reasonable legal notices
or author attributions in that material or in the Appropriate
Legal Notices displayed by works containing it; or

c. Prohibiting misrepresentation of the origin of that material,
or requiring that modified versions of such material be marked
in reasonable ways as different from the original version; or

d. Limiting the use for publicity purposes of names of licensors
or authors of the material; or

e. Declining to grant rights under trademark law for use of some
trade names,
trademarks, or service marks; or

f. Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified
versions of it) with contractual assumptions of liability to
the recipient, for any liability that these contractual
assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered further restrictions within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to
accept this License in order to receive or
run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An entity transaction is a transaction transferring control of an organization, or substantially
all assets of one, or subdividing an
organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the partys predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering
for sale, or importing the Program or any portion
of it.

11. Patents.

A contributor is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based.

The work thus licensed is called the contributors contributor version.

A contributors essential patent claims are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, control includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributors essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a patent license is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To grant such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. Knowingly relying means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipients use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the

patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is discriminatory if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March
2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU

General Public License or any later version applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxys public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM AS IS WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA

BEING RENDERED INACCURATE OR LOSSES
SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF
THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely
approximates an absolute waiver of all civil liability in
connection with the Program, unless a warranty or assumption of
liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs
==========

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under
these
terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least the
copyright line and a pointer to where the full notice is found.

ONE LINE TO GIVE THE PROGRAM'S NAME AND A BRIEF IDEA OF WHAT IT DOES.
Copyright (C) YEAR NAME OF AUTHOR

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or (at
your option) any later version.

This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice
like this when it starts in an interactive mode:

```
PROGRAM Copyright (C) YEAR NAME OF AUTHOR
This program comes with ABSOLUTELY NO WARRANTY; for details
type show w.  This is free software, and you are
welcome to redistribute it under certain conditions;
type show c for details.
```

The hypothetical commands show w and show c should show the
appropriate parts of the General Public License. Of course, your
programs commands might be different; for a GUI interface, you would
use an about box.

You should also get your employer (if you work as a programmer) or
school, if any, to sign a copyright disclaimer for the program, if
necessary. For more information on this, and how to apply and follow
the GNU GPL, see <https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your
program into proprietary programs. If your program is a subroutine
library, you may consider it more useful to permit linking proprietary
applications with the library. If this is what you want to do, use the
GNU Lesser General Public License instead of this License. But first,
please read <https://www.gnu.org/philosophy/why-not-lgpl.html>.

File: gpgme.info, Node: Concept Index, Next: Function and Data Index, Prev: Copying, Up: Top

Concept Index
****

[index]
* Menu:

* aborting operations: Cancellation. (line 6)
* algorithms: Algorithms. (line 6)
* algorithms, hash: Hash Algorithms. (line 6)
* algorithms, message digest: Hash Algorithms. (line 6)
* algorithms, public key: Public Key Algorithms. (line 6)
* armor mode: ASCII Armor. (line 6)
*
ASCII armor: ASCII Armor. (line 6)
* ASSUAN: Assuan. (line 6)
* attributes, of a key: Information About Keys.
(line 6)

* auditlog: Additional Logs. (line 6)
* auditlog, of the engine: Additional Logs. (line 6)
* autoconf: Using Automake. (line 6)
* automake: Using Automake. (line 6)
* backend: Protocols and Engines. (line 6)
* callback, passphrase: Passphrase Callback. (line 6)
* callback, progress meter: Progress Meter Callback.
(line 6)
* callback, status message: Status Message Callback.
(line 6)
*
cancelling operations: Cancellation. (line 6)
* canonical text mode: Text Mode. (line 6)
* certificates, included: Included Certificates. (line 6)
* CMS: Cryptographic Message Syntax.
(line 6)
* compiler flags: Building the Source. (line 6)
* compiler options: Building the Source. (line 6)
* configuration of crypto backend: Engine Configuration. (line 6)
* context: Contexts. (line 6)
* context, armor mode: ASCII Armor. (line 6)
* context, attributes: Context Attributes. (line 6)
* context, configuring engine: Crypto Engine. (line 6)
* context, creation: Creating Contexts. (line 6)
* context, destruction: Destroying Contexts.
(line 6)
* context, offline mode: Offline Mode. (line 6)
* context, pinentry mode: Pinentry Mode. (line 6)
* context, result of operation: Result Management. (line 6)
* context, selecting protocol: Protocol Selection. (line 6)
* context, sender: Setting the Sender. (line 6)
* context, text mode: Text Mode. (line 6)
* crypto backend: Protocols and Engines. (line 6)
* crypto engine: Protocols and Engines. (line 6)
* cryptographic message syntax: Cryptographic Message Syntax.
(line 6)
* cryptographic operation: Crypto Operations. (line 6)
* cryptographic operation, aborting: Cancellation. (line 6)
* cryptographic operation, cancelling: Cancellation. (line 6)
* cryptographic operation, decryption:
Decrypt. (line 6)
* cryptographic operation, decryption and verification: Decrypt and Verify.
(line 6)
* cryptographic operation, encryption: Encrypt. (line 6)
* cryptographic operation, running: Run Control. (line 6)
* cryptographic operation, signature check: Verify. (line 6)
* cryptographic operation, signing: Sign. (line 6)
* cryptographic operation, verification: Verify. (line 6)

* cryptographic operation, wait for: Waiting For Completion.
(line 6)
* data buffer, convenience: Data Buffer Convenience.
(line 6)
* data buffer, creation: Creating Data Buffers. (line 6)
* data buffer, destruction: Destroying Data Buffers.

(line 6)
* data buffer, encoding: Data Buffer Meta-Data. (line 6)
* data buffer, file name: Data Buffer Meta-Data. (line 6)
* data buffer, I/O operations: Data Buffer I/O Operations.
(line 6)
* data buffer, manipulation: Manipulating Data Buffers.
(line 6)
* data buffer, meta-data: Data Buffer Meta-Data. (line 6)
* data buffer, read: Data Buffer I/O Operations.
(line 6)
* data buffer, seek: Data Buffer I/O Operations.
(line 6)
* data buffer, write: Data Buffer I/O Operations.
(line 6)
* data, exchanging:
Exchanging Data. (line 6)
* debug: Debugging. (line 6)
* decryption: Decrypt. (line 6)
* decryption and verification: Decrypt and Verify. (line 6)
* deprecated: Deprecated Functions. (line 6)
* encryption: Encrypt. (line 6)
* engine: Protocols and Engines. (line 6)
* engine, ASSUAN: Assuan. (line 6)
* engine, configuration of: Engine Configuration. (line 6)
* engine, configuration per context: Crypto Engine. (line 6)
* engine, GnuPG: OpenPGP. (line 6)
* engine, GpgSM: Cryptographic Message Syntax.
(line 6)
* engine, information about: Engine Information. (line 6)
* error codes:
Error Values. (line 6)
* error codes, list of: Error Sources. (line 6)
* error codes, list of <1>: Error Codes. (line 6)
* error codes, printing of: Error Strings. (line 6)
* error handling: Error Handling. (line 6)
* error sources: Error Values. (line 6)
* error sources, printing of: Error Strings. (line 6)
* error strings: Error Strings. (line 6)
* error values: Error Values. (line 6)
* error values, printing of: Error Strings. (line 6)
* event loop, external: Using External Event Loops.

(line 6)
* flags, of a context: Context Flags. (line 6)
* From:: Setting the Sender.
(line 6)
* GDK, using GPGME with: I/O Callback Example GDK.
(line 6)
* GnuPG: OpenPGP. (line 6)
* GPGME_DEBUG: Debugging. (line 6)
* GpgSM: Cryptographic Message Syntax.
(line 6)
* GTK+, using GPGME with: I/O Callback Example GTK+.
(line 6)
* hash algorithms: Hash Algorithms. (line 6)
* header file: Header. (line 6)
* identify: Data Buffer Convenience.
(line 6)
* include file: Header. (line 6)
* key listing: Listing Keys.
(line 6)
* key listing mode: Key Listing Mode. (line 6)
* key listing, mode of: Key Listing Mode. (line 6)
* key listing, start: Listing Keys. (line 6)
* key management: Key Management. (line 6)
* key ring, add: Generating Keys. (line 6)
* key ring, delete from: Deleting Keys. (line 6)
* key ring, export from: Exporting Keys. (line 6)
* key ring, import to: Importing Keys. (line 6)
* key ring, list: Listing Keys. (line 6)
* key ring, search: Listing Keys. (line 6)
* key, attributes: Information About Keys.
(line 6)
* key, creation: Generating Keys. (line 6)
* key, delete: Deleting
Keys. (line 6)
* key, edit: Advanced Key Editing. (line 6)
* key, export: Exporting Keys. (line 6)
* key, import: Importing Keys. (line 6)
* key, information about: Information About Keys.
(line 6)
* key, manipulation: Manipulating Keys. (line 6)
* key, signing: Signing Keys. (line 6)
* largefile support: Largefile Support (LFS).
(line 6)
* LFS: Largefile Support (LFS).
(line 6)
* LGPL, GNU Lesser General Public License: Library Copying. (line 6)
* libtool: Using Libtool. (line 6)
* listing keys: Listing

Keys. (line 6)
* locale, default: Locale. (line 6)
* locale, of a context: Locale. (line 6)
* message digest algorithms: Hash Algorithms. (line 6)
* multi-threading: Multi-Threading. (line 6)
* notation data: Verify. (line 6)
* notation data <1>: Signature Notation Data.
(line 6)
* offline mode: Offline Mode. (line 6)
* OpenPGP: OpenPGP. (line 6)
* passphrase callback: Passphrase Callback. (line 6)
* passphrase, change: Changing Passphrases. (line 6)
* pinentry mode: Pinentry Mode. (line 6)
* policy URL: Signature Notation Data.
(line 6)
* progress meter callback: Progress Meter Callback.
(line 6)
* protocol: Protocols and Engines. (line 6)
* protocol, ASSUAN: Assuan. (line 6)
* protocol, CMS: Cryptographic Message Syntax.
(line 6)
* protocol, GnuPG: OpenPGP. (line 6)
* protocol, S/MIME: Cryptographic Message Syntax.
(line 6)
* protocol, selecting: Protocol Selection. (line 6)
* public key algorithms: Public Key Algorithms. (line 6)
* Qt, using GPGME with: I/O Callback Example Qt.
(line 6)
* run control:
Run Control. (line 6)
* S/MIME: Cryptographic Message Syntax.
(line 6)
* sender: Setting the Sender. (line 6)
* sign: Sign. (line 6)
* signal handling: Signal Handling. (line 6)
* signals: Signal Handling. (line 6)
* signature check: Decrypt and Verify. (line 6)
* signature notation data: Verify. (line 6)
* signature notation data <1>: Signature Notation Data.
(line 6)
* signature, creation: Sign. (line 6)
* signature, selecting signers: Selecting Signers. (line 6)
* signature, verification: Verify. (line 6)
* signers, selecting:
Selecting Signers. (line 6)
* status message callback: Status Message Callback.
(line 6)

* text mode: Text Mode. (line 6)
* thread-safeness: Multi-Threading. (line 6)
* type of data: Data Buffer Convenience.
(line 6)
* UI server: UI Server Protocol. (line 6)
* user interface server: UI Server Protocol. (line 6)
* validity, TOFU: Changing TOFU Data. (line 6)
* verification: Verify. (line 6)
* verification and decryption: Decrypt and Verify. (line 6)
* version check, of the engines: Engine Version Check. (line 6)
* version check, of the library: Library Version Check. (line 6)
* wait for completion:
Waiting For Completion.
(line 6)

File: gpgme.info, Node: Function and Data Index, Prev: Concept Index, Up: Top

Function and Data Index
****

[index]
* Menu:

* AM_PATH_GPGME: Using Automake. (line 11)
* AM_PATH_GPGME_PTH: Using Automake. (line 13)
* AM_PATH_GPGME_PTHREAD: Using Automake. (line 15)
* CHECKSUM_CREATE_FILES: UI Server Checksum Files.
(line 9)
* CHECKSUM_VERIFY_FILES: UI Server Checksum Files.
(line 22)
* DECRYPT: UI Server Decrypt. (line 26)
* DECRYPT_FILES: UI Server Verify/Decrypt Files.
(line 9)
* DECRYPT_VERIFY_FILES:
UI Server Verify/Decrypt Files.
(line 11)
* ENCRYPT: UI Server Encrypt. (line 47)
* ENCRYPT_FILES: UI Server Sign/Encrypt Files.
(line 9)
* ENCRYPT_SIGN_FILES: UI Server Sign/Encrypt Files.
(line 11)
* enum gpgme_data_encoding_t: Data Buffer Meta-Data.
(line 31)
* enum gpgme_data_type_t: Data Buffer Convenience.
(line 6)
* enum gpgme_event_io_t: I/O Callback Interface.
(line 58)

* enum gpgme_hash_algo_t: Hash Algorithms. (line 9)
* enum gpgme_pinentry_mode_t:
Pinentry Mode. (line 25)
* enum gpgme_protocol_t: Protocols and Engines.
(line 16)
* enum gpgme_pubkey_algo_t: Public Key Algorithms.
(line 9)
* enum gpgme_sig_mode_t: Creating a Signature.
(line 6)
* enum gpgme_sig_stat_t: Deprecated Functions.
(line 387)
* enum gpgme_tofu_policy_t: Changing TOFU Data. (line 10)
* FILE: UI Server Set Input Files.
(line 9)
* GETINFO: Miscellaneous UI Server Commands.
(line 9)
* gpgme_addrspec_from_uid:
Decrypt and Verify. (line 48)
* gpgme_attr_t: Deprecated Functions.
(line 140)
* gpgme_attr_t <1>: Deprecated Functions.
(line 301)
* gpgme_cancel: Cancellation. (line 16)
* gpgme_cancel_async: Cancellation. (line 38)
* gpgme_check_version: Library Version Check.
(line 6)
* gpgme_ctx_get_engine_info: Crypto Engine. (line 12)
* gpgme_ctx_set_engine_info: Crypto Engine. (line 26)
* gpgme_ctx_t: Contexts. (line 11)
* gpgme_data_encoding_t: Data Buffer Meta-Data.
(line 32)
* gpgme_data_get_encoding: Data Buffer
Meta-Data.
(line 81)
* gpgme_data_get_file_name: Data Buffer Meta-Data.
(line 6)
* gpgme_data_identify: Data Buffer Convenience.
(line 46)
* gpgme_data_new: Memory Based Data Buffers.
(line 12)
* gpgme_data_new_from_cbs: Callback Based Data Buffers.
(line 80)
* gpgme_data_new_from_estream: File Based Data Buffers.
(line 49)
* gpgme_data_new_from_fd: File Based Data Buffers.
(line 10)
* gpgme_data_new_from_file: Memory Based Data Buffers.

(line 37)
* gpgme_data_new_from_filepart: Memory Based Data Buffers.
(line 54)
* gpgme_data_new_from_mem: Memory Based Data Buffers.
(line 22)
* gpgme_data_new_from_stream: File Based Data Buffers.
(line 29)
* gpgme_data_new_with_read_cb: Deprecated Functions.
(line 110)
* gpgme_data_read: Data Buffer I/O Operations.
(line 6)
* gpgme_data_read_cb_t: Callback Based Data Buffers.
(line 13)
* gpgme_data_release: Destroying Data Buffers.

(line 6)
* gpgme_data_release_and_get_mem: Destroying Data Buffers.
(line 11)
* gpgme_data_release_cb_t: Callback Based Data Buffers.
(line 55)
* gpgme_data_rewind: Deprecated Functions.
(line 134)
* gpgme_data_seek: Data Buffer I/O Operations.
(line 26)
* gpgme_data_seek_cb_t: Callback Based Data Buffers.
(line 46)
* gpgme_data_set_encoding: Data Buffer Meta-Data.
(line 87)
* gpgme_data_set_file_name: Data Buffer Meta-Data.

(line 18)
* gpgme_data_set_flag: Data Buffer Meta-Data.
(line 92)
* gpgme_data_t: Exchanging Data. (line 13)
* gpgme_data_type_t: Data Buffer Convenience.
(line 7)
* gpgme_data_write: Data Buffer I/O Operations.
(line 16)
* gpgme_data_write_cb_t: Callback Based Data Buffers.
(line 29)
* gpgme_decrypt_result_t: Decrypt. (line 101)
* gpgme_edit_cb_t: Deprecated Functions.
(line 33)
* gpgme_encrypt_result_t: Encrypting a Plaintext.
(line
241)
* gpgme_engine_check_version: Engine Version Check.
(line 67)

* gpgme_engine_info_t: Engine Information. (line 6)
* gpgme_error: Error Values. (line 65)
* gpgme_error_from_errno: Error Values. (line 89)
* gpgme_error_t: Error Values. (line 24)
* gpgme_error_t (*gpgme_assuan_data_cb_t) (void *OPAQUE, const void *DATA, size_t DATALEN): Using the Assuan protocol.
(line 15)
* gpgme_error_t (*gpgme_assuan_inquire_cb_t) (void *OPAQUE, const char *NAME, const char *ARGS, gpgme_data_t *R_DATA): Using the Assuan protocol.
(line 24)
* gpgme_error_t (*gpgme_assuan_status_cb_t) (void *OPAQUE, const char *STATUS, const char *ARGS): Using the Assuan protocol.

(line 38)
* gpgme_error_t (*gpgme_edit_cb_t) (void *HANDLE, gpgme_status_code_t STATUS, const char *ARGS, int FD): Deprecated Functions.
(line 31)
* gpgme_error_t (*gpgme_interact_cb_t) (void *HANDLE, const char *STATUS, const char *ARGS, int FD): Advanced Key Editing.
(line 6)
* gpgme_error_t (*gpgme_io_cb_t) (void *DATA, int FD): I/O Callback Interface.
(line 6)
* gpgme_error_t (*gpgme_passphrase_cb_t)(void *HOOK, const char *UID_HINT, const char *PASSPHRASE_INFO, int PREV_WAS_BAD, int FD): Passphrase Callback.
(line 6)
* gpgme_error_t (*gpgme_register_io_cb_t) (void *DATA, int FD, int DIR, gpgme_io_cb_t FNC, void *FNC_DATA, void **TAG): I/O Callback Interface.

(line 19)
* gpgme_error_t (*gpgme_status_cb_t)(void *HOOK, const char *KEYWORD, const char *ARGS): Status Message Callback.
(line 6)
* gpgme_err_code: Error Values. (line 42)
* gpgme_err_code_from_errno: Error Values. (line 98)
* gpgme_err_code_t: Error Values. (line 6)
* gpgme_err_code_to_errno: Error Values. (line 103)
* gpgme_err_make: Error Values. (line 57)
* gpgme_err_make_from_errno: Error Values. (line 83)
* gpgme_err_source: Error Values. (line 49)
* gpgme_err_source_t: Error Values. (line 13)
* gpgme_event_io_t: I/O Callback Interface.
(line 59)
* gpgme_event_io_t <1>: Registering I/O Callbacks.
(line 7)
* gpgme_free: Destroying Data Buffers.
(line 25)
* gpgme_genkey_result_t: Generating Keys. (line 381)
* gpgme_get_armor: ASCII Armor. (line 13)

* gpgme_get_ctx_flag: Context Flags. (line 135)
* gpgme_get_dirinfo: Engine Version Check.
(line 6)
* gpgme_get_engine_info: Engine Information. (line 46)
* gpgme_get_include_certs: Included Certificates.
(line 37)
* gpgme_get_io_cbs: Registering I/O Callbacks.
(line 44)
* gpgme_get_key: Listing Keys. (line 178)
*
gpgme_get_keylist_mode: Key Listing Mode. (line 103)
* gpgme_get_offline: Offline Mode. (line 31)
* gpgme_get_passphrase_cb: Passphrase Callback. (line 63)
* gpgme_get_pinentry_mode: Pinentry Mode. (line 18)
* gpgme_get_progress_cb: Progress Meter Callback.
(line 31)
* gpgme_get_protocol: Protocol Selection. (line 21)
* gpgme_get_protocol_name: Protocols and Engines.
(line 58)
* gpgme_get_sender: Setting the Sender. (line 29)
* gpgme_get_sig_key: Deprecated Functions.
(line 587)
* gpgme_get_sig_status: Deprecated Functions.
(line 435)
* gpgme_get_sig_string_attr:
Deprecated Functions.
(line 491)
* gpgme_get_sig_ulong_attr: Deprecated Functions.
(line 525)
* gpgme_get_status_cb: Status Message Callback.
(line 31)
* gpgme_get_textmode: Text Mode. (line 20)
* gpgme_hash_algo_name: Hash Algorithms. (line 30)
* gpgme_hash_algo_t: Hash Algorithms. (line 10)
* gpgme_import_result_t: Importing Keys. (line 118)
* gpgme_import_status_t: Importing Keys. (line 80)
* gpgme_interact_cb_t: Advanced Key Editing.
(line 11)
* gpgme_invalid_key_t: Crypto Operations. (line 10)
* gpgme_io_cb_t:
I/O Callback Interface.
(line 7)
* gpgme_keylist_result_t: Listing Keys. (line 155)
* gpgme_key_get_string_attr: Deprecated Functions.
(line 266)
* gpgme_key_get_ulong_attr: Deprecated Functions.
(line 280)
* gpgme_key_ref: Manipulating Keys. (line 6)

* gpgme_key_release: Deprecated Functions.
(line 14)
* gpgme_key_sig_get_string_attr: Deprecated Functions.
(line 357)
* gpgme_key_sig_get_ulong_attr: Deprecated Functions.
(line 373)
* gpgme_key_sig_t: Key objects. (line
346)
* gpgme_key_t: Key objects. (line 10)
* gpgme_key_unref: Manipulating Keys. (line 10)
* gpgme_new: Creating Contexts. (line 6)
* gpgme_new_signature_t: Creating a Signature.
(line 57)
* gpgme_off_t: Exchanging Data. (line 24)
* gpgme_op_adduid: Generating Keys. (line 189)
* gpgme_op_adduid_start: Generating Keys. (line 215)
* gpgme_op_assuan_transact_ext: Using the Assuan protocol.
(line 64)
* gpgme_op_assuan_transact_start: Using the Assuan protocol.
(line 47)
* gpgme_op_card_edit: Deprecated Functions.
(line 85)
*
gpgme_op_card_edit_start: Deprecated Functions.
(line 95)
* gpgme_op_createkey: Generating Keys. (line 14)
* gpgme_op_createkey_start: Generating Keys. (line 119)
* gpgme_op_createsubkey: Generating Keys. (line 132)
* gpgme_op_createsubkey_start: Generating Keys. (line 176)
* gpgme_op_decrypt: Decrypt. (line 6)
* gpgme_op_decrypt_ext: Decrypt. (line 30)
* gpgme_op_decrypt_ext_start: Decrypt. (line 60)
* gpgme_op_decrypt_result: Decrypt. (line 164)
* gpgme_op_decrypt_start: Decrypt. (line 20)
* gpgme_op_decrypt_verify: Decrypt and Verify. (line 6)
* gpgme_op_decrypt_verify_start: Decrypt and Verify. (line 30)
* gpgme_op_delete: Deleting Keys.
(line 47)
* gpgme_op_delete_ext: Deleting Keys. (line 6)
* gpgme_op_delete_ext_start: Deleting Keys. (line 33)
* gpgme_op_delete_start: Deleting Keys. (line 52)
* gpgme_op_edit: Deprecated Functions.
(line 44)
* gpgme_op_edit_start: Deprecated Functions.
(line 68)
* gpgme_op_encrypt: Encrypting a Plaintext.
(line 6)
* gpgme_op_encrypt_ext: Encrypting a Plaintext.

(line 131)
* gpgme_op_encrypt_ext_start: Encrypting a Plaintext.
(line 224)
* gpgme_op_encrypt_result: Encrypting a Plaintext.

(line 252)
* gpgme_op_encrypt_sign: Encrypting a Plaintext.
(line 263)
* gpgme_op_encrypt_sign_ext: Encrypting a Plaintext.
(line 288)
* gpgme_op_encrypt_sign_ext_start: Encrypting a Plaintext.
(line 304)
* gpgme_op_encrypt_sign_start: Encrypting a Plaintext.
(line 274)
* gpgme_op_encrypt_start: Encrypting a Plaintext.
(line 113)
* gpgme_op_export: Exporting Keys. (line 59)
* gpgme_op_export_ext: Exporting Keys. (line 92)
* gpgme_op_export_ext_start: Exporting Keys. (line 114)
* gpgme_op_export_keys:
Exporting Keys. (line 126)
* gpgme_op_export_keys_start: Exporting Keys. (line 153)
* gpgme_op_export_start: Exporting Keys. (line 80)
* gpgme_op_genkey: Generating Keys. (line 304)
* gpgme_op_genkey_result: Generating Keys. (line 418)
* gpgme_op_genkey_start: Generating Keys. (line 369)
* gpgme_op_getauditlog: Additional Logs. (line 9)
* gpgme_op_getauditlog_start: Additional Logs. (line 54)
* gpgme_op_import: Importing Keys. (line 9)
* gpgme_op_import_ext: Deprecated Functions.
(line 18)
* gpgme_op_import_keys: Importing Keys. (line 35)
* gpgme_op_import_keys_start: Importing Keys. (line 65)
* gpgme_op_import_result: Importing Keys. (line 174)
* gpgme_op_import_start:
Importing Keys. (line 24)
* gpgme_op_interact: Advanced Key Editing.
(line 23)
* gpgme_op_interact_start: Advanced Key Editing.
(line 53)
* gpgme_op_keylist_end: Listing Keys. (line 111)
* gpgme_op_keylist_ext_start: Listing Keys. (line 34)
* gpgme_op_keylist_from_data_start: Listing Keys. (line 67)
* gpgme_op_keylist_next: Listing Keys. (line 94)
* gpgme_op_keylist_result: Listing Keys. (line 166)
* gpgme_op_keylist_start: Listing Keys. (line 6)
* gpgme_op_keysign: Signing Keys. (line 12)
* gpgme_op_keysign_start: Signing Keys. (line 73)

* gpgme_op_passwd: Changing Passphrases.
(line 6)
* gpgme_op_passwd_start: Changing Passphrases.
(line 21)
* gpgme_op_query_swdb: Checking for updates.
(line 68)
* gpgme_op_query_swdb_result: Checking for updates.
(line 80)
* gpgme_op_revsig: Signing Keys. (line 84)
* gpgme_op_revsig_start: Signing Keys. (line 119)
* gpgme_op_revuid: Generating Keys. (line 224)
* gpgme_op_revuid_start: Manipulating Keys. (line 58)
* gpgme_op_revuid_start <1>: Generating Keys. (line 252)
* gpgme_op_setexpire: Manipulating Keys. (line 15)
* gpgme_op_setexpire_start: Manipulating Keys. (line 47)
* gpgme_op_set_uid_flag_start:
Generating Keys. (line 293)
* gpgme_op_set_ui_flag: Generating Keys. (line 261)
* gpgme_op_sign: Creating a Signature.
(line 21)
* gpgme_op_sign_result: Creating a Signature.
(line 99)
* gpgme_op_sign_start: Creating a Signature.
(line 47)
* gpgme_op_spawn: Running other Programs.
(line 13)
* gpgme_op_spawn_start: Running other Programs.
(line 45)
* gpgme_op_tofu_policy: Changing TOFU Data. (line 29)
* gpgme_op_tofu_policy_start: Changing TOFU Data. (line 43)
* gpgme_op_verify: Verify. (line
6)
* gpgme_op_verify_result: Verify. (line 298)
* gpgme_op_verify_start: Verify. (line 26)
* gpgme_passphrase_cb_t: Passphrase Callback. (line 10)
* gpgme_pinentry_mode_t: Pinentry Mode. (line 26)
* gpgme_progress_cb_t: Progress Meter Callback.
(line 8)
* gpgme_protocol_t: Protocols and Engines.
(line 17)
* gpgme_protocol_t <1>: Engine Information. (line 7)
* gpgme_pubkey_algo_name: Public Key Algorithms.
(line 58)
* gpgme_pubkey_algo_string: Public Key Algorithms.
(line 68)
* gpgme_pubkey_algo_t: Public Key Algorithms.

(line 10)
* gpgme_query_swdb_result_t: Checking for updates.
(line 11)
* gpgme_recipient_t: Decrypt. (line 75)
* gpgme_register_io_cb_t: I/O Callback Interface.
(line 23)
* gpgme_release: Destroying Contexts. (line 6)
* gpgme_result_ref: Result Management. (line 15)
* gpgme_result_unref: Result Management. (line 23)
* gpgme_set_armor: ASCII Armor. (line 6)
* gpgme_set_ctx_flag: Context Flags. (line 6)
* gpgme_set_engine_info: Engine Configuration.
(line 11)
* gpgme_set_global_flag: Library Version Check.

(line 44)
* gpgme_set_include_certs: Included Certificates.
(line 6)
* gpgme_set_io_cbs: Registering I/O Callbacks.
(line 35)
* gpgme_set_keylist_mode: Key Listing Mode. (line 6)
* gpgme_set_locale: Locale. (line 14)
* gpgme_set_offline: Offline Mode. (line 6)
* gpgme_set_passphrase_cb: Passphrase Callback. (line 40)
* gpgme_set_pinentry_mode: Pinentry Mode. (line 6)
* gpgme_set_progress_cb: Progress Meter Callback.
(line 16)
* gpgme_set_protocol: Protocol Selection. (line 6)
* gpgme_set_sender: Setting the Sender. (line 13)
* gpgme_set_status_cb:
Status Message Callback.
(line 17)
* gpgme_set_textmode: Text Mode. (line 6)
* gpgme_signature_t: Verify. (line 92)
* gpgme_signers_add: Selecting Signers. (line 18)
* gpgme_signers_clear: Selecting Signers. (line 11)
* gpgme_signers_count: Selecting Signers. (line 25)
* gpgme_signers_enum: Selecting Signers. (line 31)
* gpgme_sign_result_t: Creating a Signature.
(line 85)
* gpgme_sig_mode_t: Creating a Signature.
(line 7)
* gpgme_sig_notation_add: Signature Notation Data.
(line 19)
* gpgme_sig_notation_clear:
Signature Notation Data.
(line 10)
* gpgme_sig_notation_get: Signature Notation Data.

(line 45)
* gpgme_sig_notation_t: Verify. (line 38)
* gpgme_sig_stat_t: Deprecated Functions.
(line 388)
* gpgme_ssize_t: Exchanging Data. (line 32)
* gpgme_status_cb_t: Status Message Callback.
(line 8)
* gpgme_strerror: Error Strings. (line 6)
* gpgme_strerror_r: Error Strings. (line 15)
* gpgme_strsource: Error Strings. (line 26)
* gpgme_subkey_t: Key objects. (line 112)
* gpgme_tofu_info_t: Key objects.
(line 282)
* gpgme_tofu_policy_t: Changing TOFU Data. (line 13)
* gpgme_user_id_t: Key objects. (line 217)
* gpgme_validity_t: Information About Keys.
(line 9)
* gpgme_verify_result_t: Verify. (line 276)
* gpgme_wait: Waiting For Completion.
(line 6)
* IMPORT_FILES: UI Server Import/Export Keys.
(line 9)
* INPUT: UI Server Encrypt. (line 23)
* INPUT <1>: UI Server Sign. (line 12)
* INPUT <2>: UI Server Decrypt. (line 12)
* INPUT <3>: UI Server Verify. (line 16)
* MESSAGE: UI
Server Verify. (line 10)
* MICALG: UI Server Sign. (line 43)
* off_t (*gpgme_data_seek_cb_t) (void *HANDLE, off_t OFFSET, int WHENCE): Callback Based Data Buffers.
(line 43)
* OUTPUT: UI Server Encrypt. (line 36)
* OUTPUT <1>: UI Server Sign. (line 18)
* OUTPUT <2>: UI Server Decrypt. (line 19)
* OUTPUT <3>: UI Server Verify. (line 23)
* PREP_ENCRYPT: UI Server Encrypt. (line 72)
* PROTOCOL: UI Server Encrypt. (line 98)
* RECIPIENT: UI Server Encrypt. (line 9)
* SENDER: Miscellaneous UI Server Commands.
(line 50)
* SESSION: Miscellaneous UI Server
Commands.
(line 69)
* SIGN: UI Server Sign. (line 33)
* SIGN_FILES: UI Server Sign/Encrypt Files.
(line 10)
* SIGSTATUS: UI Server Verify. (line 56)
* ssize_t (*gpgme_data_read_cb_t) (void *HANDLE, void *BUFFER, size_t SIZE): Callback Based Data Buffers.

(line 10)
* ssize_t (*gpgme_data_write_cb_t) (void *HANDLE, const void *BUFFER, size_t SIZE): Callback Based Data Buffers.
(line 27)
* START_CONFDIALOG: Miscellaneous UI Server Commands.
(line 41)
* START_KEYMANAGER: Miscellaneous UI Server Commands.

(line 31)
* struct gpgme_data_cbs: Callback Based Data Buffers.
(line 59)
* struct gpgme_io_cbs: Registering I/O Callbacks.
(line 6)
* VERIFY: UI Server Verify. (line 31)
* VERIFY_FILES: UI Server Verify/Decrypt Files.
(line 10)
* void (*gpgme_data_release_cb_t) (void *HANDLE): Callback Based Data Buffers.
(line 54)
* void (*gpgme_event_io_cb_t) (void *DATA, gpgme_event_io_t TYPE, void *TYPE_DATA): I/O Callback Interface.
(line 83)
* void (*gpgme_progress_cb_t)(void *HOOK, const char *WHAT, int TYPE, int CURRENT, int TOTAL): Progress Meter Callback.

(line 6)
* void (*gpgme_remove_io_cb_t) (void *TAG): I/O Callback Interface.
(line 48)
* window-id: Miscellaneous UI Server Commands.
(line 21)
{
"op": "decrypt",
"base64": true,
"data":
"hQEOA2rm1+5GqHH4EAP+NCYW3vVuCLDTUYhBaKHNgp4fMq9TNACH2NiZyVSaYLe0VE+2LLurHN/X
LwlP7xhl2XijBUe6Q7M+KyoPd9iNIgX9q914dPUN0Q3sJinSbujnFzsy0L2x6kgUJCK/XA7rp0VpmJGUWIQYAE
T8Xx6SaWd2XxIdIITUz2MqrTzWrgED/iOuRxuT4loNJ/DM2YrOZr0He25SxJskg0t1bik2nM+wHAbJrSa6BqPJY
U4scnG6AH0RRxFV177ADjOcBLeutXw7DE+6YOExWZD2Fb0oax/ppDulMudrJnj6Wg5/EHbBLDF96Xd6vQX
1rcHmrxImvaQNbavEKswlDZgoYwaV7PYPhQEOAwQHH7gHKHE0EAP/So0a3deCbXVSPkABRO3yZa6kHcV
uO5+lTsunfxav1TwaMkBOiK6usRz2zt3rjozNrh3vXn3o2WpFKebwhIUF0q2qPw3OKIGq9jFT63t+DPjpbSorAev
mVqXWdmaqDPJZ/QIY6NkBhprTdIGPSTFh66eggQLz+BBUVx2myM7AqgcD/3PnOGIiqINQzFkfa6lHiV/TZ8A
aMNfvyx4FFG4Zi45ZnDwLCJZ+J7ATXzECauEDLzhjk8M9OP0PwFT1WsnWefKDSLzbO5hEnf8NYdY6i8f2MJ
KYcnpeI4PZA3OK9ovmAoJl31K+/vBJRP4kiJ4Weu7fzMi6Zz87tfHDEpbRR7N80qoBTlT7I044LG5OJKgQukb7
HOv+c668i56UzZVgz+LCsFpjYEFTlrPVR5Me3PjSSb8M+tt9NUjenNnghJEcxeD902YJcqgRWPotouzx5fKDTay/
LofFqckEWGlP5pnkeNfYIBIaSSrG/KcdQ0rPOAxKrZzIifYVwnJm/ISxU6uMpNfDJGOJppf4xqXgTKBdIsCljg5Ll
gNvGhNMYaXQkGQInzXvLSUbxLerWw=="
}
/*
result.h - base class for results

```
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_RESULT_P_H__
#define
 __GPGMEPP_RESULT_P_H__

#define make_default_ctor(x) \
  GpgME::x::x() : GpgME::Result(), d() {}

#define make_error_ctor(x) \
  GpgME::x::x( const Error & error ) \
     : GpgME::Result( error ), d() \
  { \
     \
  }

#define make_isNull(x) bool GpgME::x::isNull() const { return !d && !bool(error()); }

#define make_standard_stuff(x) \
  make_default_ctor(x) \
  make_error_ctor(x) \
  make_isNull(x)

#endif // __GPGMEPP_RESULT_P_H__
#include "qgpgme/decryptjob.h"
Just GNU it!
{
  "success":      true
```

```
}
/*
  keygenerationjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special
 exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __KLEO_KEYGENERATIONJOB_H__
#define __KLEO_KEYGENERATIONJOB_H__

#include "job.h"
#include "qgpgme_export.h"

#include <QtCore/QByteArray>

namespace GpgME
{
class Error;
class KeyGenerationResult;
```

```
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous key generation

  To use a KeyGenerationJob, first obtain an instance from the
  CryptoBackend implementation,
 connect the progress() and result()
  signals to suitable slots and then start the key generation with
  a call to start(). This call might fail, in which case the
  KeyGenerationJob instance will have scheduled it's own
  destruction with a call to QObject::deleteLater().

  After result() is emitted, the KeyGenerationJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT KeyGenerationJob : public Job
{
  Q_OBJECT
protected:
  explicit KeyGenerationJob(QObject *parent);
public:
  ~KeyGenerationJob();

  /**
    Starts the key generation operation. \a parameters is a
    backend-specific string containing the parameters of the key to
    create (length, capabilities, etc).
  */
  virtual GpgME::Error start(const QString &parameters) = 0;

Q_SIGNALS:
  void result(const GpgME::KeyGenerationResult &result, const QByteArray &pubKeyData, const QString
&auditLogAsHtml = QString(), const GpgME::Error &auditLogError
 = GpgME::Error());
};

}

#endif // __KLEO_KEYGENERATIONJOB_H__
/*
 tofuinfo.h - wraps gpgme tofu info
 Copyright (C) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH
```

```
 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_TOFUINFO_H__
#define __GPGMEPP_TOFUINFO_H__

#include
 "gpgmepp_export.h"

#include "global.h"

#include <memory>

namespace GpgME
{

class GPGMEPP_EXPORT TofuInfo
{
public:
  TofuInfo();
  explicit TofuInfo(gpgme_tofu_info_t info);

  const TofuInfo &operator=(TofuInfo other)
  {
     swap(other);
     return *this;
  }

  void swap(TofuInfo &other)
  {
     using std::swap;
     swap(this->d, other.d);
  }
```

```
  bool isNull() const;

  /* @enum Validity
   * @brief The TOFU Validity. */
  enum Validity : unsigned int {
     /*! Unknown (uninitialized).*/
     ValidityUnknown,
     /*! TOFU Conflict.*/
     Conflict,
     /*! Key without history.*/
     NoHistory,
     /*! Key with too little history.*/
     LittleHistory,
     /*! Key with enough history for basic trust.*/
     BasicHistory,
     /*! Key with a lot of history.*/
     LargeHistory,
  };
  Validity validity() const;

  /* @enum Policy
   * @brief The TOFU Validity. */
  enum Policy : unsigned
int {
     /*! GPGME_TOFU_POLICY_NONE */
     PolicyNone,
     /*! GPGME_TOFU_POLICY_AUTO */
     PolicyAuto,
     /*! GPGME_TOFU_POLICY_GOOD */
     PolicyGood,
     /*! GPGME_TOFU_POLICY_UNKNOWN */
     PolicyUnknown,
     /*! GPGME_TOFU_POLICY_BAD */
     PolicyBad,
     /*! GPGME_TOFU_POLICY_ASK */
     PolicyAsk,
  };
  Policy policy() const;

  /* Number of signatures seen for this binding.  Capped at USHRT_MAX.  */
  unsigned short signCount() const;

  /* Number of encryption done to this binding.  Capped at USHRT_MAX.  */
  unsigned short encrCount() const;

  /** Number of seconds since epoch when the first message was verified */
  unsigned long signFirst() const;
```

```
  /** Number of seconds since epoch when the last message was verified */
  unsigned long signLast() const;

  /** Number of seconds since epoch when the first message was encrypted */
  unsigned long encrFirst() const;

  /** Number of seconds since
 epoch when the last message was encrypted */
  unsigned long encrLast() const;

  /* If non-NULL a human readable string summarizing the TOFU data. */
  const char *description() const;

private:
  class Private;
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const TofuInfo &info);

} // namespace GpgME

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(TofuInfo)
#endif // __GPGMEPP_TOFUINFO_H__
/* defaultkeygenerationjob.h

  Copyright (c) 2016 Klarlvdalens Datakonsult AB
  2016 Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a special exception, the copyright holders give
  permission to link the code of
```

```
 this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/
#ifndef QGPGME_DEFAULTKEYGENERATION_H
#define QGPGME_DEFAULTKEYGENERATION_H

#include "job.h"

#include "qgpgme_export.h"

namespace GpgME {
class KeyGenerationResult;
}

namespace QGpgME{

/**
* Generates a PGP RSA/2048 bit key pair for given name and email address.
*/
class QGPGME_EXPORT DefaultKeyGenerationJob : public Job
{
  Q_OBJECT
public:
  explicit DefaultKeyGenerationJob(QObject *parent = Q_NULLPTR);
  ~DefaultKeyGenerationJob();

  GpgME::Error
 start(const QString &email, const QString &name);

  QString auditLogAsHtml() const Q_DECL_OVERRIDE;
  GpgME::Error auditLogError() const Q_DECL_OVERRIDE;


public Q_SLOTS:
  void slotCancel() Q_DECL_OVERRIDE;

Q_SIGNALS:
  void result(const GpgME::KeyGenerationResult &result, const QByteArray &pubkeyData,
          const QString &auditLogAsHtml, const GpgME::Error &auditLogError);

protected:
```

```
  bool eventFilter(QObject *watched, QEvent *event) Q_DECL_OVERRIDE;

private:
  class Private;
  Private * const d;
};

}

#endif
{
  "dec_info":    {
     "wrong_key_usage":     false,
        "is_de_vs":    false,
        "is_mime":     false,
        "legacy_cipher_nomdc":  false,
        "recipients":   [{
           "pubkey_algo_name":    "ELG-E",
           "status_string":       "Success",
           "status_code":  0
        }]
  },
  "type": "plaintext",
  "base64": false,
  "data": "Hello\n"
}
/*
  encryptjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004, 2007 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA
```

```
   In addition, as a special
 exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_ENCRYPTJOB_H__
#define __KLEO_ENCRYPTJOB_H__

#include "job.h"

#include <memory>
#include <vector>

#ifdef BUILDING_QGPGME
# include "context.h"
#else
# include <gpgme++/context.h>
#endif

class QByteArray;
class QIODevice;

namespace GpgME
{
class Error;
class Key;
class EncryptionResult;
}

namespace QGpgME
{

/**
  @short An abstract base class for asynchronous encrypters

   To use a EncryptJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then start the encryption with a
  call to start(). This call might fail, in which case the
  EncryptJob instance will have scheduled it's own destruction with
```

```
  a call to QObject::deleteLater().

  After result() is emitted, the EncryptJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT EncryptJob : public Job
{
  Q_OBJECT
protected:
  explicit EncryptJob(QObject *parent);
public:
  ~EncryptJob();

  /**
    Starts the encryption operation. \a recipients is the a list of
    keys to encrypt \a plainText to. Empty (null) keys are
    ignored. If \a recipients is empty, performs symmetric
    (passphrase) encryption.

    If \a alwaysTrust is true, validity checking for the keys will
    not be performed, but full validity assumed for all keys

    without further checks.
  */
  virtual GpgME::Error start(const std::vector<GpgME::Key> &recipients,
        const QByteArray &plainText, bool alwaysTrust = false) = 0;

  /*!
    \overload

    If \a cipherText is non-null, the ciphertext is written
    there. Otherwise, it will be delivered in the second argument of
    result().

    \throws GpgME::Exception if starting fails
  */
  virtual void start(const std::vector<GpgME::Key> &recipients,
                const std::shared_ptr<QIODevice> &plainText,
                const std::shared_ptr<QIODevice> &cipherText = std::shared_ptr<QIODevice>(),
                bool alwaysTrust = false) = 0;

  virtual GpgME::EncryptionResult exec(const std::vector<GpgME::Key> &recipients,
                               const QByteArray &plainText,
                               bool alwaysTrust, QByteArray &cipherText) = 0;
  /*!
    This is a hack to request BASE64 output (instead
 of whatever
    comes out normally).
```

```
  */
  virtual void setOutputIsBase64Encoded(bool) = 0;

  /** Like start but with an additional argument for EncryptionFlags for
   * more flexibility. */
  virtual void start(const std::vector<GpgME::Key> &recipients,
                     const std::shared_ptr<QIODevice> &plainText,
                     const std::shared_ptr<QIODevice> &cipherText = std::shared_ptr<QIODevice>(),
                     const GpgME::Context::EncryptionFlags flags = GpgME::Context::None) = 0;

  /** Like exec but with an additional argument for EncryptionFlags for
   * more flexibility. */
  virtual GpgME::EncryptionResult exec(const std::vector<GpgME::Key> &recipients,
                                       const QByteArray &plainText,
                                       const GpgME::Context::EncryptionFlags flags, QByteArray &cipherText) = 0;
Q_SIGNALS:
  void result(const GpgME::EncryptionResult &result, const QByteArray &cipherText,
 const QString &auditLogAsHtml = QString(), const GpgME::Error &auditLogError = GpgME::Error());
};

}

#endif // __KLEO_ENCRYPTJOB_H__
# -*- mode: org -*-
#+TITLE: GNU Privacy Guard (GnuPG) Made Easy Python Bindings HOWTO (English)
#+AUTHOR: Ben McGinnes
#+LATEX_COMPILER: xelatex
#+LATEX_CLASS: article
#+LATEX_CLASS_OPTIONS: [12pt]
#+LATEX_HEADER: \usepackage{xltxtra}
#+LATEX_HEADER: \usepackage[margin=1in]{geometry}
#+LATEX_HEADER: \setmainfont[Ligatures={Common}]{Times New Roman}
#+LATEX_HEADER: \author{Ben McGinnes <ben@gnupg.org>}


* Introduction
 :PROPERTIES:
 :CUSTOM_ID: intro
 :END:

| Version:       | 0.1.5                                |
| GPGME Version: | 1.13.0                               |
| Author:        | Ben McGinnes <ben@gnupg.org>         |
| Author GPG Key: | DB4724E6FA4286C92B4E55C4321E4E2373590E5D |
| Language:      | Australian English, British English  |
| Language codes: | en-AU, en-GB, en                     |

This document provides basic instruction in how to use the GPGME
```

Python bindings to programmatically leverage the GPGME library.

** Python 2 versus Python
3
:PROPERTIES:
:CUSTOM_ID: py2-vs-py3
:END:

Though the GPGME Python bindings themselves provide support for both
Python 2 and 3, the focus is unequivocally on Python 3 and
specifically from Python 3.4 and above. As a consequence all the
examples and instructions in this guide use Python 3 code.

Much of it will work with Python 2, but much of it also deals with
Python 3 byte literals, particularly when reading and writing data.
Developers concentrating on Python 2.7, and possibly even 2.6, will
need to make the appropriate modifications to support the older string
and unicode types as opposed to bytes.

There are multiple reasons for concentrating on Python 3; some of
which relate to the immediate integration of these bindings, some of
which relate to longer term plans for both GPGME and the python
bindings and some of which relate to the impending EOL period for
Python 2.7. Essentially, though, there is little value in tying the
bindings to a version of the language which
is a dead end and the
advantages offered by Python 3 over Python 2 make handling the data
types with which GPGME deals considerably easier.

** Examples
:PROPERTIES:
:CUSTOM_ID: howto-python3-examples
:END:

All of the examples found in this document can be found as Python 3
scripts in the =lang/python/examples/howto= directory.

** Unofficial Drafts
:PROPERTIES:
:CUSTOM_ID: unofficial-drafts
:END:

In addition to shipping with each release of GPGME, there is a section
on locations to read or download [[#draft-editions][draft editions]] of this document from
at the end of it. These are unofficial versions produced in between

major releases.

** What's New
  :PROPERTIES:
  :CUSTOM_ID: new-stuff
  :END:

Full details of what is new are now available in the [[file:what-is-new.org][What's New]] file
and archives of the preceding /What's New/ sections are available in
the [[file:what-was-new][What Was New]] file.

*** New in GPGME 1130
   :PROPERTIES:
   :CUSTOM_ID:
 new-stuff-1-13-0
   :END:

See the [[file:what-is-new#new-stuff-1-13-0][What's New]] document for what is new in version 1.13.0.

*** New in GPGME 1120
   :PROPERTIES:
   :CUSTOM_ID: new-stuff-1-12-0
   :END:

See the [[file:what-was-new#new-stuff-1-12-0][What Was New]] document for what was new in version 1.12.0.

* GPGME Concepts
 :PROPERTIES:
 :CUSTOM_ID: gpgme-concepts
 :END:

** A C API
  :PROPERTIES:
  :CUSTOM_ID: gpgme-c-api
  :END:

Unlike many modern APIs with which programmers will be more familiar
with these days, the GPGME API is a C API. The API is intended for
use by C coders who would be able to access its features by including
the =gpgme.h= header file with their own C source code and then access
its functions just as they would any other C headers.

This is a very effective method of gaining complete access to the API

and in the most efficient manner possible. It does, however, have the drawback that it cannot be directly used by other languages without some
 means of providing an interface to those languages. This is where the need for bindings in various languages stems.

** Python bindings
  :PROPERTIES:
  :CUSTOM_ID: gpgme-python-bindings
  :END:

The Python bindings for GPGME provide a higher level means of accessing the complete feature set of GPGME itself. It also provides a more pythonic means of calling these API functions.

The bindings are generated dynamically with SWIG and the copy of =gpgme.h= generated when GPGME is compiled.

This means that a version of the Python bindings is fundamentally tied to the exact same version of GPGME used to generate that copy of =gpgme.h=.

** Difference between the Python bindings and other GnuPG Python packages
  :PROPERTIES:
  :CUSTOM_ID: gpgme-python-bindings-diffs
  :END:

There have been numerous attempts to add GnuPG support to Python over the years. Some of the most well known are listed here, along with what differentiates them.

*** The python-gnupg package maintained
 by Vinay Sajip
   :PROPERTIES:
   :CUSTOM_ID: diffs-python-gnupg
   :END:

This is arguably the most popular means of integrating GPG with Python. The package utilises the =subprocess= module to implement wrappers for the =gpg= and =gpg2= executables normally invoked on the command line (=gpg.exe= and =gpg2.exe= on Windows).

The popularity of this package stemmed from its ease of use and capability in providing the most commonly required features.

Unfortunately it has been beset by a number of security issues in the
past; most of which stemmed from using unsafe methods of accessing the
command line via the =subprocess= calls. While some effort has been
made over the last two to three years (as of 2018) to mitigate this,
particularly by no longer providing shell access through those
subprocess calls, the wrapper is still somewhat limited in the scope
of its GnuPG features coverage.

The python-gnupg package is available under the MIT license.

*** The gnupg package created
 and maintained by Isis Lovecruft
  :PROPERTIES:
  :CUSTOM_ID: diffs-isis-gnupg
  :END:

In 2015 Isis Lovecruft from the Tor Project forked and then
re-implemented the python-gnupg package as just gnupg. This new
package also relied on subprocess to call the =gpg= or =gpg2=
binaries, but did so somewhat more securely.

The naming and version numbering selected for this package, however,
resulted in conflicts with the original python-gnupg and since its
functions were called in a different manner to python-gnupg, the
release of this package also resulted in a great deal of consternation
when people installed what they thought was an upgrade that
subsequently broke the code relying on it.

The gnupg package is available under the GNU General Public License
version 3.0 (or any later version).

*** The PyME package maintained by Martin Albrecht
  :PROPERTIES:
  :CUSTOM_ID: diffs-pyme
  :END:

This package is the origin of these bindings, though they are somewhat
different now.
  For details of when and how the PyME package was
folded back into GPGME itself see the [[file:short-history.org][Short History]] document.[fn:1]

The PyME package was first released in 2002 and was also the first
attempt to implement a low level binding to GPGME. In doing so it
provided access to considerably more functionality than either the
=python-gnupg= or =gnupg= packages.

The PyME package is only available for Python 2.6 and 2.7.

Porting the PyME package to Python 3.4 in 2015 is what resulted in it
being folded into the GPGME project and the current bindings are the
end result of that effort.

The PyME package is available under the same dual licensing as GPGME
itself: the GNU General Public License version 2.0 (or any later
version) and the GNU Lesser General Public License version 2.1 (or any
later version).

* GPGME Python bindings installation
 :PROPERTIES:
 :CUSTOM_ID: gpgme-python-install
 :END:

** No PyPI
  :PROPERTIES:
  :CUSTOM_ID: do-not-use-pypi
  :END:

Most
 third-party Python packages and modules are available and
distributed through the Python Package Installer, known as PyPI.

Due to the nature of what these bindings are and how they work, it is
infeasible to install the GPGME Python bindings in the same way.

This is because the bindings use SWIG to dynamically generate C
bindings against =gpgme.h= and =gpgme.h= is generated from
=gpgme.h.in= at compile time when GPGME is built from source. Thus to
include a package in PyPI which actually built correctly would require
either statically built libraries for every architecture bundled with
it or a full implementation of C for each architecture.

See the additional notes regarding [[#snafu-cffi][CFFI and SWIG]] at the end of this
section for further details.

** Requirements
  :PROPERTIES:
  :CUSTOM_ID: gpgme-python-requirements
  :END:

The GPGME Python bindings only have three requirements:

1. A suitable version of Python 2 or Python 3. With Python 2 that
  means CPython
 2.7 and with Python 3 that means CPython 3.4 or
  higher.
2. [[https://www.swig.org][SWIG]].
3. GPGME itself. Which also means that all of GPGME's dependencies
  must be installed too.

*** Recommended Additions
  :PROPERTIES:
  :CUSTOM_ID: gpgme-python-recommendations
  :END:

Though none of the following are absolute requirements, they are all
recommended for use with the Python bindings. In some cases these
recommendations refer to which version(s) of CPython to use the
bindings with, while others refer to third party modules which provide
a significant advantage in some way.

1. If possible, use Python 3 instead of 2.
2. Favour a more recent version of Python since even 3.4 is due to
  reach EOL soon. In production systems and services, Python 3.6
  should be robust enough to be relied on.
3. If possible add the following Python modules which are not part of
  the standard library: [[http://docs.python-requests.org/en/latest/index.html][Requests]],
[[https://cython.org/][Cython]],
 [[https://pendulum.eustace.io/][Pendulum]] and [[https://github.com/Selfnet/hkp4py][hkp4py]].

Chances are quite high that at least the first one and maybe two of
those will already be installed.

Note that, as with Cython, some of advanced use case scenarios will
bring with them additional requirements. Most of these will be fairly
well known and commonly installed ones, however, which are in many
cases likely to have already been installed on many systems or be
familiar to Python programmers.

** Installation
  :PROPERTIES:
  :CUSTOM_ID: installation
  :END:

Installing the Python bindings is effectively achieved by compiling
and installing GPGME itself.

Once SWIG is installed with Python and all the dependencies for GPGME

are installed you only need to confirm that the version(s) of Python
you want the bindings installed for are in your =$PATH=.

By default GPGME will attempt to install the bindings for the most
recent or highest version number of Python 2 and Python
 3 it detects
in =$PATH=. It specifically checks for the =python= and =python3=
executables first and then checks for specific version numbers.

For Python 2 it checks for these executables in this order: =python=,
=python2= and =python2.7=.

For Python 3 it checks for these executables in this order: =python3=,
=python3.7=, =python3.6=, =python3.5= and =python3.4=.[fn:2]

On systems where =python= is actually =python3= and not =python2= it
may be possible that =python2= may be overlooked, but there have been
no reports of that actually occurring as yet.

In the three months or so since the release of Python 3.7.0 there has
been extensive testing and work with these bindings with no issues
specifically relating to the new version of Python or any of the new
features of either the language or the bindings. This has also been
the case with Python 3.7.1rc1. With that in mind and given the
release of Python 3.7.1 is scheduled for around the same time as GPGME
1.12.0, the order of preferred
 Python versions has been changed to
move Python 3.7 ahead of Python 3.6.

*** Installing GPGME
  :PROPERTIES:
  :CUSTOM_ID: install-gpgme
  :END:

See the GPGME =README= file for details of how to install GPGME from
source.

** Known Issues
 :PROPERTIES:
 :CUSTOM_ID: snafu
 :END:

There are a few known issues with the current build process and the
Python bindings. For the most part these are easily addressed should
they be encountered.

*** Breaking Builds
  :PROPERTIES:
  :CUSTOM_ID: snafu-a-swig-of-this-builds-character
  :END:

Occasionally when installing GPGME with the Python bindings included
it may be observed that the =make= portion of that process induces a
large very number of warnings and, eventually errors which end that
part of the build process. Yet following that with =make check= and
=make install= appears to work seamlessly.

The cause of this is related to the way SWIG needs to be called to
dynamically generate the C bindings for GPGME in
 the first place. So
the entire process will always produce =lang/python/python2-gpg/= and
=lang/python/python3-gpg/= directories. These should contain the
build output generated during compilation, including the complete
bindings and module installed into =site-packages=.

Occasionally the errors in the early part or some other conflict
(e.g. not installing as */root/* or */su/*) may result in nothing
being installed to the relevant =site-packages= directory and the
build directory missing a lot of expected files. Even when this
occurs, the solution is actually quite simple and will always work.

That solution is simply to run the following commands as either the
root user or prepended with =sudo -H=[fn:3] in the =lang/python/=
directory:

#+BEGIN_SRC shell
 /path/to/pythonX.Y setup.py build
 /path/to/pythonX.Y setup.py build
 /path/to/pythonX.Y setup.py install
#+END_SRC

Yes, the build command does need to be run twice. Yes, you still need
to run the potentially failing or
 incomplete steps during the
=configure=, =make= and =make install= steps with installing GPGME.
This is because those steps generate a lot of essential files needed,
both by and in order to create, the bindings (including both the
=setup.py= and =gpgme.h= files).

**** IMPORTANT Note
  :PROPERTIES:
  :CUSTOM_ID: snafu-swig-build-note

:END:

If specifying a selected number of languages to create bindings for,
try to leave Python last. Currently the majority of the other
language bindings are also preceding Python of either version when
listed alphabetically (not counting the Qt bindings).

If Python is set to precede one of the other languages then it is
possible that the errors described here may interrupt the build
process before generating bindings for those other languages. In
these cases it may be preferable to configure all preferred language
bindings separately with alternative =configure= steps for GPGME using
the =--enable-languages=$LANGUAGE= option.

Alternatively
 =make= (or =gmake=, depending on your platform) may be
run with the the =-k= option, which tells make to keep going even if
errors are encountered. In that case the failure of one language's
set of bindings to build should not hamper another language's bindings
to build.

*** Reinstalling Responsibly
:PROPERTIES:
:CUSTOM_ID: snafu-lessons-for-the-lazy
:END:

Regardless of whether you're installing for one version of Python or
several, there will come a point where reinstallation is required.
With most Python module installations, the installed files go into the
relevant site-packages directory and are then forgotten about. Then
the module is upgraded, the new files are copied over the old and
that's the end of the matter.

While the same is true of these bindings, there have been intermittent
issues observed on some platforms which have benefited significantly
from removing all the previous installations of the bindings before
installing the updated versions.

Removing
 the previous version(s) is simply a matter of changing to the
relevant =site-packages= directory for the version of Python in
question and removing the =gpg/= directory and any accompanying
egg-info files for that module.

In most cases this will require root or administration privileges on
the system, but the same is true of installing the module in the first
place.

*** Multiple installations
:PROPERTIES:
:CUSTOM_ID: snafu-the-full-monty
:END:

For a variety of reasons it may be either necessary or just preferable
to install the bindings to alternative installed Python versions which
meet the requirements of these bindings.

On POSIX systems this will generally be most simply achieved by
running the manual installation commands (build, build, install) as
described in the previous section for each Python installation the
bindings need to be installed to.

As per the SWIG documentation: the compilers, libraries and runtime
used to build GPGME and the Python Bindings *must*
match those used to
compile Python itself, including the version number(s) (at least going
by major version numbers and probably minor numbers too).

On most POSIX systems, including OS X, this will very likely be the
case in most, if not all, cases.

Note that from GPGME [[https://dev.gnupg.org/rMff6ff616aea6f59b7f2ce1176492850ecdf3851e][1.12.1]] the
default installation installs to each
version of Python it can find first. That is that it will currently
install for the first copies of Python versions 2.7, 3.4, 3.5, and so on
up until the current dev branch that it finds. Usually this will be in the
same prefix as GPGME itself, but is dictated by the =$PATH= when the
installation is performed. The above instructions can still be
performed on other python installations which the installer does not
find, including alternative prefixes.

*** Won't Work With Windows
:PROPERTIES:
:CUSTOM_ID: snafu-runtime-not-funtime
:END:

There are semi-regular reports of Windows users
having considerable
difficulty in installing and using the Python bindings at all. Very
often, possibly even always, these reports come from Cygwin users
and/or MinGW users and/or Msys2 users. Though not all of them have
been confirmed, it appears that these reports have also come from

people who installed Python using the Windows installer files from the
[[https://python.org][Python website]] (i.e. mostly MSI installers, sometimes self-extracting
=.exe= files).

The Windows versions of Python are not built using Cygwin, MinGW or
Msys2; they're built using Microsoft Visual Studio. Furthermore the
version used is /considerably/ more advanced than the version which
MinGW obtained a small number of files from many years ago in order to
be able to compile anything at all. Not only that, but there are
changes to the version of Visual Studio between some micro releases,
though that is is particularly the case with Python 2.7, since it has
been kept around far longer than it should have
 been.

There are two theoretical solutions to this issue:

1. Compile and install the GnuPG stack, including GPGME and the
   Python bindings using the same version of Microsoft Visual Studio
   used by the Python Foundation to compile the version of Python
   installed.

   If there are multiple versions of Python then this will need to be
   done with each different version of Visual Studio used for those
   versions of Python.

2. Compile and install Python using the same tools used by choice,
   such as MinGW or Msys2.

Do *not* use the official Windows installer for Python unless
following the first method.

In this type of situation it may even be for the best to accept that
there are less limitations on permissive software than free software
and simply opt to use a recent version of the Community Edition of
Microsoft Visual Studio to compile and build all of it, no matter
what.

Investigations into the extent or the limitations of this issue are
ongoing.

The following
 table lists the version of Microsoft Visual Studio which
needs to be used when compiling GPGME and the Python bindings with
each version of the CPython binary released [[https://www.python.org/downloads/windows/][for Windows]]:

CPython	Microsoft product name	runtime filename
2.7.6	Visual Studio 2008	MSVCR90.DLL
3.4.0	Visual Studio 2010	MSVCR100.DLL

3.5.0	Visual Studio 2015	*see below*
3.6.0	Visual Studio 2015	*see below*
3.7.0	Visual Studio 2017*	*see below*

It is important to note that MingW and Msys2 ship with the Visual C runtime from Microsoft Visual Studio 2005 and are thus *incompatible* with all the versions of CPython which can be used with the GPGME Python bindings.

It is also important to note that from CPython 3.5 onwards, the Python Foundation has adopted the reworking of the Visual C runtime which was performed for Visual Studio 2015 and aimed at resolving many of these kinds of issues. Much greater detail on these issues and the correct file(s) to link to are available from Matthew Brett's invaluable page, [[https://matthew-brett.github.io/pydagogue/python_msvc.html][Using Microsoft Visual C with Python]]. It is also worth reading the Microsoft Developer Network blog post on [[http://blogs.msdn.com/b/vcblog/archive/2015/03/03/introducing-the-universal-crt.aspx][the universal CRT]] and Steve Dower's blog posts on Python extensions ([[http://stevedower.id.au/blog/building-for-python-3-5][part 1]] and [[http://stevedower.id.au/blog/building-for-python-3-5-part-two][part 2]]).

The second of those two posts by Steve Dower contains the details of specific configuration options required for compiling anything to be used with official CPython releases. In addition to those configuration and compiler settings to use, the versions of Visual Studio prior to Visual Studio 2015 did not support 64-bit systems by default. So compiling a 64-bit version of these bindings for a 64-bit version of CPython 2.7 or 3.4 requires additional work.

In addition to the blog posts, the [[https://wiki.python.org/moin/WindowsCompilers][Windows compilers]] wiki page on the CPython wiki is another essential reference on the relevant versions of Visual Studio to use and the degree of compatibility with CPython releases.

Eventually someone will ask why there isn't an installable binary for Windows, which the GPGME of the licenses do not preclude as long as the source code is available in conjunction with such a release.

The sheer number of versions of Visual Studio in conjunction with differing configuration options depending on the target Windows version and whether the architecture is 64-bit or 32-bit makes it difficult to provide a correct binary installer for Windows users. At the bare minimum doing so would require the GnuPG project compile ten different versions of the bindings with each release; both 32-bit and 64-bit versions for CPython 2.7 and 3.4,

with 64-bit versions for both
x86-64 (i.e. Intel and AMD) and ARM architectures for CPython 3.5,
3.6, 3.7 and later releases. That's the bare *minimum*, it'd probably
be higher.

Additionally, with only a binary installation used in conjunction with
the CPython installer from =python.org= the advanced options available
which utilise [[#cython][Cython]] will not be able to be used at all. Cython
depends on being able to compile the C code it generates and that too
would need to utilise a matching runtime to both the installed version
of CPython and these bindings in order to work with the bindings.

Considering all of that, what do we recommend?

1. Use a recent version of CPython; at least 3.5, but ideally 3.6 or
   later.

2. Use Visual Studio 2015 or the standalone build tools for Visual
   Studio 2017 (or later).

3. Compile both CPython and GPGME with these bindings using the tools
   selected in step 2.

4. Ignore MingW, Msys2 and the official CPython binary installers.

5. Be thankful the answer to this question wasn't simply to say
   something like, install Linux or install FreeBSD (or even
   Apple's OS X).

*** CFFI is the Best and GPGME should use it instead of SWIG
   :PROPERTIES:
   :CUSTOM_ID: snafu-cffi
   :END:

There are many reasons for favouring [[https://cffi.readthedocs.io/en/latest/overview.html][CFFI]] and proponents of it are
quite happy to repeat these things as if all it would take to switch
from SWIG to CFFI is repeating that list as if it were a new concept.

The fact is that there are things which Python's CFFI implementation
cannot handle in the GPGME C code. Beyond that there are features of
SWIG which are simply not available with CFFI at all. SWIG generates
the bindings to Python using the =gpgme.h= file, but that file is not
a single version shipped with each release, it too is generated when
GPGME is compiled.

CFFI is currently unable to adapt to such a potentially mutable

codebase. If there were some means of
 applying SWIG's dynamic code
generation to produce the Python/CFFI API modes of accessing the GPGME
libraries (or the source source code directly), but such a thing does
not exist yet either and it currently appears that work is needed in
at least one of CFFI's dependencies before any of this can be
addressed.

So if you're a massive fan of CFFI; that's great, but if you want this
project to switch to CFFI then rather than just insisting that it
should, I'd suggest you volunteer to bring CFFI up to the level this
project needs.

If you're actually seriously considering doing so, then I'd suggest
taking the =gpgme-tool.c= file in the GPGME =src/= directory and
getting that to work with any of the CFFI API methods (not the ABI
methods, they'll work with pretty much anything). When you start
running into trouble with "ifdefs" then you'll know what sort of
things are lacking. That doesn't even take into account the amount of
work saved via SWIG's code generation techniques either.

***
 Virtualised Environments
   :PROPERTIES:
   :CUSTOM_ID: snafu-venv
   :END:

It is fairly common practice amongst Python developers to, as much as
possible, use packages like virtualenv to keep various things that are
to be installed from interfering with each other. Given how much of
the GPGME bindings is often at odds with the usual pythonic way of
doing things, it stands to reason that this would be called into
question too.

As it happens the answer as to whether or not the bindings can be used
with virtualenv, the answer is both yes and no.

In general we recommend installing to the relevant path and matching
prefix of GPGME itself. Which means that when GPGME, and ideally the
rest of the GnuPG stack, is installed to a prefix like =/usr/local= or
=/opt/local= then the bindings would need to be installed to the main
Python installation and not a virtualised abstraction. Attempts to
separate the two in the past have been known to cause weird and
intermittent errors ranging from
 minor annoyances to complete failures
in the build process.

As a consequence we only recommend building with and installing to the
main Python installations within the same prefix as GPGME is installed
to or which are found by GPGME's configuration stage immediately prior
to running the make commands. Which is exactly what the compiling and
installing process of GPGME does by default.

Once that is done, however, it appears that a copy of the compiled
module may be installed into a virtualenv of the same major and minor
version matching the build. Alternatively it is possible to utilise a
=sites.pth= file in the =site-packages/= directory of a virtualenv
installation, which links back to the system installations
corresponding directory in order to import anything installed system
wide. This may or may not be appropriate on a case by case basis.

Though extensive testing of either of these options is not yet
complete, preliminary testing of them indicates that both are viable
as
 long as the main installation is complete. Which means that
certain other options normally restricted to virtual environments are
also available, including integration with pythonic test suites
(e.g. [[https://docs.pytest.org/en/latest/index.html][pytest]]) and other large projects.

That said, it is worth reiterating the warning regarding non-standard
installations. If one were to attempt to install the bindings only to
a virtual environment without somehow also including the full GnuPG
stack (or enough of it as to include GPGME) then it is highly likely
that errors would be encountered at some point and more than a little
likely that the build process itself would break.

If a degree of separation from the main operating system is still
required in spite of these warnings, then consider other forms of
virtualisation. Either a virtual machine (e.g. [[https://www.virtualbox.org/][VirtualBox]]), a
hardware emulation layer (e.g. [[https://www.qemu.org/][QEMU]]) or an application container
(e.g.
 [[https://www.docker.com/why-docker][Docker]]).

Finally it should be noted that the limited tests conducted thus far
have been using the =virtualenv= command in a new directory to create
the virtual python environment. As opposed to the standard =python3
-m venv= and it is possible that this will make a difference depending
on the system and version of Python in use. Another option is to run
the command =python3 -m virtualenv /path/to/install/virtual/thingy=
instead.

*** Post installation
  :PROPERTIES:
  :CUSTOM_ID: snafu-docs

:END:

Following installation it is recommended to move the
=post_installer.py= script from the =lang/python/examples/howto/=
directory to the =lang/python/= directory and run it. This will fix
or restore files needed by Sphinx which may be removed during a
distribution build for release. It will also generate reST files from
Org mode files with Pandoc and generate Texinfo files from Org mode
files with GNU Emacs and Org mode (in batch
mode). Additionally it
will fix the UTF-8 declaration line in the Texinfo files (Emacs
expects "UTF-8" to be "utf-8").

* Fundamentals
:PROPERTIES:
:CUSTOM_ID: howto-fund-a-mental
:END:

Before we can get to the fun stuff, there are a few matters regarding
GPGME's design which hold true whether you're dealing with the C code
directly or these Python bindings.

** No REST
:PROPERTIES:
:CUSTOM_ID: no-rest-for-the-wicked
:END:

The first part of which is or will be fairly blatantly obvious upon
viewing the first example, but it's worth reiterating anyway. That
being that this API is /*not*/ a REST API. Nor indeed could it ever
be one.

Most, if not all, Python programmers (and not just Python programmers)
know how easy it is to work with a RESTful API. In fact they've
become so popular that many other APIs attempt to emulate REST-like
behaviour as much as they are able. Right down to the use of JSON
formatted output to facilitate the use of their API without having
to
retrain developers.

This API does not do that. It would not be able to do that and also
provide access to the entire C API on which it's built. It does,
however, provide a very pythonic interface on top of the direct
bindings and it's this pythonic layer that this HOWTO deals with.

** Context
 :PROPERTIES:
 :CUSTOM_ID: howto-get-context
 :END:

One of the reasons which prevents this API from being RESTful is that most operations require more than one instruction to the API to perform the task. Sure, there are certain functions which can be performed simultaneously, particularly if the result known or strongly anticipated (e.g. selecting and encrypting to a key known to be in the public keybox).

There are many more, however, which cannot be manipulated so readily: they must be performed in a specific sequence and the result of one operation has a direct bearing on the outcome of subsequent operations. Not merely by generating an error either.

When dealing with this type
 of persistent state on the web, full of
both the RESTful and REST-like, it's most commonly referred to as a session. In GPGME, however, it is called a context and every operation type has one.

* Working with keys
 :PROPERTIES:
 :CUSTOM_ID: howto-keys
 :END:

** Key selection
 :PROPERTIES:
 :CUSTOM_ID: howto-keys-selection
 :END:

Selecting keys to encrypt to or to sign with will be a common occurrence when working with GPGMe and the means available for doing so are quite simple.

They do depend on utilising a Context; however once the data is recorded in another variable, that Context does not need to be the same one which subsequent operations are performed.

The easiest way to select a specific key is by searching for that key's key ID or fingerprint, preferably the full fingerprint without any spaces in it. A long key ID will probably be okay, but is not advised and short key IDs are already a problem with some being generated to match specific patterns. It does not

matter whether the
pattern is upper or lower case.

So this is the best method:

```
#+BEGIN_SRC python -i
import gpg

k = gpg.Context().keylist(pattern="258E88DCBD3CD44D8E7AB43F6ECB6AF0DEADBEEF")
keys = list(k)
#+END_SRC
```

This is passable and very likely to be common:

```
#+BEGIN_SRC python -i
import gpg

k = gpg.Context().keylist(pattern="0x6ECB6AF0DEADBEEF")
keys = list(k)
#+END_SRC
```

And this is a really bad idea:

```
#+BEGIN_SRC python -i
import gpg

k = gpg.Context().keylist(pattern="0xDEADBEEF")
keys = list(k)
#+END_SRC
```

Alternatively it may be that the intention is to create a list of keys
which all match a particular search string. For instance all the
addresses at a particular domain, like this:

```
#+BEGIN_SRC python -i
import gpg

ncsc = gpg.Context().keylist(pattern="ncsc.mil")
nsa = list(ncsc)
#+END_SRC
```

*** Counting keys
  :PROPERTIES:
  :CUSTOM_ID: howto-keys-counting
  :END:

Counting the number of keys in your public keybox (=pubring.kbx=), the

format which has superseded
 the old keyring format (=pubring.gpg= and
=secring.gpg=), or the number of secret keys is a very simple task.

#+BEGIN_SRC python -i
import gpg

c = gpg.Context()
seckeys = c.keylist(pattern=None, secret=True)
pubkeys = c.keylist(pattern=None, secret=False)

seclist = list(seckeys)
secnum = len(seclist)

publist = list(pubkeys)
pubnum = len(publist)

print("""
 Number of secret keys: {0}
 Number of public keys: {1}
""".format(secnum, pubnum))
#+END_SRC

NOTE: The [[#cython][Cython]] introduction in the [[#advanced-use][Advanced and Experimental]]
section uses this same key counting code with Cython to demonstrate
some areas where Cython can improve performance even with the
bindings. Users with large public keyrings or keyboxes, for instance,
should consider these options if they are comfortable with using
Cython.

** Get key
  :PROPERTIES:
  :CUSTOM_ID: howto-get-key
  :END:

An alternative method of getting a single key via its fingerprint is
available directly within a Context
 with =Context().get_key=. This is
the preferred method of selecting a key in order to modify it, sign or
certify it and for obtaining relevant data about a single key as a
part of other functions; when verifying a signature made by that key,
for instance.

By default this method will select public keys, but it can select
secret keys as well.

This first example demonstrates selecting the current key of Werner

Koch, which is due to expire at the end of 2018:

#+BEGIN_SRC python -i
import gpg

fingerprint = "80615870F5BAD690333686D0F2AD85AC1E42B367"
key = gpg.Context().get_key(fingerprint)
#+END_SRC

Whereas this example demonstrates selecting the author's current key
with the =secret= key word argument set to =True=:

#+BEGIN_SRC python -i
import gpg

fingerprint = "DB4724E6FA4286C92B4E55C4321E4E2373590E5D"
key = gpg.Context().get_key(fingerprint, secret=True)
#+END_SRC

It is, of course, quite possible to select expired, disabled and
revoked keys with this function, but only to effectively
 display
information about those keys.

It is also possible to use both unicode or string literals and byte
literals with the fingerprint when getting a key in this way.

** Importing keys
  :PROPERTIES:
  :CUSTOM_ID: howto-import-key
  :END:

Importing keys is possible with the =key_import()= method and takes
one argument which is a bytes literal object containing either the
binary or ASCII armoured key data for one or more keys.

The following example retrieves one or more keys from the SKS
keyservers via the web using the requests module. Since requests
returns the content as a bytes literal object, we can then use that
directly to import the resulting data into our keybox.

#+BEGIN_SRC python -i
import gpg
import os.path
import requests

c = gpg.Context()

```
url = "https://sks-keyservers.net/pks/lookup"
pattern = input("Enter the pattern to search for key or user IDs: ")
payload = {"op": "get", "search": pattern}

r = requests.get(url, verify=True, params=payload)
result
 = c.key_import(r.content)

if result is not None and hasattr(result, "considered") is False:
  print(result)
elif result is not None and hasattr(result, "considered") is True:
  num_keys = len(result.imports)
  new_revs = result.new_revocations
  new_sigs = result.new_signatures
  new_subs = result.new_sub_keys
  new_uids = result.new_user_ids
  new_scrt = result.secret_imported
  nochange = result.unchanged
  print("""
 The total number of keys considered for import was:  {0}

    Number of keys revoked:  {1}
  Number of new signatures:  {2}
     Number of new subkeys:  {3}
    Number of new user IDs:  {4}
 Number of new secret keys:  {5}
  Number of unchanged keys:  {6}

 The key IDs for all considered keys were:
""".format(num_keys, new_revs, new_sigs, new_subs, new_uids, new_scrt,
         nochange))
  for i in range(num_keys):
      print("{0}\n".format(result.imports[i].fpr))
else:
  pass
#+END_SRC

NOTE: When searching for a key ID of any length
 or a fingerprint
(without spaces), the SKS servers require the the leading =0x=
indicative of hexadecimal be included.  Also note that the old short
key IDs (e.g. =0xDEADBEEF=) should no longer be used due to the
relative ease by which such key IDs can be reproduced, as demonstrated
by the Evil32 Project in 2014 (which was subsequently exploited in
2016).

Testing for whether a string in any given search is or may be a
hexadecimal value which may be missing the leading =0x= is a simple
```

matter of using a try/except statement which attempts to convert the
string as hex to an integer and then back to hex; then using that to
search with. Raising a ValueError simply results in treating the
string as a string. This is the method and logic utilised in the
=import-keys-hkp.py= script (see below).

*** Working with ProtonMail
  :PROPERTIES:
  :CUSTOM_ID: import-protonmail
  :END:

Here is a variation on the example above which checks the constrained
ProtonMail keyserver for ProtonMail
 public keys.

```
#+BEGIN_SRC python -i
import gpg
import requests
import sys

print("""
This script searches the ProtonMail key server for the specified key and
imports it.
""")

c = gpg.Context(armor=True)
url = "https://api.protonmail.ch/pks/lookup"
ksearch = []

if len(sys.argv) >= 2:
  keyterm = sys.argv[1]
else:
  keyterm = input("Enter the key ID, UID or search string: ")

if keyterm.count("@") == 2 and keyterm.startswith("@") is True:
  ksearch.append(keyterm[1:])
  ksearch.append(keyterm[1:])
  ksearch.append(keyterm[1:])
elif keyterm.count("@") == 1 and keyterm.startswith("@") is True:
  ksearch.append("{0}@protonmail.com".format(keyterm[1:]))
  ksearch.append("{0}@protonmail.ch".format(keyterm[1:]))
  ksearch.append("{0}@pm.me".format(keyterm[1:]))
elif keyterm.count("@") == 0:
  ksearch.append("{0}@protonmail.com".format(keyterm))
  ksearch.append("{0}@protonmail.ch".format(keyterm))
  ksearch.append("{0}@pm.me".format(keyterm))
elif keyterm.count("@") ==
```

```
 2 and keyterm.startswith("@") is False:
   uidlist = keyterm.split("@")
   for uid in uidlist:
      ksearch.append("{0}@protonmail.com".format(uid))
      ksearch.append("{0}@protonmail.ch".format(uid))
      ksearch.append("{0}@pm.me".format(uid))
elif keyterm.count("@") > 2:
   uidlist = keyterm.split("@")
   for uid in uidlist:
      ksearch.append("{0}@protonmail.com".format(uid))
      ksearch.append("{0}@protonmail.ch".format(uid))
      ksearch.append("{0}@pm.me".format(uid))
else:
   ksearch.append(keyterm)

for k in ksearch:
   payload = {"op": "get", "search": k}
   try:
      r = requests.get(url, verify=True, params=payload)
      if r.ok is True:
         result = c.key_import(r.content)
      elif r.ok is False:
         result = r.content
   except Exception as e:
      result = None

   if result is not None and hasattr(result, "considered") is False:
      print("{0} for {1}".format(result.decode(), k))
   elif result is not None
 and hasattr(result, "considered") is True:
      num_keys = len(result.imports)
      new_revs = result.new_revocations
      new_sigs = result.new_signatures
      new_subs = result.new_sub_keys
      new_uids = result.new_user_ids
      new_scrt = result.secret_imported
      nochange = result.unchanged
      print("""
The total number of keys considered for import was:  {0}

With UIDs wholely or partially matching the following string:

      {1}

  Number of keys revoked:  {2}
Number of new signatures:  {3}
   Number of new subkeys:  {4}
  Number of new user IDs:  {5}
```

```
Number of new secret keys:  {6}
Number of unchanged keys:  {7}

The key IDs for all considered keys were:
""".format(num_keys, k, new_revs, new_sigs, new_subs, new_uids, new_scrt,
          nochange))
       for i in range(num_keys):
           print(result.imports[i].fpr)
       print("")
   elif result is None:
       print(e)
#+END_SRC
```

Both the above example, [[../examples/howto/pmkey-import.py][pmkey-import.py]],
and a version which prompts
for an alternative GnuPG home directory, [[../examples/howto/pmkey-import-alt.py][pmkey-import-alt.py]], are
available with the other examples and are executable scripts.

Note that while the ProtonMail servers are based on the SKS servers,
their server is related more to their API and is not feature complete
by comparison to the servers in the SKS pool. One notable difference
being that the ProtonMail server does not permit non ProtonMail users
to update their own keys, which could be a vector for attacking
ProtonMail users who may not receive a key's revocation if it had been
compromised.

*** Importing with HKP for Python
  :PROPERTIES:
  :CUSTOM_ID: import-hkp4py
  :END:

Performing the same tasks with the [[https://github.com/Selfnet/hkp4py][hkp4py module]] (available via PyPI)
is not too much different, but does provide a number of options of
benefit to end users. Not least of which being the ability to perform
some
checks on a key before importing it or not. For instance it may
be the policy of a site or project to only import keys which have not
been revoked. The hkp4py module permits such checks prior to the
importing of the keys found.

```
#+BEGIN_SRC python -i
import gpg
import hkp4py
import sys

c = gpg.Context()
server = hkp4py.KeyServer("hkps://hkps.pool.sks-keyservers.net")
```

```
results = []
keys = []

if len(sys.argv) > 2:
  pattern = " ".join(sys.argv[1:])
elif len(sys.argv) == 2:
  pattern = sys.argv[1]
else:
  pattern = input("Enter the pattern to search for keys or user IDs: ")


if pattern is not None:
  try:
    key = server.search(hex(int(pattern, 16)))
    keyed = True
  except ValueError as ve:
    key = server.search(pattern)
    keyed = False

  if key is not None:
    keys.append(key[0])
    if keyed is True:
      try:
        fob = server.search(pattern)
      except:
        fob = None
      if fob is not
 None:
        keys.append(fob[0])
    else:
      pass
  else:
    pass

  for logrus in pattern.split():
    try:
      key = server.search(hex(int(logrus, 16)))
      hexed = True
    except ValueError as ve:
      key = server.search(logrus)
      hexed = False

    if key is not None:
      keys.append(key[0])
      if hexed is True:
        try:
          fob = server.search(logrus)
        except:
```

```
                fob = None
            if fob is not None:
                keys.append(fob[0])
        else:
            pass
    else:
        pass


if len(keys) > 0:
  for key in keys:
    import_result = c.key_import(key.key_blob)
    results.append(import_result)

for result in results:
  if result is not None and hasattr(result, "considered") is False:
    print(result)
  elif result is not None and hasattr(result, "considered") is True:
     num_keys = len(result.imports)
    new_revs = result.new_revocations
    new_sigs = result.new_signatures
    new_subs = result.new_sub_keys
    new_uids = result.new_user_ids
    new_scrt = result.secret_imported
    nochange = result.unchanged
    print("""
The total number of keys considered for import was:  {0}

  Number of keys revoked:  {1}
Number of new signatures:  {2}
   Number of new subkeys:  {3}
  Number of new user IDs:  {4}
Number of new secret keys:  {5}
Number of unchanged keys:  {6}

The key IDs for all considered keys were:
""".format(num_keys, new_revs, new_sigs, new_subs, new_uids, new_scrt,
       nochange))
    for i in range(num_keys):
       print(result.imports[i].fpr)
    print("")
  else:
    pass
#+END_SRC
```

Since the hkp4py module handles multiple keys just as effectively as
one (=keys= is a list of responses per matching key), the example
above is able to do a little bit more with the returned

data before
anything is actually imported.

*** Importing from ProtonMail with HKP for Python
:PROPERTIES:
:CUSTOM_ID: import-protonmail-hkp4py
:END:

Though this can provide certain benefits even when working with ProtonMail, the scope is somewhat constrained there due to the limitations of the ProtonMail keyserver.

For instance, searching the SKS keyserver pool for the term "gnupg" produces hundreds of results from any time the word appears in any part of a user ID. Performing the same search on the ProtonMail keyserver returns zero results, even though there are at least two test accounts which include it as part of the username.

The cause of this discrepancy is the deliberate configuration of that server by ProtonMail to require an exact match of the full email address of the ProtonMail user whose key is being requested. Presumably this is intended to reduce breaches of privacy of their users as an email address must already be known before a key for that address
can be obtained.

**** Import from ProtonMail via HKP for Python Example no. 1
:PROPERTIES:
:CUSTOM_ID: import-hkp4py-pm1
:END:

The following script is available with the rest of the examples under the somewhat less than original name, =pmkey-import-hkp.py=.

```
#+BEGIN_SRC python -i
import gpg
import hkp4py
import os.path
import sys

print("""
This script searches the ProtonMail key server for the specified key and
imports it.

Usage:  pmkey-import-hkp.py [search strings]
""")
```

```
c = gpg.Context(armor=True)
server = hkp4py.KeyServer("hkps://api.protonmail.ch")
keyterms = []
ksearch = []
allkeys = []
results = []
paradox = []
homeless = None

if len(sys.argv) > 2:
  keyterms = sys.argv[1:]
elif len(sys.argv) == 2:
  keyterm = sys.argv[1]
  keyterms.append(keyterm)
else:
  key_term = input("Enter the key ID, UID or search string: ")
  keyterms = key_term.split()

for keyterm in keyterms:
  if keyterm.count("@") == 2 and keyterm.startswith("@") is True:
     ksearch.append(keyterm[1:])
      ksearch.append(keyterm[1:])
     ksearch.append(keyterm[1:])
  elif keyterm.count("@") == 1 and keyterm.startswith("@") is True:
     ksearch.append("{0}@protonmail.com".format(keyterm[1:]))
     ksearch.append("{0}@protonmail.ch".format(keyterm[1:]))
     ksearch.append("{0}@pm.me".format(keyterm[1:]))
  elif keyterm.count("@") == 0:
     ksearch.append("{0}@protonmail.com".format(keyterm))
     ksearch.append("{0}@protonmail.ch".format(keyterm))
     ksearch.append("{0}@pm.me".format(keyterm))
  elif keyterm.count("@") == 2 and keyterm.startswith("@") is False:
     uidlist = keyterm.split("@")
     for uid in uidlist:
        ksearch.append("{0}@protonmail.com".format(uid))
        ksearch.append("{0}@protonmail.ch".format(uid))
        ksearch.append("{0}@pm.me".format(uid))
  elif keyterm.count("@") > 2:
     uidlist = keyterm.split("@")
     for uid in uidlist:
        ksearch.append("{0}@protonmail.com".format(uid))
         ksearch.append("{0}@protonmail.ch".format(uid))
        ksearch.append("{0}@pm.me".format(uid))
  else:
     ksearch.append(keyterm)

for k in ksearch:
```

```
  print("Checking for key for: {0}".format(k))
  try:
     keys = server.search(k)
     if isinstance(keys, list) is True:
        for key in keys:
           allkeys.append(key)
           try:
              import_result = c.key_import(key.key_blob)
           except Exception as e:
              import_result = c.key_import(key.key)
     else:
        paradox.append(keys)
        import_result = None
  except Exception as e:
     import_result = None
  results.append(import_result)

for result in results:
  if result is not None and hasattr(result, "considered") is False:
     print("{0} for {1}".format(result.decode(), k))
  elif result is not None and hasattr(result, "considered") is True:
     num_keys = len(result.imports)
      new_revs = result.new_revocations
     new_sigs = result.new_signatures
     new_subs = result.new_sub_keys
     new_uids = result.new_user_ids
     new_scrt = result.secret_imported
     nochange = result.unchanged
     print("""
The total number of keys considered for import was:  {0}

With UIDs wholely or partially matching the following string:

     {1}

  Number of keys revoked:  {2}
Number of new signatures:  {3}
   Number of new subkeys:  {4}
  Number of new user IDs:  {5}
Number of new secret keys:  {6}
Number of unchanged keys:  {7}

The key IDs for all considered keys were:
""".format(num_keys, k, new_revs, new_sigs, new_subs, new_uids, new_scrt,
        nochange))
     for i in range(num_keys):
        print(result.imports[i].fpr)
     print("")
```

```
  elif result is None:
     pass
#+END_SRC
```

**** Import from ProtonMail via HKP for Python Example no. 2
:PROPERTIES:
:CUSTOM_ID: import-hkp4py-pm2
:END:

Like its counterpart above, this script can also be found with the rest of the examples, by the name pmkey-import-hkp-alt.py.

With this script a modicum of effort has been made to treat anything passed as a =homedir= which either does not exist or which is not a directory, as also being a pssible user ID to check for. It's not guaranteed to pick up on all such cases, but it should cover most of them.

```
#+BEGIN_SRC python -i
import gpg
import hkp4py
import os.path
import sys

print("""
This script searches the ProtonMail key server for the specified key and
imports it.  Optionally enables specifying a different GnuPG home directory.

Usage:  pmkey-import-hkp.py [homedir] [search string]
  or:  pmkey-import-hkp.py [search string]
""")

c = gpg.Context(armor=True)
server = hkp4py.KeyServer("hkps://api.protonmail.ch")
keyterms = []
ksearch = []
allkeys = []
results = []
paradox = []
homeless = None

if len(sys.argv) > 3:
  homedir = sys.argv[1]
  keyterms = sys.argv[2:]
elif len(sys.argv)
```

```
 == 3:
   homedir = sys.argv[1]
   keyterm = sys.argv[2]
   keyterms.append(keyterm)
elif len(sys.argv) == 2:
   homedir = ""
   keyterm = sys.argv[1]
   keyterms.append(keyterm)
else:
   keyterm = input("Enter the key ID, UID or search string: ")
   homedir = input("Enter the GPG configuration directory path (optional): ")
   keyterms.append(keyterm)

if len(homedir) == 0:
   homedir = None
   homeless = False

if homedir is not None:
   if homedir.startswith("~"):
      if os.path.exists(os.path.expanduser(homedir)) is True:
         if os.path.isdir(os.path.expanduser(homedir)) is True:
            c.home_dir = os.path.realpath(os.path.expanduser(homedir))
         else:
            homeless = True
      else:
         homeless = True
   elif os.path.exists(os.path.realpath(homedir)) is True:
      if os.path.isdir(os.path.realpath(homedir)) is True:
         c.home_dir = os.path.realpath(homedir)
      else:
         homeless = True
    else:
      homeless = True

# First check to see if the homedir really is a homedir and if not, treat it as
# a search string.
if homeless is True:
   keyterms.append(homedir)
   c.home_dir = None
else:
   pass

for keyterm in keyterms:
   if keyterm.count("@") == 2 and keyterm.startswith("@") is True:
      ksearch.append(keyterm[1:])
      ksearch.append(keyterm[1:])
      ksearch.append(keyterm[1:])
   elif keyterm.count("@") == 1 and keyterm.startswith("@") is True:
```

```
      ksearch.append("{0}@protonmail.com".format(keyterm[1:]))
      ksearch.append("{0}@protonmail.ch".format(keyterm[1:]))
      ksearch.append("{0}@pm.me".format(keyterm[1:]))
    elif keyterm.count("@") == 0:
      ksearch.append("{0}@protonmail.com".format(keyterm))
      ksearch.append("{0}@protonmail.ch".format(keyterm))
      ksearch.append("{0}@pm.me".format(keyterm))
    elif keyterm.count("@") == 2 and keyterm.startswith("@") is False:
      uidlist = keyterm.split("@")

    for uid in uidlist:
        ksearch.append("{0}@protonmail.com".format(uid))
        ksearch.append("{0}@protonmail.ch".format(uid))
        ksearch.append("{0}@pm.me".format(uid))
    elif keyterm.count("@") > 2:
      uidlist = keyterm.split("@")
      for uid in uidlist:
        ksearch.append("{0}@protonmail.com".format(uid))
        ksearch.append("{0}@protonmail.ch".format(uid))
        ksearch.append("{0}@pm.me".format(uid))
    else:
      ksearch.append(keyterm)

  for k in ksearch:
    print("Checking for key for: {0}".format(k))
    try:
      keys = server.search(k)
      if isinstance(keys, list) is True:
        for key in keys:
          allkeys.append(key)
          try:
            import_result = c.key_import(key.key_blob)
          except Exception as e:
            import_result = c.key_import(key.key)
      else:
        paradox.append(keys)
        import_result = None
    except Exception
   as e:
      import_result = None
    results.append(import_result)

  for result in results:
    if result is not None and hasattr(result, "considered") is False:
      print("{0} for {1}".format(result.decode(), k))
    elif result is not None and hasattr(result, "considered") is True:
      num_keys = len(result.imports)
      new_revs = result.new_revocations
```

```
        new_sigs = result.new_signatures
        new_subs = result.new_sub_keys
        new_uids = result.new_user_ids
        new_scrt = result.secret_imported
        nochange = result.unchanged
        print("""
The total number of keys considered for import was:  {0}

With UIDs wholely or partially matching the following string:

      {1}

  Number of keys revoked:  {2}
Number of new signatures:  {3}
   Number of new subkeys:  {4}
  Number of new user IDs:  {5}
Number of new secret keys:  {6}
Number of unchanged keys:  {7}

The key IDs for all considered keys were:
""".format(num_keys, k, new_revs, new_sigs,
 new_subs, new_uids, new_scrt,
          nochange))
        for i in range(num_keys):
           print(result.imports[i].fpr)
        print("")
    elif result is None:
        pass
#+END_SRC


** Exporting keys
  :PROPERTIES:
  :CUSTOM_ID: howto-export-key
  :END:

Exporting keys remains a reasonably simple task, but has been
separated into three different functions for the OpenPGP cryptographic
engine.  Two of those functions are for exporting public keys and the
third is for exporting secret keys.


*** Exporting public keys
   :PROPERTIES:
   :CUSTOM_ID: howto-export-public-key
   :END:

There are two methods of exporting public keys, both of which are very
```

similar to the other. The default method, =key_export()=, will export
a public key or keys matching a specified pattern as normal. The
alternative, the =key_export_minimal()= method, will do the same thing
except producing a minimised output with extra signatures and third
party signatures or certifications removed.

```
#+BEGIN_SRC
 python -i
import gpg
import os.path
import sys

print("""
This script exports one or more public keys.
""")

c = gpg.Context(armor=True)

if len(sys.argv) >= 4:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
else:
  keyfile = input("Enter the path and filename to save the secret key to: ")
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if homedir.startswith("~"):
  if os.path.exists(os.path.expanduser(homedir)) is True:
     c.home_dir = os.path.expanduser(homedir)
  else:
     pass
elif
 os.path.exists(homedir) is True:
  c.home_dir = homedir
else:
  pass

try:
  result = c.key_export(pattern=logrus)
```

```
except:
  result = c.key_export(pattern=None)

if result is not None:
  with open(keyfile, "wb") as f:
    f.write(result)
else:
  pass
#+END_SRC
```

It should be noted that the result will only return =None= when a
search pattern has been entered, but has not matched any keys. When
the search pattern itself is set to =None= this triggers the exporting
of the entire public keybox.

```
#+BEGIN_SRC python -i
import gpg
import os.path
import sys

print("""
This script exports one or more public keys in minimised form.
""")

c = gpg.Context(armor=True)

if len(sys.argv) >= 4:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus
 = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
else:
  keyfile = input("Enter the path and filename to save the secret key to: ")
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if homedir.startswith("~"):
  if os.path.exists(os.path.expanduser(homedir)) is True:
    c.home_dir = os.path.expanduser(homedir)
  else:
```

```
    pass
elif os.path.exists(homedir) is True:
  c.home_dir = homedir
else:
  pass

try:
  result = c.key_export_minimal(pattern=logrus)
except:
  result = c.key_export_minimal(pattern=None)

if result is not None:
  with open(keyfile, "wb") as f:
    f.write(result)
else:
  pass
#+END_SRC
```

*** Exporting secret keys
  :PROPERTIES:
  :CUSTOM_ID: howto-export-secret-key
  :END:

Exporting secret keys is, functionally, very similar to exporting
public
 keys; save for the invocation of =pinentry= via =gpg-agent= in
order to securely enter the key's passphrase and authorise the export.

The following example exports the secret key to a file which is then
set with the same permissions as the output files created by the
command line secret key export options.

```
#+BEGIN_SRC python -i
import gpg
import os
import os.path
import sys

print("""
This script exports one or more secret keys.

The gpg-agent and pinentry are invoked to authorise the export.
""")

c = gpg.Context(armor=True)

if len(sys.argv) >= 4:
```

```
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
else:
   keyfile = input("Enter the path and filename to save the secret key to: ")
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if len(homedir) == 0:
  homedir = None
elif homedir.startswith("~"):
  userdir = os.path.expanduser(homedir)
  if os.path.exists(userdir) is True:
     homedir = os.path.realpath(userdir)
  else:
     homedir = None
else:
  homedir = os.path.realpath(homedir)

if os.path.exists(homedir) is False:
  homedir = None
else:
  if os.path.isdir(homedir) is False:
     homedir = None
  else:
     pass

if homedir is not None:
  c.home_dir = homedir
else:
  pass

try:
  result = c.key_export_secret(pattern=logrus)
except:
  result = c.key_export_secret(pattern=None)

if result is not None:
  with open(keyfile, "wb") as f:
     f.write(result)
```

```
  os.chmod(keyfile, 0o600)
else:
  pass
#+END_SRC

Alternatively the approach
 of the following script can be used.  This
longer example saves the exported secret key(s) in files in the GnuPG
home directory, in addition to setting the file permissions as only
readable and writable by the user.  It also exports the secret key(s)
twice in order to output both GPG binary (=.gpg=) and ASCII armoured
(=.asc=) files.

#+BEGIN_SRC python -i
import gpg
import os
import os.path
import subprocess
import sys

print("""
This script exports one or more secret keys as both ASCII armored and binary
file formats, saved in files within the user's GPG home directory.

The gpg-agent and pinentry are invoked to authorise the export.
""")

if sys.platform == "win32":
  gpgconfcmd = "gpgconf.exe --list-dirs homedir"
else:
  gpgconfcmd = "gpgconf --list-dirs homedir"

a = gpg.Context(armor=True)
b = gpg.Context()
c = gpg.Context()

if len(sys.argv) >= 4:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
   logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
```

```
else:
  keyfile = input("Enter the filename to save the secret key to: ")
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if len(homedir) == 0:
  homedir = None
elif homedir.startswith("~"):
  userdir = os.path.expanduser(homedir)
  if os.path.exists(userdir) is True:
    homedir = os.path.realpath(userdir)
  else:
    homedir = None
else:
  homedir = os.path.realpath(homedir)

if os.path.exists(homedir) is False:
  homedir = None
else:
  if os.path.isdir(homedir) is False:
    homedir = None
  else:
    pass

if homedir is not None:
  c.home_dir
 = homedir
else:
  pass

if c.home_dir is not None:
  if c.home_dir.endswith("/"):
    gpgfile = "{0}{1}.gpg".format(c.home_dir, keyfile)
    ascfile = "{0}{1}.asc".format(c.home_dir, keyfile)
  else:
    gpgfile = "{0}/{1}.gpg".format(c.home_dir, keyfile)
    ascfile = "{0}/{1}.asc".format(c.home_dir, keyfile)
else:
  if os.path.exists(os.environ["GNUPGHOME"]) is True:
    hd = os.environ["GNUPGHOME"]
  else:
    try:
      hd = subprocess.getoutput(gpgconfcmd)
    except:
      process = subprocess.Popen(gpgconfcmd.split(),
                                 stdout=subprocess.PIPE)
      procom = process.communicate()
      if sys.version_info[0] == 2:
```

```
            hd = procom[0].strip()
          else:
            hd = procom[0].decode().strip()
  gpgfile = "{0}/{1}.gpg".format(hd, keyfile)
  ascfile = "{0}/{1}.asc".format(hd, keyfile)

try:
  a_result = a.key_export_secret(pattern=logrus)
  b_result
 = b.key_export_secret(pattern=logrus)
except:
  a_result = a.key_export_secret(pattern=None)
  b_result = b.key_export_secret(pattern=None)

if a_result is not None:
  with open(ascfile, "wb") as f:
    f.write(a_result)
  os.chmod(ascfile, 0o600)
else:
  pass

if b_result is not None:
  with open(gpgfile, "wb") as f:
    f.write(b_result)
  os.chmod(gpgfile, 0o600)
else:
  pass
#+END_SRC


*** Sending public keys to the SKS Keyservers
  :PROPERTIES:
  :CUSTOM_ID: howto-send-public-key
  :END:

As with the previous section on importing keys, the =hkp4py= module
adds another option with exporting keys in order to send them to the
public keyservers.

The following example demonstrates how this may be done.

#+BEGIN_SRC python -i
import gpg
import hkp4py
import os.path
import sys

print("""
```

```
This script sends one or more public keys to the SKS keyservers and is
essentially a slight variation on the export-key.py script.
""")

c = gpg.Context(armor=True)
server
 = hkp4py.KeyServer("hkps://hkps.pool.sks-keyservers.net")

if len(sys.argv) > 2:
  logrus = " ".join(sys.argv[1:])
elif len(sys.argv) == 2:
  logrus = sys.argv[1]
else:
  logrus = input("Enter the UID matching the key(s) to send: ")

if len(logrus) > 0:
  try:
    export_result = c.key_export(pattern=logrus)
  except Exception as e:
    print(e)
    export_result = None
else:
  export_result = c.key_export(pattern=None)

if export_result is not None:
  try:
    try:
      send_result = server.add(export_result)
    except:
      send_result = server.add(export_result.decode())
    if send_result is not None:
      print(send_result)
    else:
      pass
  except Exception as e:
    print(e)
else:
  pass
#+END_SRC

An expanded version of this script with additional functions for
specifying an alternative homedir location is in the examples
directory as =send-key-to-keyserver.py=.

The =hkp4py= module appears to
 handle both string and byte literal text
data equally well, but the GPGME bindings deal primarily with byte
literal data only and so this script sends in that format first, then
```

tries the string literal form.

* Basic Functions
 :PROPERTIES:
 :CUSTOM_ID: howto-the-basics
 :END:

The most frequently called features of any cryptographic library will be the most fundamental tasks for encryption software. In this section we will look at how to programmatically encrypt data, decrypt it, sign it and verify signatures.

** Encryption
  :PROPERTIES:
  :CUSTOM_ID: howto-basic-encryption
  :END:

Encrypting is very straight forward. In the first example below the message, =text=, is encrypted to a single recipient's key. In the second example the message will be encrypted to multiple recipients.

*** Encrypting to one key
   :PROPERTIES:
   :CUSTOM_ID: howto-basic-encryption-single
   :END:

Once the the Context is set the main issues with encrypting data is essentially reduced
 to key selection and the keyword arguments
specified in the =gpg.Context().encrypt()= method.

Those keyword arguments are: =recipients=, a list of keys encrypted to (covered in greater detail in the following section); =sign=, whether or not to sign the plaintext data, see subsequent sections on signing and verifying signatures below (defaults to =True=); =sink=, to write results or partial results to a secure sink instead of returning it (defaults to =None=); =passphrase=, only used when utilising symmetric encryption (defaults to =None=); =always_trust=, used to override the trust model settings for recipient keys (defaults to =False=); =add_encrypt_to=, utilises any preconfigured =encrypt-to= or =default-key= settings in the user's =gpg.conf= file (defaults to =False=); =prepare=, prepare for encryption (defaults to =False=); =expect_sign=, prepare for signing (defaults to =False=); =compress=, compresses the plaintext prior to encryption (defaults to =True=).

```
#+BEGIN_SRC python -i
import
 gpg

a_key = "0x12345678DEADBEEF"
text = b"""Some text to test with.

Since the text in this case must be bytes, it is most likely that
the input form will be a separate file which is opened with "rb"
as this is the simplest method of obtaining the correct data format.
"""

c = gpg.Context(armor=True)
rkey = list(c.keylist(pattern=a_key, secret=False))
ciphertext, result, sign_result = c.encrypt(text, recipients=rkey, sign=False)

with open("secret_plans.txt.asc", "wb") as afile:
  afile.write(ciphertext)
#+END_SRC
```

Though this is even more likely to be used like this; with the plaintext input read from a file, the recipient keys used for encryption regardless of key trust status and the encrypted output also encrypted to any preconfigured keys set in the =gpg.conf= file:

```
#+BEGIN_SRC python -i
import gpg

a_key = "0x12345678DEADBEEF"

with open("secret_plans.txt", "rb") as afile:
  text = afile.read()

c = gpg.Context(armor=True)
rkey = list(c.keylist(pattern=a_key, secret=False))
ciphertext,
 result, sign_result = c.encrypt(text, recipients=rkey, sign=True,
                                 always_trust=True,
                                 add_encrypt_to=True)

with open("secret_plans.txt.asc", "wb") as afile:
  afile.write(ciphertext)
#+END_SRC
```

If the =recipients= parameter is empty then the plaintext is encrypted symmetrically. If no =passphrase= is supplied as a parameter or via a callback registered with the =Context()= then an out-of-band prompt for the passphrase via pinentry will be invoked.

*** Encrypting to multiple keys
  :PROPERTIES:
  :CUSTOM_ID: howto-basic-encryption-multiple
  :END:

Encrypting to multiple keys essentially just expands upon the key
selection process and the recipients from the previous examples.

The following example encrypts a message (=text=) to everyone with an
email address on the =gnupg.org= domain,[fn:4] but does /not/ encrypt
to a default key or other key which is configured to
 normally encrypt
to.

#+BEGIN_SRC python -i
import gpg

text = b"""Oh look, another test message.

The same rules apply as with the previous example and more likely
than not, the message will actually be drawn from reading the
contents of a file or, maybe, from entering data at an input()
prompt.

Since the text in this case must be bytes, it is most likely that
the input form will be a separate file which is opened with "rb"
as this is the simplest method of obtaining the correct data
format.
"""

c = gpg.Context(armor=True)
rpattern = list(c.keylist(pattern="@gnupg.org", secret=False))
logrus = []

for i in range(len(rpattern)):
  if rpattern[i].can_encrypt == 1:
    logrus.append(rpattern[i])

ciphertext, result, sign_result = c.encrypt(text, recipients=logrus,
                                  sign=False, always_trust=True)

with open("secret_plans.txt.asc", "wb") as afile:
  afile.write(ciphertext)
#+END_SRC

All it would take to change the above example to sign

the message
and also encrypt the message to any configured default keys would
be to change the =c.encrypt= line to this:

```
#+BEGIN_SRC python -i
ciphertext, result, sign_result = c.encrypt(text, recipients=logrus,
                                  always_trust=True,
                                  add_encrypt_to=True)
#+END_SRC
```

The only keyword arguments requiring modification are those for which
the default values are changing. The default value of =sign= is
=True=, the default of =always_trust= is =False=, the default of
=add_encrypt_to= is =False=.

If =always_trust= is not set to =True= and any of the recipient keys
are not trusted (e.g. not signed or locally signed) then the
encryption will raise an error. It is possible to mitigate this
somewhat with something more like this:

```
#+BEGIN_SRC python -i
import gpg

with open("secret_plans.txt.asc", "rb") as afile:
  text = afile.read()

c = gpg.Context(armor=True)
rpattern = list(c.keylist(pattern="@gnupg.org",
 secret=False))
logrus = []

for i in range(len(rpattern)):
  if rpattern[i].can_encrypt == 1:
    logrus.append(rpattern[i])

  try:
    ciphertext, result, sign_result = c.encrypt(text, recipients=logrus,
                                      add_encrypt_to=True)
  except gpg.errors.InvalidRecipients as e:
    for i in range(len(e.recipients)):
      for n in range(len(logrus)):
        if logrus[n].fpr == e.recipients[i].fpr:
          logrus.remove(logrus[n])
        else:
          pass
    try:
      ciphertext, result, sign_result = c.encrypt(text,
                                        recipients=logrus,
```

```
                                        add_encrypt_to=True)
        with open("secret_plans.txt.asc", "wb") as afile:
            afile.write(ciphertext)
    except:
        pass
#+END_SRC
```

This will attempt to encrypt to all the keys searched
 for, then remove
invalid recipients if it fails and try again.

** Decryption
 :PROPERTIES:
 :CUSTOM_ID: howto-basic-decryption
 :END:

Decrypting something encrypted to a key in one's secret keyring is
fairly straight forward.

In this example code, however, preconfiguring either =gpg.Context()=
or =gpg.core.Context()= as =c= is unnecessary because there is no need
to modify the Context prior to conducting the decryption and since the
Context is only used once, setting it to =c= simply adds lines for no
gain.

```
#+BEGIN_SRC python -i
import gpg

ciphertext = input("Enter path and filename of encrypted file: ")
newfile = input("Enter path and filename of file to save decrypted data to: ")

with open(ciphertext, "rb") as cfile:
  try:
    plaintext, result, verify_result = gpg.Context().decrypt(cfile)
  except gpg.errors.GPGMEError as e:
    plaintext = None
    print(e)

if plaintext is not None:
  with open(newfile, "wb") as nfile:
   nfile.write(plaintext)

  else:
    pass
#+END_SRC
```

The data available in =plaintext= in this example is the decrypted

content as a byte object, the recipient key IDs and algorithms in
=result= and the results of verifying any signatures of the data in
=verify_result=.

If =gpg.Context().decrypt(cfile, verify=False)= is called instead,
then =verify_result= will be returned as =None= and the rest remains
as described here.

** Signing text and files
 :PROPERTIES:
 :CUSTOM_ID: howto-basic-signing
 :END:

The following sections demonstrate how to specify keys to sign with.

*** Signing key selection
  :PROPERTIES:
  :CUSTOM_ID: howto-basic-signing-signers
  :END:

By default GPGME and the Python bindings will use the default key
configured for the user invoking the GPGME API. If there is no
default key specified and there is more than one secret key available
it may be necessary to specify the key or keys with which to sign
messages and files.

#+BEGIN_SRC python -i
import gpg

logrus = input("Enter
 the email address or string to match signing keys to: ")
hancock = gpg.Context().keylist(pattern=logrus, secret=True)
sig_src = list(hancock)
#+END_SRC

The signing examples in the following sections include the explicitly
designated =signers= parameter in two of the five examples; once where
the resulting signature would be ASCII armoured and once where it
would not be armoured.

While it would be possible to enter a key ID or fingerprint here to
match a specific key, it is not possible to enter two fingerprints and
match two keys since the patten expects a string, bytes or None and
not a list. A string with two fingerprints won't match any single
key.

*** Normal or default signing messages or files
  :PROPERTIES:
  :CUSTOM_ID: howto-basic-signing-normal
  :END:

The normal or default signing process is essentially the same as is most often invoked when also encrypting a message or file. So when the encryption component is not utilised, the result is to produce an encoded
 and signed output which may or may not be ASCII armoured and which may or may not also be compressed.

By default compression will be used unless GnuPG detects that the plaintext is already compressed. ASCII armouring will be determined according to the value of =gpg.Context().armor=.

The compression algorithm is selected in much the same way as the symmetric encryption algorithm or the hash digest algorithm is when multiple keys are involved; from the preferences saved into the key itself or by comparison with the preferences with all other keys involved.

```
#+BEGIN_SRC python -i
import gpg

text0 = """Declaration of ... something.

"""
text = text0.encode()

c = gpg.Context(armor=True, signers=sig_src)
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.NORMAL)

with open("/path/to/statement.txt.asc", "w") as afile:
  afile.write(signed_data.decode())
#+END_SRC
```

Though everything in this example is accurate, it is more likely that reading the input data from another
 file and writing the result to a
new file will be performed more like the way it is done in the next example. Even if the output format is ASCII armoured.

```
#+BEGIN_SRC python -i
import gpg

with open("/path/to/statement.txt", "rb") as tfile:
```

```
  text = tfile.read()

c = gpg.Context()
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.NORMAL)

with open("/path/to/statement.txt.sig", "wb") as afile:
  afile.write(signed_data)
#+END_SRC
```

*** Detached signing messages and files
  :PROPERTIES:
  :CUSTOM_ID: howto-basic-signing-detached
  :END:

Detached signatures will often be needed in programmatic uses of
GPGME, either for signing files (e.g. tarballs of code releases) or as
a component of message signing (e.g. PGP/MIME encoded email).

```
#+BEGIN_SRC python -i
import gpg

text0 = """Declaration of ... something.

"""
text = text0.encode()

c = gpg.Context(armor=True)
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.DETACH)

with open("/path/to/statement.txt.asc",
 "w") as afile:
  afile.write(signed_data.decode())
#+END_SRC
```

As with normal signatures, detached signatures are best handled as
byte literals, even when the output is ASCII armoured.

```
#+BEGIN_SRC python -i
import gpg

with open("/path/to/statement.txt", "rb") as tfile:
  text = tfile.read()

c = gpg.Context(signers=sig_src)
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.DETACH)

with open("/path/to/statement.txt.sig", "wb") as afile:
```

```
  afile.write(signed_data)
#+END_SRC


*** Clearsigning messages or text
  :PROPERTIES:
  :CUSTOM_ID: howto-basic-signing-clear
  :END:

Though PGP/in-line messages are no longer encouraged in favour of
PGP/MIME, there is still sometimes value in utilising in-line
signatures.  This is where clear-signed messages or text is of value.

#+BEGIN_SRC python -i
import gpg

text0 = """Declaration of ... something.

"""
text = text0.encode()

c = gpg.Context()
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.CLEAR)

with
 open("/path/to/statement.txt.asc", "w") as afile:
  afile.write(signed_data.decode())
#+END_SRC

In spite of the appearance of a clear-signed message, the data handled
by GPGME in signing it must still be byte literals.

#+BEGIN_SRC python -i
import gpg

with open("/path/to/statement.txt", "rb") as tfile:
  text = tfile.read()

c = gpg.Context()
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.CLEAR)

with open("/path/to/statement.txt.asc", "wb") as afile:
  afile.write(signed_data)
#+END_SRC


** Signature verification
 :PROPERTIES:
```

:CUSTOM_ID: howto-basic-verification
:END:

Essentially there are two principal methods of verification of a signature. The first of these is for use with the normal or default signing method and for clear-signed messages. The second is for use with files and data with detached signatures.

The following example is intended for use with the default signing method where the file was not ASCII armoured:

```
#+BEGIN_SRC python
 -i
import gpg
import time

filename = "statement.txt"
gpg_file = "statement.txt.gpg"

c = gpg.Context()

try:
  data, result = c.verify(open(gpg_file))
  verified = True
except gpg.errors.BadSignatures as e:
  verified = False
  print(e)

if verified is True:
  for i in range(len(result.signatures)):
     sign = result.signatures[i]
     print("""Good signature from:
{0}
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
        time.ctime(sign.timestamp)))
else:
  pass
#+END_SRC
```

Whereas this next example, which is almost identical would work with normal ASCII armoured files and with clear-signed files:

```
#+BEGIN_SRC python -i
import gpg
import time
```

```
filename = "statement.txt"
asc_file = "statement.txt.asc"

c = gpg.Context()

try:
  data, result = c.verify(open(asc_file))
  verified = True
except gpg.errors.BadSignatures as e:
  verified = False
  print(e)

if verified is True:
  for i in range(len(result.signatures)):
      sign = result.signatures[i]
     print("""Good signature from:
{0}
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
       time.ctime(sign.timestamp)))
else:
  pass
#+END_SRC
```

In both of the previous examples it is also possible to compare the original data that was signed against the signed data in =data= to see if it matches with something like this:

```
#+BEGIN_SRC python -i
with open(filename, "rb") as afile:
  text = afile.read()

if text == data:
  print("Good signature.")
else:
  pass
#+END_SRC
```

The following two examples, however, deal with detached signatures. With his method of verification the data that was signed does not get returned since it is already being explicitly referenced in the first argument of =c.verify=. So =data= is =None= and only the information in =result= is available.

```
#+BEGIN_SRC python -i
import gpg
import time
```

```
filename = "statement.txt"
sig_file = "statement.txt.sig"

c = gpg.Context()

try:
   data,
 result = c.verify(open(filename), open(sig_file))
   verified = True
except gpg.errors.BadSignatures as e:
   verified = False
   print(e)

if verified is True:
   for i in range(len(result.signatures)):
      sign = result.signatures[i]
      print("""Good signature from:
{0}
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
         time.ctime(sign.timestamp)))
else:
   pass
#+END_SRC

#+BEGIN_SRC python -i
import gpg
import time

filename = "statement.txt"
asc_file = "statement.txt.asc"

c = gpg.Context()

try:
   data, result = c.verify(open(filename), open(asc_file))
   verified = True
except gpg.errors.BadSignatures as e:
   verified = False
   print(e)

if verified is True:
   for i in range(len(result.signatures)):
      sign = result.signatures[i]
      print("""Good signature from:
{0}
```

```
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
        time.ctime(sign.timestamp)))
else:
  pass
#+END_SRC
```

*
Creating keys and subkeys
:PROPERTIES:
:CUSTOM_ID: key-generation
:END:

The one thing, aside from GnuPG itself, that GPGME depends on, of course, is the keys themselves. So it is necessary to be able to generate them and modify them by adding subkeys, revoking or disabling them, sometimes deleting them and doing the same for user IDs.

In the following examples a key will be created for the world's greatest secret agent, Danger Mouse. Since Danger Mouse is a secret agent he needs to be able to protect information to =SECRET= level clearance, so his keys will be 3072-bit keys.

The pre-configured =gpg.conf= file which sets cipher, digest and other preferences contains the following configuration parameters:

```
#+BEGIN_SRC conf
expert
allow-freeform-uid
allow-secret-key-import
trust-model tofu+pgp
tofu-default-policy unknown
enable-large-rsa
enable-dsa2
cert-digest-algo SHA512
default-preference-list TWOFISH CAMELLIA256 AES256 CAMELLIA192 AES192 CAMELLIA128
AES BLOWFISH IDEA CAST5 3DES SHA512 SHA384 SHA256 SHA224 RIPEMD160 SHA1 ZLIB BZIP2 ZIP
Uncompressed
personal-cipher-preferences TWOFISH CAMELLIA256 AES256 CAMELLIA192 AES192 CAMELLIA128 AES
BLOWFISH IDEA CAST5 3DES
personal-digest-preferences SHA512 SHA384 SHA256 SHA224 RIPEMD160 SHA1
personal-compress-preferences ZLIB BZIP2 ZIP Uncompressed
#+END_SRC
```

** Primary key

:PROPERTIES:
:CUSTOM_ID: keygen-primary
:END:

Generating a primary key uses the =create_key= method in a Context.
It contains multiple arguments and keyword arguments, including:
=userid=, =algorithm=, =expires_in=, =expires=, =sign=, =encrypt=,
=certify=, =authenticate=, =passphrase= and =force=. The defaults for
all of those except =userid=, =algorithm=, =expires_in=, =expires= and
=passphrase= is =False=. The defaults for =algorithm= and
=passphrase= is =None=. The default for =expires_in= is =0=. The
default for =expires= is =True=. There is no default for =userid=.

If =passphrase= is left as =None=
then the key will not be generated
with a passphrase, if =passphrase= is set to a string then that will
be the passphrase and if =passphrase= is set to =True= then gpg-agent
will launch pinentry to prompt for a passphrase. For the sake of
convenience, these examples will keep =passphrase= set to =None=.

#+BEGIN_SRC python -i
import gpg

c = gpg.Context()

c.home_dir = "~/.gnupg-dm"
userid = "Danger Mouse <dm@secret.example.net>"

dmkey = c.create_key(userid, algorithm="rsa3072", expires_in=31536000,
sign=True, certify=True)
#+END_SRC

One thing to note here is the use of setting the =c.home_dir=
parameter. This enables generating the key or keys in a different
location. In this case to keep the new key data created for this
example in a separate location rather than adding it to existing and
active key store data. As with the default directory, =~/.gnupg=, any
temporary or separate directory needs the permissions set to only
permit access by the directory
owner. On posix systems this means
setting the directory permissions to 700.

The =temp-homedir-config.py= script in the HOWTO examples directory
will create an alternative homedir with these configuration options
already set and the correct directory and file permissions.

The successful generation of the key can be confirmed via the returned
=GenkeyResult= object, which includes the following data:

```
#+BEGIN_SRC python -i
print("""
Fingerprint: {0}
Primary Key: {1}
 Public Key: {2}
 Secret Key: {3}
Sub Key: {4}
User IDs: {5}
""".format(dmkey.fpr, dmkey.primary, dmkey.pubkey, dmkey.seckey, dmkey.sub,
        dmkey.uid))
#+END_SRC
```

Alternatively the information can be confirmed using the command line program:

```
#+BEGIN_SRC shell
 bash-4.4$ gpg --homedir ~/.gnupg-dm -K
 ~/.gnupg-dm/pubring.kbx
 ----------------------
 sec   rsa3072 2018-03-15 [SC] [expires: 2019-03-15]
 177B7C25DB99745EE2EE13ED026D2F19E99E63AA
 uid           [ultimate] Danger Mouse <dm@secret.example.net>

  bash-4.4$
#+END_SRC
```

As with generating keys manually, to preconfigure expanded preferences for the cipher, digest and compression algorithms, the =gpg.conf= file must contain those details in the home directory in which the new key is being generated. I used a cut down version of my own =gpg.conf= file in order to be able to generate this:

```
#+BEGIN_SRC shell
 bash-4.4$ gpg --homedir ~/.gnupg-dm --edit-key 177B7C25DB99745EE2EE13ED026D2F19E99E63AA showpref
quit
 Secret key is available.

 sec  rsa3072/026D2F19E99E63AA
     created: 2018-03-15  expires: 2019-03-15  usage: SC
     trust: ultimate      validity: ultimate
 [ultimate] (1). Danger Mouse <dm@secret.example.net>

 [ultimate] (1). Danger Mouse <dm@secret.example.net>
     Cipher: TWOFISH, CAMELLIA256, AES256, CAMELLIA192, AES192, CAMELLIA128, AES, BLOWFISH,
IDEA, CAST5, 3DES
     Digest: SHA512, SHA384, SHA256, SHA224, RIPEMD160, SHA1
     Compression: ZLIB, BZIP2, ZIP, Uncompressed
```

```
     Features: MDC, Keyserver
 no-modify

 bash-4.4$
#+END_SRC
```

** Subkeys
  :PROPERTIES:
  :CUSTOM_ID: keygen-subkeys
  :END:

Adding subkeys to a primary key is fairly similar to creating the primary key with the =create_subkey= method. Most of the arguments are the same, but not quite all. Instead of the =userid= argument there is now a =key= argument for selecting which primary key to add the subkey to.

In the following example an encryption subkey will be added to the primary key. Since Danger Mouse is a security conscious secret agent, this subkey will only be valid for about six months, half the length of the primary key.

```
#+BEGIN_SRC python -i
import gpg

c = gpg.Context()
c.home_dir = "~/.gnupg-dm"

key = c.get_key(dmkey.fpr, secret=True)
dmsub = c.create_subkey(key, algorithm="rsa3072", expires_in=15768000,
                        encrypt=True)
#+END_SRC
```

As with the primary key, the results here can be checked with:

```
#+BEGIN_SRC python -i
print("""
Fingerprint: {0}
Primary Key: {1}
  Public Key: {2}
 Secret Key: {3}
Sub Key: {4}
User IDs: {5}
""".format(dmsub.fpr, dmsub.primary, dmsub.pubkey, dmsub.seckey, dmsub.sub,
           dmsub.uid))
#+END_SRC
```

As well as on the command line with:

```
#+BEGIN_SRC shell
 bash-4.4$ gpg --homedir ~/.gnupg-dm -K
 ~/.gnupg-dm/pubring.kbx
 ----------------------
 sec   rsa3072 2018-03-15 [SC] [expires: 2019-03-15]
 177B7C25DB99745EE2EE13ED026D2F19E99E63AA
 uid           [ultimate] Danger Mouse <dm@secret.example.net>
 ssb   rsa3072 2018-03-15 [E] [expires: 2018-09-13]

 bash-4.4$
#+END_SRC


** User IDs
  :PROPERTIES:
  :CUSTOM_ID: keygen-uids
  :END:


*** Adding User IDs
   :PROPERTIES:
   :CUSTOM_ID: keygen-uids-add
   :END:
```

By comparison to creating primary keys and subkeys, adding a new user ID to an existing key is much simpler. The method used to do this is =key_add_uid= and the only arguments it takes are for the =key= and the new =uid=.

```
#+BEGIN_SRC python -i
import gpg

c = gpg.Context()
c.home_dir = "~/.gnupg-dm"

dmfpr
 = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
key = c.get_key(dmfpr, secret=True)
uid = "Danger Mouse <danger.mouse@secret.example.net>"

c.key_add_uid(key, uid)
#+END_SRC
```

Unsurprisingly the result of this is:

```
#+BEGIN_SRC shell
```

```
bash-4.4$ gpg --homedir ~/.gnupg-dm -K
~/.gnupg-dm/pubring.kbx
---------------------
sec   rsa3072 2018-03-15 [SC] [expires: 2019-03-15]
177B7C25DB99745EE2EE13ED026D2F19E99E63AA
uid           [ultimate] Danger Mouse <danger.mouse@secret.example.net>
uid           [ultimate] Danger Mouse <dm@secret.example.net>
ssb   rsa3072 2018-03-15 [E] [expires: 2018-09-13]

bash-4.4$
#+END_SRC
```

```
*** Revoking User IDs
  :PROPERTIES:
  :CUSTOM_ID: keygen-uids-revoke
  :END:

Revoking a user ID is a fairly similar process, except that it uses
the =key_revoke_uid= method.

#+BEGIN_SRC python -i
import gpg

c = gpg.Context()
c.home_dir = "~/.gnupg-dm"

dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
key = c.get_key(dmfpr, secret=True)
uid
 = "Danger Mouse <danger.mouse@secret.example.net>"

c.key_revoke_uid(key, uid)
#+END_SRC


** Key certification
  :PROPERTIES:
  :CUSTOM_ID: key-sign
  :END:

Since key certification is more frequently referred to as key signing,
the method used to perform this function is =key_sign=.

The =key_sign= method takes four arguments: =key=, =uids=,
=expires_in= and =local=.  The default value of =uids= is =None= and
which results in all user IDs being selected.  The default value of
both =expires_in= and =local= is =False=; which results in the
```

signature never expiring and being able to be exported.

The =key= is the key being signed rather than the key doing the signing. To change the key doing the signing refer to the signing key selection above for signing messages and files.

If the =uids= value is not =None= then it must either be a string to match a single user ID or a list of strings to match multiple user IDs. In this case the matching of those strings must be precise and it
is case sensitive.

To sign Danger Mouse's key for just the initial user ID with a signature which will last a little over a month, do this:

```
#+BEGIN_SRC python -i
import gpg

c = gpg.Context()
uid = "Danger Mouse <dm@secret.example.net>"

dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
key = c.get_key(dmfpr, secret=True)
c.key_sign(key, uids=uid, expires_in=2764800)
#+END_SRC
```

*** Verifying key certifications

```
  :PROPERTIES:
  :CUSTOM_ID: key-sign-verify
  :END:

#+BEGIN_SRC python -i
import gpg
import time

c = gpg.Context()
dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
keys = list(c.keylist(pattern=dmuid, mode=gpg.constants.keylist.mode.SIGS))
key = keys[0]

for user in key.uids:
  for sig in user.signatures:
    print("0x{0}".format(sig.keyid), "", time.ctime(sig.timestamp), "",
          sig.uid)
#+END_SRC
```

Which for Danger Mouse displays the following:

#+BEGIN_EXAMPLE
 0x92E3F6115435C65A Thu Mar 15 13:17:44 2018 Danger Mouse <dm@secret.example.net>
  0x321E4E2373590E5D Mon Nov 26 12:46:05 2018 Ben McGinnes <ben@adversary.org>
#+END_EXAMPLE

The two key signatures listed are for the self-certification of Danger
Mouse's key made when the key was created in March, 2018; and the
second is a signature made by the author and set to expire at the end
of the year. Note that the second signature was made with the
following code (including the preceding code to display the output of
the certifications or key signatures):

```
#+BEGIN_SRC python -i
import gpg
import math
import pendulum
import time

hd = "/home/dm/.gnupg"
c = gpg.Context()
d = gpg.Context(home_dir=hd)
dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
dmuid = "Danger Mouse <dm@secret.example.net>"
dkeys = list(c.keylist(pattern=dmuid))
dmkey = dkeys[0]

c.key_import(d.key_export(pattern=None))

tp = pendulum.period(pendulum.now(tz="local"), pendulum.datetime(2019, 1, 1))
ts = tp.total_seconds()
total_secs = math.ceil(ts)
c.key_sign(dmkey, uids=dmuid, expires_in=total_secs)

d.key_import(c.key_export(pattern=dmuid))
keys
 = list(c.keylist(pattern=dmuid, mode=gpg.constants.keylist.mode.SIGS))
key = keys[0]

for user in key.uids:
  for sig in user.signatures:
    print("0x{0}".format(sig.keyid), "", time.ctime(sig.timestamp), "",
        sig.uid)
#+END_SRC
```

Note that this final code block includes the use of a module which is
/not/ part of Python's standard library, the [[https://pendulum.eustace.io/][pendulum module]]. Unlike
the standard datetime module, pendulum makes working with dates and

times significantly easier in Python; just as the requests module
makes working with HTTP and HTTPS easier than the builtin modules do.

Though neither requests nor pendulum are required modules for using
the GPGME Python bindings, they are both highly recommended more
generally.

* Advanced or Experimental Use Cases
 :PROPERTIES:
 :CUSTOM_ID: advanced-use
 :END:

** C plus Python plus SWIG plus Cython
  :PROPERTIES:
  :CUSTOM_ID: cython
  :END:

In
 spite of the apparent incongruence of using Python bindings to a C
interface only to generate more C from the Python; it is in fact quite
possible to use the GPGME bindings with [[http://docs.cython.org/en/latest/index.html][Cython]]. Though in many cases
the benefits may not be obvious since the most computationally
intensive work never leaves the level of the C code with which GPGME
itself is interacting with.

Nevertheless, there are some situations where the benefits are
demonstrable. One of the better and easier examples being the one of
the early examples in this HOWTO, the [[#howto-keys-counting][key counting]] code. Running that
example as an executable Python script, =keycount.py= (available in
the =examples/howto/= directory), will take a noticeable amount of time
to run on most systems where the public keybox or keyring contains a
few thousand public keys.

Earlier in the evening, prior to starting this section, I ran that
script on my laptop; as I tend to do periodically
 and timed it using
=time= utility, with the following results:

#+BEGIN_SRC shell
 bash-4.4$ time keycount.py

 Number of secret keys: 23
 Number of public keys: 12112

```
 real 11m52.945s
 user 0m0.913s
 sys 0m0.752s

 bash-4.4$
#+END_SRC
```

Sometime after that I imported another key and followed it with a
little test of Cython. This test was kept fairly basic, essentially
lifting the material from the [[http://docs.cython.org/en/latest/src/tutorial/cython_tutorial.html][Cython Basic Tutorial]] to demonstrate
compiling Python code to C. The first step was to take the example
key counting code quoted previously, essentially from the importing of
the =gpg= module to the end of the script:

```
#+BEGIN_SRC python -i
import gpg

c = gpg.Context()
seckeys = c.keylist(pattern=None, secret=True)
pubkeys = c.keylist(pattern=None, secret=False)

seclist = list(seckeys)
secnum = len(seclist)

publist = list(pubkeys)
pubnum = len(publist)

print("""
   Number of secret keys:  {0}
   Number
 of public keys:  {1}

""".format(secnum, pubnum))
#+END_SRC
```

Save that into a file called =keycount.pyx= and then create a
=setup.py= file which contains this:

```
#+BEGIN_SRC python -i
from distutils.core import setup
from Cython.Build import cythonize

setup(
   ext_modules = cythonize("keycount.pyx")
)
#+END_SRC
```

Compile it:

#+BEGIN_SRC shell
 bash-4.4$ python setup.py build_ext --inplace
 bash-4.4$
#+END_SRC

Then run it in a similar manner to =keycount.py=:

#+BEGIN_SRC shell
 bash-4.4$ time python3.7 -c "import keycount"

 Number of secret keys: 23
 Number of public keys: 12113

 real 6m47.905s
 user 0m0.785s
 sys 0m0.331s

 bash-4.4$
#+END_SRC

Cython turned =keycount.pyx= into an 81KB =keycount.o= file in the
=build/= directory, a 24KB =keycount.cpython-37m-darwin.so= file to be
imported into Python 3.7 and a 113KB =keycount.c= generated C source
code file of nearly three thousand lines. Quite a bit bigger than the
314 bytes of the =keycount.pyx= file or the full
 1,452 bytes of the
full executable =keycount.py= example script.

On the other hand it ran in nearly half the time; taking 6 minutes and
47.905 seconds to run. As opposed to the 11 minutes and 52.945 seconds
which the CPython script alone took.

The =keycount.pyx= and =setup.py= files used to generate this example
have been added to the =examples/howto/advanced/cython/= directory
The example versions include some additional options to annotate the
existing code and to detect Cython's use. The latter comes from the
[[http://docs.cython.org/en/latest/src/tutorial/pure.html#magic-attributes-within-the-pxd][Magic Attributes]] section
of the Cython documentation.

* Miscellaneous extras and work-arounds
 :PROPERTIES:
 :CUSTOM_ID: cheats-and-hacks
 :END:

Most of the things in the following sections are here simply because
there was no better place to put them, even though some are only
peripherally related to the GPGME Python bindings. Some are also
workarounds for functions not integrated
 with GPGME as yet. This is
especially true of the first of these, dealing with [[#group-lines][group lines]].

** Group lines
  :PROPERTIES:
  :CUSTOM_ID: group-lines
  :END:

There is not yet an easy way to access groups configured in the
gpg.conf file from within GPGME. As a consequence these central
groupings of keys cannot be shared amongst multiple programs, such as
MUAs readily.

The following code, however, provides a work-around for obtaining this
information in Python.

```
#+BEGIN_SRC python -i
import subprocess
import sys

if sys.platform == "win32":
   gpgconfcmd = "gpgconf.exe --list-options gpg"
else:
   gpgconfcmd = "gpgconf --list-options gpg"

process = subprocess.Popen(gpgconfcmd.split(), stdout=subprocess.PIPE)
procom = process.communicate()

if sys.version_info[0] == 2:
   lines = procom[0].splitlines()
else:
   lines = procom[0].decode().splitlines()

for line in lines:
   if line.startswith("group") is True:
      break

groups = line.split(":")[-1].replace("",
 ").split(',')

group_lines = []
group_lists = []
```

```
for group in groups:
  group_lines.append(group.split("="))
  group_lists.append(group.split("="))

for glist in group_lists:
  glist[1] = glist[1].split()
#+END_SRC
```

The result of that code is that =group_lines= is a list of lists where =group_lines[i][0]= is the name of the group and =group_lines[i][1]= is the key IDs of the group as a string.

The =group_lists= result is very similar in that it is a list of lists. The first part, =group_lists[i][0]= matches =group_lines[i][0]= as the name of the group, but =group_lists[i][1]= is the key IDs of the group as a list.

A demonstration of using the =groups.py= module is also available in the form of the executable =mutt-groups.py= script. This second script reads all the group entries in a user's =gpg.conf= file and converts them into crypt-hooks suitable for use with the Mutt and Neomutt mail clients.

** Keyserver access for Python
:PROPERTIES:
:CUSTOM_ID:
hkp4py
:END:

The [[https://github.com/Selfnet/hkp4py][hkp4py]] module by Marcel Fest was originally a port of the old [[https://github.com/dgladkov/python-hkp][python-hkp]] module from Python 2 to Python 3 and updated to use the [[http://docs.python-requests.org/en/latest/index.html][requests]] module instead. It has since been modified to provide
support for Python 2.7 as well and is available via PyPI.

Since it rewrites the =hkp= protocol prefix as =http= and =hkps= as =https=, the module is able to be used even with servers which do not support the full scope of keyserver functions.[fn:5] It also works quite readily when incorporated into a [[#cython][Cython]] generated and compiled version of any code.

*** Key import format
:PROPERTIES:
:CUSTOM_ID: hkp4py-strings
:END:

The hkp4py module returns key data via requests as string literals
(=r.text=) instead of byte literals (=r.content=). This means that
the retrurned key data must be encoded to UTF-8 when importing
 that
key material using a =gpg.Context().key_import()= method.

For this reason an alternative method has been added to the =search=
function of =hkp4py.KeyServer()= which returns the key in the correct
format as expected by =key_import=. When importing using this module,
it is now possible to import with this:

#+BEGIN_SRC python -i
for key in keys:
  if key.revoked is False:
     gpg.Context().key_import(key.key_blob)
  else:
     pass
#+END_SRC

Without that recent addition it would have been necessary to encode
the contents of each =hkp4py.KeyServer().search()[i].key= in
=hkp4py.KeyServer().search()= before trying to import it.

An example of this is included in the [[#howto-import-key][Importing Keys]] section of this
HOWTO and the corresponding executable version of that example is
available in the =lang/python/examples/howto= directory as normal; the
executable version is the =import-keys-hkp.py= file.

** GPGME version checking
 :PROPERTIES:
 :CUSTOM_ID: gpgme-version-check
  :END:

For various reasons it may be necessary to check which version of
GPGME the bindings have been built against; including whether a
minimum required version of GPGME is in use.

For the most part the =gpg.version.versionstr= and
=gpg.version.versionlist= methods have been quite sufficient. The
former returns the same string as =gpgme-config --version=, while the
latter returns the major, minor and patch values in a list.

To check if the installed bindings have actually been built against
the current installed libgpgme version, this check can be performed:

#+BEGIN_SRC python -i
import gpg

```
import subprocess
import sys

gpgme_version_call = subprocess.Popen(["gpgme-config", "--version"],
                                      stdout=subprocess.PIPE,
                                      stderr=subprocess.PIPE)
gpgme_version_str = gpgme_version_call.communicate()

if sys.version_info[0] == 2:
  gpgme_version = gpgme_version_str[0].strip()
elif sys.version_info[0]
 >= 3:
  gpgme_version = gpgme_version_str[0].decode().strip()
else:
  gpgme_version = None

if gpgme_version is not None:
  if gpgme_version == gpg.version.versionstr:
     print("The GPGME Python bindings match libgpgme.")
  else:
     print("The GPGME Python bindings do NOT match libgpgme.")
else:
  print("Upgrade Python and reinstall the GPGME Python bindings.")
#+END_SRC
```

For many developers, however, the preferred checking means checking for a minimum version or point release. This is now readily available via the =gpg.version.versionintlist= method (added in version =1.12.1-beta79=). It is also now possible to easily check whether the installed GPGME Python bindings were built from a development or beta branch of the GPGME source code.

The following code demonstrates how both of those methods may be used:

```
#+BEGIN_SRC python -i
import gpg

try:
  if gpg.version.is_beta is True:
     print("The installed GPGME Python bindings were built from beta code.")
   else:
     print("The installed GPGME Python bindings are a released version.")
except Exception as e:
  print(e)

try:
  if gpg.version.versionintlist[0] == 1:
     if gpg.version.versionintlist[1] == 12:
```

```
        if gpg.version.versionintlist[2] == 1:
            print("This is the minimum version for using versionintlist.")
        elif gpg.version.versionintlist[2] > 1:
            print("The versionintlist method is available.")
        else:
            pass
    elif gpg.version.versionintlist[1] > 12:
        print("The versionintlist method is available.")
    else:
        pass
  elif gpg.version.versionintlist[0] > 1:
    print("The versionintlist method is available.")
  else:
    pass
except Exception as e:
  print(e)
#+END_SRC
```

The points where =pass= is used in the above example will most likely
also produce an =Exception= error since those results should only
occur in versions which do not have the =gpgme.version.is_beta=
 and
=gpgme.version.versionintlist= methods available.

* Copyright and Licensing
 :PROPERTIES:
 :CUSTOM_ID: copyright-and-license
 :END:

** Copyright
  :PROPERTIES:
  :CUSTOM_ID: copyright
  :END:

Copyright The GnuPG Project, 2018.

** Draft Editions of this HOWTO
  :PROPERTIES:
  :CUSTOM_ID: draft-editions
  :END:

Draft editions of this HOWTO may be periodically available directly
from the author at any of the following URLs:

- [[https://files.au.adversary.org/crypto/gpgme-python-howto.html][GPGME Python Bindings HOWTO draft

(HTML single file, AWS S3 SSL)]]
- [[http://files.au.adversary.org/crypto/gpgme-python-howto.html][GPGME Python Bindings HOWTO draft (HTML single file, AWS S3 no SSL)]]
- [[https://files.au.adversary.org/crypto/gpgme-python-howto-split/index.html][GPGME Python Bindings HOWTO draft (HTML multiple files, AWS S3 SSL)]]
- [[http://files.au.adversary.org/crypto/gpgme-python-howto/index.html][GPGME Python Bindings HOWTO draft (HTML
multiple files, AWS S3 no SSL)]]

These draft versions have been generated from this document via GNU
Emacs [[https://orgmode.org/][Org mode]] to =.texi= and [[https://www.gnu.org/software/texinfo/][GNU Texinfo]] to HTML. Though it is
likely that the specific [[https://files.au.adversary.org/crypto/gpgme-python-howto][file]]
[[http://files.au.adversary.org/crypto/gpgme-python-howto.org][version]] used will be on the same server
with the generated output formats. Occasionally I may include the Org
mode generated XHTML versions:

- [[https://files.au.adversary.org/crypto/gpgme-python-howto.xhtml][GPGME Python Bindings HOWTO draft (HTML single file, AWS S3 SSL)]]
- [[http://files.au.adversary.org/crypto/gpgme-python-howto.xhtml][GPGME Python Bindings HOWTO draft (HTML single file, AWS S3 no SSL)]]

That XHTML version, however, is exported in a way which inherits a
colour scheme from [[https://github.com/holomorph/emacs-zenburn][the author's Emacs theme]] (which is a higher contrast
version
of [[http://kippura.org/zenburnpage/][Zenburn]] ported by [[https://github.com/holomorph][Holomorph]]). So it's fine for people who
prefer dark themed web pages, but not so great for everyone else.

The GNU Texinfo and reStructured Text versions ship with the software,
while the GNU Emacs Info version is generated from the Texinfo
version using GNU Texinfo or GNU Makeinfo. The Texinfo format is
generated from the original Org mode source file in Org mode itself
either within GNU Emacs or via the command line by invoking Emacs in
batch mode:

#+BEGIN_SRC shell
emacs gpgme-python-howto.org --batch -f org-texinfo-export-to-texinfo --kill
emacs gpgme-python-howto --batch -f org-texinfo-export-to-texinfo --kill
#+END_SRC

The reStructuredText format is also generated from the Org mode source
file, except it is generated using [[https://pandoc.org][Pandoc]] with either of the following
commands (depending on the filename):

#+BEGIN_SRC shell
pandoc -f org -t rst+smart -o gpgme-python-howto.rst

```
 gpgme-python-howto.org
 pandoc -f org -t rst+smart -o gpgme-python-howto.rst gpgme-python-howto
#+END_SRC
```

Note that the Org mode source files are identified as such via a mode
line at the top of each file and have had their =.org= file extensions
dropped in order to make scripted generation of output formats easier
and not require renaming files post-conversion.

Due to a bug in Org mode's texinfo conversion method, the recommended
steps for generating the Texinfo files for all the files in the
=lang/python/doc/src/= directory are as follows:

```
#+BEGIN_SRC shell
 for x in * ; do
    emacs $x --batch -f org-texinfo-export-to-texinfo --kill
    cat $x.texi | sed -e 's/@documentencoding UTF-8/@documentencoding utf-8/g' > ../texinfo/$x.texi
    pandoc -f org -t rst+smart -o ../rst/$x.rst $x
 done ;
 rm -fv *.texi
 cd ../texinfo
 mkdir info
 mkdir html
 for x in *.texi ; do
    makeinfo -v $x
    makeinfo --html --no-split $x
 done ;
 mv *.info info/
 mv
 *.html html/
#+END_SRC
```

This code snippet includes the generation of the reStructuredText
files and would be expected to be run from the =doc/src/= directory
containing the Org mode source files. It also assumes that the
commands are being run on POSIX compliant systems with basic tools
like sed, the Bourne shell and GNU Emacs[fn:6] available. The code
snippet also includes the steps for generating the Emacs Info files
and HTML files from the Texinfo files. Using reStructuredText files
with Sphinx is best left for the documentation of that project.

In addition to these there is a significantly less frequently updated
version as a HTML [[https://files.au.adversary.org/crypto/gpgme-python/dita/webhelp/index.html][WebHelp site]]
(AWS S3 SSL); generated from DITA XML
source files, which can be found in [[https://dev.gnupg.org/source/gpgme/browse/ben%252Fhowto-dita/][an
alternative branch]] of the GPGME
git repository.

Various generated output formats may occasionally be found in
subdirectories
 of the [[https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python][gpgme-python]] directory. In
particular within
the [[https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python/dita][DITA]],
[[https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python/rst][reStructuredText]] and
[[https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python/texinfo][Texinfo]] subdirectories. The
=rst=
directory contains output files generated with Sphinx and may include a
considerable number of its possible output formats, but there are no
guarantees as to how recent these are or even if they are present.

These draft editions are not official documents and the version of
documentation in the master branch or which ships with released
versions is the only official documentation. Nevertheless, these
draft editions may occasionally be of use by providing more accessible
web versions which are updated between releases. They are provided on
the understanding
 that they may contain errors or may contain content
subject to change prior to an official release.

** License GPL compatible
  :PROPERTIES:
  :CUSTOM_ID: license
  :END:

This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE.

* Footnotes

[fn:1] =short-history= and/or =short-history.html=.

[fn:2] With no issues reported specific to Python 3.7, the release of
Python 3.7.1 at around the same time as GPGME 1.12.0 and the testing
with Python 3.7.1rc1, there is no reason to delay moving 3.7 ahead of
3.6 now. Production environments with more conservative requirements
will always enforce their own policies anyway and installation to each
supported

minor release is quite possible too.

[fn:3] Yes, even if you use virtualenv with everything you do in Python. If you want to install this module as just your user account then you will need to manually configure, compile and install the /entire/ GnuPG stack as that user as well. This includes libraries which are not often installed that way. It can be done and there are circumstances under which it is worthwhile, but generally only on POSIX systems which utilise single user mode (some even require it).

[fn:4] You probably don't really want to do this. Searching the keyservers for "gnupg.org" produces over 400 results, the majority of which aren't actually at the gnupg.org domain, but just included a comment regarding the project in their key somewhere.

[fn:5] Such as with ProtonMail servers. This also means that restricted servers which only advertise either HTTP or HTTPS end points and not HKP or HKPS end points must still be identified as as HKP or HKPS within the Python
Code. The =hkp4py= module will rewrite
these appropriately when the connection is made to the server.

[fn:6] Okay, Emacs might not necessarily qualify as a basic tool, but it is common enough that having it installed on a system isn't too great an expectation, nor is it difficult to add to most POSIX systems, even if the users of those systems do not personally use it.
#include "qgpgme/verifydetachedjob.h"
#include "qgpgme/downloadjob.h"
```
{
  "op": "createkey",
  "userid": "foo@bar.baz",
  "algo": "rsa1024"
}
```
#include "qgpgme/multideletejob.h"
```
/*
  qgpgmekeylistjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
```

```
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as
 a special exception, the copyright holders give
  permission to link the code of this program with any edition of
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEKEYLISTJOB_H__
#define __QGPGME_QGPGMEKEYLISTJOB_H__

#include "keylistjob.h"

#include "threadedjobmixin.h"

#ifdef BUILDING_QGPGME
# include "keylistresult.h"
#else
#include <gpgme++/keylistresult.h>
#endif
#ifdef BUILDING_QGPGME
# include "key.h"
#else
#include <gpgme++/key.h>
#endif

namespace QGpgME
{

class QGpgMEKeyListJob
#ifdef Q_MOC_RUN
  : public
 KeyListJob
#else
  : public _detail::ThreadedJobMixin<KeyListJob, std::tuple<GpgME::KeyListResult, std::vector<GpgME::Key>,
```

```
QString, GpgME::Error> >
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
  explicit QGpgMEKeyListJob(GpgME::Context *context);
  ~QGpgMEKeyListJob();

  /* from KeyListJob */
  GpgME::Error start(const QStringList &patterns, bool secretOnly) Q_DECL_OVERRIDE;

  /* from KeyListJob */
  GpgME::KeyListResult exec(const QStringList &patterns, bool secretOnly, std::vector<GpgME::Key> &keys)
Q_DECL_OVERRIDE;

  void addMode(GpgME::KeyListMode mode) Q_DECL_OVERRIDE;

  /* from ThreadedJobMixin */
  void resultHook(const result_type &result) Q_DECL_OVERRIDE;
private:
  GpgME::KeyListResult mResult;
  bool mSecretOnly;
};

}

#endif // __QGPGME_QGPGMEKEYLISTJOB_H__
/*
  changeexpiryjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.
```

```
   You should have received a copy of the GNU General Public License
   along with this program; if not, write to the Free Software
   Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a special
 exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_CHANGEEXPIRYJOB_H__
#define __KLEO_CHANGEEXPIRYJOB_H__

#include "job.h"

#ifdef BUILDING_QGPGME
# include "key.h"
#else
# include <gpgme++/key.h>
#endif

#include <vector>

namespace GpgME
{
class Error;
}

class QDateTime;

namespace QGpgME
{

/**
  @short An abstract base class to change expiry asynchronously

  To use a ChangeExpiryJob, first obtain an instance from
 the
  CryptoBackend implementation, connect the progress() and result()
  signals to suitable slots and then start the job with a call
```

```
  to start(). This call might fail, in which case the ChangeExpiryJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the ChangeExpiryJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT ChangeExpiryJob : public Job
{
  Q_OBJECT
protected:
  explicit ChangeExpiryJob(QObject *parent);
public:
  ~ChangeExpiryJob();

  /**
    Starts the change-expiry operation. \a key is the key to change
    the expiry of. \a expiry is the new expiry time. If \a expiry
    is not valid, \a key is set to never expire.
  */
  virtual GpgME::Error start(const GpgME::Key &key, const QDateTime &expiry) = 0;

  /**
    Starts the change-expiry operation. \a key is the key to change,
    \a subkeys is a list of subkeys of the
 key, and \a expiry is the
    new expiry time. If \a subkeys is empty, then the expiry of \a key
    is changed. Otherwise, the expiry of \a subkeys is changed. If
    \a expiry is not valid, then \a key or \a subkeys are set to never expire.
  */
  virtual GpgME::Error start(const GpgME::Key &key, const QDateTime &expiry,
                             const std::vector<GpgME::Subkey> &subkeys);

Q_SIGNALS:
  void result(const GpgME::Error &result, const QString &auditLogAsHtml = QString(), const GpgME::Error
&auditLogError = GpgME::Error());
};

}

#endif // __KLEO_CHANGEEXPIRYJOB_H__
/* t-support.h - Helper routines for regression tests.
* Copyright (C) 2000 Werner Koch (dd9jn)
* Copyright (C) 2001, 2002, 2003, 2004 g10 Code GmbH
*
* This file is part of GPGME.
*
* GPGME is free software; you can redistribute it and/or modify it
```

```
* under the terms of the GNU Lesser General Public License as
* published by the Free Software Foundation; either version 2.1 of
* the License, or (at your option) any later version.
*
* GPGME is distributed in the hope that it will be useful, but
* WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
* Lesser General Public License for more details.
*
* You should have received a copy of the GNU Lesser General Public
* License along with this program; if not, see <https://gnu.org/licenses/>.
* SPDX-License-Identifier: LGPL-2.1-or-later
*/

#include <unistd.h>
#include <errno.h>
#include <stdlib.h>
#include <locale.h>

#include <gpgme.h>

#ifndef DIM
#define
 DIM(v)       (sizeof(v)/sizeof((v)[0]))
#endif

#define fail_if_err(err)     \
 do       \
   {       \
     if (err)       \
       {       \
         fprintf (stderr, "%s:%d: %s: %s (%d.%d)\n",         \
                  __FILE__, __LINE__, gpgme_strsource (err), \
     gpgme_strerror (err),                       \
                  gpgme_err_source (err), gpgme_err_code (err)); \
         exit (1);      \
       }       \
   }       \
 while (0)


void
print_data (gpgme_data_t dh)
{
#define BUF_SIZE 512
 char buf[BUF_SIZE + 1];
 int ret;
```

```
 ret = gpgme_data_seek (dh, 0, SEEK_SET);
 if (ret)
   fail_if_err (gpgme_error_from_errno (errno));
 while ((ret = gpgme_data_read (dh, buf, BUF_SIZE)) > 0)
   fwrite (buf, ret, 1, stdout);
 if (ret < 0)
   fail_if_err (gpgme_error_from_errno (errno));
}


gpgme_error_t
passphrase_cb (void *opaque, const char *uid_hint, const char *passphrase_info,
        int last_was_bad, int fd)
{
 int res;
 char pass[] = "abc\n";
  int passlen = strlen (pass);
 int off = 0;

 (void)opaque;
 (void)uid_hint;
 (void)passphrase_info;
 (void)last_was_bad;

 do
   {
     res = gpgme_io_write (fd, &pass[off], passlen - off);
     if (res > 0)
 off += res;
   }
 while (res > 0 && off != passlen);

 return off == passlen ? 0 : gpgme_error_from_errno (errno);
}


char *
make_filename (const char *fname)
{
 const char *srcdir = getenv ("srcdir");
 char *buf;

 if (!srcdir)
   srcdir = ".";
 buf = malloc (strlen(srcdir) + strlen(fname) + 2);
 if (!buf)
   exit (8);
 strcpy (buf, srcdir);
```

```
 strcat (buf, "/");
 strcat (buf, fname);
 return buf;
}


void
init_gpgme (gpgme_protocol_t proto)
{
 gpgme_error_t err;

 gpgme_check_version (NULL);
#ifndef HAVE_W32_SYSTEM
 setlocale (LC_ALL, "");
 gpgme_set_locale (NULL, LC_CTYPE, setlocale (LC_CTYPE, NULL));
 gpgme_set_locale (NULL, LC_MESSAGES, setlocale (LC_MESSAGES, NULL));
#endif

 err = gpgme_engine_check_version (proto);
 fail_if_err (err);
}
{
  "env": {
     "browser": true,
     "es6": true
  },
  "extends": "eslint:recommended",
  "parserOptions": {
     "sourceType": "module"
  },
  "rules": {
     "indent": [
        "warn",
        4
     ],
     "linebreak-style": [
        "error",
        "unix"
     ],
     "quotes": [
        "error",
        "single"
     ],
     "semi": [
        "error",
        "always"
     ],
     "no-var": [
```

```
        "warn"
      ],
      "max-len": 1,
      "default-case": 2,
      "no-invalid-this": 2,
      "no-lone-blocks": 1,
      "no-self-compare": 2,
      "radix": 2,
      "no-use-before-define": ["error", {
        "functions": false,
        "classes": false,
        "variables": true
      }],
      "no-useless-constructor": 1,
      "space-before-function-paren": ["error", "always"],
      "keyword-spacing": 2,
      "spaced-comment": 1,
      "space-unary-ops":
 2,
      "object-curly-spacing": ["error", "always"],
      "array-bracket-spacing": ["error", "never"]
    }
}
/*
  qgpgmedeletejob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004,2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

  In addition, as a
 special exception, the copyright holders give
  permission to link the code of this program with any edition of
```

```
  the Qt library by Trolltech AS, Norway (or with modified versions
  of Qt that use the same license as Qt), and distribute linked
  combinations including the two.  You must obey the GNU General
  Public License in all respects for all of the code used other than
  Qt.  If you modify this file, you may extend this exception to
  your version of the file, but you are not obligated to do so.  If
  you do not wish to do so, delete this exception statement from
  your version.
*/

#ifndef __QGPGME_QGPGMEDELETEJOB_H__
#define __QGPGME_QGPGMEDELETEJOB_H__

#include "deletejob.h"

#include "threadedjobmixin.h"

namespace GpgME
{
class Key;
}

namespace QGpgME
{

class QGpgMEDeleteJob
#ifdef Q_MOC_RUN
  : public DeleteJob
#else
  : public _detail::ThreadedJobMixin<DeleteJob>
#endif
{
  Q_OBJECT
#ifdef Q_MOC_RUN
public Q_SLOTS:
  void slotFinished();
#endif
public:
   explicit QGpgMEDeleteJob(GpgME::Context *context);
  ~QGpgMEDeleteJob();

  /* from DeleteJob */
  GpgME::Error start(const GpgME::Key &key, bool allowSecretKeyDeletion) Q_DECL_OVERRIDE;
};

}

#endif // __QGPGME_QGPGMEDELETEJOB_H__
```

```
{
  "op": "export",
  "keys": "alpha@example.net",
  "armor": true,
  "with-sec-fprs":true
}
/*
 signingresult.h - wraps a gpgme sign result
 Copyright (C) 2004 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

#ifndef __GPGMEPP_SIGNINGRESULT_H__
#define
 __GPGMEPP_SIGNINGRESULT_H__

#include "global.h"
#include "result.h"

#include <time.h>

#include <memory>

#include <vector>
#include <iosfwd>

namespace GpgME
{

class Error;
```

```
class CreatedSignature;
class InvalidSigningKey;

class GPGMEPP_EXPORT SigningResult : public Result
{
public:
  SigningResult();
  SigningResult(gpgme_ctx_t ctx, int error);
  SigningResult(gpgme_ctx_t ctx, const Error &error);
  explicit SigningResult(const Error &err);

  const SigningResult &operator=(SigningResult other)
  {
    swap(other);
    return *this;
  }

  void swap(SigningResult &other)
  {
    Result::swap(other);
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  CreatedSignature createdSignature(unsigned int index) const;
  std::vector<CreatedSignature> createdSignatures() const;

  InvalidSigningKey invalidSigningKey(unsigned int index) const;
  std::vector<InvalidSigningKey> invalidSigningKeys()
 const;

  class Private;
private:
  void init(gpgme_ctx_t ctx);
  std::shared_ptr<Private> d;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const SigningResult &result);

class GPGMEPP_EXPORT InvalidSigningKey
{
  friend class ::GpgME::SigningResult;
  InvalidSigningKey(const std::shared_ptr<SigningResult::Private> &parent, unsigned int index);
public:
  InvalidSigningKey();
```

```
  const InvalidSigningKey &operator=(InvalidSigningKey other)
  {
    swap(other);
    return *this;
  }

  void swap(InvalidSigningKey &other)
  {
    using std::swap;
    swap(this->d, other.d);
    swap(this->idx, other.idx);
  }

  bool isNull() const;

  const char *fingerprint() const;
  Error reason() const;

private:
  std::shared_ptr<SigningResult::Private> d;
  unsigned int idx;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const InvalidSigningKey &key);

class GPGMEPP_EXPORT CreatedSignature
{
  friend class ::GpgME::SigningResult;
   CreatedSignature(const std::shared_ptr<SigningResult::Private> &parent, unsigned int index);
public:

  CreatedSignature();

  const CreatedSignature &operator=(CreatedSignature other)
  {
    swap(other);
    return *this;
  }

  void swap(CreatedSignature &other)
  {
    using std::swap;
    swap(this->d, other.d);
    swap(this->idx, other.idx);
  }

  bool isNull() const;
```

```
  const char *fingerprint() const;

  time_t creationTime() const;

  SignatureMode mode() const;

  unsigned int publicKeyAlgorithm() const;
  const char *publicKeyAlgorithmAsString() const;

  unsigned int hashAlgorithm() const;
  const char *hashAlgorithmAsString() const;

  unsigned int signatureClass() const;

private:
  std::shared_ptr<SigningResult::Private> d;
  unsigned int idx;
};

GPGMEPP_EXPORT std::ostream &operator<<(std::ostream &os, const CreatedSignature &sig);

}

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(SigningResult)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(InvalidSigningKey)
GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(CreatedSignature)

#endif
 // __GPGMEPP_SIGNINGRESULT_H__
/*
  changeownertrustjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2008 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as
  published by the Free Software Foundation; either version 2 of the
  License, or (at your option) any later version.

  QGpgME is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  General Public License for more details.

  You should have received a copy of the GNU General Public License
```

```
   along with this program; if not, write to the Free Software
   Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a
 special exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_CHANGEOWNERTRUST_H__
#define __KLEO_CHANGEOWNERTRUST_H__

#include "job.h"

#ifdef BUILDING_QGPGME
# include "key.h"
#else
# include <gpgme++/key.h>
#endif

namespace QGpgME
{

/**
  @short An abstract base class to change owner trust asynchronously

  To use a ChangeOwnerTrustJob, first obtain an instance from the
  CryptoBackend implementation, connect the progress()
 and result()
  signals to suitable slots and then start the job with a call
  to start(). This call might fail, in which case the ChangeOwnerTrustJob
  instance will have scheduled it's own destruction with a call to
  QObject::deleteLater().

  After result() is emitted, the ChangeOwnerTrustJob will schedule it's own
  destruction by calling QObject::deleteLater().
*/
class QGPGME_EXPORT ChangeOwnerTrustJob : public Job
{
   Q_OBJECT
protected:
```

```
  explicit ChangeOwnerTrustJob(QObject *parent);
public:
  ~ChangeOwnerTrustJob();

  /**
    Starts the change-owner trust operation. \a key is the key to change
    the owner trust of . \a trust is the new trust level.
  */
  virtual GpgME::Error start(const GpgME::Key &key, GpgME::Key::OwnerTrust trust) = 0;

Q_SIGNALS:
  void result(const GpgME::Error &result, const QString &auditLogAsHtml = QString(), const GpgME::Error
&auditLogError = GpgME::Error());
};

}

#endif // __KLEO_CHANGEOWNERTRUSTJOB_H__
/*
 scdgetinfoassuantransaction.h - Assuan Transaction to get information from scdaemon
 Copyright (C) 2009 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME++.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301,
 USA.
*/

#ifndef __GPGMEPP_SCDGETINFOASSUANTRANSACTION_H__
#define __GPGMEPP_SCDGETINFOASSUANTRANSACTION_H__

#include <interfaces/assuantransaction.h>
```

```
#include <string>
#include <vector>

namespace GpgME
{

class GPGMEPP_EXPORT ScdGetInfoAssuanTransaction : public AssuanTransaction
{
public:
  enum InfoItem {
     Version,        // string
     Pid,            // unsigned long
     SocketName,     // string (path)
     Status,         // char (status)
     ReaderList,     // string list
     DenyAdmin,      // (none, returns GPG_ERR_GENERAL when admin commands are allowed)
     ApplicationList, // string list

     LastInfoItem
  };

  explicit ScdGetInfoAssuanTransaction(InfoItem item);
  ~ScdGetInfoAssuanTransaction();

  std::string version() const;
  unsigned int pid() const;
  std::string socketName() const;
  char status() const;
  std::vector<std::string> readerList() const;
  std::vector<std::string> applicationList() const;

private:
   const char *command() const;
  Error data(const char *data, size_t datalen) override;
  Data inquire(const char *name, const char *args, Error &err) override;
  Error status(const char *status, const char *args) override;

private:
  void makeCommand() const;

private:
  InfoItem m_item;
  mutable std::string m_command;
  std::string m_data;
};

} // namespace GpgME
```

```
#endif // __GPGMEPP_SCDGETINFOASSUANTRANSACTION_H__
#include "qgpgme/job.h"
% Created 2019-01-18 Fri 10:10
% Intended LaTeX compiler: xelatex
\documentclass[12pt]{article}
\usepackage{graphicx}
\usepackage{grffile}
\usepackage{longtable}
\usepackage{wrapfig}
\usepackage{rotating}
\usepackage[normalem]{ulem}
\usepackage{amsmath}
\usepackage{textcomp}
\usepackage{amssymb}
\usepackage{capt-of}
\usepackage{hyperref}
\usepackage{xltxtra}
\usepackage[margin=1in]{geometry}
\setmainfont[Ligatures={Common}]{Times New Roman}
\author{Ben McGinnes <ben@gnupg.org>}
\author{Ben McGinnes}
\date{\today}
\title{GNU Privacy Guard (GnuPG) Made Easy Python Bindings HOWTO (English)}
\hypersetup{
pdfauthor={Ben McGinnes},
pdftitle={GNU Privacy Guard (GnuPG) Made Easy Python Bindings HOWTO (English)},
pdfkeywords={},
pdfsubject={},
pdfcreator={Emacs 26.1 (Org mode 9.1.14)},
pdflang={English}}
\begin{document}

\maketitle
\tableofcontents



\section{Introduction}
\label{sec:org8e5fa02}
\begin{center}
\begin{tabular}{ll}
Version: & 0.1.4\\
GPGME Version: & 1.12.1\\
Author: & Ben
 McGinnes <ben@gnupg.org>\\
Author GPG Key: & DB4724E6FA4286C92B4E55C4321E4E2373590E5D\\
Language: & Australian English, British English\\
Language codes: & en-AU, en-GB, en\\
```

\end{tabular}
\end{center}

This document provides basic instruction in how to use the GPGME
Python bindings to programmatically leverage the GPGME library.

\subsection{Python 2 versus Python 3}
\label{sec:org517cbf4}
Though the GPGME Python bindings themselves provide support for both
Python 2 and 3, the focus is unequivocally on Python 3 and
specifically from Python 3.4 and above. As a consequence all the
examples and instructions in this guide use Python 3 code.

Much of it will work with Python 2, but much of it also deals with
Python 3 byte literals, particularly when reading and writing data.
Developers concentrating on Python 2.7, and possibly even 2.6, will
need to make the appropriate modifications to support the older string
and unicode types as opposed to bytes.

There are multiple reasons for concentrating
 on Python 3; some of
which relate to the immediate integration of these bindings, some of
which relate to longer term plans for both GPGME and the python
bindings and some of which relate to the impending EOL period for
Python 2.7. Essentially, though, there is little value in tying the
bindings to a version of the language which is a dead end and the
advantages offered by Python 3 over Python 2 make handling the data
types with which GPGME deals considerably easier.

\subsection{Examples}
\label{sec:org2c08d53}
All of the examples found in this document can be found as Python 3
scripts in the \texttt{lang/python/examples/howto} directory.

\subsection{Unofficial Drafts}
\label{sec:orgceb2216}
In addition to shipping with each release of GPGME, there is a section
on locations to read or download \hyperref[sec:org080a94a]{draft editions} of this document from
at the end of it. These are unofficial versions produced in between
major releases.

\subsection{What's New}
\label{sec:orga79ddc2}
Full

details of what is new are now available in the \href{what-is-new.org}{What's New} file
and archives of the preceding \emph{What's New} sections are available in
the \href{what-was-new}{What Was New} file.

\subsubsection{New in GPGME 1130}
\label{sec:org746b75d}
See the \href{what-is-new\#new-stuff-1-13-0}{What's New} document for what is new in version 1.13.0.

\subsubsection{New in GPGME 1120}
\label{sec:org7adcade}
See the \href{what-was-new\#new-stuff-1-12-0}{What Was New} document for what was new in version 1.12.0.

\section{GPGME Concepts}
\label{sec:orgb257fc1}
\subsection{A C API}
\label{sec:org4fe1dfa}
Unlike many modern APIs with which programmers will be more familiar
with these days, the GPGME API is a C API. The API is intended for
use by C coders who would be able to access its features by including
the \texttt{gpgme.h} header file with their own C source code and then access
its functions just as they would any other C headers.

This is a very
effective method of gaining complete access to the API
and in the most efficient manner possible. It does, however, have the
drawback that it cannot be directly used by other languages without
some means of providing an interface to those languages. This is
where the need for bindings in various languages stems.

\subsection{Python bindings}
\label{sec:org0e49e52}
The Python bindings for GPGME provide a higher level means of
accessing the complete feature set of GPGME itself. It also provides
a more pythonic means of calling these API functions.

The bindings are generated dynamically with SWIG and the copy of
\texttt{gpgme.h} generated when GPGME is compiled.

This means that a version of the Python bindings is fundamentally tied
to the exact same version of GPGME used to generate that copy of
\texttt{gpgme.h}.

\subsection{Difference between the Python bindings and other GnuPG Python packages}

\label{sec:org97acfd7}
There have been numerous attempts to add GnuPG support to Python
over
the years. Some of the most well known are listed here, along with
what differentiates them.

\subsubsection{The python-gnupg package maintained by Vinay Sajip}
\label{sec:org0136847}
This is arguably the most popular means of integrating GPG with
Python. The package utilises the \texttt{subprocess} module to implement
wrappers for the \texttt{gpg} and \texttt{gpg2} executables normally invoked on the
command line (\texttt{gpg.exe} and \texttt{gpg2.exe} on Windows).

The popularity of this package stemmed from its ease of use and
capability in providing the most commonly required features.

Unfortunately it has been beset by a number of security issues in the
past; most of which stemmed from using unsafe methods of accessing the
command line via the \texttt{subprocess} calls. While some effort has been
made over the last two to three years (as of 2018) to mitigate this,
particularly by no longer providing shell access through those
subprocess calls, the wrapper is still somewhat
limited in the scope
of its GnuPG features coverage.

The python-gnupg package is available under the MIT license.

\subsubsection{The gnupg package created and maintained by Isis Lovecruft}
\label{sec:orgdc03987}
In 2015 Isis Lovecruft from the Tor Project forked and then
re-implemented the python-gnupg package as just gnupg. This new
package also relied on subprocess to call the \texttt{gpg} or \texttt{gpg2}
binaries, but did so somewhat more securely.

The naming and version numbering selected for this package, however,
resulted in conflicts with the original python-gnupg and since its
functions were called in a different manner to python-gnupg, the
release of this package also resulted in a great deal of consternation
when people installed what they thought was an upgrade that
subsequently broke the code relying on it.

The gnupg package is available under the GNU General Public License
version 3.0 (or any later version).

\subsubsection{The PyME package maintained by Martin

Albrecht}
\label{sec:org715600b}
This package is the origin of these bindings, though they are somewhat
different now. For details of when and how the PyME package was
folded back into GPGME itself see the \href{short-history.org}{Short History} document.\footnote{\texttt{short-history} and/or \texttt{short-history.html}.}

The PyME package was first released in 2002 and was also the first
attempt to implement a low level binding to GPGME. In doing so it
provided access to considerably more functionality than either the
\texttt{python-gnupg} or \texttt{gnupg} packages.

The PyME package is only available for Python 2.6 and 2.7.

Porting the PyME package to Python 3.4 in 2015 is what resulted in it
being folded into the GPGME project and the current bindings are the
end result of that effort.

The PyME package is available under the same dual licensing as GPGME
itself: the GNU General Public License version 2.0 (or any later
version) and the GNU Lesser General Public License version
2.1 (or any
later version).

\section{GPGME Python bindings installation}
\label{sec:org73d8d6f}
\subsection{No PyPI}
\label{sec:orgec9a038}
Most third-party Python packages and modules are available and
distributed through the Python Package Installer, known as PyPI.

Due to the nature of what these bindings are and how they work, it is
infeasible to install the GPGME Python bindings in the same way.

This is because the bindings use SWIG to dynamically generate C
bindings against \texttt{gpgme.h} and \texttt{gpgme.h} is generated from
\texttt{gpgme.h.in} at compile time when GPGME is built from source. Thus to
include a package in PyPI which actually built correctly would require
either statically built libraries for every architecture bundled with
it or a full implementation of C for each architecture.

See the additional notes regarding \hyperref[sec:org645735a]{CFFI and SWIG} at the end of this
section for further details.

\subsection{Requirements}
\label{sec:org2f7f06c}

The
GPGME Python bindings only have three requirements:

\begin{enumerate}
\item A suitable version of Python 2 or Python 3. With Python 2 that
means CPython 2.7 and with Python 3 that means CPython 3.4 or
higher.
\item \href{https://www.swig.org}{SWIG}.
\item GPGME itself. Which also means that all of GPGME's dependencies
must be installed too.
\end{enumerate}

\subsubsection{Recommended Additions}
\label{sec:org25bd7d4}
Though none of the following are absolute requirements, they are all
recommended for use with the Python bindings. In some cases these
recommendations refer to which version(s) of CPython to use the
bindings with, while others refer to third party modules which provide
a significant advantage in some way.

\begin{enumerate}
\item If possible, use Python 3 instead of 2.
\item Favour a more recent version of Python since even 3.4 is due to
reach EOL soon. In production systems and services, Python 3.6
should be robust enough to be relied on.
\item If possible add the
following Python modules which are not part of
the standard library: \href{http://docs.python-requests.org/en/latest/index.html}{Requests},
\href{https://cython.org/}{Cython}, \href{https://pendulum.eustace.io/}{Pendulum} and
\href{https://github.com/Selfnet/hkp4py}{hkp4py}.
\end{enumerate}

Chances are quite high that at least the first one and maybe two of
those will already be installed.

Note that, as with Cython, some of advanced use case scenarios will
bring with them additional requirements. Most of these will be fairly
well known and commonly installed ones, however, which are in many
cases likely to have already been installed on many systems or be
familiar to Python programmers.

\subsection{Installation}
\label{sec:orgf1c7587}
Installing the Python bindings is effectively achieved by compiling
and installing GPGME itself.

Once SWIG is installed with Python and all the dependencies for GPGME
are installed you only need to confirm that the version(s) of Python
you want the
bindings installed for are in your \texttt{\$PATH}.

By default GPGME will attempt to install the bindings for the most
recent or highest version number of Python 2 and Python 3 it detects
in \texttt{\$PATH}. It specifically checks for the \texttt{python} and \texttt{python3}
executables first and then checks for specific version numbers.

For Python 2 it checks for these executables in this order: \texttt{python},
\texttt{python2} and \texttt{python2.7}.

For Python 3 it checks for these executables in this order: \texttt{python3},
\texttt{python3.7}, \texttt{python3.6}, \texttt{python3.5} and \texttt{python3.4}.\footnote{With no issues reported
specific to Python 3.7, the release of
Python 3.7.1 at around the same time as GPGME 1.12.0 and the testing
with Python 3.7.1rc1, there is no reason to delay moving 3.7 ahead of
3.6 now. Production environments with more conservative requirements
will always enforce their own policies anyway and installation to each
supported minor release
is quite possible too.}

On systems where \texttt{python} is actually \texttt{python3} and not \texttt{python2} it
may be possible that \texttt{python2} may be overlooked, but there have been
no reports of that actually occurring as yet.

In the three months or so since the release of Python 3.7.0 there has
been extensive testing and work with these bindings with no issues
specifically relating to the new version of Python or any of the new
features of either the language or the bindings. This has also been
the case with Python 3.7.1rc1. With that in mind and given the
release of Python 3.7.1 is scheduled for around the same time as GPGME
1.12.0, the order of preferred Python versions has been changed to
move Python 3.7 ahead of Python 3.6.

\subsubsection{Installing GPGME}
\label{sec:org903bd67}
See the GPGME \texttt{README} file for details of how to install GPGME from
source.

\subsection{Known Issues}
\label{sec:org0d2a332}
There are a few known issues with the current build process
and the
Python bindings. For the most part these are easily addressed should

they be encountered.

\subsubsection{Breaking Builds}
\label{sec:orgbac75f3}
Occasionally when installing GPGME with the Python bindings included
it may be observed that the \texttt{make} portion of that process induces a
large very number of warnings and, eventually errors which end that
part of the build process. Yet following that with \texttt{make check} and
\texttt{make install} appears to work seamlessly.

The cause of this is related to the way SWIG needs to be called to
dynamically generate the C bindings for GPGME in the first place. So
the entire process will always produce \texttt{lang/python/python2-gpg/} and
\texttt{lang/python/python3-gpg/} directories. These should contain the
build output generated during compilation, including the complete
bindings and module installed into \texttt{site-packages}.

Occasionally the errors in the early part or some other conflict
(e.g. not installing
 as \textbf{\emph{root}} or \textbf{\emph{su}}) may result in nothing
being installed to the relevant \texttt{site-packages} directory and the
build directory missing a lot of expected files. Even when this
occurs, the solution is actually quite simple and will always work.

That solution is simply to run the following commands as either the
\textbf{root} user or prepended with \texttt{sudo -H}\footnote{Yes, even if you use virtualenv with everything you do in
Python. If you want to install this module as just your user account
then you will need to manually configure, compile and install the
\emph{entire} GnuPG stack as that user as well. This includes libraries
which are not often installed that way. It can be done and there are
circumstances under which it is worthwhile, but generally only on
POSIX systems which utilise single user mode (some even require it).} in the \texttt{lang/python/}
directory:

\begin{verbatim}
/path/to/pythonX.Y setup.py build
/path/to/pythonX.Y setup.py
 build
/path/to/pythonX.Y setup.py install
\end{verbatim}

Yes, the build command does need to be run twice. Yes, you still need
to run the potentially failing or incomplete steps during the
\texttt{configure}, \texttt{make} and \texttt{make install} steps with installing GPGME.
This is because those steps generate a lot of essential files needed,
both by and in order to create, the bindings (including both the

\texttt{setup.py} and \texttt{gpgme.h} files).

\begin{enumerate}
\item IMPORTANT Note
\label{sec:org37f3d4a}
If specifying a selected number of languages to create bindings for,
try to leave Python last. Currently the majority of the other
language bindings are also preceding Python of either version when
listed alphabetically (not counting the Qt bindings).

If Python is set to precede one of the other languages then it is
possible that the errors described here may interrupt the build
process before generating bindings for those other languages. In
these cases it may be preferable
 to configure all preferred language
bindings separately with alternative \texttt{configure} steps for GPGME using
the \texttt{-{}-enable-languages=\$LANGUAGE} option.

Alternatively \texttt{make} (or \texttt{gmake}, depending on your platform) may be
run with the the \texttt{-k} option, which tells make to keep going even if
errors are encountered. In that case the failure of one language's
set of bindings to build should not hamper another language's bindings
to build.
\end{enumerate}

\subsubsection{Reinstalling Responsibly}
\label{sec:org21e4dec}
Regardless of whether you're installing for one version of Python or
several, there will come a point where reinstallation is required.
With most Python module installations, the installed files go into the
relevant site-packages directory and are then forgotten about. Then
the module is upgraded, the new files are copied over the old and
that's the end of the matter.

While the same is true of these bindings, there have been intermittent
issues
 observed on some platforms which have benefited significantly
from removing all the previous installations of the bindings before
installing the updated versions.

Removing the previous version(s) is simply a matter of changing to the
relevant \texttt{site-packages} directory for the version of Python in
question and removing the \texttt{gpg/} directory and any accompanying
egg-info files for that module.

In most cases this will require root or administration privileges on

the system, but the same is true of installing the module in the first
place.

\subsubsection{Multiple installations}
\label{sec:org30b18bd}
For a variety of reasons it may be either necessary or just preferable
to install the bindings to alternative installed Python versions which
meet the requirements of these bindings.

On POSIX systems this will generally be most simply achieved by
running the manual installation commands (build, build, install) as
described in the previous section for each Python
 installation the
bindings need to be installed to.

As per the SWIG documentation: the compilers, libraries and runtime
used to build GPGME and the Python Bindings \textbf{must} match those used to
compile Python itself, including the version number(s) (at least going
by major version numbers and probably minor numbers too).

On most POSIX systems, including OS X, this will very likely be the
case in most, if not all, cases.

Note that from GPGME \href{https://dev.gnupg.org/rMff6ff616aea6f59b7f2ce1176492850ecdf3851e}{1.12.1} the
default installation installs to each
version of Python it can find first. That is that it will currently
install for the first copies of Python versions 2.7, 3.4, 3.5, 3.6,
3.7 and 3.8 (dev branch) that it finds. Usually this will be in the
same prefix as GPGME itself, but is dictated by the \texttt{\$PATH} when the
installation is performed. The above instructions can still be
performed on other python installations which the installer does not
find,
 including alternative prefixes.

\subsubsection{Won't Work With Windows}
\label{sec:org0ebae3a}
There are semi-regular reports of Windows users having considerable
difficulty in installing and using the Python bindings at all. Very
often, possibly even always, these reports come from Cygwin users
and/or MinGW users and/or Msys2 users. Though not all of them have
been confirmed, it appears that these reports have also come from
people who installed Python using the Windows installer files from the
\href{https://python.org}{Python website} (i.e. mostly MSI installers, sometimes self-extracting
\texttt{.exe} files).

The Windows versions of Python are not built using Cygwin, MinGW or
Msys2; they're built using Microsoft Visual Studio. Furthermore the
version used is \emph{considerably} more advanced than the version which
MinGW obtained a small number of files from many years ago in order to
be able to compile anything at all. Not only that, but there are
changes to the version of
 Visual Studio between some micro releases,
though that is is particularly the case with Python 2.7, since it has
been kept around far longer than it should have been.

There are two theoretical solutions to this issue:

\begin{enumerate}
\item Compile and install the GnuPG stack, including GPGME and the
Python bindings using the same version of Microsoft Visual Studio
used by the Python Foundation to compile the version of Python
installed.

If there are multiple versions of Python then this will need to be
done with each different version of Visual Studio used for those
versions of Python.

\item Compile and install Python using the same tools used by choice,
such as MinGW or Msys2.
\end{enumerate}

Do \textbf{not} use the official Windows installer for Python unless
following the first method.

In this type of situation it may even be for the best to accept that
there are less limitations on permissive software than free software
and simply opt to use a recent version of the Community
 Edition of
Microsoft Visual Studio to compile and build all of it, no matter
what.

Investigations into the extent or the limitations of this issue are
ongoing.

The following table lists the version of Microsoft Visual Studio which
needs to be used when compiling GPGME and the Python bindings with
each version of the CPython binary released \href{https://www.python.org/downloads/windows/}{for Windows}:

\begin{center}
\begin{tabular}{rll}
CPython & Microsoft product name & runtime filename\\
2.7.6 & Visual Studio 2008 & MSVCR90.DLL\\
3.4.0 & Visual Studio 2010 & MSVCR100.DLL\\

3.5.0 & Visual Studio 2015 & \textbf{see below}\\
3.6.0 & Visual Studio 2015 & \textbf{see below}\\
3.7.0 & Visual Studio 2017* & \textbf{see below}\\
\end{tabular}
\end{center}

It is important to note that MingW and Msys2 ship with the Visual C runtime from Microsoft Visual Studio 2005 and are thus \textbf{incompatible} with all the versions of CPython which can be used with the GPGME Python bindings.

It is also important to note that from CPython 3.5 onwards, the Python Foundation has adopted the reworking of the Visual C runtime which was performed for Visual Studio 2015 and aimed at resolving many of these kinds of issues. Much greater detail on these issues and the correct file(s) to link to are available from Matthew Brett's invaluable page, \href{https://matthew-brett.github.io/pydagogue/python_msvc.html}{Using Microsoft Visual C with Python}. It is also worth reading the Microsoft Developer Network blog post on \href{http://blogs.msdn.com/b/vcblog/archive/2015/03/03/introducing-the-universal-crt.aspx}{the universal CRT} and Steve Dower's blog posts on Python extensions (\href{http://stevedower.id.au/blog/building-for-python-3-5}{part 1} and \href{http://stevedower.id.au/blog/building-for-python-3-5-part-two}{part 2}).

The second of those two posts by Steve Dower contains the details of specific configuration options required for compiling anything to be used with official CPython releases. In addition to those configuration and compiler settings to use, the versions of Visual Studio prior to Visual Studio 2015 did not support 64-bit systems by default. So compiling a 64-bit version of these bindings for a 64-bit version of CPython 2.7 or 3.4 requires additional work.

In addition to the blog posts, the \href{https://wiki.python.org/moin/WindowsCompilers}{Windows compilers} wiki page on the CPython wiki is another essential reference on the relevant versions of Visual Studio to use and the degree of compatibility with CPython releases.

Eventually someone will ask why there isn't an installable binary for Windows, which the GPGME of the licenses do not preclude as long as the source code is available in conjunction with such a release.

The sheer number of versions of Visual Studio in conjunction with differing configuration options depending on the target Windows version and whether the architecture is 64-bit or 32-bit makes it difficult to provide a correct

binary installer for Windows users. At
the bare minimum doing so would require the GnuPG project compile ten
different versions of the bindings with each release; both 32-bit and
64-bit versions for CPython 2.7 and 3.4, with 64-bit versions for both
x86-64 (i.e. Intel and AMD) and ARM architectures for CPython 3.5,
3.6, 3.7 and later releases. That's the bare \textbf{minimum}, it'd probably
be higher.

Additionally, with only a binary installation used in conjunction with
the CPython installer from \texttt{python.org} the advanced options available
which utilise \hyperref[sec:org3b53926]{Cython} will not be able to be used at all. Cython
depends on being able to compile the C code it generates and that too
would need to utilise a matching runtime to both the installed version
of CPython and these bindings in order to work with the bindings.

Considering all of that, what do we recommend?

\begin{enumerate}
\item Use a recent version of CPython; at least 3.5, but ideally 3.6 or
later.

\item
Use Visual Studio 2015 or the standalone build tools for Visual
Studio 2017 (or later).

\item Compile both CPython and GPGME with these bindings using the tools
selected in step 2.

\item Ignore MingW, Msys2 and the official CPython binary installers.

\item Be thankful the answer to this question wasn't simply to say
something like, install Linux or install FreeBSD (or even
Apple's OS X).
\end{enumerate}

\subsubsection{CFFI is the Best and GPGME should use it instead of SWIG}
\label{sec:org645735a}
There are many reasons for favouring \href{https://cffi.readthedocs.io/en/latest/overview.html}{CFFI} and
proponents of it are
quite happy to repeat these things as if all it would take to switch
from SWIG to CFFI is repeating that list as if it were a new concept.

The fact is that there are things which Python's CFFI implementation
cannot handle in the GPGME C code. Beyond that there are features of
SWIG which are simply not available with CFFI at all. SWIG generates
the

bindings to Python using the \texttt{gpgme.h} file, but that file is not a single version shipped with each release, it too is generated when GPGME is compiled.

CFFI is currently unable to adapt to such a potentially mutable codebase. If there were some means of applying SWIG's dynamic code generation to produce the Python/CFFI API modes of accessing the GPGME libraries (or the source source code directly), but such a thing does not exist yet either and it currently appears that work is needed in at least one of CFFI's dependencies before any of this can be addressed.

So if you're a massive fan of CFFI; that's great, but if you want this project to switch to CFFI then rather than just insisting that it should, I'd suggest you volunteer to bring CFFI up to the level this project needs.

If you're actually seriously considering doing so, then I'd suggest taking the \texttt{gpgme-tool.c} file in the GPGME \texttt{src/} directory and getting that to work with any of the CFFI API methods (not the ABI methods, they'll work with pretty much anything). When you start running into trouble with "ifdefs" then you'll know what sort of things are lacking. That doesn't even take into account the amount of work saved via SWIG's code generation techniques either.

\subsubsection{Virtualised Environments}
\label{sec:orgb0d56f5}
It is fairly common practice amongst Python developers to, as much as possible, use packages like virtualenv to keep various things that are to be installed from interfering with each other. Given how much of the GPGME bindings is often at odds with the usual pythonic way of doing things, it stands to reason that this would be called into question too.

As it happens the answer as to whether or not the bindings can be used with virtualenv, the answer is both yes and no.

In general we recommend installing to the relevant path and matching prefix of GPGME itself. Which means that when GPGME, and ideally the rest of the GnuPG stack, is installed to a prefix like \texttt{/usr/local} or \texttt{/opt/local} then the bindings would need to be installed to the main Python installation and not a virtualised abstraction. Attempts to separate the two in the past have been known to cause weird and intermittent errors ranging from minor annoyances to complete failures in the build process.

As a consequence we only recommend building with and installing to the
main Python installations within the same prefix as GPGME is installed
to or which are found by GPGME's configuration stage immediately prior
to running the make commands. Which is exactly what the compiling and
installing process of GPGME does by default.

Once that is done, however, it appears that a copy of the compiled
module may be installed into a virtualenv of the same major and minor
version matching the build. Alternatively it is possible to utilise a
\texttt{sites.pth} file in the \texttt{site-packages/} directory of a virtualenv
installation, which links back to the system
 installations
corresponding directory in order to import anything installed system
wide. This may or may not be appropriate on a case by case basis.

Though extensive testing of either of these options is not yet
complete, preliminary testing of them indicates that both are viable
as long as the main installation is complete. Which means that
certain other options normally restricted to virtual environments are
also available, including integration with pythonic test suites
(e.g. \href{https://docs.pytest.org/en/latest/index.html}{pytest}) and other large projects.

That said, it is worth reiterating the warning regarding non-standard
installations. If one were to attempt to install the bindings only to
a virtual environment without somehow also including the full GnuPG
stack (or enough of it as to include GPGME) then it is highly likely
that errors would be encountered at some point and more than a little
likely that the build process itself would break.

If a degree of separation
 from the main operating system is still
required in spite of these warnings, then consider other forms of
virtualisation. Either a virtual machine (e.g. \href{https://www.virtualbox.org/}{VirtualBox}), a
hardware emulation layer (e.g. \href{https://www.qemu.org/}{QEMU}) or an application container
(e.g. \href{https://www.docker.com/why-docker}{Docker}).

Finally it should be noted that the limited tests conducted thus far
have been using the \texttt{virtualenv} command in a new directory to create
the virtual python environment. As opposed to the standard \texttt{python3
-m venv} and it is possible that this will make a difference depending
on the system and version of Python in use. Another option is to run
the command \texttt{python3 -m virtualenv /path/to/install/virtual/thingy}
instead.

\section{Fundamentals}
\label{sec:org832642e}

Before we can get to the fun stuff, there are a few matters regarding
GPGME's design which hold true whether you're dealing with the C code
directly
 or these Python bindings.

\subsection{No REST}
\label{sec:org3d694ba}
The first part of which is or will be fairly blatantly obvious upon
viewing the first example, but it's worth reiterating anyway. That
being that this API is \emph{\textbf{not}} a REST API. Nor indeed could it ever
be one.

Most, if not all, Python programmers (and not just Python programmers)
know how easy it is to work with a RESTful API. In fact they've
become so popular that many other APIs attempt to emulate REST-like
behaviour as much as they are able. Right down to the use of JSON
formatted output to facilitate the use of their API without having to
retrain developers.

This API does not do that. It would not be able to do that and also
provide access to the entire C API on which it's built. It does,
however, provide a very pythonic interface on top of the direct
bindings and it's this pythonic layer that this HOWTO deals with.

\subsection{Context}
\label{sec:org10e4004}
One of the reasons which prevents
 this API from being RESTful is that
most operations require more than one instruction to the API to
perform the task. Sure, there are certain functions which can be
performed simultaneously, particularly if the result known or strongly
anticipated (e.g. selecting and encrypting to a key known to be in the
public keybox).

There are many more, however, which cannot be manipulated so readily:
they must be performed in a specific sequence and the result of one
operation has a direct bearing on the outcome of subsequent
operations. Not merely by generating an error either.

When dealing with this type of persistent state on the web, full of
both the RESTful and REST-like, it's most commonly referred to as a
session. In GPGME, however, it is called a context and every
operation type has one.

\section{Working with keys}

\label{sec:orgff114ca}
\subsection{Key selection}
\label{sec:org6589217}
Selecting keys to encrypt to or to sign with will be a common
occurrence when working with
 GPGMe and the means available for doing
so are quite simple.

They do depend on utilising a Context; however once the data is
recorded in another variable, that Context does not need to be the
same one which subsequent operations are performed.

The easiest way to select a specific key is by searching for that
key's key ID or fingerprint, preferably the full fingerprint without
any spaces in it. A long key ID will probably be okay, but is not
advised and short key IDs are already a problem with some being
generated to match specific patterns. It does not matter whether the
pattern is upper or lower case.

So this is the best method:

\begin{verbatim}
import gpg

k = gpg.Context().keylist(pattern="258E88DCBD3CD44D8E7AB43F6ECB6AF0DEADBEEF")
keys = list(k)
\end{verbatim}

This is passable and very likely to be common:

\begin{verbatim}
import gpg

k = gpg.Context().keylist(pattern="0x6ECB6AF0DEADBEEF")
keys = list(k)
\end{verbatim}

And this is a really bad idea:

\begin{verbatim}
import
 gpg

k = gpg.Context().keylist(pattern="0xDEADBEEF")
keys = list(k)
\end{verbatim}

Alternatively it may be that the intention is to create a list of keys

which all match a particular search string. For instance all the
addresses at a particular domain, like this:

\begin{verbatim}
import gpg

ncsc = gpg.Context().keylist(pattern="ncsc.mil")
nsa = list(ncsc)
\end{verbatim}

\subsubsection{Counting keys}
\label{sec:org63a3d62}
Counting the number of keys in your public keybox (\texttt{pubring.kbx}), the
format which has superseded the old keyring format (\texttt{pubring.gpg} and
\texttt{secring.gpg}), or the number of secret keys is a very simple task.

\begin{verbatim}
import gpg

c = gpg.Context()
seckeys = c.keylist(pattern=None, secret=True)
pubkeys = c.keylist(pattern=None, secret=False)

seclist = list(seckeys)
secnum = len(seclist)

publist = list(pubkeys)
pubnum = len(publist)

print("""
 Number of secret keys: {0}
 Number of public keys: {1}
""".format(secnum, pubnum))
\end{verbatim}

NOTE:
 The \hyperref[sec:org3b53926]{Cython} introduction in the \hyperref[sec:org944cc00]{Advanced and
Experimental}
section uses this same key counting code with Cython to demonstrate
some areas where Cython can improve performance even with the
bindings. Users with large public keyrings or keyboxes, for instance,
should consider these options if they are comfortable with using
Cython.

\subsection{Get key}
\label{sec:org26adb2e}

An alternative method of getting a single key via its fingerprint is
available directly within a Context with \texttt{Context().get_key}. This is
the preferred method of selecting a key in order to modify it, sign or
certify it and for obtaining relevant data about a single key as a
part of other functions; when verifying a signature made by that key,
for instance.

By default this method will select public keys, but it can select
secret keys as well.

This first example demonstrates selecting the current key of Werner
Koch, which is due
 to expire at the end of 2018:

\begin{verbatim}
import gpg

fingerprint = "80615870F5BAD690333686D0F2AD85AC1E42B367"
key = gpg.Context().get_key(fingerprint)
\end{verbatim}

Whereas this example demonstrates selecting the author's current key
with the \texttt{secret} key word argument set to \texttt{True}:

\begin{verbatim}
import gpg

fingerprint = "DB4724E6FA4286C92B4E55C4321E4E2373590E5D"
key = gpg.Context().get_key(fingerprint, secret=True)
\end{verbatim}

It is, of course, quite possible to select expired, disabled and
revoked keys with this function, but only to effectively display
information about those keys.

It is also possible to use both unicode or string literals and byte
literals with the fingerprint when getting a key in this way.

\subsection{Importing keys}
\label{sec:org1ad598a}
Importing keys is possible with the \texttt{key_import()} method and takes
one argument which is a bytes literal object containing either the
binary or ASCII armoured key data for one or more
 keys.

The following example retrieves one or more keys from the SKS
keyservers via the web using the requests module. Since requests

returns the content as a bytes literal object, we can then use that
directly to import the resulting data into our keybox.

\begin{verbatim}
import gpg
import os.path
import requests

c = gpg.Context()
url = "https://sks-keyservers.net/pks/lookup"
pattern = input("Enter the pattern to search for key or user IDs: ")
payload = {"op": "get", "search": pattern}

r = requests.get(url, verify=True, params=payload)
result = c.key_import(r.content)

if result is not None and hasattr(result, "considered") is False:
  print(result)
elif result is not None and hasattr(result, "considered") is True:
  num_keys = len(result.imports)
  new_revs = result.new_revocations
  new_sigs = result.new_signatures
  new_subs = result.new_sub_keys
  new_uids = result.new_user_ids
  new_scrt = result.secret_imported
  nochange = result.unchanged
  print("""
 The total number of keys considered for import was: {0}

   Number of keys revoked: {1}
  Number of new signatures: {2}
    Number of new subkeys: {3}
   Number of new user IDs: {4}
 Number of new secret keys: {5}
  Number of unchanged keys: {6}

 The key IDs for all considered keys were:
""".format(num_keys, new_revs, new_sigs, new_subs, new_uids, new_scrt,
        nochange))
  for i in range(num_keys):
    print("{0}\n".format(result.imports[i].fpr))
else:
  pass
\end{verbatim}

NOTE: When searching for a key ID of any length or a fingerprint
(without spaces), the SKS servers require the the leading \texttt{0x}
indicative of hexadecimal be included. Also note that the old short

key IDs (e.g. \texttt{0xDEADBEEF}) should no longer be used due to the relative ease by which such key IDs can be reproduced, as demonstrated by the Evil32 Project in 2014 (which was subsequently exploited in 2016).

Testing for whether a string in any given search is or may be a hexadecimal
 value which may be missing the leading \texttt{0x} is a simple matter of using a try/except statement which attempts to convert the string as hex to an integer and then back to hex; then using that to search with. Raising a ValueError simply results in treating the string as a string. This is the method and logic utilised in the \texttt{import-keys-hkp.py} script (see below).

\subsubsection{Working with ProtonMail}
\label{sec:org27b0d6f}
Here is a variation on the example above which checks the constrained ProtonMail keyserver for ProtonMail public keys.

```
\begin{verbatim}
import gpg
import requests
import sys

print("""
This script searches the ProtonMail key server for the specified key and
imports it.
""")

c = gpg.Context(armor=True)
url = "https://api.protonmail.ch/pks/lookup"
ksearch = []

if len(sys.argv) >= 2:
  keyterm = sys.argv[1]
else:
  keyterm = input("Enter the key ID, UID or search string: ")

if keyterm.count("@") == 2 and keyterm.startswith("@") is
 True:
  ksearch.append(keyterm[1:])
  ksearch.append(keyterm[1:])
  ksearch.append(keyterm[1:])
elif keyterm.count("@") == 1 and keyterm.startswith("@") is True:
  ksearch.append("{0}@protonmail.com".format(keyterm[1:]))
  ksearch.append("{0}@protonmail.ch".format(keyterm[1:]))
  ksearch.append("{0}@pm.me".format(keyterm[1:]))
```

```
elif keyterm.count("@") == 0:
  ksearch.append("{0}@protonmail.com".format(keyterm))
  ksearch.append("{0}@protonmail.ch".format(keyterm))
  ksearch.append("{0}@pm.me".format(keyterm))
elif keyterm.count("@") == 2 and keyterm.startswith("@") is False:
  uidlist = keyterm.split("@")
  for uid in uidlist:
     ksearch.append("{0}@protonmail.com".format(uid))
     ksearch.append("{0}@protonmail.ch".format(uid))
     ksearch.append("{0}@pm.me".format(uid))
elif keyterm.count("@") > 2:
  uidlist = keyterm.split("@")
  for uid in uidlist:
     ksearch.append("{0}@protonmail.com".format(uid))
     ksearch.append("{0}@protonmail.ch".format(uid))
      ksearch.append("{0}@pm.me".format(uid))
else:
  ksearch.append(keyterm)

for k in ksearch:
  payload = {"op": "get", "search": k}
  try:
     r = requests.get(url, verify=True, params=payload)
     if r.ok is True:
        result = c.key_import(r.content)
     elif r.ok is False:
        result = r.content
  except Exception as e:
     result = None

  if result is not None and hasattr(result, "considered") is False:
     print("{0} for {1}".format(result.decode(), k))
  elif result is not None and hasattr(result, "considered") is True:
     num_keys = len(result.imports)
     new_revs = result.new_revocations
     new_sigs = result.new_signatures
     new_subs = result.new_sub_keys
     new_uids = result.new_user_ids
     new_scrt = result.secret_imported
     nochange = result.unchanged
     print("""
The total number of keys considered for import was:  {0}

With UIDs wholely or partially matching the
 following string:

     {1}
```

```
  Number of keys revoked: {2}
Number of new signatures: {3}
   Number of new subkeys: {4}
  Number of new user IDs: {5}
Number of new secret keys: {6}
Number of unchanged keys: {7}

The key IDs for all considered keys were:
""".format(num_keys, k, new_revs, new_sigs, new_subs, new_uids, new_scrt,
          nochange))
       for i in range(num_keys):
           print(result.imports[i].fpr)
       print("")
   elif result is None:
       print(e)
\end{verbatim}

Both the above example, \href{../examples/howto/pmkey-import.py}{pmkey-import.py}, and a version which
prompts
for an alternative GnuPG home directory, \href{../examples/howto/pmkey-import-alt.py}{pmkey-import-alt.py}, are
available with the other examples and are executable scripts.

Note that while the ProtonMail servers are based on the SKS servers,
their server is related more to their API and is not feature complete
by comparison to the servers in the SKS pool.  One notable difference
being
 that the ProtonMail server does not permit non ProtonMail users
to update their own keys, which could be a vector for attacking
ProtonMail users who may not receive a key's revocation if it had been
compromised.


\subsubsection{Importing with HKP for Python}
\label{sec:org592d7ab}
Performing the same tasks with the \href{https://github.com/Selfnet/hkp4py}{hkp4py module} (available via PyPI)
is not too much different, but does provide a number of options of
benefit to end users.  Not least of which being the ability to perform
some checks on a key before importing it or not.  For instance it may
be the policy of a site or project to only import keys which have not
been revoked.  The hkp4py module permits such checks prior to the
importing of the keys found.

\begin{verbatim}
import gpg
import hkp4py
import sys

c = gpg.Context()
```

```
server = hkp4py.KeyServer("hkps://hkps.pool.sks-keyservers.net")
results = []
keys = []

if len(sys.argv) > 2:
  pattern = " ".join(sys.argv[1:])
elif
 len(sys.argv) == 2:
  pattern = sys.argv[1]
else:
  pattern = input("Enter the pattern to search for keys or user IDs: ")


if pattern is not None:
  try:
    key = server.search(hex(int(pattern, 16)))
    keyed = True
  except ValueError as ve:
    key = server.search(pattern)
    keyed = False

  if key is not None:
    keys.append(key[0])
    if keyed is True:
      try:
        fob = server.search(pattern)
      except:
        fob = None
      if fob is not None:
        keys.append(fob[0])
    else:
      pass
  else:
    pass

  for logrus in pattern.split():
    try:
      key = server.search(hex(int(logrus, 16)))
      hexed = True
    except ValueError as ve:
      key = server.search(logrus)
      hexed = False

    if key is not None:
      keys.append(key[0])
      if hexed is True:
        try:
```

```
 fob = server.search(logrus)
            except:
               fob = None
            if fob is not None:
               keys.append(fob[0])
         else:
            pass
      else:
         pass


if len(keys) > 0:
   for key in keys:
      import_result = c.key_import(key.key_blob)
      results.append(import_result)

for result in results:
   if result is not None and hasattr(result, "considered") is False:
      print(result)
   elif result is not None and hasattr(result, "considered") is True:
      num_keys = len(result.imports)
      new_revs = result.new_revocations
      new_sigs = result.new_signatures
      new_subs = result.new_sub_keys
      new_uids = result.new_user_ids
      new_scrt = result.secret_imported
      nochange = result.unchanged
      print("""
The total number of keys considered for import was:  {0}

  Number of keys revoked:  {1}
Number of new signatures:  {2}
   Number of new subkeys:  {3}
  Number
 of new user IDs:  {4}
Number of new secret keys:  {5}
Number of unchanged keys:  {6}

The key IDs for all considered keys were:
""".format(num_keys, new_revs, new_sigs, new_subs, new_uids, new_scrt,
         nochange))
      for i in range(num_keys):
         print(result.imports[i].fpr)
      print("")
   else:
      pass
\end{verbatim}
```

Since the hkp4py module handles multiple keys just as effectively as one (\texttt{keys} is a list of responses per matching key), the example above is able to do a little bit more with the returned data before anything is actually imported.

\subsubsection{Importing from ProtonMail with HKP for Python}
\label{sec:org3966a76}
Though this can provide certain benefits even when working with ProtonMail, the scope is somewhat constrained there due to the limitations of the ProtonMail keyserver.

For instance, searching the SKS keyserver pool for the term "gnupg" produces hundreds of results from any time the word appears in any part of
a user ID. Performing the same search on the ProtonMail keyserver returns zero results, even though there are at least two test accounts which include it as part of the username.

The cause of this discrepancy is the deliberate configuration of that server by ProtonMail to require an exact match of the full email address of the ProtonMail user whose key is being requested. Presumably this is intended to reduce breaches of privacy of their users as an email address must already be known before a key for that address can be obtained.

\begin{enumerate}
\item Import from ProtonMail via HKP for Python Example no. 1
\label{sec:org6cd15c3}
The following script is available with the rest of the examples under the somewhat less than original name, \texttt{pmkey-import-hkp.py}.

\begin{verbatim}
import gpg
import hkp4py
import os.path
import sys

print("""
This script searches the ProtonMail key server for the specified key and imports it.

Usage: pmkey-import-hkp.py [search strings]
""")

c

```
 = gpg.Context(armor=True)
server = hkp4py.KeyServer("hkps://api.protonmail.ch")
keyterms = []
ksearch = []
allkeys = []
results = []
paradox = []
homeless = None

if len(sys.argv) > 2:
  keyterms = sys.argv[1:]
elif len(sys.argv) == 2:
  keyterm = sys.argv[1]
  keyterms.append(keyterm)
else:
  key_term = input("Enter the key ID, UID or search string: ")
  keyterms = key_term.split()

for keyterm in keyterms:
  if keyterm.count("@") == 2 and keyterm.startswith("@") is True:
     ksearch.append(keyterm[1:])
     ksearch.append(keyterm[1:])
     ksearch.append(keyterm[1:])
  elif keyterm.count("@") == 1 and keyterm.startswith("@") is True:
     ksearch.append("{0}@protonmail.com".format(keyterm[1:]))
     ksearch.append("{0}@protonmail.ch".format(keyterm[1:]))
     ksearch.append("{0}@pm.me".format(keyterm[1:]))
  elif keyterm.count("@") == 0:
     ksearch.append("{0}@protonmail.com".format(keyterm))
     ksearch.append("{0}@protonmail.ch".format(keyterm))
      ksearch.append("{0}@pm.me".format(keyterm))
  elif keyterm.count("@") == 2 and keyterm.startswith("@") is False:
     uidlist = keyterm.split("@")
     for uid in uidlist:
        ksearch.append("{0}@protonmail.com".format(uid))
        ksearch.append("{0}@protonmail.ch".format(uid))
        ksearch.append("{0}@pm.me".format(uid))
  elif keyterm.count("@") > 2:
     uidlist = keyterm.split("@")
     for uid in uidlist:
        ksearch.append("{0}@protonmail.com".format(uid))
        ksearch.append("{0}@protonmail.ch".format(uid))
        ksearch.append("{0}@pm.me".format(uid))
  else:
     ksearch.append(keyterm)

for k in ksearch:
  print("Checking for key for: {0}".format(k))
```

```
  try:
     keys = server.search(k)
     if isinstance(keys, list) is True:
        for key in keys:
           allkeys.append(key)
           try:
              import_result = c.key_import(key.key_blob)

 except Exception as e:
              import_result = c.key_import(key.key)
     else:
        paradox.append(keys)
        import_result = None
  except Exception as e:
     import_result = None
  results.append(import_result)

for result in results:
  if result is not None and hasattr(result, "considered") is False:
     print("{0} for {1}".format(result.decode(), k))
  elif result is not None and hasattr(result, "considered") is True:
     num_keys = len(result.imports)
     new_revs = result.new_revocations
     new_sigs = result.new_signatures
     new_subs = result.new_sub_keys
     new_uids = result.new_user_ids
     new_scrt = result.secret_imported
     nochange = result.unchanged
     print("""
The total number of keys considered for import was:  {0}

With UIDs wholely or partially matching the following string:

     {1}

  Number of keys revoked:  {2}
Number of new signatures:  {3}
   Number of new subkeys:  {4}

  Number of new user IDs:  {5}
Number of new secret keys:  {6}
Number of unchanged keys:  {7}

The key IDs for all considered keys were:
""".format(num_keys, k, new_revs, new_sigs, new_subs, new_uids, new_scrt,
        nochange))
     for i in range(num_keys):
        print(result.imports[i].fpr)
```

```
      print("")
   elif result is None:
      pass
\end{verbatim}


\item Import from ProtonMail via HKP for Python Example no. 2
\label{sec:org3b674e5}
Like its counterpart above, this script can also be found with the
rest of the examples, by the name pmkey-import-hkp-alt.py.

With this script a modicum of effort has been made to treat anything
passed as a \texttt{homedir} which either does not exist or which is not a
directory, as also being a pssible user ID to check for.  It's not
guaranteed to pick up on all such cases, but it should cover most of
them.

\begin{verbatim}
import gpg
import hkp4py
import os.path
import sys

print("""
This script searches the ProtonMail key server
 for the specified key and
imports it.  Optionally enables specifying a different GnuPG home directory.

Usage:  pmkey-import-hkp.py [homedir] [search string]
  or:  pmkey-import-hkp.py [search string]
""")

c = gpg.Context(armor=True)
server = hkp4py.KeyServer("hkps://api.protonmail.ch")
keyterms = []
ksearch = []
allkeys = []
results = []
paradox = []
homeless = None

if len(sys.argv) > 3:
   homedir = sys.argv[1]
   keyterms = sys.argv[2:]
elif len(sys.argv) == 3:
   homedir = sys.argv[1]
   keyterm = sys.argv[2]
   keyterms.append(keyterm)
```

```
elif len(sys.argv) == 2:
  homedir = ""
  keyterm = sys.argv[1]
  keyterms.append(keyterm)
else:
  keyterm = input("Enter the key ID, UID or search string: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
  keyterms.append(keyterm)

if len(homedir) == 0:
  homedir = None
  homeless = False

if homedir is not None:
  if homedir.startswith("~"):
     if os.path.exists(os.path.expanduser(homedir))
 is True:
        if os.path.isdir(os.path.expanduser(homedir)) is True:
           c.home_dir = os.path.realpath(os.path.expanduser(homedir))
        else:
           homeless = True
     else:
        homeless = True
  elif os.path.exists(os.path.realpath(homedir)) is True:
     if os.path.isdir(os.path.realpath(homedir)) is True:
        c.home_dir = os.path.realpath(homedir)
     else:
        homeless = True
  else:
     homeless = True

# First check to see if the homedir really is a homedir and if not, treat it as
# a search string.
if homeless is True:
  keyterms.append(homedir)
  c.home_dir = None
else:
  pass

for keyterm in keyterms:
  if keyterm.count("@") == 2 and keyterm.startswith("@") is True:
     ksearch.append(keyterm[1:])
     ksearch.append(keyterm[1:])
     ksearch.append(keyterm[1:])
  elif keyterm.count("@") == 1 and keyterm.startswith("@") is True:
     ksearch.append("{0}@protonmail.com".format(keyterm[1:]))
      ksearch.append("{0}@protonmail.ch".format(keyterm[1:]))
     ksearch.append("{0}@pm.me".format(keyterm[1:]))
```

```
  elif keyterm.count("@") == 0:
    ksearch.append("{0}@protonmail.com".format(keyterm))
    ksearch.append("{0}@protonmail.ch".format(keyterm))
    ksearch.append("{0}@pm.me".format(keyterm))
  elif keyterm.count("@") == 2 and keyterm.startswith("@") is False:
    uidlist = keyterm.split("@")
    for uid in uidlist:
      ksearch.append("{0}@protonmail.com".format(uid))
      ksearch.append("{0}@protonmail.ch".format(uid))
      ksearch.append("{0}@pm.me".format(uid))
  elif keyterm.count("@") > 2:
    uidlist = keyterm.split("@")
    for uid in uidlist:
      ksearch.append("{0}@protonmail.com".format(uid))
      ksearch.append("{0}@protonmail.ch".format(uid))
      ksearch.append("{0}@pm.me".format(uid))
  else:
    ksearch.append(keyterm)

for k in ksearch:
  print("Checking
 for key for: {0}".format(k))
  try:
    keys = server.search(k)
    if isinstance(keys, list) is True:
      for key in keys:
        allkeys.append(key)
        try:
          import_result = c.key_import(key.key_blob)
        except Exception as e:
          import_result = c.key_import(key.key)
    else:
      paradox.append(keys)
      import_result = None
  except Exception as e:
    import_result = None
  results.append(import_result)

for result in results:
  if result is not None and hasattr(result, "considered") is False:
    print("{0} for {1}".format(result.decode(), k))
  elif result is not None and hasattr(result, "considered") is True:
    num_keys = len(result.imports)
    new_revs = result.new_revocations
    new_sigs = result.new_signatures
    new_subs = result.new_sub_keys
    new_uids = result.new_user_ids
    new_scrt = result.secret_imported
```

```
        nochange = result.unchanged
        print("""
The total number of keys considered for import was:  {0}

With UIDs wholely or partially matching the following string:

      {1}

  Number of keys revoked:  {2}
Number of new signatures:  {3}
   Number of new subkeys:  {4}
  Number of new user IDs:  {5}
Number of new secret keys:  {6}
Number of unchanged keys:  {7}

The key IDs for all considered keys were:
""".format(num_keys, k, new_revs, new_sigs, new_subs, new_uids, new_scrt,
           nochange))
        for i in range(num_keys):
            print(result.imports[i].fpr)
        print("")
    elif result is None:
        pass
\end{verbatim}
\end{enumerate}


\subsection{Exporting keys}
\label{sec:org4596a77}
Exporting keys remains a reasonably simple task, but has been
separated into three different functions for the OpenPGP cryptographic
engine.  Two of those functions are for exporting public keys and the
third is for exporting secret keys.


\subsubsection{Exporting
 public keys}
\label{sec:org873704f}
There are two methods of exporting public keys, both of which are very
similar to the other.  The default method, \texttt{key\_export()}, will export
a public key or keys matching a specified pattern as normal.  The
alternative, the \texttt{key\_export\_minimal()} method, will do the same thing
except producing a minimised output with extra signatures and third
party signatures or certifications removed.

\begin{verbatim}
import gpg
import os.path
```

```
import sys

print("""
This script exports one or more public keys.
""")

c = gpg.Context(armor=True)

if len(sys.argv) >= 4:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the
 GPG configuration directory path (optional): ")
else:
  keyfile = input("Enter the path and filename to save the secret key to: ")
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if homedir.startswith("~"):
  if os.path.exists(os.path.expanduser(homedir)) is True:
    c.home_dir = os.path.expanduser(homedir)
  else:
    pass
elif os.path.exists(homedir) is True:
  c.home_dir = homedir
else:
  pass

try:
  result = c.key_export(pattern=logrus)
except:
  result = c.key_export(pattern=None)

if result is not None:
  with open(keyfile, "wb") as f:
    f.write(result)
else:
  pass
\end{verbatim}
```

It should be noted that the result will only return \texttt{None} when a
search pattern has been entered, but has not matched any keys. When
the search pattern itself is set to \texttt{None} this triggers the exporting
of the entire public keybox.

\begin{verbatim}
import
 gpg
import os.path
import sys

print("""
This script exports one or more public keys in minimised form.
""")

c = gpg.Context(armor=True)

if len(sys.argv) >= 4:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
else:
  keyfile = input("Enter the path and filename to save the secret key to: ")
  logrus = input("Enter the UID matching the key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if homedir.startswith("~"):
  if os.path.exists(os.path.expanduser(homedir)) is True:
     c.home_dir = os.path.expanduser(homedir)
  else:
     pass
elif os.path.exists(homedir)
 is True:
  c.home_dir = homedir
else:
  pass

try:
  result = c.key_export_minimal(pattern=logrus)
except:

```
  result = c.key_export_minimal(pattern=None)

if result is not None:
  with open(keyfile, "wb") as f:
     f.write(result)
else:
  pass
\end{verbatim}


\subsubsection{Exporting secret keys}
\label{sec:org6c28d3d}
Exporting secret keys is, functionally, very similar to exporting
public keys; save for the invocation of \texttt{pinentry} via \texttt{gpg-agent} in
order to securely enter the key's passphrase and authorise the export.

The following example exports the secret key to a file which is then
set with the same permissions as the output files created by the
command line secret key export options.

\begin{verbatim}
import gpg
import os
import os.path
import sys

print("""
This script exports one or more secret keys.

The gpg-agent and pinentry are invoked to authorise the export.
""")

c = gpg.Context(armor=True)

if len(sys.argv) >= 4:
  keyfile
 = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
else:
```

```
  keyfile = input("Enter the path and filename to save the secret key to: ")
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if len(homedir) == 0:
  homedir = None
elif homedir.startswith("~"):
  userdir = os.path.expanduser(homedir)
  if os.path.exists(userdir) is True:
     homedir = os.path.realpath(userdir)
  else:
     homedir = None
else:
  homedir = os.path.realpath(homedir)

if os.path.exists(homedir) is False:
  homedir =
 None
else:
  if os.path.isdir(homedir) is False:
     homedir = None
  else:
     pass

if homedir is not None:
  c.home_dir = homedir
else:
  pass

try:
  result = c.key_export_secret(pattern=logrus)
except:
  result = c.key_export_secret(pattern=None)

if result is not None:
  with open(keyfile, "wb") as f:
     f.write(result)
  os.chmod(keyfile, 0o600)
else:
  pass
\end{verbatim}
```

Alternatively the approach of the following script can be used. This
longer example saves the exported secret key(s) in files in the GnuPG
home directory, in addition to setting the file permissions as only
readable and writable by the user. It also exports the secret key(s)
twice in order to output both GPG binary (\texttt{.gpg}) and ASCII armoured
(\texttt{.asc}) files.

```
\begin{verbatim}
import gpg
import os
import os.path
import subprocess
import sys

print("""
This script exports one or more secret keys as both ASCII armored and binary
file formats, saved in files within the
 user's GPG home directory.

The gpg-agent and pinentry are invoked to authorise the export.
""")

if sys.platform == "win32":
  gpgconfcmd = "gpgconf.exe --list-dirs homedir"
else:
  gpgconfcmd = "gpgconf --list-dirs homedir"

a = gpg.Context(armor=True)
b = gpg.Context()
c = gpg.Context()

if len(sys.argv) >= 4:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = sys.argv[3]
elif len(sys.argv) == 3:
  keyfile = sys.argv[1]
  logrus = sys.argv[2]
  homedir = input("Enter the GPG configuration directory path (optional): ")
elif len(sys.argv) == 2:
  keyfile = sys.argv[1]
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")
else:
  keyfile = input("Enter the filename to save the secret key to: ")
  logrus = input("Enter the UID matching the secret key(s) to export: ")
  homedir = input("Enter the GPG configuration directory path (optional): ")

if len(homedir)
 == 0:
  homedir = None
elif homedir.startswith("~"):
  userdir = os.path.expanduser(homedir)
  if os.path.exists(userdir) is True:
```

```
    homedir = os.path.realpath(userdir)
  else:
    homedir = None
else:
  homedir = os.path.realpath(homedir)

if os.path.exists(homedir) is False:
  homedir = None
else:
  if os.path.isdir(homedir) is False:
    homedir = None
  else:
    pass

if homedir is not None:
  c.home_dir = homedir
else:
  pass

if c.home_dir is not None:
  if c.home_dir.endswith("/"):
    gpgfile = "{0}{1}.gpg".format(c.home_dir, keyfile)
    ascfile = "{0}{1}.asc".format(c.home_dir, keyfile)
  else:
    gpgfile = "{0}/{1}.gpg".format(c.home_dir, keyfile)
    ascfile = "{0}/{1}.asc".format(c.home_dir, keyfile)
else:
  if os.path.exists(os.environ["GNUPGHOME"]) is True:
    hd = os.environ["GNUPGHOME"]
  else:
    try:
      hd = subprocess.getoutput(gpgconfcmd)
    except:
      process = subprocess.Popen(gpgconfcmd.split(),
                                 stdout=subprocess.PIPE)
      procom = process.communicate()
      if sys.version_info[0] == 2:
        hd = procom[0].strip()
      else:
        hd = procom[0].decode().strip()
  gpgfile = "{0}/{1}.gpg".format(hd, keyfile)
  ascfile = "{0}/{1}.asc".format(hd, keyfile)

try:
  a_result = a.key_export_secret(pattern=logrus)
  b_result = b.key_export_secret(pattern=logrus)
except:
  a_result = a.key_export_secret(pattern=None)
```

```
  b_result = b.key_export_secret(pattern=None)

if a_result is not None:
  with open(ascfile, "wb") as f:
    f.write(a_result)
  os.chmod(ascfile, 0o600)
else:
  pass

if b_result is not None:
  with open(gpgfile, "wb") as f:
    f.write(b_result)
  os.chmod(gpgfile, 0o600)
else:
  pass
\end{verbatim}
```

\subsubsection{Sending public keys to the SKS Keyservers}
\label{sec:org82d4958}
As with the previous section on importing
keys, the \texttt{hkp4py} module
adds another option with exporting keys in order to send them to the
public keyservers.

The following example demonstrates how this may be done.

```
\begin{verbatim}
import gpg
import hkp4py
import os.path
import sys

print("""
This script sends one or more public keys to the SKS keyservers and is
essentially a slight variation on the export-key.py script.
""")

c = gpg.Context(armor=True)
server = hkp4py.KeyServer("hkps://hkps.pool.sks-keyservers.net")

if len(sys.argv) > 2:
  logrus = " ".join(sys.argv[1:])
elif len(sys.argv) == 2:
  logrus = sys.argv[1]
else:
  logrus = input("Enter the UID matching the key(s) to send: ")
```

```
if len(logrus) > 0:
  try:
     export_result = c.key_export(pattern=logrus)
  except Exception as e:
     print(e)
     export_result = None
else:
  export_result = c.key_export(pattern=None)

if export_result is not None:
  try:
     try:
        send_result = server.add(export_result)
     except:
         send_result = server.add(export_result.decode())
     if send_result is not None:
        print(send_result)
     else:
        pass
  except Exception as e:
     print(e)
else:
  pass
\end{verbatim}

An expanded version of this script with additional functions for
specifying an alternative homedir location is in the examples
directory as \texttt{send-key-to-keyserver.py}.

The \texttt{hkp4py} module appears to handle both string and byte literal text
data equally well, but the GPGME bindings deal primarily with byte
literal data only and so this script sends in that format first, then
tries the string literal form.


\section{Basic Functions}
\label{sec:orgb40b488}
The most frequently called features of any cryptographic library will
be the most fundamental tasks for encryption software.  In this
section we will look at how to programmatically encrypt data, decrypt
it, sign it and verify signatures.


\subsection{Encryption}
\label{sec:org3170365}
Encrypting
 is very straight forward.  In the first example below the
message, \texttt{text}, is encrypted to a single recipient's key.  In the
```

second example the message will be encrypted to multiple recipients.

\subsubsection{Encrypting to one key}
\label{sec:org8098c64}
Once the the Context is set the main issues with encrypting data is
essentially reduced to key selection and the keyword arguments
specified in the \texttt{gpg.Context().encrypt()} method.

Those keyword arguments are: \texttt{recipients}, a list of keys encrypted to
(covered in greater detail in the following section); \texttt{sign}, whether
or not to sign the plaintext data, see subsequent sections on signing
and verifying signatures below (defaults to \texttt{True}); \texttt{sink}, to write
results or partial results to a secure sink instead of returning it
(defaults to \texttt{None}); \texttt{passphrase}, only used when utilising symmetric
encryption (defaults to \texttt{None}); \texttt{always_trust}, used to override
 the
trust model settings for recipient keys (defaults to \texttt{False});
\texttt{add_encrypt_to}, utilises any preconfigured \texttt{encrypt-to} or
\texttt{default-key} settings in the user's \texttt{gpg.conf} file (defaults to
\texttt{False}); \texttt{prepare}, prepare for encryption (defaults to \texttt{False});
\texttt{expect_sign}, prepare for signing (defaults to \texttt{False}); \texttt{compress},
compresses the plaintext prior to encryption (defaults to \texttt{True}).

\begin{verbatim}
import gpg

a_key = "0x12345678DEADBEEF"
text = b"""Some text to test with.

Since the text in this case must be bytes, it is most likely that
the input form will be a separate file which is opened with "rb"
as this is the simplest method of obtaining the correct data format.
"""

c = gpg.Context(armor=True)
rkey = list(c.keylist(pattern=a_key, secret=False))
ciphertext, result, sign_result = c.encrypt(text, recipients=rkey, sign=False)

with open("secret_plans.txt.asc", "wb") as afile:
    afile.write(ciphertext)
\end{verbatim}

Though this is even more likely to be used like this; with the
plaintext input read from a file, the recipient keys used for
encryption regardless of key trust status and the encrypted output
also encrypted to any preconfigured keys set in the \texttt{gpg.conf} file:

\begin{verbatim}
import gpg

a_key = "0x12345678DEADBEEF"

with open("secret_plans.txt", "rb") as afile:
  text = afile.read()

c = gpg.Context(armor=True)
rkey = list(c.keylist(pattern=a_key, secret=False))
ciphertext, result, sign_result = c.encrypt(text, recipients=rkey, sign=True,
                                always_trust=True,
                                add_encrypt_to=True)

with open("secret_plans.txt.asc", "wb") as afile:
  afile.write(ciphertext)
\end{verbatim}

If the \texttt{recipients} parameter is empty then the plaintext is encrypted
symmetrically. If no \texttt{passphrase} is supplied as a parameter or via a
callback registered with
 the \texttt{Context()} then an out-of-band prompt
for the passphrase via pinentry will be invoked.

\subsubsection{Encrypting to multiple keys}
\label{sec:orgdcf6e47}
Encrypting to multiple keys essentially just expands upon the key
selection process and the recipients from the previous examples.

The following example encrypts a message (\texttt{text}) to everyone with an
email address on the \texttt{gnupg.org} domain,\footnote{You probably don't really want to do this. Searching the
keyservers for "gnupg.org" produces over 400 results, the majority of
which aren't actually at the gnupg.org domain, but just included a
comment regarding the project in their key somewhere.} but does \emph{not} encrypt
to a default key or other key which is configured to normally encrypt
to.

\begin{verbatim}
import gpg

text = b"""Oh look, another test message.

The same rules apply as with the previous example and more likely
than not, the message will actually be drawn from reading the
contents
 of a file or, maybe, from entering data at an input()
prompt.

Since the text in this case must be bytes, it is most likely that
the input form will be a separate file which is opened with "rb"
as this is the simplest method of obtaining the correct data
format.
"""

c = gpg.Context(armor=True)
rpattern = list(c.keylist(pattern="@gnupg.org", secret=False))
logrus = []

for i in range(len(rpattern)):
  if rpattern[i].can_encrypt == 1:
    logrus.append(rpattern[i])

ciphertext, result, sign_result = c.encrypt(text, recipients=logrus,
                                sign=False, always_trust=True)

with open("secret_plans.txt.asc", "wb") as afile:
  afile.write(ciphertext)
\end{verbatim}

All it would take to change the above example to sign the message
and also encrypt the message to any configured default keys would
be to change the \texttt{c.encrypt} line to this:

\begin{verbatim}
ciphertext, result, sign_result = c.encrypt(text, recipients=logrus,

                        always_trust=True,
                                add_encrypt_to=True)
\end{verbatim}

The only keyword arguments requiring modification are those for which
the default values are changing. The default value of \texttt{sign} is
\texttt{True}, the default of \texttt{always_trust} is \texttt{False}, the default of
\texttt{add_encrypt_to} is \texttt{False}.

If \texttt{always_trust} is not set to \texttt{True} and any of the recipient keys
are not trusted (e.g. not signed or locally signed) then the
encryption will raise an error. It is possible to mitigate this
somewhat with something more like this:

\begin{verbatim}
import gpg

with open("secret_plans.txt.asc", "rb") as afile:
  text = afile.read()

```
c = gpg.Context(armor=True)
rpattern = list(c.keylist(pattern="@gnupg.org", secret=False))
logrus = []

for i in range(len(rpattern)):
  if rpattern[i].can_encrypt == 1:
     logrus.append(rpattern[i])

  try:
     ciphertext, result,
 sign_result = c.encrypt(text, recipients=logrus,
                                      add_encrypt_to=True)
  except gpg.errors.InvalidRecipients as e:
     for i in range(len(e.recipients)):
        for n in range(len(logrus)):
           if logrus[n].fpr == e.recipients[i].fpr:
              logrus.remove(logrus[n])
           else:
              pass
     try:
        ciphertext, result, sign_result = c.encrypt(text,
                                          recipients=logrus,
                                          add_encrypt_to=True)
        with open("secret_plans.txt.asc", "wb") as afile:
           afile.write(ciphertext)
     except:
        pass
\end{verbatim}

This will attempt to encrypt to all the keys searched for, then remove
invalid recipients if it fails and try again.


\subsection{Decryption}
\label{sec:org1282b3d}
Decrypting something encrypted to a key in one's secret
 keyring is
fairly straight forward.

In this example code, however, preconfiguring either \texttt{gpg.Context()}
or \texttt{gpg.core.Context()} as \texttt{c} is unnecessary because there is no need
to modify the Context prior to conducting the decryption and since the
Context is only used once, setting it to \texttt{c} simply adds lines for no
gain.

\begin{verbatim}
import gpg
```

```
ciphertext = input("Enter path and filename of encrypted file: ")
newfile = input("Enter path and filename of file to save decrypted data to: ")

with open(ciphertext, "rb") as cfile:
  try:
     plaintext, result, verify_result = gpg.Context().decrypt(cfile)
  except gpg.errors.GPGMEError as e:
     plaintext = None
     print(e)

if plaintext is not None:
  with open(newfile, "wb") as nfile:
   nfile.write(plaintext)
  else:
     pass
\end{verbatim}

The data available in \texttt{plaintext} in this example is the decrypted
content as a byte object, the recipient key IDs and algorithms
 in
\texttt{result} and the results of verifying any signatures of the data in
\texttt{verify\_result}.

If \texttt{gpg.Context().decrypt(cfile, verify=False)} is called instead,
then \texttt{verify\_result} will be returned as \texttt{None} and the rest remains
as described here.


\subsection{Signing text and files}
\label{sec:org59f1262}
The following sections demonstrate how to specify keys to sign with.


\subsubsection{Signing key selection}
\label{sec:org909cb3c}
By default GPGME and the Python bindings will use the default key
configured for the user invoking the GPGME API.  If there is no
default key specified and there is more than one secret key available
it may be necessary to specify the key or keys with which to sign
messages and files.

\begin{verbatim}
import gpg

logrus = input("Enter the email address or string to match signing keys to: ")
hancock = gpg.Context().keylist(pattern=logrus, secret=True)
sig_src = list(hancock)
```

\end{verbatim}

The signing examples in the
following sections include the explicitly
designated \texttt{signers} parameter in two of the five examples; once where
the resulting signature would be ASCII armoured and once where it
would not be armoured.

While it would be possible to enter a key ID or fingerprint here to
match a specific key, it is not possible to enter two fingerprints and
match two keys since the patten expects a string, bytes or None and
not a list. A string with two fingerprints won't match any single
key.

\subsubsection{Normal or default signing messages or files}
\label{sec:org6ee259d}
The normal or default signing process is essentially the same as is
most often invoked when also encrypting a message or file. So when
the encryption component is not utilised, the result is to produce an
encoded and signed output which may or may not be ASCII armoured and
which may or may not also be compressed.

By default compression will be used unless GnuPG detects that the
plaintext is already compressed. ASCII armouring
will be determined
according to the value of \texttt{gpg.Context().armor}.

The compression algorithm is selected in much the same way as the
symmetric encryption algorithm or the hash digest algorithm is when
multiple keys are involved; from the preferences saved into the key
itself or by comparison with the preferences with all other keys
involved.

\begin{verbatim}
import gpg

text0 = """Declaration of ... something.

"""
text = text0.encode()

c = gpg.Context(armor=True, signers=sig_src)
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.NORMAL)

with open("/path/to/statement.txt.asc", "w") as afile:
  afile.write(signed_data.decode())
\end{verbatim}

Though everything in this example is accurate, it is more likely that
reading the input data from another file and writing the result to a
new file will be performed more like the way it is done in the next
example. Even if the output format is ASCII armoured.

\begin{verbatim}
import gpg

with open("/path/to/statement.txt",
 "rb") as tfile:
   text = tfile.read()

c = gpg.Context()
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.NORMAL)

with open("/path/to/statement.txt.sig", "wb") as afile:
   afile.write(signed_data)
\end{verbatim}

\subsubsection{Detached signing messages and files}
\label{sec:org51049d4}
Detached signatures will often be needed in programmatic uses of
GPGME, either for signing files (e.g. tarballs of code releases) or as
a component of message signing (e.g. PGP/MIME encoded email).

\begin{verbatim}
import gpg

text0 = """Declaration of ... something.

"""
text = text0.encode()

c = gpg.Context(armor=True)
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.DETACH)

with open("/path/to/statement.txt.asc", "w") as afile:
   afile.write(signed_data.decode())
\end{verbatim}

As with normal signatures, detached signatures are best handled as
byte literals, even when the output is ASCII armoured.

\begin{verbatim}
import gpg

```
with open("/path/to/statement.txt",
 "rb") as tfile:
   text = tfile.read()

c = gpg.Context(signers=sig_src)
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.DETACH)

with open("/path/to/statement.txt.sig", "wb") as afile:
   afile.write(signed_data)
\end{verbatim}
```

```
\subsubsection{Clearsigning messages or text}
\label{sec:orgf528a20}
Though PGP/in-line messages are no longer encouraged in favour of
PGP/MIME, there is still sometimes value in utilising in-line
signatures.  This is where clear-signed messages or text is of value.

\begin{verbatim}
import gpg

text0 = """Declaration of ... something.

"""
text = text0.encode()

c = gpg.Context()
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.CLEAR)

with open("/path/to/statement.txt.asc", "w") as afile:
   afile.write(signed_data.decode())
\end{verbatim}

In spite of the appearance of a clear-signed message, the data handled
by GPGME in signing it must still be byte literals.

\begin{verbatim}
import gpg

with open("/path/to/statement.txt",
 "rb") as tfile:
   text = tfile.read()

c = gpg.Context()
signed_data, result = c.sign(text, mode=gpg.constants.sig.mode.CLEAR)

with open("/path/to/statement.txt.asc", "wb") as afile:
   afile.write(signed_data)
```

\end{verbatim}

\subsection{Signature verification}
\label{sec:org6cd81af}
Essentially there are two principal methods of verification of a signature. The first of these is for use with the normal or default signing method and for clear-signed messages. The second is for use with files and data with detached signatures.

The following example is intended for use with the default signing method where the file was not ASCII armoured:

\begin{verbatim}
import gpg
import time

filename = "statement.txt"
gpg_file = "statement.txt.gpg"

c = gpg.Context()

try:
  data, result = c.verify(open(gpg_file))
  verified = True
except gpg.errors.BadSignatures as e:
  verified = False
  print(e)

if verified is True:
  for i in range(len(result.signatures)):

    sign = result.signatures[i]
     print("""Good signature from:
{0}
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
       time.ctime(sign.timestamp)))
else:
  pass
\end{verbatim}

Whereas this next example, which is almost identical would work with normal ASCII armoured files and with clear-signed files:

\begin{verbatim}
import gpg

```
import time

filename = "statement.txt"
asc_file = "statement.txt.asc"

c = gpg.Context()

try:
  data, result = c.verify(open(asc_file))
  verified = True
except gpg.errors.BadSignatures as e:
  verified = False
  print(e)

if verified is True:
  for i in range(len(result.signatures)):
    sign = result.signatures[i]
    print("""Good signature from:
{0}
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
       time.ctime(sign.timestamp)))
else:
  pass
\end{verbatim}

In both of the previous examples it is also possible to compare the
original data that was signed
 against the signed data in \texttt{data} to see
if it matches with something like this:

\begin{verbatim}
with open(filename, "rb") as afile:
  text = afile.read()

if text == data:
  print("Good signature.")
else:
  pass
\end{verbatim}

The following two examples, however, deal with detached signatures.
With his method of verification the data that was signed does not get
returned since it is already being explicitly referenced in the first
argument of \texttt{c.verify}.  So \texttt{data} is \texttt{None} and only the information
in \texttt{result} is available.
```

```
\begin{verbatim}
import gpg
import time

filename = "statement.txt"
sig_file = "statement.txt.sig"

c = gpg.Context()

try:
  data, result = c.verify(open(filename), open(sig_file))
  verified = True
except gpg.errors.BadSignatures as e:
  verified = False
  print(e)

if verified is True:
  for i in range(len(result.signatures)):
    sign = result.signatures[i]
    print("""Good signature from:
{0}
with
 key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
       time.ctime(sign.timestamp)))
else:
  pass
\end{verbatim}

\begin{verbatim}
import gpg
import time

filename = "statement.txt"
asc_file = "statement.txt.asc"

c = gpg.Context()

try:
  data, result = c.verify(open(filename), open(asc_file))
  verified = True
except gpg.errors.BadSignatures as e:
  verified = False
  print(e)

if verified is True:
  for i in range(len(result.signatures)):
```

```
      sign = result.signatures[i]
      print("""Good signature from:
{0}
with key {1}
made at {2}
""".format(c.get_key(sign.fpr).uids[0].uid, sign.fpr,
         time.ctime(sign.timestamp)))
else:
  pass
\end{verbatim}


\section{Creating keys and subkeys}
\label{sec:org754c6df}
The one thing, aside from GnuPG itself, that GPGME depends on, of
course, is the keys themselves.  So it is necessary to be able to
generate them and modify them by adding subkeys, revoking or disabling
them, sometimes
 deleting them and doing the same for user IDs.

In the following examples a key will be created for the world's
greatest secret agent, Danger Mouse.  Since Danger Mouse is a secret
agent he needs to be able to protect information to \texttt{SECRET} level
clearance, so his keys will be 3072-bit keys.

The pre-configured \texttt{gpg.conf} file which sets cipher, digest and other
preferences contains the following configuration parameters:

\begin{verbatim}
expert
allow-freeform-uid
allow-secret-key-import
trust-model tofu+pgp
tofu-default-policy unknown
enable-large-rsa
enable-dsa2
cert-digest-algo SHA512
default-preference-list TWOFISH CAMELLIA256 AES256 CAMELLIA192 AES192 CAMELLIA128 AES
BLOWFISH IDEA CAST5 3DES SHA512 SHA384 SHA256 SHA224 RIPEMD160 SHA1 ZLIB BZIP2 ZIP
Uncompressed
personal-cipher-preferences TWOFISH CAMELLIA256 AES256 CAMELLIA192 AES192 CAMELLIA128 AES
BLOWFISH IDEA CAST5 3DES
personal-digest-preferences SHA512 SHA384 SHA256 SHA224 RIPEMD160 SHA1
personal-compress-preferences
 ZLIB BZIP2 ZIP Uncompressed
\end{verbatim}
```

\subsection{Primary key}
\label{sec:org0185c23}
Generating a primary key uses the \texttt{create_key} method in a Context.
It contains multiple arguments and keyword arguments, including:
\texttt{userid}, \texttt{algorithm}, \texttt{expires_in}, \texttt{expires}, \texttt{sign}, \texttt{encrypt},
\texttt{certify}, \texttt{authenticate}, \texttt{passphrase} and \texttt{force}. The defaults for
all of those except \texttt{userid}, \texttt{algorithm}, \texttt{expires_in}, \texttt{expires} and
\texttt{passphrase} is \texttt{False}. The defaults for \texttt{algorithm} and
\texttt{passphrase} is \texttt{None}. The default for \texttt{expires_in} is \texttt{0}. The
default for \texttt{expires} is \texttt{True}. There is no default for \texttt{userid}.

If \texttt{passphrase} is left as \texttt{None} then the key will not be generated
with a passphrase, if \texttt{passphrase} is set to a string then that will
be the passphrase and if
 \texttt{passphrase} is set to \texttt{True} then gpg-agent
will launch pinentry to prompt for a passphrase. For the sake of
convenience, these examples will keep \texttt{passphrase} set to \texttt{None}.

\begin{verbatim}
import gpg

c = gpg.Context()

c.home_dir = "~/.gnupg-dm"
userid = "Danger Mouse <dm@secret.example.net>"

dmkey = c.create_key(userid, algorithm="rsa3072", expires_in=31536000,
                     sign=True, certify=True)
\end{verbatim}

One thing to note here is the use of setting the \texttt{c.home_dir}
parameter. This enables generating the key or keys in a different
location. In this case to keep the new key data created for this
example in a separate location rather than adding it to existing and
active key store data. As with the default directory, \texttt{\textasciitilde{}/.gnupg}, any
temporary or separate directory needs the permissions set to only
permit access by the directory owner. On posix systems this means
setting the directory permissions to
 700.

The \texttt{temp-homedir-config.py} script in the HOWTO examples directory
will create an alternative homedir with these configuration options
already set and the correct directory and file permissions.

The successful generation of the key can be confirmed via the returned
\texttt{GenkeyResult} object, which includes the following data:

\begin{verbatim}

```
print("""
Fingerprint: {0}
Primary Key: {1}
 Public Key: {2}
 Secret Key: {3}
Sub Key: {4}
User IDs: {5}
""".format(dmkey.fpr, dmkey.primary, dmkey.pubkey, dmkey.seckey, dmkey.sub,
        dmkey.uid))
\end{verbatim}

Alternatively the information can be confirmed using the command line
program:

\begin{verbatim}
bash-4.4$ gpg --homedir ~/.gnupg-dm -K
~/.gnupg-dm/pubring.kbx
----------------------
sec   rsa3072 2018-03-15 [SC] [expires: 2019-03-15]
    177B7C25DB99745EE2EE13ED026D2F19E99E63AA
uid           [ultimate] Danger Mouse <dm@secret.example.net>

bash-4.4$
\end{verbatim}

As with generating keys manually,
 to preconfigure expanded preferences
for the cipher, digest and compression algorithms, the \texttt{gpg.conf} file
must contain those details in the home directory in which the new key
is being generated.  I used a cut down version of my own \texttt{gpg.conf}
file in order to be able to generate this:

\begin{verbatim}
bash-4.4$ gpg --homedir ~/.gnupg-dm --edit-key 177B7C25DB99745EE2EE13ED026D2F19E99E63AA showpref
quit
Secret key is available.

sec  rsa3072/026D2F19E99E63AA
   created: 2018-03-15  expires: 2019-03-15  usage: SC
   trust: ultimate      validity: ultimate
[ultimate] (1). Danger Mouse <dm@secret.example.net>

[ultimate] (1). Danger Mouse <dm@secret.example.net>
   Cipher: TWOFISH, CAMELLIA256, AES256, CAMELLIA192, AES192, CAMELLIA128, AES, BLOWFISH,
IDEA, CAST5, 3DES
   Digest: SHA512, SHA384, SHA256, SHA224, RIPEMD160, SHA1
   Compression: ZLIB, BZIP2, ZIP, Uncompressed
   Features: MDC, Keyserver no-modify
```

```
bash-4.4$
\end{verbatim}


\subsection{Subkeys}
\label{sec:org5e2acbc}
Adding
 subkeys to a primary key is fairly similar to creating the
primary key with the \texttt{create\_subkey} method.  Most of the arguments
are the same, but not quite all.  Instead of the \texttt{userid} argument
there is now a \texttt{key} argument for selecting which primary key to add
the subkey to.

In the following example an encryption subkey will be added to the
primary key.  Since Danger Mouse is a security conscious secret agent,
this subkey will only be valid for about six months, half the length
of the primary key.

\begin{verbatim}
import gpg

c = gpg.Context()
c.home_dir = "~/.gnupg-dm"

key = c.get_key(dmkey.fpr, secret=True)
dmsub = c.create_subkey(key, algorithm="rsa3072", expires_in=15768000,
                        encrypt=True)
\end{verbatim}

As with the primary key, the results here can be checked with:

\begin{verbatim}
print("""
Fingerprint:  {0}
Primary Key:  {1}
 Public Key:  {2}
 Secret Key:  {3}
Sub Key:  {4}
User IDs:  {5}
""".format(dmsub.fpr,
 dmsub.primary, dmsub.pubkey, dmsub.seckey, dmsub.sub,
          dmsub.uid))
\end{verbatim}

As well as on the command line with:

\begin{verbatim}
```

```
bash-4.4$ gpg --homedir ~/.gnupg-dm -K
~/.gnupg-dm/pubring.kbx
----------------------
sec   rsa3072 2018-03-15 [SC] [expires: 2019-03-15]
      177B7C25DB99745EE2EE13ED026D2F19E99E63AA
uid           [ultimate] Danger Mouse <dm@secret.example.net>
ssb   rsa3072 2018-03-15 [E] [expires: 2018-09-13]

bash-4.4$
\end{verbatim}


\subsection{User IDs}
\label{sec:org4869c58}
\subsubsection{Adding User IDs}
\label{sec:orgebb13ca}
By comparison to creating primary keys and subkeys, adding a new user
ID to an existing key is much simpler.  The method used to do this is
\texttt{key\_add\_uid} and the only arguments it takes are for the \texttt{key} and
the new \texttt{uid}.

\begin{verbatim}
import gpg

c = gpg.Context()
c.home_dir = "~/.gnupg-dm"

dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
key = c.get_key(dmfpr, secret=True)
uid
 = "Danger Mouse <danger.mouse@secret.example.net>"

c.key_add_uid(key, uid)
\end{verbatim}

Unsurprisingly the result of this is:

\begin{verbatim}
bash-4.4$ gpg --homedir ~/.gnupg-dm -K
~/.gnupg-dm/pubring.kbx
----------------------
sec   rsa3072 2018-03-15 [SC] [expires: 2019-03-15]
      177B7C25DB99745EE2EE13ED026D2F19E99E63AA
uid           [ultimate] Danger Mouse <danger.mouse@secret.example.net>
uid           [ultimate] Danger Mouse <dm@secret.example.net>
ssb   rsa3072 2018-03-15 [E] [expires: 2018-09-13]

bash-4.4$
```

\end{verbatim}

\subsubsection{Revoking User IDs}
\label{sec:org1683695}
Revoking a user ID is a fairly similar process, except that it uses
the \texttt{key_revoke_uid} method.

\begin{verbatim}
import gpg

c = gpg.Context()
c.home_dir = "~/.gnupg-dm"

dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
key = c.get_key(dmfpr, secret=True)
uid = "Danger Mouse <danger.mouse@secret.example.net>"

c.key_revoke_uid(key, uid)
\end{verbatim}

\subsection{Key certification}
\label{sec:orgf431bf8}
Since
 key certification is more frequently referred to as key signing,
the method used to perform this function is \texttt{key_sign}.

The \texttt{key_sign} method takes four arguments: \texttt{key}, \texttt{uids},
\texttt{expires_in} and \texttt{local}. The default value of \texttt{uids} is \texttt{None} and
which results in all user IDs being selected. The default value of
both \texttt{expires_in} and \texttt{local} is \texttt{False}; which results in the
signature never expiring and being able to be exported.

The \texttt{key} is the key being signed rather than the key doing the
signing. To change the key doing the signing refer to the signing key
selection above for signing messages and files.

If the \texttt{uids} value is not \texttt{None} then it must either be a string to
match a single user ID or a list of strings to match multiple user
IDs. In this case the matching of those strings must be precise and
it is case sensitive.

To sign Danger
 Mouse's key for just the initial user ID with a
signature which will last a little over a month, do this:

\begin{verbatim}

```
import gpg

c = gpg.Context()
uid = "Danger Mouse <dm@secret.example.net>"

dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
key = c.get_key(dmfpr, secret=True)
c.key_sign(key, uids=uid, expires_in=2764800)
\end{verbatim}


\subsubsection{Verifying key certifications}
\label{sec:org87abdd3}
\begin{verbatim}
import gpg
import time

c = gpg.Context()
dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
keys = list(c.keylist(pattern=dmuid, mode=gpg.constants.keylist.mode.SIGS))
key = keys[0]

for user in key.uids:
  for sig in user.signatures:
    print("0x{0}".format(sig.keyid), "", time.ctime(sig.timestamp), "",
          sig.uid)
\end{verbatim}

Which for Danger Mouse displays the following:

\begin{verbatim}
0x92E3F6115435C65A  Thu Mar 15 13:17:44 2018  Danger Mouse <dm@secret.example.net>
0x321E4E2373590E5D  Mon Nov 26 12:46:05 2018  Ben McGinnes <ben@adversary.org>
\end{verbatim}

The
 two key signatures listed are for the self-certification of Danger
Mouse's key made when the key was created in March, 2018; and the
second is a signature made by the author and set to expire at the end
of the year.  Note that the second signature was made with the
following code (including the preceding code to display the output of
the certifications or key signatures):

\begin{verbatim}
import gpg
import math
import pendulum
import time
```

```
hd = "/home/dm/.gnupg"
c = gpg.Context()
d = gpg.Context(home_dir=hd)
dmfpr = "177B7C25DB99745EE2EE13ED026D2F19E99E63AA"
dmuid = "Danger Mouse <dm@secret.example.net>"
dkeys = list(c.keylist(pattern=dmuid))
dmkey = dkeys[0]

c.key_import(d.key_export(pattern=None))

tp = pendulum.period(pendulum.now(tz="local"), pendulum.datetime(2019, 1, 1))
ts = tp.total_seconds()
total_secs = math.ceil(ts)
c.key_sign(dmkey, uids=dmuid, expires_in=total_secs)

d.key_import(c.key_export(pattern=dmuid))
keys = list(c.keylist(pattern=dmuid,
 mode=gpg.constants.keylist.mode.SIGS))
key = keys[0]

for user in key.uids:
  for sig in user.signatures:
    print("0x{0}".format(sig.keyid), "", time.ctime(sig.timestamp), "",
        sig.uid)
\end{verbatim}
```

Note that this final code block includes the use of a module which is \emph{not} part of Python's standard library, the \href{https://pendulum.eustace.io/}{pendulum module}. Unlike the standard datetime module, pendulum makes working with dates and times significantly easier in Python; just as the requests module makes working with HTTP and HTTPS easier than the builtin modules do.

Though neither requests nor pendulum are required modules for using the GPGME Python bindings, they are both highly recommended more generally.

\section{Advanced or Experimental Use Cases}
\label{sec:org944cc00}
\subsection{C plus Python plus SWIG plus Cython}
\label{sec:org3b53926}

In spite of the apparent incongruence of using Python bindings to a C interface only to generate more C from the Python; it is in fact quite possible to use the GPGME bindings with \href{http://docs.cython.org/en/latest/index.html}{Cython}. Though in many cases the benefits may not be obvious since the most computationally

intensive work never leaves the level of the C code with which GPGME
itself is interacting with.

Nevertheless, there are some situations where the benefits are
demonstrable. One of the better and easier examples being the one of
the early examples in this HOWTO, the \hyperref[sec:org63a3d62]{key counting} code. Running that
example as an executable Python script, \texttt{keycount.py} (available in
the \texttt{examples/howto/} directory), will take a noticeable amount of time
to run on most systems where the public keybox or keyring contains a
few thousand public keys.

Earlier in the evening, prior to starting this section, I ran that
script on my laptop; as I tend to do periodically and timed it using
\texttt{time} utility, with the following results:

\begin{verbatim}
bash-4.4$
 time keycount.py

Number of secret keys: 23
Number of public keys: 12112

real 11m52.945s
user 0m0.913s
sys 0m0.752s

bash-4.4$
\end{verbatim}

Sometime after that I imported another key and followed it with a
little test of Cython. This test was kept fairly basic, essentially
lifting the material from the \href{http://docs.cython.org/en/latest/src/tutorial/cython_tutorial.html}{Cython Basic Tutorial} to demonstrate
compiling Python code to C. The first step was to take the example
key counting code quoted previously, essentially from the importing of
the \texttt{gpg} module to the end of the script:

\begin{verbatim}
import gpg

c = gpg.Context()
seckeys = c.keylist(pattern=None, secret=True)
pubkeys = c.keylist(pattern=None, secret=False)

seclist = list(seckeys)
secnum = len(seclist)

```
publist = list(pubkeys)
pubnum = len(publist)

print("""
   Number of secret keys:  {0}
   Number of public keys:  {1}

""".format(secnum, pubnum))
\end{verbatim}

Save
 that into a file called \texttt{keycount.pyx} and then create a
\texttt{setup.py} file which contains this:

\begin{verbatim}
from distutils.core import setup
from Cython.Build import cythonize

setup(
   ext_modules = cythonize("keycount.pyx")
)
\end{verbatim}

Compile it:

\begin{verbatim}
bash-4.4$ python setup.py build_ext --inplace
bash-4.4$
\end{verbatim}

Then run it in a similar manner to \texttt{keycount.py}:

\begin{verbatim}
bash-4.4$ time python3.7 -c "import keycount"

Number of secret keys:  23
Number of public keys:  12113



real 6m47.905s
user 0m0.785s
sys 0m0.331s

bash-4.4$
\end{verbatim}

Cython turned \texttt{keycount.pyx} into an 81KB \texttt{keycount.o} file in the
\texttt{build/} directory, a 24KB \texttt{keycount.cpython-37m-darwin.so} file to be
```

imported into Python 3.7 and a 113KB \texttt{keycount.c} generated C source
code file of nearly three thousand lines. Quite a bit bigger than the
314 bytes of the \texttt{keycount.pyx} file or the full 1,452 bytes
 of the
full executable \texttt{keycount.py} example script.

On the other hand it ran in nearly half the time; taking 6 minutes and
47.905 seconds to run. As opposed to the 11 minutes and 52.945 seconds
which the CPython script alone took.

The \texttt{keycount.pyx} and \texttt{setup.py} files used to generate this example
have been added to the \texttt{examples/howto/advanced/cython/} directory
The example versions include some additional options to annotate the
existing code and to detect Cython's use. The latter comes from the
\href{http://docs.cython.org/en/latest/src/tutorial/pure.html\#magic-attributes-within-the-pxd}{Magic Attributes}
section of the Cython documentation.

\section{Miscellaneous extras and work-arounds}
\label{sec:orgd72f7de}
Most of the things in the following sections are here simply because
there was no better place to put them, even though some are only
peripherally related to the GPGME Python bindings. Some are also
workarounds for functions not integrated
 with GPGME as yet. This is
especially true of the first of these, dealing with \hyperref[sec:org83f4d00]{group lines}.

\subsection{Group lines}
\label{sec:org83f4d00}
There is not yet an easy way to access groups configured in the
gpg.conf file from within GPGME. As a consequence these central
groupings of keys cannot be shared amongst multiple programs, such as
MUAs readily.

The following code, however, provides a work-around for obtaining this
information in Python.

\begin{verbatim}
import subprocess
import sys

if sys.platform == "win32":
  gpgconfcmd = "gpgconf.exe --list-options gpg"
else:
  gpgconfcmd = "gpgconf --list-options gpg"

process = subprocess.Popen(gpgconfcmd.split(), stdout=subprocess.PIPE)

```
procom = process.communicate()

if sys.version_info[0] == 2:
  lines = procom[0].splitlines()
else:
  lines = procom[0].decode().splitlines()

for line in lines:
  if line.startswith("group") is True:
     break

groups = line.split(":")[-1].replace("", '').split(',')

group_lines
 = []
group_lists = []

for i in range(len(groups)):
  group_lines.append(groups[i].split("="))
  group_lists.append(groups[i].split("="))

for i in range(len(group_lists)):
  group_lists[i][1] = group_lists[i][1].split()
\end{verbatim}

The result of that code is that \texttt{group\_lines} is a list of lists where
\texttt{group\_lines[i][0]} is the name of the group and \texttt{group\_lines[i][1]}
is the key IDs of the group as a string.

The \texttt{group\_lists} result is very similar in that it is a list of
lists.  The first part, \texttt{group\_lists[i][0]} matches
\texttt{group\_lines[i][0]} as the name of the group, but \texttt{group\_lists[i][1]}
is the key IDs of the group as a list.

A demonstration of using the \texttt{groups.py} module is also available in
the form of the executable \texttt{mutt-groups.py} script.  This second
script reads all the group entries in a user's \texttt{gpg.conf} file and
converts them into crypt-hooks suitable for use
 with the Mutt and
Neomutt mail clients.


\subsection{Keyserver access for Python}
\label{sec:org5ad99aa}
The \href{https://github.com/Selfnet/hkp4py}{hkp4py} module by Marcel Fest was originally a port of the old
\href{https://github.com/dgladkov/python-hkp}{python-hkp} module from Python 2 to Python 3 and updated to use
the
\href{http://docs.python-requests.org/en/latest/index.html}{requests} module instead.  It has since been modified to
```

provide
support for Python 2.7 as well and is available via PyPI.

Since it rewrites the \texttt{hkp} protocol prefix as \texttt{http} and \texttt{hkps} as
\texttt{https}, the module is able to be used even with servers which do not
support the full scope of keyserver functions.\footnote{Such as with ProtonMail servers. This also means that
restricted servers which only advertise either HTTP or HTTPS end
points and not HKP or HKPS end points must still be identified as as
HKP or HKPS within the Python Code. The \texttt{hkp4py} module will rewrite
these
 appropriately when the connection is made to the server.} It also works quite
readily when incorporated into a \hyperref[sec:org3b53926]{Cython} generated and compiled version
of any code.

\subsubsection{Key import format}
\label{sec:org1e47c97}
The hkp4py module returns key data via requests as string literals
(\texttt{r.text}) instead of byte literals (\texttt{r.content}). This means that
the retrurned key data must be encoded to UTF-8 when importing that
key material using a \texttt{gpg.Context().key_import()} method.

For this reason an alternative method has been added to the \texttt{search}
function of \texttt{hkp4py.KeyServer()} which returns the key in the correct
format as expected by \texttt{key_import}. When importing using this module,
it is now possible to import with this:

\begin{verbatim}
for key in keys:
  if key.revoked is False:
     gpg.Context().key_import(key.key_blob)
  else:
     pass
\end{verbatim}

Without that recent addition it would
 have been necessary to encode
the contents of each \texttt{hkp4py.KeyServer().search()[i].key} in
\texttt{hkp4py.KeyServer().search()} before trying to import it.

An example of this is included in the \hyperref[sec:org1ad598a]{Importing Keys} section of this
HOWTO and the corresponding executable version of that example is
available in the \texttt{lang/python/examples/howto} directory as normal; the
executable version is the \texttt{import-keys-hkp.py} file.

\subsection{GPGME version checking}
\label{sec:org18b8ef8}

For various reasons it may be necessary to check which version of
GPGME the bindings have been built against; including whether a
minimum required version of GPGME is in use.

For the most part the \texttt{gpg.version.versionstr} and
\texttt{gpg.version.versionlist} methods have been quite sufficient. The
former returns the same string as \texttt{gpgme-config -{}-version}, while the
latter returns the major, minor and patch values in a list.

To check if the installed bindings
 have actually been built against
the current installed libgpgme version, this check can be performed:

\begin{verbatim}
import gpg
import subprocess
import sys

gpgme_version_call = subprocess.Popen(["gpgme-config", "--version"],
                                      stdout=subprocess.PIPE,
                                      stderr=subprocess.PIPE)
gpgme_version_str = gpgme_version_call.communicate()

if sys.version_info[0] == 2:
  gpgme_version = gpgme_version_str[0].strip()
elif sys.version_info[0] >= 3:
  gpgme_version = gpgme_version_str[0].decode().strip()
else:
  gpgme_version = None

if gpgme_version is not None:
  if gpgme_version == gpg.version.versionstr:
    print("The GPGME Python bindings match libgpgme.")
  else:
    print("The GPGME Python bindings do NOT match libgpgme.")
else:
  print("Upgrade Python and reinstall the GPGME Python bindings.")
\end{verbatim}

For many developers, however, the preferred checking means checking
for a minimum
 version or point release. This is now readily available
via the \texttt{gpg.version.versionintlist} method (added in version
\texttt{1.12.1-beta79}). It is also now possible to easily check whether the
installed GPGME Python bindings were built from a development or beta
branch of the GPGME source code.

The following code demonstrates how both of those methods may be used:

```
\begin{verbatim}
import gpg

try:
  if gpg.version.is_beta is True:
     print("The installed GPGME Python bindings were built from beta code.")
  else:
     print("The installed GPGME Python bindings are a released version.")
except Exception as e:
  print(e)

try:
  if gpg.version.versionintlist[0] == 1:
     if gpg.version.versionintlist[1] == 12:
        if gpg.version.versionintlist[2] == 1:
           print("This is the minimum version for using versionintlist.")
        elif gpg.version.versionintlist[2] > 1:
           print("The versionintlist method is available.")

        else:
           pass
     elif gpg.version.versionintlist[1] > 12:
        print("The versionintlist method is available.")
     else:
        pass
  elif gpg.version.versionintlist[0] > 1:
     print("The versionintlist method is available.")
  else:
     pass
except Exception as e:
  print(e)
\end{verbatim}

The points where \texttt{pass} is used in the above example will most likely
also produce an \texttt{Exception} error since those results should only
occur in versions which do not have the \texttt{gpgme.version.is\_beta} and
\texttt{gpgme.version.versionintlist} methods available.


\section{Copyright and Licensing}
\label{sec:org9d52a23}
\subsection{Copyright}
\label{sec:org26ed04d}
Copyright  The GnuPG Project, 2018.

Copyright (C) The GnuPG Project, 2018.
```

\subsection{Draft Editions of this HOWTO}
\label{sec:org080a94a}
Draft editions of this HOWTO may be periodically available directly
from the author at any of the following URLs:

\begin{itemize}
\item
 \href{https://files.au.adversary.org/crypto/gpgme-python-howto.html}{GPGME Python Bindings HOWTO draft (XHTML single file, AWS S3 SSL)}
\item \href{http://files.au.adversary.org/crypto/gpgme-python-howto.html}{GPGME Python Bindings HOWTO draft (XHTML single file, AWS S3 no SSL)}
\item \href{https://files.au.adversary.org/crypto/gpgme-python-howto-split/index.html}{GPGME Python Bindings HOWTO draft (XHTML multiple files, AWS S3 SSL)}
\item \href{http://files.au.adversary.org/crypto/gpgme-python-howto/index.html}{GPGME Python Bindings HOWTO draft (XHTML multiple files, AWS S3 no SSL)}
\end{itemize}

All of these draft versions except for one have been generated from
this document via GNU Emacs \href{https://orgmode.org/}{Org mode} and
\href{https://www.gnu.org/software/texinfo/}{GNU Texinfo}. Though it is
likely that the specific \href{https://files.au.adversary.org/crypto/gpgme-python-howto}{file}
\href{http://files.au.adversary.org/crypto/gpgme-python-howto.org}{version}
 used will be on the same server
with the generated output formats.

The GNU Texinfo and reStructured Text versions ship with the software,
while the GNU Emacs Info verseion is generated from the Texinfo
version using GNU Texinfo or GNU Makeinfo. The Texinfo format is
generated from the original Org mode source file in Org mode itself
either within GNU Emacs or via the command line by invoking Emacs in
batch mode:

\begin{verbatim}
emacs gpgme-python-howto.org --batch -f org-texinfo-export-to-texinfo --kill
emacs gpgme-python-howto --batch -f org-texinfo-export-to-texinfo --kill
\end{verbatim}

The reStructuredText format is also generated from the Org-mode source
file, except it is generated using \href{https://pandoc.org}{Pandoc} with either of the following
commands:

\begin{verbatim}
pandoc -f org -t rst+smart -o gpgme-python-howto.rst gpgme-python-howto.org
pandoc -f org -t rst+smart -o gpgme-python-howto.rst gpgme-python-howto
\end{verbatim}

In addition to these there is

a significantly less frequently updated
version as a HTML \href{https://files.au.adversary.org/crypto/gpgme-python/dita/webhelp/index.html}{WebHelp site} (AWS S3 SSL); generated from DITA XML
source files, which can be found in \href{https://dev.gnupg.org/source/gpgme/browse/ben\%252Fhowto-dita/}{an alternative branch} of the GPGME
git repository.

Various generated output formats may occasionally be found in
subdirectories of the \href{https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python}{gpgme-python} directory. In particular within
the \href{https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python/dita}{DITA},
\href{https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python/rst}{reStructuredText} and
\href{https://s3.amazonaws.com/files.au.adversary.org/crypto/gpgme-python/texinfo}{Texinfo} subdirectories. The \texttt{rst}
directory contains output files generated with Sphix and may include a
considerable number of its possible output formats.

These
draft editions are not official documents and the version of
documentation in the master branch or which ships with released
versions is the only official documentation. Nevertheless, these
draft editions may occasionally be of use by providing more accessible
web versions which are updated between releases. They are provided on
the understanding that they may contain errors or may contain content
subject to change prior to an official release.

\subsection{License GPL compatible}
\label{sec:orge78f3b7}
This file is free software; as a special exception the author gives
unlimited permission to copy and/or distribute it, with or without
modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY, to the extent permitted by law; without even the
implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE.
\end{document}
/*
  listallkeysjob.h

  This file is part of qgpgme, the Qt API binding for gpgme
  Copyright (c) 2004 Klarlvdalens Datakonsult AB
  Copyright (c) 2016 by Bundesamt fr Sicherheit in der Informationstechnik
  Software engineering by Intevation GmbH

  QGpgME is free software; you can redistribute it and/or
  modify it under the terms of the GNU General Public License as

```
   published by the Free Software Foundation; either version 2 of the
   License, or (at your option) any later version.

   QGpgME is distributed in the hope that it will be useful,
   but WITHOUT ANY WARRANTY; without even the implied warranty of
   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
   General Public License for more details.

   You should have received a copy of the GNU General Public License
   along with this program; if not, write to the Free Software
   Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  02110-1301  USA

   In addition, as a special
 exception, the copyright holders give
   permission to link the code of this program with any edition of
   the Qt library by Trolltech AS, Norway (or with modified versions
   of Qt that use the same license as Qt), and distribute linked
   combinations including the two.  You must obey the GNU General
   Public License in all respects for all of the code used other than
   Qt.  If you modify this file, you may extend this exception to
   your version of the file, but you are not obligated to do so.  If
   you do not wish to do so, delete this exception statement from
   your version.
*/

#ifndef __KLEO_LISTALLKEYSJOB_H__
#define __KLEO_LISTALLKEYSJOB_H__

#include "job.h"
#include "qgpgme_export.h"

#ifdef BUILDING_QGPGME
# include "key.h"
#else
# include <gpgme++/key.h>
#endif

#include <vector>

namespace GpgME
{
class Error;
class KeyListResult;
}

namespace QGpgME
{
```

```
/**
  @short An abstract base class for asynchronously listing all keys

  To use a ListAllKeysJob,
 first obtain an instance from the
  CryptoBackend implementation, connect the progress()
  and result() signals to suitable slots and then start the key
  listing with a call to start(). This call might fail, in which
  case the ListAllKeysJob instance will have schedules it's own
  destruction with a call to QObject::deleteLater().

  After result() is emitted, the ListAllKeysJob will schedule it's
  own destruction by calling QObject::deleteLater().

  This is potentially much faster than a KeyListJob with empty
  pattern.
*/
class QGPGME_EXPORT ListAllKeysJob : public Job
{
  Q_OBJECT
protected:
  explicit ListAllKeysJob(QObject *parent);

public:
  ~ListAllKeysJob();

  /**
    Starts the listallkeys operation.  In general, all keys are
    returned (however, the backend is free to truncate the result
    and should do so; when this happens, it will be reported by the
    result object).

    If GnuPG 2.1 or later is used, then \a mergeKeys is ignored. Otherwise,
     if \a mergeKeys is true, then some (but not all) information of the
    secret keys is merged into public keys.
  */
  virtual GpgME::Error start(bool mergeKeys = false) = 0;

  /**
     Synchronous version of start().
  */
  virtual GpgME::KeyListResult exec(std::vector<GpgME::Key> &pub, std::vector<GpgME::Key> &sec, bool
mergeKeys = false) = 0;

Q_SIGNALS:
  void result(const GpgME::KeyListResult &result, const std::vector<GpgME::Key> &pub =
std::vector<GpgME::Key>(), const std::vector<GpgME::Key> &sec = std::vector<GpgME::Key>(), const QString
&auditLogAsHtml = QString(), const GpgME::Error &auditLogError = GpgME::Error());
```

```
};

}

#endif // __KLEO_LISTALLKEYSJOB_H__
/*
 trustitem.h - wraps a gpgme trust item
 Copyright (C) 2003 Klarlvdalens Datakonsult AB
 2016 Bundesamt fr Sicherheit in der Informationstechnik
 Software engineering by Intevation GmbH

 This file is part of GPGME.

 GPGME++ is free software; you can redistribute it and/or
 modify it under the terms of the GNU Library General Public
 License as published by the Free Software Foundation; either
 version 2 of the License, or (at your option) any later version.

 GPGME++ is distributed in the hope that it will be useful,
 but WITHOUT ANY WARRANTY; without even the implied warranty of
 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
 GNU Library General Public License for more details.

 You should have received a copy of the GNU Library General Public License
 along with GPGME++; see the file COPYING.LIB.  If not, write to the
 Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor,
 Boston, MA 02110-1301, USA.
*/

// -*- c++ -*-
#ifndef __GPGMEPP_TRUSTITEM_H__
#define
 __GPGMEPP_TRUSTITEM_H__

#include "gpgmefw.h"
#include <key.h>
#include "gpgmepp_export.h"

#include <algorithm>

namespace GpgME
{

class Context;

class GPGMEPP_EXPORT TrustItem
{
  friend class ::GpgME::Context;
```

```
public:
  explicit TrustItem(gpgme_trust_item_t item = nullptr);
  TrustItem(const TrustItem &other);
  virtual ~TrustItem();

  const TrustItem &operator=(TrustItem other)
  {
    swap(other);
    return *this;
  }

  void swap(TrustItem &other)
  {
    using std::swap;
    swap(this->d, other.d);
  }

  bool isNull() const;

  const char *keyID() const;
  const char *userID() const;

  const char *ownerTrustAsString() const;
  const char *validityAsString() const;

  int trustLevel() const;

  enum Type { Unknown = 0, Key = 1, UserID = 2 };
  Type type() const;

private:
  gpgme_trust_item_t impl() const;
  class Private;
  Private *d;
};

} // namepace GpgME

GPGMEPP_MAKE_STD_SWAP_SPECIALIZATION(TrustItem)

#endif
 // __GPGMEPP_TRUSTITEM_H__
#include "qgpgme/exportjob.h"
/* ath.h - Interfaces for thread-safeness library.
  Copyright (C) 2002, 2003, 2004 g10 Code GmbH

  This file is part of GPGME.
```

```
  GPGME is free software; you can redistribute it and/or modify it
  under the terms of the GNU Lesser General Public License as
  published by the Free Software Foundation; either version 2.1 of
  the License, or (at your option) any later version.

  GPGME is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Lesser General Public License for more details.

  You should have received a copy of the GNU Lesser General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
  02111-1307, USA.  */

#ifndef ATH_H
#define ATH_H

#ifdef HAVE_STDINT_H
#include <stdint.h>
#endif
#ifdef HAVE_W32_SYSTEM
 /* fixme: Check how we did it in libgcrypt.
  */
 struct msghdr { int dummy; };
 typedef int socklen_t;
# include <windows.h>
# include <io.h>

#else /*!HAVE_W32_SYSTEM*/

# ifdef HAVE_SYS_SELECT_H
#  include <sys/select.h>
# else
#  ifdef HAVE_SYS_TIME_H
#   include <sys/time.h>
#  endif
# endif
# ifdef HAVE_SYS_TYPES_H
#  include <sys/types.h>
# endif
# include <sys/socket.h>

#endif  /*!HAVE_W32_SYSTEM*/



/* Define _ATH_EXT_SYM_PREFIX if you want to give all external symbols
```

```
  a prefix.  */
#define _ATH_EXT_SYM_PREFIX _gpgme_

#ifdef _ATH_EXT_SYM_PREFIX
#define _ATH_PREFIX1(x,y) x ## y
#define _ATH_PREFIX2(x,y) _ATH_PREFIX1(x,y)
#define _ATH_PREFIX(x) _ATH_PREFIX2(_ATH_EXT_SYM_PREFIX,x)
#define ath_read _ATH_PREFIX(ath_read)
#define ath_write _ATH_PREFIX(ath_write)
#define ath_select _ATH_PREFIX(ath_select)
#define ath_waitpid _ATH_PREFIX(ath_waitpid)
#define ath_connect _ATH_PREFIX(ath_connect)
#define ath_accept _ATH_PREFIX(ath_accept)
#define ath_sendmsg _ATH_PREFIX(ath_sendmsg)
#define ath_recvmsg _ATH_PREFIX(ath_recvmsg)
#endif


uintptr_t
 ath_self (void);

/* Replacement for the POSIX functions, which can be used to allow
  other (user-level) threads to run.  */
gpgme_ssize_t ath_read (int fd, void *buf, size_t nbytes);
gpgme_ssize_t ath_write (int fd, const void *buf, size_t nbytes);
gpgme_ssize_t ath_select (int nfd, fd_set *rset, fd_set *wset, fd_set *eset,
                          struct timeval *timeout);
gpgme_ssize_t ath_waitpid (pid_t pid, int *status, int options);
int ath_accept (int s, struct sockaddr *addr, socklen_t *length_ptr);
int ath_connect (int s, const struct sockaddr *addr, socklen_t length);
int ath_sendmsg (int s, const struct msghdr *msg, int flags);
int ath_recvmsg (int s, struct msghdr *msg, int flags);

#endif /* ATH_H */
#include "qgpgme/decryptverifyjob.h"
```

1.147 acl 2.3.1-4.el9

1.147.1 Available under license :

Most components of the "acl" package are licensed under
Version 2.1 of the GNU Lesser General Public License (see COPYING.LGPL).

Some components (as annotated in the source) are licensed
under Version 2 of the GNU General Public License (see below),

---

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so

that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications

or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if
the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works
based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions

are
prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License,
they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution
system, which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation
may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision
will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR

DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one
line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts
in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it

under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License
does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
Most components of the "acl" package are licensed under
Version 2.1 of the GNU Lesser General Public License (see below).
below.

Some components (as annotated in the source) are licensed
under Version 2 of the GNU General Public License (see COPYING).

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

Licenses are intended to guarantee your freedom
to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions
that forbid
distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free
library. Also, if the library is
modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a

restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries
into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a
certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions
for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains code derived from the library, whereas the latter must
be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other
program which contains a notice placed by the copyright holder or
other authorized party saying it may be distributed under the terms of
this Lesser General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under
these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly into another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control compilation
and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use
of the Library in a tool for
writing it). Whether that is true depends on what the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an

appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote

it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere
aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library
into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of

the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file
is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of
this License. If the work
during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under

Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library

facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It
is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution
limitation excluding those countries,
so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the

"copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License
for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.148 cyrus-sasl 2.1.27-22.el9

1.148.1 Available under license :

/* CMU libsasl
* Tim Martin
* Rob Earhart
* Rob Siemborski
*/
/*
* Copyright (c) 1998-2003 Carnegie Mellon University. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions

* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in
*   the documentation and/or other materials provided with the
*   distribution.
*
* 3. The name "Carnegie Mellon University" must not be used to
*   endorse or promote products derived from this software without
*   prior written permission. For permission or any other legal
*   details, please contact
*   Office of Technology Transfer
*   Carnegie Mellon University
*   5000 Forbes Avenue
*   Pittsburgh, PA 15213-3890
*   (412) 268-4387, fax: (412) 268-7395
*   tech-transfer@andrew.cmu.edu
*
* 4. Redistributions of any form whatsoever must retain the following
*   acknowledgment:
*   "This product includes software developed by Computing Services
*   at Carnegie Mellon University (http://www.cmu.edu/computing/)."
*
* CARNEGIE MELLON UNIVERSITY DISCLAIMS ALL WARRANTIES WITH REGARD TO
* THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
* AND FITNESS, IN NO EVENT SHALL CARNEGIE MELLON UNIVERSITY BE LIABLE
* FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN
* AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING
* OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*/
/* CMU libsasl
* Tim Martin
* Rob Earhart
* Rob Siemborski
*/
/*
* Copyright (c) 2001 Carnegie Mellon University. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.

*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in
*   the documentation and/or other materials provided with the
*   distribution.
*
* 3. The name "Carnegie Mellon University" must not be used to
*   endorse or promote products derived from this software without
*   prior written permission. For permission or any other legal
*   details, please contact
*   Office of Technology Transfer
*   Carnegie Mellon University
*   5000 Forbes Avenue
*   Pittsburgh, PA 15213-3890
*   (412) 268-4387, fax: (412) 268-7395
*   tech-transfer@andrew.cmu.edu
*
* 4. Redistributions of any form whatsoever must retain the following
*   acknowledgment:
*   "This product includes software developed by Computing Services
*   at Carnegie Mellon University (http://www.cmu.edu/computing/)."
*
* CARNEGIE MELLON UNIVERSITY DISCLAIMS ALL WARRANTIES WITH REGARD TO
* THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
* AND FITNESS, IN NO EVENT SHALL CARNEGIE MELLON UNIVERSITY BE LIABLE
* FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN
* AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING
* OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*/
/*
* Copyright (C) 1989 by the Massachusetts Institute of Technology
*
* Export of this software from the United States of America is assumed
* to require a specific license from the United States Government.
* It is the responsibility of any person or organization contemplating
* export to obtain such a license before exporting.
*
* WITHIN THAT CONSTRAINT, permission to use, copy, modify, and
* distribute this software and its documentation for any purpose and
* without fee is hereby granted, provided that the above copyright
* notice appear in all copies and that both that copyright notice and
* this permission notice appear in supporting documentation, and that
* the name of M.I.T. not be used in advertising or publicity pertaining
* to distribution of the software without specific, written prior
* permission. M.I.T. makes no representations about the suitability of
* this software for any purpose. It is provided "as is" without express
* or implied warranty.

```
*
*/

#ifndef _KERBEROS_MIT_COPYRIGHT_H
#define _KERBEROS_MIT_COPYRIGHT_H

/*
 #pragma ident "@(#)mit-copyright.h 1.4 93/02/04 SMI" */

#endif /* _KERBEROS_MIT_COPYRIGHT_H */
/*
* Copyright 1987 by the Student Information Processing Board
*  of the Massachusetts Institute of Technology
*
* Permission to use, copy, modify, and distribute this software
* and its documentation for any purpose and without fee is
* hereby granted, provided that the above copyright notice
* appear in all copies and that both that copyright notice and
* this permission notice appear in supporting documentation,
* and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
* used in advertising or publicity pertaining to distribution
* of the software without specific, written prior permission.
* M.I.T. and the M.I.T. S.I.P.B. make no representations about
* the suitability of this software for any purpose.  It is
* provided "as is" without express or implied warranty.
*
*/

#ifndef _KERBEROS_MIT_COPYRIGHT_H
#define _KERBEROS_MIT_COPYRIGHT_H

#pragma ident "@(#)mit-sipb-copyright.h 1.5 93/02/04 SMI"

#endif /* _KERBEROS_MIT_COPYRIGHT_H */
Copyright (C) 1995-1997 Eric Young (eay@mincom.oz.au)
All rights reserved.

This package is an DES implementation written by Eric Young (eay@mincom.oz.au).
The implementation was written so as to conform with MIT's libdes.

This library is free for commercial and non-commercial use as long as
the following conditions are aheared to.  The following conditions
apply to all code found in this distribution.

Copyright remains Eric Young's, and as such any Copyright notices in
the code are not to be removed.
If this package is used in a product, Eric Young should be given attribution
as the author of that the SSL library.  This can be in the form of a textual
```

message at program startup or in documentation (online or textual) provided
with the package.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the copyright
  notice, this list of conditions and the
 following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software
  must display the following acknowledgement:
  This product includes software developed by Eric Young (eay@mincom.oz.au)

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY,
 OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

The license and distribution terms for any publically available version or
derivative of this code cannot be changed. i.e. this code cannot simply be
copied and put under another distrubution license
[including the GNU Public License.]

The reason behind this being stated in this direct manner is past
experience in code simply being copied and the attribution removed
from it and then being distributed as part of other packages. This
implementation was a non-trivial and unpaid effort.

1.149 zlib 1.2.11-40.el9

1.149.1 Available under license :

Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,

execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.150 pcre2 10.40-6.el9

1.150.1 Available under license :

PCRE2 LICENCE

Please see the file LICENCE in the PCRE2 distribution for licensing details.

End
PCRE2 LICENCE

PCRE2 is a library of functions to support regular expressions whose syntax
and semantics are as close as possible to those of the Perl 5 language.

Releases 10.00 and above of PCRE2 are distributed under the terms of the "BSD"
licence, as specified below, with one exemption for certain binary
redistributions. The documentation for PCRE2, supplied in the "doc" directory,
is distributed under the same terms as the software itself. The data in the
testdata directory is not copyrighted and is in the public domain.

The basic library functions are written in C and are freestanding. Also
included in the distribution is a just-in-time compiler that can be used to
optimize pattern matching. This is an optional feature that can be omitted when
the library is built.

THE BASIC LIBRARY FUNCTIONS

Written by: Philip Hazel
Email local part: Philip.Hazel
Email domain: gmail.com

Retired from University of Cambridge Computing Service,
Cambridge,
England.

Copyright (c) 1997-2022 University of Cambridge
All rights reserved.

PCRE2 JUST-IN-TIME COMPILATION SUPPORT

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2010-2022 Zoltan Herczeg
All rights reserved.

STACK-LESS JUST-IN-TIME COMPILER

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2009-2022 Zoltan Herczeg
All rights reserved.

THE "BSD" LICENCE

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notices,
this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notices, this list of conditions and the following disclaimer

in the
documentation and/or other materials provided with the distribution.

* Neither the name of the University of Cambridge nor the names of any
contributors may be used to endorse or promote products derived from this
software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,
EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

EXEMPTION FOR BINARY LIBRARY-LIKE PACKAGES

The second condition in the BSD licence (covering binary redistributions) does not apply all the way down a chain of software. If binary package A includes PCRE2, it must respect the condition, but if package B is software that includes package A, the condition is not imposed on package B unless it uses PCRE2 independently.

End
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.151 libsigsegv 2.13-4.el9

1.151.1 Available under license :

/* List of signals. BSD version.
Copyright (C) 2002 Bruno Haible <bruno@clisp.org>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software Foundation,
Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA. */

/* List of signals that are sent when an invalid virtual memory address
is accessed, or when the stack overflows. */
#define SIGSEGV_FOR_ALL_SIGNALS(var,body) \
{ int var; var = SIGSEGV; { body } var =
SIGBUS; { body } }
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301, USA.
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This

General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak
of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright
the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS

AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the
files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an

announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified
work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not
bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative

is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from
the same place counts as
distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all
its terms and conditions for copying, distributing or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you
may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems

or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute
it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking
 proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
/* Fault handler information. BSD Unix version.
  Copyright (C) 2002 Bruno Haible <bruno@clisp.org>

  This program is free software; you can redistribute it and/or modify
  it under the terms of the GNU General Public License as published by
  the Free Software Foundation; either version 2, or (at your option)
  any later version.

  This program is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
  GNU General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program; if not, write to the Free Software Foundation,
  Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA. */

#define SIGSEGV_FAULT_HANDLER_ARGLIST int sig, int code, void *scp, void *addr
#define SIGSEGV_FAULT_ADDRESS addr

1.152 basesystem 11-13.el9

1.152.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

%global distroname %(source /etc/os-release; echo ${REDHAT_SUPPORT_PRODUCT})

Summary: The skeleton package which defines a simple %{distroname} system
Name: basesystem
Version: 11
Release: 13%{?dist}
License: Public Domain
Requires(pre): setup filesystem
BuildArch: noarch

%description
Basesystem defines the components of a basic %{distroname} system
(for example, the package installation order to use during bootstrapping).
Basesystem should be in every installation of a system, and it
should never be removed.

%prep

%build

%install

%files

%changelog
* Mon Aug 09 2021 Mohan Boddu <mboddu@redhat.com> - 11-13
- Rebuilt for IMA sigs, glibc 2.34, aarch64 flags
Related: rhbz#1991688

* Thu Apr 15 2021 Mohan Boddu <mboddu@redhat.com> - 11-12
- Rebuilt for RHEL 9 BETA on Apr 15th 2021. Related: rhbz#1947937

* Tue Jan 26 2021 Fedora Release Engineering <releng@fedoraproject.org> - 11-11
- Rebuilt for https://fedoraproject.org/wiki/Fedora_34_Mass_Rebuild

*
Mon Jul 27 2020 Fedora Release Engineering <releng@fedoraproject.org> - 11-10
- Rebuilt for https://fedoraproject.org/wiki/Fedora_33_Mass_Rebuild

* Tue Jan 28 2020 Fedora Release Engineering <releng@fedoraproject.org> - 11-9
- Rebuilt for https://fedoraproject.org/wiki/Fedora_32_Mass_Rebuild

* Wed Jul 24 2019 Fedora Release Engineering <releng@fedoraproject.org> - 11-8
- Rebuilt for https://fedoraproject.org/wiki/Fedora_31_Mass_Rebuild

* Thu Jan 31 2019 Fedora Release Engineering <releng@fedoraproject.org> - 11-7
- Rebuilt for https://fedoraproject.org/wiki/Fedora_30_Mass_Rebuild

* Thu Jul 12 2018 Fedora Release Engineering <releng@fedoraproject.org> - 11-6
- Rebuilt for https://fedoraproject.org/wiki/Fedora_29_Mass_Rebuild

* Wed Feb 07 2018 Fedora Release Engineering <releng@fedoraproject.org> - 11-5
- Rebuilt for https://fedoraproject.org/wiki/Fedora_28_Mass_Rebuild

* Wed Jul 26 2017 Fedora Release Engineering <releng@fedoraproject.org>
- 11-4
- Rebuilt for https://fedoraproject.org/wiki/Fedora_27_Mass_Rebuild

* Fri Feb 10 2017 Fedora Release Engineering <releng@fedoraproject.org> - 11-3
- Rebuilt for https://fedoraproject.org/wiki/Fedora_26_Mass_Rebuild

* Wed Feb 03 2016 Fedora Release Engineering <releng@fedoraproject.org> - 11-2
- Rebuilt for https://fedoraproject.org/wiki/Fedora_24_Mass_Rebuild

* Thu Jul 09 2015 Ondrej Vasik <ovasik@redhat.com> 11-1
- automatically determine OS name at build time (#1195396)

* Wed Jun 17 2015 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-11
- Rebuilt for https://fedoraproject.org/wiki/Fedora_23_Mass_Rebuild

* Sat Jun 07 2014 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-10
- Rebuilt for https://fedoraproject.org/wiki/Fedora_21_Mass_Rebuild

* Sat Aug 03 2013 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-9
- Rebuilt for https://fedoraproject.org/wiki/Fedora_20_Mass_Rebuild

* Wed Feb 13 2013 Fedora Release Engineering
<rel-eng@lists.fedoraproject.org> - 10.0-8
- Rebuilt for https://fedoraproject.org/wiki/Fedora_19_Mass_Rebuild

* Wed Jul 18 2012 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-7
- Rebuilt for https://fedoraproject.org/wiki/Fedora_18_Mass_Rebuild

* Thu Jan 12 2012 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-6
- Rebuilt for https://fedoraproject.org/wiki/Fedora_17_Mass_Rebuild

* Thu Jun 23 2011 Ondrej Vasik <ovasik@redhat.com> 10.0-5
- fix FTBFS typo (#715640), add disttag

* Mon Feb 07 2011 Fedora Release Engineering <rel-eng@lists.fedoraproject.org>
- Rebuilt for https://fedoraproject.org/wiki/Fedora_15_Mass_Rebuild

* Fri Jul 24 2009 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-3
- Rebuilt for https://fedoraproject.org/wiki/Fedora_12_Mass_Rebuild

* Mon Feb 23 2009 Fedora Release Engineering <rel-eng@lists.fedoraproject.org> - 10.0-2
- Rebuilt for https://fedoraproject.org/wiki/Fedora_11_Mass_Rebuild

* Mon
Oct 20 2008 Phil Knirsch <pknirsch@redhat.com> 10.0-1
- Bump version and rebuild for Fedora 10 (#451289)

* Fri Mar 02 2007 Phil Knirsch <pknirsch@redhat.com> - 8.1-1
- Cleanup per package review (#225608)

* Wed Jul 12 2006 Jesse Keating <jkeating@redhat.com> - 8.0-5.1.1
- rebuild

* Fri Dec 09 2005 Jesse Keating <jkeating@redhat.com>
- rebuilt

* Wed Sep 22 2004 Bill Nottingham <notting@redhat.com>
- rebuilt

* Fri Feb 13 2004 Elliot Lee <sopwith@redhat.com>
- rebuilt

* Wed Jan 22 2003 Tim Powers <timp@redhat.com>
- rebuilt

* Wed Aug 21 2002 Bill Nottingham <notting@redhat.com>
- bump rev

* Fri Jun 21 2002 Tim Powers <timp@redhat.com>
- automated rebuild

* Thu May 23 2002 Tim Powers <timp@redhat.com>
- automated rebuild

* Wed Jan 09 2002 Tim Powers <timp@redhat.com>
- automated rebuild

* Wed Jul 12 2000 Prospector <bugzilla@redhat.com>
- automatic rebuild

* Tue Jun 6 2000 Bill Nottingham <notting@redhat.com>
- rebuild. Wheee.

* Sun Mar 21 1999 Cristian Gafton <gafton@redhat.com>

- auto rebuild in the new build environment (release 4)

* Tue Mar 16 1999 Cristian Gafton <gafton@redhat.com>
- don't require rpm (breaks dependency chain)

* Tue Mar 16 1999 Erik Troan <ewt@redhat.com>
- require rpm

* Wed Dec 30 1998 Cristian Gafton <gafton@redhat.com>
- build for 6.0

* Tue Aug 11 1998 Jeff Johnson <jbj@redhat.com>
- build root

* Mon Apr 27 1998 Prospector System <bugs@redhat.com>
- translations modified for de, fr, tr

* Tue Sep 23 1997 Erik Troan <ewt@redhat.com>
- made a noarch package

Found in path(s):
* /basesystem-11-13.el9-1.src.rpm-cosi-expand-archive-kw7PFRbi/basesystem.spec

1.153 libxcrypt 4.4.18-3.el9

1.153.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with

the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data

prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the

ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object

file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at

least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your

rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE

LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.154 selinux 3.6-3.el9

1.154.1 Available under license :

This library (libselinux) is public domain software, i.e. not copyrighted.

Warranty Exclusion

You agree that this software is a
non-commercially developed program that may contain "bugs" (as that
term is used in the industry) and that it may not function as intended.
The software is licensed "as is". NSA makes no, and hereby expressly
disclaims all, warranties, express, implied, statutory, or otherwise
with respect to the software, including noninfringement and the implied
warranties of merchantability and fitness for a particular purpose.

Limitation of Liability

In no event will NSA be liable for any damages, including loss of data,
lost profits, cost of cover, or other special, incidental,
consequential, direct or indirect damages arising from the software or
the use thereof, however caused and on any theory of liability. This
limitation will apply even if NSA has been advised of the possibility
of such damage. You acknowledge that this is
 a reasonable allocation of
risk.

1.155 dnf 4.14.0-31.el9

1.155.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we

want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable

source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

5. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Program or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying or distributing the Program (or any work based on the

Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY

YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate

parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.156 libreport-filesystem 2.15.2-6.el9

1.156.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed

to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,

either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to

control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the
source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent

license would not permit royalty-free redistribution
of the Program by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under
any particular circumstance, the balance of the section is intended to
apply and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w'
and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.157 lz4 1.9.3-5.el9

1.157.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of

Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or

distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to

be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,

INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute

it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.
Copyright (c) 2014, lpsantil
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES;
 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This repository uses 2 different licenses :
- all files in the `lib` directory use a BSD 2-Clause license
- all other files use a GPLv2 license, unless explicitly stated otherwise

Relevant license is reminded at the top of each source file,
and with presence of COPYING or LICENSE file in associated directories.

This model is selected to emphasize that
files in the `lib` directory are designed to be included into 3rd party applications,
while all other files, in `programs`, `tests` or `examples`,
receive more limited attention and support for such scenario.
LZ4 Library
Copyright (c) 2011-2016, Yann Collet
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this
 list of conditions and the following disclaimer in the documentation and/or
 other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
 GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Format: http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: liblz4
Upstream-Contact: Yann Collet <Cyan4973@github.com>
Source: https://github.com/lz4/lz4

Files: *
Copyright: (C) 2011-2020 Yann Collet
License: GPL-2+
The full text of license: https://github.com/lz4/lz4/blob/dev/lib/LICENSE

1.158 libffi 3.4.2-8.el9

1.158.1 Available under license :

The libffi source distribution contains certain code that is not part
of libffi, and is only used as tooling to assist with the building and
testing of libffi. This includes the msvcc.sh script used to wrap the
Microsoft compiler with GNU compatible command-line options,
make_sunver.pl, and the libffi test code distributed in the
testsuite/libffi.bhaible directory. This code is distributed with
libffi for the purpose of convenience only, and libffi is in no way
derived from this code.

msvcc.sh an testsuite/libffi.bhaible are both distributed under the
terms of the GNU GPL version 2, as below.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software
are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions

that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by
others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program
or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of

running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based

on the Program, the distribution of the whole must be on the terms of this License, whose
permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily
used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the
scripts used to
control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have
received copies, or rights, from you under
this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You
are not responsible for enforcing compliance by third parties to
this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under

any particular circumstance, the balance
of the section is intended to
apply and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright
holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free
Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and

of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY
AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve
this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more
details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work
as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
libffi - Copyright (c) 1996-2021 Anthony Green, Red Hat, Inc and others.
See source files for details.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
``Software''), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
 CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.159 json-c 0.14-11.el9

1.159.1 Available under license :

Copyright (c) 2009-2012 Eric Haszlakiewicz

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
 WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

Copyright (c) 2004, 2005 Metaparadigm Pte Ltd

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation

the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE
FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.160 libcap 2.48-10.el9

1.160.1 Available under license :

Unless otherwise *explicitly* stated the following text describes the
licensed conditions under which the contents of this module release
may be distributed:

Redistribution and use in source and binary forms of this module, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
copyright notices, this list of conditions, and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. The name of any author may not be used to endorse or promote
products derived from this software without their specific prior
written permission.

ALTERNATIVELY, this product may be distributed under
the terms of the
GNU Library General Public License, in which case the provisions of
the GNU LGPL are required INSTEAD OF the above restrictions. (This
clause is necessary due to a potential conflict between the GNU LGPL
and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

Unless otherwise *explicitly* stated, the following text describes the
licensed conditions under which the contents of this libcap/psx release
may be used and distributed:

Redistribution and use in source and binary forms of libcap/psx, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
  notice, and this entire permission notice in its entirety,
  including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
  copyright notices, this list of conditions, and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

3. The name of any author may not be used to endorse or promote
  products derived from this software without their specific prior
  written permission.

ALTERNATIVELY, this product may be
 distributed under the terms of the
GNU General Public License (v2.0 - see below), in which case the
provisions of the GNU GPL are required INSTEAD OF the above
restrictions. (This clause is necessary due to a potential conflict
between the GNU GPL and the restrictions contained in a BSD-style
copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,

BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Full
text of gpl-2.0.txt:

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the
GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that

you have. You must make sure that they, too, receive or can get the source code. And you must
 show them these terms so they know their
rights.

 We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

 Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

 Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

 The precise terms and conditions for copying,
 distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

 0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only
 if its contents constitute a work based on the
Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

 1. You may copy and distribute verbatim copies of the Program's

source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the
Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with
the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access
to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the
Program (or any work based on the
Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy
simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT
OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright
(C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary
programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
Unless otherwise *explicitly* stated, the following text describes the
licensed conditions under which the contents of this libcap/cap release
may be used and distributed:

Redistribution and use in source and binary forms of libcap/cap, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
copyright notices, this list of conditions, and the following
disclaimer in the documentation and/or other materials provided

with the distribution.

3. The name of any author may not be used to endorse or promote
products derived from this software without their specific prior
written permission.

ALTERNATIVELY, this product may be
distributed under the terms of the
GNU General Public License (v2.0 - see below), in which case the
provisions of the GNU GPL are required INSTEAD OF the above
restrictions. (This clause is necessary due to a potential conflict
between the GNU GPL and the restrictions contained in a BSD-style
copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

Full
text of gpl-2.0.txt:

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to

using it. (Some other Free Software Foundation software is covered by the
GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must
show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying,
distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only
if its contents constitute a work based on the
Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under

these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the
Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with
the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access
to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the
Program (or any work based on the
Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not

excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free

Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it
does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright
(C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary

programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
Unless otherwise *explicitly* stated, the following text describes the
licensed conditions under which the contents of this libcap release
may be used and distributed:

Redistribution and use in source and binary forms of libcap, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
copyright notices, this list of conditions, and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. The name of any author may not be used to endorse or promote
products derived from this software without their specific prior
written permission.

ALTERNATIVELY, this product may be distributed
under the terms of the
GNU General Public License (v2.0 - see below), in which case the
provisions of the GNU GPL are required INSTEAD OF the above
restrictions. (This clause is necessary due to a potential conflict
between the GNU GPL and the restrictions contained in a BSD-style
copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

Full
text of gpl-2.0.txt:

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU
Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show
them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying,
distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its
contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a)
You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the
Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program
(or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program
(or any work based on the
Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously
your obligations under this
License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions
to the wide range of software distributed
through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING

WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT
OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year
name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.

This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs.
If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

1.161 bash 5.1.8-9.el9

1.161.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below,

refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but

does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for

making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the
source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot

distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Program at all. For example, if a patent
license would not permit royalty-free redistribution
of the Program by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under
any particular circumstance, the balance of the section is intended to
apply and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of

this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w'
and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General

Public License instead of this License.

GNU Free Documentation License
Version 1.3, 3 November 2008

Copyright (C) 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
<http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections,
in the notice
that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters
or
for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of

transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The "publisher" means any person or entity that distributes copies of the Document to the public.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and

you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should
put the first ones listed (as many as fit
reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before
redistributing any large number of copies, to
give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release

the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
D. Preserve all the copyright notices of the Document.
E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
H. Include an unaltered copy of this License.
I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
L. Preserve all the Invariant Sections of the Document,

unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.
M. Delete any section Entitled "Endorsements". Such a section
may not be included in the Modified Version.
N. Do not retitle any existing section to be Entitled "Endorsements"
or to conflict in title with any Invariant Section.
O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document, you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains
nothing but
endorsements of your Modified Version by various
parties--for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

5. COMBINING
DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and

multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections
Entitled "History"
in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives
with other separate
and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the

electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

"Massive Multiauthor Collaboration Site" (or "MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A "Massive Multiauthor Collaboration" (or "MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

"CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

"Incorporate" means to publish or republish a Document, in whole or in

part, as part of another Document.

An MMC is "eligible for relicensing" if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole or
in part into the MMC, (1) had no cover texts or invariant sections, and
(2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

  Copyright (c) YEAR YOUR NAME.
  Permission is granted to copy, distribute and/or modify this document
   under the terms of the GNU Free Documentation License, Version 1.3
  or any later version published by the Free Software Foundation;
  with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
  A copy of the license is included in the section entitled "GNU
  Free Documentation License".

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the "with...Texts." line with this:

  with the Invariant Sections being LIST THEIR TITLES, with the
  Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.
@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display

Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
 must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that
contains a notice placed by the copyright holder saying it can be
distributed under the terms of this License. Such a notice grants a
world-wide, royalty-free license, unlimited in duration, to use that
work under the conditions stated herein. The ``Document'', below,
refers
 to any such manual or work. Any member of the public is a
licensee, and is addressed as ``you''. You accept the license if you
copy, modify or distribute the work in a way requiring permission
under copyright law.

A ``Modified Version'' of the Document means any work containing the

Document or a portion of it, either copied verbatim, or with
modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section
of the Document that deals exclusively with the relationship of the
publishers or authors of the Document to the Document's overall
subject (or to related matters) and contains nothing that could fall
directly within that overall subject. (Thus, if the Document is in
part a textbook of mathematics, a Secondary Section may not explain
any mathematics.) The relationship could be a matter of historical
connection with the subject or with related matters, or of legal,
commercial, philosophical, ethical or political
 position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles
are designated, as being those of Invariant Sections, in the notice
that says that the Document is released under this License. If a
section does not fit the above definition of Secondary then it is not
allowed to be designated as Invariant. The Document may contain zero
Invariant Sections. If the Document does not identify any Invariant
Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,
as Front-Cover Texts or Back-Cover Texts, in the notice that says that
the Document is released under this License. A Front-Cover Text may
be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,
represented in a format whose specification is available to the
general public, that is suitable for revising the document
straightforwardly with generic text editors or (for
 images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
@sc{ascii} without markup, Texinfo input format, La@TeX{} input
format, @acronym{SGML} or @acronym{XML} using a publicly available
@acronym{DTD}, and standard-conforming simple @acronym{HTML},
PostScript or @acronym{PDF} designed for human modification. Examples
of transparent image formats include @acronym{PNG}, @acronym{XCF} and

@acronym{JPG}. Opaque formats
 include proprietary formats that can be
read and edited only by proprietary word processors, @acronym{SGML} or
@acronym{XML} for which the @acronym{DTD} and/or processing tools are
not generally available, and the machine-generated @acronym{HTML},
PostScript or @acronym{PDF} produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means
the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in
 another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'', or ``History''.)  To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which
states that this License applies to the Document. These Warranty
Disclaimers are considered to be included by reference in this
License, but only as regards disclaiming warranties: any other
implication that these Warranty Disclaimers may have is void and has
no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either
commercially or noncommercially, provided that this License, the
copyright notices, and the license notice saying this License applies
to the Document are reproduced in all copies, and that you add no other
conditions whatsoever
 to those of this License. You may not use
technical measures to obstruct or control the reading or further
copying of the copies you make or distribute. However, you may accept
compensation in exchange for copies. If you distribute a large enough
number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.
You may add other material on the covers in addition.
Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that
this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release

the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from
 those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same title as a previous version
if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities
responsible for authorship of the modifications in the Modified
Version, together with at least five of the principal authors of the
Document (all of its principal authors, if it has fewer than five),
unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the
Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications
adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice
giving the public permission to use the Modified Version under the
terms of this License, in the form shown in
 the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add
to it an item stating at least the title, year, new authors, and

publisher of the Modified Version as given on the Title Page. If
there is no section Entitled ``History'' in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the ``History'' section.
You may omit a network location for a work that was published at
least
four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document,
you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains

nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf
 of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of
 each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract
a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate
and independent documents or works, in or on a volume of a storage or
distribution medium, is called an ``aggregate'' if the copyright
resulting from the compilation is not used to limit the legal rights
of the compilation's users beyond what the individual works permit.
When the Document is included in an aggregate, this License does not
apply to the other works in the aggregate which are not themselves
derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these
copies of the Document, then if the Document is less than one half of
the entire aggregate, the Document's Cover Texts may
be placed on
covers that bracket the Document within the aggregate, or the
electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole
aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may
distribute translations of the Document under the terms of section 4.
Replacing Invariant Sections with translations requires special
permission from their copyright holders, but you may include
translations of some or all Invariant Sections in addition to the
original versions of these Invariant Sections. You may include a
translation of this License, and all the license notices in the
Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice

or disclaimer, the original
version will prevail.

If a section in the Document is Entitled ``Acknowledgements'',
``Dedications'', or ``History'', the requirement (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies
you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that

a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'')
 contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the
 MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License".
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts." line with this:

@smallexample
@group
   with the Invariant Sections being @var{list their titles}, with
   the Front-Cover
 Texts being @var{list}, and with the Back-Cover Texts
   being @var{list}.
@end group
@end smallexample

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic

pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other

parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those

subprograms and other parts of the work.

The Corresponding Source need not include anything that users
can regenerate automatically from other parts of the Corresponding
Source.

The Corresponding Source for a work in source code form is that
same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of
copyright on the Program, and are irrevocable provided the stated
conditions are met. This License explicitly affirms your unlimited
permission to run the unmodified Program. The output from running a
covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or

modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work,

and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)

that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in

ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or

requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed

under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
Unless otherwise stated, all files in this directory are Copyright (C)
1991,1992,1993,1994,1995,1996,1997,1998,1999,2000,2001,2002,2003,
2004,2005,2006,2007,2008,2009,2010,2011
Free Software Foundation, Inc.

See the file COPYING in the bash distribution root directory for copying
and usage restrictions.

The file ifs-posix.tests is Copyright (C) 2005 Glen Fowler.

1.162 rootfiles 8.1-35.el9

1.162.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):

*
No license file was found, but licenses were detected in source scan.

Summary: The basic required files for the root user's directory

Found in path(s):
* /rootfiles-8.1-35.el9.src.rpm-cosi-expand-archive-RwDIoiod/rootfiles.spec

1.163 glibc-common 2.34-231.el9_7.2

1.163.1 Available under license :

@c The GNU Lesser General Public License.
@center Version 2.1, February 1999

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]
@end display

@subheading Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software---to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software---typically
libraries---of the Free
Software Foundation and other authors who decide to use it. You can use
it too, but we suggest you first think carefully about whether this
license or the ordinary General Public License is the better strategy to
use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge

for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library
or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation
will not be affected by problems that might be
introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative

of the original library. The ordinary
General Public License therefore permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the @dfn{Lesser} General Public License because it
does @emph{Less} to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the
same job as widely used non-free libraries. In this
case, there is little to gain by limiting the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
``work based on the library'' and a ``work that uses the library''. The
former
contains code derived from the library, whereas the latter must
be combined with the library in order to run.

@subheading TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

@enumerate 0
@item
This License Agreement applies to any software library or other program
which contains a notice placed by the copyright holder or other

authorized party saying it may be distributed under the terms of this Lesser General Public License (also called ``this License''). Each licensee is addressed as ``you''.

A ``library'' means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The ``Library'', below, refers to any such software library or work which has been distributed under these terms. A ``work based on the Library'' means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it,
either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term ``modification''.)

``Source code'' for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

@item
You may copy and distribute
verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

@item
You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and

distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

@enumerate a
@item
The modified work must itself be a software library.

@item
You must cause the files modified to carry prominent notices
stating that you changed the files and the date of any change.

@item
You must
 cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

@item
If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must
be optional: if the application does not supply it, the square
root function must still compute square roots.)
@end enumerate

These requirements apply to the modified work as a whole. If
identifiable sections
 of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or

collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this
License.

@item
You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

@item
You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and
2 above provided that you accompany
it with the complete corresponding machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

@item
A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a ``work that uses the Library''. Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a ``work that uses the Library'' with the Library

creates an executable that is a derivative of the Library (because
it
contains portions of the Library), rather than a ``work that uses the
library''. The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a ``work that uses the Library'' uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise,
if the work is a derivative of the Library, you may
distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

@item
As an exception to the Sections above, you may also combine or
link a ``work that uses the Library'' with the Library to produce a
work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of
this License. Also, you must do one
of these things:

@enumerate a
@item
Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under

Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable ``work that
uses the Library'', as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

@item
Use a suitable shared library mechanism for linking with the Library. A
suitable mechanism is one that (1) uses at run time a copy of the
library already present on the user's computer system, rather than
copying library functions into the executable,
 and (2) will operate
properly with a modified version of the library, if the user installs
one, as long as the modified version is interface-compatible with the
version that the work was made with.

@item
Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

@item
If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

@item
Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.
@end enumerate

 For an executable, the required form of the ``work that uses the
Library'' must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that
 is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies the
executable.

 It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot

use both them and the Library together in an executable that you
distribute.

@item
You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

@enumerate a
@item
Accompany the combined library with a copy of the same work
based on the Library,
 uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

@item
Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.
@end enumerate

@item
You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

@item
You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited
 by law if you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

@item
Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the

original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.

@item
If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License,
 they do not
excuse you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply,
and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software
 distribution system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

@item
If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

@item
The Free Software Foundation
may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
``any later version'', you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

@item
If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for
this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

@center @b{NO WARRANTY}

@item
BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY ``AS IS'' WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item
IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING

RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.
@end enumerate

@subheading END OF TERMS AND CONDITIONS

@page
@subheading How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source
file to most effectively
convey the exclusion of warranty; and each file should have at least the ``copyright'' line and a pointer to where the full notice is found.

@smallexample
@var{one line to give the library's name and an idea of what it does.}
Copyright (C) @var{year} @var{name of author}

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.
@end
smallexample

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a ``copyright disclaimer'' for the library, if

necessary. Here is a sample; alter the names:

@smallexample
Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

@var{signature of Ty Coon}, 1 April 1990
Ty Coon, President of Vice
@end smallexample

That's all there is to it!
Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.
GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change

free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that

any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact

all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that

uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on

the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.

11. If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent

license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these,

write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision
will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by

the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed

under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this

License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for

making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot

distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of

this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this

is what you want to do, use the GNU Lesser General
Public License instead of this License.
UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories
http://www.unicode.org/Public/, http://www.unicode.org/reports/, and
http://www.unicode.org/cldr/data/. Unicode Data Files do not include PDF
online code charts under the directory http://www.unicode.org/Public/.
Software includes any source code published in the Unicode Standard or under
the directories http://www.unicode.org/Public/,
http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode,
Inc. All rights reserved. Distributed under
the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software
that the data or
software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE

DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.
This file contains the copying permission notices for various files in the GNU C Library distribution that have copyright owners other than the Free Software Foundation. These notices all require that a copy of the notice be included in the accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

All code incorporated from 4.4 BSD is distributed under the following license:

Copyright (C) 1991 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. [This condition was removed.]
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The DNS resolver code, taken from BIND 4.9.5, is copyrighted by UC Berkeley, by Digital Equipment Corporation and by Internet Software Consortium. The DEC portions are under the following license:

Portions Copyright (C) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies, and that the name of Digital Equipment Corporation not be used in advertising or publicity pertaining to distribution of the document or software without specific, written prior permission.

THE SOFTWARE IS PROVIDED ``AS IS'' AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING
FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The ISC portions are under the following license:

Portions Copyright (c) 1996-1999 by Internet Software Consortium.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING
OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The Sun RPC support (from rpcsrc-4.0) is covered by the following license:

Copyright (c) 2010, Oracle America, Inc.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are

met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials
  provided with the distribution.
* Neither the name of the "Oracle America, Inc." nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following CMU license covers some of the support code for Mach,
derived from Mach 3.0:

Mach Operating System
Copyright (C) 1991,1990,1989 Carnegie Mellon University
All Rights Reserved.

Permission to use, copy, modify and distribute this software and its
documentation is hereby granted, provided that
 both the copyright
notice and this permission notice appear in all copies of the
software, derivative works or modified versions, and any portions
thereof, and that both notices appear in supporting documentation.

CARNEGIE MELLON ALLOWS FREE USE OF THIS SOFTWARE IN ITS ``AS IS''
CONDITION. CARNEGIE MELLON DISCLAIMS ANY LIABILITY OF ANY KIND FOR
ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

Carnegie Mellon requests users of this software to return to

Software Distribution Coordinator

School of Computer Science
Carnegie Mellon University
Pittsburgh PA 15213-3890

or Software.Distribution@CS.CMU.EDU any improvements or
extensions that they make and grant Carnegie Mellon the rights to
redistribute these changes.

The file if_ppp.h is under the following CMU license:

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the
 above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors
   may be used to endorse or promote products derived from this software
   without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CARNEGIE MELLON UNIVERSITY AND
CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE UNIVERSITY OR CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
 BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN
IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following license covers the files from Intel's "Highly Optimized
Mathematical Functions for Itanium" collection:

Intel License Agreement

Copyright (c) 2000, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are

met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* The name of Intel Corporation may not be used to endorse
 or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The files inet/getnameinfo.c and sysdeps/posix/getaddrinfo.c are copyright
(C) by Craig Metz and are distributed under the following license:

/* The Inner Net License,
 Version 2.00

 The author(s) grant permission for redistribution and use in source and
binary forms, with or without modification, of the software and documentation
provided that the following conditions are met:

0. If you receive a version of the software that is specifically labelled
  as not being for redistribution (check the version message and/or README),
  you are not permitted to redistribute that version of the software in any
  way or form.
1. All terms of the all other applicable copyrights and licenses must be
  followed.
2. Redistributions of source code must retain the authors' copyright
  notice(s), this list of conditions, and the following disclaimer.
3. Redistributions in binary form must reproduce the authors' copyright
  notice(s), this list of conditions, and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
4. [The copyright holder has authorized the removal of this clause.]

5. Neither the name(s)
of the author(s) nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ITS AUTHORS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

If these license terms cause you a real problem, contact the author. */

The file sunrpc/des_impl.c
is copyright Eric Young:

Copyright (C) 1992 Eric Young
Collected from libdes and modified for SECURE RPC by Martin Kuck 1994
This file is distributed under the terms of the GNU Lesser General
Public License, version 2.1 or later - see the file COPYING.LIB for details.
If you did not receive a copy of the license with this program, please
see <https://www.gnu.org/licenses/> to obtain a copy.

The file inet/rcmd.c is under a UCB copyright and the following:

Copyright (C) 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with
the distribution.
3. Neither the name of the project nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The file posix/runtests.c is copyright Tom Lord:

Copyright
1995 by Tom Lord

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of the copyright holder not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

Tom Lord DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL TOM LORD BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The posix/rxspencer tests
are copyright Henry Spencer:

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by

explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

The file posix/PCRE.tests
is copyright University of Cambridge:

Copyright (c) 1997-2003 University of Cambridge

Permission is granted to anyone to use this software for any purpose on any computer system, and to redistribute it freely, subject to the following restrictions:

1. This software is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

2. The origin of this software must not be misrepresented, either by explicit claim or by omission. In practice, this means that if you use PCRE in software that you distribute to others, commercially or otherwise, you must put a sentence like this

Regular expression support is provided by the PCRE library package, which is open source software, written by Philip Hazel, and copyright by the University of Cambridge, England.

somewhere reasonably visible in your documentation and in any relevant files or online
help data or similar. A reference to the ftp site for the source, that is, to

ftp://ftp.csx.cam.ac.uk/pub/software/programming/pcre/

should also be given in the documentation. However, this condition is not intended to apply to whole chains of software. If package A includes PCRE, it must acknowledge it, but if package B is software that includes package A, the condition is not imposed on package B (unless it uses PCRE independently).

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. If PCRE is embedded in any software that is released under the GNU

General Purpose Licence (GPL), or Lesser General Purpose Licence (LGPL),
then the terms of that licence shall supersede any condition above with
which it is incompatible.

Files from Sun fdlibm are copyright Sun Microsystems, Inc.:

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems,
Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice
is preserved.

Various long double libm functions are copyright Stephen L. Moshier:

Copyright 2001 by Stephen L. Moshier <moshier@na-net.ornl.gov>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, see
<https://www.gnu.org/licenses/>. */

1.164 libgcrypt 1.10.0-11.el9

1.164.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively

when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer

to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to

this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it

free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
Additional license notices for Libgcrypt. -*- org -*-

This file contains the copying permission notices for various files in
the Libgcrypt distribution which are not covered by the GNU Lesser
General Public License (LGPL) or the GNU General Public License (GPL).

These notices all require that a copy of the notice be included
in the accompanying documentation and be distributed with binary
distributions of the code, so be sure to include this file along
with any binary distributions derived from the GNU C Library.

* BSD_3Clause

For files:
- cipher/sha256-avx-amd64.S
- cipher/sha256-avx2-bmi2-amd64.S
- cipher/sha256-ssse3-amd64.S
- cipher/sha512-avx-amd64.S
- cipher/sha512-avx2-bmi2-amd64.S
- cipher/sha512-ssse3-amd64.S
- cipher/sha512-ssse3-i386.c

#+begin_quote
Copyright (c) 2012, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the
  distribution.

* Neither the name of the Intel Corporation nor the names of its
  contributors may be used to endorse or promote products derived from
  this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY INTEL CORPORATION "AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL CORPORATION OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
#+end_quote

For files:
- random/jitterentropy-base.c
- random/jitterentropy-gcd.c
- random/jitterentropy-gcd.h
- random/jitterentropy-health.c
- random/jitterentropy-health.h
- random/jitterentropy-noise.c
- random/jitterentropy-noise.h
- random/jitterentropy-sha3.c
- random/jitterentropy-sha3.h
- random/jitterentropy-timer.c
- random/jitterentropy-timer.h
- random/jitterentropy.h
- random/rndjent.c (plus common Libgcrypt copyright holders)

#+begin_quote
Copyright (C) 2017 - 2021, Stephan Mueller <smueller@chronox.de>

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that
 the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, and the entire permission notice in its entirety,
   including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

3. The name of the author may not be used to endorse or promote
   products derived from this software without specific prior
   written permission.

ALTERNATIVELY, this product may be distributed under the terms of
the GNU General Public License, in which case the provisions of the GPL2
are required INSTEAD OF the above restrictions. (This clause is
necessary due to a potential bad interaction between the GPL and
the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT
 NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
#+end_quote

 For files:
 - cipher/cipher-gcm-ppc.c

#+begin_quote
Copyright (c) 2006, CRYPTOGAMS by <appro@openssl.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

    * Redistributions of source code must retain copyright notices,
      this list of conditions and the following disclaimer.

    * Redistributions in binary form must reproduce the above
      copyright notice, this list of conditions and the following
      disclaimer in the documentation and/or other materials
      provided with the distribution.

    * Neither the name of the CRYPTOGAMS nor the names of its
      copyright holder and contributors may be used to endorse or
      promote products derived from this software without specific
      prior written permission.

ALTERNATIVELY, provided that this notice is retained in full, this
product may be distributed under the terms of the GNU General Public
License (GPL), in which case the provisions of the GPL apply INSTEAD OF
those given above.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
#+end_quote

* X License

For files:
- install.sh

#+begin_quote
Copyright (C) 1994 X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit
persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-

ings in this Software without prior written authorization from the X Consortium.
#+end_quote

* Public domain

For files:
- cipher/arcfour-amd64.S

#+begin_quote
Author: Marc Bevand <bevand_m (at) epita.fr>
Licence: I hereby disclaim the copyright on this code and place it
in the public domain.
#+end_quote

* OCB license 1

For files:
- cipher/cipher-ocb.c

#+begin_quote
OCB is covered by several patents but may be used freely by most
software. See http://web.cs.ucdavis.edu/~rogaway/ocb/license.htm .
In particular license 1 is suitable for Libgcrypt: See
http://web.cs.ucdavis.edu/~rogaway/ocb/license1.pdf for the full
license document; it basically says:

License 1 License for Open-Source Software Implementations of OCB
(Jan 9, 2013)

Under this license, you are authorized to make, use, and
distribute open-source software implementations of OCB. This
license terminates for you if you sue someone over their
open-source software implementation of OCB claiming that you have
a patent covering their implementation.

License for Open Source Software Implementations of OCB
January
9, 2013

1 Definitions

1.1 Licensor means Phillip Rogaway.

1.2 Licensed Patents means any patent that claims priority to United
States Patent Application No. 09/918,615 entitled Method and Apparatus

for Facilitating Efficient Authenticated Encryption, and any utility, divisional, provisional, continuation, continuations-in-part, reexamination, reissue, or foreign counterpart patents that may issue with respect to the aforesaid patent application. This includes, but is not limited to, United States Patent No. 7,046,802; United States Patent No. 7,200,227; United States Patent No. 7,949,129; United States Patent No. 8,321,675 ; and any patent that issues out of United States Patent Application No. 13/669,114.

1.3 Use means any practice of any invention claimed in the Licensed Patents.

1.4 Software Implementation means any practice of any invention claimed in the Licensed Patents that takes the form of software executing on a user-programmable, general-purpose computer or that takes the form of a computer-readable medium storing such software. Software Implementation does not include, for example, application-specific integrated circuits (ASICs), field-programmable gate arrays (FPGAs), embedded systems, or IP cores.

1.5 Open Source Software means software whose source code is published and made available for inspection and use by anyone because either (a) the source code is subject to a license that permits recipients to copy, modify, and distribute the source code without payment of fees or royalties, or (b) the source code is in the public domain, including code released for public use through a CC0 waiver. All licenses certified by the Open Source Initiative at opensource.org as of January 9, 2013 and all Creative Commons licenses identified on the creativecommons.org website as of January 9, 2013, including the Public License Fallback of the CC0 waiver, satisfy these requirements for the purposes of this license.

1.6 Open Source Software Implementation means a Software Implementation in which the software implicating the Licensed Patents is Open Source Software. Open Source Software Implementation does not include any Software Implementation in which the software implicating the Licensed Patents is combined, so as to form a larger program, with software that is not Open Source Software.

2 License Grant

2.1 License. Subject to your compliance with the term s of this license, including the restriction set forth in Section 2.2, Licensor hereby grants to you a perpetual, worldwide, non-exclusive, non-transferable, non-sublicenseable, no-charge, royalty-free, irrevocable license to practice any invention claimed in the Licensed Patents in any Open Source Software Implementation.

2.2 Restriction. If you or your affiliates institute patent litigation (including, but not limited to, a cross-claim or counterclaim in a lawsuit)

against any entity alleging that any Use authorized by this license infringes
another patent, then any rights granted to you under this license automatically terminate as of the date such litigation is filed.

3 Disclaimer
YOUR USE OF THE LICENSED PATENTS IS AT YOUR OWN RISK AND UNLESS REQUIRED BY APPLICABLE LAW, LICENSOR MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE LICENSED PATENTS OR ANY PRODUCT EMBODYING ANY LICENSED PATENT, EXPRESS OR IMPLIED, STATUT ORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTIBILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL LICENSOR BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM OR RELATED TO ANY USE OF THE LICENSED PATENTS, INCLUDING, WITHOUT LIMITATION, DIRECT, INDIRECT, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR SPECIAL DAMAGES, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES PRIOR TO SUCH AN OCCURRENCE.
#+end_quote

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,

not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.
^L
Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using

a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it
becomes a de-facto standard. To achieve this, non-free programs must
be allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains code derived from the library, whereas the latter must
be combined with the library in order
to run.
^L
GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other

program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under
the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can
be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the
ordinary GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete
corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work
that uses the
library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be

linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute
the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a)
Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will
operate properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least
three years, to give the same user the materials specified in
Subsection 6a, above, for a charge no more than the cost of
performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that
is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.
^L
7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined
with any other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited
by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they
do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any

patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution
 system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

 12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License
may add an explicit geographical distribution limitation excluding those
countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

 13. The Free Software Foundation
 may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.
^L
 14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this.
  Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

                    NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED
ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file
to most
effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston,
MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.165 libverto 0.3.2-3.el9

1.165.1 Available under license :

Copyright 2011 Red Hat, Inc.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation files
(the "Software"), to deal in the Software without restriction,
including without limitation the rights to use, copy, modify, merge,
publish, distribute, sublicense, and/or sell copies of the Software,
and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS
BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN

CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.166 libgcc 11.5.0-11.el9

1.166.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide
to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for

you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether
gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General

Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work

which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another
language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms

of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that uses
the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file
that is part of the Library, the object code for the work may be a
derivative work of the Library even though the source code is not.
Whether this is true is especially significant if the work can be
linked without the Library, or if the work is itself a library. The
threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data
structure layouts and accessors, and small macros and small inline
functions (ten lines or less in length), then the use of the object
file is unrestricted, regardless of whether it is legally a derivative
work. (Executables containing this object code plus portions of the
Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object
code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the
work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License
may add an explicit geographical distribution limitation excluding those
countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will
be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
This file contains a list of individuals who submit their patches to
the Cygwin sources under 2-clause BSD license, as well as a list of
individuals who signed the former Cygwin Copyright Assignment up to 2016.

==========
2-clause BSD:
==========
Copyright (c) <YEAR>, <OWNER>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE

POSSIBILITY OF SUCH DAMAGE.
==========

Individuals submitting their patches under 2-clause BSD:

David Allsopp David.Allsopp@cl.cam.ac.uk
Erik M. Bray erik.bray@lri.fr
Brian Inglis Brian.Inglis@SystematicSw.ab.ca
Daniel Santos daniel.santos@pobox.com
Sergejs Lukanihins slukanihin@gmail.com
J.H.
van de Water houder@xs4all.nl

==========

Individuals who signed the former Cygwin Copyright Assignment:

AJ Reins tbisp@qwest.net
Brian E. Dessent brian@dessent.net
Brian Kenneth Ford Brian.Ford@FlightSafety.com
Charles K. Moore keithmo@exmsft.com
Christian Franke franke@computer.org
Christian Lestrade christian.lestrade@free.fr
Christopher Faylor me@cgf.cx
Christopher January chris@atomice.net
Conrad Scott conrad.scott@dsl.pipex.com
Corinna Vinschen corinna@vinschen.de
Craig Iain McGeachie slapdau@yahoo.com.au
David Korn dave.korn.cygwin@gmail.com
Davis Euresti davie@alum.mit.edu
Dennis Vshivkov walrus@amur.ru
Elfyn McBratney elfyn@ubertales.co.uk
Eric Blake eblake@redhat.com
Ernie Coskrey ernie.coskrey@steeleye.com
Gerd Spalink Gerd.Spalink@t-online.de
Hartmut Honisch hhonisch@users.sourceforge.net
Igor Pechtchanski pechtcha@cs.nyu.edu
Jacek Trzcinski jacek@certum.pl
Jeffrey
Eric Altman jaltman@openafs.org
Jerry D. Hedden jerry@hedden.us
Joe Loh joel@pivot3.com
Johan Rydberg johan@rydberg.com
Johannes Schindelin johannes.schindelin@gmx.de
John Hood cgull@glup.org
Jon Turney jon.turney@dronecode.org.uk
Yoni Londner yonihola2@gmail.com
Joseph H. Buehler jbuehler@hekimian.com

Joshua Daniel Franklin joshuadfranklin@yahoo.com
Ken Brown kbrown@cornell.edu
Lapo Luchini lapo@lapo.it
Lev Bishop lev.bishop@gmail.com
Mark Geisert mark@maxrnd.com
Max Kaehn slothman@electric-cloud.com
Micha Nelissen mdvpost@hotmail.com
Michael Haubenwallner michael.haubenwallner@ssi-schaefer.com
Nicholas S. Wourms nwourms@netscape.com
Pavel Yonkov Tsekov ptsekov@gmx.net
Peter Foley pefoley2@pefoley.com
Pierre A. Humblet phumblet@phumblet.no-ip.org
Robert G. Byrnes byrnes@curl.com
Ryan C. Gordon icculus@icculus.org
Sam Steingold sds@gnu.org
Stephen Cleary shammah@spamcop.net
Stephen Osborn bub@io.com
Takashi
Yano takashi.yano@nifty.ne.jp
Thomas Pfaff tpfaff@gmx.net
Vaclav Haisman vhaisman@gmail.com
Yaakov Selkovitz yselkowi@redhat.com
Yitzchak Scott-Thoennes sthoenna@efn.org

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we
suggest you first think carefully about whether
this license or the ordinary General Public License is the better

strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those

libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination
fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we
use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of

a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file

that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any
executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable
source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the

Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying
or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute
so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL
DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line
and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You
should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
/* Copyright (C) 2013-2015 Free Software Foundation, Inc.

This file is part of GCC.

modify it under the terms of the GNU Library General Public License
as published by the Free Software Foundation; either version 2, or
(at your option) any later version.

```
  In addition to the permissions in the GNU Library General Public
  License, the Free Software Foundation gives you unlimited
  permission to link the compiled version of this file into
  combinations with other programs, and to distribute those
  combinations without any restriction coming from the use of this
  file.  (The Library Public License restrictions do apply in other
  respects; for example, they cover modification of the file, and
  distribution when not linked into a combined executable.)

  This program is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Library
 General Public License for more details.

  You should have received a copy of the GNU Library General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street - Fifth Floor, Boston, MA
  02110-1301, USA.  */


#ifndef __VTV_H__
#define __VTV_H__

/* We could have used an enumeration here but it just makes it more
  difficult for the compiler to generate a call to this.  These are
  used as arguments to the function __VLTChangePermission, declared
  below.  */
#define __VLTP_READ_ONLY  0
#define __VLTP_READ_WRITE 1

#ifdef __cplusplus
extern "C" void __VLTChangePermission (int);
#else
extern void __VLTChangePermission (int);
#endif

#ifdef BIG_PAGE_SIZE
/* TODO - Replace '4096' below with correct big page size.  */
#define VTV_PAGE_SIZE 4096
#else
#if defined(__sun__) && defined(__svr4__) && defined(__sparc__)
#define VTV_PAGE_SIZE 8192
#else
#define VTV_PAGE_SIZE 4096
#endif
#endif
```

#endif /* __VTV_H__ */
DRuntime: Runtime Library for the D Programming Language
==========

Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED
"AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE
FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
/**
* DISCLAIMER
* This file has no copyright assigned and is placed in the Public Domain.
*
* Its code is distributed in the hope that it will be useful but WITHOUT
* ANY WARRANTY. ALL WARRANTIES, EXPRESSED OR IMPLIED ARE HEREBY DISCLAIMED.
* This includes but is not limited to warranties of MERCHANTABILITY or
* FITNESS FOR A PARTICULAR PURPOSE.
*/
The newlib subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source
file. Unless otherwise noted in the body of the source file(s), the following copyright
notices will apply to the contents of the newlib subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use,
modify, copy, or redistribute it subject to the terms and conditions
of the BSD License. This program is distributed in the hope that
it will be useful, but WITHOUT ANY WARRANTY expressed or implied,
including the implied warranties of MERCHANTABILITY or FITNESS FOR
A PARTICULAR PURPOSE. A copy of this license is available at
http://www.opensource.org/licenses. Any Red Hat trademarks that are
incorporated in the source code or documentation are not subject to
the BSD License and may only be used or replicated with the express
permission
of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of the University nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY
OF SUCH DAMAGE.

(3) David M. Gay (AT&T 1991, Lucent 1998)

The author of this software is David M. Gay.

Copyright (c) 1991 by AT&T.

Permission to use, copy, modify, and distribute this software for any
purpose without fee is hereby granted, provided that this entire notice
is included in all copies of any software which is or includes a copy
or modification of this software and in
all copies of the supporting
documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR AT&T MAKES ANY
REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY
OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

The author of this software is David M. Gay.

Copyright (C) 1998-2001 by Lucent Technologies
All Rights Reserved

Permission to use, copy, modify, and distribute this software and
its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that the copyright notice and this
permission notice and warranty disclaimer appear in supporting
documentation, and that the name of Lucent or any of its entities
not be used in advertising or publicity pertaining to
distribution of the software without specific, written prior
permission.

LUCENT
DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS.
IN NO EVENT SHALL LUCENT OR ANY OF ITS ENTITIES BE LIABLE FOR ANY
SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER
IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF
THIS SOFTWARE.

(4) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which

specifically grants the user the right to modify, use and distribute this
software provided this notice is not removed or altered. All other rights
are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING,
PERFORMANCE, OR
USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the 29K Technical Support Center at
800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or
0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(5)

(6)

(7) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice is preserved.

(8) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:
permission to use, copy, modify, and distribute this file
for any purpose is hereby
granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the

suitability of this software for any purpose.

(9) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is
freely granted, provided that the above copyright notice, this notice
and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE.

(10) Stephane Carrez (m68hc11-elf/m68hc12-elf targets only)

Copyright (C) 1999, 2000, 2001, 2002 Stephane Carrez (stcarrez@nerim.fr)

The authors hereby grant permission
 to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(11) Christopher G. Demetriou

Copyright (c) 2001 Christopher G. Demetriou
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice,
 this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR

IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) SuperH, Inc.

Copyright
2002 SuperH, Inc. All rights reserved

This software is the property of SuperH, Inc (SuperH) which specifically
grants the user the right to modify, use and distribute this software
provided this notice is not removed or altered. All other rights are
reserved by SuperH.

SUPERH MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL SUPERH BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the SuperH Support Center via
e-mail at softwaresupport@superh.com .

SuperH, Inc.
405 River Oaks Parkway
San Jose
CA 95134
USA

(13) Royal Institute of Technology

Copyright (c) 1999 Kungliga Tekniska Hgskolan
(Royal Institute of Technology, Stockholm, Sweden).
All rights reserved.

Redistribution and use in source and binary
forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of KTH nor the names of its contributors may be
used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY KTH AND ITS CONTRIBUTORS ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL KTH OR ITS CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) Alexey Zelkin

Copyright (c) 2000, 2001 Alexey Zelkin <phantom@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS
``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(15) Andrey A. Chernov

Copyright (C) 1997 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(16)
FreeBSD

Copyright (c) 1997-2002 FreeBSD Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(17) S. L. Moshier

Author: S. L. Moshier.

Copyright (c) 1984,2000 S.L. Moshier

Permission to use, copy, modify, and distribute this software for any
purpose without fee is hereby granted, provided that this entire notice
is included in all copies of any software which is or includes a copy
or modification of this software and in all copies of the supporting
documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
WARRANTY. IN PARTICULAR, THE AUTHOR MAKES NO REPRESENTATION
OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS
SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

(18) Citrus Project

Copyright (c)1999 Citrus Project,
All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT

LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) Todd C. Miller

Copyright (c) 1998 Todd C. Miller <Todd.Miller@courtesan.com>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE
 IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(20) DJ Delorie (i386 / arm)
Copyright (C) 1991 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted
provided that the above copyright notice and following paragraph are
duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even
 the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(21) Free Software Foundation LGPL License (*-linux* targets only)

 Copyright (C) 1990-1999, 2000, 2001 Free Software Foundation, Inc.
 This file is part of the GNU C Library.

Contributed by Mark Kettenis <kettenis@phys.uva.nl>, 1997.

The GNU C Library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

The GNU C Library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with the GNU C Library; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA
02110-1301 USA.

(22) Xavier Leroy LGPL License (i[3456]86-*-linux* targets only)

Copyright (C) 1996 Xavier Leroy (Xavier.Leroy@inria.fr)

This program is free software; you can redistribute it and/or
modify it under the terms of the GNU Library General Public License
as published by the Free Software Foundation; either version 2
of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

(23) Intel (i960)

Copyright (c) 1993 Intel Corporation

Intel hereby grants you permission to copy, modify, and distribute this
software and its documentation. Intel grants this permission provided
that the above copyright notice appears in all copies and that both the
copyright notice and this permission
notice appear in supporting
documentation. In addition, Intel grants this permission provided that
you prominently mark as "not part of the original" any modifications
made to this software or documentation, and that the name of Intel
Corporation not be used in advertising or publicity pertaining to
distribution of the software or the documentation without specific,
written prior permission.

Intel Corporation provides this AS IS, WITHOUT ANY WARRANTY, EXPRESS OR
IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY
OR FITNESS FOR A PARTICULAR PURPOSE. Intel makes no guarantee or
representations regarding the use of, or the results of the use of,
the software and documentation in terms of correctness, accuracy,
reliability, currentness, or otherwise; and you rely on the software,
documentation and results solely at your own risk.

IN NO EVENT SHALL INTEL BE LIABLE FOR ANY LOSS OF USE, LOSS OF BUSINESS,
LOSS OF PROFITS, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL
DAMAGES
OF ANY KIND. IN NO EVENT SHALL INTEL'S TOTAL LIABILITY EXCEED THE SUM
PAID TO INTEL FOR THE PRODUCT LICENSED HEREUNDER.

(24) Hewlett-Packard (hppa targets only)

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:
permission to use, copy, modify, and distribute this file
for any purpose is hereby granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(25) Henry Spencer (only *-linux targets)

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the
Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
explicit claim or by omission. Since few users ever read sources,
credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be

misrepresented as being the original software. Since few users
ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

(26) Mike Barcroft

Copyright (c) 2001 Mike Barcroft <mike@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(27) Konstantin Chuguev (--enable-newlib-iconv)

Copyright (c) 1999, 2000
Konstantin Chuguev. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR
 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

 iconv (Charset Conversion Library) v2.0

(28) Artem Bityuckiy (--enable-newlib-iconv)

Copyright (c) 2003, Artem B. Bityuckiy, SoftMine Corporation.
Rights transferred to Franklin Electronic Publishers.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(29) IBM, Sony, Toshiba (only spu-* targets)

 (C) Copyright 2001,2006,
 International Business Machines Corporation,
  Sony Computer Entertainment, Incorporated,
 Toshiba Corporation,

 All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* Neither the names of the copyright holders nor the names of their
  contributors may be used to endorse or promote products derived from this
  software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

(30) - Alex Tatmanjants (targets using libc/posix)

Copyright (c) 1995 Alex Tatmanjants <alex@elvisti.kiev.ua>
 at Electronni Visti IA, Kiev, Ukraine.
  All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH
DAMAGE.

(31) - M. Warner Losh (targets using libc/posix)

Copyright (c) 1998, M. Warner Losh <imp@freebsd.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(32) - Andrey A. Chernov (targets using libc/posix)

Copyright (C) 1996 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other

materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(33) - Daniel Eischen (targets using libc/posix)

Copyright (c) 2001 Daniel Eischen <deischen@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification,
are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(34) - Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without

modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(35) - Arm Ltd

Copyright (c) 2009-2018 Arm Ltd
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer
in the
documentation and/or other materials provided with the distribution.
3. The name of the company may not be used to endorse or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY ARM LTD ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL ARM LTD BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(36) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright
(c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(37) Texas Instruments Incorporated (tic6x-*, *-tirtos targets)

Copyright (c) 1996-2010,2014 Texas Instruments Incorporated
http://www.ti.com/

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Texas Instruments Incorporated nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(38) National Semiconductor (cr16-* and crx-* targets)

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(39) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this

list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
* Neither the name of Adapteva nor the names of its contributors may be used
to endorse or promote products derived from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(40) - Altera Corportion (nios2-* targets)

Copyright (c) 2003 Altera Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

o Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
o Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
o Neither
the name of Altera Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ALTERA CORPORATION, THE COPYRIGHT HOLDER, AND ITS CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR

TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(41) Ed Schouten - Free BSD

Copyright (c) 2008 Ed Schouten <ed@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(42) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Rolls-Royce Controls and Data Services Limited nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(43) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The
authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(44) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2) Redistributions in binary form
must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE
OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(45) Phoenix Systems - Phoenix-RTOS targets

Copyright (c) 2016 Phoenix Systems
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(46) embedded brains - RTEMS targets

Copyright (c) 2017 embedded brains GmbH
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials
provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(47) John Baldwin - RTEMS targets

Copyright (c) 2015 John Baldwin <jhb@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(48) Jeffrey Roberson - RTEMS targets

Copyright (c) 2008, Jeffrey Roberson <jeff@freebsd.org>
All rights reserved.

Copyright (c) 2008 Nokia Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice unmodified, this list of conditions, and the following
  disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED
 BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(49) - SiFive Inc. (riscv-* targets)

Copyright (c) 2017 SiFive Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use,
modify, copy, or redistribute it subject to the terms and conditions
of the FreeBSD License.   This program is distributed in the hope that
it will be useful,
 but WITHOUT ANY WARRANTY expressed or implied,
including the implied warranties of MERCHANTABILITY or FITNESS FOR
A PARTICULAR PURPOSE. A copy of this license is available at
http://www.opensource.org/licenses.

(50) Michael R. Neilly (riscv-* targets)

(c) Copyright 2017 Michael R. Neilly
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* Neither the names of the copyright holders nor the names of their
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE
IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

(51) Mentor Graphics (amdgcn-* targets)

Copyright (c) 2014-2017 Mentor Graphics.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices
are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(52) BSD-2-Clause-FreeBSD (pru-* targets)

SPDX-License-Identifier: BSD-2-Clause-FreeBSD

Copyright (c) 2018-2019 Dimitar Dimitrov <dimitar@dinux.eu>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation
 and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
The libgloss subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source
file. Unless otherwise noted in the body of the source file(s), the following copyright
notices will apply to the contents of the libgloss subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify,
copy, or redistribute it subject to the terms and conditions of the BSD
License.   This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties
of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license
is available at http://www.opensource.org/licenses. Any Red Hat trademarks that
are incorporated in the source code or documentation are not subject to the BSD
License and may only be used or replicated with the express
 permission of
Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of the University nor the names of its contributors may
  be used to endorse or promote products derived from this software without
  specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
 LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY
OF SUCH DAMAGE.

(3) DJ Delorie

Copyright (C) 1993 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted
provided that the above copyright notice and following paragraph are
duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
 PURPOSE.

(4) (formerly GPL for fr30)

The GPL is no longer applicable to the fr30 platform. The piece of
code (syscalls.c) referencing the GPL has been officially relicensed.

(5) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which
specifically grants the user the right to modify, use and distribute this
software provided this notice is not removed or altered. All other rights
are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems
or suggestions about this software to the 29K Technical Support Center at
800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or
0031-11-1129 in
Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(6) - Analog Devices, Inc. (bfin-* targets)

Copyright (C) 2006, 2008, 2009, 2011, 2012 Analog Devices, Inc.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(7) University of Utah and the Computer Systems Laboratory (CSL)
[applies only to hppa*-*-pro* targets]
Copyright (c) 1990,1994
The University of Utah and
the Computer Systems Laboratory (CSL). All rights reserved.

Permission to use, copy, modify and distribute this software is hereby
granted provided that (1) source code retains these copyright, permission,

and disclaimer notices, and (2) redistributions including binaries
reproduce the notices in supporting documentation, and (3) all advertising
materials mentioning features or use of this software display the following
acknowledgement: ``This product includes software developed by the
Computer Systems Laboratory at the University of Utah."

THE UNIVERSITY OF UTAH AND CSL ALLOW FREE USE OF THIS SOFTWARE IN ITS "AS
IS" CONDITION. THE UNIVERSITY OF UTAH AND CSL DISCLAIM ANY LIABILITY OF
ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

CSL requests users of this software to return to csl-dist@cs.utah.edu any
improvements that they make and grant CSL redistribution rights.

(8) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems,
 Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice is preserved.

(9) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS"
without any express or implied warranty:

permission to use, copy, modify, and distribute this file
for any purpose is hereby granted without fee, provided that
the above copyright notice and this notice appears in all
copies, and that the name of Hewlett-Packard Company not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
Hewlett-Packard Company makes no representations about the
suitability of this software for any purpose.

(10) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is
freely granted, provided that
 the above copyright notice, this notice
and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR

IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

(11) IBM Corp. spu processor (only spu-* targets)

(C) Copyright IBM Corp. 2005, 2006

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of IBM nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

(13) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright (c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

1. Redistributions source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of Xilinx nor the names of its contributors may be
used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS
IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) - National Semiconductor Corporation

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice
 is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(15) - CodeSourcery, Inc. (tic6x-* targets)

Copyright (c) 2010 CodeSourcery, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above copyright
    notice, this list of conditions and the following disclaimer in the
    documentation and/or other materials provided with the distribution.
  * Neither the name of CodeSourcery
 nor the
    names of its contributors may be used to endorse or promote products
    derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CODESOURCERY, INC. ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL CODESOURCERY BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16) - GPL with exception (sparc-*leon*, crx-*, cr16-* targets only)

 Copyright (C) 1992 Free Software Foundation,

Inc.
Written By David Vinayak Henkel-Wallace, June 1992

This file is free software; you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by the
Free Software Foundation; either version 2, or (at your option) any
later version.

In addition to the permissions in the GNU General Public License, the
Free Software Foundation gives you unlimited permission to link the
compiled version of this file with other programs, and to distribute
those programs without any restriction coming from the use of this
file. (The General Public License restrictions do apply in other
respects; for example, they cover modification of the file, and
distribution when not linked into another program.)

This file is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a
copy of the GNU General Public License
along with this program; see the file COPYING. If not, write to
the Free Software Foundation, 59 Temple Place - Suite 330,
Boston, MA 02111-1307, USA.

As a special exception, if you link this library with files
compiled with GCC to produce an executable, this does not cause
the resulting executable to be covered by the GNU General Public License.
This exception does not however invalidate any other reasons why
the executable file might be covered by the GNU General Public License.

(17) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,

this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
* Neither the name of Adapteva nor the names of its contributors may be used

to endorse or promote products derived from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(18) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* Neither the name of Rolls-Royce Controls and Data Services Limited nor
  the names of its contributors may be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT
HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and
 that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(20) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2) Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names
 of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(21) BSD-2-Clause-FreeBSD (pru-* targets)

SPDX-License-Identifier: BSD-2-Clause-FreeBSD

Copyright (c)

2018-2019 Dimitar Dimitrov <dimitar@dinux.eu>
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS;
 OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY

THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
/* Copyright (C) 2013-2021 Free Software Foundation, Inc.

  This file is part of GCC.

  modify it under the terms of the GNU Library General Public License
  as published by the Free Software Foundation; either version 2, or
  (at your option) any later version.

  In addition to the permissions in the GNU Library General Public
  License, the Free Software Foundation gives you unlimited
  permission to link the compiled version of this file into
  combinations with other programs, and to distribute those
  combinations without any restriction coming from the use of this
  file.  (The Library Public License restrictions do apply in other
  respects; for example, they cover modification of the file, and
  distribution when not linked into a combined executable.)

  This program is distributed in the hope that it will be useful, but
  WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
  Library
 General Public License for more details.

  You should have received a copy of the GNU Library General Public
  License along with this program; if not, write to the Free Software
  Foundation, Inc., 51 Franklin Street - Fifth Floor, Boston, MA
  02110-1301, USA.  */


#ifndef __VTV_H__
#define __VTV_H__

/* We could have used an enumeration here but it just makes it more
  difficult for the compiler to generate a call to this.  These are
  used as arguments to the function __VLTChangePermission, declared
  below.  */
#define __VLTP_READ_ONLY  0
#define __VLTP_READ_WRITE 1

#ifdef __cplusplus
extern "C" void __VLTChangePermission (int);
#else
extern void __VLTChangePermission (int);
#endif
```

```
#ifdef BIG_PAGE_SIZE
/* TODO - Replace '4096' below with correct big page size.  */
#define VTV_PAGE_SIZE 4096
#else
#if defined(__sun__) && defined(__svr4__) && defined(__sparc__)
#define VTV_PAGE_SIZE 8192
#else
#define VTV_PAGE_SIZE 4096
#endif
#endif



#endif /* __VTV_H__ */
/* Definitions for BSD assembler syntax for Intel 386
  (actually AT&T syntax for insns and operands,
  adapted to BSD conventions for symbol names and debugging.)
  Copyright (C) 1988-2021 Free Software Foundation, Inc.

This file is part of GCC.

GCC is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3, or (at your option)
any later version.

GCC is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with GCC; see the file COPYING3.  If not see
<http://www.gnu.org/licenses/>.  */

/* Use the Sequent Symmetry assembler syntax.  */

/* Define the syntax of pseudo-ops, labels and comments.  */

/* Prefix for internally generated assembler
 labels.  If we aren't using
  underscores, we are using prefix `.'s to identify labels that should
  be ignored, as in `i386/gas.h' --karl@cs.umb.edu  */

#define LPREFIX "L"

/* Assembler pseudos to introduce constants of various size.  */
```

```
#define ASM_BYTE "\t.byte\t"
#define ASM_SHORT "\t.word\t"
#define ASM_LONG "\t.long\t"
#define ASM_QUAD "\t.quad\t"  /* Should not be used for 32bit compilation.  */

/* This was suggested, but it shouldn't be right for DBX output. -- RMS
  #define ASM_OUTPUT_SOURCE_FILENAME(FILE, NAME) */


/* Define the syntax of labels and symbol definitions/declarations.  */

/* This is how to output an assembler line
  that says to advance the location counter by SIZE bytes.  */

#define ASM_OUTPUT_SKIP(FILE,SIZE)  \
 fprintf (FILE, "\t.space " HOST_WIDE_INT_PRINT_UNSIGNED"\n", (SIZE))

/* Define the syntax of labels and symbol definitions/declarations.  */

/* This says how to output an assembler line
  to define a global common symbol.  */

#define
 ASM_OUTPUT_COMMON(FILE, NAME, SIZE, ROUNDED)  \
( fputs (".comm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u\n", (int)(ROUNDED)))

/* This says how to output an assembler line
  to define a local common symbol.  */

#define ASM_OUTPUT_LOCAL(FILE, NAME, SIZE, ROUNDED)  \
( fputs (".lcomm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u\n", (int)(ROUNDED)))

#ifdef HAVE_GAS_LCOMM_WITH_ALIGNMENT
#define ASM_OUTPUT_ALIGNED_LOCAL(FILE, NAME, SIZE, ALIGNMENT)  \
( fputs (".lcomm ", (FILE)),   \
 assemble_name ((FILE), (NAME)),  \
 fprintf ((FILE), ",%u,%u\n", (int)(SIZE), (int)(ALIGNMENT) / BITS_PER_UNIT))
#endif

/* This is how to output an assembler line
  that says to advance the location counter
  to a multiple of 2**LOG bytes.  */

#define ASM_OUTPUT_ALIGN(FILE,LOG) \
```

```
 if ((LOG)!=0) fprintf ((FILE), "\t.align %d\n", (LOG))

/* This is how to store into the string BUF
  the symbol_ref name of an internal numbered label
 where
  PREFIX is the class of label and NUM is the number within the class.
  This is suitable for output with `assemble_name'.  */

#define ASM_GENERATE_INTERNAL_LABEL(BUF,PREFIX,NUMBER) \
   sprintf ((BUF), "*%s%ld", (PREFIX), (long)(NUMBER))

/* The prefix to add to user-visible assembler symbols.  */

#define USER_LABEL_PREFIX "_"

/* Sequent has some changes in the format of DBX symbols.  */
#define DBX_NO_XREFS 1

/* Don't split DBX symbols into continuations.  */
#define DBX_CONTIN_LENGTH 0
```

```
================================================================================
compiler_rt License
================================================================================

The compiler_rt library is dual licensed under both the University of Illinois
"BSD-Like" license and the MIT license.  As a user of this code you may choose
to use it under either license.  As a contributor, you agree to allow your code
to be used under both.

Full text of the relevant licenses is included below.

================================================================================

University of Illinois/NCSA
Open Source License

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:

  LLVM Team

  University of Illinois at Urbana-Champaign

  http://llvm.org
```

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal with the Software without restriction,
including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimers.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimers in the documentation and/or other materials provided with the distribution.

* Neither the names of the LLVM Team, University of Illinois at Urbana-Champaign, nor the names of its contributors may be used to endorse or promote products derived from this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

==========

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or
substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

==
Copyrights and Licenses for Third Party Software Distributed with LLVM:
==
The LLVM software contains code written by third parties. Such software will
have its own individual LICENSE.TXT file in the directory in which it appears.
This file will describe the copyrights, license, and restrictions which apply
to that code.

The disclaimer of
 warranty in the University of Illinois Open Source License
applies to all code in the LLVM Distribution, and nothing in any of the
other licenses gives permission to use the names of the LLVM Team or the
University of Illinois to endorse or promote products derived from this
Software.

The following pieces of software have additional or alternate copyrights,
licenses, and/or restrictions:

Program   Directory
-------   ---------
mach_override   lib/interception/mach_override
@node Library Copying
@appendixsec GNU LESSER GENERAL PUBLIC LICENSE

@cindex LGPL, Lesser General Public License
@center Version 2.1, February 1999

@display
Copyright @copyright{} 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street - Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence the
version number 2.1.]
@end display

@appendixsubsec Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change

free software---to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software---typically libraries---of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be

consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the @dfn{Lesser} General Public License because it does @emph{Less} to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and

modification follow. Pay close attention to the difference between a
``work based on the library'' and a ``work that uses the library''. The
former contains code derived from the
 library, whereas the latter must
be combined with the library in order to run.

@iftex
@appendixsubsec TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
@end iftex
@ifinfo
@center GNU LESSER GENERAL PUBLIC LICENSE
@center TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
@end ifinfo

@enumerate 0
@item
This License Agreement applies to any software library or other program
which contains a notice placed by the copyright holder or other
authorized party saying it may be distributed under the terms of this
Lesser General Public License (also called ``this License''). Each
licensee is addressed as ``you''.

 A ``library'' means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

 The ``Library'', below, refers to any such software library or work
which has been distributed under these terms. A ``work based on the
Library'' means
 either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or translated
straightforwardly into another language. (Hereinafter, translation is
included without limitation in the term ``modification''.)

 ``Source code'' for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control compilation
and installation of the library.

 Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether

that is true depends on what the Library does
and what the program that uses the Library does.

@item
You may copy and distribute verbatim copies of the Library's
complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the
Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a
fee.

@item
You may modify your copy or copies of the Library or any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

@enumerate a
@item
The modified work must itself be a software library.

@item
You must cause
the files modified to carry prominent notices
stating that you changed the files and the date of any change.

@item
You must cause the whole of the work to be licensed at no
charge to all third parties under the terms of this License.

@item
If a facility in the modified Library refers to a function or a
table of data to be supplied by an application program that uses
the facility, other than as an argument passed when the facility
is invoked, then you must make a good faith effort to ensure that,
in the event an application does not supply such function or
table, the facility still operates, and performs whatever part of
its purpose remains meaningful.

(For example, a function in a library to compute square roots has
a purpose that is entirely well-defined independent of the
application. Therefore, Subsection 2d requires that any
application-supplied function or table used by this function must

be optional: if the application does not supply it, the square
root function must still
 compute square roots.)
@end enumerate

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Library,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work
 based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

@item
You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

 Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

 This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

@item
You may copy and distribute the Library
 (or a portion or
derivative of it, under Section 2) in object code or executable form

under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

@item
A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a ``work that uses the Library''. Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However,
linking a ``work that uses the Library'' with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a ``work that uses the library''. The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a ``work that uses the Library'' uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work.
(Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

@item
As an exception to the Sections above, you may also combine or link a ``work that uses the Library'' with the Library to produce a

work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices,
you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of this License. Also, you must do one
of these things:

@enumerate a
@item
Accompany the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable ``work that
uses the Library'', as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

@item
Use a suitable shared library mechanism for linking with the Library. A
suitable mechanism is one that (1) uses at run time
a copy of the
library already present on the user's computer system, rather than
copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs
one, as long as the modified version is interface-compatible with the
version that the work was made with.

@item
Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

@item
If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

@item
Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.
@end enumerate

For an executable, the required form of the ``work that uses the
Library" must include any data and utility programs needed for
reproducing
the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies the
executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

@item
You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that
you do these two things:

@enumerate a
@item
Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other library
facilities. This must be distributed under the terms of the
Sections above.

@item
Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.
@end enumerate

@item
You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or

distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

@item
You are not required to accept this License, since you have not signed it. However,
nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

@item
Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

@item
If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions
are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims
or to contest validity of any
such claims; this section has the sole purpose of protecting the

integrity of the free software distribution system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

@item
If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded.
  In such case, this License incorporates the limitation as if
written in the body of this License.

@item
The Free Software Foundation may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
``any later version'', you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

@item
If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software
 which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

@center NO WARRANTY

@item
BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY ``AS IS'' WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item
IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED
 TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A
FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF
SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH
DAMAGES.
@end enumerate

@iftex
@heading END OF TERMS AND CONDITIONS
@end iftex
@ifinfo
@center END OF TERMS AND CONDITIONS
@end ifinfo

@page
@appendixsubsec How to Apply These Terms to Your New Libraries

 If you develop a new library, and you want it to be of the greatest
possible use to the public, we recommend making it free software that
everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively,
 under the terms of the
ordinary General Public License).

 To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
``copyright'' line and a pointer to where the full notice is found.

@smallexample

@var{one line to give the library's name and an idea of what it does.}
Copyright (C) @var{year} @var{name of author}

This library is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 2.1 of the License, or (at
your option) any later version.

This library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should
 have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301,
USA.
@end smallexample

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a ``copyright disclaimer'' for the library, if
necessary. Here is a sample; alter the names:

@smallexample
Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

@var{signature of Ty Coon}, 1 April 1990
Ty Coon, President of Vice
@end smallexample

That's all there is to it!
     GNU GENERAL PUBLIC LICENSE
       Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
   51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

      Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free

software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work
which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim
copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such

interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is

allowed only for noncommercial distribution and only if you
received the program in object code
or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy
the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.
Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version
number of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE
LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the
License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands
`show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org

bzip2/libbzip2 version 1.0.6 of 6 September 2010

MIT License (MIT)

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
 USE OR OTHER DEALINGS IN THE
SOFTWARE.
Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone
and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on
any computer system, and to alter it and redistribute it, subject
to the following restrictions:

1. The author is not responsible for the consequences of use of this
  software, no matter how awful, even if they arise from flaws in it.

2. The origin of this software must not be misrepresented, either by
  explicit claim or by omission. Since few users ever read sources,
  credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be
  misrepresented as being the original software. Since few users
  ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

=-=-=-

*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES
 OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)COPYRIGHT 8.1 (Berkeley) 3/16/94
*/
==========
The LLVM Project is under the Apache License v2.0 with LLVM Exceptions:
==========

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common

control with that entity. For the purposes of this definition,
"control" means (i) the
power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached
to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition,
"submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative
Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work
includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional
attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License
does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,

whether in tort (including
negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such
obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and
limitations under the License.

---- LLVM Exceptions to the Apache 2.0 License ----

As an exception, if, as a result of your compiling your source code, portions
of this Software are embedded into an Object form of such source code, you
may redistribute such embedded portions in such Object form without complying
with the conditions of Sections 4(a), 4(b) and 4(d) of the License.

In addition, if you combine or link compiled
forms of this Software with
software that is licensed under the GPLv2 ("Combined Software") and if a
court of competent jurisdiction determines that the patent provision (Section
3), the indemnity provision (Section 9) or other Section of the License
conflicts with the conditions of the GPLv2, you may retroactively and
prospectively choose to deem waived or otherwise exclude such Section(s) of
the License, but only in their entirety and only with respect to the Combined
Software.

==
Software from third parties included in the LLVM Project:
==
The LLVM Project contains third party software which is under different license
terms. All such code will be identified clearly using at least one of two
mechanisms:
1) It will be in a separate directory tree with its own `LICENSE.txt` or
`LICENSE` file at the top containing the specific
license and restrictions
which apply to that software, or
2) It will contain specific license and restriction terms at the top of every
file.

==
Legacy LLVM License (https://llvm.org/docs/DeveloperPolicy.html#legacy):
==

The software contained in this directory tree is dual licensed under both the
University of Illinois "BSD-Like" license and the MIT license. As a user of
this code you may choose to use it under either license. As a contributor,
you agree to allow your code to be used under both.

Full text of the relevant licenses is included below.

==

University of Illinois/NCSA

Open Source License

Copyright (c) 2017-2019 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:
Threading Runtimes Team
Intel Corporation
http://www.intel.com

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal with the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimers.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimers in the documentation and/or other materials provided with the distribution.

* Neither the names of Intel Corporation Threading Runtimes Team nor the names of its contributors may be used to endorse or promote products derived from
this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

==========

Copyright (c) 2017-2019 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software,

and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
GCC RUNTIME LIBRARY EXCEPTION

Version 3.1, 31 March 2009

Copyright (C) 2009 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this
license document, but changing it is not allowed.

This GCC Runtime Library Exception ("Exception") is an additional
permission under section 7 of the GNU General Public License, version

3 ("GPLv3"). It applies to a given file (the "Runtime Library") that bears a notice placed by the copyright holder of the file stating that the file is governed by GPLv3 along with this Exception.

When you use GCC to compile a program, GCC may combine portions of certain GCC header files and runtime libraries with the compiled program. The purpose of this Exception is to allow compilation of non-GPL (including proprietary) programs to use, in this way, the header files and runtime libraries covered by this Exception.

0. Definitions.

A file is an "Independent Module" if it either requires the Runtime Library
for execution after a Compilation Process, or makes use of an interface provided by the Runtime Library, but is not otherwise based on the Runtime Library.

"GCC" means a version of the GNU Compiler Collection, with or without modifications, governed by version 3 (or a specified later version) of the GNU General Public License (GPL) with the option of using any subsequent versions published by the FSF.

"GPL-compatible Software" is software whose conditions of propagation, modification and use would permit combination with GCC in accord with the license of GCC.

"Target Code" refers to output from any compiler for a real or virtual target processor architecture, in executable form or suitable for input to an assembler, loader, linker and/or execution phase. Notwithstanding that, Target Code does not include data in any format that is used as a compiler intermediate representation, or used for producing a compiler intermediate representation.

The "Compilation Process" transforms code
entirely represented in
non-intermediate languages designed for human-written code, and/or in Java Virtual Machine byte code, into Target Code. Thus, for example, use of source code generators and preprocessors need not be considered part of the Compilation Process, since the Compilation Process can be understood as starting with the output of the generators or preprocessors.

A Compilation Process is "Eligible" if it is done using GCC, alone or with other GPL-compatible software, or if it is done without using any work based on GCC. For example, using non-GPL-compatible Software to optimize any GCC intermediate representations would not qualify as an Eligible Compilation Process.

1. Grant of Additional Permission.

You have permission to propagate a work of Target Code formed by
combining the Runtime Library with Independent Modules, even if such
propagation would otherwise violate the terms of GPLv3, provided that
all Target Code was generated by Eligible Compilation Processes. You
may
 then convey such a combination under terms of your choice,
consistent with the licensing of the Independent Modules.

2. No Weakening of GCC Copyleft.

The availability of this Exception does not imply any general
presumption that third-party software is unaffected by the copyleft
requirements of the license of GCC.
THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESSED OR
IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Unless stated otherwise, the sources under the cygwin subdirectory,
as well as the sources under the cygserver subdirectory linked into
the Cygwin DLL, are licensed under the Lesser Gnu Public License,
version 3 or (at your option) any later version (LGPLv3+). See the
COPYING.LIB file for the exact wording of that license.

Unless stated otherwise, the sources under the cygserver subdir not
linked into the Cygwin DLL, as well as the sources under the lsaauth
and the utils subdirectories are licensed under the Gnu Public License,
version 3 or (at your option) any later version (GPLv3+). See the
COPYING file for the exact wording of that license.

Parts of the sources in any subdirectory are licensed using a BSD-like
license. The affected source files contain explicit copyright notices
to that
 effect.

Linking Exception:

 As a special exception, the copyright holders of the Cygwin library
 grant you additional permission to link libcygwin.a, crt0.o, and
 gcrt0.o with independent modules to produce an executable, and to
 convey the resulting executable under terms of your choice, without
 any need to comply with the conditions of LGPLv3 section 4. An
 independent module is a module which is not itself based on the
 Cygwin library.
This is the file "copying.dj". It does not apply to any sources
copyrighted by UCB Berkeley or the Free Software Foundation.

Copyright Information for sources and executables that are marked
Copyright (C) DJ Delorie
24 Kirsten Ave
Rochester NH 03867-2954

This document is Copyright (C) DJ Delorie and may be distributed
verbatim, but changing it is not allowed.

Source code copyright DJ Delorie is distributed under the terms of the
GNU General Public Licence, with the following exceptions:

* Any existing copyright or authorship information in any given source
file must remain intact. If you modify a source file, a notice to that
effect must be added to the authorship information in the source file.

* binaries provided in djgpp may be distributed without sources ONLY if
the recipient is given sufficient information to obtain a copy of djgpp
themselves. This primarily applies to go32.exe, emu387, stub.exe, and
the graphics drivers.

* modified versions of the binaries provided
in djgpp must be
distributed under the terms of the GPL.

* objects and libraries linked into an application may be distributed
without sources.

Changes to source code copyright BSD or FSF are copyright DJ Delorie, but
fall under the terms of the original copyright.

A copy of the file "COPYING" is included with this document. If you did not
receive a copy of "COPYING", you may obtain one from whence this document
was obtained, or by writing:
Free Software Foundation
675 Mass Ave
Cambridge, MA 02139
USA
libffi - Copyright (c) 1996-2014 Anthony Green, Red Hat, Inc and others.
See source files for details.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
``Software''), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by
the Library is deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code

for portions of the Combined Work that, considered in isolation, are
based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the
object code and/or source code for the Application, including any data
and utility programs needed for reproducing the Combined Work from the
Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License
without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a
facility refers to a function or data to be supplied by an Application
that uses the facility (other than as an argument passed when the
facility is invoked), then you may convey a copy of the modified
version:

a) under this License, provided that you make a good faith effort to
ensure that, in the event an Application does not supply the
function or data, the facility still operates, and performs
whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of
this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from
a header file that is part of the Library. You may convey such object
code under terms of your choice, provided that, if the incorporated
material is not limited to numerical parameters,
data structure
layouts and accessors, or small macros, inline functions and templates
(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the
Library is used in it and that the Library and its use are
covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license
document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic

pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other

parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those

subprograms and other parts of the work.

The Corresponding Source need not include anything that users
can regenerate automatically from other parts of the Corresponding
Source.

The Corresponding Source for a work in source code form is that
same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of
copyright on the Program, and are irrevocable provided the stated
conditions are met. This License explicitly affirms your unlimited
permission to run the unmodified Program. The output from running a
covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or

modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work,

and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)

that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in

ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or

requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed

under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
GNU LIBRARY GENERAL PUBLIC LICENSE
****

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place -- Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble
========

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of

this Library General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim or with modifications and/or
translated straightforwardly into another language. (Hereinafter,
translation is included without limitation in the term
"modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code
means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the library.

Activities other than copying, distribution and modification are
not covered by this License; they are outside its scope. The act
of running
a program using the Library is not restricted, and
output from such a program is covered only if its contents
constitute a work based on the Library (independent of the use of
the Library in a tool for writing it). Whether that is true
depends on what the Library does and what the program that uses
the Library does.

1. You may copy and distribute verbatim copies of the Library's
complete source code as you receive it, in any medium, provided
that you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep
intact all the notices that refer to this License and to the
absence of any warranty; and distribute a copy of this License
along with the Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange
for a fee.

2. You may modify your copy or copies of the Library or
any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

a. The modified work must itself be a software library.

b. You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c. You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d. If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and

performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License,
whose permissions
for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public
License instead of this License to a given copy of the Library.
To do this, you must alter all the notices that refer to this
License, so that they refer to the ordinary GNU General Public
License, version 2, instead of to this License. (If a
newer
version than version 2 of the ordinary GNU General Public License
has appeared, then you can specify that version instead if you
wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to
all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable
form under the terms of Sections 1 and 2 above provided that you
accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software
interchange.

If distribution of object code is
made by offering access to copy
from a designated place, then offering equivalent access to copy
the source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being
compiled or linked with it, is called a "work that uses the
Library". Such a work, in isolation, is not a derivative work of
the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because
it contains portions of the Library), rather than a "work that
uses the library". The executable is therefore covered by this
License. Section 6 states terms for distribution of such
executables.

When a "work that uses the Library" uses material from a header
file that is part of the Library, the object code for the work may
be a derivative work of the Library even though the source code is

not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any
executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a.
Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b. Accompany the work with a written offer, valid for at least

three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of

performing this distribution.

c. If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d. Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries
that do not normally
accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a. Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b. Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the

Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License
to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously

your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of

any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO

WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT
UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries
==========

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution
under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

ONE LINE TO GIVE THE LIBRARY'S NAME AND AN IDEA OF WHAT IT DOES.
Copyright (C) YEAR NAME OF AUTHOR

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Library General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper
mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library
`Frob' (a library for tweaking knobs) written by James Random Hacker.

SIGNATURE OF TY COON, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library is

deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code
for portions of the Combined Work that, considered in isolation, are
based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the
object code and/or source code for the Application, including any data
and utility programs needed for reproducing the Combined Work from the
Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License
without being bound by section 3 of the GNU GPL.

2. Conveying
Modified Versions.

If you modify a copy of the Library, and, in your modifications, a
facility refers to a function or data to be supplied by an Application
that uses the facility (other than as an argument passed when the
facility is invoked), then you may convey a copy of the modified
version:

a) under this License, provided that you make a good faith effort to
ensure that, in the event an Application does not supply the
function or data, the facility still operates, and performs
whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of
this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from
a header file that is part of the Library. You may convey such object
code under terms of your choice, provided that, if the incorporated
material is not limited to numerical parameters, data
structure
layouts and accessors, or small macros, inline functions and templates

(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide

whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/. Unicode Data Files do not include PDF online code charts under the directory http://www.unicode.org/Public/. Software includes any source code published in the Unicode Standard or under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode, Inc. All rights reserved. Distributed under the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software that the data or software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR

PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.
Copyright (c) 2019 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.167 pcre2-syntax 10.40-6.el9

1.167.1 Available under license :

PCRE2 LICENCE

Please see the file LICENCE in the PCRE2 distribution for licensing details.

End
PCRE2 LICENCE

PCRE2 is a library of functions to support regular expressions whose syntax
and semantics are as close as possible to those of the Perl 5 language.

Releases 10.00 and above of PCRE2 are distributed under the terms of the "BSD"
licence, as specified below, with one exemption for certain binary
redistributions. The documentation for PCRE2, supplied in the "doc" directory,
is distributed under the same terms as the software itself. The data in the
testdata directory is not copyrighted and is in the public domain.

The basic library functions are written in C and are freestanding. Also
included in the distribution is a just-in-time compiler that can be used to
optimize pattern matching. This is an optional feature that can be omitted when
the library is built.

THE BASIC LIBRARY FUNCTIONS

Written by: Philip Hazel
Email local part: Philip.Hazel
Email domain: gmail.com

Retired from University of Cambridge Computing Service,
Cambridge,
England.

Copyright (c) 1997-2022 University of Cambridge
All rights reserved.

PCRE2 JUST-IN-TIME COMPILATION SUPPORT

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2010-2022 Zoltan Herczeg
All rights reserved.

STACK-LESS JUST-IN-TIME COMPILER

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2009-2022 Zoltan Herczeg
All rights reserved.

THE "BSD" LICENCE

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notices,
  this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
  notices, this list of conditions and the following disclaimer
in the
  documentation and/or other materials provided with the distribution.

* Neither the name of the University of Cambridge nor the names of any
  contributors may be used to endorse or promote products derived from this
  software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,
 EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

EXEMPTION FOR BINARY LIBRARY-LIKE PACKAGES

The second condition in the BSD licence (covering binary redistributions) does
not apply all the way down a chain of software. If binary package A includes
PCRE2, it must respect the condition, but if package B is software that
includes package A, the condition is not imposed on package B unless it uses
PCRE2 independently.

End

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT
 OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.168 readline 8.1

1.168.1 Available under license :

@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to

assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that
contains a notice placed by the copyright holder saying it can be
distributed under the terms of this License. Such a notice grants a
world-wide, royalty-free license, unlimited in duration, to use that
work under the conditions stated herein. The ``Document'', below,
refers
to any such manual or work. Any member of the public is a
licensee, and is addressed as ``you''. You accept the license if you
copy, modify or distribute the work in a way requiring permission
under copyright law.

A ``Modified Version'' of the Document means any work containing the
Document or a portion of it, either copied verbatim, or with
modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section
of the Document that deals exclusively with the relationship of the
publishers or authors of the Document to the Document's overall
subject (or to related matters) and contains nothing that could fall
directly within that overall subject. (Thus, if the Document is in
part a textbook of mathematics, a Secondary Section may not explain
any mathematics.) The relationship could be a matter of historical
connection with the subject or with related matters, or of legal,
commercial, philosophical, ethical or political

position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles
are designated, as being those of Invariant Sections, in the notice
that says that the Document is released under this License. If a
section does not fit the above definition of Secondary then it is not
allowed to be designated as Invariant. The Document may contain zero
Invariant Sections. If the Document does not identify any Invariant
Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,
as Front-Cover Texts or Back-Cover Texts, in the notice that says that
the Document is released under this License. A Front-Cover Text may
be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,
represented in a format whose specification is available to the
general public, that is suitable for revising the document
straightforwardly with generic text editors or (for
images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
@sc{ascii} without markup, Texinfo input format, La@TeX{} input
format, @acronym{SGML} or @acronym{XML} using a publicly available
@acronym{DTD}, and standard-conforming simple @acronym{HTML},
PostScript or @acronym{PDF} designed for human modification. Examples
of transparent image formats include @acronym{PNG}, @acronym{XCF} and
@acronym{JPG}. Opaque formats
include proprietary formats that can be
read and edited only by proprietary word processors, @acronym{SGML} or
@acronym{XML} for which the @acronym{DTD} and/or processing tools are
not generally available, and the machine-generated @acronym{HTML},
PostScript or @acronym{PDF} produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means

the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in
 another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'', or ``History''.)  To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which
states that this License applies to the Document. These Warranty
Disclaimers are considered to be included by reference in this
License, but only as regards disclaiming warranties: any other
implication that these Warranty Disclaimers may have is void and has
no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either
commercially or noncommercially, provided that this License, the
copyright notices, and the license notice saying this License applies
to the Document are reproduced in all copies, and that you add no other
conditions whatsoever
 to those of this License. You may not use
technical measures to obstruct or control the reading or further
copying of the copies you make or distribute. However, you may accept
compensation in exchange for copies. If you distribute a large enough
number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and
you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have
printed covers) of the Document, numbering more than 100, and the
Document's license notice requires Cover Texts, you must enclose the
copies in covers that carry, clearly and legibly, all these Cover
Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on
the back cover. Both covers must also clearly and legibly identify

you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.
You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that
this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from
those of previous versions
(which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version

if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in
the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History'' section. You may omit a network location for a work that was published at

least
four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document,
you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf

of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of
each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract
a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate
and independent documents or works, in or on a volume of a storage or
distribution medium, is called an ``aggregate'' if the copyright
resulting from the compilation is not used to limit the legal rights
of the compilation's users beyond what the individual works permit.
When the Document is included in an aggregate, this License does not
apply to the other works in the aggregate which are not themselves
derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these
copies of the Document, then if the Document is less than one half of
the entire aggregate, the Document's Cover Texts may
 be placed on
covers that bracket the Document within the aggregate, or the
electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole
aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may
distribute translations of the Document under the terms of section 4.
Replacing Invariant Sections with translations requires special
permission from their copyright holders, but you may include
translations of some or all Invariant Sections in addition to the
original versions of these Invariant Sections. You may include a
translation of this License, and all the license notices in the
Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice
or disclaimer, the original
 version will prevail.

If a section in the Document is Entitled ``Acknowledgements'',
``Dedications'', or ``History'', the requirement (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document

except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies
 you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that
 a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'')
 contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the
 MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover

Texts. A copy of the license is included in the section entitled ``GNU
Free Documentation License".
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts." line with this:

@smallexample
@group
  with the Invariant Sections being @var{list their titles}, with
  the Front-Cover
Texts being @var{list}, and with the Back-Cover Texts
  being @var{list}.
@end group
@end smallexample

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to

your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could

make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of

copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;

keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms

of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded

from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,
procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the
Corresponding Source conveyed under this section must be accompanied
by the Installation Information. But this requirement does not apply
if neither you nor any third party retains the ability to install
modified object code on the User Product (for example, the work has
been installed in
ROM).

The requirement to provide Installation Information does not include a
requirement to continue to provide support service, warranty, or updates
for a work that has been modified or installed by the recipient, or for
the User Product in which it has been modified or installed. Access to a
network may be denied when the modification itself materially and
adversely affects the operation of the network or violates the rules and
protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided,
in accord with this section must be in a format that is publicly

documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for

any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the

licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to

address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it

under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.

These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the

Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of

this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or
executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering

access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to

apply and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.169 berkeley-db 5.3.28

1.169.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextDuplicate Method (LockingInfo)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_3" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_3" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle
Title="MoveNextDuplicate Method (LockingInfo)" /><MSHelp:RLTitle
Title="SecondaryCursor.MoveNextDuplicate Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate(BerkeleyDB.LockingInfo)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data
pair, move the cursor to the next key/data pair in the database, and store the secondary key and primary ..."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextDuplicate Method (LockingInfo)</td></tr><tr
id="headerTableRow3"><td align="left">SecondaryCursor Class See Also

Found in path(s):
* Report Feedback on this item in the Oracle Technology Network Forum <p />Copyright (c) 2008, 2013 Oracle. All rights reserved. </body></html>db-5.3.28/docs/csharp/html/M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_3.htm
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

Found in path(s):
* db-5.3.28/test/csharp/AllTestData.xml
* db-5.3.28/lang/java/src/com/sleepycat/db/ReplicationConfig.java
* db-5.3.28/lang/csharp/src/SecondaryHashDatabase.cs
* db-5.3.28/examples/java/src/persist/gettingStarted/SimpleDA.java
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

Found in path(s):
* }
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Cursor" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="HashDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Cursor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also

Found in path(s):
* Report Feedback on this item in the Oracle Technology Network Forum <p />Copyright (c) 2008, 2013 Oracle. All rights reserved. </body></html>db-5.3.28/docs/csharp/html/M_BerkeleyDB_HashDatabase_Cursor.htm
No license file was found, but licenses were detected in source scan.

```
/*-
* See the file LICENSE for redistribution information.
*
* Copyright (c) 1996, 2013 Oracle and/or its affiliates.  All rights reserved.
*
* $Id$
*/
```

Found in path(s):
* /db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignKeyNullifyDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ForeignKeyNullifyDelegate" /><meta name="guid" content="T_BerkeleyDB_ForeignKeyNullifyDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ForeignKeyNullifyDelegate" /><MSHelp:TOCTitle Title="ForeignKeyNullifyDelegate Delegate" /><MSHelp:RLTitle Title="ForeignKeyNullifyDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ForeignKeyNullifyDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBForeignKeyNullifyDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="ForeignKeyNullifyDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ForeignKeyNullifyDelegate delegate" /><MSHelp:Keyword Index="F" Term="ForeignKeyNullifyDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignKeyNullifyDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyNullifyDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyNullifyDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyNullifyDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyNullifyDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyNullifyDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"

src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignKeyNullifyDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also

Found in path(s):
* Report Feedback on this item in the Oracle Technology Network Forum <p />Copyright (c) 2008, 2013 Oracle. All rights reserved. </body></html>db-5.3.28/docs/csharp/html/T_BerkeleyDB_ForeignKeyNullifyDelegate.htm
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataFlags Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_MetadataFlags" /><meta name="guid" content="P_BerkeleyDB_QueueStats_MetadataFlags" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.QueueStats.MetadataFlags" /><MSHelp:TOCTitle Title="MetadataFlags Property "
/><MSHelp:RLTitle Title="QueueStats.MetadataFlags Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.QueueStats.MetadataFlags" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBQueueStatsClassMetadataFlagsTopic" /><MSHelp:Keyword Index="K"
Term="MetadataFlags property" /><MSHelp:Keyword Index="K" Term="QueueStats.MetadataFlags property"
/><MSHelp:Keyword Index="F" Term="MetadataFlags"
 /><MSHelp:Keyword Index="F" Term="QueueStats.MetadataFlags" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.QueueStats.MetadataFlags" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.QueueStats.MetadataFlags" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.QueueStats.get_MetadataFlags" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Metadata flags."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
 image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
 ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
 Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">QueueStats..::.MetadataFlags Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryQueueDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryQueueDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_SecondaryQueueDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryQueueDatabase.Open(System.String,BerkeleyDB.SecondaryQueueDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryQueueDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Open Method (String, SecondaryQueueDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryQueueDatabase.Open(System.String,BerkeleyDB.SecondaryQueueDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryQueueDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Open Method (String, SecondaryQueueDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeartbeatSend Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_HeartbeatSend" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_HeartbeatSend" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.HeartbeatSend" /><MSHelp:TOCTitle Title="HeartbeatSend Property " /><MSHelp:RLTitle Title="ReplicationConfig.HeartbeatSend Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.HeartbeatSend" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBReplicationConfigClassHeartbeatSendTopic" /><MSHelp:Keyword Index="K" Term="HeartbeatSend property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.HeartbeatSend property" /><MSHelp:Keyword Index="F" Term="HeartbeatSend" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.HeartbeatSend" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.HeartbeatSend" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.HeartbeatSend" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_HeartbeatSend" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_HeartbeatSend" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The frequency at which the replication manager, running at a master site, broadcasts a heartbeat message in an otherwise idle system. When 0 (the default), no heartbeat messages will be sent." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">ReplicationConfig..::.HeartbeatSend Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BaseDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_BaseDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.BaseDatabase" /><MSHelp:TOCTitle Title="BaseDatabase Members" /><MSHelp:RLTitle Title="BaseDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BaseDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="BaseDatabase class" /><MSHelp:Keyword Index="K" Term="BaseDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BaseDatabase class" /><MSHelp:Keyword Index="F" Term="BaseDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class Methods Properties See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxMMapSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MaxMMapSize" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxMMapSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxMMapSize" /><MSHelp:TOCTitle Title="MaxMMapSize Property " /><MSHelp:RLTitle Title="MPoolStats.MaxMMapSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxMMapSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxMMapSizeTopic" /><MSHelp:Keyword Index="K" Term="MaxMMapSize property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxMMapSize property" /><MSHelp:Keyword Index="F" Term="MaxMMapSize" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxMMapSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxMMapSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxMMapSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxMMapSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum file size for mmap." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxMMapSize Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CreationDir Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_CreationDir" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_CreationDir" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.CreationDir" /><MSHelp:TOCTitle Title="CreationDir Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.CreationDir Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.CreationDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassCreationDirTopic" /><MSHelp:Keyword Index="K" Term="CreationDir field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.CreationDir field" /><MSHelp:Keyword Index="F" Term="CreationDir" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.CreationDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.CreationDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.CreationDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of a directory to be used as the location to create the access method database files. When , , or is used to create a file it will be created relative to this path. ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;

height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.CreationDir Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorFeedbackDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ErrorFeedbackDelegate" /><meta name="guid" content="T_BerkeleyDB_ErrorFeedbackDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ErrorFeedbackDelegate" /><MSHelp:TOCTitle Title="ErrorFeedbackDelegate Delegate" /><MSHelp:RLTitle Title="ErrorFeedbackDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="T:BerkeleyDB.ErrorFeedbackDelegate" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBErrorFeedbackDelegateClassTopic" /><MSHelp:Keyword Index="K"
Term="ErrorFeedbackDelegate delegate" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.ErrorFeedbackDelegate delegate" /><MSHelp:Keyword Index="F"
Term="ErrorFeedbackDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorFeedbackDelegate"
/><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ErrorFeedbackDelegate" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ErrorFeedbackDelegate.ctor" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ErrorFeedbackDelegate.Invoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ErrorFeedbackDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ErrorFeedbackDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The application-
specified error reporting function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorFeedbackDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrev" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method " /><MSHelp:RLTitle Title="SecondaryCursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store the secondary key and primary key/data pair in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verbosity Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Verbosity" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Verbosity" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Verbosity" /><MSHelp:TOCTitle Title="Verbosity Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Verbosity Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Verbosity" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassVerbosityTopic" /><MSHelp:Keyword Index="K" Term="Verbosity field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Verbosity field" /><MSHelp:Keyword Index="F" Term="Verbosity" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.Verbosity" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.Verbosity" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.Verbosity" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specific additional informational and debugging messages in the Berkeley DB message output." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..<span
class="cpp">::.Verbosity Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MPoolConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_MPoolConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MPoolConfig" /><MSHelp:TOCTitle Title="MPoolConfig Properties " /><MSHelp:RLTitle Title="MPoolConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MPoolConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MPoolConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveFirstMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveFirstMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveFirstMultipleKey" /><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveFirstMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveFirstMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveFirstMultipleKey method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveFirstMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultipleKey" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor<span

class="cs">..::.MoveFirstMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevDuplicate_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevDuplicate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and that pair is stored in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintTransactionSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintTransactionSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintTransactionSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintTransactionSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintTransactionSystemStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats(System.Boolean,System.Boolean)"

/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the transaction subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintTransactionSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryRecnoDatabaseConfig Fields</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Fields_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><meta name="guid"
content="Fields_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:TOCTitle
Title="SecondaryRecnoDatabaseConfig
Fields" /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Fields.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetEnumerator Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_GetEnumerator" /><meta name="guid" content="M_BerkeleyDB_JoinCursor_GetEnumerator" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.GetEnumerator" /><MSHelp:TOCTitle Title="GetEnumerator Method " /><MSHelp:RLTitle Title="JoinCursor.GetEnumerator Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.GetEnumerator" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassGetEnumeratorTopic" /><MSHelp:Keyword Index="K" Term="GetEnumerator method" /><MSHelp:Keyword Index="K" Term="JoinCursor.GetEnumerator method" /><MSHelp:Keyword Index="F" Term="GetEnumerator" /><MSHelp:Keyword Index="F"

Term="JoinCursor.GetEnumerator" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.JoinCursor.GetEnumerator" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.JoinCursor.GetEnumerator" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Returns an
enumerator that iterates through the ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">JoinCursor<span
class="cs">..::<span
class="nu">.GetEnumerator Method </td></tr><tr id="headerTableRow3"><td
align="left">JoinCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Renumber Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RecnoDatabaseConfig_Renumber" /><meta name="guid" content="F_BerkeleyDB_RecnoDatabaseConfig_Renumber" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RecnoDatabaseConfig.Renumber" /><MSHelp:TOCTitle Title="Renumber Field" /><MSHelp:RLTitle Title="RecnoDatabaseConfig.Renumber Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RecnoDatabaseConfig.Renumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassRenumberTopic" /><MSHelp:Keyword Index="K" Term="Renumber field" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.Renumber field" /><MSHelp:Keyword Index="F" Term="Renumber" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.Renumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.Renumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.Renumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Cause the logical record numbers to be mutable,
and change as records are added to and deleted from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoDatabaseConfig.<span
class="vb">.::.Renumber
Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoDatabaseConfig.htm">RecnoDatabaseConfig Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepMgrConnectionFailure Field</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_VerboseMessages_RepMgrConnectionFailure"
/><meta name="guid" content="F_BerkeleyDB_VerboseMessages_RepMgrConnectionFailure"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.RepMgrConnectionFailure"
/><MSHelp:TOCTitle Title="RepMgrConnectionFailure Field" /><MSHelp:RLTitle
Title="VerboseMessages.RepMgrConnectionFailure Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.VerboseMessages.RepMgrConnectionFailure" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBVerboseMessagesClassRepMgrConnectionFailureTopic" /><MSHelp:Keyword Index="K"
Term="RepMgrConnectionFailure field" /><MSHelp:Keyword Index="K"
Term="VerboseMessages.RepMgrConnectionFailure field" /><MSHelp:Keyword Index="F"
Term="RepMgrConnectionFailure" /><MSHelp:Keyword Index="F"
Term="VerboseMessages.RepMgrConnectionFailure" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.VerboseMessages.RepMgrConnectionFailure" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr

Name="APIName" Value="BerkeleyDB.VerboseMessages.RepMgrConnectionFailure" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about Replication Manager connection failures." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.RepMgrConnectionFailure Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BufferSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_BufferSize" /><meta name="guid" content="P_BerkeleyDB_LogStats_BufferSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.BufferSize" /><MSHelp:TOCTitle Title="BufferSize Property " /><MSHelp:RLTitle Title="LogStats.BufferSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.BufferSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassBufferSizeTopic" /><MSHelp:Keyword Index="K" Term="BufferSize property" /><MSHelp:Keyword Index="K" Term="LogStats.BufferSize property" /><MSHelp:Keyword Index="F" Term="BufferSize" /><MSHelp:Keyword Index="F" Term="LogStats.BufferSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.BufferSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.BufferSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_BufferSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log buffer size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.BufferSize Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockObjectCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitLockObjectCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitLockObjectCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitLockObjectCount" /><MSHelp:TOCTitle Title="InitLockObjectCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitLockObjectCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitLockObjectCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitLockObjectCountTopic" /><MSHelp:Keyword Index="K" Term="InitLockObjectCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitLockObjectCount property" /><MSHelp:Keyword Index="F" Term="InitLockObjectCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitLockObjectCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitLockObjectCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitLockObjectCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitLockObjectCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitLockObjectCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of lock objects allocated when the environment is created" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitLockObjectCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MasterChanges

Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_MasterChanges" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MasterChanges" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MasterChanges" /><MSHelp:TOCTitle Title="MasterChanges Property " /><MSHelp:RLTitle Title="ReplicationStats.MasterChanges Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MasterChanges" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMasterChangesTopic" /><MSHelp:Keyword Index="K" Term="MasterChanges property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MasterChanges property" /><MSHelp:Keyword Index="F" Term="MasterChanges" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MasterChanges" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MasterChanges" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MasterChanges" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MasterChanges" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of times we've switched masters." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MasterChanges Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoPanic Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_NoPanic" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_NoPanic" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.NoPanic" /><MSHelp:TOCTitle Title="NoPanic Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.NoPanic Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.NoPanic" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassNoPanicTopic" /><MSHelp:Keyword Index="K" Term="NoPanic property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.NoPanic property" /><MSHelp:Keyword Index="F" Term="NoPanic" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.NoPanic" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.NoPanic" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.NoPanic" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_NoPanic" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_NoPanic" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will ignore any panic state in the database environment. (Database environments in a panic state normally refuse all attempts to call

Berkeley DB functions, throwing .) This f ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.NoPanic Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_LockStats_RegionWait" /><meta name="guid"
content="P_BerkeleyDB_LockStats_RegionWait"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.RegionWait" /><MSHelp:TOCTitle
Title="RegionWait Property " /><MSHelp:RLTitle Title="LockStats.RegionWait Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.RegionWait" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassRegionWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionWait
property" /><MSHelp:Keyword Index="K" Term="LockStats.RegionWait property" /><MSHelp:Keyword
Index="F" Term="RegionWait" /><MSHelp:Keyword Index="F" Term="LockStats.RegionWait"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.RegionWait" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockStats.RegionWait" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.get_RegionWait" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Region lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.RegionWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrAckPolicy Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_RepMgrAckPolicy" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_RepMgrAckPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.RepMgrAckPolicy" /><MSHelp:TOCTitle Title="RepMgrAckPolicy Field" /><MSHelp:RLTitle Title="ReplicationConfig.RepMgrAckPolicy Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.RepMgrAckPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassRepMgrAckPolicyTopic" /><MSHelp:Keyword Index="K" Term="RepMgrAckPolicy field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.RepMgrAckPolicy field" /><MSHelp:Keyword Index="F" Term="RepMgrAckPolicy" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.RepMgrAckPolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.RepMgrAckPolicy" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.RepMgrAckPolicy" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify how master and client sites will handle acknowledgment of replication messages which are necessary for "permanent" records. The current implementation requires all sites in a replication group ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::<span
class="nu">.RepMgrAckPolicy Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultiple_6" /><meta
name="guid" content="M_BerkeleyDB_Cursor_MoveMultiple_6" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEnt
ry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32)" /><MSHelp:TOCTitle Title="MoveMultiple
Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean,
Int32)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry),
Boolean, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEnt
ry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Move the cursor to the specified key/data pair of the database, and store that key/data pair and as many
duplicate data items associated with the given key that can fit in a buffer the size of
in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultiple Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxObjects Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxObjects" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxObjects" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxObjects" /><MSHelp:TOCTitle Title="MaxObjects Property " /><MSHelp:RLTitle Title="LockStats.MaxObjects Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxObjects" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxObjectsTopic" /><MSHelp:Keyword Index="K" Term="MaxObjects property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxObjects property" /><MSHelp:Keyword Index="F" Term="MaxObjects" /><MSHelp:Keyword Index="F" Term="LockStats.MaxObjects" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxObjects" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxObjects" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxObjects" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of objects so far." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxObjects Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (DatabaseEntry, DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_BaseDatabase_Get_2" /><meta name="guid"
content="M_BerkeleyDB_BaseDatabase_Get_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Get Method (DatabaseEntry, DatabaseEntry, Transaction)"
/><MSHelp:RLTitle Title="BaseDatabase.Get Method (DatabaseEntry, DatabaseEntry, Transaction) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Retrieve a key/data pair from the database. In the presence of duplicate key values, Get will return the first data item for . If the data is a partial , bytes starting bytes ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method (DatabaseEntry, DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSiteConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbSiteConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_DbSiteConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbSiteConfig.#ctor" /><MSHelp:TOCTitle Title="DbSiteConfig Constructor " /><MSHelp:RLTitle Title="DbSiteConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbSiteConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class, constructor" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.DbSiteConfig constructor" /><MSHelp:Keyword Index="F" Term="DbSiteConfig" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.DbSiteConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.DbSiteConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new DbSiteConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (String, String, DatabaseEnvironment)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Remove_3" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Remove_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Remove(System.String,System.String,BerkeleyDB.DatabaseEnvironment)" /><MSHelp:TOCTitle Title="Remove Method (String, String, DatabaseEnvironment)" /><MSHelp:RLTitle Title="BaseDatabase.Remove Method (String, String, DatabaseEnvironment) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Remove(System.String,System.String,BerkeleyDB.DatabaseEnvironment)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Remove"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the database specified by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Remove Method (String, String, DatabaseEnvironment)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_FastStats_2" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_FastStats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="HeapDatabase.FastStats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.FastStats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockRequests Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockRequests" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockRequests" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockRequests" /><MSHelp:TOCTitle Title="LockRequests Property " /><MSHelp:RLTitle Title="LockStats.LockRequests Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockRequests" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockRequestsTopic" /><MSHelp:Keyword Index="K" Term="LockRequests property" /><MSHelp:Keyword Index="K" Term="LockStats.LockRequests property" /><MSHelp:Keyword Index="F" Term="LockRequests" /><MSHelp:Keyword Index="F" Term="LockStats.LockRequests" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockRequests" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockRequests" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockRequests" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lock gets." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockRequests Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_SecondaryCursor_Delete" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_Delete" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.Delete" /><MSHelp:TOCTitle Title="Delete Method "
/><MSHelp:RLTitle Title="SecondaryCursor.Delete Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Delete" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassDeleteTopic" /><MSHelp:Keyword Index="K"
Term="Delete method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.Delete method"
/><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.Delete"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.Delete" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryCursor.Delete" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Delete the key/data pair to which the cursor refers from the primary
database and all secondary indices." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">SecondaryCursor..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoLogs Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BackupOptions_NoLogs" /><meta name="guid" content="F_BerkeleyDB_BackupOptions_NoLogs" /><xml><MSHelp:Attr
 Name="AssetID" Value="F:BerkeleyDB.BackupOptions.NoLogs" /><MSHelp:TOCTitle Title="NoLogs Field" /><MSHelp:RLTitle Title="BackupOptions.NoLogs Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BackupOptions.NoLogs" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassNoLogsTopic" /><MSHelp:Keyword Index="K" Term="NoLogs field" /><MSHelp:Keyword Index="K" Term="BackupOptions.NoLogs field" /><MSHelp:Keyword Index="F" Term="NoLogs" /><MSHelp:Keyword Index="F" Term="BackupOptions.NoLogs" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.NoLogs" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions.NoLogs" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, log files are not included in the backup. Instead, only *.db files are copied to the target directory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions..::.NoLogs Field</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepHoldElection Method (UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta
name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepHoldElection_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepHoldElection_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepHoldElection(System.UInt32)" /><MSHelp:TOCTitle Title="RepHoldElection Method (UInt32)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepHoldElection Method (UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepHoldElection(System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepHoldElection"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Hold an election for the master of a replication group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepHoldElection Method (UInt32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EnvironmentID Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_EnvironmentID" /><meta name="guid" content="T_BerkeleyDB_EnvironmentID" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EnvironmentID" /><MSHelp:TOCTitle Title="EnvironmentID Enumeration" /><MSHelp:RLTitle Title="EnvironmentID Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EnvironmentID" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.EnvironmentID.EID_BROADCAST" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.EnvironmentID.EID_INVALID" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.EnvironmentID.EID_MASTER" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEnvironmentIDClassTopic" /><MSHelp:Keyword Index="K" Term="EnvironmentID enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EnvironmentID enumeration" /><MSHelp:Keyword Index="K" Term="EID_BROADCAST enumeration member" /><MSHelp:Keyword Index="K" Term="EID_INVALID enumeration member" /><MSHelp:Keyword Index="K" Term="EID_MASTER enumeration member" /><MSHelp:Keyword Index="F" Term="EnvironmentID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentID" /><MSHelp:Keyword Index="F" Term="EnvironmentID.EID_BROADCAST" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentID.EID_BROADCAST" /><MSHelp:Keyword Index="F" Term="EnvironmentID.EID_INVALID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentID.EID_INVALID" /><MSHelp:Keyword Index="F" Term="EnvironmentID.EID_MASTER" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentID.EID_MASTER" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentID.EID_BROADCAST" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentID.EID_INVALID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentID.EID_MASTER" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Special environment IDs." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EnvironmentID Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabaseConfig_SetForeignKeyConstraint" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabaseConfig_SetForeignKeyConstraint" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:TOCTitle Title="SetForeignKeyConstraint Method " /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.SetForeignKeyConstraint Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassSetForeignKeyConstraintTopic" /><MSHelp:Keyword Index="K" Term="SetForeignKeyConstraint method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.SetForeignKeyConstraint method" /><MSHelp:Keyword Index="F" Term="SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.SetForeignKeyConstraint Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryCursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Members" /><MSHelp:RLTitle Title="SecondaryCursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryCursor class" /><MSHelp:Keyword Index="K" Term="SecondaryCursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryCursor class" /><MSHelp:Keyword Index="F" Term="SecondaryCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All
</nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class Methods
Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupOptions
Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Methods_T_BerkeleyDB_BackupOptions" /><meta name="guid"
content="Methods_T_BerkeleyDB_BackupOptions" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.BackupOptions" /><MSHelp:TOCTitle Title="BackupOptions Methods "
/><MSHelp:RLTitle Title="BackupOptions Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Methods.T:BerkeleyDB.BackupOptions" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBackupOptionsMethodsTopic" /><MSHelp:Keyword Index="K" Term="BackupOptions
class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions Methods </td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Refresh_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_Refresh_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Refresh Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.Refresh Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers in . If either the key or the data is partial , its bytes starting bytes from the beginning of the retrieved data reco ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Refresh Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MutexSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_MutexSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_MutexSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:TOCTitle Title="MutexSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.MutexSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMutexSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="MutexSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MutexSystemStats method" /><MSHelp:Keyword Index="F" Term="MutexSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MutexSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span

id="memberOptionsDropdown" class="filter" tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MutexSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveLast_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveLast_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry,

LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkel
eyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to
refer to the last key/data pair of the database, and store the secondary key and primary key/data pair in . If the last
key has duplicate values, the last data item in the set of ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryCursor.<span
class="vb">.::.MoveLast Method
(DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td
align="left">SecondaryCursor Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>SendRequest Method (DatabaseEntry[], Int32, UInt32)</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DbChannel_SendRequest" /><meta name="guid"
content="M_BerkeleyDB_DbChannel_SendRequest" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DbChannel.SendRequest(BerkeleyDB.DatabaseEntry[],System.Int32,System.UInt32)"
/><MSHelp:TOCTitle Title="SendRequest Method (DatabaseEntry[], Int32, UInt32)" /><MSHelp:RLTitle
Title="DbChannel.SendRequest Method (DatabaseEntry[], Int32, UInt32) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.DbChannel.SendRequest(BerkeleyDB.DatabaseEntry[],System.Int32,System.UInt32)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.SendRequest"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Send a message on the message channel. The message is sent synchronously. The method blocks waiting for a response before returning.
If a response is not received within the timeout value configur ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.SendRequest Method (array<DatabaseEntry>[]()[], Int32, UInt32)</td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Deadlocks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactData_Deadlocks" /><meta name="guid" content="P_BerkeleyDB_CompactData_Deadlocks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactData.Deadlocks" /><MSHelp:TOCTitle Title="Deadlocks Property " /><MSHelp:RLTitle Title="CompactData.Deadlocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactData.Deadlocks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassDeadlocksTopic" /><MSHelp:Keyword Index="K" Term="Deadlocks property" /><MSHelp:Keyword Index="K" Term="CompactData.Deadlocks property" /><MSHelp:Keyword Index="F" Term="Deadlocks" /><MSHelp:Keyword Index="F" Term="CompactData.Deadlocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData.Deadlocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.Deadlocks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.get_Deadlocks" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If no parameter was specified, the number of deadlocks which occurred." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData..::.Deadlocks Property </td></tr><tr id="headerTableRow3"><td align="left">CompactData
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LockingConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_LockingConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LockingConfig" /><MSHelp:TOCTitle Title="LockingConfig Properties " /><MSHelp:RLTitle Title="LockingConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LockingConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="LockingConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_PageSize" /><meta name="guid" content="P_BerkeleyDB_QueueStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="QueueStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="QueueStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="QueueStats.PageSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page size." /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxPermanentLSN Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_ReplicationStats_MaxPermanentLSN" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_MaxPermanentLSN" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.MaxPermanentLSN" /><MSHelp:TOCTitle Title="MaxPermanentLSN
Property " /><MSHelp:RLTitle Title="ReplicationStats.MaxPermanentLSN Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MaxPermanentLSN"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMaxPermanentLSNTopic"
/><MSHelp:Keyword Index="K" Term="MaxPermanentLSN property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.MaxPermanentLSN property" /><MSHelp:Keyword Index="F"
Term="MaxPermanentLSN" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MaxPermanentLSN"
/><MSHelp:Keyword
Index="F" Term="BerkeleyDB.ReplicationStats.MaxPermanentLSN" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.MaxPermanentLSN" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationStats.get_MaxPermanentLSN" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Maximum permanent LSN." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MaxPermanentLSN Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignConflictException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ForeignConflictException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ForeignConflictException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ForeignConflictException" /><MSHelp:TOCTitle Title="ForeignConflictException Members" /><MSHelp:RLTitle Title="ForeignConflictException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ForeignConflictException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBForeignConflictExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="ForeignConflictException class" /><MSHelp:Keyword Index="K" Term="ForeignConflictException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ForeignConflictException class" /><MSHelp:Keyword Index="F" Term="ForeignConflictException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignConflictException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignConflictException Members</td></tr><tr id="headerTableRow3"><td align="left">ForeignConflictException Class Constructors Methods Fields Properties See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InOrder Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabase_InOrder" /><meta name="guid" content="P_BerkeleyDB_QueueDatabase_InOrder" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueDatabase.InOrder" /><MSHelp:TOCTitle Title="InOrder Property " /><MSHelp:RLTitle Title="QueueDatabase.InOrder Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabase.InOrder" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassInOrderTopic" /><MSHelp:Keyword Index="K" Term="InOrder property" /><MSHelp:Keyword Index="K" Term="QueueDatabase.InOrder property" /><MSHelp:Keyword Index="F" Term="InOrder" /><MSHelp:Keyword Index="F" Term="QueueDatabase.InOrder" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.InOrder" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.InOrder" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.get_InOrder" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, modify the operation of to return key/data pairs in order. That is, they will always return the key/data item from the head of the queue." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.InOrder Property </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUnique_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUnique_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUnique(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUnique Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextUnique Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUnique(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized,

MoveNextUnique is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum in . MoveN ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUnique Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepNoBlocking

Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepNoBlocking" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepNoBlocking" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepNoBlocking" /><MSHelp:TOCTitle Title="RepNoBlocking Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepNoBlocking Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepNoBlocking" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepNoBlockingTopic" /><MSHelp:Keyword Index="K" Term="RepNoBlocking property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepNoBlocking property" /><MSHelp:Keyword Index="F" Term="RepNoBlocking" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepNoBlocking" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepNoBlocking" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepNoBlocking" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepNoBlocking" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepNoBlocking" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB method calls that would normally block while clients are in recovery will return errors immediately (defaults to false)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepNoBlocking Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingInfo Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LockingInfo" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LockingInfo" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LockingInfo" /><MSHelp:TOCTitle Title="LockingInfo Members" /><MSHelp:RLTitle Title="LockingInfo Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LockingInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingInfoMembersTopic" /><MSHelp:Keyword Index="K" Term="LockingInfo class" /><MSHelp:Keyword Index="K" Term="LockingInfo class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockingInfo class" /><MSHelp:Keyword Index="F" Term="LockingInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingInfo" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingInfo Members</td></tr><tr id="headerTableRow3"><td align="left">LockingInfo Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Stats_2" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Stats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="Stats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="QueueDatabase.Stats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Stats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TxnNoWait" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TxnNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TxnNoWait" /><MSHelp:TOCTitle Title="TxnNoWait Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TxnNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TxnNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTxnNoWaitTopic" /><MSHelp:Keyword Index="K" Term="TxnNoWait property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TxnNoWait property" /><MSHelp:Keyword Index="F" Term="TxnNoWait" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TxnNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TxnNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TxnNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TxnNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TxnNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true and a lock is unavailable for any Berkeley DB operation performed in the context

of a transaction, cause the operation to throw (or if configured with)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TxnNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_NOTFOUND Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script

type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_NOTFOUND" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_NOTFOUND" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_NOTFOUND" /><MSHelp:TOCTitle Title="DB_NOTFOUND Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_NOTFOUND Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_NOTFOUND" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_NOTFOUNDTopic" /><MSHelp:Keyword Index="K" Term="DB_NOTFOUND field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_NOTFOUND field" /><MSHelp:Keyword Index="F" Term="DB_NOTFOUND" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_NOTFOUND" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_NOTFOUND" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_NOTFOUND" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Key/data pair not found (EOF)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_NOTFOUND Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LogStats" /><meta name="guid" content="Methods_T_BerkeleyDB_LogStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LogStats" /><MSHelp:TOCTitle Title="LogStats Methods " /><MSHelp:RLTitle Title="LogStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LogStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="LogStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats Methods </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script

type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_Sequence" /><meta name="guid" content="Properties_T_BerkeleyDB_Sequence" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.Sequence" /><MSHelp:TOCTitle Title="Sequence Properties " /><MSHelp:RLTitle Title="Sequence Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.Sequence" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequencePropertiesTopic" /><MSHelp:Keyword Index="K" Term="Sequence class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence Properties </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_PutNoOverwrite" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.PutNoOverwrite" /><MSHelp:TOCTitle Title="PutNoOverwrite Method " /><MSHelp:RLTitle Title="BTreeDatabase.PutNoOverwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassPutNoOverwriteTopic" /><MSHelp:Keyword Index="K" Term="PutNoOverwrite method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.PutNoOverwrite method" /><MSHelp:Keyword Index="F" Term="PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.PutNoOverwrite Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabase
Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Properties_T_BerkeleyDB_QueueDatabase" /><meta name="guid"
content="Properties_T_BerkeleyDB_QueueDatabase" /><xml><MSHelp:Attr
Name="AssetID" Value="Properties.T:BerkeleyDB.QueueDatabase" /><MSHelp:TOCTitle Title="QueueDatabase
Properties " /><MSHelp:RLTitle Title="QueueDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Properties.T:BerkeleyDB.QueueDatabase" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBQueueDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabase
class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FailedMessageSends Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_FailedMessageSends" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_FailedMessageSends" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.FailedMessageSends" /><MSHelp:TOCTitle Title="FailedMessageSends Property " /><MSHelp:RLTitle Title="ReplicationStats.FailedMessageSends Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.FailedMessageSends" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassFailedMessageSendsTopic" /><MSHelp:Keyword Index="K" Term="FailedMessageSends property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.FailedMessageSends property" /><MSHelp:Keyword Index="F" Term="FailedMessageSends" /><MSHelp:Keyword Index="F" Term="ReplicationStats.FailedMessageSends" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.FailedMessageSends" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.FailedMessageSends" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_FailedMessageSends" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of failed message sends." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.FailedMessageSends Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MovePrev" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method " /><MSHelp:RLTitle Title="BTreeCursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MovePrev" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMovePrevTopic" /><MSHelp:Keyword Index="K" Term="MovePrev method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MovePrev method" /><MSHelp:Keyword Index="F" Term="MovePrev" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MovePrev" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_MPoolStats" /><meta name="guid" content="Methods_T_BerkeleyDB_MPoolStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.MPoolStats" /><MSHelp:TOCTitle Title="MPoolStats Methods " /><MSHelp:RLTitle Title="MPoolStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.MPoolStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="MPoolStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse

image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats Methods </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>AppliedTransactions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_ReplicationStats_AppliedTransactions" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_AppliedTransactions" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.AppliedTransactions" /><MSHelp:TOCTitle Title="AppliedTransactions
Property " /><MSHelp:RLTitle Title="ReplicationStats.AppliedTransactions Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.AppliedTransactions"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassAppliedTransactionsTopic"
/><MSHelp:Keyword Index="K" Term="AppliedTransactions property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.AppliedTransactions property" /><MSHelp:Keyword Index="F"
Term="AppliedTransactions" /><MSHelp:Keyword Index="F" Term="ReplicationStats.AppliedTransactions"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.AppliedTransactions" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.AppliedTransactions" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.get_AppliedTransactions" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of transactions applied." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.AppliedTransactions Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecoveryException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RunRecoveryException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RunRecoveryException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RunRecoveryException" /><MSHelp:TOCTitle Title="RunRecoveryException Members" /><MSHelp:RLTitle Title="RunRecoveryException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RunRecoveryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRunRecoveryExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RunRecoveryException class" /><MSHelp:Keyword Index="F" Term="RunRecoveryException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RunRecoveryException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RunRecoveryException Members</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_RunRecoveryException.htm">RunRecoveryException Class Constructors Methods Fields Properties
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_Move" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.Move" /><MSHelp:TOCTitle Title="Move Method " /><MSHelp:RLTitle Title="BTreeCursor.Move Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.Move" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveTopic" /><MSHelp:Keyword Index="K" Term="Move method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.Move method" /><MSHelp:Keyword Index="F" Term="Move" /><MSHelp:Keyword Index="F" Term="BTreeCursor.Move" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img id="devlangsDropdownImage"

src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Move Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Refresh" /><meta name="guid" content="M_BerkeleyDB_Cursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="Cursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Refresh" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Refresh Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor

Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Files Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BackupOptions_Files" /><meta name="guid" content="F_BerkeleyDB_BackupOptions_Files" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BackupOptions.Files" /><MSHelp:TOCTitle Title="Files Field" /><MSHelp:RLTitle Title="BackupOptions.Files Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BackupOptions.Files" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassFilesTopic" /><MSHelp:Keyword Index="K" Term="Files field" /><MSHelp:Keyword Index="K" Term="BackupOptions.Files field" /><MSHelp:Keyword Index="F" Term="Files" /><MSHelp:Keyword Index="F" Term="BackupOptions.Files" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.Files" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions.Files" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, all ordinary files that might exist in the environment, as well as might exist in the environment's subdirectories, are backed up; otherwise, only files necessary for the proper operation of ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions..::.Files Field</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MessagesSent Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_MessagesSent" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MessagesSent" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MessagesSent" /><MSHelp:TOCTitle Title="MessagesSent Property " /><MSHelp:RLTitle Title="ReplicationStats.MessagesSent Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MessagesSent" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMessagesSentTopic" /><MSHelp:Keyword Index="K" Term="MessagesSent property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MessagesSent property" /><MSHelp:Keyword Index="F" Term="MessagesSent" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MessagesSent" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MessagesSent" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MessagesSent" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MessagesSent" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of successful message sends." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::<span
class="nu">.MessagesSent Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SyncMemPool Method (LSN)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_SyncMemPool_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_SyncMemPool_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.SyncMemPool(BerkeleyDB.LSN)" /><MSHelp:TOCTitle Title="SyncMemPool Method (LSN)" /><MSHelp:RLTitle Title="DatabaseEnvironment.SyncMemPool Method (LSN) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.SyncMemPool(BerkeleyDB.LSN)" />
<MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SyncMemPool" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Flush modified pages in the cache with log sequence numbers less than to their backing files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SyncMemPool Method (LSN)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogRegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogRegionSize" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogRegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogRegionSize" /><MSHelp:TOCTitle Title="LogRegionSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogRegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogRegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="LogRegionSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogRegionSize property" /><MSHelp:Keyword Index="F" Term="LogRegionSize" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogRegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogRegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogRegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogRegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogRegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the underlying logging area of the Berkeley DB environment, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogRegionSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbThreadID Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DbThreadID" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DbThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DbThreadID" /><MSHelp:TOCTitle Title="DbThreadID Members" /><MSHelp:RLTitle Title="DbThreadID Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DbThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbThreadIDMembersTopic" /><MSHelp:Keyword Index="K" Term="DbThreadID class" /><MSHelp:Keyword Index="K" Term="DbThreadID class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbThreadID class" /><MSHelp:Keyword Index="F" Term="DbThreadID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbThreadID" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID Members</td></tr><tr id="headerTableRow3"><td align="left">DbThreadID Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetThreadID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_SetThreadID" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_SetThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.SetThreadID" /><MSHelp:TOCTitle Title="SetThreadID Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.SetThreadID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.SetThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassSetThreadIDTopic" /><MSHelp:Keyword Index="K" Term="SetThreadID property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.SetThreadID property" /><MSHelp:Keyword Index="F" Term="SetThreadID" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.SetThreadID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.SetThreadID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SetThreadID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_SetThreadID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_SetThreadID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A delegate that

returns a unique identifier pair for the current thread of control." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SetThreadID Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitRegions Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"

/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_InitRegions" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_InitRegions" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.InitRegions" /><MSHelp:TOCTitle Title="InitRegions Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.InitRegions Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.InitRegions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassInitRegionsTopic" /><MSHelp:Keyword Index="K" Term="InitRegions field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.InitRegions field" /><MSHelp:Keyword Index="F" Term="InitRegions" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.InitRegions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.InitRegions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.InitRegions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will page-fault
shared regions into memory when initially creating or joining a Berkeley DB environment. In addition, Berkeley DB will write the shared regions when creating an ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.InitRegions Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheInfo Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_CacheInfo" /><meta name="guid" content="T_BerkeleyDB_CacheInfo" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.CacheInfo" /><MSHelp:TOCTitle Title="CacheInfo Class" /><MSHelp:RLTitle Title="CacheInfo Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.CacheInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoClassTopic" /><MSHelp:Keyword Index="K" Term="CacheInfo class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CacheInfo class" /><MSHelp:Keyword Index="K" Term="CacheInfo class, about CacheInfo class" /><MSHelp:Keyword Index="F" Term="CacheInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CacheInfo" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CacheInfo" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class to represent information about the Berkeley DB cache" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CacheInfo Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Reads Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_Reads" /><meta name="guid" content="P_BerkeleyDB_LogStats_Reads" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.Reads" /><MSHelp:TOCTitle Title="Reads Property " /><MSHelp:RLTitle Title="LogStats.Reads Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.LogStats.Reads" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogStatsClassReadsTopic" /><MSHelp:Keyword Index="K" Term="Reads property"
/><MSHelp:Keyword Index="K" Term="LogStats.Reads property" /><MSHelp:Keyword Index="F"
Term="Reads" /><MSHelp:Keyword Index="F" Term="LogStats.Reads" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LogStats.Reads" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogStats.Reads" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogStats.get_Reads" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Total I/O reads from the log." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">LogStats.<span
class="vb">.::.Reads Property

</td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NonDurableTxns Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_NonDurableTxns" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_NonDurableTxns" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.NonDurableTxns" /><MSHelp:TOCTitle Title="NonDurableTxns Field" /><MSHelp:RLTitle Title="DatabaseConfig.NonDurableTxns Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.NonDurableTxns" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassNonDurableTxnsTopic" /><MSHelp:Keyword Index="K" Term="NonDurableTxns field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.NonDurableTxns field" /><MSHelp:Keyword Index="F" Term="NonDurableTxns" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.NonDurableTxns" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.NonDurableTxns" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.NonDurableTxns" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will not write log records for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.NonDurableTxns Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OldVersionException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_OldVersionException" /><meta name="guid" content="Fields_T_BerkeleyDB_OldVersionException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.OldVersionException" /><MSHelp:TOCTitle Title="OldVersionException Fields" /><MSHelp:RLTitle Title="OldVersionException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.OldVersionException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBOldVersionExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="OldVersionException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">OldVersionException Fields</td></tr><tr id="headerTableRow3"><td align="left">OldVersionException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RepMgrStats" /><meta name="guid" content="T_BerkeleyDB_RepMgrStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RepMgrStats" /><MSHelp:TOCTitle Title="RepMgrStats Class" /><MSHelp:RLTitle Title="RepMgrStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RepMgrStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsClassTopic" /><MSHelp:Keyword Index="K" Term="RepMgrStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RepMgrStats class" /><MSHelp:Keyword Index="K" Term="RepMgrStats class, about RepMgrStats class" /><MSHelp:Keyword Index="F" Term="RepMgrStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about the Replication Manager" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="HashDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="HashDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Open Method

</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLockers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockingConfig_MaxLockers" /><meta name="guid" content="P_BerkeleyDB_LockingConfig_MaxLockers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockingConfig.MaxLockers" /><MSHelp:TOCTitle Title="MaxLockers Property " /><MSHelp:RLTitle Title="LockingConfig.MaxLockers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockingConfig.MaxLockers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigClassMaxLockersTopic" /><MSHelp:Keyword Index="K" Term="MaxLockers property" /><MSHelp:Keyword Index="K" Term="LockingConfig.MaxLockers property" /><MSHelp:Keyword Index="F" Term="MaxLockers" /><MSHelp:Keyword Index="F" Term="LockingConfig.MaxLockers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.MaxLockers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.MaxLockers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.get_MaxLockers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.set_MaxLockers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum number of simultaneous locking entities supported by the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
  <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.MaxLockers Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadIsAlive Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_ThreadIsAlive" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_ThreadIsAlive" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.ThreadIsAlive" /><MSHelp:TOCTitle Title="ThreadIsAlive Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.ThreadIsAlive Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.ThreadIsAlive" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassThreadIsAliveTopic" /><MSHelp:Keyword Index="K" Term="ThreadIsAlive property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ThreadIsAlive

property" /><MSHelp:Keyword
Index="F" Term="ThreadIsAlive" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ThreadIsAlive"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ThreadIsAlive" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ThreadIsAlive" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_ThreadIsAlive" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_ThreadIsAlive" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A delegate that returns if a thread of control (either a true thread or a process) is still
running." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment<span
class="languageSpecificText">..<span
class="cpp">::.ThreadIsAlive Property </td></tr><tr

id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8"
/><META NAME="save" CONTENT="history" /><title>RepAutoInit Property </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepAutoInit" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepAutoInit" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.RepAutoInit"
/><MSHelp:TOCTitle Title="RepAutoInit Property " /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepAutoInit Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.RepAutoInit" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepAutoInitTopic" /><MSHelp:Keyword Index="K"
Term="RepAutoInit property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepAutoInit
property" /><MSHelp:Keyword Index="F" Term="RepAutoInit" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepAutoInit" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepAutoInit" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepAutoInit" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_RepAutoInit" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.set_RepAutoInit"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, the replication master will automatically re-initialize outdated
clients (defaults to true)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepAutoInit Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, HashDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Open(System.String,BerkeleyDB.HashDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, HashDatabaseConfig)" /><MSHelp:RLTitle Title="HashDatabase.Open Method (String, HashDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Open(System.String,BerkeleyDB.HashDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HashDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Open Method (String, HashDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Add Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_HashCursor_Add" /><meta name="guid"
content="Overload_BerkeleyDB_HashCursor_Add" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashCursor.Add" /><MSHelp:TOCTitle Title="Add Method " /><MSHelp:RLTitle
Title="HashCursor.Add Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.HashCursor.Add" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashCursorClassAddTopic" /><MSHelp:Keyword Index="K" Term="Add method"
/><MSHelp:Keyword Index="K" Term="HashCursor.Add method" /><MSHelp:Keyword Index="F" Term="Add"
/><MSHelp:Keyword Index="F" Term="HashCursor.Add" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashCursor.Add" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HashCursor<span
class="cs">..::<span
class="nu">.Add Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashCursor.htm">HashCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method
(CursorConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_BTreeDatabase_Cursor_2" /><meta name="guid"
content="M_BerkeleyDB_BTreeDatabase_Cursor_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)"
/><MSHelp:TOCTitle Title="Cursor Method (CursorConfig, Transaction)" /><MSHelp:RLTitle
Title="BTreeDatabase.Cursor Method (CursorConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.BTreeDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Cursor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor with the given

configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Cursor Method (CursorConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Levels Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_Levels" /><meta name="guid"
content="P_BerkeleyDB_RecnoStats_Levels" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.RecnoStats.Levels" /><MSHelp:TOCTitle Title="Levels Property " /><MSHelp:RLTitle
Title="RecnoStats.Levels Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.RecnoStats.Levels" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoStatsClassLevelsTopic" /><MSHelp:Keyword Index="K" Term="Levels property"
/><MSHelp:Keyword Index="K" Term="RecnoStats.Levels property" /><MSHelp:Keyword Index="F"
Term="Levels" /><MSHelp:Keyword Index="F" Term="RecnoStats.Levels" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoStats.Levels" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RecnoStats.Levels" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoStats.get_Levels" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Tree levels." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>
<img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.Levels Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BeginTransaction Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_BeginTransaction" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_BeginTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:TOCTitle Title="BeginTransaction Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.BeginTransaction Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBeginTransactionTopic" /><MSHelp:Keyword Index="K" Term="BeginTransaction method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BeginTransaction method" /><MSHelp:Keyword Index="F" Term="BeginTransaction" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BeginTransaction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BeginTransaction Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Join Method

</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Join" /><meta name="guid" content="M_BerkeleyDB_Database_Join" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Join(BerkeleyDB.SecondaryCursor[],System.Boolean)" /><MSHelp:TOCTitle Title="Join Method " /><MSHelp:RLTitle Title="Database.Join Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Join(BerkeleyDB.SecondaryCursor[],System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassJoinTopic" /><MSHelp:Keyword Index="K" Term="Join method" /><MSHelp:Keyword Index="K" Term="Database.Join method" /><MSHelp:Keyword Index="F" Term="Join" /><MSHelp:Keyword Index="F" Term="Database.Join" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Join" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Join" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a specialized join cursor for use in performing equality or natural joins on secondary indices." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Join Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintReplicationSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintReplicationSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintReplicationSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:TOCTitle Title="PrintReplicationSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintReplicationSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the replication subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintReplicationSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_RecnoCursor_MoveNextUniqueMultipleKey" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MoveNextUniqueMultipleKey" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextUniqueMultipleKey"
/><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey
Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNextUniqueMultipleKey Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNextUniqueMultipleKey"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveNextUniqueMultipleKeyTopic"
/><MSHelp:Keyword Index="K" Term="MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="K"
Term="RecnoCursor.MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="F"
Term="MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F"
Term="RecnoCursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoCursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoCursor.<span
class="vb">.::.MoveNextUniqueMultipleKey
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoCursor.htm">RecnoCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>DatabaseEnvironmentConfig Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="AllMembers_T_BerkeleyDB_DatabaseEnvironmentConfig"
/><meta name="guid" content="AllMembers_T_BerkeleyDB_DatabaseEnvironmentConfig"
/><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DatabaseEnvironmentConfig"
/><MSHelp:TOCTitle Title="DatabaseEnvironmentConfig Members" /><MSHelp:RLTitle
Title="DatabaseEnvironmentConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="AllMembers.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigMembersTopic" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig class" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig
class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseEnvironmentConfig class"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Attr Name="HelpPriority" Value="1"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig Members</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class Constructors Methods Fields Properties
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintSubsystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintSubsystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintSubsystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintSubsystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintSubsystemStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats(System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintSubsystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveLast" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="Cursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.Cursor.MoveLast" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store that pair in . If the last key has duplicate values, the last data item in the set of duplicates is stored in . ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveLast Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst
Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_SecondaryCursor_MoveFirst_1" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_MoveFirst_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berke
leyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveFirst Method (DatabaseEntry, DatabaseEntry,
DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveFirst Method (DatabaseEntry, DatabaseEntry,
DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkel
eyDB.DatabaseEntry)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store the secondary
key along with the corresponding primary key/data pair in . If the first key has duplicate values, the f ..."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveFirst Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Stats_2" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Stats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="Stats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="BTreeDatabase.Stats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Stats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_SequenceStats_CacheSize" /><meta name="guid"
content="P_BerkeleyDB_SequenceStats_CacheSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SequenceStats.CacheSize" /><MSHelp:TOCTitle Title="CacheSize Property "
/><MSHelp:RLTitle Title="SequenceStats.CacheSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SequenceStats.CacheSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSequenceStatsClassCacheSizeTopic" /><MSHelp:Keyword
Index="K" Term="CacheSize property" /><MSHelp:Keyword Index="K" Term="SequenceStats.CacheSize
property" /><MSHelp:Keyword Index="F" Term="CacheSize" /><MSHelp:Keyword Index="F"
Term="SequenceStats.CacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.CacheSize"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.CacheSize"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_CacheSize" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Cache size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">SequenceStats..::.CacheSize Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Stats" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="HashDatabase.Stats Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Stats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Open" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Open
Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUnique_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUnique_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum in . MoveN ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrRunElections Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrRunElections" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrRunElections" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepMgrRunElections" /><MSHelp:TOCTitle Title="RepMgrRunElections Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrRunElections Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepMgrRunElections" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrRunElectionsTopic" /><MSHelp:Keyword Index="K" Term="RepMgrRunElections property" /><MSHelp:Keyword Index="K"

Term="DatabaseEnvironment.RepMgrRunElections property" /><MSHelp:Keyword Index="F"
Term="RepMgrRunElections" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepMgrRunElections" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepMgrRunElections" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrRunElections" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepMgrRunElections" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepMgrRunElections"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, Replication Manager automatically runs elections to choose a
new master when the old master appears to have become disconnected (defaults to true)." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span

class="nu">.RepMgrRunElections Property </td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextDuplicateMultiple Method (LockingInfo)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple_1" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle
Title="MoveNextDuplicateMultiple Method (LockingInfo)" /><MSHelp:RLTitle
Title="Cursor.MoveNextDuplicateMultiple Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next
key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next
key/data pair in the database, and store that pair and as many duplicate data ..." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultiple Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, RecnoDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Open(System.String,BerkeleyDB.RecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, RecnoDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Open Method (String, RecnoDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Open(System.String,BerkeleyDB.RecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="Abstract" Value="Instantiate a new RecnoDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::<span
class="nu">.Open Method (String, RecnoDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryBTreeDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryBTreeDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Open Method (String, String, SecondaryBTreeDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryBTreeDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Open Method (String, String, SecondaryBTreeDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TempDir Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TempDir" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TempDir" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.TempDir" /><MSHelp:TOCTitle Title="TempDir Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TempDir Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.TempDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTempDirTopic" /><MSHelp:Keyword Index="K" Term="TempDir field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TempDir field" /><MSHelp:Keyword Index="F" Term="TempDir" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TempDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TempDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TempDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of a directory to be used as the location of temporary files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TempDir Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_ThreadID" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_ThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.ThreadID" /><MSHelp:TOCTitle Title="ThreadID Property " /><MSHelp:RLTitle Title="ActiveTransaction.ThreadID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.ThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassThreadIDTopic" /><MSHelp:Keyword Index="K" Term="ThreadID property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.ThreadID property" /><MSHelp:Keyword Index="F" Term="ThreadID" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.ThreadID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.ThreadID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.ThreadID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_ThreadID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The thread of control ID of the originator of the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction..::.ThreadID Property </td></tr><tr id="headerTableRow3"><td
align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LogStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LogStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LogStats" /><MSHelp:TOCTitle Title="LogStats Members" /><MSHelp:RLTitle Title="LogStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LogStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="LogStats class" /><MSHelp:Keyword Index="K" Term="LogStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LogStats class" /><MSHelp:Keyword Index="F" Term="LogStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
  <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats Members</td></tr><tr id="headerTableRow3"><td align="left">LogStats Class Methods
Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SequenceStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SequenceStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SequenceStats" /><MSHelp:TOCTitle Title="SequenceStats Members" /><MSHelp:RLTitle Title="SequenceStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SequenceStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="SequenceStats class" /><MSHelp:Keyword Index="K"
Term="SequenceStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SequenceStats class" /><MSHelp:Keyword Index="F" Term="SequenceStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats Members</td></tr><tr id="headerTableRow3"><td align="left">SequenceStats
Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AppendRecordDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_AppendRecordDelegate" /><meta name="guid" content="T_BerkeleyDB_AppendRecordDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.AppendRecordDelegate" /><MSHelp:TOCTitle Title="AppendRecordDelegate Delegate" /><MSHelp:RLTitle Title="AppendRecordDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.AppendRecordDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAppendRecordDelegateClassTopic"
/><MSHelp:Keyword Index="K" Term="AppendRecordDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.AppendRecordDelegate delegate" /><MSHelp:Keyword Index="F" Term="AppendRecordDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AppendRecordDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.AppendRecordDelegate" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.AppendRecordDelegate.ctor" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.AppendRecordDelegate.Invoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.AppendRecordDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.AppendRecordDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A function to call after the record number has been selected but before the data has been
stored into the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">AppendRecordDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left"><a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_FastStats_2" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_FastStats_2"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="HashDatabase.FastStats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.FastStats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Type Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Type" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_Type" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.Type" /><MSHelp:TOCTitle Title="Type Property " /><MSHelp:RLTitle Title="BaseDatabase.Type Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.Type" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassTypeTopic" /><MSHelp:Keyword Index="K" Term="Type property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Type property" /><MSHelp:Keyword Index="F" Term="Type" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Type" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Type" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Type" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_Type" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The type of the underlying access method (and file format). This value may be used to determine the type of the database after an ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Type Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Fields_T_BerkeleyDB_SecondaryDatabaseConfig" /><meta name="guid"
content="Fields_T_BerkeleyDB_SecondaryDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryDatabaseConfig
Fields" /><MSHelp:RLTitle Title="SecondaryDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Fields.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ConsumeInOrder Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_QueueDatabaseConfig_ConsumeInOrder" /><meta name="guid" content="F_BerkeleyDB_QueueDatabaseConfig_ConsumeInOrder" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.QueueDatabaseConfig.ConsumeInOrder" /><MSHelp:TOCTitle Title="ConsumeInOrder Field" /><MSHelp:RLTitle Title="QueueDatabaseConfig.ConsumeInOrder Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.QueueDatabaseConfig.ConsumeInOrder" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassConsumeInOrderTopic" /><MSHelp:Keyword Index="K" Term="ConsumeInOrder field" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig.ConsumeInOrder field" /><MSHelp:Keyword Index="F" Term="ConsumeInOrder" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig.ConsumeInOrder" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig.ConsumeInOrder" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.ConsumeInOrder" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, modify the operation of to return key/data pairs in order. That is, they will always

return the key/data item from the head of the queue." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig..::.ConsumeInOrder Field</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_SecondaryCursor_Duplicate" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_Duplicate" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.Duplicate(System.Boolean)" /><MSHelp:TOCTitle Title="Duplicate
Method " /><MSHelp:RLTitle Title="SecondaryCursor.Duplicate Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.SecondaryCursor.Duplicate(System.Boolean)" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryCursorClassDuplicateTopic" /><MSHelp:Keyword Index="K" Term="Duplicate
method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.Duplicate method" /><MSHelp:Keyword
Index="F" Term="Duplicate" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.Duplicate"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.Duplicate"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Duplicate"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Create a new cursor that uses the same transaction and locker ID as the
original cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Duplicate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NextPage Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_NextPage" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_NextPage" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.NextPage" /><MSHelp:TOCTitle Title="NextPage Property " /><MSHelp:RLTitle Title="ReplicationStats.NextPage Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.NextPage" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassNextPageTopic" /><MSHelp:Keyword Index="K" Term="NextPage property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.NextPage property" /><MSHelp:Keyword Index="F" Term="NextPage" /><MSHelp:Keyword Index="F" Term="ReplicationStats.NextPage" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.NextPage" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.NextPage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_NextPage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Next pg we expect." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.NextPage Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Legacy Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_Legacy" /><meta name="guid" content="P_BerkeleyDB_DbSite_Legacy" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSite.Legacy" /><MSHelp:TOCTitle Title="Legacy Property " /><MSHelp:RLTitle Title="DbSite.Legacy Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.DbSite.Legacy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassLegacyTopic" /><MSHelp:Keyword Index="K" Term="Legacy property" /><MSHelp:Keyword Index="K" Term="DbSite.Legacy property" /><MSHelp:Keyword Index="F" Term="Legacy" /><MSHelp:Keyword Index="F" Term="DbSite.Legacy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.Legacy" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.Legacy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.get_Legacy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.set_Legacy" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is within a legacy group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.Legacy Property

</td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
 charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionTiebreaker Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionTiebreaker" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionTiebreaker" /><xml><MSHelp:Attr
 Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionTiebreaker" /><MSHelp:TOCTitle Title="ElectionTiebreaker Property " /><MSHelp:RLTitle Title="ReplicationStats.ElectionTiebreaker Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionTiebreaker" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionTiebreakerTopic" /><MSHelp:Keyword Index="K" Term="ElectionTiebreaker property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionTiebreaker property" /><MSHelp:Keyword Index="F" Term="ElectionTiebreaker" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionTiebreaker" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionTiebreaker" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionTiebreaker" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionTiebreaker"
 /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Election tiebreaker value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
 id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionTiebreaker Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_LogConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_LogConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.LogConfig" /><MSHelp:TOCTitle Title="LogConfig Fields" /><MSHelp:RLTitle Title="LogConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.LogConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="LogConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_RegionSize" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="MPoolStats.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="MPoolStats.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="MPoolStats.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MPoolStats<span
class="cs">..::<span
class="nu">.RegionSize Property </td></tr><tr id="headerTableRow3"><td
align="left">MPoolStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MoveMultiple Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_Cursor_MoveMultiple"
/><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveMultiple" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:TOCTitle
Title="MoveMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBCursorClassMoveMultipleTopic" /><MSHelp:Keyword Index="K"
Term="MoveMultiple method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveMultiple method"
/><MSHelp:Keyword Index="F" Term="MoveMultiple" /><MSHelp:Keyword Index="F"
Term="Cursor.MoveMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveMultiple"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"

Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..<span

class="cpp">::.MoveMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Version Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_Version" /><meta name="guid" content="P_BerkeleyDB_HashStats_Version" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.Version" /><MSHelp:TOCTitle Title="Version Property " /><MSHelp:RLTitle Title="HashStats.Version Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.Version" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassVersionTopic" /><MSHelp:Keyword Index="K" Term="Version property" /><MSHelp:Keyword Index="K" Term="HashStats.Version property" /><MSHelp:Keyword Index="F" Term="Version" /><MSHelp:Keyword Index="F" Term="HashStats.Version" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.Version" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.Version" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_Version" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Version number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HashStats.<span
class="vb">.::.Version Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashStats.htm">HashStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AddUnique
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_BTreeCursor_AddUnique" /><meta name="guid"
content="M_BerkeleyDB_BTreeCursor_AddUnique" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeCursor.AddUnique(System.Collections.Generic.KeyValuePair{BerkeleyDB.Database
Entry,BerkeleyDB.DatabaseEntry})" /><MSHelp:TOCTitle Title="AddUnique Method " /><MSHelp:RLTitle
Title="BTreeCursor.AddUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BTreeCursor.AddUnique(System.Collections.Generic.KeyValuePair{BerkeleyDB.Database
Entry,BerkeleyDB.DatabaseEntry})" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeCursorClassAddUniqueTopic" /><MSHelp:Keyword Index="K" Term="AddUnique
method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.AddUnique method" /><MSHelp:Keyword
Index="F" Term="AddUnique" /><MSHelp:Keyword Index="F" Term="BTreeCursor.AddUnique"
/><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeCursor.AddUnique" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.BTreeCursor.AddUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Insert the specified key/data pair into the database, unless a key/data pair comparing equally to it already exists in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.AddUnique Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveLast_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveLast_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveLast Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MoveLast Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store that pair in . If the last key has duplicate values, the last data item in the set of duplicates is stored in . If eith ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveLast Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryDatabase" /><MSHelp:TOCTitle Title="SecondaryDatabase Members" /><MSHelp:RLTitle Title="SecondaryDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase class" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryDatabase class" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">SecondaryDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNext" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="Cursor.MoveNext Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNext" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair in . In the presence of duplicate key val ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Constructor (String, UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationHostAddress__ctor_2" /><meta name="guid" content="M_BerkeleyDB_ReplicationHostAddress__ctor_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationHostAddress.#ctor(System.String,System.UInt32)" /><MSHelp:TOCTitle Title="ReplicationHostAddress Constructor (String, UInt32)" /><MSHelp:RLTitle Title="ReplicationHostAddress Constructor (String, UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationHostAddress.#ctor(System.String,System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationHostAddress..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new address" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress Constructor (String, UInt32)</td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_QueueDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_QueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"

Value="Properties.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:TOCTitle Title="QueueDatabaseConfig Properties " /><MSHelp:RLTitle Title="QueueDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig class, properties" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RemoveDB Method (String, String, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB_2" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.String,System.Boolean)" /><MSHelp:TOCTitle Title="RemoveDB Method (String, String, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RemoveDB Method (String, String, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.String,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the database specified by and . If no database is specified, the underlying file represented by is removed, incidentally removing all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RemoveDB Method (String, String, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BeginTransaction Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_BeginTransaction" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_BeginTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:TOCTitle Title="BeginTransaction Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.BeginTransaction Method

(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new transaction in the environment, with the default configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BeginTransaction Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordLength Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoDatabase_RecordLength" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabase_RecordLength" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabase.RecordLength" /><MSHelp:TOCTitle Title="RecordLength Property " /><MSHelp:RLTitle Title="RecnoDatabase.RecordLength Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabase.RecordLength" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassRecordLengthTopic" /><MSHelp:Keyword Index="K" Term="RecordLength property" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.RecordLength property" /><MSHelp:Keyword Index="F" Term="RecordLength" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.RecordLength" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.RecordLength" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.RecordLength" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.get_RecordLength" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.set_RecordLength" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If using fixed-length, not byte-delimited records, the length of the records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.RecordLength Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MoveLast" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMoveLastTopic" /><MSHelp:Keyword Index="K" Term="MoveLast method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MoveLast method" /><MSHelp:Keyword Index="F" Term="MoveLast" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MoveLast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td>
<label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveLast Method </td></tr><tr

id="headerTableRow3"><td align="left">SecondaryCursor Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
 rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_FastStats_2" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_FastStats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="BTreeDatabase.FastStats
 Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
 height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
 event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.FastStats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextDuplicateMultiple" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextDuplicateMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextDuplicateMultiple" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultiple Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextDuplicateMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextDuplicateMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveNextDuplicateMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockConflictsNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockConflictsNoWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockConflictsNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockConflictsNoWait" /><MSHelp:TOCTitle Title="LockConflictsNoWait Property " /><MSHelp:RLTitle Title="LockStats.LockConflictsNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockConflictsNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockConflictsNoWaitTopic" /><MSHelp:Keyword Index="K" Term="LockConflictsNoWait property" /><MSHelp:Keyword Index="K" Term="LockStats.LockConflictsNoWait property" /><MSHelp:Keyword Index="F" Term="LockConflictsNoWait" /><MSHelp:Keyword Index="F" Term="LockStats.LockConflictsNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockConflictsNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockConflictsNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockConflictsNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Lock conflicts w/o subsequent wait" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockConflictsNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseMVCC Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_UseMVCC" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_UseMVCC" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.UseMVCC" /><MSHelp:TOCTitle Title="UseMVCC Property " /><MSHelp:RLTitle Title="BaseDatabase.UseMVCC Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.BaseDatabase.UseMVCC" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassUseMVCCTopic" /><MSHelp:Keyword Index="K" Term="UseMVCC property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.UseMVCC property" /><MSHelp:Keyword Index="F" Term="UseMVCC" /><MSHelp:Keyword Index="F" Term="BaseDatabase.UseMVCC" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.UseMVCC" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.UseMVCC" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_UseMVCC" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the database was opened with support for multiversion concurrency control." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::<span

class="nu">.UseMVCC Property </td></tr><tr
id="headerTableRow3"><td align="left">BaseDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_RecnoDatabase_Stats_2" /><meta name="guid"
content="M_BerkeleyDB_RecnoDatabase_Stats_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.RecnoDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)"
/><MSHelp:TOCTitle Title="Stats Method (Transaction, Isolation)" /><MSHelp:RLTitle
Title="RecnoDatabase.Stats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.RecnoDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr
Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical
information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Stats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, DatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Open_2" /><meta name="guid" content="M_BerkeleyDB_Database_Open_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Open(System.String,System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, DatabaseConfig)" /><MSHelp:RLTitle Title="Database.Open Method (String, String, DatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Open(System.String,System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new Database object and open the database represented by and . The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Open Method (String, String, DatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_QueueStats" /><meta name="guid" content="Methods_T_BerkeleyDB_QueueStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.QueueStats" /><MSHelp:TOCTitle Title="QueueStats Methods " /><MSHelp:RLTitle Title="QueueStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.QueueStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="QueueStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats Methods </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupBufferSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_BackupBufferSize" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_BackupBufferSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.BackupBufferSize" /><MSHelp:TOCTitle Title="BackupBufferSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.BackupBufferSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.BackupBufferSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupBufferSizeTopic" /><MSHelp:Keyword Index="K" Term="BackupBufferSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BackupBufferSize property" /><MSHelp:Keyword Index="F" Term="BackupBufferSize" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BackupBufferSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BackupBufferSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BackupBufferSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_BackupBufferSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_BackupBufferSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the buffer, in bytes, to read from the database during a hot backup." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BackupBufferSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_Database_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="Database.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="Database.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="Database.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::<span
class="nu">.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="BaseDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassPrintStatsTopic"
/><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="BaseDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RenameDB Method (String, String, String, Boolean, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB_3" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="RenameDB Method (String, String, String, Boolean, Transaction)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RenameDB Method (String, String, String, Boolean, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the database specified by and to . If no database is specified, the underlying file represented by is renamed using the value supplied to , incidentally renaming all of the ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment<span
class="languageSpecificText">..<span
class="cpp">::.RenameDB Method (String, String, String, Boolean,
Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Stats Method (Boolean)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Sequence_Stats_1" /><meta name="guid" content="M_BerkeleyDB_Sequence_Stats_1"
/><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.Sequence.Stats(System.Boolean)" /><MSHelp:TOCTitle Title="Stats
Method (Boolean)" /><MSHelp:RLTitle Title="Sequence.Stats Method (Boolean) (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Stats(System.Boolean)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Stats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Return statistical information for this sequence." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Stats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_Duplicates" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Duplicates Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Duplicates property" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.Duplicates" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the insertion of duplicate data items in the database is permitted, and whether duplicates items are sorted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Duplicates Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNext" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="HashCursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNext" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextTopic" /><MSHelp:Keyword Index="K" Term="MoveNext method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNext method" /><MSHelp:Keyword Index="F" Term="MoveNext" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNext" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" />
<MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReceivedMessages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ReplicationStats_ReceivedMessages" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_ReceivedMessages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.ReceivedMessages" /><MSHelp:TOCTitle Title="ReceivedMessages
Property " /><MSHelp:RLTitle Title="ReplicationStats.ReceivedMessages Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ReceivedMessages" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBReplicationStatsClassReceivedMessagesTopic" /><MSHelp:Keyword
Index="K" Term="ReceivedMessages property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.ReceivedMessages property" /><MSHelp:Keyword Index="F" Term="ReceivedMessages"
/><MSHelp:Keyword Index="F" Term="ReplicationStats.ReceivedMessages" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationStats.ReceivedMessages" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.ReceivedMessages" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationStats.get_ReceivedMessages" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Messages received and processed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"

data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ReceivedMessages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_QueueDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_QueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:TOCTitle Title="QueueDatabaseConfig Members" /><MSHelp:RLTitle Title="QueueDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.QueueDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Files Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_Files" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_Files" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.Files" /><MSHelp:TOCTitle Title="Files Property " /><MSHelp:RLTitle Title="MPoolStats.Files Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.Files" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassFilesTopic" /><MSHelp:Keyword Index="K" Term="Files property" /><MSHelp:Keyword Index="K" Term="MPoolStats.Files property" /><MSHelp:Keyword Index="F" Term="Files" /><MSHelp:Keyword Index="F" Term="MPoolStats.Files" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.Files" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.Files" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_Files" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Stats for files open in the memory pool" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.Files Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultipleKey Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultipleKey is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum a ..." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUniqueMultipleKey Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Append_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Append_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Append(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Append Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Append Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Append(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append the data item to the end of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Append Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexSystemCfg Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_MutexSystemCfg" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_MutexSystemCfg" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.MutexSystemCfg" /><MSHelp:TOCTitle Title="MutexSystemCfg Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.MutexSystemCfg Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.MutexSystemCfg" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassMutexSystemCfgTopic" /><MSHelp:Keyword Index="K" Term="MutexSystemCfg field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.MutexSystemCfg field" /><MSHelp:Keyword Index="F" Term="MutexSystemCfg" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.MutexSystemCfg" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.MutexSystemCfg" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.MutexSystemCfg" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration for the mutex subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.MutexSystemCfg Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EmptyPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_EmptyPages" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_EmptyPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.EmptyPages" /><MSHelp:TOCTitle Title="EmptyPages Property " /><MSHelp:RLTitle Title="RecnoStats.EmptyPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.RecnoStats.EmptyPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassEmptyPagesTopic" /><MSHelp:Keyword Index="K" Term="EmptyPages property" /><MSHelp:Keyword Index="K" Term="RecnoStats.EmptyPages property" /><MSHelp:Keyword Index="F" Term="EmptyPages" /><MSHelp:Keyword Index="F" Term="RecnoStats.EmptyPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.EmptyPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.EmptyPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_EmptyPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Empty pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..<span

class="cpp">::.EmptyPages Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryHashDatabaseConfig Members" /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryHashDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockPolicy Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_DeadlockPolicy" /><meta
name="guid" content="Fields_T_BerkeleyDB_DeadlockPolicy" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.DeadlockPolicy" /><MSHelp:TOCTitle Title="DeadlockPolicy Fields"
/><MSHelp:RLTitle Title="DeadlockPolicy Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.DeadlockPolicy" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDeadlockPolicyFieldsTopic" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy
class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy Fields</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_FastStats_2" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_FastStats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="QueueDatabase.FastStats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.FastStats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_FastStats_1" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_FastStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction)" /><MSHelp:RLTitle Title="QueueDatabase.FastStats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase.<span

class="vb">.::.FastStats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnWriteNoSync Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnWriteNoSync" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnWriteNoSync" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnWriteNoSync" /><MSHelp:TOCTitle Title="TxnWriteNoSync Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TxnWriteNoSync Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnWriteNoSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTxnWriteNoSyncTopic" /><MSHelp:Keyword Index="K" Term="TxnWriteNoSync field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TxnWriteNoSync field" /><MSHelp:Keyword Index="F" Term="TxnWriteNoSync" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TxnWriteNoSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TxnWriteNoSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TxnWriteNoSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will write, but will not synchronously flush, the log on transaction commit." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TxnWriteNoSync Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_CacheSize" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_CacheSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.CacheSize" /><MSHelp:TOCTitle Title="CacheSize Property " /><MSHelp:RLTitle Title="LogVerifyConfig.CacheSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.CacheSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassCacheSizeTopic" /><MSHelp:Keyword Index="K"

Term="CacheSize property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.CacheSize property" /><MSHelp:Keyword Index="F" Term="CacheSize" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.CacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.CacheSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.CacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_CacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_CacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The cache size for the internal database environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.CacheSize Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_LogVerifyConfig.htm">LogVerifyConfig Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultiple_7" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultiple_7" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database, and store that key/data pair and as many duplicate data items associated with the given key that can fit in a buffer the size of in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultiple Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IgnoredMessages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_IgnoredMessages" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_IgnoredMessages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.IgnoredMessages" /><MSHelp:TOCTitle Title="IgnoredMessages Property " /><MSHelp:RLTitle Title="ReplicationStats.IgnoredMessages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.IgnoredMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassIgnoredMessagesTopic" /><MSHelp:Keyword Index="K" Term="IgnoredMessages property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.IgnoredMessages

property" /><MSHelp:Keyword Index="F" Term="IgnoredMessages" /><MSHelp:Keyword Index="F" Term="ReplicationStats.IgnoredMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.IgnoredMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.IgnoredMessages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_IgnoredMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Messages ignored because this site was a client in recovery." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.IgnoredMessages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="BTreeDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BucketPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_BucketPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_HashStats_BucketPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.BucketPagesFreeBytes" /><MSHelp:TOCTitle Title="BucketPagesFreeBytes Property " /><MSHelp:RLTitle Title="HashStats.BucketPagesFreeBytes Property (BerkeleyDB)"

/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.BucketPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassBucketPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="BucketPagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="HashStats.BucketPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="BucketPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="HashStats.BucketPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.BucketPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.BucketPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_BucketPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes
free on bucket pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats.<span

class="vb">.::.BucketPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSiteConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_DbSiteConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_DbSiteConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.DbSiteConfig" /><MSHelp:TOCTitle Title="DbSiteConfig Fields" /><MSHelp:RLTitle Title="DbSiteConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.DbSiteConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Append" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Append" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Append" /><MSHelp:TOCTitle Title="Append Method " /><MSHelp:RLTitle Title="RecnoDatabase.Append Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Append" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassAppendTopic" /><MSHelp:Keyword Index="K" Term="Append method"

/><MSHelp:Keyword Index="K" Term="RecnoDatabase.Append method" /><MSHelp:Keyword Index="F" Term="Append" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Append" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"

/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Append
Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Offset Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LSN_Offset" /><meta name="guid" content="F_BerkeleyDB_LSN_Offset" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LSN.Offset" /><MSHelp:TOCTitle Title="Offset Field" /><MSHelp:RLTitle Title="LSN.Offset Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LSN.Offset" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNClassOffsetTopic" /><MSHelp:Keyword Index="K" Term="Offset field" /><MSHelp:Keyword Index="K" Term="LSN.Offset field" /><MSHelp:Keyword Index="F" Term="Offset" /><MSHelp:Keyword Index="F" Term="LSN.Offset" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LSN.Offset" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LSN.Offset" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The offset in the log file." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN<span
class="languageSpecificText">..<span
class="cpp">::.Offset Field</td></tr><tr
id="headerTableRow3"><td align="left">LSN Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method
(String, DatabaseConfig, TextWriter)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_Database_Salvage_5" /><meta name="guid"
content="M_BerkeleyDB_Database_Salvage_5" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.IO.TextWriter)"
/><MSHelp:TOCTitle Title="Salvage Method (String, DatabaseConfig, TextWriter)" /><MSHelp:RLTitle
Title="Database.Salvage Method (String, DatabaseConfig, TextWriter) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.IO.TextWriter)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Salvage"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Write the key/data pairs from all databases in the file to . Key values are written for Btree, Hash and Queue databases, but not for Recno databases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Salvage Method (String, DatabaseConfig, TextWriter)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLockingSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintLockingSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLockingSystemStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats(System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLockingSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ExtentSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryQueueDatabaseConfig_ExtentSize" /><meta name="guid" content="P_BerkeleyDB_SecondaryQueueDatabaseConfig_ExtentSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryQueueDatabaseConfig.ExtentSize" /><MSHelp:TOCTitle Title="ExtentSize Property " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig.ExtentSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryQueueDatabaseConfig.ExtentSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassExtentSizeTopic" /><MSHelp:Keyword Index="K" Term="ExtentSize property" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig.ExtentSize property" /><MSHelp:Keyword Index="F" Term="ExtentSize" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig.ExtentSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig.ExtentSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.ExtentSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.get_ExtentSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.set_ExtentSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the extents used to hold pages in a , specified as a number of

pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig..::.ExtentSize Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Append" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Append" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Append(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Append Method (DatabaseEntry)" /><MSHelp:RLTitle Title="HeapDatabase.Append Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Append(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append the data item to the end of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Append Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequentialWritePause Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_SequentialWritePause" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_SequentialWritePause" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.SequentialWritePause" /><MSHelp:TOCTitle Title="SequentialWritePause Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.SequentialWritePause Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.SequentialWritePause" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassSequentialWritePauseTopic" /><MSHelp:Keyword Index="K" Term="SequentialWritePause property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.SequentialWritePause property" /><MSHelp:Keyword Index="F" Term="SequentialWritePause" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.SequentialWritePause" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.SequentialWritePause" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SequentialWritePause" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_SequentialWritePause" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of microseconds the thread of control will pause before scheduling further write operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SequentialWritePause Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitTxnCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitTxnCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitTxnCount" /><xml><MSHelp:Attr

Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitTxnCount" /><MSHelp:TOCTitle Title="InitTxnCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitTxnCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitTxnCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitTxnCountTopic" /><MSHelp:Keyword Index="K" Term="InitTxnCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitTxnCount property" /><MSHelp:Keyword Index="F" Term="InitTxnCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitTxnCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitTxnCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitTxnCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitTxnCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitTxnCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of transaction objects allocated when the environment is created" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitTxnCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LoggingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_LoggingSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_LoggingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:TOCTitle Title="LoggingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LoggingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLoggingSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="LoggingSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LoggingSystemStats method" /><MSHelp:Keyword Index="F" Term="LoggingSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LoggingSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LoggingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_SecondaryCursor" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryQueueDatabase_SecondaryCursor" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.SecondaryCursor"
/><MSHelp:TOCTitle Title="SecondaryCursor Method " /><MSHelp:RLTitle
Title="SecondaryQueueDatabase.SecondaryCursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.SecondaryQueueDatabase.SecondaryCursor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassSecondaryCursorTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryCursor method" /><MSHelp:Keyword
Index="K" Term="SecondaryQueueDatabase.SecondaryCursor method" /><MSHelp:Keyword Index="F"
Term="SecondaryCursor" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.SecondaryCursor"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.SecondaryCursor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage" src="../icons/dropdown.gif"
/> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.SecondaryCursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordPadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_RecordPadByte" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_RecordPadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.RecordPadByte" /><MSHelp:TOCTitle Title="RecordPadByte Property " /><MSHelp:RLTitle Title="RecnoStats.RecordPadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.RecordPadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassRecordPadByteTopic" /><MSHelp:Keyword Index="K" Term="RecordPadByte property" /><MSHelp:Keyword Index="K" Term="RecnoStats.RecordPadByte property" /><MSHelp:Keyword Index="F" Term="RecordPadByte" /><MSHelp:Keyword Index="F" Term="RecnoStats.RecordPadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.RecordPadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.RecordPadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_RecordPadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Fixed-length record pad." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.RecordPadByte Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8"
/><META NAME="save" CONTENT="history" /><title>RepLeaseTimeout Property </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepLeaseTimeout" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepLeaseTimeout" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.RepLeaseTimeout" /><MSHelp:TOCTitle Title="RepLeaseTimeout
Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepLeaseTimeout Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepLeaseTimeout"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepLeaseTimeoutTopic"
/><MSHelp:Keyword Index="K" Term="RepLeaseTimeout property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepLeaseTimeout property" /><MSHelp:Keyword Index="F"
Term="RepLeaseTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepLeaseTimeout"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepLeaseTimeout" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepLeaseTimeout"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepLeaseTimeout"
/><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepLeaseTimeout" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The amount of time a client grants its master lease to a master. When using master leases
all sites in a replication group must use the same lease timeout value. There is no default value. If leases ..."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepLeaseTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ArchivableLogFiles Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_ArchivableLogFiles" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_ArchivableLogFiles" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.ArchivableLogFiles(System.Boolean)" /><MSHelp:TOCTitle Title="ArchivableLogFiles Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.ArchivableLogFiles Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.ArchivableLogFiles(System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassArchivableLogFilesTopic" /><MSHelp:Keyword Index="K" Term="ArchivableLogFiles method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ArchivableLogFiles method" /><MSHelp:Keyword Index="F" Term="ArchivableLogFiles" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ArchivableLogFiles" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ArchivableLogFiles" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ArchivableLogFiles" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The names of all of the log files that are no longer in use (for example, that are no longer involved in active transactions), and that may safely be archived for catastrophic recovery and then rem ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ArchivableLogFiles Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RECNO Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseType_RECNO" /><meta name="guid" content="F_BerkeleyDB_DatabaseType_RECNO" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseType.RECNO" /><MSHelp:TOCTitle Title="RECNO Field" /><MSHelp:RLTitle Title="DatabaseType.RECNO Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseType.RECNO" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassRECNOTopic" /><MSHelp:Keyword Index="K" Term="RECNO field" /><MSHelp:Keyword Index="K" Term="DatabaseType.RECNO field" /><MSHelp:Keyword Index="F"

Term="RECNO" /><MSHelp:Keyword Index="F" Term="DatabaseType.RECNO" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.RECNO" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.RECNO" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Recno access method" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType..::.RECNO Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockerWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockerWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockerWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockerWait" /><MSHelp:TOCTitle Title="LockerWait Property " /><MSHelp:RLTitle Title="LockStats.LockerWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockerWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockerWaitTopic" /><MSHelp:Keyword Index="K" Term="LockerWait property" /><MSHelp:Keyword Index="K" Term="LockStats.LockerWait property" /><MSHelp:Keyword Index="F" Term="LockerWait" /><MSHelp:Keyword Index="F" Term="LockStats.LockerWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockerWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockerWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockerWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Locker lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockerWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockPolicy Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DeadlockPolicy" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DeadlockPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DeadlockPolicy" /><MSHelp:TOCTitle Title="DeadlockPolicy Members" /><MSHelp:RLTitle Title="DeadlockPolicy Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DeadlockPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyMembersTopic" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy class" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DeadlockPolicy class" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DeadlockPolicy" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy Members</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class <a

href="#methodTableToggle" onclick="OpenSection(methodTableToggle)">Methods <a
href="#fieldTableToggle" onclick="OpenSection(fieldTableToggle)">Fields
  See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FileOps
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js">
 </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_FileOps" /><meta
name="guid" content="F_BerkeleyDB_VerboseMessages_FileOps" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.VerboseMessages.FileOps" /><MSHelp:TOCTitle Title="FileOps Field"
/><MSHelp:RLTitle Title="VerboseMessages.FileOps Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.VerboseMessages.FileOps" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBVerboseMessagesClassFileOpsTopic" /><MSHelp:Keyword Index="K" Term="FileOps
field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.FileOps field" /><MSHelp:Keyword Index="F"
Term="FileOps"
 /><MSHelp:Keyword Index="F" Term="VerboseMessages.FileOps" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.VerboseMessages.FileOps" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.VerboseMessages.FileOps" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display additional
information when performing filesystem operations such as open, close or rename. May not be available on all
platforms." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;"
 src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
 event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.FileOps Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Put" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Put" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Put" /><MSHelp:TOCTitle Title="Put Method " /><MSHelp:RLTitle Title="HeapDatabase.Put Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Put" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassPutTopic" /><MSHelp:Keyword Index="K" Term="Put method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Put method" /><MSHelp:Keyword Index="F" Term="Put" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Put" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase.<span

class="vb">.::.Put Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_FastStats" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="RecnoDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HeapDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_HeapDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:TOCTitle Title="HeapDatabaseConfig Class" /><MSHelp:RLTitle Title="HeapDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class, about HeapDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr

Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig Class</td></tr><tr
id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="HashDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword
Index="K" Term="HashDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="HashDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Max Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_Max" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_Max" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.Max" /><MSHelp:TOCTitle Title="Max Property " /><MSHelp:RLTitle Title="SequenceStats.Max Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.Max" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassMaxTopic" /><MSHelp:Keyword Index="K" Term="Max property" /><MSHelp:Keyword Index="K" Term="SequenceStats.Max property" /><MSHelp:Keyword Index="F" Term="Max" /><MSHelp:Keyword Index="F" Term="SequenceStats.Max" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.Max" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.Max" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_Max" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="Abstract" Value="Maximum value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats<span
class="cs">..::.Max Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"

/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveMultiple" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveMultiple" /><MSHelp:TOCTitle Title="MoveMultiple Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveMultiple method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveMultiple method" /><MSHelp:Keyword Index="F" Term="MoveMultiple" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoCursor..::.MoveMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_HANDLE_DEAD Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_HANDLE_DEAD" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_HANDLE_DEAD" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_HANDLE_DEAD" /><MSHelp:TOCTitle Title="DB_REP_HANDLE_DEAD Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_HANDLE_DEAD Field (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_HANDLE_DEAD" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_HANDLE_DEADTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_HANDLE_DEAD field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_HANDLE_DEAD field" /><MSHelp:Keyword Index="F" Term="DB_REP_HANDLE_DEAD" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_HANDLE_DEAD" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_HANDLE_DEAD" /><MSHelp:Attr Name="APIType"

Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_HANDLE_DEAD" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rolled
back a commit." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_HANDLE_DEAD Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RenameDB Method (String, String, String, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB_2" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.String,System.Boolean)" /><MSHelp:TOCTitle Title="RenameDB Method (String, String, String, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RenameDB Method (String, String, String, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.String,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the database specified by and to . If no database is specified, the underlying file represented by is renamed using the value supplied to , incidentally renaming all of the ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RenameDB Method (String, String, String, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Get" /><meta name="guid" content="M_BerkeleyDB_Sequence_Get" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Get(System.Int32)" /><MSHelp:TOCTitle Title="Get Method (Int32)" /><MSHelp:RLTitle Title="Sequence.Get Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Get(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the next available element in the sequence and change the sequence value by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Get Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreeThreaded Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_FreeThreaded" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_FreeThreaded" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.FreeThreaded" /><MSHelp:TOCTitle Title="FreeThreaded Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.FreeThreaded Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.FreeThreaded" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassFreeThreadedTopic" /><MSHelp:Keyword Index="K" Term="FreeThreaded property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.FreeThreaded property" /><MSHelp:Keyword Index="F" Term="FreeThreaded" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.FreeThreaded" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.FreeThreaded" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.FreeThreaded" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_FreeThreaded" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the object is free-threaded; that is, concurrently usable by multiple threads in the address space." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.FreeThreaded Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_BTreeDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_BTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:TOCTitle Title="BTreeDatabaseConfig Fields" /><MSHelp:RLTitle Title="BTreeDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Cursor" /><meta

name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="RecnoDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"
for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Decrement Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceConfig_Decrement" /><meta name="guid" content="P_BerkeleyDB_SequenceConfig_Decrement" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceConfig.Decrement" /><MSHelp:TOCTitle Title="Decrement Property " /><MSHelp:RLTitle Title="SequenceConfig.Decrement Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceConfig.Decrement" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassDecrementTopic" /><MSHelp:Keyword Index="K" Term="Decrement property" /><MSHelp:Keyword Index="K" Term="SequenceConfig.Decrement property" /><MSHelp:Keyword Index="F" Term="Decrement" /><MSHelp:Keyword Index="F" Term="SequenceConfig.Decrement" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.Decrement" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.Decrement" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.get_Decrement" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.set_Decrement" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the sequence will be decremented." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.Decrement Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Decrement Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script

type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Decrement" /><meta name="guid" content="P_BerkeleyDB_Sequence_Decrement" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.Decrement" /><MSHelp:TOCTitle Title="Decrement Property " /><MSHelp:RLTitle Title="Sequence.Decrement Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Decrement" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassDecrementTopic" /><MSHelp:Keyword Index="K" Term="Decrement property" /><MSHelp:Keyword Index="K" Term="Sequence.Decrement property" /><MSHelp:Keyword Index="F" Term="Decrement" /><MSHelp:Keyword Index="F" Term="Sequence.Decrement" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Decrement" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Decrement" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Decrement" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the sequence will be decremented." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"

type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Decrement Property </td></tr><tr
id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordPadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_RecordPadByte" /><meta name="guid" content="P_BerkeleyDB_QueueStats_RecordPadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.RecordPadByte" /><MSHelp:TOCTitle Title="RecordPadByte Property " /><MSHelp:RLTitle Title="QueueStats.RecordPadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.RecordPadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassRecordPadByteTopic" /><MSHelp:Keyword Index="K" Term="RecordPadByte property" /><MSHelp:Keyword
Index="K" Term="QueueStats.RecordPadByte property" /><MSHelp:Keyword Index="F" Term="RecordPadByte" /><MSHelp:Keyword Index="F" Term="QueueStats.RecordPadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.RecordPadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.RecordPadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_RecordPadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Fixed-length record pad." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.RecordPadByte Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EncryptAlgorithm Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_EncryptAlgorithm" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_EncryptAlgorithm" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.EncryptAlgorithm" /><MSHelp:TOCTitle Title="EncryptAlgorithm Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.EncryptAlgorithm

Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.EncryptAlgorithm" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassEncryptAlgorithmTopic" /><MSHelp:Keyword Index="K" Term="EncryptAlgorithm property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.EncryptAlgorithm property" /><MSHelp:Keyword Index="F" Term="EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.EncryptAlgorithm" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.EncryptAlgorithm" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_EncryptAlgorithm" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The algorithm used by the Berkeley DB library to perform encryption and decryption." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.EncryptAlgorithm Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheRegions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_CacheRegions" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_CacheRegions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.CacheRegions" /><MSHelp:TOCTitle Title="CacheRegions Property " /><MSHelp:RLTitle Title="MPoolStats.CacheRegions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.CacheRegions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassCacheRegionsTopic" /><MSHelp:Keyword Index="K" Term="CacheRegions property" /><MSHelp:Keyword Index="K" Term="MPoolStats.CacheRegions property" /><MSHelp:Keyword Index="F" Term="CacheRegions" /><MSHelp:Keyword Index="F" Term="MPoolStats.CacheRegions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.CacheRegions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.CacheRegions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_CacheRegions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of regions." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.CacheRegions Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FrozenBuffersFreed Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_FrozenBuffersFreed" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_FrozenBuffersFreed" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.FrozenBuffersFreed" /><MSHelp:TOCTitle Title="FrozenBuffersFreed Property " /><MSHelp:RLTitle Title="MPoolStats.FrozenBuffersFreed Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.FrozenBuffersFreed" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassFrozenBuffersFreedTopic" /><MSHelp:Keyword Index="K" Term="FrozenBuffersFreed property" /><MSHelp:Keyword Index="K" Term="MPoolStats.FrozenBuffersFreed

property" /><MSHelp:Keyword Index="F" Term="FrozenBuffersFreed" /><MSHelp:Keyword Index="F" Term="MPoolStats.FrozenBuffersFreed" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.FrozenBuffersFreed" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.FrozenBuffersFreed" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_FrozenBuffersFreed" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Frozen buffers freed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.FrozenBuffersFreed Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveLast" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="Cursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveLast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveLastTopic" /><MSHelp:Keyword Index="K" Term="MoveLast method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveLast method" /><MSHelp:Keyword Index="F" Term="MoveLast" /><MSHelp:Keyword Index="F" Term="Cursor.MoveLast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveLast Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="RecnoDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.GetBoth"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox"

data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesNotInCache Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesNotInCache" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesNotInCache" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesNotInCache" /><MSHelp:TOCTitle Title="PagesNotInCache Property " /><MSHelp:RLTitle Title="MPoolStats.PagesNotInCache Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PagesNotInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesNotInCacheTopic" /><MSHelp:Keyword Index="K" Term="PagesNotInCache property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PagesNotInCache property" /><MSHelp:Keyword Index="F" Term="PagesNotInCache" /><MSHelp:Keyword Index="F" Term="MPoolStats.PagesNotInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PagesNotInCache" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PagesNotInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PagesNotInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages not found in the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PagesNotInCache Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_PrintStats_1" /><meta name="guid"

content="M_BerkeleyDB_Sequence_PrintStats_1"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.PrintStats(System.Boolean)"
/><MSHelp:TOCTitle Title="PrintStats Method (Boolean)" /><MSHelp:RLTitle Title="Sequence.PrintStats
Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Sequence.PrintStats(System.Boolean)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Sequence.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Print diagnostic
information." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input
type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Sequence<span
class="languageSpecificText">..<span
class="cpp">::.PrintStats Method (Boolean)</td></tr><tr
id="headerTableRow3"><td align="left">Sequence Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionConfig_TxnTimeout" /><meta name="guid" content="P_BerkeleyDB_TransactionConfig_TxnTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionConfig.TxnTimeout" /><MSHelp:TOCTitle Title="TxnTimeout Property " /><MSHelp:RLTitle Title="TransactionConfig.TxnTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionConfig.TxnTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassTxnTimeoutTopic" /><MSHelp:Keyword Index="K" Term="TxnTimeout property" /><MSHelp:Keyword Index="K" Term="TransactionConfig.TxnTimeout property" /><MSHelp:Keyword Index="F" Term="TxnTimeout" /><MSHelp:Keyword Index="F" Term="TransactionConfig.TxnTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.TxnTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.TxnTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.get_TxnTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.set_TxnTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The timeout value for locks for the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.TxnTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryDatabase" /><meta name="guid" content="T_BerkeleyDB_SecondaryDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryDatabase" /><MSHelp:TOCTitle Title="SecondaryDatabase Class" /><MSHelp:RLTitle Title="SecondaryDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryDatabase class" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase class, about SecondaryDatabase class" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a secondary Berkeley DB database, a base class for access method specific classes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>JoinCursor Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Properties_T_BerkeleyDB_JoinCursor" /><meta name="guid"
content="Properties_T_BerkeleyDB_JoinCursor" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.JoinCursor" /><MSHelp:TOCTitle Title="JoinCursor Properties "
/><MSHelp:RLTitle Title="JoinCursor Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Properties.T:BerkeleyDB.JoinCursor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBJoinCursorPropertiesTopic" /><MSHelp:Keyword Index="K" Term="JoinCursor class,
properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">JoinCursor Properties </td></tr><tr id="headerTableRow3"><td
align="left">JoinCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8"
/><META NAME="save" CONTENT="history" /><title>BackupWriteDirect Property </title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_BackupWriteDirect" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_BackupWriteDirect" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.BackupWriteDirect" /><MSHelp:TOCTitle
Title="BackupWriteDirect Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.BackupWriteDirect
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.BackupWriteDirect" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupWriteDirectTopic" /><MSHelp:Keyword Index="K"
Term="BackupWriteDirect property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.BackupWriteDirect property" /><MSHelp:Keyword Index="F"
Term="BackupWriteDirect" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BackupWriteDirect"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BackupWriteDirect" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BackupWriteDirect"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_BackupWriteDirect"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_BackupWriteDirect"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, direct I/O is used when writing pages to the disk during a hot backup. For some environments, direct I/O can provide faster write throughput, but usually it is slower becau ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BackupWriteDirect Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Helper Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_Helper" /><meta name="guid"
content="P_BerkeleyDB_DbSite_Helper" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DbSite.Helper" /><MSHelp:TOCTitle Title="Helper Property " /><MSHelp:RLTitle
Title="DbSite.Helper Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DbSite.Helper" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDbSiteClassHelperTopic" /><MSHelp:Keyword Index="K" Term="Helper property"
/><MSHelp:Keyword Index="K" Term="DbSite.Helper
property" /><MSHelp:Keyword Index="F" Term="Helper" /><MSHelp:Keyword Index="F"
Term="DbSite.Helper" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.Helper" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.Helper" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSite.get_Helper" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSite.set_Helper" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is a helper site."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.Helper Property </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EnvironmentFeedbackDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_EnvironmentFeedbackDelegate" /><meta name="guid" content="T_BerkeleyDB_EnvironmentFeedbackDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EnvironmentFeedbackDelegate" /><MSHelp:TOCTitle Title="EnvironmentFeedbackDelegate Delegate" /><MSHelp:RLTitle Title="EnvironmentFeedbackDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EnvironmentFeedbackDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEnvironmentFeedbackDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="EnvironmentFeedbackDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EnvironmentFeedbackDelegate delegate" /><MSHelp:Keyword Index="F" Term="EnvironmentFeedbackDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentFeedbackDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackDelegate.EndInvoke"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The application-specified feedback function called to report Berkeley DB operation progress." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EnvironmentFeedbackDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Consume Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_QueueDatabase_Consume" /><meta name="guid"
content="Overload_BerkeleyDB_QueueDatabase_Consume" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.QueueDatabase.Consume" /><MSHelp:TOCTitle Title="Consume Method "
/><MSHelp:RLTitle Title="QueueDatabase.Consume Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.QueueDatabase.Consume" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBQueueDatabaseClassConsumeTopic" /><MSHelp:Keyword Index="K" Term="Consume
method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Consume method" /><MSHelp:Keyword
Index="F" Term="Consume" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Consume"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Consume" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">QueueDatabase.<span
class="vb">.::.Consume Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_QueueDatabase.htm">QueueDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>AllocatedObjects Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_LockStats_AllocatedObjects" /><meta name="guid"
content="P_BerkeleyDB_LockStats_AllocatedObjects" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.AllocatedObjects" /><MSHelp:TOCTitle Title="AllocatedObjects Property "
/><MSHelp:RLTitle Title="LockStats.AllocatedObjects Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockStats.AllocatedObjects" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassAllocatedObjectsTopic" /><MSHelp:Keyword Index="K"
Term="AllocatedObjects property" /><MSHelp:Keyword Index="K" Term="LockStats.AllocatedObjects property"
/><MSHelp:Keyword Index="F" Term="AllocatedObjects" /><MSHelp:Keyword Index="F"
Term="LockStats.AllocatedObjects" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockStats.AllocatedObjects" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.AllocatedObjects" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_AllocatedObjects" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current number of lock objects allocated." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.AllocatedObjects Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method (DatabaseEntry, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Exists_2" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Exists_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Exists(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Exists Method (DatabaseEntry, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="BaseDatabase.Exists Method (DatabaseEntry, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Exists(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Check whether appears in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Exists Method (DatabaseEntry, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Refresh_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Refresh_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the secondary key and primary key/data pair to which the cursor refers in . If , or , or is partial , its bytes starting bytes from the beginning of ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseExpiredException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Fields_T_BerkeleyDB_LeaseExpiredException" /><meta name="guid"
content="Fields_T_BerkeleyDB_LeaseExpiredException" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:TOCTitle Title="LeaseExpiredException
Fields" /><MSHelp:RLTitle Title="LeaseExpiredException Fields (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Fields.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLeaseExpiredExceptionFieldsTopic" /><MSHelp:Keyword Index="K"
Term="LeaseExpiredException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LeaseExpiredException Fields</td></tr><tr id="headerTableRow3"><td align="left">LeaseExpiredException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Wrap Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SequenceConfig_Wrap" /><meta name="guid" content="F_BerkeleyDB_SequenceConfig_Wrap" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SequenceConfig.Wrap" /><MSHelp:TOCTitle Title="Wrap Field" /><MSHelp:RLTitle Title="SequenceConfig.Wrap Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SequenceConfig.Wrap" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassWrapTopic" /><MSHelp:Keyword Index="K" Term="Wrap field" /><MSHelp:Keyword Index="K" Term="SequenceConfig.Wrap field" /><MSHelp:Keyword Index="F" Term="Wrap" /><MSHelp:Keyword Index="F" Term="SequenceConfig.Wrap" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.Wrap" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.Wrap" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the sequence should wrap around when it is incremented (decremented) past the specified maximum (minimum) value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.Wrap Field</td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapRecordId Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HeapRecordId" /><meta name="guid" content="T_BerkeleyDB_HeapRecordId" /><xml><MSHelp:Attr Name="AssetID"

Value="T:BerkeleyDB.HeapRecordId" /><MSHelp:TOCTitle Title="HeapRecordId Class" /><MSHelp:RLTitle Title="HeapRecordId Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HeapRecordId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdClassTopic" /><MSHelp:Keyword Index="K" Term="HeapRecordId class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapRecordId class" /><MSHelp:Keyword Index="K" Term="HeapRecordId class, about HeapRecordId class" /><MSHelp:Keyword Index="F" Term="HeapRecordId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Content used for the key in a Heap database record. Berkeley DB creates this value for you when you create a record in a Heap database. You should never create this structure yourself; Berkeley DB must creat ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">HeapRecordId Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashEntriesSearched Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_HashEntriesSearched" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_HashEntriesSearched" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.HashEntriesSearched" /><MSHelp:TOCTitle Title="HashEntriesSearched Property " /><MSHelp:RLTitle Title="MPoolStats.HashEntriesSearched Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.HashEntriesSearched" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassHashEntriesSearchedTopic" /><MSHelp:Keyword Index="K" Term="HashEntriesSearched property" /><MSHelp:Keyword Index="K" Term="MPoolStats.HashEntriesSearched property" /><MSHelp:Keyword Index="F" Term="HashEntriesSearched" /><MSHelp:Keyword Index="F" Term="MPoolStats.HashEntriesSearched" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.HashEntriesSearched" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.HashEntriesSearched" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_HashEntriesSearched" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total hash entries searched." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.HashEntriesSearched Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method (MultipleKeyDatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_PutNoOverwrite_3" /><meta name="guid" content="M_BerkeleyDB_Database_PutNoOverwrite_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.MultipleKeyDatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="PutNoOverwrite Method (MultipleKeyDatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="Database.PutNoOverwrite Method (MultipleKeyDatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.MultipleKeyDatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pairs in the database, only if the key does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.PutNoOverwrite Method (MultipleKeyDatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method

(Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Stats_2" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Stats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="Stats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="HashDatabase.Stats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HashDatabase<span
class="cs">..::<span
class="nu">.Stats Method (Transaction, Isolation)</td></tr><tr
id="headerTableRow3"><td align="left">HashDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TruncateUnusedPages Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BTreeDatabase_TruncateUnusedPages" /><meta name="guid"
content="M_BerkeleyDB_BTreeDatabase_TruncateUnusedPages" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeDatabase.TruncateUnusedPages" /><MSHelp:TOCTitle
Title="TruncateUnusedPages Method " /><MSHelp:RLTitle Title="BTreeDatabase.TruncateUnusedPages Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.TruncateUnusedPages"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Return pages to the filesystem that are already free and at the end of the file."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.TruncateUnusedPages Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentOffset Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_CurrentOffset" /><meta name="guid" content="P_BerkeleyDB_LogStats_CurrentOffset" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.CurrentOffset" /><MSHelp:TOCTitle Title="CurrentOffset Property " /><MSHelp:RLTitle Title="LogStats.CurrentOffset Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.CurrentOffset" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassCurrentOffsetTopic" /><MSHelp:Keyword Index="K" Term="CurrentOffset property" /><MSHelp:Keyword Index="K" Term="LogStats.CurrentOffset property" /><MSHelp:Keyword

Index="F" Term="CurrentOffset" /><MSHelp:Keyword Index="F" Term="LogStats.CurrentOffset" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.CurrentOffset" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.CurrentOffset" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_CurrentOffset" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current log file offset." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.CurrentOffset Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Consume Method (Boolean, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Consume_1" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Consume_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Consume(System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Consume Method (Boolean, Transaction)" /><MSHelp:RLTitle Title="QueueDatabase.Consume Method (Boolean, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Consume(System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Consume" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the record number and data from the available record closest to the head of the queue, and delete the record." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Consume Method (Boolean, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheInfo Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_CacheInfo__ctor" /><meta name="guid" content="M_BerkeleyDB_CacheInfo__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.CacheInfo.#ctor(System.UInt32,System.UInt32,System.Int32)" /><MSHelp:TOCTitle Title="CacheInfo Constructor " /><MSHelp:RLTitle Title="CacheInfo Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.CacheInfo.#ctor(System.UInt32,System.UInt32,System.Int32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoClassctorTopic" /><MSHelp:Keyword Index="K" Term="CacheInfo class, constructor" /><MSHelp:Keyword Index="K" Term="CacheInfo.CacheInfo constructor" /><MSHelp:Keyword Index="F" Term="CacheInfo" /><MSHelp:Keyword Index="F" Term="CacheInfo.CacheInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CacheInfo.CacheInfo" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CacheInfo..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new CacheInfo object. The size of the cache is set to gbytes gigabytes plus bytes and spread over numCaches separate caches." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CacheInfo Constructor </td></tr><tr id="headerTableRow3"><td align="left">CacheInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delimiter Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_SecondaryRecnoDatabase_Delimiter" /><meta name="guid"
content="P_BerkeleyDB_SecondaryRecnoDatabase_Delimiter" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryRecnoDatabase.Delimiter" /><MSHelp:TOCTitle Title="Delimiter Property "
/><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Delimiter Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabase.Delimiter" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassDelimiterTopic" /><MSHelp:Keyword Index="K"
Term="Delimiter property" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Delimiter property"
/><MSHelp:Keyword Index="F" Term="Delimiter" /><MSHelp:Keyword
Index="F" Term="SecondaryRecnoDatabase.Delimiter" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryRecnoDatabase.Delimiter" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabase.Delimiter" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabase.get_Delimiter" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The delimiting byte used to mark the end of a record in ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Delimiter Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="QueueDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Add Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Add" /><meta name="guid" content="M_BerkeleyDB_Cursor_Add" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Add(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry})" /><MSHelp:TOCTitle Title="Add Method " /><MSHelp:RLTitle Title="Cursor.Add Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Add(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry})" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassAddTopic" /><MSHelp:Keyword Index="K" Term="Add method" /><MSHelp:Keyword Index="K" Term="Cursor.Add method" /><MSHelp:Keyword Index="F" Term="Add" /><MSHelp:Keyword Index="F" Term="Cursor.Add" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Add" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Add" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Stores the key/data pair in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Add Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LogConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_LogConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LogConfig" /><MSHelp:TOCTitle Title="LogConfig Methods " /><MSHelp:RLTitle Title="LogConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LogConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="LogConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabase_Length" /><meta name="guid" content="P_BerkeleyDB_QueueDatabase_Length" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueDatabase.Length" /><MSHelp:TOCTitle Title="Length Property " /><MSHelp:RLTitle Title="QueueDatabase.Length Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabase.Length" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassLengthTopic" /><MSHelp:Keyword Index="K" Term="Length property" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Length property" /><MSHelp:Keyword Index="F" Term="Length" /><MSHelp:Keyword
Index="F" Term="QueueDatabase.Length" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Length" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.get_Length" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The length of records in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (KeyValuePair(DatabaseEntry, KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Move_4" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Move_4" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry}},System.Boolean)" /><MSHelp:TOCTitle Title="Move Method (KeyValuePair(DatabaseEntry, KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean)" /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (KeyValuePair(DatabaseEntry, KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry}},System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move
the cursor to the specified key/data pair of the database. The cursor is positioned to a key/data pair if both the key and data match the values provided on the key and data parameters." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Move Method (KeyValuePair<(Of <(DatabaseEntry, KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>)>)>), Boolean)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats

Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="BTreeDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Lockdown Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Lockdown" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Lockdown" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Lockdown" /><MSHelp:TOCTitle Title="Lockdown Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Lockdown Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Lockdown" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLockdownTopic" /><MSHelp:Keyword Index="K" Term="Lockdown property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Lockdown property" /><MSHelp:Keyword Index="F" Term="Lockdown" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Lockdown" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Lockdown" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.DatabaseEnvironment.Lockdown" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Lockdown" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, lock shared Berkeley DB environment files and memory-mapped databases into memory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Lockdown Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Increment Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexConfig_Increment" /><meta name="guid" content="P_BerkeleyDB_MutexConfig_Increment" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexConfig.Increment" /><MSHelp:TOCTitle Title="Increment Property " /><MSHelp:RLTitle Title="MutexConfig.Increment Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexConfig.Increment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigClassIncrementTopic" /><MSHelp:Keyword Index="K" Term="Increment property" /><MSHelp:Keyword Index="K" Term="MutexConfig.Increment property" /><MSHelp:Keyword Index="F" Term="Increment" /><MSHelp:Keyword Index="F" Term="MutexConfig.Increment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig.Increment" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.Increment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.get_Increment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.set_Increment" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure the number of additional mutexes to allocate." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig..::.Increment Property </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TruncateUnusedPages Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_TruncateUnusedPages_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_TruncateUnusedPages_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.TruncateUnusedPages(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="TruncateUnusedPages Method (Transaction)" /><MSHelp:RLTitle Title="HashDatabase.TruncateUnusedPages Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.TruncateUnusedPages(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return pages to the filesystem that are already free and at the end of the file." /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.TruncateUnusedPages Method (Transaction)</td></tr><tr
id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Priority" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.Priority" /><MSHelp:TOCTitle Title="Priority Property " /><MSHelp:RLTitle Title="BaseDatabase.Priority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority property" /><MSHelp:Keyword
Index="K" Term="BaseDatabase.Priority property" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Priority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Priority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The cache priority for pages referenced by this object." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Priority Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UsingReplication Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UsingReplication" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UsingReplication" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UsingReplication" /><MSHelp:TOCTitle Title="UsingReplication Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UsingReplication Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UsingReplication" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUsingReplicationTopic" /><MSHelp:Keyword Index="K" Term="UsingReplication property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UsingReplication property" /><MSHelp:Keyword Index="F" Term="UsingReplication" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UsingReplication" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UsingReplication" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UsingReplication" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UsingReplication" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the replication subsystem was initialized." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UsingReplication Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextUniqueMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextUniqueMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextUniqueMultipleKey" /><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextUniqueMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextUniqueMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveNextUniqueMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoCursor_Duplicate" /><meta name="guid" content="M_BerkeleyDB_RecnoCursor_Duplicate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoCursor.Duplicate(System.Boolean)" /><MSHelp:TOCTitle Title="Duplicate Method " /><MSHelp:RLTitle Title="RecnoCursor.Duplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoCursor.Duplicate(System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassDuplicateTopic" /><MSHelp:Keyword Index="K" Term="Duplicate method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.Duplicate method" /><MSHelp:Keyword Index="F"
Term="Duplicate" /><MSHelp:Keyword Index="F" Term="RecnoCursor.Duplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.Duplicate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoCursor.Duplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new cursor that uses the same transaction and locker ID as the original cursor." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.Duplicate Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SyncMemPool Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_SyncMemPool" /><meta name="guid"
content="Overload_BerkeleyDB_DatabaseEnvironment_SyncMemPool" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.DatabaseEnvironment.SyncMemPool" /><MSHelp:TOCTitle Title="SyncMemPool
Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.SyncMemPool Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.SyncMemPool"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassSyncMemPoolTopic"
/><MSHelp:Keyword Index="K" Term="SyncMemPool method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.SyncMemPool method" /><MSHelp:Keyword Index="F" Term="SyncMemPool"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.SyncMemPool" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.SyncMemPool" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment..::.SyncMemPool Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, HeapDatabaseConfig, Transaction)</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Open(System.String,BerkeleyDB.HeapDatabaseConfig,BerkeleyDB.Transaction)"
/><MSHelp:TOCTitle Title="Open Method (String, HeapDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="HeapDatabase.Open Method (String, HeapDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Open(System.String,BerkeleyDB.HeapDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HeapDatabase object and open the database

represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Open Method (String, HeapDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncated

Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Truncated" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_Truncated" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.Truncated" /><MSHelp:TOCTitle Title="Truncated Property " /><MSHelp:RLTitle Title="BaseDatabase.Truncated Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.Truncated" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassTruncatedTopic" /><MSHelp:Keyword Index="K" Term="Truncated property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Truncated property" /><MSHelp:Keyword Index="F" Term="Truncated" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Truncated" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Truncated" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Truncated" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_Truncated" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the underlying file was physically truncated upon open, discarding all previous databases it might have held." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Truncated Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ClientServiceRequestsMissing Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ClientServiceRequestsMissing" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ClientServiceRequestsMissing" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ClientServiceRequestsMissing" /><MSHelp:TOCTitle Title="ClientServiceRequestsMissing Property " /><MSHelp:RLTitle Title="ReplicationStats.ClientServiceRequestsMissing Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ClientServiceRequestsMissing" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassClientServiceRequestsMissingTopic" /><MSHelp:Keyword Index="K" Term="ClientServiceRequestsMissing property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ClientServiceRequestsMissing property" /><MSHelp:Keyword Index="F" Term="ClientServiceRequestsMissing" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ClientServiceRequestsMissing" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ClientServiceRequestsMissing" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ClientServiceRequestsMissing" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ClientServiceRequestsMissing" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"

Value="Number of client service requests missing on this client." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ClientServiceRequestsMissing Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UsingLocking Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UsingLocking" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UsingLocking" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UsingLocking" /><MSHelp:TOCTitle Title="UsingLocking Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UsingLocking Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UsingLocking" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUsingLockingTopic" /><MSHelp:Keyword Index="K" Term="UsingLocking property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UsingLocking property" /><MSHelp:Keyword Index="F" Term="UsingLocking" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UsingLocking" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UsingLocking" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UsingLocking" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UsingLocking" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the locking subsystem was initialized." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UsingLocking Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transaction Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_Transaction" /><meta name="guid" content="Methods_T_BerkeleyDB_Transaction" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.Transaction" /><MSHelp:TOCTitle Title="Transaction Methods " /><MSHelp:RLTitle Title="Transaction Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.Transaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionMethodsTopic" /><MSHelp:Keyword Index="K" Term="Transaction class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">Transaction Methods </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Transaction.htm">Transaction Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TransactionSystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_DatabaseEnvironment_TransactionSystemStats" /><meta name="guid"
content="Overload_BerkeleyDB_DatabaseEnvironment_TransactionSystemStats" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.TransactionSystemStats"
/><MSHelp:TOCTitle Title="TransactionSystemStats Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.TransactionSystemStats
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.DatabaseEnvironment.TransactionSystemStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassTransactionSystemStatsTopic" /><MSHelp:Keyword
Index="K" Term="TransactionSystemStats method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.TransactionSystemStats method" /><MSHelp:Keyword Index="F"
Term="TransactionSystemStats" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.TransactionSystemStats" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.TransactionSystemStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TransactionSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MIN_WRITE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_MIN_WRITE" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_MIN_WRITE"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.MIN_WRITE" /><MSHelp:TOCTitle Title="MIN_WRITE Field" /><MSHelp:RLTitle Title="DeadlockPolicy.MIN_WRITE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DeadlockPolicy.MIN_WRITE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassMIN_WRITETopic"

/><MSHelp:Keyword Index="K" Term="MIN_WRITE field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.MIN_WRITE field" /><MSHelp:Keyword Index="F" Term="MIN_WRITE" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.MIN_WRITE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.MIN_WRITE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.MIN_WRITE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject the lock request for the locker ID with the fewest write locks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy..::.MIN_WRITE Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Active Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_TransactionStats_Active" /><meta name="guid"
content="P_BerkeleyDB_TransactionStats_Active" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.TransactionStats.Active" /><MSHelp:TOCTitle Title="Active Property "
/><MSHelp:RLTitle Title="TransactionStats.Active Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.TransactionStats.Active" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionStatsClassActiveTopic" /><MSHelp:Keyword Index="K" Term="Active
property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Active property" /><MSHelp:Keyword
Index="F" Term="Active" /><MSHelp:Keyword Index="F" Term="TransactionStats.Active" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.TransactionStats.Active" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionStats.Active"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Active" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Number of active transactions" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>

 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.Active Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Legacy Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSiteConfig_Legacy" /><meta name="guid" content="P_BerkeleyDB_DbSiteConfig_Legacy" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSiteConfig.Legacy" /><MSHelp:TOCTitle Title="Legacy Property " /><MSHelp:RLTitle Title="DbSiteConfig.Legacy Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSiteConfig.Legacy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassLegacyTopic" /><MSHelp:Keyword Index="K" Term="Legacy property" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.Legacy property" /><MSHelp:Keyword Index="F" Term="Legacy" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.Legacy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.Legacy"

/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.Legacy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.get_Legacy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.set_Legacy" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is within a legacy group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.Legacy Property </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionMax Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_RegionMax" /><meta name="guid" content="P_BerkeleyDB_MutexStats_RegionMax" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.RegionMax" /><MSHelp:TOCTitle Title="RegionMax Property " /><MSHelp:RLTitle Title="MutexStats.RegionMax Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.RegionMax" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassRegionMaxTopic" /><MSHelp:Keyword Index="K" Term="RegionMax property" /><MSHelp:Keyword Index="K" Term="MutexStats.RegionMax property" /><MSHelp:Keyword Index="F" Term="RegionMax" /><MSHelp:Keyword Index="F" Term="MutexStats.RegionMax" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.RegionMax" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.RegionMax" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_RegionMax" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutex region max size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.RegionMax Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BTreeDatabaseConfig_BTreeCompare" /><meta name="guid" content="F_BerkeleyDB_BTreeDatabaseConfig_BTreeCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BTreeDatabaseConfig.BTreeCompare" /><MSHelp:TOCTitle Title="BTreeCompare Field" /><MSHelp:RLTitle Title="BTreeDatabaseConfig.BTreeCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BTreeDatabaseConfig.BTreeCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassBTreeCompareTopic" /><MSHelp:Keyword Index="K" Term="BTreeCompare field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.BTreeCompare field" /><MSHelp:Keyword Index="F" Term="BTreeCompare" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.BTreeCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.BTreeCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.BTreeCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree key comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.BTreeCompare Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionConfig_LockTimeout" /><meta name="guid" content="P_BerkeleyDB_TransactionConfig_LockTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionConfig.LockTimeout" /><MSHelp:TOCTitle Title="LockTimeout Property " /><MSHelp:RLTitle Title="TransactionConfig.LockTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionConfig.LockTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassLockTimeoutTopic" /><MSHelp:Keyword Index="K" Term="LockTimeout property" /><MSHelp:Keyword Index="K" Term="TransactionConfig.LockTimeout property" /><MSHelp:Keyword Index="F" Term="LockTimeout" /><MSHelp:Keyword Index="F" Term="TransactionConfig.LockTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.LockTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.LockTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.get_LockTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.set_LockTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The timeout value for locks for the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.LockTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Data Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEntry_Data" /><meta name="guid" content="P_BerkeleyDB_DatabaseEntry_Data" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEntry.Data" /><MSHelp:TOCTitle Title="Data Property " /><MSHelp:RLTitle Title="DatabaseEntry.Data Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEntry.Data" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassDataTopic" /><MSHelp:Keyword Index="K" Term="Data property" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.Data property" /><MSHelp:Keyword Index="F" Term="Data" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.Data" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry.Data" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.Data" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.get_Data" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.set_Data" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The byte string stored in or retrieved from a database" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEntry<span
class="cs">..::<span
class="nu">.Data Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEntry.htm">DatabaseEntry Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>DatabaseEnvironment Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css"

/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DatabaseEnvironment" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DatabaseEnvironment" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:TOCTitle Title="DatabaseEnvironment Members" /><MSHelp:RLTitle Title="DatabaseEnvironment Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentMembersTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment class" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseEnvironment class" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment Members</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Move_4" /><meta name="guid" content="M_BerkeleyDB_Cursor_Move_4" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:TOCTitle Title="Move Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean)" /><MSHelp:RLTitle Title="Cursor.Move Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database.
The cursor is positioned to a key/data pair if both the key and data match the values provided on the key and data parameters." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_CompactConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_CompactConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.CompactConfig" /><MSHelp:TOCTitle Title="CompactConfig Members" /><MSHelp:RLTitle Title="CompactConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.CompactConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="CompactConfig class" /><MSHelp:Keyword Index="K" Term="CompactConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CompactConfig class" /><MSHelp:Keyword Index="F" Term="CompactConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig Members</td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultipleKey(BerkeleyDB.LockingInfo)"

/><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveFirstMultipleKey Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span

class="cs">..::.MoveFirstMultipleKey Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MagicNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_MagicNumber" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_MagicNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.MagicNumber" /><MSHelp:TOCTitle Title="MagicNumber Property " /><MSHelp:RLTitle Title="BTreeStats.MagicNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.MagicNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassMagicNumberTopic" /><MSHelp:Keyword Index="K" Term="MagicNumber property" /><MSHelp:Keyword Index="K" Term="BTreeStats.MagicNumber property" /><MSHelp:Keyword Index="F" Term="MagicNumber" /><MSHelp:Keyword Index="F" Term="BTreeStats.MagicNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.MagicNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.MagicNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_MagicNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Magic number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.MagicNumber Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseCursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BaseCursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_BaseCursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.BaseCursor" /><MSHelp:TOCTitle Title="BaseCursor Members" /><MSHelp:RLTitle Title="BaseCursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BaseCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="BaseCursor class" /><MSHelp:Keyword Index="K" Term="BaseCursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BaseCursor class" /><MSHelp:Keyword Index="F" Term="BaseCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseCursor" /><MSHelp:Attr

Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor Members</td></tr><tr id="headerTableRow3"><td align="left">BaseCursor Class Methods See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbChannel_Dispose" /><meta name="guid" content="M_BerkeleyDB_DbChannel_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbChannel.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="DbChannel.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbChannel.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="DbChannel.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="DbChannel.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbChannel.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by this object, and close the
channel if it's still open." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Elections Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_Elections" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_Elections" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.Elections" /><MSHelp:TOCTitle Title="Elections Field" /><MSHelp:RLTitle Title="ReplicationConfig.Elections Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.Elections" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassElectionsTopic" /><MSHelp:Keyword Index="K" Term="Elections field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.Elections field" /><MSHelp:Keyword Index="F" Term="Elections" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.Elections" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.Elections" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.Elections" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Replication Manager automatically runs elections to choose a new master when the old master appears to have become disconnected (defaults to true)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.Elections Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_FOREIGN_CONFLICT Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_FOREIGN_CONFLICT" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_FOREIGN_CONFLICT" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_FOREIGN_CONFLICT" /><MSHelp:TOCTitle Title="DB_FOREIGN_CONFLICT Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_FOREIGN_CONFLICT Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_FOREIGN_CONFLICT" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_FOREIGN_CONFLICTTopic" /><MSHelp:Keyword Index="K" Term="DB_FOREIGN_CONFLICT field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_FOREIGN_CONFLICT field" /><MSHelp:Keyword Index="F" Term="DB_FOREIGN_CONFLICT" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_FOREIGN_CONFLICT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_FOREIGN_CONFLICT" />
<MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_FOREIGN_CONFLICT" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A foreign db constraint triggered." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_FOREIGN_CONFLICT Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (CursorConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Cursor_2" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Cursor_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor Method (CursorConfig, Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Cursor Method (CursorConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Cursor Method (CursorConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFileMode Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogFileMode"

/><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogFileMode" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogFileMode" /><MSHelp:TOCTitle Title="LogFileMode Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogFileMode Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogFileMode" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogFileModeTopic" /><MSHelp:Keyword Index="K" Term="LogFileMode property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogFileMode
property" /><MSHelp:Keyword Index="F" Term="LogFileMode" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogFileMode" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogFileMode" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogFileMode" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogFileMode" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogFileMode" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The absolute file mode for created log files. This property is only useful for the rare Berkeley DB application that
does not control its umask value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogFileMode Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MovePrevUnique" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MovePrevUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:TOCTitle Title="MovePrevUnique Method " /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMovePrevUniqueTopic" /><MSHelp:Keyword Index="K" Term="MovePrevUnique method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MovePrevUnique method" /><MSHelp:Keyword Index="F" Term="MovePrevUnique" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MovePrevUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"

style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>LogVerifyConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LogVerifyConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LogVerifyConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LogVerifyConfig" /><MSHelp:TOCTitle Title="LogVerifyConfig Members" /><MSHelp:RLTitle Title="LogVerifyConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LogVerifyConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig class" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LogVerifyConfig class" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig Members</td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class Constructors Methods Properties See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryKeyGenDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryKeyGenDelegate" /><meta name="guid" content="T_BerkeleyDB_SecondaryKeyGenDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryKeyGenDelegate" /><MSHelp:TOCTitle Title="SecondaryKeyGenDelegate Delegate" /><MSHelp:RLTitle Title="SecondaryKeyGenDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryKeyGenDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryKeyGenDelegateClassTopic" /><MSHelp:Keyword Index="K"

Term="SecondaryKeyGenDelegate delegate" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryKeyGenDelegate delegate" /><MSHelp:Keyword Index="F"
Term="SecondaryKeyGenDelegate" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.SecondaryKeyGenDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryKeyGenDelegate"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryKeyGenDelegate.ctor" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryKeyGenDelegate.Invoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryKeyGenDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryKeyGenDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The function that
creates the set of secondary keys corresponding to a given primary
key and data pair. To create multiple secondary keys, return a ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryKeyGenDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>YOUNGEST Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_YOUNGEST" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_YOUNGEST" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.YOUNGEST" /><MSHelp:TOCTitle Title="YOUNGEST Field" /><MSHelp:RLTitle Title="DeadlockPolicy.YOUNGEST Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DeadlockPolicy.YOUNGEST" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassYOUNGESTTopic" /><MSHelp:Keyword Index="K" Term="YOUNGEST field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.YOUNGEST field" /><MSHelp:Keyword Index="F" Term="YOUNGEST" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.YOUNGEST" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.YOUNGEST" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.YOUNGEST" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject the lock request for the locker ID with the youngest lock." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy..::.YOUNGEST Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nKeys Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_nKeys" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_nKeys" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.nKeys"
/><MSHelp:TOCTitle Title="nKeys Property " /><MSHelp:RLTitle Title="RecnoStats.nKeys Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.nKeys" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassnKeysTopic" /><MSHelp:Keyword Index="K" Term="nKeys property" /><MSHelp:Keyword Index="K" Term="RecnoStats.nKeys property" /><MSHelp:Keyword Index="F" Term="nKeys" /><MSHelp:Keyword Index="F" Term="RecnoStats.nKeys" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.nKeys" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.nKeys" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.RecnoStats.get_nKeys" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of unique keys." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.nKeys Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSize Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_MPoolConfig_CacheSize" /><meta name="guid" content="F_BerkeleyDB_MPoolConfig_CacheSize" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.MPoolConfig.CacheSize" /><MSHelp:TOCTitle Title="CacheSize Field" /><MSHelp:RLTitle Title="MPoolConfig.CacheSize Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.MPoolConfig.CacheSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassCacheSizeTopic" /><MSHelp:Keyword Index="K" Term="CacheSize field" /><MSHelp:Keyword Index="K" Term="MPoolConfig.CacheSize field" /><MSHelp:Keyword Index="F" Term="CacheSize" /><MSHelp:Keyword Index="F" Term="MPoolConfig.CacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.CacheSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.CacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the shared memory buffer pool — that is, the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.CacheSize Field</td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Feedback Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_Feedback" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_Feedback" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.Feedback" /><MSHelp:TOCTitle Title="Feedback Field" /><MSHelp:RLTitle Title="DatabaseConfig.Feedback Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.Feedback" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassFeedbackTopic" /><MSHelp:Keyword Index="K" Term="Feedback field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.Feedback field" /><MSHelp:Keyword Index="F" Term="Feedback" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.Feedback" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.Feedback" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.Feedback"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.Feedback Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MovePrevDuplicate"

/><meta name="guid" content="Overload_BerkeleyDB_Cursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="Cursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMovePrevDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MovePrevDuplicate method" /><MSHelp:Keyword Index="K" Term="Cursor.MovePrevDuplicate method" /><MSHelp:Keyword Index="F" Term="MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="Cursor.MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransmitLimitGBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_TransmitLimitGBytes" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_TransmitLimitGBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.TransmitLimitGBytes" /><MSHelp:TOCTitle Title="TransmitLimitGBytes Property " /><MSHelp:RLTitle Title="ReplicationConfig.TransmitLimitGBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.TransmitLimitGBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassTransmitLimitGBytesTopic" /><MSHelp:Keyword Index="K" Term="TransmitLimitGBytes property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.TransmitLimitGBytes property" /><MSHelp:Keyword Index="F" Term="TransmitLimitGBytes" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.TransmitLimitGBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.TransmitLimitGBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.TransmitLimitGBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_TransmitLimitGBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The gigabytes component of the byte-count limit on the amount of data that will be transmitted from a site in response to a single message processed by ." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">ReplicationConfig<span
class="languageSpecificText">..<span
class="cpp">::.TransmitLimitGBytes Property </td></tr><tr
id="headerTableRow3"><td align="left">ReplicationConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>PrintSubsystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_DatabaseEnvironment_PrintSubsystemStats" /><meta name="guid"
content="Overload_BerkeleyDB_DatabaseEnvironment_PrintSubsystemStats" /><xml><MSHelp:Attr
Name="AssetID"
Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:TOCTitle
Title="PrintSubsystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintSubsystemStats
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintSubsystemStatsTopic" /><MSHelp:Keyword Index="K"
Term="PrintSubsystemStats method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.PrintSubsystemStats method" /><MSHelp:Keyword Index="F"
Term="PrintSubsystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.PrintSubsystemStats"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited"
value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintSubsystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="RecnoDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>DatabaseException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_DatabaseException" /><meta name="guid"
content="Methods_T_BerkeleyDB_DatabaseException" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.DatabaseException" /><MSHelp:TOCTitle Title="DatabaseException Methods "
/><MSHelp:RLTitle Title="DatabaseException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Methods.T:BerkeleyDB.DatabaseException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseExceptionMethodsTopic" /><MSHelp:Keyword Index="K"
Term="DatabaseException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden"
 id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable"
 cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException Methods </td></tr><tr id="headerTableRow3"><td align="left">DatabaseException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullLogBufferException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_FullLogBufferException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_FullLogBufferException" /><xml><MSHelp:Attr Name="AssetID"

Value="AllMembers.T:BerkeleyDB.FullLogBufferException"
/><MSHelp:TOCTitle Title="FullLogBufferException Members" /><MSHelp:RLTitle
Title="FullLogBufferException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="AllMembers.T:BerkeleyDB.FullLogBufferException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBFullLogBufferExceptionMembersTopic" /><MSHelp:Keyword Index="K"
Term="FullLogBufferException class" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class, all
members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.FullLogBufferException class"
/><MSHelp:Keyword Index="F" Term="FullLogBufferException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.FullLogBufferException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"
for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">FullLogBufferException Members</td></tr><tr id="headerTableRow3"><td align="left">FullLogBufferException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFileNumber Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LSN_LogFileNumber" /><meta name="guid" content="F_BerkeleyDB_LSN_LogFileNumber" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LSN.LogFileNumber" /><MSHelp:TOCTitle Title="LogFileNumber Field" /><MSHelp:RLTitle Title="LSN.LogFileNumber Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LSN.LogFileNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNClassLogFileNumberTopic" /><MSHelp:Keyword Index="K" Term="LogFileNumber field" /><MSHelp:Keyword Index="K" Term="LSN.LogFileNumber field" /><MSHelp:Keyword Index="F" Term="LogFileNumber" /><MSHelp:Keyword Index="F" Term="LSN.LogFileNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LSN.LogFileNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LSN.LogFileNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The log file number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN..::.LogFileNumber Field</td></tr><tr id="headerTableRow3"><td align="left">LSN Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoCursor Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RecnoCursor" /><meta name="guid" content="T_BerkeleyDB_RecnoCursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RecnoCursor" /><MSHelp:TOCTitle Title="RecnoCursor Class" /><MSHelp:RLTitle Title="RecnoCursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RecnoCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassTopic" /><MSHelp:Keyword Index="K" Term="RecnoCursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoCursor class" /><MSHelp:Keyword Index="K" Term="RecnoCursor class, about RecnoCursor class" /><MSHelp:Keyword Index="F" Term="RecnoCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class for traversing the records of a" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ActiveTransaction Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ActiveTransaction" /><meta name="guid" content="T_BerkeleyDB_ActiveTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ActiveTransaction" /><MSHelp:TOCTitle Title="ActiveTransaction Class" /><MSHelp:RLTitle Title="ActiveTransaction Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ActiveTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassTopic" /><MSHelp:Keyword Index="K" Term="ActiveTransaction class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ActiveTransaction class" /><MSHelp:Keyword Index="K" Term="ActiveTransaction class, about ActiveTransaction class" /><MSHelp:Keyword Index="F" Term="ActiveTransaction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The ActiveTransaction class describes a currently active transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label

id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ActiveTransaction Class</td></tr><tr id="headerTableRow3"><td align="left"><a
href="AllMembers_T_BerkeleyDB_ActiveTransaction.htm">Members <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>PrintRepMgrSystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintRepMgrSystemStats" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_PrintRepMgrSystemStats" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:TOCTitle
Title="PrintRepMgrSystemStats Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.PrintRepMgrSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the replication manager

statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintRepMgrSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowWrites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_LogStats_OverflowWrites" /><meta name="guid"
content="P_BerkeleyDB_LogStats_OverflowWrites" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LogStats.OverflowWrites" /><MSHelp:TOCTitle Title="OverflowWrites Property "
/><MSHelp:RLTitle Title="LogStats.OverflowWrites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LogStats.OverflowWrites" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogStatsClassOverflowWritesTopic" /><MSHelp:Keyword Index="K"
Term="OverflowWrites property" /><MSHelp:Keyword Index="K" Term="LogStats.OverflowWrites property"
/><MSHelp:Keyword Index="F" Term="OverflowWrites" /><MSHelp:Keyword Index="F"
Term="LogStats.OverflowWrites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.OverflowWrites"
/><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.OverflowWrites" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LogStats.get_OverflowWrites" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Overflow writes to the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"

data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.OverflowWrites Property</td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironmentConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DatabaseEnvironmentConfig" /><meta name="guid" content="T_BerkeleyDB_DatabaseEnvironmentConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:TOCTitle Title="DatabaseEnvironmentConfig Class" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseEnvironmentConfig class" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig class, about DatabaseEnvironmentConfig class" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ONE_PEER Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_AckPolicy_ONE_PEER" /><meta

name="guid" content="F_BerkeleyDB_AckPolicy_ONE_PEER" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.AckPolicy.ONE_PEER" /><MSHelp:TOCTitle Title="ONE_PEER Field" /><MSHelp:RLTitle Title="AckPolicy.ONE_PEER Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.AckPolicy.ONE_PEER" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyClassONE_PEERTopic" /><MSHelp:Keyword Index="K" Term="ONE_PEER field" /><MSHelp:Keyword Index="K" Term="AckPolicy.ONE_PEER field" /><MSHelp:Keyword Index="F" Term="ONE_PEER" /><MSHelp:Keyword Index="F" Term="AckPolicy.ONE_PEER" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy.ONE_PEER" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.AckPolicy.ONE_PEER" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The master should wait until at least one electable peer has acknowledged each permanent replication message (where "electable peer" means a client capable of being subsequently elected master of t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"

cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy..::.ONE_PEER Field</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullElectionTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_FullElectionTimeout" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_FullElectionTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.FullElectionTimeout" /><MSHelp:TOCTitle Title="FullElectionTimeout Property " /><MSHelp:RLTitle Title="ReplicationConfig.FullElectionTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.FullElectionTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassFullElectionTimeoutTopic" /><MSHelp:Keyword Index="K" Term="FullElectionTimeout property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.FullElectionTimeout property" /><MSHelp:Keyword Index="F" Term="FullElectionTimeout" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.FullElectionTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.FullElectionTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.FullElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_FullElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_FullElectionTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An optional configuration timeout period to wait for full election participation the first time the replication group finds a master. By default this option is turned off and normal election timeouts ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::<span
class="nu">.FullElectionTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="Overload_BerkeleyDB_Database_Cursor" /><meta name="guid"
content="Overload_BerkeleyDB_Database_Cursor" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.Database.Cursor" /><MSHelp:TOCTitle Title="Cursor Method "
/><MSHelp:RLTitle Title="Database.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.Database.Cursor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseClassCursorTopic" /><MSHelp:Keyword
Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="Database.Cursor method"
/><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="Database.Cursor"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Cursor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::<span
class="nu">.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TableSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabaseConfig_TableSize" /><meta name="guid" content="P_BerkeleyDB_HashDatabaseConfig_TableSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabaseConfig.TableSize" /><MSHelp:TOCTitle Title="TableSize Property " /><MSHelp:RLTitle Title="HashDatabaseConfig.TableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabaseConfig.TableSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassTableSizeTopic"
/><MSHelp:Keyword Index="K" Term="TableSize property" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.TableSize property" /><MSHelp:Keyword Index="F" Term="TableSize" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.TableSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.TableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.get_TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.set_TableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An estimate of the final size

of the hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..::.TableSize Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method (CompactConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Compact" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Compact" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Compact(BerkeleyDB.CompactConfig)" /><MSHelp:TOCTitle Title="Compact Method (CompactConfig)" /><MSHelp:RLTitle Title="BTreeDatabase.Compact Method (CompactConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Compact(BerkeleyDB.CompactConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Compact the database, and optionally return unused database pages to the underlying filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Compact Method (CompactConfig)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HotbackupInProgress Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_HotbackupInProgress" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_HotbackupInProgress" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.HotbackupInProgress" /><MSHelp:TOCTitle Title="HotbackupInProgress Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.HotbackupInProgress Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.HotbackupInProgress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassHotbackupInProgressTopic" /><MSHelp:Keyword Index="K" Term="HotbackupInProgress property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.HotbackupInProgress property" /><MSHelp:Keyword Index="F" Term="HotbackupInProgress" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.HotbackupInProgress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.HotbackupInProgress" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.HotbackupInProgress" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_HotbackupInProgress" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_HotbackupInProgress" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether there is any hot backup in progress." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.HotbackupInProgress Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_RecnoStats" /><meta

name="guid" content="Properties_T_BerkeleyDB_RecnoStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.RecnoStats" /><MSHelp:TOCTitle Title="RecnoStats Properties " /><MSHelp:RLTitle Title="RecnoStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.RecnoStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="RecnoStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats Properties </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleKeyDatabaseEntry Constructor (Byte[], Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MultipleKeyDatabaseEntry__ctor" /><meta name="guid" content="M_BerkeleyDB_MultipleKeyDatabaseEntry__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MultipleKeyDatabaseEntry.#ctor(System.Byte[],System.Boolean)" /><MSHelp:TOCTitle Title="MultipleKeyDatabaseEntry Constructor (Byte[], Boolean)" /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Constructor (Byte[], Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MultipleKeyDatabaseEntry.#ctor(System.Byte[],System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleKeyDatabaseEntry..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Construct a new bulk buffer for key/data pairs with a formatted byte array." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table

id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleKeyDatabaseEntry Constructor (array<Byte>[]()[], Boolean)</td></tr><tr id="headerTableRow3"><td align="left">MultipleKeyDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_FastStats" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="QueueDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBQueueDatabaseClassFastStatsTopic" /><MSHelp:Keyword Index="K" Term="FastStats method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.FastStats method" /><MSHelp:Keyword Index="F" Term="FastStats" /><MSHelp:Keyword Index="F" Term="QueueDatabase.FastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevUnique_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevUnique_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevUnique(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevUnique Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MovePrevUnique Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrevUnique(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and store that key and associated datum in . Mo ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;

width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevUnique Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>fromArray Method (Byte[], ByteOrder)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapRecordId_fromArray_1" /><meta name="guid" content="M_BerkeleyDB_HeapRecordId_fromArray_1" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.HeapRecordId.fromArray(System.Byte[],BerkeleyDB.ByteOrder)" /><MSHelp:TOCTitle Title="fromArray Method (Byte[], ByteOrder)" /><MSHelp:RLTitle Title="HeapRecordId.fromArray Method (Byte[], ByteOrder) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapRecordId.fromArray(System.Byte[],BerkeleyDB.ByteOrder)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.fromArray" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Construct a HeapRecordId from a byte array, typically ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.fromArray Method (array<Byte<span class="languageSpecificText"><span

class="cpp">>[]()[], ByteOrder)</td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeartbeatMonitor Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_HeartbeatMonitor" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_HeartbeatMonitor" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.HeartbeatMonitor" /><MSHelp:TOCTitle Title="HeartbeatMonitor Property " /><MSHelp:RLTitle Title="ReplicationConfig.HeartbeatMonitor Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.HeartbeatMonitor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassHeartbeatMonitorTopic" /><MSHelp:Keyword Index="K" Term="HeartbeatMonitor property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.HeartbeatMonitor property" /><MSHelp:Keyword Index="F" Term="HeartbeatMonitor" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.HeartbeatMonitor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.HeartbeatMonitor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.HeartbeatMonitor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_HeartbeatMonitor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_HeartbeatMonitor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time the replication manager, running at a client site, waits for some message activity on the connection from the master (heartbeats or other messages) before concluding that the con ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.HeartbeatMonitor Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_BUFFER_SMALL Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_BUFFER_SMALL" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_BUFFER_SMALL" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_BUFFER_SMALL" /><MSHelp:TOCTitle Title="DB_BUFFER_SMALL Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_BUFFER_SMALL Field

(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_BUFFER_SMALL" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_BUFFER_SMALLTopic" /><MSHelp:Keyword Index="K" Term="DB_BUFFER_SMALL field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_BUFFER_SMALL field" /><MSHelp:Keyword Index="F" Term="DB_BUFFER_SMALL" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_BUFFER_SMALL" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_BUFFER_SMALL" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_BUFFER_SMALL" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="User memory too small for return." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_BUFFER_SMALL

Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ErrorCodes.htm">ErrorCodes Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingInfo
Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
 src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Fields_T_BerkeleyDB_LockingInfo" /><meta name="guid"
content="Fields_T_BerkeleyDB_LockingInfo" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.LockingInfo" /><MSHelp:TOCTitle Title="LockingInfo Fields" /><MSHelp:RLTitle
Title="LockingInfo Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.LockingInfo" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingInfoFieldsTopic" /><MSHelp:Keyword Index="K" Term="LockingInfo class,
fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle"
 /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
 onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">LockingInfo Fields</td></tr><tr id="headerTableRow3"><td
align="left">LockingInfo Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats
Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_PrintFastStats" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_PrintFastStats" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.PrintFastStats" /><MSHelp:TOCTitle
Title="PrintFastStats Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.PrintFastStats Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.PrintFastStats" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox"

data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (DatabaseEntry, Boolean, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultiple_2" />
<meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultiple_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32)" /><MSHelp:TOCTitle Title="MoveMultiple Method (DatabaseEntry, Boolean, Int32)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (DatabaseEntry, Boolean, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Set the cursor to refer to , and store that key and as many duplicate data items associated with the given key that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultiple Method (DatabaseEntry, Boolean, Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetEnumerator Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB"

/><meta name="file" content="M_BerkeleyDB_MultipleKeyDatabaseEntry_GetEnumerator" /><meta name="guid" content="M_BerkeleyDB_MultipleKeyDatabaseEntry_GetEnumerator" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MultipleKeyDatabaseEntry.GetEnumerator" /><MSHelp:TOCTitle Title="GetEnumerator Method " /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry.GetEnumerator Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MultipleKeyDatabaseEntry.GetEnumerator" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryClassGetEnumeratorTopic" /><MSHelp:Keyword Index="K" Term="GetEnumerator method" /><MSHelp:Keyword Index="K" Term="MultipleKeyDatabaseEntry.GetEnumerator method" /><MSHelp:Keyword Index="F" Term="GetEnumerator" /><MSHelp:Keyword Index="F" Term="MultipleKeyDatabaseEntry.GetEnumerator" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MultipleKeyDatabaseEntry.GetEnumerator" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleKeyDatabaseEntry.GetEnumerator" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return an enumerator which iterates over all pairs represented by the ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleKeyDatabaseEntry..::.GetEnumerator Method </td></tr><tr id="headerTableRow3"><td align="left">MultipleKeyDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Committed Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_Committed" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_Committed" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.Committed" /><MSHelp:TOCTitle Title="Committed Property " /><MSHelp:RLTitle Title="TransactionStats.Committed Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.Committed" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassCommittedTopic" /><MSHelp:Keyword Index="K" Term="Committed property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Committed property" /><MSHelp:Keyword Index="F" Term="Committed" /><MSHelp:Keyword Index="F" Term="TransactionStats.Committed" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.Committed" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.Committed" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Committed" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of committed transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.Committed Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNextUnique(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUnique Method (LockingInfo)" /><MSHelp:RLTitle

Title="SecondaryCursor.MoveNextUnique Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextUnique(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store the secondary key and primary key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextUnique Method

(LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_PAGE_NOTFOUND Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_PAGE_NOTFOUND" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_PAGE_NOTFOUND" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_PAGE_NOTFOUND" /><MSHelp:TOCTitle Title="DB_PAGE_NOTFOUND Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_PAGE_NOTFOUND Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_PAGE_NOTFOUND" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_PAGE_NOTFOUNDTopic" /><MSHelp:Keyword Index="K" Term="DB_PAGE_NOTFOUND field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_PAGE_NOTFOUND field" /><MSHelp:Keyword Index="F" Term="DB_PAGE_NOTFOUND" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_PAGE_NOTFOUND" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_PAGE_NOTFOUND" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_PAGE_NOTFOUND" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Requested page not found." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_PAGE_NOTFOUND Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetMaxSequentialWrites Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_SetMaxSequentialWrites" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_SetMaxSequentialWrites" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.SetMaxSequentialWrites(System.Int32,System.UInt32)" /><MSHelp:TOCTitle Title="SetMaxSequentialWrites Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.SetMaxSequentialWrites Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.SetMaxSequentialWrites(System.Int32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassSetMaxSequentialWritesTopic" /><MSHelp:Keyword

Index="K" Term="SetMaxSequentialWrites method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.SetMaxSequentialWrites method" /><MSHelp:Keyword Index="F" Term="SetMaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.SetMaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.SetMaxSequentialWrites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SetMaxSequentialWrites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Limit the number of sequential write operations scheduled by the library when flushing dirty pages from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SetMaxSequentialWrites

Method </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FillFactor
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_SecondaryHashDatabase_FillFactor" /><meta name="guid"
content="P_BerkeleyDB_SecondaryHashDatabase_FillFactor" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryHashDatabase.FillFactor" /><MSHelp:TOCTitle Title="FillFactor Property "
/><MSHelp:RLTitle Title="SecondaryHashDatabase.FillFactor Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.SecondaryHashDatabase.FillFactor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryHashDatabaseClassFillFactorTopic" /><MSHelp:Keyword
Index="K" Term="FillFactor property" /><MSHelp:Keyword Index="K"
Term="SecondaryHashDatabase.FillFactor property" /><MSHelp:Keyword Index="F" Term="FillFactor"
/><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.FillFactor" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryHashDatabase.FillFactor" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryHashDatabase.FillFactor" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryHashDatabase.get_FillFactor" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The desired
density within the hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.FillFactor Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_ReplicationHostAddress" /><meta name="guid" content="Fields_T_BerkeleyDB_ReplicationHostAddress" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:TOCTitle Title="ReplicationHostAddress Fields" /><MSHelp:RLTitle Title="ReplicationHostAddress Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressFieldsTopic" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress class, fields" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ReplicationHostAddress Fields</td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReadModifyWrite Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LockingInfo_ReadModifyWrite" /><meta name="guid" content="F_BerkeleyDB_LockingInfo_ReadModifyWrite" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LockingInfo.ReadModifyWrite" /><MSHelp:TOCTitle Title="ReadModifyWrite Field" /><MSHelp:RLTitle Title="LockingInfo.ReadModifyWrite Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LockingInfo.ReadModifyWrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingInfoClassReadModifyWriteTopic" />
<MSHelp:Keyword Index="K" Term="ReadModifyWrite field" /><MSHelp:Keyword Index="K" Term="LockingInfo.ReadModifyWrite field" /><MSHelp:Keyword Index="F" Term="ReadModifyWrite" /><MSHelp:Keyword Index="F" Term="LockingInfo.ReadModifyWrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingInfo.ReadModifyWrite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingInfo.ReadModifyWrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, acquire write locks instead of read locks when doing a read, if locking is configured." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingInfo..::.ReadModifyWrite Field</td></tr><tr id="headerTableRow3"><td align="left">LockingInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_DUPMASTER Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_DUPMASTER" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_DUPMASTER" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_DUPMASTER" /><MSHelp:TOCTitle Title="DB_REP_DUPMASTER Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_DUPMASTER Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_DUPMASTER" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBErrorCodesClassDB_REP_DUPMASTERTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_DUPMASTER field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_DUPMASTER field" /><MSHelp:Keyword Index="F" Term="DB_REP_DUPMASTER" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_DUPMASTER" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_DUPMASTER" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_DUPMASTER" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="There are two masters." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_DUPMASTER Field</td></tr><tr id="headerTableRow3"><td

align="left">ErrorCodes Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_BaseDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_BaseDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.BaseDatabase" /><MSHelp:TOCTitle Title="BaseDatabase Methods " /><MSHelp:RLTitle Title="BaseDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.BaseDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="BaseDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_JOIN_FAILURE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_JOIN_FAILURE" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_JOIN_FAILURE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_JOIN_FAILURE" /><MSHelp:TOCTitle Title="DB_REP_JOIN_FAILURE Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_JOIN_FAILURE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_JOIN_FAILURE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_JOIN_FAILURETopic" /><MSHelp:Keyword Index="K" Term="DB_REP_JOIN_FAILURE field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_JOIN_FAILURE field" /><MSHelp:Keyword Index="F"

Term="DB_REP_JOIN_FAILURE" /><MSHelp:Keyword Index="F"
Term="ErrorCodes.DB_REP_JOIN_FAILURE" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ErrorCodes.DB_REP_JOIN_FAILURE" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_JOIN_FAILURE" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Unable to join replication group." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">ErrorCodes<span
class="languageSpecificText">..<span
class="cpp">::.DB_REP_JOIN_FAILURE Field</td></tr><tr
id="headerTableRow3"><td align="left">ErrorCodes Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextUniqueMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextUniqueMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextUniqueMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.MoveNextUniqueMultiple
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate"
/><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:TOCTitle

Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store the secondary key and primary ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseCursor Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BaseCursor"
/><meta name="guid" content="T_BerkeleyDB_BaseCursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BaseCursor" /><MSHelp:TOCTitle Title="BaseCursor Class" /><MSHelp:RLTitle Title="BaseCursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BaseCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorClassTopic" /><MSHelp:Keyword Index="K" Term="BaseCursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BaseCursor class" /><MSHelp:Keyword Index="K" Term="BaseCursor class, about BaseCursor class" /><MSHelp:Keyword Index="F" Term="BaseCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseCursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The abstract base class from which all cursor classes inherit. Cursors may span threads, but only serially, that is, the application must serialize access to the cursor handle. ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Nullifier Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryDatabase_Nullifier" /><meta name="guid" content="P_BerkeleyDB_SecondaryDatabase_Nullifier" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabase.Nullifier" /><MSHelp:TOCTitle Title="Nullifier Property " /><MSHelp:RLTitle Title="SecondaryDatabase.Nullifier Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryDatabase.Nullifier" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassNullifierTopic" /><MSHelp:Keyword Index="K" Term="Nullifier property" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Nullifier property" /><MSHelp:Keyword Index="F" Term="Nullifier" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Nullifier" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Nullifier" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.Nullifier" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.get_Nullifier" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.set_Nullifier" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The nullifying function used to set the foreign key to null." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Nullifier Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NotFoundException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"

/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_NotFoundException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_NotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.NotFoundException" /><MSHelp:TOCTitle Title="NotFoundException Members" /><MSHelp:RLTitle Title="NotFoundException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.NotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotFoundExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="NotFoundException class" /><MSHelp:Keyword Index="K" Term="NotFoundException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.NotFoundException class" /><MSHelp:Keyword Index="F" Term="NotFoundException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.NotFoundException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">NotFoundException Members</td></tr><tr id="headerTableRow3"><td align="left">NotFoundException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BTreeDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_BTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:TOCTitle Title="BTreeDatabaseConfig Class" /><MSHelp:RLTitle Title="BTreeDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K"

Term="BTreeDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig class, about BTreeDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNext_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNext_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNext Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNext Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store the secondary key and primary key/data pair in . In ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNext Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbSite_Dispose" /><meta name="guid" content="M_BerkeleyDB_DbSite_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbSite.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="DbSite.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbSite.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="DbSite.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="DbSite.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by this object, and close the site if it's still open." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabase_Compare" /><meta name="guid" content="P_BerkeleyDB_HashDatabase_Compare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabase.Compare" /><MSHelp:TOCTitle Title="Compare Property " /><MSHelp:RLTitle Title="HashDatabase.Compare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabase.Compare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare property" /><MSHelp:Keyword Index="K" Term="HashDatabase.Compare property" /><MSHelp:Keyword Index="F" Term="Compare" /><MSHelp:Keyword Index="F" Term="HashDatabase.Compare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Compare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.get_Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.set_Compare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Hash key comparison function. The comparison function is called whenever it is necessary to compare a key specified by the application with a key currently stored in the tree." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HashDatabase<span
class="cs">..::<span
class="nu">.Compare Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashDatabase.htm">HashDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxObjects
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockingConfig_MaxObjects" /><meta
name="guid" content="P_BerkeleyDB_LockingConfig_MaxObjects" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockingConfig.MaxObjects" /><MSHelp:TOCTitle Title="MaxObjects Property "
/><MSHelp:RLTitle Title="LockingConfig.MaxObjects Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.LockingConfig.MaxObjects" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingConfigClassMaxObjectsTopic" /><MSHelp:Keyword Index="K"
Term="MaxObjects property" /><MSHelp:Keyword Index="K" Term="LockingConfig.MaxObjects property"
/><MSHelp:Keyword Index="F" Term="MaxObjects" /><MSHelp:Keyword Index="F"
Term="LockingConfig.MaxObjects" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockingConfig.MaxObjects" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.MaxObjects" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.get_MaxObjects" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.set_MaxObjects" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum
number of locked objects supported by the Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.MaxObjects Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TableSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabase_TableSize" /><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabase_TableSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabase.TableSize" /><MSHelp:TOCTitle Title="TableSize Property " /><MSHelp:RLTitle Title="SecondaryHashDatabase.TableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryHashDatabase.TableSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassTableSizeTopic" /><MSHelp:Keyword Index="K" Term="TableSize property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.TableSize property" /><MSHelp:Keyword Index="F" Term="TableSize" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.TableSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.TableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.get_TableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An estimate of the final size of the hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.TableSize Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabase Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryHashDatabase" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryHashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:TOCTitle Title="SecondaryHashDatabase Properties " /><MSHelp:RLTitle Title="SecondaryHashDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryHashDatabase Properties </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryHashDatabase.htm">SecondaryHashDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReadOnly
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_ReadOnly" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_ReadOnly" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.ReadOnly" /><MSHelp:TOCTitle Title="ReadOnly Field" /><MSHelp:RLTitle Title="DatabaseConfig.ReadOnly Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.ReadOnly" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassReadOnlyTopic" /><MSHelp:Keyword Index="K" Term="ReadOnly field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.ReadOnly field" /><MSHelp:Keyword Index="F" Term="ReadOnly" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.ReadOnly" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.ReadOnly" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.ReadOnly" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Open the database for reading only. Any attempt to modify items in the database will fail, regardless of the actual permissions of any underlying files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.ReadOnly Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ClockskewFast Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_ClockskewFast" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_ClockskewFast" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.ClockskewFast" /><MSHelp:TOCTitle Title="ClockskewFast Property " /><MSHelp:RLTitle Title="ReplicationConfig.ClockskewFast Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.ClockskewFast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassClockskewFastTopic" /><MSHelp:Keyword Index="K" Term="ClockskewFast property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.ClockskewFast property" /><MSHelp:Keyword Index="F" Term="ClockskewFast" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.ClockskewFast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.ClockskewFast" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.ClockskewFast" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_ClockskewFast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The value, relative to , of the fastest clock in the group of sites." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.ClockskewFast Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetEnumerator Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_SecondaryCursor_GetEnumerator" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_GetEnumerator" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.GetEnumerator" /><MSHelp:TOCTitle Title="GetEnumerator
Method " /><MSHelp:RLTitle Title="SecondaryCursor.GetEnumerator Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.GetEnumerator" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassGetEnumeratorTopic" /><MSHelp:Keyword Index="K"
Term="GetEnumerator method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.GetEnumerator
method" /><MSHelp:Keyword Index="F" Term="GetEnumerator" /><MSHelp:Keyword Index="F"
Term="SecondaryCursor.GetEnumerator" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryCursor.GetEnumerator" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.GetEnumerator" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Returns an enumerator that iterates through the ."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.GetEnumerator Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseRecordNumbers Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BTreeDatabaseConfig_UseRecordNumbers" /><meta name="guid" content="F_BerkeleyDB_BTreeDatabaseConfig_UseRecordNumbers" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:TOCTitle Title="UseRecordNumbers Field" /><MSHelp:RLTitle Title="BTreeDatabaseConfig.UseRecordNumbers Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassUseRecordNumbersTopic" /><MSHelp:Keyword Index="K" Term="UseRecordNumbers field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.UseRecordNumbers field" /><MSHelp:Keyword Index="F" Term="UseRecordNumbers" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, support retrieval from the Btree using record numbers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.UseRecordNumbers Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_KeyRange" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_KeyRange" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.KeyRange(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle

Title="KeyRange Method (DatabaseEntry)" /><MSHelp:RLTitle Title="BTreeDatabase.KeyRange Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.KeyRange(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.KeyRange" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return an estimate of the proportion of keys that are less than, equal to, and greater than the specified key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.KeyRange Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultiple Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultiple Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultiple Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair and as many duplicate data ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultiple Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, QueueDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Open(System.String,BerkeleyDB.QueueDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, QueueDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="QueueDatabase.Open Method (String, QueueDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Open(System.String,BerkeleyDB.QueueDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="Abstract" Value="Instantiate a new QueueDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Open Method (String, QueueDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseCheckedMissesNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ReplicationStats_LeaseCheckedMissesNumber" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_LeaseCheckedMissesNumber" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.LeaseCheckedMissesNumber" /><MSHelp:TOCTitle
Title="LeaseCheckedMissesNumber Property " /><MSHelp:RLTitle
Title="ReplicationStats.LeaseCheckedMissesNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ReplicationStats.LeaseCheckedMissesNumber" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBReplicationStatsClassLeaseCheckedMissesNumberTopic"
/><MSHelp:Keyword Index="K" Term="LeaseCheckedMissesNumber property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.LeaseCheckedMissesNumber property" /><MSHelp:Keyword Index="F"
Term="LeaseCheckedMissesNumber" /><MSHelp:Keyword Index="F"
Term="ReplicationStats.LeaseCheckedMissesNumber" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationStats.LeaseCheckedMissesNumber" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.LeaseCheckedMissesNumber" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.get_LeaseCheckedMissesNumber" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of invalid lease validity checks."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.LeaseCheckedMissesNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LSN Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_LSN__ctor" /><meta name="guid" content="M_BerkeleyDB_LSN__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.LSN.#ctor(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="LSN Constructor " /><MSHelp:RLTitle Title="LSN Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LSN.#ctor(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNClassctorTopic" /><MSHelp:Keyword Index="K" Term="LSN class, constructor" /><MSHelp:Keyword Index="K" Term="LSN.LSN constructor" /><MSHelp:Keyword Index="F" Term="LSN" /><MSHelp:Keyword Index="F" Term="LSN.LSN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LSN.LSN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LSN..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new LSN object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN Constructor </td></tr><tr id="headerTableRow3"><td align="left">LSN Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BulkBufferTransfers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_BulkBufferTransfers" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_BulkBufferTransfers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.BulkBufferTransfers" /><MSHelp:TOCTitle Title="BulkBufferTransfers Property " /><MSHelp:RLTitle Title="ReplicationStats.BulkBufferTransfers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.BulkBufferTransfers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassBulkBufferTransfersTopic" /><MSHelp:Keyword Index="K" Term="BulkBufferTransfers property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.BulkBufferTransfers property" /><MSHelp:Keyword Index="F" Term="BulkBufferTransfers" /><MSHelp:Keyword Index="F" Term="ReplicationStats.BulkBufferTransfers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.BulkBufferTransfers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.BulkBufferTransfers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_BulkBufferTransfers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Transfers of bulk buffers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.BulkBufferTransfers Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_Close" /><meta name="guid" content="M_BerkeleyDB_JoinCursor_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="JoinCursor.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="JoinCursor.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="JoinCursor.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Discard the cursor. It is possible for the Close() method to throw a , signaling that any enclosing transaction should be aborted. If the application is already ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashFunction Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabase_HashFunction" /><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabase_HashFunction" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabase.HashFunction" /><MSHelp:TOCTitle Title="HashFunction Property " /><MSHelp:RLTitle Title="SecondaryHashDatabase.HashFunction Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryHashDatabase.HashFunction"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassHashFunctionTopic" /><MSHelp:Keyword Index="K" Term="HashFunction property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.HashFunction property" /><MSHelp:Keyword Index="F" Term="HashFunction" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.HashFunction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.HashFunction" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.HashFunction" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.get_HashFunction" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.set_HashFunction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A user-defined hash function; if no hash function is specified, a default hash function is used." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.HashFunction Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryRecnoDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryRecnoDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:TOCTitle Title="SecondaryRecnoDatabase Members" /><MSHelp:RLTitle Title="SecondaryRecnoDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase class" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryRecnoDatabase class" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseType Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

```
</script><script type="text/javascript"
 src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Fields_T_BerkeleyDB_DatabaseType" /><meta name="guid"
content="Fields_T_BerkeleyDB_DatabaseType" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.DatabaseType" /><MSHelp:TOCTitle Title="DatabaseType Fields"
/><MSHelp:RLTitle Title="DatabaseType Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.DatabaseType" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseTypeFieldsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseType class,
fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
 type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image"
 /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> </span><span>    </span><span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
 id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></span><span>    </span><span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></span></td></tr></table><div id="devlangsMenu"><input
 id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label><br /><input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
```

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType Fields</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockNotGrantedException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LockNotGrantedException" /><meta name="guid" content="Methods_T_BerkeleyDB_LockNotGrantedException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:TOCTitle Title="LockNotGrantedException Methods " /><MSHelp:RLTitle Title="LockNotGrantedException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockNotGrantedExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockNotGrantedException Methods </td></tr><tr id="headerTableRow3"><td align="left">LockNotGrantedException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>processID Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DbThreadID_processID" /><meta name="guid"
content="F_BerkeleyDB_DbThreadID_processID" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DbThreadID.processID" /><MSHelp:TOCTitle Title="processID Field"
/><MSHelp:RLTitle Title="DbThreadID.processID Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.DbThreadID.processID" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDbThreadIDClassprocessIDTopic" /><MSHelp:Keyword
Index="K" Term="processID field" /><MSHelp:Keyword Index="K" Term="DbThreadID.processID field"
/><MSHelp:Keyword Index="F" Term="processID" /><MSHelp:Keyword Index="F"
Term="DbThreadID.processID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbThreadID.processID"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbThreadID.processID"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The Process ID of the thread of control" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID..::.processID Field</td></tr><tr id="headerTableRow3"><td align="left">DbThreadID Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_PutNoDuplicate_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_PutNoDuplicate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="HashDatabase.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.PutNoDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair in the database only if it does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockUpgrades Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockUpgrades" /><meta name="guid"

content="P_BerkeleyDB_LockStats_LockUpgrades" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.LockUpgrades"
/><MSHelp:TOCTitle Title="LockUpgrades Property " /><MSHelp:RLTitle Title="LockStats.LockUpgrades
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockUpgrades"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockUpgradesTopic"
/><MSHelp:Keyword Index="K" Term="LockUpgrades property" /><MSHelp:Keyword Index="K"
Term="LockStats.LockUpgrades property" /><MSHelp:Keyword Index="F" Term="LockUpgrades"
/><MSHelp:Keyword Index="F" Term="LockStats.LockUpgrades" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockStats.LockUpgrades" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.LockUpgrades" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.get_LockUpgrades" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Number of lock upgrades." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockUpgrades Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseSentNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_LeaseSentNumber" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_LeaseSentNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.LeaseSentNumber" /><MSHelp:TOCTitle Title="LeaseSentNumber Property " /><MSHelp:RLTitle Title="ReplicationStats.LeaseSentNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.LeaseSentNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassLeaseSentNumberTopic" /><MSHelp:Keyword Index="K" Term="LeaseSentNumber property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.LeaseSentNumber property" /><MSHelp:Keyword Index="F" Term="LeaseSentNumber" /><MSHelp:Keyword Index="F" Term="ReplicationStats.LeaseSentNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.LeaseSentNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.LeaseSentNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_LeaseSentNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of live messages sent while using leases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.LeaseSentNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryRecnoDatabase_Length" /><meta name="guid" content="P_BerkeleyDB_SecondaryRecnoDatabase_Length" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryRecnoDatabase.Length" /><MSHelp:TOCTitle Title="Length Property " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Length Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabase.Length" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassLengthTopic" /><MSHelp:Keyword Index="K"

Term="Length property" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Length property" /><MSHelp:Keyword Index="F" Term="Length" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Length" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Length" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.get_Length" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If using fixed-length, not byte-delimited records, the length of the records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext
Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_SecondaryCursor_MoveNext" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method "
/><MSHelp:RLTitle Title="SecondaryCursor.MoveNext
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNext"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store the secondary key and primary key/data pair in . In ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, HashDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Open_2" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Open(System.String,System.String,BerkeleyDB.HashDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, HashDatabaseConfig)" /><MSHelp:RLTitle Title="HashDatabase.Open Method (String, String, HashDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Open(System.String,System.String,BerkeleyDB.HashDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HashDatabase object and open the database represented by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Open Method (String, String, HashDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="HeapDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Exists"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
  <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and store the secondary key and primary key/dat ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextUnique" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextUnique" /><MSHelp:TOCTitle Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextUniqueTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUnique method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextUnique method" /><MSHelp:Keyword Index="F" Term="MoveNextUnique" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSite Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DbSite" /><meta name="guid" content="Methods_T_BerkeleyDB_DbSite" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DbSite" /><MSHelp:TOCTitle Title="DbSite Methods " /><MSHelp:RLTitle Title="DbSite Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DbSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteMethodsTopic" /><MSHelp:Keyword Index="K" Term="DbSite class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td

align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite Methods </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabase Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_BTreeDatabase" /><meta name="guid" content="Properties_T_BerkeleyDB_BTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.BTreeDatabase" /><MSHelp:TOCTitle Title="BTreeDatabase Properties " /><MSHelp:RLTitle Title="BTreeDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.BTreeDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method "

/><MSHelp:RLTitle Title="BaseDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input

id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HeapDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_HeapDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:TOCTitle Title="HeapDatabaseConfig Properties " /><MSHelp:RLTitle Title="HeapDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HeapDatabaseConfig Properties </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HeapDatabaseConfig.htm">HeapDatabaseConfig Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>RepTransmitLimitGBytes Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepTransmitLimitGBytes" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepTransmitLimitGBytes" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepTransmitLimitGBytes" /><MSHelp:TOCTitle
Title="RepTransmitLimitGBytes Property " /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepTransmitLimitGBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.RepTransmitLimitGBytes" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepTransmitLimitGBytesTopic" /><MSHelp:Keyword
Index="K" Term="RepTransmitLimitGBytes property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepTransmitLimitGBytes property" /><MSHelp:Keyword Index="F"
Term="RepTransmitLimitGBytes" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepTransmitLimitGBytes" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepTransmitLimitGBytes"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepTransmitLimitGBytes" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_RepTransmitLimitGBytes" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The gigabytes component of the byte-count limit on the amount of data that will be transmitted from a site
in response to a single message processed by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepTransmitLimitGBytes Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataFlags Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_MetadataFlags" /><meta name="guid" content="P_BerkeleyDB_HeapStats_MetadataFlags" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.MetadataFlags" /><MSHelp:TOCTitle Title="MetadataFlags Property " /><MSHelp:RLTitle Title="HeapStats.MetadataFlags Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.MetadataFlags" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassMetadataFlagsTopic" /><MSHelp:Keyword Index="K" Term="MetadataFlags property" /><MSHelp:Keyword Index="K" Term="HeapStats.MetadataFlags property" /><MSHelp:Keyword Index="F" Term="MetadataFlags" /><MSHelp:Keyword Index="F" Term="HeapStats.MetadataFlags" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.MetadataFlags" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.MetadataFlags" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_MetadataFlags" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reports
internal flags. For internal use only." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats..::.MetadataFlags Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryHashDatabaseConfig,

Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryHashDatabase_Open_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryHashDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryHashDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryHashDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryHashDatabase.Open Method (String, String, SecondaryHashDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryHashDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryHashDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Open Method (String, String, SecondaryHashDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLocksInTable Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxLocksInTable" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxLocksInTable" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxLocksInTable" /><MSHelp:TOCTitle Title="MaxLocksInTable Property " /><MSHelp:RLTitle Title="LockStats.MaxLocksInTable Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxLocksInTable" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxLocksInTableTopic" /><MSHelp:Keyword Index="K" Term="MaxLocksInTable property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxLocksInTable property" /><MSHelp:Keyword Index="F" Term="MaxLocksInTable" /><MSHelp:Keyword Index="F" Term="LockStats.MaxLocksInTable" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxLocksInTable" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxLocksInTable" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxLocksInTable" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of locks in table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxLocksInTable Property </td></tr><tr
id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MovePrev" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method " /><MSHelp:RLTitle Title="Cursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MovePrev" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMovePrevTopic" /><MSHelp:Keyword Index="K" Term="MovePrev method" /><MSHelp:Keyword Index="K" Term="Cursor.MovePrev method" /><MSHelp:Keyword Index="F" Term="MovePrev" /><MSHelp:Keyword Index="F" Term="Cursor.MovePrev" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td
align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DatabaseConfig" /><MSHelp:TOCTitle Title="DatabaseConfig Members" /><MSHelp:RLTitle Title="DatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class, all members"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseConfig class" /><MSHelp:Keyword Index="F" Term="DatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseConfig Members</td></tr><tr id="headerTableRow3"><td
align="left">DatabaseConfig Class
 Constructors <a
href="#methodTableToggle" onclick="OpenSection(methodTableToggle)">Methods <a
href="#fieldTableToggle" onclick="OpenSection(fieldTableToggle)">Fields <a href="#propertyTableToggle"
onclick="OpenSection(propertyTableToggle)">Properties <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ObjectNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_ObjectNoWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_ObjectNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.ObjectNoWait" /><MSHelp:TOCTitle Title="ObjectNoWait Property " /><MSHelp:RLTitle Title="LockStats.ObjectNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.ObjectNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassObjectNoWaitTopic" /><MSHelp:Keyword Index="K" Term="ObjectNoWait property" /><MSHelp:Keyword Index="K" Term="LockStats.ObjectNoWait property" /><MSHelp:Keyword Index="F" Term="ObjectNoWait" /><MSHelp:Keyword Index="F" Term="LockStats.ObjectNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.ObjectNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.ObjectNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_ObjectNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Object lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">LockStats.<span
class="vb">.::.ObjectNoWait Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LockStats.htm">LockStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Renumber Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_RecnoDatabase_Renumber" /><meta name="guid"
content="P_BerkeleyDB_RecnoDatabase_Renumber"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabase.Renumber"
/><MSHelp:TOCTitle Title="Renumber Property " /><MSHelp:RLTitle Title="RecnoDatabase.Renumber Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabase.Renumber"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassRenumberTopic"
/><MSHelp:Keyword Index="K" Term="Renumber property" /><MSHelp:Keyword Index="K"
Term="RecnoDatabase.Renumber property" /><MSHelp:Keyword Index="F" Term="Renumber"
/><MSHelp:Keyword Index="F" Term="RecnoDatabase.Renumber" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoDatabase.Renumber" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.Renumber" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.RecnoDatabase.get_Renumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the logical record numbers are mutable, and change as records are added to and deleted from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Renumber Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SequenceStats" /><meta name="guid" content="Methods_T_BerkeleyDB_SequenceStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SequenceStats" /><MSHelp:TOCTitle Title="SequenceStats Methods " /><MSHelp:RLTitle Title="SequenceStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SequenceStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="SequenceStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats Methods </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveMultiple" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:TOCTitle Title="MoveMultiple Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveMultiple method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveMultiple method" /><MSHelp:Keyword Index="F" Term="MoveMultiple" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr

id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNextUniqueMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNextUniqueMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextUniqueMultiple" /><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextUniqueMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextUniqueMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextUniqueMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Address Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_RepMgrSite_Address" /><meta name="guid"
content="F_BerkeleyDB_RepMgrSite_Address" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.RepMgrSite.Address" /><MSHelp:TOCTitle Title="Address Field" /><MSHelp:RLTitle
Title="RepMgrSite.Address Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.RepMgrSite.Address" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRepMgrSiteClassAddressTopic" /><MSHelp:Keyword Index="K" Term="Address field"
/><MSHelp:Keyword Index="K" Term="RepMgrSite.Address field" /><MSHelp:Keyword Index="F"
Term="Address" /><MSHelp:Keyword Index="F" Term="RepMgrSite.Address" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepMgrSite.Address" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RepMgrSite.Address" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The address of the site" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrSite..::.Address Field</td></tr><tr id="headerTableRow3"><td align="left">RepMgrSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Cursor" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="RecnoDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Clean Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BackupOptions_Clean" /><meta name="guid" content="F_BerkeleyDB_BackupOptions_Clean" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BackupOptions.Clean" /><MSHelp:TOCTitle Title="Clean Field" /><MSHelp:RLTitle Title="BackupOptions.Clean Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BackupOptions.Clean" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassCleanTopic" /><MSHelp:Keyword Index="K" Term="Clean field" /><MSHelp:Keyword Index="K" Term="BackupOptions.Clean field" /><MSHelp:Keyword Index="F" Term="Clean" /><MSHelp:Keyword Index="F" Term="BackupOptions.Clean" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.Clean" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions.Clean" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, all files are removed from the target backup directory before the back up is performed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">BackupOptions<span
class="cs">..::<span
class="nu">.Clean Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BackupOptions.htm">BackupOptions Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryBTreeDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryBTreeDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Open Method (String, SecondaryBTreeDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryBTreeDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Open Method (String, SecondaryBTreeDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogForceSync Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogForceSync" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogForceSync" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogForceSync" /><MSHelp:TOCTitle Title="LogForceSync Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogForceSync Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogForceSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogForceSyncTopic" /><MSHelp:Keyword Index="K" Term="LogForceSync property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogForceSync property" /><MSHelp:Keyword Index="F" Term="LogForceSync" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogForceSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogForceSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogForceSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogForceSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogForceSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will flush log writes to the backing disk before returning from the write system call, rather than flushing log writes explicitly in a separate system call, as necessary." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment<span
class="languageSpecificText">..<span
class="cpp">::.LogForceSync Property </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionLockWait Property </title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_MPoolStats_RegionLockWait" /><meta name="guid"
content="P_BerkeleyDB_MPoolStats_RegionLockWait" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MPoolStats.RegionLockWait"
/><MSHelp:TOCTitle Title="RegionLockWait Property " /><MSHelp:RLTitle
Title="MPoolStats.RegionLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.MPoolStats.RegionLockWait" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMPoolStatsClassRegionLockWaitTopic" /><MSHelp:Keyword Index="K"
Term="RegionLockWait property" /><MSHelp:Keyword Index="K" Term="MPoolStats.RegionLockWait
property" /><MSHelp:Keyword Index="F" Term="RegionLockWait" /><MSHelp:Keyword Index="F"
Term="MPoolStats.RegionLockWait" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MPoolStats.RegionLockWait" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.RegionLockWait" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.get_RegionLockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Region lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.RegionLockWait Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method (CompactConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Compact_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Compact_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Compact(BerkeleyDB.CompactConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Compact Method (CompactConfig, Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Compact Method (CompactConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Compact(BerkeleyDB.CompactConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Compact the database, and optionally return unused database pages to the underlying filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Compact Method (CompactConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Commit Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Transaction_Commit" /><meta name="guid" content="Overload_BerkeleyDB_Transaction_Commit" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Transaction.Commit" /><MSHelp:TOCTitle Title="Commit Method " /><MSHelp:RLTitle Title="Transaction.Commit Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Transaction.Commit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassCommitTopic" /><MSHelp:Keyword Index="K" Term="Commit method" /><MSHelp:Keyword Index="K" Term="Transaction.Commit method" /><MSHelp:Keyword Index="F" Term="Commit" /><MSHelp:Keyword Index="F" Term="Transaction.Commit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Commit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Commit Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackingFile Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RecnoDatabaseConfig_BackingFile" /><meta name="guid" content="F_BerkeleyDB_RecnoDatabaseConfig_BackingFile" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RecnoDatabaseConfig.BackingFile" /><MSHelp:TOCTitle Title="BackingFile Field" /><MSHelp:RLTitle Title="RecnoDatabaseConfig.BackingFile Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RecnoDatabaseConfig.BackingFile" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassBackingFileTopic" /><MSHelp:Keyword Index="K" Term="BackingFile field" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.BackingFile field" /><MSHelp:Keyword Index="F" Term="BackingFile" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.BackingFile" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.BackingFile" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.BackingFile" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The underlying source file for the Recno access method." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig..::.BackingFile Field</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordPad Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoDatabase_RecordPad" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabase_RecordPad" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabase.RecordPad" /><MSHelp:TOCTitle Title="RecordPad Property " /><MSHelp:RLTitle Title="RecnoDatabase.RecordPad Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabase.RecordPad" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassRecordPadTopic" /><MSHelp:Keyword Index="K" Term="RecordPad property" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.RecordPad property" /><MSHelp:Keyword Index="F" Term="RecordPad" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.RecordPad" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.RecordPad" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.RecordPad" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.get_RecordPad" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.set_RecordPad" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.RecordPad Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirst_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirst_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveFirst Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MoveFirst Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair in . If the first key has duplicate values, the first data item in the set of duplicates is stored in . If e ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirst Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Decompress Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabaseConfig_Decompress" /><meta name="guid"

content="P_BerkeleyDB_BTreeDatabaseConfig_Decompress" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabaseConfig.Decompress" /><MSHelp:TOCTitle Title="Decompress Property " /><MSHelp:RLTitle Title="BTreeDatabaseConfig.Decompress Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabaseConfig.Decompress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassDecompressTopic" /><MSHelp:Keyword Index="K" Term="Decompress property" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.Decompress property" /><MSHelp:Keyword Index="F" Term="Decompress" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.Decompress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.Decompress" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.Decompress" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.get_Decompress" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The decompression function used to retrieve key/data pairs from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.Decompress Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Constructor (SequenceConfig, Transaction)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script
 type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence__ctor_1" /><meta name="guid"
content="M_BerkeleyDB_Sequence__ctor_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Sequence.#ctor(BerkeleyDB.SequenceConfig,BerkeleyDB.Transaction)"
/><MSHelp:TOCTitle Title="Sequence Constructor (SequenceConfig, Transaction)" /><MSHelp:RLTitle
Title="Sequence Constructor (SequenceConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Sequence.#ctor(BerkeleyDB.SequenceConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence..ctor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
 Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Instantiate a new Sequence object." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none;
 height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence Constructor (SequenceConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_SECONDARY_BAD Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_SECONDARY_BAD" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_SECONDARY_BAD" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_SECONDARY_BAD" /><MSHelp:TOCTitle Title="DB_SECONDARY_BAD Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_SECONDARY_BAD Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_SECONDARY_BAD" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_SECONDARY_BADTopic" /><MSHelp:Keyword Index="K" Term="DB_SECONDARY_BAD field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_SECONDARY_BAD field" /><MSHelp:Keyword Index="F" Term="DB_SECONDARY_BAD" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_SECONDARY_BAD" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_SECONDARY_BAD" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.ErrorCodes.DB_SECONDARY_BAD" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Secondary index corrupt." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_SECONDARY_BAD Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_nPages" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_nPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.nPages" /><MSHelp:TOCTitle Title="nPages Property " /><MSHelp:RLTitle Title="BTreeStats.nPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.nPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassnPagesTopic" /><MSHelp:Keyword Index="K" Term="nPages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.nPages property" /><MSHelp:Keyword Index="F" Term="nPages" /><MSHelp:Keyword Index="F" Term="BTreeStats.nPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.nPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.nPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_nPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page count." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.nPages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxCommitsPerFlush Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_MaxCommitsPerFlush" /><meta name="guid" content="P_BerkeleyDB_LogStats_MaxCommitsPerFlush" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.MaxCommitsPerFlush" /><MSHelp:TOCTitle Title="MaxCommitsPerFlush Property " /><MSHelp:RLTitle Title="LogStats.MaxCommitsPerFlush Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.MaxCommitsPerFlush" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassMaxCommitsPerFlushTopic" /><MSHelp:Keyword Index="K" Term="MaxCommitsPerFlush property" /><MSHelp:Keyword Index="K" Term="LogStats.MaxCommitsPerFlush property" /><MSHelp:Keyword Index="F" Term="MaxCommitsPerFlush" /><MSHelp:Keyword Index="F" Term="LogStats.MaxCommitsPerFlush" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.MaxCommitsPerFlush" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.MaxCommitsPerFlush" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_MaxCommitsPerFlush" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max number of commits in a flush." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.MaxCommitsPerFlush Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method (String, DatabaseConfig, Boolean, TextWriter)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Salvage_4" /><meta
name="guid" content="M_BerkeleyDB_Database_Salvage_4" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean,System.IO.
TextWriter)" /><MSHelp:TOCTitle Title="Salvage Method (String, DatabaseConfig, Boolean, TextWriter)"
/><MSHelp:RLTitle Title="Database.Salvage Method (String, DatabaseConfig, Boolean, TextWriter)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean,System.IO.T
extWriter)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Salvage"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Write the key/data pairs from all databases in the file to . Key values are
written for Btree, Hash and Queue databases, but not for Recno databases." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Salvage Method (String, DatabaseConfig, Boolean, TextWriter)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForceFlush Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_ForceFlush" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_ForceFlush" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.ForceFlush" /><MSHelp:TOCTitle Title="ForceFlush Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.ForceFlush Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.ForceFlush" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassForceFlushTopic" /><MSHelp:Keyword Index="K" Term="ForceFlush field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.ForceFlush field" /><MSHelp:Keyword Index="F" Term="ForceFlush" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.ForceFlush" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.ForceFlush" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.ForceFlush" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will flush database writes to the backing disk before returning from the write system call, rather than flushing database writes explicitly in a separate system call, as necessary. ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironmentConfig.<span
class="vb">.::.ForceFlush
Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeCursor
Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_BTreeCursor" /><meta
name="guid" content="Properties_T_BerkeleyDB_BTreeCursor" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.BTreeCursor" /><MSHelp:TOCTitle Title="BTreeCursor Properties "

/><MSHelp:RLTitle Title="BTreeCursor Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.BTreeCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorPropertiesTopic" /><MSHelp:Keyword Index="K" Term="BTreeCursor class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label

class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor Properties </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="BTreeDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label

id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeDatabase.<span
class="vb">.::.PrintStats Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeDatabase.htm">BTreeDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>BucketsCheckedDuringAlloc
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_MPoolStats_BucketsCheckedDuringAlloc" /><meta name="guid"
content="P_BerkeleyDB_MPoolStats_BucketsCheckedDuringAlloc" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MPoolStats.BucketsCheckedDuringAlloc"
/><MSHelp:TOCTitle Title="BucketsCheckedDuringAlloc Property " /><MSHelp:RLTitle
Title="MPoolStats.BucketsCheckedDuringAlloc Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.MPoolStats.BucketsCheckedDuringAlloc" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMPoolStatsClassBucketsCheckedDuringAllocTopic" /><MSHelp:Keyword Index="K"
Term="BucketsCheckedDuringAlloc property" /><MSHelp:Keyword Index="K"
Term="MPoolStats.BucketsCheckedDuringAlloc property" /><MSHelp:Keyword Index="F"
Term="BucketsCheckedDuringAlloc" /><MSHelp:Keyword Index="F"
Term="MPoolStats.BucketsCheckedDuringAlloc" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MPoolStats.BucketsCheckedDuringAlloc" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.MPoolStats.BucketsCheckedDuringAlloc" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.MPoolStats.get_BucketsCheckedDuringAlloc" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Buckets checked during allocation." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.BucketsCheckedDuringAlloc Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (UInt32, Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultiple_3" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultiple Method (UInt32, Int32, LockingInfo)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultiple Method (UInt32, Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultiple Method (UInt32, Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="F_BerkeleyDB_BTreeDatabaseConfig_Creation" /><meta name="guid"
content="F_BerkeleyDB_BTreeDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.BTreeDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field"
/><MSHelp:RLTitle Title="BTreeDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.BTreeDatabaseConfig.Creation" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K"
Term="Creation field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.Creation field"
/><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F"
Term="BTreeDatabaseConfig.Creation" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for
how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="HashDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassPrintFastStatsTopic" />
<MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="HashDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="HashDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td>

<label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_Duplicates" /><meta name="guid" content="P_BerkeleyDB_BTreeDatabase_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabase.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Property " /><MSHelp:RLTitle Title="BTreeDatabase.Duplicates Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates property" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Duplicates property" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Duplicates" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.get_Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the insertion
of duplicate data items in the database is permitted, and whether duplicates items are sorted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Duplicates Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Max Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Max" /><meta name="guid" content="P_BerkeleyDB_Sequence_Max" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.Max" /><MSHelp:TOCTitle Title="Max Property " /><MSHelp:RLTitle Title="Sequence.Max Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Max" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassMaxTopic" /><MSHelp:Keyword Index="K" Term="Max property" /><MSHelp:Keyword Index="K" Term="Sequence.Max property" /><MSHelp:Keyword Index="F" Term="Max" /><MSHelp:Keyword Index="F" Term="Sequence.Max" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Max" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Max" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Max" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum value in the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Max Property </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorCodes Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ErrorCodes" /><meta name="guid" content="Methods_T_BerkeleyDB_ErrorCodes" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ErrorCodes" /><MSHelp:TOCTitle Title="ErrorCodes Methods " /><MSHelp:RLTitle Title="ErrorCodes Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="Methods.T:BerkeleyDB.ErrorCodes" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBErrorCodesMethodsTopic" /><MSHelp:Keyword Index="K" Term="ErrorCodes class,
methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input

id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes Methods </td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_RepMgrSite" /><meta name="guid" content="Fields_T_BerkeleyDB_RepMgrSite" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.RepMgrSite" /><MSHelp:TOCTitle Title="RepMgrSite Fields" /><MSHelp:RLTitle Title="RepMgrSite Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.RepMgrSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrSiteFieldsTopic" /><MSHelp:Keyword Index="K" Term="RepMgrSite class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RepMgrSite Fields</td></tr><tr id="headerTableRow3"><td
align="left">RepMgrSite Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ID Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ActiveTransaction_ID" /><meta name="guid"

content="P_BerkeleyDB_ActiveTransaction_ID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.ID" /><MSHelp:TOCTitle Title="ID Property " /><MSHelp:RLTitle Title="ActiveTransaction.ID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.ID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassIDTopic" /><MSHelp:Keyword Index="K" Term="ID property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.ID property" /><MSHelp:Keyword Index="F" Term="ID" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.ID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.ID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.ID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_ID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The transaction ID of the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">ActiveTransaction..::.ID Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nKeys Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_nKeys" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_nKeys" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.nKeys" /><MSHelp:TOCTitle Title="nKeys Property " /><MSHelp:RLTitle Title="BTreeStats.nKeys Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.nKeys" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassnKeysTopic" /><MSHelp:Keyword Index="K" Term="nKeys property" /><MSHelp:Keyword Index="K" Term="BTreeStats.nKeys property" /><MSHelp:Keyword Index="F" Term="nKeys" /><MSHelp:Keyword Index="F" Term="BTreeStats.nKeys" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.nKeys" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.nKeys" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_nKeys" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of unique keys." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.nKeys Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">DatabaseEnvironment..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Alignment Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexConfig_Alignment" /><meta name="guid" content="P_BerkeleyDB_MutexConfig_Alignment" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexConfig.Alignment" /><MSHelp:TOCTitle Title="Alignment Property " /><MSHelp:RLTitle Title="MutexConfig.Alignment Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexConfig.Alignment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigClassAlignmentTopic" /><MSHelp:Keyword Index="K" Term="Alignment property" /><MSHelp:Keyword Index="K" Term="MutexConfig.Alignment property" /><MSHelp:Keyword Index="F" Term="Alignment" /><MSHelp:Keyword Index="F" Term="MutexConfig.Alignment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig.Alignment" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.Alignment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.get_Alignment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.set_Alignment" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mutex alignment,
in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig..::.Alignment Property </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, QueueDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Open(System.String,BerkeleyDB.QueueDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, QueueDatabaseConfig)" /><MSHelp:RLTitle Title="QueueDatabase.Open Method (String, QueueDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Open(System.String,BerkeleyDB.QueueDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Open"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new QueueDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Open Method (String, QueueDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DeadlockException" /><meta name="guid" content="Properties_T_BerkeleyDB_DeadlockException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DeadlockException" /><MSHelp:TOCTitle Title="DeadlockException Properties " /><MSHelp:RLTitle Title="DeadlockException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DeadlockException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DeadlockException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockException Properties </td></tr><tr id="headerTableRow3"><td align="left">DeadlockException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLockSteals Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxLockSteals" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxLockSteals" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxLockSteals" /><MSHelp:TOCTitle Title="MaxLockSteals Property " /><MSHelp:RLTitle Title="LockStats.MaxLockSteals Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxLockSteals" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxLockStealsTopic" /><MSHelp:Keyword Index="K" Term="MaxLockSteals property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxLockSteals property" /><MSHelp:Keyword Index="F" Term="MaxLockSteals" /><MSHelp:Keyword Index="F" Term="LockStats.MaxLockSteals" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxLockSteals" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxLockSteals" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.LockStats.get_MaxLockSteals" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number steals in any partition." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxLockSteals Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePagesFreeBytes
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_DuplicatePagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_DuplicatePagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.DuplicatePagesFreeBytes"
/><MSHelp:TOCTitle Title="DuplicatePagesFreeBytes Property " /><MSHelp:RLTitle Title="BTreeStats.DuplicatePagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassDuplicatePagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="DuplicatePagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="BTreeStats.DuplicatePagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BTreeStats.DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.DuplicatePagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.DuplicatePagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_DuplicatePagesFreeBytes" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in duplicate pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.DuplicatePagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseCheckedRefreshNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_LeaseCheckedRefreshNumber" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_LeaseCheckedRefreshNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.LeaseCheckedRefreshNumber" /><MSHelp:TOCTitle Title="LeaseCheckedRefreshNumber Property " /><MSHelp:RLTitle Title="ReplicationStats.LeaseCheckedRefreshNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.LeaseCheckedRefreshNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassLeaseCheckedRefreshNumberTopic" /><MSHelp:Keyword Index="K" Term="LeaseCheckedRefreshNumber property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.LeaseCheckedRefreshNumber property" /><MSHelp:Keyword Index="F" Term="LeaseCheckedRefreshNumber" /><MSHelp:Keyword Index="F" Term="ReplicationStats.LeaseCheckedRefreshNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.LeaseCheckedRefreshNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.LeaseCheckedRefreshNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_LeaseCheckedRefreshNumber"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lease refresh attempts during lease validity checks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.LeaseCheckedRefreshNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStartClient Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepStartClient" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepStartClient" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:TOCTitle Title="RepStartClient Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStartClient Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure the database environment as a client in a group of replicated database environments." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepStartClient Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VersionMismatchException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_VersionMismatchException" /><meta name="guid" content="Methods_T_BerkeleyDB_VersionMismatchException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.VersionMismatchException" /><MSHelp:TOCTitle Title="VersionMismatchException Methods " /><MSHelp:RLTitle Title="VersionMismatchException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.VersionMismatchException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVersionMismatchExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VersionMismatchException Methods </td></tr><tr id="headerTableRow3"><td align="left">VersionMismatchException
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GroupCreator Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_GroupCreator" /><meta name="guid" content="P_BerkeleyDB_DbSite_GroupCreator" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSite.GroupCreator" /><MSHelp:TOCTitle Title="GroupCreator Property " /><MSHelp:RLTitle Title="DbSite.GroupCreator Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSite.GroupCreator" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassGroupCreatorTopic" /><MSHelp:Keyword Index="K" Term="GroupCreator property" /><MSHelp:Keyword Index="K" Term="DbSite.GroupCreator property" /><MSHelp:Keyword Index="F" Term="GroupCreator"
/><MSHelp:Keyword Index="F" Term="DbSite.GroupCreator" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.GroupCreator" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.GroupCreator" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.get_GroupCreator" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.set_GroupCreator" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is a group creator." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.GroupCreator Property </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Bulk Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_TransactionConfig_Bulk" /><meta name="guid" content="F_BerkeleyDB_TransactionConfig_Bulk" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.TransactionConfig.Bulk" /><MSHelp:TOCTitle Title="Bulk Field" /><MSHelp:RLTitle Title="TransactionConfig.Bulk Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.Bulk" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassBulkTopic" /><MSHelp:Keyword Index="K" Term="Bulk field" /><MSHelp:Keyword Index="K" Term="TransactionConfig.Bulk field" /><MSHelp:Keyword Index="F" Term="Bulk" /><MSHelp:Keyword Index="F" Term="TransactionConfig.Bulk" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.Bulk" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.Bulk" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configures the transaction to enable or disable the transactional bulk insert optimization." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.Bulk Field</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingInfo Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LockingInfo" /><meta name="guid" content="T_BerkeleyDB_LockingInfo"

/><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LockingInfo" /><MSHelp:TOCTitle Title="LockingInfo Class" /><MSHelp:RLTitle Title="LockingInfo Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LockingInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingInfoClassTopic" /><MSHelp:Keyword Index="K" Term="LockingInfo class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockingInfo class" /><MSHelp:Keyword Index="K" Term="LockingInfo class, about LockingInfo class" /><MSHelp:Keyword Index="F" Term="LockingInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingInfo" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingInfo" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing the locking options for Berkeley DB operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingInfo

Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStrict2Site Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepStrict2Site" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepStrict2Site" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepStrict2Site" /><MSHelp:TOCTitle Title="RepStrict2Site Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStrict2Site Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepStrict2Site" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepStrict2SiteTopic" /><MSHelp:Keyword Index="K" Term="RepStrict2Site property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepStrict2Site property" /><MSHelp:Keyword Index="F" Term="RepStrict2Site" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepStrict2Site" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepStrict2Site" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepStrict2Site" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepStrict2Site" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepStrict2Site" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Replication Manager observes the strict "majority" rule in managing elections, even in a group with only 2 sites. This means the client in a 2-site group will be unable to take over as master if the ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepStrict2Site Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>JoinCursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_JoinCursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_JoinCursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.JoinCursor" /><MSHelp:TOCTitle Title="JoinCursor Members" /><MSHelp:RLTitle Title="JoinCursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.JoinCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="JoinCursor class" /><MSHelp:Keyword Index="K" Term="JoinCursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.JoinCursor

class" /><MSHelp:Keyword Index="F" Term="JoinCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"

onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor Members</td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class Methods
  Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
 </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryHashDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_SecondaryHashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryHashDatabaseConfig Class" /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K"
 Term="SecondaryHashDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryHashDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class, about SecondaryHashDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion"
 Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionMemoryLimitBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RegionMemoryLimitBytes" /><meta name="guid"

content="P_BerkeleyDB_DatabaseEnvironment_RegionMemoryLimitBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitBytes" /><MSHelp:TOCTitle Title="RegionMemoryLimitBytes Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RegionMemoryLimitBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRegionMemoryLimitBytesTopic" /><MSHelp:Keyword Index="K" Term="RegionMemoryLimitBytes property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RegionMemoryLimitBytes property" /><MSHelp:Keyword Index="F" Term="RegionMemoryLimitBytes" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RegionMemoryLimitBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RegionMemoryLimitBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The bytes component of the byte-count limit on the amount of memory to be used by shared structures in the main environment region. These are the structures other than mutexes and the page cache (m ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RegionMemoryLimitBytes Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupDatabase Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_BackupDatabase" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_BackupDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.BackupDatabase(System.String,System.String,System.Boolean)" /><MSHelp:TOCTitle Title="BackupDatabase Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.BackupDatabase Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.BackupDatabase(System.String,System.String,System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupDatabaseTopic" /><MSHelp:Keyword Index="K" Term="BackupDatabase method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BackupDatabase method" /><MSHelp:Keyword Index="F" Term="BackupDatabase" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BackupDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BackupDatabase" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BackupDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Perform a hot back up of a single database file contained within the environment. To back up the entire environment, use the method. You can make some tun ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BackupDatabase Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockNotGrantedException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LockNotGrantedException" /><meta name="guid" content="T_BerkeleyDB_LockNotGrantedException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LockNotGrantedException" /><MSHelp:TOCTitle Title="LockNotGrantedException Class" /><MSHelp:RLTitle Title="LockNotGrantedException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LockNotGrantedException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockNotGrantedExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockNotGrantedException class" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class, about LockNotGrantedException class" /><MSHelp:Keyword Index="F" Term="LockNotGrantedException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockNotGrantedException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockNotGrantedException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If is true, database calls timing out based on lock or transaction timeout values will throw a LockNotGrantedException, instead of a DeadlockException." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockNotGrantedException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ReplicationConfig" /><meta name="guid" content="T_BerkeleyDB_ReplicationConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ReplicationConfig" /><MSHelp:TOCTitle Title="ReplicationConfig Class" /><MSHelp:RLTitle Title="ReplicationConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ReplicationConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassTopic" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ReplicationConfig class" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class, about ReplicationConfig class" /><MSHelp:Keyword Index="F" Term="ReplicationConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for a 's replication subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DoChecksum Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_DoChecksum" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_DoChecksum" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.DoChecksum" /><MSHelp:TOCTitle Title="DoChecksum Field" /><MSHelp:RLTitle Title="DatabaseConfig.DoChecksum Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.DoChecksum" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBDatabaseConfigClassDoChecksumTopic" /><MSHelp:Keyword Index="K" Term="DoChecksum field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.DoChecksum field" /><MSHelp:Keyword Index="F" Term="DoChecksum" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.DoChecksum" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.DoChecksum" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.DoChecksum" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, do checksum verification of pages read into the cache from the backing filestore." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.DoChecksum

Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseConfig.htm">DatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReadOnly
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_ReadOnly" /><meta
name="guid" content="P_BerkeleyDB_BaseDatabase_ReadOnly" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BaseDatabase.ReadOnly" /><MSHelp:TOCTitle Title="ReadOnly Property "
/><MSHelp:RLTitle Title="BaseDatabase.ReadOnly Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.ReadOnly" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassReadOnlyTopic" /><MSHelp:Keyword Index="K" Term="ReadOnly
property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.ReadOnly property" /><MSHelp:Keyword
Index="F"
Term="ReadOnly" /><MSHelp:Keyword Index="F" Term="BaseDatabase.ReadOnly" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.BaseDatabase.ReadOnly" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.ReadOnly" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_ReadOnly" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, this
database has been opened for reading only. Any attempt to modify items in the database will fail, regardless of the
actual permissions of any underlying files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.ReadOnly Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ByteOrder Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ByteOrder" /><meta name="guid" content="Methods_T_BerkeleyDB_ByteOrder" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ByteOrder" /><MSHelp:TOCTitle Title="ByteOrder Methods " /><MSHelp:RLTitle Title="ByteOrder Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.ByteOrder" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBByteOrderMethodsTopic" /><MSHelp:Keyword Index="K" Term="ByteOrder class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder Methods </td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesFreed Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactData_PagesFreed" /><meta name="guid" content="P_BerkeleyDB_CompactData_PagesFreed" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactData.PagesFreed" /><MSHelp:TOCTitle Title="PagesFreed Property " /><MSHelp:RLTitle Title="CompactData.PagesFreed Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactData.PagesFreed" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassPagesFreedTopic" /><MSHelp:Keyword Index="K" Term="PagesFreed property" /><MSHelp:Keyword Index="K" Term="CompactData.PagesFreed property" /><MSHelp:Keyword Index="F" Term="PagesFreed" /><MSHelp:Keyword Index="F" Term="CompactData.PagesFreed" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData.PagesFreed" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.PagesFreed" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.get_PagesFreed" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of database pages freed during the compaction phase." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData..<span
class="cpp">::.PagesFreed Property </td></tr><tr id="headerTableRow3"><td align="left">CompactData Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Wrap Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Wrap" /><meta name="guid" content="P_BerkeleyDB_Sequence_Wrap" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.Wrap" /><MSHelp:TOCTitle Title="Wrap Property " /><MSHelp:RLTitle Title="Sequence.Wrap Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Wrap" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassWrapTopic" /><MSHelp:Keyword Index="K" Term="Wrap property" /><MSHelp:Keyword Index="K" Term="Sequence.Wrap property" /><MSHelp:Keyword Index="F" Term="Wrap" /><MSHelp:Keyword Index="F" Term="Sequence.Wrap" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Wrap" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Wrap" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Wrap" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the sequence should wrap around when it is incremented (decremented) past the specified maximum (minimum) value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Sequence..::.Wrap Property </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EnvID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_EnvID" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_EnvID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.EnvID" /><MSHelp:TOCTitle Title="EnvID Property " /><MSHelp:RLTitle Title="ReplicationStats.EnvID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.EnvID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassEnvIDTopic" /><MSHelp:Keyword Index="K" Term="EnvID property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.EnvID property" /><MSHelp:Keyword Index="F" Term="EnvID" /><MSHelp:Keyword Index="F" Term="ReplicationStats.EnvID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.EnvID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.EnvID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_EnvID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current environment ID." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.EnvID Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Lockdown Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Lockdown" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Lockdown" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Lockdown" /><MSHelp:TOCTitle Title="Lockdown Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Lockdown Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Lockdown" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassLockdownTopic" /><MSHelp:Keyword Index="K" Term="Lockdown field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Lockdown field" /><MSHelp:Keyword Index="F" Term="Lockdown" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.Lockdown" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.Lockdown" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.Lockdown" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, lock shared Berkeley DB environment files and memory-mapped databases into memory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.Lockdown Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_SecondaryCursor" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.SecondaryCursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassSecondaryCursorTopic" /><MSHelp:Keyword Index="K" Term="SecondaryCursor method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.SecondaryCursor method" /><MSHelp:Keyword Index="F" Term="SecondaryCursor" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.SecondaryCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.SecondaryCursor Method </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultiple is identical to . Otherwise,

move the cursor to the next non-duplicate key in the database, and store that key and associated datum and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUniqueMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_HeapStats_nPages" /><meta name="guid"
content="P_BerkeleyDB_HeapStats_nPages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.HeapStats.nPages" /><MSHelp:TOCTitle Title="nPages Property " /><MSHelp:RLTitle
Title="HeapStats.nPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.HeapStats.nPages" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHeapStatsClassnPagesTopic" /><MSHelp:Keyword Index="K" Term="nPages property"
/><MSHelp:Keyword Index="K" Term="HeapStats.nPages property" /><MSHelp:Keyword Index="F"
Term="nPages" /><MSHelp:Keyword Index="F" Term="HeapStats.nPages" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HeapStats.nPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapStats.nPages" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapStats.get_nPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of pages in the
database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats..::.nPages Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LSN Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LSN" /><meta name="guid" content="Methods_T_BerkeleyDB_LSN" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LSN" /><MSHelp:TOCTitle Title="LSN Methods " /><MSHelp:RLTitle Title="LSN Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LSN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNMethodsTopic" /><MSHelp:Keyword Index="K" Term="LSN class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
 style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
 id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected"
 value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">LSN Methods </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LSN.htm">LSN Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
 xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepCheckpointDelay Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepCheckpointDelay" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepCheckpointDelay" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.RepCheckpointDelay" /><MSHelp:TOCTitle
Title="RepCheckpointDelay Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepCheckpointDelay
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.RepCheckpointDelay" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepCheckpointDelayTopic" /><MSHelp:Keyword Index="K"
Term="RepCheckpointDelay property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepCheckpointDelay property" /><MSHelp:Keyword Index="F"
Term="RepCheckpointDelay" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepCheckpointDelay" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepCheckpointDelay"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepCheckpointDelay" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_RepCheckpointDelay" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.set_RepCheckpointDelay" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The amount of time a master site will delay between completing a checkpoint and writing a checkpoint
record into the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepCheckpointDelay Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxQueuedLogRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_MaxQueuedLogRecords" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MaxQueuedLogRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MaxQueuedLogRecords" /><MSHelp:TOCTitle Title="MaxQueuedLogRecords Property " /><MSHelp:RLTitle Title="ReplicationStats.MaxQueuedLogRecords Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MaxQueuedLogRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMaxQueuedLogRecordsTopic" /><MSHelp:Keyword Index="K" Term="MaxQueuedLogRecords property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MaxQueuedLogRecords property" /><MSHelp:Keyword Index="F" Term="MaxQueuedLogRecords" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MaxQueuedLogRecords" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MaxQueuedLogRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MaxQueuedLogRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MaxQueuedLogRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max. log records queued at once." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MaxQueuedLogRecords Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Upgrade Method (String, DatabaseConfig, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Upgrade_1" /><meta name="guid" content="M_BerkeleyDB_Database_Upgrade_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Upgrade(System.String,BerkeleyDB.DatabaseConfig,System.Boolean)" /><MSHelp:TOCTitle Title="Upgrade Method (String, DatabaseConfig, Boolean)" /><MSHelp:RLTitle Title="Database.Upgrade Method (String, DatabaseConfig, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Database.Upgrade(System.String,BerkeleyDB.DatabaseConfig,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Upgrade" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Upgrade all of the databases included in the file , if necessary. If no upgrade is necessary, Upgrade always returns successfully." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Upgrade Method (String, DatabaseConfig, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DEFAULT Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_DEFAULT" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_DEFAULT" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.DEFAULT" /><MSHelp:TOCTitle Title="DEFAULT Field" /><MSHelp:RLTitle Title="DeadlockPolicy.DEFAULT Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DeadlockPolicy.DEFAULT" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassDEFAULTTopic" /><MSHelp:Keyword Index="K" Term="DEFAULT field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.DEFAULT field" /><MSHelp:Keyword Index="F" Term="DEFAULT" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.DEFAULT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.DEFAULT" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.DEFAULT" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If no DeadlockPolicy has yet been specified, use ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy..::.DEFAULT Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_FastStats" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="BTreeDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>StartSyncMessagesDelayed Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_StartSyncMessagesDelayed" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_StartSyncMessagesDelayed" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.StartSyncMessagesDelayed" /><MSHelp:TOCTitle Title="StartSyncMessagesDelayed Property " /><MSHelp:RLTitle Title="ReplicationStats.StartSyncMessagesDelayed Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.StartSyncMessagesDelayed" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassStartSyncMessagesDelayedTopic" /><MSHelp:Keyword Index="K" Term="StartSyncMessagesDelayed property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.StartSyncMessagesDelayed property" /><MSHelp:Keyword Index="F" Term="StartSyncMessagesDelayed" /><MSHelp:Keyword Index="F" Term="ReplicationStats.StartSyncMessagesDelayed" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.StartSyncMessagesDelayed" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.StartSyncMessagesDelayed" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_StartSyncMessagesDelayed" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of STARTSYNC msgs delayed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..<span
class="cpp">::.StartSyncMessagesDelayed Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_FastStats" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="HeapDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verify Method (String, String, DatabaseConfig, Database.VerifyOperation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script

type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Verify_2" /><meta name="guid" content="M_BerkeleyDB_Database_Verify_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Verify(System.String,System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Database.VerifyOperation)" /><MSHelp:TOCTitle Title="Verify Method (String, String, DatabaseConfig, Database.VerifyOperation)" /><MSHelp:RLTitle Title="Database.Verify Method (String, String, DatabaseConfig, Database.VerifyOperation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Verify(System.String,System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Database.VerifyOperation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Verify" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Verify the integrity of the database specified by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Verify Method (String, String, DatabaseConfig, Database..::.VerifyOperation)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueuedLogRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_QueuedLogRecords" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_QueuedLogRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.QueuedLogRecords" /><MSHelp:TOCTitle Title="QueuedLogRecords Property " /><MSHelp:RLTitle Title="ReplicationStats.QueuedLogRecords Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.QueuedLogRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassQueuedLogRecordsTopic" /><MSHelp:Keyword Index="K" Term="QueuedLogRecords property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.QueuedLogRecords property" /><MSHelp:Keyword Index="F" Term="QueuedLogRecords" /><MSHelp:Keyword Index="F" Term="ReplicationStats.QueuedLogRecords" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.QueuedLogRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.QueuedLogRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_QueuedLogRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total # of log recs. ever queued." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.QueuedLogRecords Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB"

/><meta name="file" content="P_BerkeleyDB_RecnoDatabaseConfig_PadByte" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabaseConfig_PadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabaseConfig.PadByte" /><MSHelp:TOCTitle Title="PadByte Property " /><MSHelp:RLTitle Title="RecnoDatabaseConfig.PadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabaseConfig.PadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassPadByteTopic" /><MSHelp:Keyword Index="K" Term="PadByte property" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.PadByte property" /><MSHelp:Keyword Index="F" Term="PadByte" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.PadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.get_PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.set_PadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transaction Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_Transaction" /><meta name="guid" content="Properties_T_BerkeleyDB_Transaction" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.Transaction" /><MSHelp:TOCTitle Title="Transaction Properties " /><MSHelp:RLTitle Title="Transaction Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.Transaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="Transaction class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label
class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Transaction Properties </td></tr><tr id="headerTableRow3"><td
align="left">Transaction Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Delete Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Delete" /><meta
name="guid" content="M_BerkeleyDB_BaseDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.BaseDatabase.Delete(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Delete Method (DatabaseEntry)" /><MSHelp:RLTitle Title="BaseDatabase.Delete Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Delete(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove key/data pairs from the
database. If is DatabaseEntry, the key/data pair associated with is discarded from the database. In the presence of duplicate key values, all records associated wi ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Delete Method

(DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_Move" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.Move" /><MSHelp:TOCTitle Title="Move Method " /><MSHelp:RLTitle Title="HashCursor.Move Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.Move" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveTopic" /><MSHelp:Keyword Index="K" Term="Move method" /><MSHelp:Keyword Index="K" Term="HashCursor.Move method" /><MSHelp:Keyword Index="F" Term="Move" /><MSHelp:Keyword Index="F" Term="HashCursor.Move" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this,
'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">HashCursor<span
class="languageSpecificText">..<span
class="cpp">::.Move Method </td></tr><tr
id="headerTableRow3"><td align="left">HashCursor Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MaxLeaseUSec Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ReplicationStats_MaxLeaseUSec"

/><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MaxLeaseUSec" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MaxLeaseUSec" /><MSHelp:TOCTitle Title="MaxLeaseUSec Property " /><MSHelp:RLTitle Title="ReplicationStats.MaxLeaseUSec Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MaxLeaseUSec" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMaxLeaseUSecTopic" /><MSHelp:Keyword Index="K" Term="MaxLeaseUSec property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MaxLeaseUSec property" /><MSHelp:Keyword Index="F" Term="MaxLeaseUSec" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MaxLeaseUSec" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MaxLeaseUSec" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MaxLeaseUSec" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MaxLeaseUSec" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum lease timestamp useconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MaxLeaseUSec Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryQueueDatabaseConfig_PadByte" /><meta name="guid" content="P_BerkeleyDB_SecondaryQueueDatabaseConfig_PadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryQueueDatabaseConfig.PadByte" /><MSHelp:TOCTitle Title="PadByte Property " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig.PadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryQueueDatabaseConfig.PadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassPadByteTopic" /><MSHelp:Keyword Index="K" Term="PadByte property" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig.PadByte property" /><MSHelp:Keyword Index="F" Term="PadByte" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig.PadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.get_PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.set_PadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AckTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_AckTimeout" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_AckTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.AckTimeout"

/><MSHelp:TOCTitle Title="AckTimeout Property " /><MSHelp:RLTitle Title="ReplicationConfig.AckTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.AckTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassAckTimeoutTopic" /><MSHelp:Keyword Index="K" Term="AckTimeout property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.AckTimeout property" /><MSHelp:Keyword Index="F" Term="AckTimeout" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.AckTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.AckTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.AckTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_AckTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_AckTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time the replication manager's transport function waits to collect enough acknowledgments from replication group clients, before giving up and returning a failure indication. The defa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.AckTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryRecnoDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
 </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,BerkeleyDB.SecondaryRecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryRecnoDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Open Method (String, SecondaryRecnoDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,BerkeleyDB.SecondaryRecnoDatabaseConfig,BerkeleyDB.Transaction)" />
<MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryRecnoDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
 height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Open Method (String, SecondaryRecnoDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method (String, DatabaseConfig, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Salvage_1" /><meta name="guid" content="M_BerkeleyDB_Database_Salvage_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean)" /><MSHelp:TOCTitle Title="Salvage Method (String, DatabaseConfig, Boolean)" /><MSHelp:RLTitle Title="Database.Salvage Method (String, DatabaseConfig,

Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Salvage"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Write the key/data pairs from all databases in the file to . Key values are
written for Btree, Hash and Queue databases, but not for Recno databases." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">..<span
class="cpp">::.Salvage Method (String, DatabaseConfig,
Boolean)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AppendCallback Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_RecnoDatabase_AppendCallback" /><meta name="guid"
content="P_BerkeleyDB_RecnoDatabase_AppendCallback" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.RecnoDatabase.AppendCallback" /><MSHelp:TOCTitle Title="AppendCallback Property "
/><MSHelp:RLTitle Title="RecnoDatabase.AppendCallback Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.RecnoDatabase.AppendCallback" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoDatabaseClassAppendCallbackTopic" /><MSHelp:Keyword Index="K"
Term="AppendCallback property" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.AppendCallback
property" /><MSHelp:Keyword Index="F" Term="AppendCallback" /><MSHelp:Keyword Index="F"
Term="RecnoDatabase.AppendCallback" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoDatabase.AppendCallback" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.AppendCallback" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.get_AppendCallback" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.set_AppendCallback" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A function to call after the record number has been selected but before the data has been stored into the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.AppendCallback Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxTransactions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_MaxTransactions" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_MaxTransactions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.MaxTransactions" /><MSHelp:TOCTitle Title="MaxTransactions Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.MaxTransactions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.MaxTransactions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassMaxTransactionsTopic" /><MSHelp:Keyword Index="K" Term="MaxTransactions property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.MaxTransactions property" /><MSHelp:Keyword Index="F" Term="MaxTransactions" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.MaxTransactions"

/><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.MaxTransactions" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.MaxTransactions" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_MaxTransactions" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.set_MaxTransactions" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The number of active transactions supported by the environment. This value bounds the
size of the memory allocated for transactions. Child transactions are counted as active until they either commit or ..."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig<span
class="languageSpecificText">..<span
class="cpp">::.MaxTransactions Property </td></tr><tr

id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
 CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_Database_Salvage" /><meta name="guid"
content="Overload_BerkeleyDB_Database_Salvage" /><xml><MSHelp:Attr Name="AssetID"
 Value="Overload:BerkeleyDB.Database.Salvage" /><MSHelp:TOCTitle Title="Salvage Method "
/><MSHelp:RLTitle Title="Database.Salvage Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.Database.Salvage" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseClassSalvageTopic" /><MSHelp:Keyword Index="K" Term="Salvage method"
/><MSHelp:Keyword Index="K" Term="Database.Salvage method" /><MSHelp:Keyword Index="F"
Term="Salvage" /><MSHelp:Keyword Index="F" Term="Database.Salvage" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Database.Salvage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset"
 /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
 style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Salvage Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CleanPagesEvicted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_CleanPagesEvicted" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_CleanPagesEvicted" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.CleanPagesEvicted"

/><MSHelp:TOCTitle Title="CleanPagesEvicted Property " /><MSHelp:RLTitle Title="MPoolStats.CleanPagesEvicted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.CleanPagesEvicted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassCleanPagesEvictedTopic" /><MSHelp:Keyword Index="K" Term="CleanPagesEvicted property" /><MSHelp:Keyword Index="K" Term="MPoolStats.CleanPagesEvicted property" /><MSHelp:Keyword Index="F" Term="CleanPagesEvicted" /><MSHelp:Keyword Index="F" Term="MPoolStats.CleanPagesEvicted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.CleanPagesEvicted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.CleanPagesEvicted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_CleanPagesEvicted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Clean pages forced from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.CleanPagesEvicted Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbChannel Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DbChannel" /><meta name="guid" content="Methods_T_BerkeleyDB_DbChannel" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DbChannel" /><MSHelp:TOCTitle Title="DbChannel Methods " /><MSHelp:RLTitle Title="DbChannel Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DbChannel" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelMethodsTopic" /><MSHelp:Keyword Index="K" Term="DbChannel class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel Methods </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_RefreshMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_RefreshMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.RefreshMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle

Title="RefreshMultiple
Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.RefreshMultiple Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.RefreshMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Store the key/data pair to which the cursor refers and as many duplicate data items that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input
type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Cursor<span
class="cs">..::<span
class="nu">.RefreshMultiple Method (Int32, LockingInfo)</td></tr><tr
id="headerTableRow3"><td align="left">Cursor Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryDatabaseConfig Class</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_SecondaryDatabaseConfig" /><meta name="guid"
content="T_BerkeleyDB_SecondaryDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryDatabaseConfig Class"
/><MSHelp:RLTitle Title="SecondaryDatabaseConfig
Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryDatabaseConfig"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassTopic"
/><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="SecondaryDatabaseConfig class, about SecondaryDatabaseConfig class" /><MSHelp:Keyword Index="F"
Term="SecondaryDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HashDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HashDatabase" /><MSHelp:TOCTitle Title="HashDatabase Members" /><MSHelp:RLTitle Title="HashDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="HashDatabase class" /><MSHelp:Keyword Index="K" Term="HashDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashDatabase class" /><MSHelp:Keyword Index="F" Term="HashDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase Members</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_HashDatabase.htm">HashDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_QueueStats" /><meta name="guid" content="T_BerkeleyDB_QueueStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.QueueStats" /><MSHelp:TOCTitle Title="QueueStats Class" /><MSHelp:RLTitle Title="QueueStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.QueueStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassTopic" /><MSHelp:Keyword Index="K" Term="QueueStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.QueueStats class" /><MSHelp:Keyword Index="K" Term="QueueStats class, about QueueStats class" /><MSHelp:Keyword Index="F" Term="QueueStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about a QueueDatabase" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetMaxSequentialWrites Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MPoolConfig_SetMaxSequentialWrites" /><meta name="guid" content="M_BerkeleyDB_MPoolConfig_SetMaxSequentialWrites" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MPoolConfig.SetMaxSequentialWrites(System.Int32,System.UInt32)" /><MSHelp:TOCTitle Title="SetMaxSequentialWrites Method " /><MSHelp:RLTitle Title="MPoolConfig.SetMaxSequentialWrites Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MPoolConfig.SetMaxSequentialWrites(System.Int32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassSetMaxSequentialWritesTopic" /><MSHelp:Keyword Index="K" Term="SetMaxSequentialWrites method" /><MSHelp:Keyword Index="K" Term="MPoolConfig.SetMaxSequentialWrites method" /><MSHelp:Keyword Index="F" Term="SetMaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="MPoolConfig.SetMaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.SetMaxSequentialWrites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.SetMaxSequentialWrites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Limit the number of sequential write operations scheduled by the library when flushing dirty pages from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.SetMaxSequentialWrites Method </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_HashDatabase_GetBoth" /><meta name="guid"
content="Overload_BerkeleyDB_HashDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method "
/><MSHelp:RLTitle Title="HashDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.HashDatabase.GetBoth" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth
method" /><MSHelp:Keyword Index="K" Term="HashDatabase.GetBoth method" /><MSHelp:Keyword
Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="HashDatabase.GetBoth"
/><MSHelp:Keyword
Index="F" Term="BerkeleyDB.HashDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
 style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
 id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class <a href="#seeAlsoToggle"
 onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
 src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HashDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:TOCTitle Title="HashDatabaseConfig Members" /><MSHelp:RLTitle Title="HashDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBHashDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"

value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabaseConfig_SetForeignKeyConstraint" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabaseConfig_SetForeignKeyConstraint" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:TOCTitle Title="SetForeignKeyConstraint Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.SetForeignKeyConstraint Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassSetForeignKeyConstraintTopic" /><MSHelp:Keyword Index="K" Term="SetForeignKeyConstraint method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.SetForeignKeyConstraint method" /><MSHelp:Keyword Index="F" Term="SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryBTreeDatabaseConfig<span
class="cs">..::<span
class="nu">.SetForeignKeyConstraint Method </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryBTreeDatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MissedPages
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_ReplicationStats_MissedPages" /><meta name="guid"

content="P_BerkeleyDB_ReplicationStats_MissedPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MissedPages" /><MSHelp:TOCTitle Title="MissedPages Property " /><MSHelp:RLTitle Title="ReplicationStats.MissedPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MissedPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMissedPagesTopic" /><MSHelp:Keyword Index="K" Term="MissedPages property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MissedPages property" /><MSHelp:Keyword Index="F" Term="MissedPages" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MissedPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MissedPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MissedPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MissedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages missed and requested." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MissedPages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HotbackupInProgress Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_HotbackupInProgress" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_HotbackupInProgress" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.HotbackupInProgress" /><MSHelp:TOCTitle Title="HotbackupInProgress Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.HotbackupInProgress Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.HotbackupInProgress" />
<MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassHotbackupInProgressTopic" /><MSHelp:Keyword Index="K" Term="HotbackupInProgress field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.HotbackupInProgress field" /><MSHelp:Keyword Index="F" Term="HotbackupInProgress" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.HotbackupInProgress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.HotbackupInProgress" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.HotbackupInProgress" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set a flag in the environment indicating that a hot backup is in progress." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.HotbackupInProgress Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Append"

/><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Append" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Append" /><MSHelp:TOCTitle Title="Append Method " /><MSHelp:RLTitle Title="QueueDatabase.Append Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Append" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassAppendTopic" /><MSHelp:Keyword Index="K" Term="Append method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Append method" /><MSHelp:Keyword Index="F" Term="Append" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Append" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Append Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:TOCTitle Title="MovePrevUnique Method " /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and store the secondary key and primary key/dat ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryCursor<span
class="cs">..::<span
class="nu">.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryCursor Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>CacheSize Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_SequenceConfig_CacheSize"
/><meta name="guid" content="P_BerkeleyDB_SequenceConfig_CacheSize" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.SequenceConfig.CacheSize" /><MSHelp:TOCTitle Title="CacheSize
Property " /><MSHelp:RLTitle Title="SequenceConfig.CacheSize Property (BerkeleyDB)" /><MSHelp:Keyword

Index="A" Term="P:BerkeleyDB.SequenceConfig.CacheSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassCacheSizeTopic" /><MSHelp:Keyword Index="K" Term="CacheSize property" /><MSHelp:Keyword Index="K" Term="SequenceConfig.CacheSize property" /><MSHelp:Keyword Index="F" Term="CacheSize" /><MSHelp:Keyword Index="F" Term="SequenceConfig.CacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.CacheSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.CacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.get_CacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.set_CacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of elements cached by a sequence handle." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">SequenceConfig..::.CacheSize Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Equal Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_KeyRange_Equal" /><meta name="guid" content="P_BerkeleyDB_KeyRange_Equal" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.KeyRange.Equal" /><MSHelp:TOCTitle Title="Equal Property " /><MSHelp:RLTitle Title="KeyRange.Equal Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.KeyRange.Equal" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyRangeClassEqualTopic" /><MSHelp:Keyword Index="K" Term="Equal property" /><MSHelp:Keyword Index="K" Term="KeyRange.Equal property" /><MSHelp:Keyword Index="F" Term="Equal" /><MSHelp:Keyword Index="F" Term="KeyRange.Equal" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyRange.Equal" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange.Equal" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange.get_Equal" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A value between 0 and 1, the proportion of keys equal to the specified key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyRange..::.Equal Property </td></tr><tr
id="headerTableRow3"><td align="left">KeyRange Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FillFactor Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabaseConfig_FillFactor" /><meta name="guid" content="P_BerkeleyDB_HashDatabaseConfig_FillFactor" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabaseConfig.FillFactor" /><MSHelp:TOCTitle Title="FillFactor Property " /><MSHelp:RLTitle Title="HashDatabaseConfig.FillFactor Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabaseConfig.FillFactor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassFillFactorTopic" /><MSHelp:Keyword Index="K" Term="FillFactor
property" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.FillFactor property" /><MSHelp:Keyword Index="F" Term="FillFactor" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.FillFactor" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.HashDatabaseConfig.FillFactor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.FillFactor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.get_FillFactor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.set_FillFactor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The desired density within the hash table. If no value is specified, the
fill factor will be selected dynamically as pages are filled." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..::.FillFactor Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AutoRemove Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LogConfig_AutoRemove" /><meta name="guid" content="F_BerkeleyDB_LogConfig_AutoRemove"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LogConfig.AutoRemove" /><MSHelp:TOCTitle Title="AutoRemove Field" /><MSHelp:RLTitle Title="LogConfig.AutoRemove Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LogConfig.AutoRemove" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassAutoRemoveTopic" /><MSHelp:Keyword Index="K" Term="AutoRemove field" /><MSHelp:Keyword Index="K" Term="LogConfig.AutoRemove field" /><MSHelp:Keyword Index="F" Term="AutoRemove" /><MSHelp:Keyword Index="F" Term="LogConfig.AutoRemove" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.AutoRemove" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.AutoRemove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will automatically remove log files that are no longer needed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.AutoRemove Field</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintSubsystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintSubsystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintSubsystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:TOCTitle Title="PrintSubsystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintSubsystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintSubsystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintSubsystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupOptions Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BackupOptions" /><meta name="guid" content="T_BerkeleyDB_BackupOptions" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BackupOptions" /><MSHelp:TOCTitle Title="BackupOptions Class" /><MSHelp:RLTitle Title="BackupOptions Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BackupOptions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassTopic" /><MSHelp:Keyword Index="K" Term="BackupOptions class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BackupOptions class" /><MSHelp:Keyword Index="K" Term="BackupOptions class, about BackupOptions class" /><MSHelp:Keyword Index="F" Term="BackupOptions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration parameters for hot backup." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextItem Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_MoveNextItem" /><meta name="guid" content="M_BerkeleyDB_JoinCursor_MoveNextItem" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:TOCTitle Title="MoveNextItem Method " /><MSHelp:RLTitle Title="JoinCursor.MoveNextItem Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Iterate over the values associated with the keys to which each passed to was initialized. Any data value that appears in all s is then stored in Current.Key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.MoveNextItem Method </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Dispose" /><meta name="guid" content="M_BerkeleyDB_Sequence_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="Sequence.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="Sequence.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="Sequence.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.Sequence.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by this object, and close the sequence if it's still open." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_UNAVAIL Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_UNAVAIL" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_UNAVAIL" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_UNAVAIL" /><MSHelp:TOCTitle Title="DB_REP_UNAVAIL Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_UNAVAIL Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_UNAVAIL" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_UNAVAILTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_UNAVAIL field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_UNAVAIL field" /><MSHelp:Keyword Index="F" Term="DB_REP_UNAVAIL" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_UNAVAIL" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_UNAVAIL" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_UNAVAIL" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Site cannot currently be reached." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_UNAVAIL Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="BTreeDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>PrintReplicationSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintReplicationSystemStats_1" /><meta
name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintReplicationSystemStats_1"
/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats(System.Boolean,System.Boolean)"
/><MSHelp:TOCTitle Title="PrintReplicationSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle
Title="DatabaseEnvironment.PrintReplicationSystemStats Method (Boolean, Boolean) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats(System.Boolean,System.Boolean)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the replication subsystem
statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintReplicationSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ByteOrder Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ByteOrder" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ByteOrder" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ByteOrder" /><MSHelp:TOCTitle Title="ByteOrder Members" /><MSHelp:RLTitle Title="ByteOrder Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ByteOrder" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBByteOrderMembersTopic" /><MSHelp:Keyword Index="K" Term="ByteOrder class" /><MSHelp:Keyword Index="K" Term="ByteOrder class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ByteOrder class" /><MSHelp:Keyword Index="F" Term="ByteOrder" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ByteOrder" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder Members</td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class Methods Fields See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HashStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HashStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HashStats" /><MSHelp:TOCTitle Title="HashStats Members" /><MSHelp:RLTitle Title="HashStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HashStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="HashStats class" /><MSHelp:Keyword Index="K" Term="HashStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashStats class" /><MSHelp:Keyword Index="F" Term="HashStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats Members</td></tr><tr id="headerTableRow3"><td align="left">HashStats Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_QueueDatabase" /><meta name="guid" content="T_BerkeleyDB_QueueDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.QueueDatabase" /><MSHelp:TOCTitle Title="QueueDatabase Class" /><MSHelp:RLTitle Title="QueueDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.QueueDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabase

class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.QueueDatabase class" /><MSHelp:Keyword Index="K" Term="QueueDatabase class, about QueueDatabase class" /><MSHelp:Keyword Index="F" Term="QueueDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a QueueDatabase. The Queue format supports fast access to fixed-length records accessed sequentially or by logical record number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members

See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Put" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Put" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Put" /><MSHelp:TOCTitle Title="Put Method " /><MSHelp:RLTitle Title="HashDatabase.Put Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Put" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassPutTopic" /><MSHelp:Keyword Index="K" Term="Put method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Put method" /><MSHelp:Keyword Index="F" Term="Put" /><MSHelp:Keyword Index="F" Term="HashDatabase.Put" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
 style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Put Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class <a href="#seeAlsoToggle"
 onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoDuplicate Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script
 type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_PutNoDuplicate" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_PutNoDuplicate" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="PutNoDuplicate Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle

Title="BTreeDatabase.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BTreeDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.PutNoDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data
pair in the database only if it does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeDatabase.<span
class="vb">.::.PutNoDuplicate Method
(DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_BTreeDatabase.htm">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MoveNextUnique" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MoveNextUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:TOCTitle Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMoveNextUniqueTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUnique method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MoveNextUnique method" /><MSHelp:Keyword Index="F" Term="MoveNextUnique" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MoveNextUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryBTreeDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryBTreeDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Open Method
(String, SecondaryBTreeDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryBTreeDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">SecondaryBTreeDatabase..::.Open Method (String, SecondaryBTreeDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnSnapshot Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnSnapshot" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnSnapshot" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnSnapshot" /><MSHelp:TOCTitle Title="TxnSnapshot Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TxnSnapshot Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnSnapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTxnSnapshotTopic" /><MSHelp:Keyword Index="K" Term="TxnSnapshot field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TxnSnapshot field" /><MSHelp:Keyword Index="F" Term="TxnSnapshot" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TxnSnapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TxnSnapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TxnSnapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, all transactions in the environment will be started as if were passed to , and all non-transactional cursors will be opened as if were passed to ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TxnSnapshot Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactData Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_CompactData" /><meta name="guid" content="Methods_T_BerkeleyDB_CompactData" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.CompactData" /><MSHelp:TOCTitle Title="CompactData Methods " /><MSHelp:RLTitle Title="CompactData Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.CompactData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataMethodsTopic" /><MSHelp:Keyword Index="K" Term="CompactData class,

methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited

Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData Methods </td></tr><tr id="headerTableRow3"><td align="left">CompactData Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNext_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNext_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNext(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNext Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNext Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNext(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair in . In the presence of duplicate key val ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNext Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_ReplicationHostAddress__ctor" /><meta name="guid" content="Overload_BerkeleyDB_ReplicationHostAddress__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.ReplicationHostAddress.#ctor" /><MSHelp:TOCTitle Title="ReplicationHostAddress Constructor " /><MSHelp:RLTitle Title="ReplicationHostAddress Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.ReplicationHostAddress.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressClassctorTopic" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress class, constructor" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress.ReplicationHostAddress constructor" /><MSHelp:Keyword Index="F"

Term="ReplicationHostAddress" /><MSHelp:Keyword Index="F"
Term="ReplicationHostAddress.ReplicationHostAddress" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationHostAddress.ReplicationHostAddress" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"

for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress Constructor </td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" />
<META NAME="save" CONTENT="history" /><title>Compact Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Compact" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Compact" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Compact" />
<MSHelp:TOCTitle Title="Compact Method " /><MSHelp:RLTitle Title="HashDatabase.Compact Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Compact" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassCompactTopic" /><MSHelp:Keyword Index="K" Term="Compact method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Compact method" /><MSHelp:Keyword Index="F" Term="Compact" /><MSHelp:Keyword Index="F" Term="HashDatabase.Compact" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" />
 <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Compact Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MinKey Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_MinKey" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_MinKey" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.MinKey" /><MSHelp:TOCTitle Title="MinKey Property " /><MSHelp:RLTitle Title="BTreeStats.MinKey Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.MinKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassMinKeyTopic" /><MSHelp:Keyword Index="K" Term="MinKey property" /><MSHelp:Keyword Index="K" Term="BTreeStats.MinKey property" /><MSHelp:Keyword Index="F" Term="MinKey" /><MSHelp:Keyword Index="F" Term="BTreeStats.MinKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.MinKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.MinKey" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_MinKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Minkey value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.MinKey Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IBackup Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_IBackup" /><meta name="guid" content="AllMembers_T_BerkeleyDB_IBackup" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.IBackup" /><MSHelp:TOCTitle Title="IBackup Members" /><MSHelp:RLTitle Title="IBackup Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.IBackup" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIBackupMembersTopic" /><MSHelp:Keyword Index="K" Term="IBackup interface" /><MSHelp:Keyword Index="K" Term="IBackup interface, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.IBackup interface" /><MSHelp:Keyword Index="F" Term="IBackup" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.IBackup" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover

image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">IBackup Members</td></tr><tr id="headerTableRow3"><td align="left">IBackup Interface Methods See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique_2" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntr
y,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevUnique Method
(DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle
Title="SecondaryCursor.MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry
,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized,
MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and
store the secondary key and primary key/dat ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitThreadCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitThreadCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitThreadCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitThreadCount" /><MSHelp:TOCTitle Title="InitThreadCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitThreadCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitThreadCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitThreadCountTopic" /><MSHelp:Keyword Index="K" Term="InitThreadCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitThreadCount property" /><MSHelp:Keyword Index="F" Term="InitThreadCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitThreadCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitThreadCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitThreadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitThreadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitThreadCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of thread objects allocated when the environment is created"

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitThreadCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META

NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SequenceStats" /><meta name="guid" content="Properties_T_BerkeleyDB_SequenceStats"
/><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SequenceStats" /><MSHelp:TOCTitle Title="SequenceStats Properties " /><MSHelp:RLTitle Title="SequenceStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SequenceStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="SequenceStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">SequenceStats Properties </td></tr><tr
id="headerTableRow3"><td align="left">SequenceStats Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNextMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MoveNextMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.RecnoCursor.MoveNextMultiple" /><MSHelp:TOCTitle Title="MoveNextMultiple
Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNextMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNextMultiple"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveNextMultipleTopic"
/><MSHelp:Keyword Index="K" Term="MoveNextMultiple method" /><MSHelp:Keyword Index="K"
Term="RecnoCursor.MoveNextMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextMultiple"
/><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveNextMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoCursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RecnoCursor<span
class="cs">..::<span
class="nu">.MoveNextMultiple Method </td></tr><tr id="headerTableRow3"><td
align="left">RecnoCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Delete" /><meta
name="guid" content="Overload_BerkeleyDB_Database_Delete" /><xml><MSHelp:Attr Name="AssetID"

Value="Overload:BerkeleyDB.Database.Delete" /><MSHelp:TOCTitle Title="Delete Method "
/><MSHelp:RLTitle Title="Database.Delete Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.Database.Delete" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method"
/><MSHelp:Keyword Index="K" Term="Database.Delete method" /><MSHelp:Keyword Index="F"
Term="Delete" /><MSHelp:Keyword Index="F" Term="Database.Delete" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Database.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">Database..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorPrefix Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_ErrorPrefix" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_ErrorPrefix" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.ErrorPrefix" /><MSHelp:TOCTitle Title="ErrorPrefix Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.ErrorPrefix Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.ErrorPrefix" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassErrorPrefixTopic" /><MSHelp:Keyword Index="K" Term="ErrorPrefix property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ErrorPrefix property" /><MSHelp:Keyword Index="F" Term="ErrorPrefix" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ErrorPrefix" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ErrorPrefix" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ErrorPrefix" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_ErrorPrefix" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_ErrorPrefix" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The prefix string that appears before error messages issued by Berkeley DB." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ErrorPrefix Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseExpiredException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LeaseExpiredException" /><meta name="guid" content="T_BerkeleyDB_LeaseExpiredException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LeaseExpiredException" /><MSHelp:TOCTitle Title="LeaseExpiredException Class" /><MSHelp:RLTitle Title="LeaseExpiredException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LeaseExpiredException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLeaseExpiredExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LeaseExpiredException class" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException class, about LeaseExpiredException class" /><MSHelp:Keyword Index="F" Term="LeaseExpiredException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LeaseExpiredException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LeaseExpiredException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The site's replication master lease has expired." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LeaseExpiredException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Checkpoint Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_Checkpoint" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_Checkpoint" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:TOCTitle Title="Checkpoint Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Checkpoint Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassCheckpointTopic" /><MSHelp:Keyword Index="K" Term="Checkpoint method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Checkpoint method" /><MSHelp:Keyword Index="F" Term="Checkpoint" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Checkpoint" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Checkpoint Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxObjects Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxObjects" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxObjects" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxObjects" /><MSHelp:TOCTitle Title="MaxObjects Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxObjects Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxObjects" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxObjectsTopic" /><MSHelp:Keyword Index="K" Term="MaxObjects property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxObjects
property" /><MSHelp:Keyword Index="F" Term="MaxObjects" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxObjects" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxObjects" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxObjects" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxObjects" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxObjects" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum number of locked objects" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxObjects Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyExistException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_KeyExistException__ctor" /><meta name="guid" content="M_BerkeleyDB_KeyExistException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.KeyExistException.#ctor" /><MSHelp:TOCTitle Title="KeyExistException Constructor " /><MSHelp:RLTitle Title="KeyExistException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.KeyExistException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyExistExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="KeyExistException class, constructor" /><MSHelp:Keyword Index="K" Term="KeyExistException.KeyExistException constructor" /><MSHelp:Keyword Index="F" Term="KeyExistException" /><MSHelp:Keyword Index="F" Term="KeyExistException.KeyExistException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyExistException.KeyExistException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyExistException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the KeyExistException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyExistException Constructor </td></tr><tr id="headerTableRow3"><td align="left">KeyExistException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HashDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_HashDatabaseConfig"

/><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:TOCTitle Title="HashDatabaseConfig Methods " /><MSHelp:RLTitle Title="HashDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div

id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreeThreaded Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_FreeThreaded" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_FreeThreaded" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.FreeThreaded" /><MSHelp:TOCTitle Title="FreeThreaded Field" /><MSHelp:RLTitle Title="DatabaseConfig.FreeThreaded Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.FreeThreaded" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassFreeThreadedTopic" /><MSHelp:Keyword Index="K" Term="FreeThreaded field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.FreeThreaded field" /><MSHelp:Keyword Index="F" Term="FreeThreaded" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.FreeThreaded" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.FreeThreaded" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.FreeThreaded" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Cause the database object to be free-threaded; that is, concurrently usable by multiple threads in the address space." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.FreeThreaded Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nPartitions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_nPartitions" /><meta name="guid" content="P_BerkeleyDB_LockStats_nPartitions" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.LockStats.nPartitions"
/><MSHelp:TOCTitle Title="nPartitions Property " /><MSHelp:RLTitle Title="LockStats.nPartitions Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.nPartitions"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassnPartitionsTopic" /><MSHelp:Keyword
Index="K" Term="nPartitions property" /><MSHelp:Keyword Index="K" Term="LockStats.nPartitions property"
/><MSHelp:Keyword Index="F" Term="nPartitions" /><MSHelp:Keyword Index="F"
Term="LockStats.nPartitions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.nPartitions"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.nPartitions"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_nPartitions" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="number of partitions." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">LockStats..::.nPartitions Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSetMemoryLimit Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RegionSetMemoryLimit" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RegionSetMemoryLimit" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RegionSetMemoryLimit(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="RegionSetMemoryLimit Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RegionSetMemoryLimit Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RegionSetMemoryLimit(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRegionSetMemoryLimitTopic" /><MSHelp:Keyword Index="K" Term="RegionSetMemoryLimit method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RegionSetMemoryLimit method" /><MSHelp:Keyword Index="F" Term="RegionSetMemoryLimit" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RegionSetMemoryLimit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RegionSetMemoryLimit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RegionSetMemoryLimit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of memory to be used by shared structures in the main environment region. These are structures other than mutexes and the page cache (memory pool)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RegionSetMemoryLimit Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_VERSION_MISMATCH Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_VERSION_MISMATCH" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_VERSION_MISMATCH" /><xml><MSHelp:Attr Name="AssetID"

Value="F:BerkeleyDB.ErrorCodes.DB_VERSION_MISMATCH" /><MSHelp:TOCTitle Title="DB_VERSION_MISMATCH Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_VERSION_MISMATCH Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_VERSION_MISMATCH" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_VERSION_MISMATCHTopic" /><MSHelp:Keyword Index="K" Term="DB_VERSION_MISMATCH field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_VERSION_MISMATCH field" /><MSHelp:Keyword Index="F" Term="DB_VERSION_MISMATCH" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_VERSION_MISMATCH" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_VERSION_MISMATCH" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_VERSION_MISMATCH" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Environment version mismatch." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">ErrorCodes<span
class="languageSpecificText">..<span
class="cpp">::.DB_VERSION_MISMATCH Field</td></tr><tr
id="headerTableRow3"><td align="left">ErrorCodes Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MultipleDatabaseEntry Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="AllMembers_T_BerkeleyDB_MultipleDatabaseEntry" /><meta name="guid"
content="AllMembers_T_BerkeleyDB_MultipleDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID"
Value="AllMembers.T:BerkeleyDB.MultipleDatabaseEntry"
/><MSHelp:TOCTitle Title="MultipleDatabaseEntry Members" /><MSHelp:RLTitle
Title="MultipleDatabaseEntry Members (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="AllMembers.T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMultipleDatabaseEntryMembersTopic" /><MSHelp:Keyword Index="K"
Term="MultipleDatabaseEntry class" /><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry class, all
members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MultipleDatabaseEntry class"
/><MSHelp:Keyword Index="F" Term="MultipleDatabaseEntry" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Members</td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class Constructors Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AutoInit

Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_AutoInit" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_AutoInit" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.AutoInit" /><MSHelp:TOCTitle Title="AutoInit Field" /><MSHelp:RLTitle Title="ReplicationConfig.AutoInit Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.AutoInit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassAutoInitTopic" /><MSHelp:Keyword Index="K" Term="AutoInit field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.AutoInit field" /><MSHelp:Keyword Index="F" Term="AutoInit" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.AutoInit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.AutoInit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.AutoInit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the replication master will automatically re-initialize outdated clients (defaults to true)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.AutoInit Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_Sequence" /><meta name="guid" content="T_BerkeleyDB_Sequence" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Sequence" /><MSHelp:TOCTitle Title="Sequence Class" /><MSHelp:RLTitle Title="Sequence Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.Sequence" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassTopic" /><MSHelp:Keyword Index="K" Term="Sequence class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Sequence class" /><MSHelp:Keyword Index="K" Term="Sequence class, about Sequence class" /><MSHelp:Keyword Index="F" Term="Sequence" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class that provides an arbitrary number of persistent objects that return an increasing or decreasing sequence of integers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence
Class</td></tr><tr id="headerTableRow3"><td align="left"><a
href="AllMembers_T_BerkeleyDB_Sequence.htm">Members <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>BufferCopiesInCache Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ActiveTransaction_BufferCopiesInCache" /><meta name="guid"
content="P_BerkeleyDB_ActiveTransaction_BufferCopiesInCache" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ActiveTransaction.BufferCopiesInCache" /><MSHelp:TOCTitle
Title="BufferCopiesInCache Property " /><MSHelp:RLTitle Title="ActiveTransaction.BufferCopiesInCache
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.ActiveTransaction.BufferCopiesInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassBufferCopiesInCacheTopic" /><MSHelp:Keyword Index="K" Term="BufferCopiesInCache property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.BufferCopiesInCache property" /><MSHelp:Keyword Index="F" Term="BufferCopiesInCache" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.BufferCopiesInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.BufferCopiesInCache" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.BufferCopiesInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_BufferCopiesInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of MVCC buffer copies created by this transaction that remain in cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction..::.BufferCopiesInCache Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_KEYEMPTY Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_KEYEMPTY" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_KEYEMPTY" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_KEYEMPTY" /><MSHelp:TOCTitle Title="DB_KEYEMPTY Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_KEYEMPTY Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_KEYEMPTY" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_KEYEMPTYTopic" /><MSHelp:Keyword Index="K" Term="DB_KEYEMPTY field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_KEYEMPTY field" /><MSHelp:Keyword Index="F" Term="DB_KEYEMPTY" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_KEYEMPTY" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_KEYEMPTY" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_KEYEMPTY" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Key/data deleted or never created." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_KEYEMPTY Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadName Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_ThreadName" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_ThreadName" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.ThreadName" /><MSHelp:TOCTitle Title="ThreadName Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.ThreadName Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.ThreadName" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassThreadNameTopic" /><MSHelp:Keyword Index="K"

Term="ThreadName field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.ThreadName field" /><MSHelp:Keyword Index="F" Term="ThreadName" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.ThreadName" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.ThreadName" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.ThreadName" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A delegate that formats a process ID and thread ID identifier pair." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.ThreadName

Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_IBackup_Open" /><meta name="guid" content="M_BerkeleyDB_IBackup_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.IBackup.Open(System.String,System.String)" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="IBackup.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.IBackup.Open(System.String,System.String)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIBackupClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="IBackup.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="IBackup.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.IBackup.Open" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.IBackup.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Called when a target location is opened during a backup. This method should do whatever is necessary to prepare the backup destination for writing the data." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:

none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">IBackup..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">IBackup Interface See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicate method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextDuplicate method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor.<span

class="vb">.::.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThawedBuffers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_ThawedBuffers" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_ThawedBuffers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.ThawedBuffers" /><MSHelp:TOCTitle Title="ThawedBuffers Property " /><MSHelp:RLTitle Title="MPoolStats.ThawedBuffers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.ThawedBuffers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassThawedBuffersTopic" /><MSHelp:Keyword Index="K" Term="ThawedBuffers property" /><MSHelp:Keyword Index="K" Term="MPoolStats.ThawedBuffers property" /><MSHelp:Keyword Index="F" Term="ThawedBuffers" /><MSHelp:Keyword Index="F" Term="MPoolStats.ThawedBuffers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.ThawedBuffers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.ThawedBuffers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_ThawedBuffers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Buffers thawed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.ThawedBuffers Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UsingLogging Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UsingLogging" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UsingLogging" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UsingLogging" /><MSHelp:TOCTitle Title="UsingLogging Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UsingLogging Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UsingLogging" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUsingLoggingTopic" /><MSHelp:Keyword Index="K" Term="UsingLogging property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UsingLogging property" /><MSHelp:Keyword Index="F" Term="UsingLogging" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UsingLogging" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.DatabaseEnvironment.UsingLogging" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UsingLogging" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UsingLogging" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the logging subsystem was initialized." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UsingLogging Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LSN Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LSN" /><meta name="guid" content="T_BerkeleyDB_LSN" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LSN" /><MSHelp:TOCTitle Title="LSN Class" /><MSHelp:RLTitle Title="LSN Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LSN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNClassTopic" /><MSHelp:Keyword Index="K" Term="LSN class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LSN class" /><MSHelp:Keyword Index="K" Term="LSN class, about LSN class" /><MSHelp:Keyword Index="F" Term="LSN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LSN" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LSN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A log sequence number, which specifies a unique location in a log file." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HashDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_HashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HashDatabase" /><MSHelp:TOCTitle Title="HashDatabase Methods " /><MSHelp:RLTitle Title="HashDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="HashDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseReplication Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseReplication" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseReplication" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseReplication" /><MSHelp:TOCTitle Title="UseReplication
Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseReplication Field (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseReplication"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseReplicationTopic"
/><MSHelp:Keyword Index="K" Term="UseReplication field" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.UseReplication field" /><MSHelp:Keyword Index="F"
Term="UseReplication" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.UseReplication"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.UseReplication"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.UseReplication" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="If true, initialize the replication subsystem."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseReplication Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveNextMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextMultipleKey method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this,
'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>BadSecondaryException Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="AllMembers_T_BerkeleyDB_BadSecondaryException" /><meta name="guid"
content="AllMembers_T_BerkeleyDB_BadSecondaryException" /><xml><MSHelp:Attr Name="AssetID"
Value="AllMembers.T:BerkeleyDB.BadSecondaryException" /><MSHelp:TOCTitle
Title="BadSecondaryException Members" /><MSHelp:RLTitle Title="BadSecondaryException Members
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BadSecondaryException"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBadSecondaryExceptionMembersTopic"
/><MSHelp:Keyword Index="K" Term="BadSecondaryException class" /><MSHelp:Keyword Index="K"
Term="BadSecondaryException class, all members" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.BadSecondaryException class" /><MSHelp:Keyword Index="F"
Term="BadSecondaryException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BadSecondaryException"
/><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BadSecondaryException Members</td></tr><tr id="headerTableRow3"><td align="left">BadSecondaryException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionPriority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionPriority" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionPriority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionPriority" /><MSHelp:TOCTitle Title="ElectionPriority Property "

/><MSHelp:RLTitle Title="ReplicationStats.ElectionPriority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionPriority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionPriorityTopic" /><MSHelp:Keyword Index="K" Term="ElectionPriority
 property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionPriority property" /><MSHelp:Keyword Index="F" Term="ElectionPriority" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionPriority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionPriority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionPriority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionPriority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current election priority." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
 id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"
 cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
 style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley

DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionPriority Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseExpiredException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LeaseExpiredException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LeaseExpiredException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:TOCTitle Title="LeaseExpiredException Members" /><MSHelp:RLTitle Title="LeaseExpiredException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLeaseExpiredExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException class" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LeaseExpiredException class" /><MSHelp:Keyword Index="F" Term="LeaseExpiredException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LeaseExpiredException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LeaseExpiredException Members</td></tr><tr id="headerTableRow3"><td align="left">LeaseExpiredException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (CursorConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link

rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Cursor_2" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Cursor_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor Method (CursorConfig, Transaction)" /><MSHelp:RLTitle Title="HashDatabase.Cursor Method (CursorConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HashDatabase.<span
class="vb">.::.Cursor Method
(CursorConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashDatabase.htm">HashDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryQueueDatabase Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryQueueDatabase"
/><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryQueueDatabase" /><xml><MSHelp:Attr
Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:TOCTitle
Title="SecondaryQueueDatabase Members" /><MSHelp:RLTitle Title="SecondaryQueueDatabase Members
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryQueueDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseMembersTopic"
/><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase class" /><MSHelp:Keyword Index="K"
Term="SecondaryQueueDatabase class, all members" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryQueueDatabase class" /><MSHelp:Keyword Index="F"
Term="SecondaryQueueDatabase" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryQueueDatabase"
/><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none;

height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevUnique_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevUnique(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevUnique Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevUnique Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevUnique(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and store the secondary key and primary key/dat ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryCursor<span
class="cs">..::<span
class="nu">.MovePrevUnique Method (LockingInfo)</td></tr><tr
id="headerTableRow3"><td align="left">SecondaryCursor
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxMutexes
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxMutexes" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_MaxMutexes" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.MaxMutexes" /><MSHelp:TOCTitle Title="MaxMutexes Property "
/><MSHelp:RLTitle Title="DatabaseEnvironment.MaxMutexes Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxMutexes" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxMutexesTopic" /><MSHelp:Keyword
Index="K" Term="MaxMutexes property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.MaxMutexes property" /><MSHelp:Keyword Index="F" Term="MaxMutexes"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxMutexes" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.MaxMutexes" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.MaxMutexes" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_MaxMutexes" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.set_MaxMutexes" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The total number
of mutexes allocated"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxMutexes Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method (String, DatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Salvage" /><meta name="guid" content="M_BerkeleyDB_Database_Salvage" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:TOCTitle Title="Salvage Method (String, DatabaseConfig)" /><MSHelp:RLTitle Title="Database.Salvage Method (String, DatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Salvage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Write the key/data pairs from all databases in the file to . Key values are written for Btree, Hash and Queue databases, but not for Recno databases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"

cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Salvage Method (String, DatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_PageSize" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="BTreeStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="BTreeStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="BTreeStats.PageSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Stats" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="BTreeDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextDuplicateMultiple
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNextDuplicateMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MoveNextDuplicateMultiple" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextDuplicateMultiple"
/><MSHelp:TOCTitle Title="MoveNextDuplicateMultiple Method " /><MSHelp:RLTitle
Title="RecnoCursor.MoveNextDuplicateMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.RecnoCursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoCursorClassMoveNextDuplicateMultipleTopic" /><MSHelp:Keyword Index="K"
Term="MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="K"
Term="RecnoCursor.MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="F"
Term="MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F"
Term="RecnoCursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoCursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveNextDuplicateMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassPrintStatsTopic"

/><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input

id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verbose Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_Verbose" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_Verbose" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.Verbose" /><MSHelp:TOCTitle Title="Verbose Property " /><MSHelp:RLTitle Title="LogVerifyConfig.Verbose Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.Verbose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassVerboseTopic" /><MSHelp:Keyword Index="K" Term="Verbose property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.Verbose property" /><MSHelp:Keyword Index="F" Term="Verbose" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.Verbose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.Verbose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.Verbose" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_Verbose" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_Verbose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether output verbose information." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"

title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">LogVerifyConfig.<span
class="vb">.::.Verbose Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LogVerifyConfig.htm">LogVerifyConfig Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseType
Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DatabaseType" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DatabaseType" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DatabaseType" /><MSHelp:TOCTitle Title="DatabaseType Members" /><MSHelp:RLTitle Title="DatabaseType Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DatabaseType" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeMembersTopic" /><MSHelp:Keyword Index="K" Term="DatabaseType class" /><MSHelp:Keyword
Index="K" Term="DatabaseType class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseType class" /><MSHelp:Keyword Index="F" Term="DatabaseType" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage" src="../icons/dropdown.gif"
/> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType Members</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType
Class Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockObjectCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockingConfig_InitLockObjectCount" /><meta name="guid" content="P_BerkeleyDB_LockingConfig_InitLockObjectCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockingConfig.InitLockObjectCount" /><MSHelp:TOCTitle Title="InitLockObjectCount Property " /><MSHelp:RLTitle Title="LockingConfig.InitLockObjectCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockingConfig.InitLockObjectCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigClassInitLockObjectCountTopic" /><MSHelp:Keyword Index="K" Term="InitLockObjectCount property" /><MSHelp:Keyword Index="K" Term="LockingConfig.InitLockObjectCount property" /><MSHelp:Keyword Index="F" Term="InitLockObjectCount" /><MSHelp:Keyword Index="F" Term="LockingConfig.InitLockObjectCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.InitLockObjectCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.InitLockObjectCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.get_InitLockObjectCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.set_InitLockObjectCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of lock objects created by the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.InitLockObjectCount Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitMutexes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexConfig_InitMutexes" /><meta name="guid" content="P_BerkeleyDB_MutexConfig_InitMutexes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexConfig.InitMutexes" /><MSHelp:TOCTitle Title="InitMutexes Property " /><MSHelp:RLTitle Title="MutexConfig.InitMutexes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexConfig.InitMutexes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigClassInitMutexesTopic" /><MSHelp:Keyword Index="K" Term="InitMutexes property" /><MSHelp:Keyword Index="K" Term="MutexConfig.InitMutexes property" /><MSHelp:Keyword Index="F" Term="InitMutexes" /><MSHelp:Keyword Index="F" Term="MutexConfig.InitMutexes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig.InitMutexes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.InitMutexes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.get_InitMutexes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.set_InitMutexes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of mutexes to allocate." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MutexConfig<span
class="cs">..::<span
class="nu">.InitMutexes Property </td></tr><tr id="headerTableRow3"><td
align="left">MutexConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepRetransmissionRequestMax Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepRetransmissionRequestMax" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepRetransmissionRequestMax" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMax"
/><MSHelp:TOCTitle Title="RepRetransmissionRequestMax Property " /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepRetransmissionRequestMax Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMax" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepRetransmissionRequestMaxTopic"
/><MSHelp:Keyword Index="K" Term="RepRetransmissionRequestMax property" /><MSHelp:Keyword
Index="K" Term="DatabaseEnvironment.RepRetransmissionRequestMax property" /><MSHelp:Keyword
Index="F" Term="RepRetransmissionRequestMax" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepRetransmissionRequestMax" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMax" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMax" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepRetransmissionRequestMax"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr

Name="Abstract" Value="The maximum number of microseconds a client waits before requesting retransmission." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepRetransmissionRequestMax Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AwaitedPage Property </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_AwaitedPage" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_AwaitedPage" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.AwaitedPage" /><MSHelp:TOCTitle Title="AwaitedPage Property " /><MSHelp:RLTitle Title="ReplicationStats.AwaitedPage Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.AwaitedPage" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassAwaitedPageTopic" /><MSHelp:Keyword Index="K" Term="AwaitedPage property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.AwaitedPage property" /><MSHelp:Keyword Index="F" Term="AwaitedPage" /><MSHelp:Keyword Index="F" Term="ReplicationStats.AwaitedPage" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.AwaitedPage" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.AwaitedPage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_AwaitedPage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="pg we're awaiting, if any." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.AwaitedPage Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseCursor_Close" /><meta name="guid" content="M_BerkeleyDB_BaseCursor_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseCursor.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="BaseCursor.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseCursor.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="BaseCursor.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="BaseCursor.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseCursor.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseCursor.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Discard the cursor. If you do not close the cursor before closing the database handle or the transaction handle that owns this cursor, then, closing a database handle or a transaction ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td>
<label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">BaseCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetEncryption Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="M_BerkeleyDB_DatabaseConfig_SetEncryption" /><meta name="guid"
content="M_BerkeleyDB_DatabaseConfig_SetEncryption" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseConfig.SetEncryption(System.String,BerkeleyDB.EncryptionAlgorithm)"
/><MSHelp:TOCTitle Title="SetEncryption Method " /><MSHelp:RLTitle Title="DatabaseConfig.SetEncryption
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseConfig.SetEncryption(System.String,BerkeleyDB.EncryptionAlgorithm)"
/><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseConfigClassSetEncryptionTopic" /><MSHelp:Keyword Index="K"
Term="SetEncryption method" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.SetEncryption method"
/><MSHelp:Keyword Index="F" Term="SetEncryption" /><MSHelp:Keyword Index="F"
Term="DatabaseConfig.SetEncryption" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseConfig.SetEncryption" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseConfig.SetEncryption" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the password
and algorithm used by the Berkeley DB library to perform encryption and decryption." /><MSHelp:Attr
Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.SetEncryption Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecoveryException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_RunRecoveryException" /><meta name="guid" content="Properties_T_BerkeleyDB_RunRecoveryException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.RunRecoveryException" /><MSHelp:TOCTitle Title="RunRecoveryException Properties " /><MSHelp:RLTitle Title="RunRecoveryException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.RunRecoveryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRunRecoveryExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RunRecoveryException Properties </td></tr><tr id="headerTableRow3"><td align="left">RunRecoveryException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HeapDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_HeapDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:TOCTitle Title="HeapDatabaseConfig Methods " /><MSHelp:RLTitle Title="HeapDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_PutNoOverwrite" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.PutNoOverwrite" /><MSHelp:TOCTitle Title="PutNoOverwrite Method " /><MSHelp:RLTitle Title="QueueDatabase.PutNoOverwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassPutNoOverwriteTopic" /><MSHelp:Keyword Index="K" Term="PutNoOverwrite method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.PutNoOverwrite method" /><MSHelp:Keyword Index="F" Term="PutNoOverwrite" /><MSHelp:Keyword
Index="F" Term="QueueDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.PutNoOverwrite Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxElectionThreads Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RepMgrStats_MaxElectionThreads" /><meta name="guid" content="P_BerkeleyDB_RepMgrStats_MaxElectionThreads" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RepMgrStats.MaxElectionThreads" /><MSHelp:TOCTitle Title="MaxElectionThreads Property " /><MSHelp:RLTitle Title="RepMgrStats.MaxElectionThreads Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RepMgrStats.MaxElectionThreads" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsClassMaxElectionThreadsTopic" /><MSHelp:Keyword Index="K" Term="MaxElectionThreads property" /><MSHelp:Keyword Index="K" Term="RepMgrStats.MaxElectionThreads property" /><MSHelp:Keyword Index="F" Term="MaxElectionThreads" /><MSHelp:Keyword Index="F" Term="RepMgrStats.MaxElectionThreads" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats.MaxElectionThreads" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.MaxElectionThreads" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.get_MaxElectionThreads" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Election threads for which space is reserved" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RepMgrStats.<span
class="vb">.::.MaxElectionThreads Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RepMgrStats.htm">RepMgrStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Name Property
</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_TransactionConfig_Name" /><meta name="guid"
content="P_BerkeleyDB_TransactionConfig_Name" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.TransactionConfig.Name" /><MSHelp:TOCTitle Title="Name Property "
/><MSHelp:RLTitle Title="TransactionConfig.Name
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionConfig.Name"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassNameTopic"
/><MSHelp:Keyword Index="K" Term="Name property" /><MSHelp:Keyword Index="K"
Term="TransactionConfig.Name property" /><MSHelp:Keyword Index="F" Term="Name" /><MSHelp:Keyword
Index="F" Term="TransactionConfig.Name" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.TransactionConfig.Name" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionConfig.Name" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionConfig.get_Name" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionConfig.set_Name" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The transaction's name. The name is returned by and displayed by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.Name Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Timeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactConfig_Timeout" /><meta name="guid" content="P_BerkeleyDB_CompactConfig_Timeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactConfig.Timeout" /><MSHelp:TOCTitle Title="Timeout Property " /><MSHelp:RLTitle Title="CompactConfig.Timeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactConfig.Timeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassTimeoutTopic" /><MSHelp:Keyword Index="K" Term="Timeout property" /><MSHelp:Keyword Index="K" Term="CompactConfig.Timeout property" /><MSHelp:Keyword Index="F" Term="Timeout" /><MSHelp:Keyword Index="F" Term="CompactConfig.Timeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.Timeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.Timeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.get_Timeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.set_Timeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If non-zero, and no is specified, this parameter identifies the lock timeout used for implicit transactions, in microseconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.Timeout Property </td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryQueueDatabaseConfig Class" /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryQueueDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class, about SecondaryQueueDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method (DatabaseEntry, DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_PutNoOverwrite_1" /><meta
name="guid" content="M_BerkeleyDB_Database_PutNoOverwrite_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkele
yDB.Transaction)" /><MSHelp:TOCTitle Title="PutNoOverwrite
Method (DatabaseEntry, DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="Database.PutNoOverwrite
Method (DatabaseEntry, DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkeley
DB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.PutNoOverwrite"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Store the key/data pair in the database, only if the key does not already
appear in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.PutNoOverwrite Method (DatabaseEntry, DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Add Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Cursor.InsertLocation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Add" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Add" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Add(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry, BerkeleyDB.DatabaseEntry},BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:TOCTitle Title="Add Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Cursor.InsertLocation)" /><MSHelp:RLTitle Title="BTreeCursor.Add Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Cursor.InsertLocation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Add(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Add" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Insert the specified key/data pair into the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Add Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Cursor..::.InsertLocation)</td></tr><tr
id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Recover Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Recover" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Recover" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.DatabaseEnvironment.Recover(System.Int32,System.Boolean)" /><MSHelp:TOCTitle Title="Recover Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Recover Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Recover(System.Int32,System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRecoverTopic" /><MSHelp:Keyword Index="K" Term="Recover method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Recover method" /><MSHelp:Keyword Index="F" Term="Recover" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Recover" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Recover" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Recover" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Restore transactions that were prepared, but not yet resolved at the time of the system shut down or crash, to their state prior to the shut down or crash, including any locks previously held." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Recover Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NotFoundException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_NotFoundException" /><meta name="guid" content="T_BerkeleyDB_NotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.NotFoundException" /><MSHelp:TOCTitle Title="NotFoundException Class" /><MSHelp:RLTitle Title="NotFoundException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.NotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotFoundExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="NotFoundException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.NotFoundException class" /><MSHelp:Keyword Index="K" Term="NotFoundException class, about NotFoundException class" /><MSHelp:Keyword Index="F" Term="NotFoundException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.NotFoundException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotFoundException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The requested key/data pair did not exist in the database or that start-of- or end-of-file has been reached by a cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">NotFoundException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_Compare" /><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_Compare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.Compare" /><MSHelp:TOCTitle Title="Compare Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.Compare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.Compare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.Compare field"

/><MSHelp:Keyword Index="F" Term="Compare" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabaseConfig.Compare" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.Compare" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.Compare"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The Btree key comparison function." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryBTreeDatabaseConfig<span
class="cs">..::<span
class="nu">.Compare Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryBTreeDatabaseConfig.htm">SecondaryBTreeDatabaseConfig Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintMutexSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintMutexSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintMutexSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:TOCTitle Title="PrintMutexSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintMutexSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintMutexSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintMutexSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.PrintMutexSystemStats method" /><MSHelp:Keyword Index="F" Term="PrintMutexSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintMutexSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="M_BerkeleyDB_Cursor_MovePrevDuplicate" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="Cursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and that pair is stored in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevDuplicate

Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepElectionRetry Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepElectionRetry" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepElectionRetry" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepElectionRetry" /><MSHelp:TOCTitle Title="RepElectionRetry Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepElectionRetry Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepElectionRetry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepElectionRetryTopic" /><MSHelp:Keyword Index="K" Term="RepElectionRetry property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepElectionRetry property" /><MSHelp:Keyword Index="F" Term="RepElectionRetry" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepElectionRetry" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepElectionRetry" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepElectionRetry" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepElectionRetry" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepElectionRetry" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure the amount of time the replication manager will wait before retrying a failed election. The default wait time is 10 seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepElectionRetry Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_GetBothMultiple" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.GetBothMultiple" /><MSHelp:TOCTitle Title="GetBothMultiple Method " /><MSHelp:RLTitle Title="RecnoDatabase.GetBothMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.GetBothMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassGetBothMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetBothMultiple method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.GetBothMultiple method" /><MSHelp:Keyword Index="F" Term="GetBothMultiple" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.GetBothMultiple" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.RecnoDatabase.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.GetBothMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabase_Compare" /><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabase_Compare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabase.Compare" /><MSHelp:TOCTitle Title="Compare Property " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Compare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryHashDatabase.Compare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Compare property" /><MSHelp:Keyword Index="F" Term="Compare" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Compare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Compare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.get_Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.set_Compare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The secondary Hash key comparison function. The comparison function is called whenever it is necessary to compare a key specified by the application with a key currently stored in the tree." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Compare Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionMax Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_RegionMax" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_RegionMax" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.RegionMax" /><MSHelp:TOCTitle Title="RegionMax Property " /><MSHelp:RLTitle

Title="MPoolStats.RegionMax Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.RegionMax" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassRegionMaxTopic" /><MSHelp:Keyword Index="K" Term="RegionMax property" /><MSHelp:Keyword Index="K" Term="MPoolStats.RegionMax property" /><MSHelp:Keyword Index="F" Term="RegionMax" /><MSHelp:Keyword Index="F" Term="MPoolStats.RegionMax" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.RegionMax" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.RegionMax" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_RegionMax" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Individual cache max." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats.<span

class="vb">.::.RegionMax Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLocks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxLocks" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxLocks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxLocks" /><MSHelp:TOCTitle Title="MaxLocks Property " /><MSHelp:RLTitle Title="LockStats.MaxLocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxLocks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxLocksTopic" /><MSHelp:Keyword Index="K" Term="MaxLocks property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxLocks property" /><MSHelp:Keyword Index="F" Term="MaxLocks" /><MSHelp:Keyword Index="F" Term="LockStats.MaxLocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxLocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxLocks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxLocks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of locks so far." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxLocks Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OldVersionException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_OldVersionException" /><meta name="guid" content="T_BerkeleyDB_OldVersionException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.OldVersionException" /><MSHelp:TOCTitle Title="OldVersionException Class" /><MSHelp:RLTitle Title="OldVersionException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.OldVersionException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBOldVersionExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="OldVersionException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.OldVersionException class" /><MSHelp:Keyword Index="K" Term="OldVersionException class, about OldVersionException class" /><MSHelp:Keyword Index="F" Term="OldVersionException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.OldVersionException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr

Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.OldVersionException"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="This version of Berkeley DB is unable to upgrade a given database."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">OldVersionException Class</td></tr><tr id="headerTableRow3"><td align="left"><a
href="AllMembers_T_BerkeleyDB_OldVersionException.htm">Members <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_LEASE_EXPIRED Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_LEASE_EXPIRED" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_LEASE_EXPIRED" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_LEASE_EXPIRED" /><MSHelp:TOCTitle Title="DB_REP_LEASE_EXPIRED Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_LEASE_EXPIRED Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_LEASE_EXPIRED" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_LEASE_EXPIREDTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_LEASE_EXPIRED field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_LEASE_EXPIRED field" /><MSHelp:Keyword Index="F" Term="DB_REP_LEASE_EXPIRED" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_LEASE_EXPIRED" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_LEASE_EXPIRED" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_LEASE_EXPIRED" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Master lease has expired." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_LEASE_EXPIRED Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ErrorCodes.htm">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="SecondaryDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K"
Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase.<span

class="vb">.::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxPartitionLockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxPartitionLockWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxPartitionLockWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxPartitionLockWait" /><MSHelp:TOCTitle Title="MaxPartitionLockWait Property " /><MSHelp:RLTitle Title="LockStats.MaxPartitionLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxPartitionLockWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxPartitionLockWaitTopic" /><MSHelp:Keyword Index="K" Term="MaxPartitionLockWait property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxPartitionLockWait property" /><MSHelp:Keyword Index="F" Term="MaxPartitionLockWait" /><MSHelp:Keyword Index="F" Term="LockStats.MaxPartitionLockWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxPartitionLockWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxPartitionLockWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxPartitionLockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max partition lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxPartitionLockWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunFatalRecovery Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_RunFatalRecovery" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_RunFatalRecovery" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.RunFatalRecovery" /><MSHelp:TOCTitle Title="RunFatalRecovery Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.RunFatalRecovery Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.RunFatalRecovery" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassRunFatalRecoveryTopic" /><MSHelp:Keyword Index="K" Term="RunFatalRecovery field" /><MSHelp:Keyword Index="K"

Term="DatabaseEnvironmentConfig.RunFatalRecovery field" /><MSHelp:Keyword Index="F"
Term="RunFatalRecovery" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.RunFatalRecovery" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.RunFatalRecovery" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.RunFatalRecovery" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, catastrophic recovery will be run on this environment before opening it for normal
use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironmentConfig.<span
class="vb">.::.RunFatalRecovery
Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig

Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.GetBoth" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextItem Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_JoinCursor_MoveNextItem" /><meta name="guid" content="Overload_BerkeleyDB_JoinCursor_MoveNextItem" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:TOCTitle Title="MoveNextItem Method "

/><MSHelp:RLTitle Title="JoinCursor.MoveNextItem Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassMoveNextItemTopic" /><MSHelp:Keyword Index="K" Term="MoveNextItem method" /><MSHelp:Keyword Index="K" Term="JoinCursor.MoveNextItem method" /><MSHelp:Keyword Index="F" Term="MoveNextItem" /><MSHelp:Keyword Index="F" Term="JoinCursor.MoveNextItem" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.MoveNextItem Method </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Database Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_Database" /><meta name="guid" content="Methods_T_BerkeleyDB_Database" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.Database" /><MSHelp:TOCTitle Title="Database Methods " /><MSHelp:RLTitle Title="Database Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.Database" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="Database class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database Methods </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InternalPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_InternalPages" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_InternalPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.InternalPages" /><MSHelp:TOCTitle Title="InternalPages Property " /><MSHelp:RLTitle Title="BTreeStats.InternalPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.InternalPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassInternalPagesTopic" /><MSHelp:Keyword Index="K" Term="InternalPages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.InternalPages property" /><MSHelp:Keyword Index="F" Term="InternalPages" /><MSHelp:Keyword Index="F" Term="BTreeStats.InternalPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.InternalPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.InternalPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_InternalPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Internal pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.InternalPages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullLogBufferException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_FullLogBufferException" /><meta name="guid" content="Properties_T_BerkeleyDB_FullLogBufferException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.FullLogBufferException" /><MSHelp:TOCTitle Title="FullLogBufferException Properties " /><MSHelp:RLTitle Title="FullLogBufferException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.FullLogBufferException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBFullLogBufferExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">FullLogBufferException Properties </td></tr><tr id="headerTableRow3"><td align="left">FullLogBufferException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepTransmitLimitBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepTransmitLimitBytes" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepTransmitLimitBytes" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepTransmitLimitBytes" /><MSHelp:TOCTitle
Title="RepTransmitLimitBytes Property " /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepTransmitLimitBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.RepTransmitLimitBytes" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepTransmitLimitBytesTopic" /><MSHelp:Keyword
Index="K" Term="RepTransmitLimitBytes property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepTransmitLimitBytes property" /><MSHelp:Keyword Index="F"
Term="RepTransmitLimitBytes" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepTransmitLimitBytes"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepTransmitLimitBytes"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepTransmitLimitBytes" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_RepTransmitLimitBytes" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The bytes component of the byte-count limit on the amount of data that will be transmitted from a site in
response to a single message processed by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepTransmitLimitBytes Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyEmptyException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_KeyEmptyException__ctor" /><meta name="guid" content="M_BerkeleyDB_KeyEmptyException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.KeyEmptyException.#ctor" /><MSHelp:TOCTitle Title="KeyEmptyException Constructor " /><MSHelp:RLTitle Title="KeyEmptyException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.KeyEmptyException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyEmptyExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class, constructor" /><MSHelp:Keyword Index="K" Term="KeyEmptyException.KeyEmptyException constructor" /><MSHelp:Keyword Index="F" Term="KeyEmptyException" /><MSHelp:Keyword Index="F" Term="KeyEmptyException.KeyEmptyException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyEmptyException.KeyEmptyException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyEmptyException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the KeyEmptyException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyEmptyException Constructor </td></tr><tr id="headerTableRow3"><td align="left">KeyEmptyException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nData Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_nData" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_nData" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.nData" /><MSHelp:TOCTitle Title="nData Property " /><MSHelp:RLTitle Title="BTreeStats.nData Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.nData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassnDataTopic" /><MSHelp:Keyword Index="K" Term="nData property" /><MSHelp:Keyword Index="K" Term="BTreeStats.nData property" /><MSHelp:Keyword Index="F" Term="nData" /><MSHelp:Keyword Index="F" Term="BTreeStats.nData" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.nData" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.nData" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_nData" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.nData Property</td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_FastStats_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_FastStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction)" /><MSHelp:RLTitle Title="HashDatabase.FastStats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.FastStats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Get" /><meta name="guid" content="Overload_BerkeleyDB_Database_Get" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.Database.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="Database.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="Database.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="Database.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Database<span
class="cs">..::.Get
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextUniqueMultiple Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_RecnoCursor_MoveNextUniqueMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MoveNextUniqueMultiple" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextUniqueMultiple"
/><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method " /><MSHelp:RLTitle
Title="RecnoCursor.MoveNextUniqueMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.RecnoCursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoCursorClassMoveNextUniqueMultipleTopic" /><MSHelp:Keyword Index="K"
Term="MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="K"
Term="RecnoCursor.MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="F"
Term="MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F"
Term="RecnoCursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoCursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveNextUniqueMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UsingCDB Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UsingCDB" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UsingCDB" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UsingCDB" /><MSHelp:TOCTitle Title="UsingCDB Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UsingCDB Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UsingCDB" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUsingCDBTopic" /><MSHelp:Keyword Index="K" Term="UsingCDB property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UsingCDB property" /><MSHelp:Keyword Index="F" Term="UsingCDB" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UsingCDB" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UsingCDB" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UsingCDB" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UsingCDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, locking for the Berkeley DB Concurrent Data Store product was initialized." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UsingCDB Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSiteConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DbSiteConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_DbSiteConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DbSiteConfig" /><MSHelp:TOCTitle Title="DbSiteConfig Properties " /><MSHelp:RLTitle Title="DbSiteConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DbSiteConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFlush Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_LogFlush" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_LogFlush" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:TOCTitle Title="LogFlush Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogFlush Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogFlushTopic" /><MSHelp:Keyword Index="K" Term="LogFlush method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogFlush method" /><MSHelp:Keyword Index="F" Term="LogFlush" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogFlush" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span
class="nu">.LogFlush Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>PrintRepMgrSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintRepMgrSystemStats_1" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_PrintRepMgrSystemStats_1" /><xml><MSHelp:Attr
Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats(System.Boolean,System.Boolean)"
/><MSHelp:TOCTitle Title="PrintRepMgrSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle
Title="DatabaseEnvironment.PrintRepMgrSystemStats Method (Boolean, Boolean) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats(System.Boolean,System.Boolean)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="Abstract" Value="Display the replication manager statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintRepMgrSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SnapshotIsolation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_CursorConfig_SnapshotIsolation" /><meta name="guid"
content="F_BerkeleyDB_CursorConfig_SnapshotIsolation" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.CursorConfig.SnapshotIsolation" /><MSHelp:TOCTitle Title="SnapshotIsolation Field"
/><MSHelp:RLTitle Title="CursorConfig.SnapshotIsolation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.CursorConfig.SnapshotIsolation" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCursorConfigClassSnapshotIsolationTopic" /><MSHelp:Keyword Index="K"
Term="SnapshotIsolation field" /><MSHelp:Keyword Index="K" Term="CursorConfig.SnapshotIsolation field"
/><MSHelp:Keyword Index="F" Term="SnapshotIsolation" /><MSHelp:Keyword Index="F"
Term="CursorConfig.SnapshotIsolation" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.CursorConfig.SnapshotIsolation" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.CursorConfig.SnapshotIsolation" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure a
transactional cursor to operate with read-only snapshot isolation. For databases with set, data values will be read as
they are when the cursor is opened, without taking read ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig..::.SnapshotIsolation Field</td></tr><tr id="headerTableRow3"><td align="left">CursorConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Count Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_Count" /><meta name="guid" content="P_BerkeleyDB_MutexStats_Count" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.Count" /><MSHelp:TOCTitle Title="Count Property " /><MSHelp:RLTitle Title="MutexStats.Count Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.Count" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassCountTopic" /><MSHelp:Keyword Index="K" Term="Count property" /><MSHelp:Keyword Index="K" Term="MutexStats.Count property" /><MSHelp:Keyword Index="F" Term="Count" /><MSHelp:Keyword Index="F" Term="MutexStats.Count" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.Count" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.Count" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_Count" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutex count" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.Count Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Host Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DbSiteConfig_Host" /><meta name="guid" content="F_BerkeleyDB_DbSiteConfig_Host" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DbSiteConfig.Host" /><MSHelp:TOCTitle Title="Host Field" /><MSHelp:RLTitle

Title="DbSiteConfig.Host Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DbSiteConfig.Host" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassHostTopic" /><MSHelp:Keyword Index="K" Term="Host field" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.Host field" /><MSHelp:Keyword Index="F" Term="Host" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.Host" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.Host" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.Host" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The host of the site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.Host Field</td></tr><tr

id="headerTableRow3"><td align="left">DbSiteConfig Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>start
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CompactConfig_start" /><meta
name="guid" content="F_BerkeleyDB_CompactConfig_start" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.CompactConfig.start" /><MSHelp:TOCTitle Title="start Field" /><MSHelp:RLTitle
Title="CompactConfig.start Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.CompactConfig.start" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCompactConfigClassstartTopic" /><MSHelp:Keyword Index="K" Term="start field"
/><MSHelp:Keyword Index="K" Term="CompactConfig.start field" /><MSHelp:Keyword Index="F" Term="start"
/><MSHelp:Keyword Index="F" Term="CompactConfig.start" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.CompactConfig.start" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.CompactConfig.start" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If non-null, the starting point for
compaction. For a Btree or Recno database compaction will start at the smallest key greater
than or equal to the starting point. For a Hash database the compac ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.start Field</td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DataDirs Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_DataDirs" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_DataDirs" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.DataDirs" /><MSHelp:TOCTitle Title="DataDirs Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.DataDirs Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.DataDirs" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassDataDirsTopic" /><MSHelp:Keyword Index="K" Term="DataDirs field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.DataDirs field" /><MSHelp:Keyword Index="F" Term="DataDirs" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.DataDirs" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.DataDirs" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.DatabaseEnvironmentConfig.DataDirs" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Paths of directories to be used as the location of the access method database files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.DataDirs Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabaseConfig.#ctor" /><MSHelp:TOCTitle Title="BTreeDatabaseConfig Constructor " /><MSHelp:RLTitle Title="BTreeDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabaseConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.BTreeDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.BTreeDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.BTreeDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new BTreeDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionTimeSec Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionTimeSec" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionTimeSec" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionTimeSec" /><MSHelp:TOCTitle Title="ElectionTimeSec Property " /><MSHelp:RLTitle Title="ReplicationStats.ElectionTimeSec Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionTimeSec" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionTimeSecTopic" /><MSHelp:Keyword Index="K" Term="ElectionTimeSec property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionTimeSec property" /><MSHelp:Keyword Index="F" Term="ElectionTimeSec" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionTimeSec" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionTimeSec" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionTimeSec" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionTimeSec" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Last election time seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionTimeSec Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="HeapDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">HeapDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Version Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_Version" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_Version" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.Version" /><MSHelp:TOCTitle Title="Version Property " /><MSHelp:RLTitle Title="RecnoStats.Version Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.Version" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassVersionTopic" /><MSHelp:Keyword Index="K" Term="Version property" /><MSHelp:Keyword Index="K" Term="RecnoStats.Version property" /><MSHelp:Keyword Index="F" Term="Version" /><MSHelp:Keyword Index="F" Term="RecnoStats.Version" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.Version" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.Version" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_Version" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Version number."

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.Version Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Properties_T_BerkeleyDB_TransactionConfig" /><meta name="guid"
content="Properties_T_BerkeleyDB_TransactionConfig" /><xml><MSHelp:Attr
Name="AssetID" Value="Properties.T:BerkeleyDB.TransactionConfig" /><MSHelp:TOCTitle
Title="TransactionConfig Properties " /><MSHelp:RLTitle Title="TransactionConfig Properties (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.TransactionConfig" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBTransactionConfigPropertiesTopic" /><MSHelp:Keyword Index="K"
Term="TransactionConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MPoolStats" /><meta name="guid" content="Properties_T_BerkeleyDB_MPoolStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MPoolStats" /><MSHelp:TOCTitle Title="MPoolStats Properties " /><MSHelp:RLTitle Title="MPoolStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MPoolStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MPoolStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
/> <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats Properties </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="AllMembers_T_BerkeleyDB_TransactionConfig" /><meta name="guid"
content="AllMembers_T_BerkeleyDB_TransactionConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="AllMembers.T:BerkeleyDB.TransactionConfig" /><MSHelp:TOCTitle Title="TransactionConfig
Members" /><MSHelp:RLTitle Title="TransactionConfig Members (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="AllMembers.T:BerkeleyDB.TransactionConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionConfigMembersTopic" /><MSHelp:Keyword Index="K"
Term="TransactionConfig class" /><MSHelp:Keyword Index="K" Term="TransactionConfig class, all members"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.TransactionConfig class" /><MSHelp:Keyword Index="F"
Term="TransactionConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig"
/><MSHelp:Attr
Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig Members</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class Constructors Methods
  Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSize Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
 </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabaseConfig_MaxSize" /><meta name="guid" content="M_BerkeleyDB_HeapDatabaseConfig_MaxSize" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabaseConfig.MaxSize(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="MaxSize Method " /><MSHelp:RLTitle Title="HeapDatabaseConfig.MaxSize Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabaseConfig.MaxSize(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A"
 Term="frlrfBerkeleyDBHeapDatabaseConfigClassMaxSizeTopic" /><MSHelp:Keyword Index="K" Term="MaxSize method" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig.MaxSize method" /><MSHelp:Keyword Index="F" Term="MaxSize" /><MSHelp:Keyword Index="F"

Term="HeapDatabaseConfig.MaxSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabaseConfig.MaxSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig.MaxSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the maximum on-disk database file size used by the database. If this value is never set, the database's file size can grow without bound. If this value
is set, then the heap file can never grow ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig..::.MaxSize Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PartitionLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_PartitionLockNoWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_PartitionLockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.PartitionLockNoWait" /><MSHelp:TOCTitle Title="PartitionLockNoWait Property " /><MSHelp:RLTitle Title="LockStats.PartitionLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.PartitionLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassPartitionLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="PartitionLockNoWait property" /><MSHelp:Keyword Index="K" Term="LockStats.PartitionLockNoWait property" /><MSHelp:Keyword Index="F" Term="PartitionLockNoWait" /><MSHelp:Keyword Index="F" Term="LockStats.PartitionLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.PartitionLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.PartitionLockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_PartitionLockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Partition lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.PartitionLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadIsAliveDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ThreadIsAliveDelegate" /><meta name="guid" content="T_BerkeleyDB_ThreadIsAliveDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ThreadIsAliveDelegate" /><MSHelp:TOCTitle Title="ThreadIsAliveDelegate Delegate" /><MSHelp:RLTitle Title="ThreadIsAliveDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ThreadIsAliveDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBThreadIsAliveDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="ThreadIsAliveDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ThreadIsAliveDelegate delegate" /><MSHelp:Keyword Index="F" Term="ThreadIsAliveDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ThreadIsAliveDelegate" /><MSHelp:Attr

Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ThreadIsAliveDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ThreadIsAliveDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ThreadIsAliveDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ThreadIsAliveDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ThreadIsAliveDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function which returns whether the thread of control, identified by , is still running." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ThreadIsAliveDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LogConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_LogConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LogConfig" /><MSHelp:TOCTitle Title="LogConfig Properties " /><MSHelp:RLTitle Title="LogConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LogConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="LogConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxBucketsCheckedDuringAlloc Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MaxBucketsCheckedDuringAlloc" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxBucketsCheckedDuringAlloc" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxBucketsCheckedDuringAlloc" /><MSHelp:TOCTitle Title="MaxBucketsCheckedDuringAlloc Property " /><MSHelp:RLTitle Title="MPoolStats.MaxBucketsCheckedDuringAlloc Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxBucketsCheckedDuringAlloc" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxBucketsCheckedDuringAllocTopic" /><MSHelp:Keyword Index="K" Term="MaxBucketsCheckedDuringAlloc property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxBucketsCheckedDuringAlloc property" /><MSHelp:Keyword Index="F" Term="MaxBucketsCheckedDuringAlloc"

/><MSHelp:Keyword Index="F" Term="MPoolStats.MaxBucketsCheckedDuringAlloc" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxBucketsCheckedDuringAlloc" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxBucketsCheckedDuringAlloc" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxBucketsCheckedDuringAlloc" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max checked during allocation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxBucketsCheckedDuringAlloc Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveLast" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveLast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveLastTopic" /><MSHelp:Keyword Index="K" Term="MoveLast method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveLast method" /><MSHelp:Keyword Index="F" Term="MoveLast" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveLast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveLast Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapRecordId Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HeapRecordId" /><meta name="guid" content="Properties_T_BerkeleyDB_HeapRecordId" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HeapRecordId" /><MSHelp:TOCTitle Title="HeapRecordId Properties " /><MSHelp:RLTitle Title="HeapRecordId Properties (BerkeleyDB)" /><MSHelp:Keyword

Index="A" Term="Properties.T:BerkeleyDB.HeapRecordId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdPropertiesTopic" /><MSHelp:Keyword Index="K" Term="HeapRecordId class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId Properties </td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_DatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DatabaseConfig" /><MSHelp:TOCTitle Title="DatabaseConfig Properties " /><MSHelp:RLTitle Title="DatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabaseConfig_SetForeignKeyConstraint" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabaseConfig_SetForeignKeyConstraint" /><xml><MSHelp:Attr Name="AssetID"

Value="Overload:BerkeleyDB.SecondaryQueueDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:TOCTitle Title="SetForeignKeyConstraint Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig.SetForeignKeyConstraint Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassSetForeignKeyConstraintTopic" /><MSHelp:Keyword Index="K" Term="SetForeignKeyConstraint method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig.SetForeignKeyConstraint method" /><MSHelp:Keyword Index="F" Term="SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig..::.SetForeignKeyConstraint Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RemoveDB Method (String, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.Boolean)" /><MSHelp:TOCTitle Title="RemoveDB Method (String, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RemoveDB Method (String, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the underlying file represented by , incidentally removing all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.RemoveDB Method (String,
Boolean)</td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Result
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RepProcMsgResult_Result" /><meta name="guid" content="F_BerkeleyDB_RepProcMsgResult_Result" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RepProcMsgResult.Result" /><MSHelp:TOCTitle Title="Result Field" /><MSHelp:RLTitle Title="RepProcMsgResult.Result Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.Result" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultClassResultTopic" /><MSHelp:Keyword Index="K" Term="Result field" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult.Result field" /><MSHelp:Keyword Index="F" Term="Result" /><MSHelp:Keyword Index="F" Term="RepProcMsgResult.Result" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepProcMsgResult.Result" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepProcMsgResult.Result" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The result of processing an incoming replication message." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepProcMsgResult..::.Result Field</td></tr><tr id="headerTableRow3"><td align="left">RepProcMsgResult Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Put" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Put" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Put" /><MSHelp:TOCTitle Title="Put Method " /><MSHelp:RLTitle Title="QueueDatabase.Put Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Put" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassPutTopic" /><MSHelp:Keyword Index="K" Term="Put method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Put method" /><MSHelp:Keyword Index="F" Term="Put" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Put" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage" src="../icons/dropdown.gif"
/> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">QueueDatabase<span
class="cs">..<span
class="cpp">::.Put Method </td></tr><tr
id="headerTableRow3"><td align="left">QueueDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>DatabaseEnvironmentConfig Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironmentConfig__ctor" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironmentConfig__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironmentConfig.#ctor" /><MSHelp:TOCTitle
Title="DatabaseEnvironmentConfig Constructor " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig
Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironmentConfig.#ctor"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassctorTopic"
/><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig class, constructor" /><MSHelp:Keyword
Index="K" Term="DatabaseEnvironmentConfig.DatabaseEnvironmentConfig constructor" /><MSHelp:Keyword
Index="F" Term="DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.DatabaseEnvironmentConfig" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig..ctor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract"
Value="Create a new object, with default settings" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, DatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Open" /><meta name="guid" content="M_BerkeleyDB_Database_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Open(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, DatabaseConfig)" /><MSHelp:RLTitle Title="Database.Open Method (String, DatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Open(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new Database object and open the database represented by . The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">..<span
class="cpp">::.Open Method (String,
DatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Restored
Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_TransactionStats_Restored" /><meta name="guid"
content="P_BerkeleyDB_TransactionStats_Restored" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.TransactionStats.Restored" /><MSHelp:TOCTitle Title="Restored Property "
/><MSHelp:RLTitle Title="TransactionStats.Restored

Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.Restored" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassRestoredTopic" /><MSHelp:Keyword Index="K" Term="Restored property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Restored property" /><MSHelp:Keyword Index="F" Term="Restored" /><MSHelp:Keyword Index="F" Term="TransactionStats.Restored" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.Restored" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.Restored" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Restored" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of restored transactions after recovery." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats.<span

class="vb">.::.Restored Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_TransactionStats.htm">TransactionStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
 xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CursorConfig
Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Fields_T_BerkeleyDB_CursorConfig"
 /><meta name="guid" content="Fields_T_BerkeleyDB_CursorConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.CursorConfig" /><MSHelp:TOCTitle Title="CursorConfig Fields"
/><MSHelp:RLTitle Title="CursorConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.CursorConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCursorConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="CursorConfig class,
fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
 title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
 event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">CursorConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AckPolicy Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_AckPolicy" /><meta name="guid" content="Methods_T_BerkeleyDB_AckPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.AckPolicy" /><MSHelp:TOCTitle Title="AckPolicy Methods " /><MSHelp:RLTitle Title="AckPolicy Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.AckPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyMethodsTopic"

/><MSHelp:Keyword Index="K" Term="AckPolicy class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include

Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy Methods </td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_Refresh" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="SecondaryCursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassRefreshTopic" /><MSHelp:Keyword Index="K" Term="Refresh method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.Refresh method" /><MSHelp:Keyword Index="F" Term="Refresh" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.Refresh" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Refresh Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashBucketMutexes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="P_BerkeleyDB_MPoolStats_HashBucketMutexes" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_HashBucketMutexes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.HashBucketMutexes" /><MSHelp:TOCTitle Title="HashBucketMutexes Property " /><MSHelp:RLTitle Title="MPoolStats.HashBucketMutexes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.HashBucketMutexes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassHashBucketMutexesTopic" /><MSHelp:Keyword Index="K" Term="HashBucketMutexes property" /><MSHelp:Keyword Index="K" Term="MPoolStats.HashBucketMutexes property" /><MSHelp:Keyword Index="F" Term="HashBucketMutexes" /><MSHelp:Keyword Index="F" Term="MPoolStats.HashBucketMutexes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.HashBucketMutexes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.HashBucketMutexes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_HashBucketMutexes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of hash bucket mutexes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.HashBucketMutexes Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InUse Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_InUse" /><meta name="guid" content="P_BerkeleyDB_MutexStats_InUse" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.InUse" /><MSHelp:TOCTitle Title="InUse Property " /><MSHelp:RLTitle Title="MutexStats.InUse Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.InUse" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassInUseTopic" /><MSHelp:Keyword Index="K" Term="InUse property" /><MSHelp:Keyword
Index="K" Term="MutexStats.InUse property" /><MSHelp:Keyword Index="F" Term="InUse" /><MSHelp:Keyword Index="F" Term="MutexStats.InUse" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.InUse" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.InUse" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_InUse" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutexes in use" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.InUse Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepNSites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepNSites" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepNSites" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepNSites" /><MSHelp:TOCTitle Title="RepNSites Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepNSites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepNSites"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepNSitesTopic" /><MSHelp:Keyword Index="K" Term="RepNSites property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepNSites property" /><MSHelp:Keyword Index="F" Term="RepNSites" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepNSites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepNSites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepNSites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepNSites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepNSites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The total number of sites in the replication group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::<span

class="nu">.RepNSites Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Move_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_Move_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, Boolean, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.Move Method (DatabaseEntry, Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the datum associated with the given key in . In the presence of duplicate key values, the first data item in the set of duplicates is stored in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method (DatabaseEntry, Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_QueueDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_QueueDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.QueueDatabase" /><MSHelp:TOCTitle Title="QueueDatabase Members" /><MSHelp:RLTitle Title="QueueDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.QueueDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabase class" /><MSHelp:Keyword Index="K" Term="QueueDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.QueueDatabase class" /><MSHelp:Keyword Index="F" Term="QueueDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_HashDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabaseConfig.#ctor" /><MSHelp:TOCTitle Title="HashDatabaseConfig Constructor " /><MSHelp:RLTitle Title="HashDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabaseConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.HashDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.HashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.HashDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HashDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HashDatabaseConfig Constructor </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashDatabaseConfig.htm">HashDatabaseConfig Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_QueueDatabase_Stats" /><meta name="guid"
content="Overload_BerkeleyDB_QueueDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.QueueDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method "
/><MSHelp:RLTitle Title="QueueDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.QueueDatabase.Stats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBQueueDatabaseClassStatsTopic" /><MSHelp:Keyword Index="K" Term="Stats method"
/><MSHelp:Keyword Index="K" Term="QueueDatabase.Stats method" /><MSHelp:Keyword Index="F"

Term="Stats" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Stats" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.QueueDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Stats" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="HeapDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Stats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassStatsTopic" /><MSHelp:Keyword Index="K" Term="Stats method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Stats method" /><MSHelp:Keyword Index="F" Term="Stats" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Stats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Stats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_BaseDatabase_GetBoth_1" /><meta name="guid"
content="M_BerkeleyDB_BaseDatabase_GetBoth_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseDatabase.GetBoth(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyD
B.Transaction)" /><MSHelp:TOCTitle Title="GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction)"
/><MSHelp:RLTitle Title="BaseDatabase.GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseDatabase.GetBoth(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyD
B.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a
key/data pair from the database which matches and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="QueueDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">QueueDatabase<span
class="cs">..::<span
class="nu">.Delete Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_QueueDatabase.htm">QueueDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Get Method </td></tr><tr
id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Objects Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_Objects" /><meta name="guid" content="P_BerkeleyDB_LockStats_Objects" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.Objects" /><MSHelp:TOCTitle Title="Objects Property " /><MSHelp:RLTitle Title="LockStats.Objects Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.Objects" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassObjectsTopic" /><MSHelp:Keyword Index="K" Term="Objects property" /><MSHelp:Keyword Index="K" Term="LockStats.Objects
property" /><MSHelp:Keyword Index="F" Term="Objects" /><MSHelp:Keyword Index="F" Term="LockStats.Objects" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.Objects" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.Objects" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_Objects" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current number of objects." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.Objects Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupOptions Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BackupOptions__ctor" /><meta name="guid" content="M_BerkeleyDB_BackupOptions__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BackupOptions.#ctor" /><MSHelp:TOCTitle Title="BackupOptions Constructor " /><MSHelp:RLTitle Title="BackupOptions Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BackupOptions.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassctorTopic" /><MSHelp:Keyword Index="K" Term="BackupOptions class, constructor" /><MSHelp:Keyword Index="K" Term="BackupOptions.BackupOptions constructor" /><MSHelp:Keyword Index="F" Term="BackupOptions" /><MSHelp:Keyword Index="F" Term="BackupOptions.BackupOptions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.BackupOptions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions Constructor </td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RepMgrSite" /><meta name="guid" content="Methods_T_BerkeleyDB_RepMgrSite" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RepMgrSite" /><MSHelp:TOCTitle Title="RepMgrSite Methods " /><MSHelp:RLTitle Title="RepMgrSite Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RepMgrSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrSiteMethodsTopic" /><MSHelp:Keyword Index="K" Term="RepMgrSite class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span id="devlangsDropdown" class="filter"

tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RepMgrSite Methods </td></tr><tr id="headerTableRow3"><td
align="left">RepMgrSite Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IsolationDegree
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_LockingInfo_IsolationDegree" /><meta name="guid"

content="F_BerkeleyDB_LockingInfo_IsolationDegree" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LockingInfo.IsolationDegree" /><MSHelp:TOCTitle Title="IsolationDegree Field" /><MSHelp:RLTitle Title="LockingInfo.IsolationDegree Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LockingInfo.IsolationDegree" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingInfoClassIsolationDegreeTopic" /><MSHelp:Keyword Index="K" Term="IsolationDegree field" /><MSHelp:Keyword Index="K" Term="LockingInfo.IsolationDegree field" /><MSHelp:Keyword Index="F" Term="IsolationDegree" /><MSHelp:Keyword Index="F" Term="LockingInfo.IsolationDegree" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingInfo.IsolationDegree" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingInfo.IsolationDegree" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The isolation degree of the operation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingInfo..::.IsolationDegree Field</td></tr><tr id="headerTableRow3"><td align="left">LockingInfo Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSizeGBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapDatabase_MaxSizeGBytes" /><meta name="guid" content="P_BerkeleyDB_HeapDatabase_MaxSizeGBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapDatabase.MaxSizeGBytes" /><MSHelp:TOCTitle Title="MaxSizeGBytes Property " /><MSHelp:RLTitle Title="HeapDatabase.MaxSizeGBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapDatabase.MaxSizeGBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassMaxSizeGBytesTopic" /><MSHelp:Keyword Index="K" Term="MaxSizeGBytes property" /><MSHelp:Keyword Index="K" Term="HeapDatabase.MaxSizeGBytes property" /><MSHelp:Keyword Index="F" Term="MaxSizeGBytes" /><MSHelp:Keyword Index="F" Term="HeapDatabase.MaxSizeGBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.MaxSizeGBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.MaxSizeGBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.get_MaxSizeGBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The gigabytes component of the maximum on-disk database file size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.MaxSizeGBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Method " /><MSHelp:RLTitle Title="SecondaryDatabase.SecondaryCursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a secondary database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.SecondaryCursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationMisc

Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_ReplicationMisc" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_ReplicationMisc" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.ReplicationMisc" /><MSHelp:TOCTitle Title="ReplicationMisc Field" /><MSHelp:RLTitle Title="VerboseMessages.ReplicationMisc Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationMisc" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationMiscTopic" /><MSHelp:Keyword Index="K" Term="ReplicationMisc field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationMisc field" /><MSHelp:Keyword Index="F" Term="ReplicationMisc" /><MSHelp:Keyword Index="F" Term="VerboseMessages.ReplicationMisc" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.ReplicationMisc" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.ReplicationMisc" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about general replication processing not covered by the other Replication* values." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.ReplicationMisc Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_GetMultiple" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_GetMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.GetMultiple" /><MSHelp:TOCTitle Title="GetMultiple Method " /><MSHelp:RLTitle Title="RecnoDatabase.GetMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.GetMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassGetMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetMultiple method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.GetMultiple method" /><MSHelp:Keyword Index="F" Term="GetMultiple" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.GetMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.GetMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MIN_LOCKS
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_DeadlockPolicy_MIN_LOCKS" /><meta name="guid"
content="F_BerkeleyDB_DeadlockPolicy_MIN_LOCKS" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DeadlockPolicy.MIN_LOCKS" /><MSHelp:TOCTitle Title="MIN_LOCKS Field"
/><MSHelp:RLTitle Title="DeadlockPolicy.MIN_LOCKS Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.DeadlockPolicy.MIN_LOCKS" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDeadlockPolicyClassMIN_LOCKSTopic" /><MSHelp:Keyword Index="K"
Term="MIN_LOCKS field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.MIN_LOCKS field"
/><MSHelp:Keyword Index="F" Term="MIN_LOCKS" /><MSHelp:Keyword Index="F"
Term="DeadlockPolicy.MIN_LOCKS" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DeadlockPolicy.MIN_LOCKS" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DeadlockPolicy.MIN_LOCKS" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject the lock
request for the locker ID with the fewest locks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy..::.MIN_LOCKS Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LockStats" /><meta name="guid" content="Properties_T_BerkeleyDB_LockStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LockStats" /><MSHelp:TOCTitle Title="LockStats Properties " /><MSHelp:RLTitle Title="LockStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LockStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="LockStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" />
<input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">LockStats Properties </td></tr><tr id="headerTableRow3"><td
align="left">LockStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and the secondary key and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RecnoDatabase" /><meta name="guid" content="T_BerkeleyDB_RecnoDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RecnoDatabase" /><MSHelp:TOCTitle Title="RecnoDatabase Class" /><MSHelp:RLTitle Title="RecnoDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RecnoDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoDatabase class" /><MSHelp:Keyword Index="K" Term="RecnoDatabase class, about RecnoDatabase class" /><MSHelp:Keyword Index="F" Term="RecnoDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a RecnoDatabase.
The Recno format supports fixed- or variable-length records, accessed sequentially or by logical record number, and optionally backed by a flat text file." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveLast" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveLast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveLastTopic" /><MSHelp:Keyword Index="K" Term="MoveLast method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveLast method" /><MSHelp:Keyword Index="F" Term="MoveLast" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveLast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RecnoCursor<span
class="cs">..::<span
class="nu">.MoveLast Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoCursor.htm">RecnoCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>SendRequest Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_DbChannel_SendRequest" /><meta name="guid"
content="Overload_BerkeleyDB_DbChannel_SendRequest"
/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DbChannel.SendRequest"
/><MSHelp:TOCTitle Title="SendRequest Method " /><MSHelp:RLTitle Title="DbChannel.SendRequest Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DbChannel.SendRequest"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelClassSendRequestTopic"
/><MSHelp:Keyword Index="K" Term="SendRequest method" /><MSHelp:Keyword Index="K"
Term="DbChannel.SendRequest method" /><MSHelp:Keyword Index="F" Term="SendRequest"
/><MSHelp:Keyword Index="F" Term="DbChannel.SendRequest" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DbChannel.SendRequest" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.SendRequest Method </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Private Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Private" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Private" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Private" /><MSHelp:TOCTitle Title="Private Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Private Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Private" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrivateTopic" /><MSHelp:Keyword Index="K" Term="Private property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Private property" /><MSHelp:Keyword Index="F" Term="Private" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Private" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Private" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Private" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Private" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, allocate region memory from the heap instead of from memory backed by the filesystem or system shared memory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"

class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Private Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_Database_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="Database.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.GetBoth" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="Database.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="Database.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database.<span

class="vb">.::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesRead Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_PagesRead" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_PagesRead" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.PagesRead" /><MSHelp:TOCTitle Title="PagesRead Property " /><MSHelp:RLTitle Title="MPoolFileStats.PagesRead Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.PagesRead" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassPagesReadTopic" /><MSHelp:Keyword Index="K" Term="PagesRead property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.PagesRead property" /><MSHelp:Keyword Index="F" Term="PagesRead" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.PagesRead" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.PagesRead" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.PagesRead" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_PagesRead" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages read in." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.PagesRead Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FileName Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_FileName" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_FileName" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.FileName" /><MSHelp:TOCTitle Title="FileName Property " /><MSHelp:RLTitle Title="MPoolFileStats.FileName Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.FileName" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassFileNameTopic" /><MSHelp:Keyword Index="K" Term="FileName property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.FileName property" /><MSHelp:Keyword Index="F" Term="FileName" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.FileName" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.FileName" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.MPoolFileStats.FileName" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolFileStats.get_FileName" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="File name."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">MPoolFileStats<span
class="languageSpecificText">..<span
class="cpp">::.FileName Property </td></tr><tr
id="headerTableRow3"><td align="left">MPoolFileStats
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QUORUM Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css"
href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_AckPolicy_QUORUM" /><meta name="guid" content="F_BerkeleyDB_AckPolicy_QUORUM" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.AckPolicy.QUORUM" /><MSHelp:TOCTitle Title="QUORUM Field" /><MSHelp:RLTitle Title="AckPolicy.QUORUM Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.AckPolicy.QUORUM" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBAckPolicyClassQUORUMTopic" /><MSHelp:Keyword Index="K" Term="QUORUM field" /><MSHelp:Keyword Index="K" Term="AckPolicy.QUORUM field" /><MSHelp:Keyword Index="F" Term="QUORUM" /><MSHelp:Keyword Index="F" Term="AckPolicy.QUORUM" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy.QUORUM" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.AckPolicy.QUORUM" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The master should wait until it has received acknowledgements from the minimum number of electable peers sufficient to ensure that the effect of the permanent record remains durable if an election is
..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">AckPolicy.<span
class="vb">.::.QUORUM
Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_AckPolicy.htm">AckPolicy Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionNoWait Property </title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_MutexStats_RegionNoWait" /><meta name="guid"
content="P_BerkeleyDB_MutexStats_RegionNoWait" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MutexStats.RegionNoWait"
/><MSHelp:TOCTitle Title="RegionNoWait Property " /><MSHelp:RLTitle Title="MutexStats.RegionNoWait
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.RegionNoWait"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassRegionNoWaitTopic"
/><MSHelp:Keyword Index="K" Term="RegionNoWait property" /><MSHelp:Keyword Index="K"
Term="MutexStats.RegionNoWait property" /><MSHelp:Keyword Index="F" Term="RegionNoWait"
/><MSHelp:Keyword Index="F" Term="MutexStats.RegionNoWait" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MutexStats.RegionNoWait" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MutexStats.RegionNoWait" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MutexStats.get_RegionNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.RegionNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_CacheSize" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_CacheSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.CacheSize" /><MSHelp:TOCTitle Title="CacheSize Property " /><MSHelp:RLTitle Title="BaseDatabase.CacheSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.CacheSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassCacheSizeTopic" /><MSHelp:Keyword Index="K" Term="CacheSize property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.CacheSize property" /><MSHelp:Keyword Index="F" Term="CacheSize" /><MSHelp:Keyword Index="F" Term="BaseDatabase.CacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.CacheSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.CacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_CacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the shared memory buffer pool -- that is, the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.CacheSize Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>End Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactData_End" /><meta name="guid" content="P_BerkeleyDB_CompactData_End" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactData.End" /><MSHelp:TOCTitle Title="End Property " /><MSHelp:RLTitle Title="CompactData.End Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactData.End" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassEndTopic" /><MSHelp:Keyword Index="K" Term="End property" /><MSHelp:Keyword Index="K" Term="CompactData.End property" /><MSHelp:Keyword Index="F" Term="End" /><MSHelp:Keyword Index="F" Term="CompactData.End" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData.End" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.End" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.get_End" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database key marking the end of the compaction operation. This is generally the first key of the page where the operation stopped and is only non-null if was true." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">CompactData.<span
class="vb">.::<span
class="nu">.End Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_CompactData.htm">CompactData Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>KeyExistException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_KeyExistException" /><meta name="guid"
content="Methods_T_BerkeleyDB_KeyExistException" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.KeyExistException" /><MSHelp:TOCTitle Title="KeyExistException Methods "
/><MSHelp:RLTitle Title="KeyExistException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Methods.T:BerkeleyDB.KeyExistException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBKeyExistExceptionMethodsTopic"
/><MSHelp:Keyword Index="K" Term="KeyExistException class, methods" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
/> <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyExistException Methods </td></tr><tr id="headerTableRow3"><td align="left">KeyExistException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Refresh_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Refresh_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the secondary key and primary key/data pair to which the cursor refers in . If , or , or is partial , its bytes starting bytes from the beginning of ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Refresh Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Bytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="P_BerkeleyDB_LogStats_Bytes" /><meta name="guid" content="P_BerkeleyDB_LogStats_Bytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.Bytes" /><MSHelp:TOCTitle Title="Bytes Property " /><MSHelp:RLTitle Title="LogStats.Bytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.Bytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassBytesTopic" /><MSHelp:Keyword Index="K" Term="Bytes property" /><MSHelp:Keyword Index="K" Term="LogStats.Bytes property" /><MSHelp:Keyword Index="F" Term="Bytes" /><MSHelp:Keyword
Index="F" Term="LogStats.Bytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.Bytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.Bytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_Bytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes to log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.Bytes Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ResetLSN Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_ResetLSN" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_ResetLSN" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.ResetLSN(System.String,System.Boolean)" /><MSHelp:TOCTitle Title="ResetLSN Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.ResetLSN Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.ResetLSN(System.String,System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassResetLSNTopic" /><MSHelp:Keyword Index="K" Term="ResetLSN method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ResetLSN method" /><MSHelp:Keyword Index="F" Term="ResetLSN" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ResetLSN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ResetLSN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ResetLSN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Allow database files to be moved from one transactional database environment to another." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table

id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ResetLSN Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PartitionLockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_PartitionLockWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_PartitionLockWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.PartitionLockWait" /><MSHelp:TOCTitle Title="PartitionLockWait Property " /><MSHelp:RLTitle Title="LockStats.PartitionLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.PartitionLockWait" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBLockStatsClassPartitionLockWaitTopic" /><MSHelp:Keyword Index="K" Term="PartitionLockWait property" /><MSHelp:Keyword Index="K" Term="LockStats.PartitionLockWait property" /><MSHelp:Keyword Index="F" Term="PartitionLockWait" /><MSHelp:Keyword Index="F" Term="LockStats.PartitionLockWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.PartitionLockWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.PartitionLockWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_PartitionLockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Partition lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.PartitionLockWait Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_LockStats.htm">LockStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
 xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordDelimiter
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_RecnoDatabase_RecordDelimiter" /><meta name="guid"
content="P_BerkeleyDB_RecnoDatabase_RecordDelimiter" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.RecnoDatabase.RecordDelimiter" /><MSHelp:TOCTitle Title="RecordDelimiter Property "
/><MSHelp:RLTitle Title="RecnoDatabase.RecordDelimiter Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.RecnoDatabase.RecordDelimiter" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoDatabaseClassRecordDelimiterTopic" /><MSHelp:Keyword Index="K"
Term="RecordDelimiter property" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.RecordDelimiter
property" /><MSHelp:Keyword Index="F" Term="RecordDelimiter" /><MSHelp:Keyword Index="F"
Term="RecnoDatabase.RecordDelimiter" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoDatabase.RecordDelimiter" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation"
 Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.RecordDelimiter" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.get_RecordDelimiter" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.set_RecordDelimiter" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The delimiting
byte used to mark the end of a record in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
 height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoDatabase.<span
class="vb">.::.RecordDelimiter
Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoDatabase.htm">RecnoDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>QueuedMessages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_RepMgrStats_QueuedMessages" /><meta name="guid"
content="P_BerkeleyDB_RepMgrStats_QueuedMessages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.RepMgrStats.QueuedMessages" /><MSHelp:TOCTitle Title="QueuedMessages Property "
/><MSHelp:RLTitle Title="RepMgrStats.QueuedMessages Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.RepMgrStats.QueuedMessages" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRepMgrStatsClassQueuedMessagesTopic"
/><MSHelp:Keyword Index="K" Term="QueuedMessages property" /><MSHelp:Keyword Index="K"
Term="RepMgrStats.QueuedMessages property" /><MSHelp:Keyword Index="F" Term="QueuedMessages"

/><MSHelp:Keyword Index="F" Term="RepMgrStats.QueuedMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats.QueuedMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.QueuedMessages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.get_QueuedMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# msgs queued for network delay." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats..::.QueuedMessages Property </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_MPoolSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_MPoolSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:TOCTitle Title="MPoolSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.MPoolSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMPoolSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="MPoolSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MPoolSystemStats method" /><MSHelp:Keyword Index="F" Term="MPoolSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MPoolSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span
class="nu">.MPoolSystemStats Method </td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Compare Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_LSN_Compare" /><meta name="guid" content="M_BerkeleyDB_LSN_Compare"
/><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.LSN.Compare(BerkeleyDB.LSN,BerkeleyDB.LSN)" /><MSHelp:TOCTitle Title="Compare Method " /><MSHelp:RLTitle Title="LSN.Compare Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LSN.Compare(BerkeleyDB.LSN,BerkeleyDB.LSN)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare method" /><MSHelp:Keyword Index="K" Term="LSN.Compare method" /><MSHelp:Keyword Index="F" Term="Compare" /><MSHelp:Keyword Index="F" Term="LSN.Compare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LSN.Compare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LSN.Compare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Compare two LSNs." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN..::.Compare Method </td></tr><tr

id="headerTableRow3"><td align="left">LSN Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
 xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Delimiter Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
 /><meta name="file" content="P_BerkeleyDB_SecondaryRecnoDatabaseConfig_Delimiter" /><meta name="guid"
content="P_BerkeleyDB_SecondaryRecnoDatabaseConfig_Delimiter" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryRecnoDatabaseConfig.Delimiter" /><MSHelp:TOCTitle Title="Delimiter
Property " /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.Delimiter Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabaseConfig.Delimiter"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassDelimiterTopic"
/><MSHelp:Keyword Index="K" Term="Delimiter property" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig.Delimiter property" /><MSHelp:Keyword Index="F" Term="Delimiter"
/><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.Delimiter" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.Delimiter" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation"
 Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.Delimiter" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.get_Delimiter" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.set_Delimiter" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The delimiting byte used to mark the end of a record in ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
 height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryRecnoDatabaseConfig<span
class="cs">..::<span
class="nu">.Delimiter Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryRecnoDatabaseConfig.htm">SecondaryRecnoDatabaseConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>NewSiteMessages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_ReplicationStats_NewSiteMessages" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_NewSiteMessages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.NewSiteMessages" /><MSHelp:TOCTitle Title="NewSiteMessages
Property " /><MSHelp:RLTitle Title="ReplicationStats.NewSiteMessages Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.NewSiteMessages"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassNewSiteMessagesTopic"
/><MSHelp:Keyword Index="K" Term="NewSiteMessages property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.NewSiteMessages property" /><MSHelp:Keyword Index="F" Term="NewSiteMessages"

/><MSHelp:Keyword Index="F" Term="ReplicationStats.NewSiteMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.NewSiteMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.NewSiteMessages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_NewSiteMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of NEWSITE msgs. received." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.NewSiteMessages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_RegionSize" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="TransactionStats.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="TransactionStats.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="TransactionStats.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>

<label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="HashDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="HashDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::<span

class="nu">.Close Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Constructor (SequenceConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence__ctor" /><meta name="guid" content="M_BerkeleyDB_Sequence__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.#ctor(BerkeleyDB.SequenceConfig)" /><MSHelp:TOCTitle Title="Sequence Constructor (SequenceConfig)" /><MSHelp:RLTitle Title="Sequence Constructor (SequenceConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.#ctor(BerkeleyDB.SequenceConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new Sequence object." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence Constructor (SequenceConfig)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>fromArray Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapRecordId_fromArray" /><meta name="guid" content="Overload_BerkeleyDB_HeapRecordId_fromArray" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapRecordId.fromArray" /><MSHelp:TOCTitle Title="fromArray Method " /><MSHelp:RLTitle Title="HeapRecordId.fromArray Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapRecordId.fromArray" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdClassfromArrayTopic" /><MSHelp:Keyword Index="K" Term="fromArray method" /><MSHelp:Keyword Index="K" Term="HeapRecordId.fromArray method" /><MSHelp:Keyword Index="F" Term="fromArray" /><MSHelp:Keyword Index="F" Term="HeapRecordId.fromArray" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId.fromArray" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HeapRecordId<span
class="cs">..::<span
class="nu">.fromArray Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HeapRecordId.htm">HeapRecordId Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryHashDatabaseConfig Fields" /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogVerifyConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LogVerifyConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_LogVerifyConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LogVerifyConfig" /><MSHelp:TOCTitle Title="LogVerifyConfig Properties " /><MSHelp:RLTitle Title="LogVerifyConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LogVerifyConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigPropertiesTopic" /><MSHelp:Keyword Index="K"

Term="LogVerifyConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashFunctionDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HashFunctionDelegate" /><meta name="guid" content="T_BerkeleyDB_HashFunctionDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HashFunctionDelegate" /><MSHelp:TOCTitle Title="HashFunctionDelegate Delegate" /><MSHelp:RLTitle Title="HashFunctionDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HashFunctionDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashFunctionDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="HashFunctionDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashFunctionDelegate delegate" /><MSHelp:Keyword Index="F" Term="HashFunctionDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashFunctionDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashFunctionDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashFunctionDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashFunctionDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashFunctionDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashFunctionDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The application-specified hash function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C#
</nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">HashFunctionDelegate
Delegate</td></tr><tr id="headerTableRow3"><td align="left"><a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ExtentSize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabaseConfig_ExtentSize" /><meta
name="guid" content="P_BerkeleyDB_QueueDatabaseConfig_ExtentSize" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.QueueDatabaseConfig.ExtentSize" /><MSHelp:TOCTitle
Title="ExtentSize Property " /><MSHelp:RLTitle Title="QueueDatabaseConfig.ExtentSize Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabaseConfig.ExtentSize"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassExtentSizeTopic"
/><MSHelp:Keyword Index="K" Term="ExtentSize property" /><MSHelp:Keyword Index="K"

Term="QueueDatabaseConfig.ExtentSize property" /><MSHelp:Keyword Index="F" Term="ExtentSize" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig.ExtentSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig.ExtentSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.ExtentSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.get_ExtentSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.set_ExtentSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the extents used to hold pages in a , specified as a number of pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig..::.ExtentSize Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_QueueDatabaseConfig.htm">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataDir Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_MetadataDir" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_MetadataDir" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.MetadataDir" /><MSHelp:TOCTitle Title="MetadataDir Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.MetadataDir Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.MetadataDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassMetadataDirTopic" /><MSHelp:Keyword Index="K" Term="MetadataDir field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.MetadataDir field" /><MSHelp:Keyword Index="F" Term="MetadataDir" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.MetadataDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.MetadataDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.MetadataDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of a directory to be used as the location to store the persistent metadata." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.MetadataDir Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabase Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_RecnoDatabase" /><meta name="guid" content="Properties_T_BerkeleyDB_RecnoDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.RecnoDatabase" /><MSHelp:TOCTitle Title="RecnoDatabase Properties " /><MSHelp:RLTitle Title="RecnoDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.RecnoDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashFunction Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_HashFunction" /><meta name="guid" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_HashFunction" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryHashDatabaseConfig.HashFunction" /><MSHelp:TOCTitle Title="HashFunction Field" /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.HashFunction Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryHashDatabaseConfig.HashFunction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassHashFunctionTopic" /><MSHelp:Keyword Index="K" Term="HashFunction field" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.HashFunction field" /><MSHelp:Keyword Index="F" Term="HashFunction" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.HashFunction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.HashFunction" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.HashFunction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A user-defined hash function; if no hash function is specified, a default hash function is used." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.HashFunction Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveLast" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="HashCursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveLast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveLastTopic" /><MSHelp:Keyword Index="K" Term="MoveLast method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveLast method" /><MSHelp:Keyword Index="F" Term="MoveLast" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveLast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::<span

class="nu">.MoveLast
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashCursor.htm">HashCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>ElectionGenerationNumber Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ReplicationStats_ElectionGenerationNumber" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_ElectionGenerationNumber" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.ElectionGenerationNumber" /><MSHelp:TOCTitle
Title="ElectionGenerationNumber Property " /><MSHelp:RLTitle
Title="ReplicationStats.ElectionGenerationNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ReplicationStats.ElectionGenerationNumber"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionGenerationNumberTopic"
/><MSHelp:Keyword Index="K" Term="ElectionGenerationNumber property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.ElectionGenerationNumber property" /><MSHelp:Keyword Index="F"
Term="ElectionGenerationNumber" /><MSHelp:Keyword Index="F"
Term="ReplicationStats.ElectionGenerationNumber" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationStats.ElectionGenerationNumber" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionGenerationNumber" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionGenerationNumber" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Election generation number."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"

title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionGenerationNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Address Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_Address" /><meta name="guid" content="P_BerkeleyDB_DbSite_Address" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSite.Address" /><MSHelp:TOCTitle Title="Address Property " /><MSHelp:RLTitle Title="DbSite.Address Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.DbSite.Address" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDbSiteClassAddressTopic" /><MSHelp:Keyword Index="K" Term="Address property"
/><MSHelp:Keyword Index="K" Term="DbSite.Address property" /><MSHelp:Keyword Index="F"
Term="Address" /><MSHelp:Keyword Index="F" Term="DbSite.Address" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DbSite.Address" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSite.Address" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSite.get_Address" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The host and port of the site." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DbSite.<span
class="vb">.::.Address Property

</td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Open" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Open(System.String,BerkeleyDB.DatabaseEnvironmentConfig)" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Open(System.String,BerkeleyDB.DatabaseEnvironmentConfig)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Open" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new DatabaseEnvironment object and open the Berkeley DB environment represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BadSecondaryException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BadSecondaryException" /><meta name="guid" content="T_BerkeleyDB_BadSecondaryException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BadSecondaryException" /><MSHelp:TOCTitle Title="BadSecondaryException Class" /><MSHelp:RLTitle Title="BadSecondaryException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BadSecondaryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBadSecondaryExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="BadSecondaryException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BadSecondaryException class" /><MSHelp:Keyword Index="K"

Term="BadSecondaryException class, about BadSecondaryException class" /><MSHelp:Keyword Index="F" Term="BadSecondaryException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BadSecondaryException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BadSecondaryException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A secondary index has been corrupted. This is likely the result of an application operating on related databases without first associating them." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BadSecondaryException Class</td></tr><tr id="headerTableRow3"><td align="left">Members <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNextUnique" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNextUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextUnique" /><MSHelp:TOCTitle Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextUniqueTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUnique method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNextUnique method" /><MSHelp:Keyword Index="F" Term="MoveNextUnique" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AutoCommit Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_AutoCommit" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_AutoCommit" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.AutoCommit" /><MSHelp:TOCTitle Title="AutoCommit Property " /><MSHelp:RLTitle Title="BaseDatabase.AutoCommit Property (BerkeleyDB)" /><MSHelp:Keyword

Index="A" Term="P:BerkeleyDB.BaseDatabase.AutoCommit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassAutoCommitTopic" /><MSHelp:Keyword Index="K" Term="AutoCommit property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.AutoCommit property" /><MSHelp:Keyword Index="F" Term="AutoCommit" /><MSHelp:Keyword Index="F" Term="BaseDatabase.AutoCommit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.AutoCommit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.AutoCommit" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_AutoCommit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, all database modification operations based on this object will be transactionally protected." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase<span

class="cs">..::.AutoCommit Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNextDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNextDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextDuplicate" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicate method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNextDuplicate method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseType Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DatabaseType" /><meta name="guid" content="T_BerkeleyDB_DatabaseType" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DatabaseType" /><MSHelp:TOCTitle Title="DatabaseType Class" /><MSHelp:RLTitle Title="DatabaseType Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DatabaseType" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassTopic" /><MSHelp:Keyword Index="K" Term="DatabaseType class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseType class" /><MSHelp:Keyword Index="K" Term="DatabaseType class, about DatabaseType class" /><MSHelp:Keyword Index="F" Term="DatabaseType" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing the supported Berkeley DB access methods." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">DatabaseType Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite Method (String, UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSite_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSite_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrSite(System.String,System.UInt32)" /><MSHelp:TOCTitle Title="RepMgrSite Method (String, UInt32)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrSite Method (String, UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrSite(System.String,System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrSite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create DbSite with the given host and port." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.RepMgrSite Method (String,
UInt32)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>LockerNoWait Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockerNoWait" /><meta
name="guid" content="P_BerkeleyDB_LockStats_LockerNoWait" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.LockerNoWait" /><MSHelp:TOCTitle Title="LockerNoWait Property "
/><MSHelp:RLTitle Title="LockStats.LockerNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockStats.LockerNoWait" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassLockerNoWaitTopic" /><MSHelp:Keyword Index="K"
Term="LockerNoWait property" /><MSHelp:Keyword Index="K" Term="LockStats.LockerNoWait property"
/><MSHelp:Keyword Index="F" Term="LockerNoWait" /><MSHelp:Keyword Index="F"
Term="LockStats.LockerNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockerNoWait"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockerNoWait"
/><MSHelp:Attr

Name="APIName" Value="BerkeleyDB.LockStats.get_LockerNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Locker lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockerNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrRemoteSites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrRemoteSites" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrRemoteSites" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepMgrRemoteSites" /><MSHelp:TOCTitle Title="RepMgrRemoteSites Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrRemoteSites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepMgrRemoteSites" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrRemoteSitesTopic" /><MSHelp:Keyword Index="K" Term="RepMgrRemoteSites property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrRemoteSites property" /><MSHelp:Keyword Index="F" Term="RepMgrRemoteSites" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrRemoteSites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrRemoteSites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrRemoteSites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepMgrRemoteSites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The status of the sites currently known by the replication manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment..::.RepMgrRemoteSites Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (DatabaseEntry)</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetMultiple" /><meta name="guid" content="M_BerkeleyDB_Database_GetMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="GetMultiple Method (DatabaseEntry)"
/><MSHelp:RLTitle Title="Database.GetMultiple Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)"
tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">.<span
class="vb">.::.GetMultiple Method
(DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MBytes
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_MBytes" /><meta name="guid" content="P_BerkeleyDB_LogStats_MBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.MBytes" /><MSHelp:TOCTitle Title="MBytes Property " /><MSHelp:RLTitle Title="LogStats.MBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.MBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassMBytesTopic" /><MSHelp:Keyword Index="K" Term="MBytes property" /><MSHelp:Keyword Index="K" Term="LogStats.MBytes property" /><MSHelp:Keyword Index="F" Term="MBytes" /><MSHelp:Keyword Index="F" Term="LogStats.MBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.MBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.MBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_MBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Megabytes to log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.MBytes Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BTreeDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_BTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.BTreeDatabase" /><MSHelp:TOCTitle Title="BTreeDatabase Members" /><MSHelp:RLTitle Title="BTreeDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BTreeDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabase class" /><MSHelp:Keyword Index="K" Term="BTreeDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeDatabase class" /><MSHelp:Keyword Index="F" Term="BTreeDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class Methods Properties See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoWaitDbExclusiveLock Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_NoWaitDbExclusiveLock" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_NoWaitDbExclusiveLock" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.NoWaitDbExclusiveLock" /><MSHelp:TOCTitle Title="NoWaitDbExclusiveLock Field" /><MSHelp:RLTitle Title="DatabaseConfig.NoWaitDbExclusiveLock Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.NoWaitDbExclusiveLock" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassNoWaitDbExclusiveLockTopic" /><MSHelp:Keyword Index="K" Term="NoWaitDbExclusiveLock field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.NoWaitDbExclusiveLock field" /><MSHelp:Keyword Index="F" Term="NoWaitDbExclusiveLock" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.NoWaitDbExclusiveLock" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.NoWaitDbExclusiveLock" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.NoWaitDbExclusiveLock" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration of handle to obtain a write lock on the entire database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.NoWaitDbExclusiveLock Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LockStats" /><meta name="guid" content="Methods_T_BerkeleyDB_LockStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LockStats" /><MSHelp:TOCTitle Title="LockStats Methods " /><MSHelp:RLTitle Title="LockStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LockStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="LockStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input
type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats Methods </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TableSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabase_TableSize" /><meta name="guid" content="P_BerkeleyDB_HashDatabase_TableSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabase.TableSize" /><MSHelp:TOCTitle Title="TableSize Property " /><MSHelp:RLTitle Title="HashDatabase.TableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabase.TableSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassTableSizeTopic" /><MSHelp:Keyword Index="K" Term="TableSize property" /><MSHelp:Keyword Index="K" Term="HashDatabase.TableSize property" /><MSHelp:Keyword Index="F" Term="TableSize" /><MSHelp:Keyword Index="F" Term="HashDatabase.TableSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.TableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.get_TableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An estimate of the final size of the hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.TableSize Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockDowngrades Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockDowngrades" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockDowngrades" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockDowngrades" /><MSHelp:TOCTitle Title="LockDowngrades Property " /><MSHelp:RLTitle Title="LockStats.LockDowngrades Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockDowngrades" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockDowngradesTopic" /><MSHelp:Keyword Index="K" Term="LockDowngrades property" /><MSHelp:Keyword Index="K" Term="LockStats.LockDowngrades property" /><MSHelp:Keyword Index="F" Term="LockDowngrades" /><MSHelp:Keyword Index="F" Term="LockStats.LockDowngrades" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockDowngrades" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockDowngrades" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockDowngrades" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lock downgrades." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockDowngrades Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_PutNoOverwrite" /><meta name="guid" content="Overload_BerkeleyDB_Database_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.PutNoOverwrite" /><MSHelp:TOCTitle Title="PutNoOverwrite Method " /><MSHelp:RLTitle Title="Database.PutNoOverwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.PutNoOverwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassPutNoOverwriteTopic" /><MSHelp:Keyword Index="K" Term="PutNoOverwrite method" /><MSHelp:Keyword Index="K" Term="Database.PutNoOverwrite method"

/><MSHelp:Keyword Index="F" Term="PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="Database.PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this,

'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.PutNoOverwrite Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordNumbers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_RecordNumbers" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_RecordNumbers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.RecordNumbers" /><MSHelp:TOCTitle Title="RecordNumbers Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.RecordNumbers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.RecordNumbers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassRecordNumbersTopic" /><MSHelp:Keyword Index="K" Term="RecordNumbers property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.RecordNumbers property" /><MSHelp:Keyword Index="F" Term="RecordNumbers" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.RecordNumbers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.RecordNumbers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.RecordNumbers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_RecordNumbers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, this object supports retrieval from the Btree using record numbers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.RecordNumbers Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveMultipleKey"

/><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveMultipleKey" /><MSHelp:TOCTitle Title="MoveMultipleKey Method " /><MSHelp:RLTitle Title="HashCursor.MoveMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveMultipleKey method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveMultipleKey" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HashCursor.<span
class="vb">.::.MoveMultipleKey Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashCursor.htm">HashCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact
Method (CompactConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_HashDatabase_Compact" /><meta name="guid"
content="M_BerkeleyDB_HashDatabase_Compact" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashDatabase.Compact(BerkeleyDB.CompactConfig)" /><MSHelp:TOCTitle
Title="Compact Method (CompactConfig)" /><MSHelp:RLTitle Title="HashDatabase.Compact Method
(CompactConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.HashDatabase.Compact(BerkeleyDB.CompactConfig)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.HashDatabase.Compact" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Compact the database, and optionally return unused database pages to the underlying filesystem."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Compact Method (CompactConfig)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_PageSize" /><meta name="guid"

content="P_BerkeleyDB_HashStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="HashStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="HashStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="HashStats.PageSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td

align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AutoCommit Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_AutoCommit" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_AutoCommit" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.AutoCommit" /><MSHelp:TOCTitle Title="AutoCommit Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.AutoCommit Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.AutoCommit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassAutoCommitTopic" /><MSHelp:Keyword Index="K" Term="AutoCommit field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.AutoCommit field" /><MSHelp:Keyword Index="F" Term="AutoCommit" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.AutoCommit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.AutoCommit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.AutoCommit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, database operations for which no explicit transaction handle was specified, and which modify databases in the database environment, will be automatically enclosed within a transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.AutoCommit Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackingFile Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryRecnoDatabase_BackingFile" /><meta name="guid" content="P_BerkeleyDB_SecondaryRecnoDatabase_BackingFile" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryRecnoDatabase.BackingFile" /><MSHelp:TOCTitle Title="BackingFile Property " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.BackingFile Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabase.BackingFile" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassBackingFileTopic"

/><MSHelp:Keyword Index="K" Term="BackingFile property" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.BackingFile property" /><MSHelp:Keyword Index="F" Term="BackingFile" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.BackingFile" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.BackingFile" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.BackingFile" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.get_BackingFile" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The underlying source file for the Recno access method." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase<span

class="cs">..::.BackingFile Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrev_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrev_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MovePrev Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MovePrev Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store that pair in . In the presence of duplicate key ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrev Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetRange Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SequenceConfig_SetRange" /><meta name="guid" content="M_BerkeleyDB_SequenceConfig_SetRange" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SequenceConfig.SetRange(System.Int64,System.Int64)" /><MSHelp:TOCTitle Title="SetRange Method " /><MSHelp:RLTitle Title="SequenceConfig.SetRange Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SequenceConfig.SetRange(System.Int64,System.Int64)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassSetRangeTopic" /><MSHelp:Keyword Index="K" Term="SetRange method" /><MSHelp:Keyword Index="K" Term="SequenceConfig.SetRange method" /><MSHelp:Keyword Index="F" Term="SetRange" /><MSHelp:Keyword Index="F" Term="SequenceConfig.SetRange" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.SetRange" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.SetRange" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Set the minimum and maximum values in the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.SetRange Method </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepHeartbeatMonitor Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepHeartbeatMonitor" /><meta
name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepHeartbeatMonitor" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepHeartbeatMonitor" /><MSHelp:TOCTitle Title="RepHeartbeatMonitor Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepHeartbeatMonitor Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepHeartbeatMonitor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepHeartbeatMonitorTopic" /><MSHelp:Keyword Index="K" Term="RepHeartbeatMonitor property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepHeartbeatMonitor property" /><MSHelp:Keyword Index="F" Term="RepHeartbeatMonitor" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepHeartbeatMonitor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepHeartbeatMonitor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepHeartbeatMonitor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepHeartbeatMonitor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepHeartbeatMonitor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time the replication manager, running at a client site, waits for some message activity on the connection from the master (heartbeats or other messages) before concluding that the con ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,

event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepHeartbeatMonitor Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PartialOffset Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEntry_PartialOffset" /><meta name="guid" content="P_BerkeleyDB_DatabaseEntry_PartialOffset" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEntry.PartialOffset" /><MSHelp:TOCTitle Title="PartialOffset Property " /><MSHelp:RLTitle Title="DatabaseEntry.PartialOffset Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEntry.PartialOffset" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassPartialOffsetTopic" /><MSHelp:Keyword Index="K" Term="PartialOffset property" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.PartialOffset property" /><MSHelp:Keyword Index="F" Term="PartialOffset" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.PartialOffset" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.DatabaseEntry.PartialOffset" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.PartialOffset" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.get_PartialOffset" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.set_PartialOffset" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The offset of the partial record being read or written by the application, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry..::.PartialOffset Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Abort Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Transaction_Abort" /><meta name="guid" content="M_BerkeleyDB_Transaction_Abort" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Transaction.Abort" /><MSHelp:TOCTitle Title="Abort Method " /><MSHelp:RLTitle Title="Transaction.Abort Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Transaction.Abort" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassAbortTopic" /><MSHelp:Keyword Index="K" Term="Abort method" /><MSHelp:Keyword Index="K" Term="Transaction.Abort method" /><MSHelp:Keyword Index="F" Term="Abort" /><MSHelp:Keyword Index="F" Term="Transaction.Abort" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Abort" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Abort" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Cause an abnormal termination of the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Abort Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoReverseSplitting Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BTreeDatabaseConfig_NoReverseSplitting" /><meta name="guid" content="F_BerkeleyDB_BTreeDatabaseConfig_NoReverseSplitting" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:TOCTitle Title="NoReverseSplitting Field" /><MSHelp:RLTitle Title="BTreeDatabaseConfig.NoReverseSplitting Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassNoReverseSplittingTopic" /><MSHelp:Keyword Index="K" Term="NoReverseSplitting field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.NoReverseSplitting field" /><MSHelp:Keyword Index="F" Term="NoReverseSplitting" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Turn reverse splitting in the Btree on or off." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.NoReverseSplitting Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>TxnWriteNoSync Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TxnWriteNoSync" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TxnWriteNoSync" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TxnWriteNoSync" /><MSHelp:TOCTitle Title="TxnWriteNoSync Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TxnWriteNoSync Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TxnWriteNoSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTxnWriteNoSyncTopic" /><MSHelp:Keyword Index="K" Term="TxnWriteNoSync property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TxnWriteNoSync property" /><MSHelp:Keyword Index="F" Term="TxnWriteNoSync" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TxnWriteNoSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TxnWriteNoSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TxnWriteNoSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TxnWriteNoSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TxnWriteNoSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="If true, Berkeley DB will write, but will not synchronously flush, the log on transaction commit." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TxnWriteNoSync Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnNoSync Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TxnNoSync" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TxnNoSync" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TxnNoSync" /><MSHelp:TOCTitle Title="TxnNoSync Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TxnNoSync Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TxnNoSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTxnNoSyncTopic" /><MSHelp:Keyword Index="K" Term="TxnNoSync property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TxnNoSync property" /><MSHelp:Keyword Index="F" Term="TxnNoSync" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TxnNoSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TxnNoSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TxnNoSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TxnNoSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TxnNoSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will not write or synchronously flush the log on transaction commit." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TxnNoSync Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_RefreshMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_RefreshMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.RefreshMultipleKey" /><MSHelp:TOCTitle Title="RefreshMultipleKey Method " /><MSHelp:RLTitle Title="BTreeCursor.RefreshMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.RefreshMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassRefreshMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="RefreshMultipleKey method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.RefreshMultipleKey method" /><MSHelp:Keyword Index="F" Term="RefreshMultipleKey" /><MSHelp:Keyword Index="F" Term="BTreeCursor.RefreshMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.RefreshMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_PageSize" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="RecnoStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="RecnoStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="RecnoStats.PageSize" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.RecnoStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
 class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"
 cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
 style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API
 Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSize
Field</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseConfig_CacheSize" /><meta name="guid"
content="F_BerkeleyDB_DatabaseConfig_CacheSize" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseConfig.CacheSize" /><MSHelp:TOCTitle Title="CacheSize Field"
/><MSHelp:RLTitle Title="DatabaseConfig.CacheSize
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.CacheSize"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassCacheSizeTopic"
/><MSHelp:Keyword Index="K" Term="CacheSize field" /><MSHelp:Keyword Index="K"
Term="DatabaseConfig.CacheSize field" /><MSHelp:Keyword Index="F" Term="CacheSize"
/><MSHelp:Keyword Index="F" Term="DatabaseConfig.CacheSize" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseConfig.CacheSize" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseConfig.CacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the
shared memory
buffer pool -- that is, the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.CacheSize Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultipleKey Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultipleKey is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum a ..." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUniqueMultipleKey Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxPagesCheckedDuringAlloc Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MaxPagesCheckedDuringAlloc" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxPagesCheckedDuringAlloc" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxPagesCheckedDuringAlloc" /><MSHelp:TOCTitle Title="MaxPagesCheckedDuringAlloc Property " /><MSHelp:RLTitle Title="MPoolStats.MaxPagesCheckedDuringAlloc Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxPagesCheckedDuringAlloc" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxPagesCheckedDuringAllocTopic" /><MSHelp:Keyword Index="K" Term="MaxPagesCheckedDuringAlloc property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxPagesCheckedDuringAlloc property" /><MSHelp:Keyword Index="F" Term="MaxPagesCheckedDuringAlloc" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxPagesCheckedDuringAlloc" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxPagesCheckedDuringAlloc" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxPagesCheckedDuringAlloc" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxPagesCheckedDuringAlloc" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max checked during allocation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxPagesCheckedDuringAlloc Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesPerExtent Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_PagesPerExtent" /><meta name="guid" content="P_BerkeleyDB_QueueStats_PagesPerExtent" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.PagesPerExtent" /><MSHelp:TOCTitle Title="PagesPerExtent Property " /><MSHelp:RLTitle Title="QueueStats.PagesPerExtent Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.PagesPerExtent" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassPagesPerExtentTopic" /><MSHelp:Keyword Index="K" Term="PagesPerExtent property" /><MSHelp:Keyword Index="K" Term="QueueStats.PagesPerExtent property" /><MSHelp:Keyword Index="F" Term="PagesPerExtent" /><MSHelp:Keyword Index="F" Term="QueueStats.PagesPerExtent" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.PagesPerExtent" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.PagesPerExtent" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_PagesPerExtent" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages per extent." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">QueueStats.<span
class="vb">.::.PagesPerExtent Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_QueueStats.htm">QueueStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseConfig
Class</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_DatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DatabaseConfig" /><MSHelp:TOCTitle Title="DatabaseConfig Class" /><MSHelp:RLTitle Title="DatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseConfig class" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class, about DatabaseConfig class" /><MSHelp:Keyword Index="F" Term="DatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Get_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Get_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Get Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="BaseDatabase.Get Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database. In the presence of duplicate key values, Get will return the first data item for . If the data is a partial , bytes starting bytes ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><div

id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreePages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_FreePages" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_FreePages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.FreePages" /><MSHelp:TOCTitle

Title="FreePages Property " /><MSHelp:RLTitle Title="RecnoStats.FreePages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.FreePages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassFreePagesTopic" /><MSHelp:Keyword Index="K" Term="FreePages property" /><MSHelp:Keyword Index="K" Term="RecnoStats.FreePages property" /><MSHelp:Keyword Index="F" Term="FreePages" /><MSHelp:Keyword Index="F" Term="RecnoStats.FreePages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.FreePages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.FreePages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_FreePages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages on the free list." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.FreePages Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_RecnoStats.htm">RecnoStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
 xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>PrintMPoolSystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats"
 /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats"
/><MSHelp:TOCTitle Title="PrintMPoolSystemStats Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.PrintMPoolSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Display the memory pool (that
 is, buffer cache) subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
 /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.PrintMPoolSystemStats
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AddUnique
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_HashCursor_AddUnique" /><meta
name="guid" content="M_BerkeleyDB_HashCursor_AddUnique" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashCursor.AddUnique(System.Collections.Generic.KeyValuePair{BerkeleyDB.Database
Entry,BerkeleyDB.DatabaseEntry})" /><MSHelp:TOCTitle Title="AddUnique Method " /><MSHelp:RLTitle
Title="HashCursor.AddUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.HashCursor.AddUnique(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseE
ntry,BerkeleyDB.DatabaseEntry})" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashCursorClassAddUniqueTopic" /><MSHelp:Keyword Index="K" Term="AddUnique
method" /><MSHelp:Keyword Index="K" Term="HashCursor.AddUnique method" /><MSHelp:Keyword
Index="F" Term="AddUnique" /><MSHelp:Keyword Index="F" Term="HashCursor.AddUnique"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.AddUnique" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName"
Value="BerkeleyDB.HashCursor.AddUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Insert the specified key/data pair into the database, unless a key/data pair comparing equally to it already exists in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.AddUnique Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete"
/><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="HeapDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Cursor
method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapRecordId Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapRecordId__ctor" /><meta name="guid" content="M_BerkeleyDB_HeapRecordId__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapRecordId.#ctor(System.UInt32,System.UInt16)" /><MSHelp:TOCTitle Title="HeapRecordId Constructor " /><MSHelp:RLTitle Title="HeapRecordId Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapRecordId.#ctor(System.UInt32,System.UInt16)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdClassctorTopic" /><MSHelp:Keyword Index="K" Term="HeapRecordId class, constructor" /><MSHelp:Keyword Index="K" Term="HeapRecordId.HeapRecordId constructor" /><MSHelp:Keyword Index="F" Term="HeapRecordId" /><MSHelp:Keyword Index="F" Term="HeapRecordId.HeapRecordId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId.HeapRecordId" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Construct a new record id, given a page number and index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId Constructor </td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_GetMultiple" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_GetMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32)" /><MSHelp:TOCTitle Title="GetMultiple Method (UInt32)" /><MSHelp:RLTitle Title="BTreeDatabase.GetMultiple Method (UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.GetMultiple Method (UInt32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MovePrevDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="RecnoCursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMovePrevDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MovePrevDuplicate method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MovePrevDuplicate method" /><MSHelp:Keyword Index="F" Term="MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage" src="../icons/dropdown.gif"

/> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..<span
class="cpp">::.MovePrevDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BytesSinceCheckpoint Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_BytesSinceCheckpoint" /><meta name="guid" content="P_BerkeleyDB_LogStats_BytesSinceCheckpoint" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.BytesSinceCheckpoint" /><MSHelp:TOCTitle Title="BytesSinceCheckpoint Property " /><MSHelp:RLTitle Title="LogStats.BytesSinceCheckpoint Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.BytesSinceCheckpoint" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassBytesSinceCheckpointTopic" /><MSHelp:Keyword Index="K" Term="BytesSinceCheckpoint property" /><MSHelp:Keyword Index="K" Term="LogStats.BytesSinceCheckpoint property" /><MSHelp:Keyword Index="F" Term="BytesSinceCheckpoint" /><MSHelp:Keyword Index="F"

Term="LogStats.BytesSinceCheckpoint" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LogStats.BytesSinceCheckpoint" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogStats.BytesSinceCheckpoint" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogStats.get_BytesSinceCheckpoint" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes to log since
checkpoint." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">LogStats.<span
class="vb">.::.BytesSinceCheckpoint
Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LogStats.htm">LogStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerboseMessages Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_VerboseMessages" /><meta name="guid" content="AllMembers_T_BerkeleyDB_VerboseMessages" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.VerboseMessages" /><MSHelp:TOCTitle Title="VerboseMessages Members" /><MSHelp:RLTitle Title="VerboseMessages Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.VerboseMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesMembersTopic" /><MSHelp:Keyword Index="K" Term="VerboseMessages class" /><MSHelp:Keyword Index="K" Term="VerboseMessages class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.VerboseMessages class" /><MSHelp:Keyword Index="F" Term="VerboseMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages Members</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_PageSize" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="MPoolFileStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.MPoolFileStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.PageSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Port Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DbSiteConfig_Port" /><meta name="guid" content="F_BerkeleyDB_DbSiteConfig_Port" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DbSiteConfig.Port" /><MSHelp:TOCTitle Title="Port Field" /><MSHelp:RLTitle Title="DbSiteConfig.Port Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DbSiteConfig.Port" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassPortTopic" /><MSHelp:Keyword Index="K" Term="Port field" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.Port field" /><MSHelp:Keyword Index="F" Term="Port" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.Port" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.Port" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.Port" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The port of the site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
  <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.Port Field</td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:TOCTitle Title="MoveNextMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveNextMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextMultiple method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextMultiple" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultiple Method

</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Recno Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MultipleKeyDatabaseEntry_Recno" /><meta name="guid" content="P_BerkeleyDB_MultipleKeyDatabaseEntry_Recno" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MultipleKeyDatabaseEntry.Recno" /><MSHelp:TOCTitle Title="Recno Property " /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry.Recno Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MultipleKeyDatabaseEntry.Recno" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryClassRecnoTopic" /><MSHelp:Keyword Index="K" Term="Recno property" /><MSHelp:Keyword Index="K" Term="MultipleKeyDatabaseEntry.Recno property" /><MSHelp:Keyword Index="F" Term="Recno" /><MSHelp:Keyword Index="F" Term="MultipleKeyDatabaseEntry.Recno" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MultipleKeyDatabaseEntry.Recno" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleKeyDatabaseEntry.Recno" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleKeyDatabaseEntry.get_Recno" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the bulk buffer is for recno or queue database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleKeyDatabaseEntry..::.Recno Property </td></tr><tr id="headerTableRow3"><td align="left">MultipleKeyDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FromConst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ByteOrder_FromConst" /><meta name="guid" content="M_BerkeleyDB_ByteOrder_FromConst" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ByteOrder.FromConst(System.Int32)" /><MSHelp:TOCTitle Title="FromConst Method " /><MSHelp:RLTitle Title="ByteOrder.FromConst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ByteOrder.FromConst(System.Int32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBByteOrderClassFromConstTopic" /><MSHelp:Keyword Index="K" Term="FromConst method" /><MSHelp:Keyword Index="K" Term="ByteOrder.FromConst method" /><MSHelp:Keyword Index="F" Term="FromConst" /><MSHelp:Keyword Index="F" Term="ByteOrder.FromConst" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ByteOrder.FromConst" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ByteOrder.FromConst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Convert from the integer constant used to represent byte order in the C library
to its corresponding ByteOrder object." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder..::.FromConst Method </td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentMultipleKey Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Cursor_CurrentMultipleKey" /><meta name="guid" content="P_BerkeleyDB_Cursor_CurrentMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Cursor.CurrentMultipleKey" /><MSHelp:TOCTitle Title="CurrentMultipleKey Property " /><MSHelp:RLTitle Title="Cursor.CurrentMultipleKey Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Cursor.CurrentMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassCurrentMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="CurrentMultipleKey property" /><MSHelp:Keyword Index="K" Term="Cursor.CurrentMultipleKey property" /><MSHelp:Keyword Index="F" Term="CurrentMultipleKey" /><MSHelp:Keyword Index="F" Term="Cursor.CurrentMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.CurrentMultipleKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.CurrentMultipleKey" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.get_CurrentMultipleKey" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.set_CurrentMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The multiple key and data items at which the cursor currently points." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.CurrentMultipleKey Property </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LSN Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_LSN" /><meta name="guid" content="Fields_T_BerkeleyDB_LSN" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.LSN" /><MSHelp:TOCTitle Title="LSN Fields" /><MSHelp:RLTitle Title="LSN Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.LSN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLSNFieldsTopic" /><MSHelp:Keyword Index="K" Term="LSN class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN Fields</td></tr><tr id="headerTableRow3"><td align="left">LSN Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OldVersionException

Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_OldVersionException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_OldVersionException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.OldVersionException" /><MSHelp:TOCTitle Title="OldVersionException Members" /><MSHelp:RLTitle Title="OldVersionException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.OldVersionException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBOldVersionExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="OldVersionException class" /><MSHelp:Keyword Index="K" Term="OldVersionException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.OldVersionException class" /><MSHelp:Keyword Index="F" Term="OldVersionException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.OldVersionException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">OldVersionException Members</td></tr><tr id="headerTableRow3"><td align="left">OldVersionException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetThreadID Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_SetThreadID" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_SetThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.SetThreadID" /><MSHelp:TOCTitle Title="SetThreadID Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.SetThreadID Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.SetThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassSetThreadIDTopic" /><MSHelp:Keyword Index="K" Term="SetThreadID field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.SetThreadID

field" /><MSHelp:Keyword Index="F" Term="SetThreadID" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.SetThreadID" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.SetThreadID"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.SetThreadID" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="A delegate that returns a unique identifier pair for the current thread of control." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironmentConfig<span
class="cs">..::<span
class="nu">.SetThreadID Field</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Aborted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_Aborted" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_Aborted" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.Aborted" /><MSHelp:TOCTitle Title="Aborted Property " /><MSHelp:RLTitle Title="TransactionStats.Aborted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.Aborted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassAbortedTopic" /><MSHelp:Keyword Index="K" Term="Aborted property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Aborted property" /><MSHelp:Keyword Index="F" Term="Aborted" /><MSHelp:Keyword Index="F" Term="TransactionStats.Aborted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.Aborted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.Aborted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Aborted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of aborted transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.Aborted Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabase_PadByte" /><meta name="guid" content="P_BerkeleyDB_QueueDatabase_PadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueDatabase.PadByte" /><MSHelp:TOCTitle Title="PadByte Property " /><MSHelp:RLTitle Title="QueueDatabase.PadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabase.PadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassPadByteTopic" /><MSHelp:Keyword Index="K" Term="PadByte property" /><MSHelp:Keyword Index="K" Term="QueueDatabase.PadByte property" /><MSHelp:Keyword Index="F" Term="PadByte" /><MSHelp:Keyword Index="F" Term="QueueDatabase.PadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.PadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.get_PadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNextDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveNextDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextDuplicate" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveNextDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicate method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveNextDuplicate method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox"
data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_OverflowPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_OverflowPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.OverflowPagesFreeBytes" /><MSHelp:TOCTitle Title="OverflowPagesFreeBytes Property " /><MSHelp:RLTitle Title="BTreeStats.OverflowPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.OverflowPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassOverflowPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="OverflowPagesFreeBytes property" /><MSHelp:Keyword Index="K"

Term="BTreeStats.OverflowPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="OverflowPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BTreeStats.OverflowPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.OverflowPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.OverflowPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_OverflowPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in overflow pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.OverflowPagesFreeBytes Property </td></tr><tr

id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (UInt32, Int32, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_GetMultiple_3" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_GetMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32,System.Int32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="GetMultiple Method (UInt32, Int32, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="BTreeDatabase.GetMultiple Method (UInt32, Int32, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32,System.Int32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.GetMultiple Method (UInt32, Int32, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="QueueDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..<span

class="cpp">::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleDatabaseEntry Constructor (IEnumerable(DatabaseEntry), Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MultipleDatabaseEntry__ctor_1" /><meta name="guid" content="M_BerkeleyDB_MultipleDatabaseEntry__ctor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MultipleDatabaseEntry.#ctor(System.Collections.Generic.IEnumerable{BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:TOCTitle Title="MultipleDatabaseEntry Constructor (IEnumerable(DatabaseEntry), Boolean)" /><MSHelp:RLTitle Title="MultipleDatabaseEntry Constructor (IEnumerable(DatabaseEntry), Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MultipleDatabaseEntry.#ctor(System.Collections.Generic.IEnumerable{BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Construct a new key or data bulk buffer with a bunch of referring to ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MultipleDatabaseEntry Constructor (IEnumerable<(Of <(DatabaseEntry>)>), Boolean)</td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_DuplicatePagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_HashStats_DuplicatePagesFreeBytes"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.DuplicatePagesFreeBytes" /><MSHelp:TOCTitle Title="DuplicatePagesFreeBytes Property " /><MSHelp:RLTitle Title="HashStats.DuplicatePagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassDuplicatePagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="DuplicatePagesFreeBytes property" /><MSHelp:Keyword Index="K"

Term="HashStats.DuplicatePagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="F" Term="HashStats.DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.DuplicatePagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.DuplicatePagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_DuplicatePagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free on duplicate pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.DuplicatePagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogVerifyConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LogVerifyConfig" /><meta name="guid" content="T_BerkeleyDB_LogVerifyConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LogVerifyConfig" /><MSHelp:TOCTitle Title="LogVerifyConfig Class" /><MSHelp:RLTitle Title="LogVerifyConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LogVerifyConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassTopic" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LogVerifyConfig class" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig class, about LogVerifyConfig class" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for log verification." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_LockingSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_LockingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:TOCTitle Title="LockingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LockingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The locking subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, DatabaseEntry, Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Move_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_Move_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, DatabaseEntry, Boolean, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.Move Method (DatabaseEntry, DatabaseEntry, Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the datum associated with the given key in . In the presence of duplicate key values, the first data item in the set of duplicates is stored in . If either ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method (DatabaseEntry, DatabaseEntry, Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_GetMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Database_GetMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.GetMultiple" /><MSHelp:TOCTitle Title="GetMultiple Method " /><MSHelp:RLTitle Title="Database.GetMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.GetMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassGetMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetMultiple method" /><MSHelp:Keyword Index="K" Term="Database.GetMultiple method" /><MSHelp:Keyword Index="F" Term="GetMultiple" /><MSHelp:Keyword Index="F" Term="Database.GetMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetMultiple Method </td></tr><tr id="headerTableRow3"><td
align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_SecondaryHashDatabaseConfig_Compare" /><meta name="guid"
content="F_BerkeleyDB_SecondaryHashDatabaseConfig_Compare" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.SecondaryHashDatabaseConfig.Compare" /><MSHelp:TOCTitle Title="Compare Field"
/><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.Compare Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.SecondaryHashDatabaseConfig.Compare" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassCompareTopic" /><MSHelp:Keyword Index="K"
Term="Compare field"
/><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.Compare field" /><MSHelp:Keyword
Index="F" Term="Compare" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.Compare"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.Compare" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.Compare"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The Secondary Hash key comparison function." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.Compare Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ObjectWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_ObjectWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_ObjectWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.ObjectWait" /><MSHelp:TOCTitle Title="ObjectWait Property " /><MSHelp:RLTitle Title="LockStats.ObjectWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.ObjectWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassObjectWaitTopic" /><MSHelp:Keyword Index="K" Term="ObjectWait property" /><MSHelp:Keyword Index="K" Term="LockStats.ObjectWait property" /><MSHelp:Keyword Index="F" Term="ObjectWait" /><MSHelp:Keyword Index="F" Term="LockStats.ObjectWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.ObjectWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.ObjectWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_ObjectWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Object lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">LockStats<span
class="languageSpecificText">..<span
class="cpp">::.ObjectWait Property </td></tr><tr
id="headerTableRow3"><td align="left">LockStats Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_BTreeCursor_MovePrevUnique" /><meta name="guid"
content="Overload_BerkeleyDB_BTreeCursor_MovePrevUnique"
/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MovePrevUnique"
/><MSHelp:TOCTitle Title="MovePrevUnique Method " /><MSHelp:RLTitle

Title="BTreeCursor.MovePrevUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.BTreeCursor.MovePrevUnique" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeCursorClassMovePrevUniqueTopic" /><MSHelp:Keyword Index="K"
Term="MovePrevUnique method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MovePrevUnique
method" /><MSHelp:Keyword Index="F" Term="MovePrevUnique" /><MSHelp:Keyword Index="F"
Term="BTreeCursor.MovePrevUnique" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
 Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
 title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
 none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
 id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NotFoundException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_NotFoundException__ctor" /><meta name="guid" content="M_BerkeleyDB_NotFoundException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.NotFoundException.#ctor" /><MSHelp:TOCTitle Title="NotFoundException Constructor " /><MSHelp:RLTitle Title="NotFoundException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.NotFoundException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotFoundExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="NotFoundException class, constructor" /><MSHelp:Keyword Index="K" Term="NotFoundException.NotFoundException constructor" /><MSHelp:Keyword Index="F" Term="NotFoundException" /><MSHelp:Keyword Index="F" Term="NotFoundException.NotFoundException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.NotFoundException.NotFoundException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotFoundException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the NotFoundException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">NotFoundException Constructor </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_NotFoundException.htm">NotFoundException Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TransactionSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_TransactionSystemStats_1" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_TransactionSystemStats_1" /><xml><MSHelp:Attr

Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.TransactionSystemStats(System.Boolean)" /><MSHelp:TOCTitle Title="TransactionSystemStats Method (Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.TransactionSystemStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.TransactionSystemStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TransactionSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The transaction subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TransactionSystemStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepMgrStartClient Method (Int32, Boolean)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
 src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrStartClient_1" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_RepMgrStartClient_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrStartClient(System.Int32,System.Boolean)"
/><MSHelp:TOCTitle Title="RepMgrStartClient Method (Int32, Boolean)" /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepMgrStartClient Method (Int32, Boolean) (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrStartClient(System.Int32,System.Boolean)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepMgrStartClient" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr
 Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Start the replication manager as a client site, and optionally call for an election." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
 style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrStartClient Method (Int32, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextItem Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_MoveNextItem_1" /><meta name="guid" content="M_BerkeleyDB_JoinCursor_MoveNextItem_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.MoveNextItem(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextItem Method (LockingInfo)" /><MSHelp:RLTitle Title="JoinCursor.MoveNextItem Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.MoveNextItem(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.MoveNextItem" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Iterate over the values associated with the keys to which each passed to was initialized. Any data value that appears in all s is then stored in Current.Key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.MoveNextItem Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitObjects Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_InitObjects" /><meta
name="guid" content="P_BerkeleyDB_LockStats_InitObjects" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.InitObjects" /><MSHelp:TOCTitle Title="InitObjects Property "
/><MSHelp:RLTitle Title="LockStats.InitObjects Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockStats.InitObjects" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassInitObjectsTopic" /><MSHelp:Keyword Index="K" Term="InitObjects
property" /><MSHelp:Keyword Index="K" Term="LockStats.InitObjects property" /><MSHelp:Keyword
Index="F" Term="InitObjects" /><MSHelp:Keyword Index="F" Term="LockStats.InitObjects"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.InitObjects" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockStats.InitObjects" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.get_InitObjects" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initial number of
lock objects allocated." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.InitObjects Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLockingSystemStats Method (Boolean, Boolean, Boolean, Boolean, Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats_2" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats(System.Boolean,System.Boolean,System.Boolean,System.Boolean,System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintLockingSystemStats Method (Boolean, Boolean, Boolean, Boolean, Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLockingSystemStats Method (Boolean, Boolean, Boolean, Boolean, Boolean, Boolean) (BerkeleyDB)" />
<MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats(System.Boolean,System.Boolean,System.Boolean,System.Boolean,System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLockingSystemStats Method (Boolean, Boolean, Boolean, Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesExamined Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_CompactData_PagesExamined" /><meta name="guid"
content="P_BerkeleyDB_CompactData_PagesExamined" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.CompactData.PagesExamined" /><MSHelp:TOCTitle Title="PagesExamined Property "
/><MSHelp:RLTitle Title="CompactData.PagesExamined
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactData.PagesExamined"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassPagesExaminedTopic"
/><MSHelp:Keyword Index="K" Term="PagesExamined property" /><MSHelp:Keyword Index="K"
Term="CompactData.PagesExamined property" /><MSHelp:Keyword Index="F" Term="PagesExamined"
/><MSHelp:Keyword Index="F" Term="CompactData.PagesExamined" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.CompactData.PagesExamined" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.CompactData.PagesExamined" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.CompactData.get_PagesExamined" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of database pages
reviewed during the compaction phase." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">CompactData<span
class="cs">..::<span
class="nu">.PagesExamined Property </td></tr><tr id="headerTableRow3"><td
align="left">CompactData Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MoveFirst Method (DatabaseEntry, DatabaseEntry, DatabaseEntry,
LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveFirst_2" /><meta
name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveFirst_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berke
leyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirst Method (DatabaseEntry,
DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveFirst Method
(DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkel
eyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first
key/data pair of the database, and store the secondary key along with the corresponding primary key/data pair in . If
the first key has duplicate values, the f ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
  <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveFirst Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageNotFoundException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_PageNotFoundException" /><meta name="guid" content="T_BerkeleyDB_PageNotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.PageNotFoundException" /><MSHelp:TOCTitle Title="PageNotFoundException Class" /><MSHelp:RLTitle Title="PageNotFoundException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="T:BerkeleyDB.PageNotFoundException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBPageNotFoundExceptionClassTopic" /><MSHelp:Keyword Index="K"
Term="PageNotFoundException class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.PageNotFoundException class" /><MSHelp:Keyword Index="K"
Term="PageNotFoundException class, about PageNotFoundException class" /><MSHelp:Keyword Index="F"
Term="PageNotFoundException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.PageNotFoundException"
/><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.PageNotFoundException" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">PageNotFoundException Class</td></tr><tr id="headerTableRow3"><td

align="left">Members See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_DatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseConfig.#ctor" /><MSHelp:TOCTitle Title="DatabaseConfig Constructor " /><MSHelp:RLTitle Title="DatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.DatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="DatabaseConfig" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.DatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.DatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new DatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig Constructor
</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CursorConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_CursorConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_CursorConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.CursorConfig.#ctor" /><MSHelp:TOCTitle Title="CursorConfig Constructor " /><MSHelp:RLTitle Title="CursorConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.CursorConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="CursorConfig class, constructor" /><MSHelp:Keyword
Index="K" Term="CursorConfig.CursorConfig constructor" /><MSHelp:Keyword Index="F" Term="CursorConfig" /><MSHelp:Keyword Index="F" Term="CursorConfig.CursorConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CursorConfig.CursorConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CursorConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new CursorConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">CursorConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BTreeStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_BTreeStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.BTreeStats" /><MSHelp:TOCTitle Title="BTreeStats Members" /><MSHelp:RLTitle Title="BTreeStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BTreeStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="BTreeStats class" /><MSHelp:Keyword Index="K" Term="BTreeStats class,
all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeStats class" /><MSHelp:Keyword Index="F" Term="BTreeStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats Members</td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultiple Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultiple Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultiple is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor.<span
class="vb">.::.MoveNextUniqueMultiple Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrefixCompare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_PrefixCompare" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_PrefixCompare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.PrefixCompare" /><MSHelp:TOCTitle Title="PrefixCompare Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.PrefixCompare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.PrefixCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassPrefixCompareTopic" /><MSHelp:Keyword Index="K" Term="PrefixCompare property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.PrefixCompare property" /><MSHelp:Keyword Index="F" Term="PrefixCompare" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.PrefixCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.PrefixCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.PrefixCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_PrefixCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.set_PrefixCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree prefix function. The prefix function is used to determine the amount by which keys stored on the Btree internal pages can be safely truncated without losing their uniqueness." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.PrefixCompare Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetEncryption Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironmentConfig_SetEncryption" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironmentConfig_SetEncryption" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironmentConfig.SetEncryption(System.String,BerkeleyDB.EncryptionAlgorithm)" /><MSHelp:TOCTitle Title="SetEncryption Method " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.SetEncryption Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironmentConfig.SetEncryption(System.String,BerkeleyDB.EncryptionAlgorithm)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassSetEncryptionTopic" /><MSHelp:Keyword Index="K" Term="SetEncryption method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.SetEncryption method" /><MSHelp:Keyword Index="F" Term="SetEncryption" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.SetEncryption" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.SetEncryption" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.SetEncryption" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the password and algorithm used by the Berkeley DB library to perform encryption and decryption." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.SetEncryption Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignKeyDatabase Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_SecondaryDatabaseConfig_ForeignKeyDatabase" /><meta name="guid"
content="P_BerkeleyDB_SecondaryDatabaseConfig_ForeignKeyDatabase" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyDatabase"
/><MSHelp:TOCTitle Title="ForeignKeyDatabase Property " /><MSHelp:RLTitle
Title="SecondaryDatabaseConfig.ForeignKeyDatabase Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyDatabase" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassForeignKeyDatabaseTopic" /><MSHelp:Keyword
Index="K" Term="ForeignKeyDatabase property" /><MSHelp:Keyword Index="K"
Term="SecondaryDatabaseConfig.ForeignKeyDatabase property" /><MSHelp:Keyword Index="F"
Term="ForeignKeyDatabase" /><MSHelp:Keyword Index="F"
Term="SecondaryDatabaseConfig.ForeignKeyDatabase" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyDatabase" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyDatabase" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.get_ForeignKeyDatabase"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The database used to check the foreign key integrity constraint."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryDatabaseConfig.<span
class="vb">.::.ForeignKeyDatabase Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryDatabaseConfig.htm">SecondaryDatabaseConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MultipleKeyDatabaseEntry Class</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_MultipleKeyDatabaseEntry" /><meta name="guid"
content="T_BerkeleyDB_MultipleKeyDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:TOCTitle Title="MultipleKeyDatabaseEntry
Class" /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Class (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="T:BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryClassTopic" /><MSHelp:Keyword Index="K"
Term="MultipleKeyDatabaseEntry class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.MultipleKeyDatabaseEntry class" /><MSHelp:Keyword Index="K"
Term="MultipleKeyDatabaseEntry class, about MultipleKeyDatabaseEntry
class" /><MSHelp:Keyword Index="F" Term="MultipleKeyDatabaseEntry" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleKeyDatabaseEntry"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="A class providing access to multiple key/data pairs." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">MultipleKeyDatabaseEntry Class</td></tr><tr id="headerTableRow3"><td
align="left">Members <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ExtentSize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_SecondaryQueueDatabase_ExtentSize" /><meta name="guid"

content="P_BerkeleyDB_SecondaryQueueDatabase_ExtentSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryQueueDatabase.ExtentSize" /><MSHelp:TOCTitle Title="ExtentSize Property " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.ExtentSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryQueueDatabase.ExtentSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassExtentSizeTopic" /><MSHelp:Keyword Index="K" Term="ExtentSize property" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.ExtentSize property" /><MSHelp:Keyword Index="F" Term="ExtentSize" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.ExtentSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.ExtentSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.ExtentSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.get_ExtentSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the extents used to hold pages in a , specified as a number of pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.ExtentSize Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_PutNoOverwrite" /><meta name="guid" content="M_BerkeleyDB_Database_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="PutNoOverwrite Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Database.PutNoOverwrite Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair in the database, only if the key does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.PutNoOverwrite Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_TransactionConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_TransactionConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.TransactionConfig.#ctor" /><MSHelp:TOCTitle Title="TransactionConfig Constructor " /><MSHelp:RLTitle Title="TransactionConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.TransactionConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="TransactionConfig class, constructor" /><MSHelp:Keyword Index="K" Term="TransactionConfig.TransactionConfig constructor" /><MSHelp:Keyword Index="F"

Term="TransactionConfig" /><MSHelp:Keyword Index="F" Term="TransactionConfig.TransactionConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.TransactionConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new TransactionConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MoveFirstMultiple Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_RecnoCursor_MoveFirstMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MoveFirstMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.RecnoCursor.MoveFirstMultiple" /><MSHelp:TOCTitle Title="MoveFirstMultiple
Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveFirstMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveFirstMultiple"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveFirstMultipleTopic"
/><MSHelp:Keyword Index="K" Term="MoveFirstMultiple method" /><MSHelp:Keyword Index="K"
Term="RecnoCursor.MoveFirstMultiple method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultiple"
/><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveFirstMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoCursor.MoveFirstMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span

id="memberOptionsDropdown" class="filter" tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered
</nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveFirstMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor"

/><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"

/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxOpenFileDescriptors Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MaxOpenFileDescriptors" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxOpenFileDescriptors" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxOpenFileDescriptors" /><MSHelp:TOCTitle Title="MaxOpenFileDescriptors Property " /><MSHelp:RLTitle Title="MPoolStats.MaxOpenFileDescriptors Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxOpenFileDescriptors" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxOpenFileDescriptorsTopic" /><MSHelp:Keyword Index="K" Term="MaxOpenFileDescriptors property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxOpenFileDescriptors property" /><MSHelp:Keyword Index="F" Term="MaxOpenFileDescriptors" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxOpenFileDescriptors" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxOpenFileDescriptors" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxOpenFileDescriptors" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxOpenFileDescriptors" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of open fd's." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxOpenFileDescriptors Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyEmptyException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_KeyEmptyException" /><meta name="guid"

content="Properties_T_BerkeleyDB_KeyEmptyException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.KeyEmptyException" /><MSHelp:TOCTitle Title="KeyEmptyException Properties " /><MSHelp:RLTitle Title="KeyEmptyException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.KeyEmptyException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyEmptyExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"

value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyEmptyException Properties </td></tr><tr id="headerTableRow3"><td align="left">KeyEmptyException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_GetBothMultiple" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.GetBothMultiple" /><MSHelp:TOCTitle Title="GetBothMultiple Method " /><MSHelp:RLTitle Title="BTreeDatabase.GetBothMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.GetBothMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassGetBothMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetBothMultiple method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.GetBothMultiple method" /><MSHelp:Keyword Index="F" Term="GetBothMultiple" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.GetBothMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.GetBothMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Move_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Move_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, Boolean)" /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (DatabaseEntry, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the primary key/data pair associated with the given secondary key in . In the presence of duplicate key values, the first data item in the set of duplicates i ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Move Method (DatabaseEntry, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbChannel_Close" /><meta name="guid" content="M_BerkeleyDB_DbChannel_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbChannel.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="DbChannel.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbChannel.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="DbChannel.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="DbChannel.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbChannel.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Close the channel." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RecnoDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RecnoDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RecnoDatabase" /><MSHelp:TOCTitle Title="RecnoDatabase Members" /><MSHelp:RLTitle Title="RecnoDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RecnoDatabase" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBRecnoDatabaseMembersTopic"
/><MSHelp:Keyword Index="K" Term="RecnoDatabase class" /><MSHelp:Keyword Index="K"
Term="RecnoDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoDatabase
class" /><MSHelp:Keyword Index="F" Term="RecnoDatabase" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown"
class="filter" tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"

data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase
Members</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AckPolicy Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_AckPolicy" /><meta name="guid" content="T_BerkeleyDB_AckPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.AckPolicy" /><MSHelp:TOCTitle Title="AckPolicy Class" /><MSHelp:RLTitle Title="AckPolicy Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.AckPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyClassTopic" /><MSHelp:Keyword Index="K" Term="AckPolicy class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.AckPolicy class" /><MSHelp:Keyword Index="K" Term="AckPolicy class, about AckPolicy class" /><MSHelp:Keyword Index="F" Term="AckPolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.AckPolicy" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The AckPolicy class specifies how master and client sites will handle acknowledgment of replication messages which are necessary for "permanent" records.
The current implementation requires all sites in a ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GlobalID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_GlobalID" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_GlobalID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.GlobalID" /><MSHelp:TOCTitle Title="GlobalID Property "

/><MSHelp:RLTitle
Title="ActiveTransaction.GlobalID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ActiveTransaction.GlobalID" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBActiveTransactionClassGlobalIDTopic" /><MSHelp:Keyword Index="K" Term="GlobalID
property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.GlobalID property" /><MSHelp:Keyword
Index="F" Term="GlobalID" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.GlobalID"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.GlobalID" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.GlobalID" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_GlobalID" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="If the transaction is a prepare transaction, the transaction's Global ID. Otherwise, the GlobalID contents are
undefined." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">ActiveTransaction..::.GlobalID Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PermissionsMode Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_PermissionsMode" /><meta name="guid" content="P_BerkeleyDB_LogStats_PermissionsMode" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.PermissionsMode" /><MSHelp:TOCTitle Title="PermissionsMode Property " /><MSHelp:RLTitle Title="LogStats.PermissionsMode Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.PermissionsMode" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassPermissionsModeTopic" /><MSHelp:Keyword Index="K" Term="PermissionsMode property" /><MSHelp:Keyword Index="K" Term="LogStats.PermissionsMode property" /><MSHelp:Keyword Index="F" Term="PermissionsMode" /><MSHelp:Keyword Index="F" Term="LogStats.PermissionsMode" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.PermissionsMode" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.PermissionsMode" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_PermissionsMode" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log file permissions mode." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.PermissionsMode Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_FastStats" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="HashDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.FastStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method

(String, String, SecondaryRecnoDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryRecnoDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryRecnoDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Open Method (String, String, SecondaryRecnoDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryRecnoDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryRecnoDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Open Method (String, String, SecondaryRecnoDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script
type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabaseConfig Fields" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig class, fields" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>OldVersionException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_OldVersionException" /><meta name="guid" content="Properties_T_BerkeleyDB_OldVersionException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.OldVersionException" /><MSHelp:TOCTitle Title="OldVersionException Properties " /><MSHelp:RLTitle Title="OldVersionException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.OldVersionException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBOldVersionExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="OldVersionException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">OldVersionException Properties </td></tr><tr id="headerTableRow3"><td align="left">OldVersionException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSiteConfig Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSiteConfig" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSiteConfig" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrSiteConfig(BerkeleyDB.DbSiteConfig)" /><MSHelp:TOCTitle Title="RepMgrSiteConfig Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrSiteConfig Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrSiteConfig(BerkeleyDB.DbSiteConfig)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrSiteConfigTopic" /><MSHelp:Keyword Index="K" Term="RepMgrSiteConfig method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrSiteConfig method" /><MSHelp:Keyword Index="F" Term="RepMgrSiteConfig" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrSiteConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrSiteConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrSiteConfig"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure a site in the replication manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrSiteConfig Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>ArchivableDatabaseFiles Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_ArchivableDatabaseFiles" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_ArchivableDatabaseFiles" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.ArchivableDatabaseFiles(System.Boolean)" /><MSHelp:TOCTitle Title="ArchivableDatabaseFiles Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.ArchivableDatabaseFiles Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.ArchivableDatabaseFiles(System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassArchivableDatabaseFilesTopic" /><MSHelp:Keyword Index="K" Term="ArchivableDatabaseFiles method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ArchivableDatabaseFiles method" /><MSHelp:Keyword Index="F" Term="ArchivableDatabaseFiles" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ArchivableDatabaseFiles" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ArchivableDatabaseFiles" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ArchivableDatabaseFiles" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database files that need to be archived in order to recover the database from catastrophic failure. If any of the database files have not been accessed during the lifetime of the current log files, ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.ArchivableDatabaseFiles
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>DatabaseException Class</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_DatabaseException" /><meta name="guid" content="T_BerkeleyDB_DatabaseException"
/><xml><MSHelp:Attr
Name="AssetID" Value="T:BerkeleyDB.DatabaseException" /><MSHelp:TOCTitle Title="DatabaseException
Class" /><MSHelp:RLTitle Title="DatabaseException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="T:BerkeleyDB.DatabaseException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseExceptionClassTopic" /><MSHelp:Keyword Index="K"
Term="DatabaseException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseException class"
/><MSHelp:Keyword Index="K" Term="DatabaseException class, about DatabaseException class"
/><MSHelp:Keyword Index="F" Term="DatabaseException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseException" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Represents errors that occur during Berkley DB operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>key Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SequenceConfig_key" /><meta name="guid" content="F_BerkeleyDB_SequenceConfig_key" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SequenceConfig.key" /><MSHelp:TOCTitle Title="key Field" /><MSHelp:RLTitle Title="SequenceConfig.key Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SequenceConfig.key" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClasskeyTopic" /><MSHelp:Keyword Index="K" Term="key field" /><MSHelp:Keyword Index="K" Term="SequenceConfig.key field" /><MSHelp:Keyword Index="F" Term="key" /><MSHelp:Keyword Index="F" Term="SequenceConfig.key" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.key" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.key" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The record in the database that stores the persistent sequence data." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.key Field</td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Insert Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Insert" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Insert" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Insert(BerkeleyDB.DatabaseEntry,BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:TOCTitle Title="Insert Method " /><MSHelp:RLTitle Title="BTreeCursor.Insert Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Insert(BerkeleyDB.DatabaseEntry,BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassInsertTopic" /><MSHelp:Keyword Index="K" Term="Insert method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.Insert method" /><MSHelp:Keyword Index="F" Term="Insert" /><MSHelp:Keyword Index="F" Term="BTreeCursor.Insert" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.Insert" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Insert" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Insert the data element as a duplicate element of the key to which the cursor refers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
 class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
 data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Insert Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
 (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SystemMemory Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
 </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_SystemMemory" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_SystemMemory" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.SystemMemory" /><MSHelp:TOCTitle Title="SystemMemory Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.SystemMemory Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="F:BerkeleyDB.DatabaseEnvironmentConfig.SystemMemory" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassSystemMemoryTopic" /><MSHelp:Keyword Index="K"
Term="SystemMemory field" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.SystemMemory field" /><MSHelp:Keyword Index="F"
Term="SystemMemory" /><MSHelp:Keyword
Index="F" Term="DatabaseEnvironmentConfig.SystemMemory" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.SystemMemory" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.SystemMemory" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, allocate region memory from system shared memory instead of from heap
memory or memory backed by the filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.SystemMemory Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Append_1" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Append_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Append(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Append Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="HeapDatabase.Append Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Append(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append the data item to the end of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Append Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_IGNORE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_IGNORE" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_IGNORE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_IGNORE" /><MSHelp:TOCTitle Title="DB_REP_IGNORE Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_IGNORE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_IGNORE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_IGNORETopic" /><MSHelp:Keyword Index="K" Term="DB_REP_IGNORE field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_IGNORE field" /><MSHelp:Keyword Index="F" Term="DB_REP_IGNORE" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_IGNORE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_IGNORE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_IGNORE" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="This msg should be ignored." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_IGNORE Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationStats Class</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ReplicationStats" /><meta name="guid" content="T_BerkeleyDB_ReplicationStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ReplicationStats" /><MSHelp:TOCTitle Title="ReplicationStats Class" /><MSHelp:RLTitle Title="ReplicationStats
Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ReplicationStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassTopic" /><MSHelp:Keyword Index="K" Term="ReplicationStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ReplicationStats class" /><MSHelp:Keyword Index="K" Term="ReplicationStats class, about ReplicationStats class" /><MSHelp:Keyword Index="F" Term="ReplicationStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Statistical information about the replication subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple
</nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Env Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_Env" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_Env" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.Env" /><MSHelp:TOCTitle Title="Env Field" /><MSHelp:RLTitle Title="DatabaseConfig.Env Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.Env" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassEnvTopic" /><MSHelp:Keyword Index="K" Term="Env field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.Env field" /><MSHelp:Keyword Index="F" Term="Env" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.Env" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.Env" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.Env" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Berkeley DB environment within which to create a database.
If null, the database will be created stand-alone; that is, it is not part of any Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.Env Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (DatabaseEntry, Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_Cursor_MoveMultiple_1" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveMultiple_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultiple Method (DatabaseEntry, Boolean, LockingInfo)"
/><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (DatabaseEntry, Boolean, LockingInfo) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store that key and as many duplicate data items associated with the given key that can fit in a buffer the size of one database page in ."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">Cursor..::.MoveMultiple Method (DatabaseEntry, Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_PutNoOverwrite" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.PutNoOverwrite" /><MSHelp:TOCTitle Title="PutNoOverwrite Method " /><MSHelp:RLTitle Title="HashDatabase.PutNoOverwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassPutNoOverwriteTopic" /><MSHelp:Keyword Index="K" Term="PutNoOverwrite method" /><MSHelp:Keyword Index="K" Term="HashDatabase.PutNoOverwrite method" /><MSHelp:Keyword Index="F" Term="PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="HashDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.PutNoOverwrite Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitRegions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitRegions" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitRegions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitRegions" /><MSHelp:TOCTitle Title="InitRegions Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitRegions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitRegions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitRegionsTopic" /><MSHelp:Keyword Index="K" Term="InitRegions property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitRegions property" /><MSHelp:Keyword Index="F" Term="InitRegions" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitRegions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitRegions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitRegions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitRegions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitRegions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will page-fault shared regions into memory when initially creating or joining a Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
 align="left">DatabaseEnvironment..::.InitRegions Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Class</title><link rel="stylesheet"
 type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryCursor" /><meta name="guid" content="T_BerkeleyDB_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Class" /><MSHelp:RLTitle Title="SecondaryCursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassTopic" /><MSHelp:Keyword Index="K" Term="SecondaryCursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryCursor class" /><MSHelp:Keyword Index="K" Term="SecondaryCursor class, about SecondaryCursor class" /><MSHelp:Keyword Index="F" Term="SecondaryCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class
 representing database cursors over secondary indexes, which allow for traversal of database records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
 title="Copy image" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Cursor Method (CursorConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Cursor_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Cursor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Cursor(BerkeleyDB.CursorConfig)"
/><MSHelp:TOCTitle Title="Cursor Method (CursorConfig)" /><MSHelp:RLTitle Title="RecnoDatabase.Cursor Method (CursorConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Cursor Method (CursorConfig)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Version Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_Version" /><meta name="guid" content="P_BerkeleyDB_QueueStats_Version" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.Version" /><MSHelp:TOCTitle Title="Version Property " /><MSHelp:RLTitle Title="QueueStats.Version Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.Version" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassVersionTopic" /><MSHelp:Keyword Index="K" Term="Version property" /><MSHelp:Keyword Index="K" Term="QueueStats.Version property" /><MSHelp:Keyword Index="F" Term="Version" /><MSHelp:Keyword Index="F" Term="QueueStats.Version" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.Version" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.Version" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_Version" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Version number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.Version Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_OverflowPages" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_OverflowPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.OverflowPages" /><MSHelp:TOCTitle Title="OverflowPages Property " /><MSHelp:RLTitle Title="RecnoStats.OverflowPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.OverflowPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassOverflowPagesTopic" /><MSHelp:Keyword Index="K" Term="OverflowPages property" /><MSHelp:Keyword Index="K" Term="RecnoStats.OverflowPages property" /><MSHelp:Keyword Index="F" Term="OverflowPages" /><MSHelp:Keyword Index="F" Term="RecnoStats.OverflowPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.OverflowPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.OverflowPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_OverflowPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Overflow pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.OverflowPages Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

```
</script><meta name="container" content="BerkeleyDB" /><meta
 name="file" content="Overload_BerkeleyDB_Cursor_MovePrevUnique" /><meta name="guid"
content="Overload_BerkeleyDB_Cursor_MovePrevUnique" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:TOCTitle Title="MovePrevUnique Method "
/><MSHelp:RLTitle Title="Cursor.MovePrevUnique Method  (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCursorClassMovePrevUniqueTopic" /><MSHelp:Keyword Index="K"
Term="MovePrevUnique method" /><MSHelp:Keyword Index="K" Term="Cursor.MovePrevUnique method"
/><MSHelp:Keyword Index="F" Term="MovePrevUnique" /><MSHelp:Keyword Index="F"
Term="Cursor.MovePrevUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MovePrevUnique"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax"
 /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
 id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /><div id="header"><table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> </span><span>    </span><span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label
 id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></span><span>    </span><span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage"
 style="display: none;"><nobr>Members: Filtered </nobr></label></span></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
```

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Duplicate" /><meta name="guid" content="M_BerkeleyDB_Cursor_Duplicate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Duplicate(System.Boolean)" /><MSHelp:TOCTitle Title="Duplicate Method " /><MSHelp:RLTitle Title="Cursor.Duplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Duplicate(System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassDuplicateTopic" /><MSHelp:Keyword Index="K" Term="Duplicate method" /><MSHelp:Keyword Index="K" Term="Cursor.Duplicate method" /><MSHelp:Keyword Index="F" Term="Duplicate" /><MSHelp:Keyword Index="F" Term="Cursor.Duplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Duplicate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Duplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new cursor that uses the same transaction and locker ID as the original cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Duplicate Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetCompression Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabaseConfig_SetCompression" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabaseConfig_SetCompression" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:TOCTitle Title="SetCompression Method " /><MSHelp:RLTitle Title="BTreeDatabaseConfig.SetCompression Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassSetCompressionTopic" /><MSHelp:Keyword Index="K" Term="SetCompression method" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.SetCompression method" /><MSHelp:Keyword Index="F" Term="SetCompression" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.SetCompression" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input

id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.SetCompression Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nData Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_nData" /><meta name="guid" content="P_BerkeleyDB_QueueStats_nData" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.nData" /><MSHelp:TOCTitle Title="nData Property " /><MSHelp:RLTitle Title="QueueStats.nData Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.nData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassnDataTopic" /><MSHelp:Keyword Index="K" Term="nData property" /><MSHelp:Keyword Index="K" Term="QueueStats.nData property" /><MSHelp:Keyword Index="F" Term="nData" /><MSHelp:Keyword Index="F" Term="QueueStats.nData" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.nData" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.nData" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_nData" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.nData Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogZeroOnCreate Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogZeroOnCreate"
/><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogZeroOnCreate" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogZeroOnCreate" /><MSHelp:TOCTitle
Title="LogZeroOnCreate Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogZeroOnCreate Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogZeroOnCreate"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogZeroOnCreateTopic"
/><MSHelp:Keyword Index="K" Term="LogZeroOnCreate property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.LogZeroOnCreate property" /><MSHelp:Keyword Index="F"
Term="LogZeroOnCreate" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogZeroOnCreate"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogZeroOnCreate" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogZeroOnCreate"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogZeroOnCreate"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, all pages of a log file are zeroed
when that log file is created." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogZeroOnCreate Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyExistException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_KeyExistException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_KeyExistException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.KeyExistException" /><MSHelp:TOCTitle Title="KeyExistException Members" /><MSHelp:RLTitle Title="KeyExistException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.KeyExistException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyExistExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="KeyExistException class" /><MSHelp:Keyword Index="K" Term="KeyExistException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.KeyExistException class" /><MSHelp:Keyword Index="F" Term="KeyExistException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyExistException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;

height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyExistException Members</td></tr><tr id="headerTableRow3"><td align="left">KeyExistException Class Constructors Methods Fields Properties See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_ReplicationSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_ReplicationSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats" /><MSHelp:TOCTitle Title="ReplicationSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.ReplicationSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The replication subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ReplicationSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockSteals Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockSteals" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockSteals" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockSteals" /><MSHelp:TOCTitle Title="LockSteals Property " /><MSHelp:RLTitle Title="LockStats.LockSteals Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockSteals" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockStealsTopic" /><MSHelp:Keyword Index="K" Term="LockSteals property" /><MSHelp:Keyword Index="K" Term="LockStats.LockSteals property" /><MSHelp:Keyword Index="F" Term="LockSteals" /><MSHelp:Keyword Index="F" Term="LockStats.LockSteals" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockSteals" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockSteals" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockSteals" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lock steals so far." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockSteals Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_nPages" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_nPages" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.RecnoStats.nPages" /><MSHelp:TOCTitle Title="nPages Property " /><MSHelp:RLTitle Title="RecnoStats.nPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.nPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassnPagesTopic" /><MSHelp:Keyword Index="K" Term="nPages property" /><MSHelp:Keyword Index="K" Term="RecnoStats.nPages property" /><MSHelp:Keyword Index="F" Term="nPages" /><MSHelp:Keyword Index="F" Term="RecnoStats.nPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.nPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.nPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_nPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page count." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats.<span

class="vb">.::.nPages Property
</td></tr><tr
id="headerTableRow3"><td align="left">RecnoStats Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple
Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_MoveMultiple_4" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveMultiple_4" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEnt
ry,BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:TOCTitle Title="MoveMultiple Method
(KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple
Method (KeyValuePair(DatabaseEntry, DatabaseEntry),
Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEnt
ry,BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified
key/data pair of the database, and store that key/data pair and as many duplicate data items associated with the given
key that can fit in a buffer the size of one database ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultiple Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_LockingSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_LockingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:TOCTitle Title="LockingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LockingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="Overload:BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLockingSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="LockingSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LockingSystemStats method" /><MSHelp:Keyword Index="F" Term="LockingSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LockingSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input

id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Duplicate" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Duplicate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Duplicate(System.Boolean)" /><MSHelp:TOCTitle Title="Duplicate Method " /><MSHelp:RLTitle Title="BTreeCursor.Duplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Duplicate(System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassDuplicateTopic" /><MSHelp:Keyword Index="K" Term="Duplicate method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.Duplicate method" /><MSHelp:Keyword Index="F" Term="Duplicate" /><MSHelp:Keyword Index="F" Term="BTreeCursor.Duplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.Duplicate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Duplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new cursor that uses the same transaction and locker ID as the original cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::<span
class="nu">.Duplicate Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLocks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="P_BerkeleyDB_LockingConfig_MaxLocks" /><meta name="guid"
content="P_BerkeleyDB_LockingConfig_MaxLocks" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockingConfig.MaxLocks" /><MSHelp:TOCTitle Title="MaxLocks Property "
/><MSHelp:RLTitle Title="LockingConfig.MaxLocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockingConfig.MaxLocks" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingConfigClassMaxLocksTopic" /><MSHelp:Keyword
Index="K" Term="MaxLocks property" /><MSHelp:Keyword Index="K" Term="LockingConfig.MaxLocks
property" /><MSHelp:Keyword Index="F" Term="MaxLocks" /><MSHelp:Keyword Index="F"
Term="LockingConfig.MaxLocks" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockingConfig.MaxLocks" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.MaxLocks" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.get_MaxLocks" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.set_MaxLocks" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum
number of locks supported by the Berkeley DB environment." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.MaxLocks Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BadSecondaryException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_BadSecondaryException" /><meta name="guid" content="Properties_T_BerkeleyDB_BadSecondaryException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.BadSecondaryException" /><MSHelp:TOCTitle Title="BadSecondaryException Properties " /><MSHelp:RLTitle Title="BadSecondaryException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.BadSecondaryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBadSecondaryExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="BadSecondaryException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label

id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">BadSecondaryException Properties
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BadSecondaryException.htm">BadSecondaryException Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Max Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_Max" /><meta name="guid" content="P_BerkeleyDB_MutexStats_Max" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.Max" /><MSHelp:TOCTitle Title="Max Property " /><MSHelp:RLTitle Title="MutexStats.Max Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.Max" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassMaxTopic" /><MSHelp:Keyword Index="K" Term="Max property" /><MSHelp:Keyword Index="K" Term="MutexStats.Max property" /><MSHelp:Keyword Index="F" Term="Max" /><MSHelp:Keyword Index="F" Term="MutexStats.Max" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.Max" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.Max" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_Max" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutex max count" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MutexStats<span
class="cs">..::<span
class="nu">.Max Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_MutexStats.htm">MutexStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ImmutableKey
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_SecondaryDatabaseConfig_ImmutableKey" /><meta name="guid"
content="F_BerkeleyDB_SecondaryDatabaseConfig_ImmutableKey" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.SecondaryDatabaseConfig.ImmutableKey" /><MSHelp:TOCTitle Title="ImmutableKey
Field" /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.ImmutableKey
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.SecondaryDatabaseConfig.ImmutableKey" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassImmutableKeyTopic" /><MSHelp:Keyword Index="K"
Term="ImmutableKey field" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.ImmutableKey
field" /><MSHelp:Keyword Index="F" Term="ImmutableKey" /><MSHelp:Keyword Index="F"
Term="SecondaryDatabaseConfig.ImmutableKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryDatabaseConfig.ImmutableKey" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.ImmutableKey" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, the secondary key is immutable." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.ImmutableKey Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_ReplicationConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationConfig.#ctor" /><MSHelp:TOCTitle Title="ReplicationConfig Constructor " /><MSHelp:RLTitle Title="ReplicationConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class, constructor" /><MSHelp:Keyword Index="K"

Term="ReplicationConfig.ReplicationConfig constructor" /><MSHelp:Keyword Index="F" Term="ReplicationConfig" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.ReplicationConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.ReplicationConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new ReplicationConfig object with default configuration values." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceConfig
Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Properties_T_BerkeleyDB_SequenceConfig" /><meta name="guid"
content="Properties_T_BerkeleyDB_SequenceConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.SequenceConfig" /><MSHelp:TOCTitle Title="SequenceConfig Properties "
/><MSHelp:RLTitle Title="SequenceConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Properties.T:BerkeleyDB.SequenceConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSequenceConfigPropertiesTopic" /><MSHelp:Keyword Index="K"
Term="SequenceConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetBothMultiple" /><meta name="guid" content="M_BerkeleyDB_Database_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="GetBothMultiple Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Database.GetBothMultiple Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetBothMultiple"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If a key/data pair in the database matches and , return the key and all duplicate data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetBothMultiple Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerificationException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_VerificationException" /><meta name="guid" content="T_BerkeleyDB_VerificationException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.VerificationException" /><MSHelp:TOCTitle Title="VerificationException Class" /><MSHelp:RLTitle Title="VerificationException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.VerificationException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerificationExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="VerificationException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.VerificationException class" /><MSHelp:Keyword Index="K" Term="VerificationException class, about VerificationException class" /><MSHelp:Keyword Index="F" Term="VerificationException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerificationException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerificationException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Thrown by if a database is corrupted, and by if all key/data pairs in the file may not have been successfully output." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerificationException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSiteConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DbSiteConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DbSiteConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DbSiteConfig" /><MSHelp:TOCTitle Title="DbSiteConfig Members" /><MSHelp:RLTitle Title="DbSiteConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DbSiteConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbSiteConfig class" /><MSHelp:Keyword Index="F" Term="DbSiteConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig Members</td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class Constructors Methods Fields Properties <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesWritten Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesWritten" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesWritten" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesWritten" /><MSHelp:TOCTitle Title="PagesWritten Property " /><MSHelp:RLTitle Title="MPoolStats.PagesWritten Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PagesWritten" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesWrittenTopic" /><MSHelp:Keyword Index="K" Term="PagesWritten property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PagesWritten property" /><MSHelp:Keyword Index="F" Term="PagesWritten" /><MSHelp:Keyword Index="F" Term="MPoolStats.PagesWritten" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PagesWritten" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PagesWritten" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PagesWritten" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages written out." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PagesWritten Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionMemoryLimitGBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RegionMemoryLimitGBytes" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RegionMemoryLimitGBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitGBytes" /><MSHelp:TOCTitle Title="RegionMemoryLimitGBytes Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RegionMemoryLimitGBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitGBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRegionMemoryLimitGBytesTopic" /><MSHelp:Keyword Index="K" Term="RegionMemoryLimitGBytes property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RegionMemoryLimitGBytes property" /><MSHelp:Keyword Index="F" Term="RegionMemoryLimitGBytes" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RegionMemoryLimitGBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitGBytes" /><MSHelp:Attr Name="APIType"

Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RegionMemoryLimitGBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RegionMemoryLimitGBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The gigabytes component of the byte-count limit on the amount of memory to be used by shared structures in the main environment region. These are the structures other than mutexes and the page cach ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RegionMemoryLimitGBytes Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreeThreaded Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SequenceConfig_FreeThreaded" /><meta name="guid" content="F_BerkeleyDB_SequenceConfig_FreeThreaded" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SequenceConfig.FreeThreaded" /><MSHelp:TOCTitle Title="FreeThreaded Field" /><MSHelp:RLTitle Title="SequenceConfig.FreeThreaded Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SequenceConfig.FreeThreaded" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassFreeThreadedTopic" /><MSHelp:Keyword Index="K" Term="FreeThreaded field" /><MSHelp:Keyword Index="K" Term="SequenceConfig.FreeThreaded field" /><MSHelp:Keyword Index="F" Term="FreeThreaded" /><MSHelp:Keyword Index="F" Term="SequenceConfig.FreeThreaded" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.FreeThreaded" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.FreeThreaded" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the object returned by the Sequence constructor will be free-threaded; that is, usable by multiple threads within a single address space. Note that if multiple threads create multiple sequ ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.FreeThreaded Field</td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetEnumerator Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MultipleDatabaseEntry_GetEnumerator" /><meta name="guid" content="M_BerkeleyDB_MultipleDatabaseEntry_GetEnumerator" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MultipleDatabaseEntry.GetEnumerator" /><MSHelp:TOCTitle Title="GetEnumerator Method " /><MSHelp:RLTitle Title="MultipleDatabaseEntry.GetEnumerator Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MultipleDatabaseEntry.GetEnumerator" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleDatabaseEntryClassGetEnumeratorTopic" /><MSHelp:Keyword Index="K" Term="GetEnumerator method" /><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry.GetEnumerator method" /><MSHelp:Keyword Index="F" Term="GetEnumerator" /><MSHelp:Keyword Index="F" Term="MultipleDatabaseEntry.GetEnumerator" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MultipleDatabaseEntry.GetEnumerator" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry.GetEnumerator" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return an enumerator which iterates over all objects represented by the ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry..::.GetEnumerator Method </td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepProcMsgResult Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RepProcMsgResult" /><meta name="guid" content="Methods_T_BerkeleyDB_RepProcMsgResult" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RepProcMsgResult" /><MSHelp:TOCTitle Title="RepProcMsgResult Methods " /><MSHelp:RLTitle Title="RepProcMsgResult Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RepProcMsgResult" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultMethodsTopic" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepProcMsgResult Methods </td></tr><tr id="headerTableRow3"><td align="left">RepProcMsgResult Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Constructor (UInt32, UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEntry__ctor_3" /><meta name="guid" content="M_BerkeleyDB_DatabaseEntry__ctor_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEntry.#ctor(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="DatabaseEntry Constructor (UInt32, UInt32)" /><MSHelp:RLTitle Title="DatabaseEntry Constructor (UInt32, UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEntry.#ctor(System.UInt32,System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new partial DatabaseEntry object." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Constructor (UInt32, UInt32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxOpenFiles Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolConfig_MaxOpenFiles" /><meta name="guid" content="P_BerkeleyDB_MPoolConfig_MaxOpenFiles" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolConfig.MaxOpenFiles" /><MSHelp:TOCTitle Title="MaxOpenFiles Property " /><MSHelp:RLTitle Title="MPoolConfig.MaxOpenFiles Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolConfig.MaxOpenFiles" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassMaxOpenFilesTopic" /><MSHelp:Keyword Index="K" Term="MaxOpenFiles property" /><MSHelp:Keyword Index="K" Term="MPoolConfig.MaxOpenFiles property" /><MSHelp:Keyword Index="F" Term="MaxOpenFiles" /><MSHelp:Keyword Index="F" Term="MPoolConfig.MaxOpenFiles" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.MaxOpenFiles" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.MaxOpenFiles" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.get_MaxOpenFiles" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.set_MaxOpenFiles" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of file descriptors the library will open concurrently when flushing dirty pages from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.MaxOpenFiles Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullLogBufferException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_FullLogBufferException" /><meta name="guid" content="Methods_T_BerkeleyDB_FullLogBufferException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.FullLogBufferException" /><MSHelp:TOCTitle Title="FullLogBufferException Methods " /><MSHelp:RLTitle Title="FullLogBufferException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.FullLogBufferException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBFullLogBufferExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">FullLogBufferException Methods </td></tr><tr id="headerTableRow3"><td align="left">FullLogBufferException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Register Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_Register" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_Register" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.Register" /><MSHelp:TOCTitle Title="Register Field" /><MSHelp:RLTitle Title="VerboseMessages.Register Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.Register" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassRegisterTopic" /><MSHelp:Keyword Index="K" Term="Register field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.Register field" /><MSHelp:Keyword Index="F" Term="Register"
/><MSHelp:Keyword Index="F" Term="VerboseMessages.Register" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.Register" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.Register" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display additional information concerning support for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.Register Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LoggingSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_LoggingSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_LoggingSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.LoggingSystemStats(System.Boolean)" /><MSHelp:TOCTitle Title="LoggingSystemStats Method (Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.LoggingSystemStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LoggingSystemStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The logging subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LoggingSystemStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MACHINE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ByteOrder_MACHINE" /><meta name="guid" content="F_BerkeleyDB_ByteOrder_MACHINE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ByteOrder.MACHINE" /><MSHelp:TOCTitle Title="MACHINE Field" /><MSHelp:RLTitle Title="ByteOrder.MACHINE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ByteOrder.MACHINE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBByteOrderClassMACHINETopic" /><MSHelp:Keyword Index="K" Term="MACHINE field" /><MSHelp:Keyword Index="K" Term="ByteOrder.MACHINE

field" /><MSHelp:Keyword Index="F" Term="MACHINE" /><MSHelp:Keyword Index="F" Term="ByteOrder.MACHINE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ByteOrder.MACHINE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ByteOrder.MACHINE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The host byte order of the machine where the Berkeley DB library was compiled." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder..::.MACHINE Field</td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EventNotify
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_EventNotify" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_EventNotify" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.EventNotify" /><MSHelp:TOCTitle Title="EventNotify Field"
/><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.EventNotify Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.EventNotify"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassEventNotifyTopic"
/><MSHelp:Keyword Index="K" Term="EventNotify field" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.EventNotify field" /><MSHelp:Keyword Index="F" Term="EventNotify"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.EventNotify" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.EventNotify" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.EventNotify" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A delegate which is called to notify the process
of specific Berkeley DB events." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig<span
class="languageSpecificText">..<span
class="cpp">::.EventNotify Field</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>JoinCursor Methods </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_JoinCursor" /><meta name="guid"
content="Methods_T_BerkeleyDB_JoinCursor"
/><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.JoinCursor" /><MSHelp:TOCTitle
Title="JoinCursor Methods " /><MSHelp:RLTitle Title="JoinCursor Methods (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.JoinCursor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBJoinCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="JoinCursor class,
methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor Methods </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_SequenceConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_SequenceConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.SequenceConfig" /><MSHelp:TOCTitle Title="SequenceConfig Fields" /><MSHelp:RLTitle Title="SequenceConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.SequenceConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="SequenceConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" />
 <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
<label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SequenceConfig Fields</td></tr><tr id="headerTableRow3"><td
align="left">SequenceConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MultipleDatabaseEntry Constructor (IEnumerable(UInt32))</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_MultipleDatabaseEntry__ctor_2" /><meta name="guid"
content="M_BerkeleyDB_MultipleDatabaseEntry__ctor_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.MultipleDatabaseEntry.#ctor(System.Collections.Generic.IEnumerable{System.UInt32})"
/><MSHelp:TOCTitle Title="MultipleDatabaseEntry Constructor (IEnumerable(UInt32))" /><MSHelp:RLTitle
Title="MultipleDatabaseEntry Constructor (IEnumerable(UInt32)) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.MultipleDatabaseEntry.#ctor(System.Collections.Generic.IEnumerable{System.UInt32})"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry..ctor"
/><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Construct a new
key or data bulk buffer with a bunch of record numbers, as keys in or" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Constructor (IEnumerable<(Of <(UInt32>)>))</td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InHostOrder Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_InHostOrder" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_InHostOrder" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.InHostOrder" /><MSHelp:TOCTitle Title="InHostOrder Property " /><MSHelp:RLTitle Title="BaseDatabase.InHostOrder Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.InHostOrder" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassInHostOrderTopic" /><MSHelp:Keyword Index="K" Term="InHostOrder property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.InHostOrder property" /><MSHelp:Keyword Index="F" Term="InHostOrder" /><MSHelp:Keyword Index="F" Term="BaseDatabase.InHostOrder" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.InHostOrder" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.InHostOrder" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_InHostOrder" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the underlying database files were created on an architecture of the same byte order as the current one. This information may be used to determine whether application data needs to be adj ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.InHostOrder Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Consume Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Consume" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Consume" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Consume(System.Boolean)"
/><MSHelp:TOCTitle Title="Consume Method (Boolean)" /><MSHelp:RLTitle Title="QueueDatabase.Consume Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Consume(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Consume" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the record number and data from the available record closest to the head of the queue, and delete the record." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Consume Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryQueueDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryQueueDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryQueueDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.SecondaryQueueDatabase.Open(System.String,BerkeleyDB.SecondaryQueueDatabaseConfig,BerkeleyDB.Transaction)"
/><MSHelp:TOCTitle Title="Open Method (String, SecondaryQueueDatabaseConfig, Transaction)"
/><MSHelp:RLTitle Title="SecondaryQueueDatabase.Open Method (String, SecondaryQueueDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryQueueDatabase.Open(System.String,BerkeleyDB.SecondaryQueueDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryQueueDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryQueueDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryQueueDatabase<span

class="cs">..::.Open Method (String, SecondaryQueueDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepClockskewFast Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepClockskewFast" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepClockskewFast" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepClockskewFast" /><MSHelp:TOCTitle Title="RepClockskewFast Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepClockskewFast Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepClockskewFast" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepClockskewFastTopic" /><MSHelp:Keyword Index="K" Term="RepClockskewFast property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepClockskewFast property" /><MSHelp:Keyword Index="F" Term="RepClockskewFast" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepClockskewFast" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepClockskewFast" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepClockskewFast" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepClockskewFast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The value, relative to , of the fastest clock in the group of sites." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepClockskewFast Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SingleDir Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BackupOptions_SingleDir" /><meta name="guid" content="F_BerkeleyDB_BackupOptions_SingleDir" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BackupOptions.SingleDir" /><MSHelp:TOCTitle Title="SingleDir Field" /><MSHelp:RLTitle Title="BackupOptions.SingleDir Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BackupOptions.SingleDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassSingleDirTopic" /><MSHelp:Keyword Index="K" Term="SingleDir field" /><MSHelp:Keyword Index="K" Term="BackupOptions.SingleDir field" /><MSHelp:Keyword Index="F" Term="SingleDir"

/><MSHelp:Keyword Index="F" Term="BackupOptions.SingleDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.SingleDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions.SingleDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, then regardless of the directory structure used by the source environment, place all back up files in the single target directory. Use this option if absolute path names to your enviro ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions..::.SingleDir Field</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbChannel Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DbChannel" /><meta name="guid" content="Properties_T_BerkeleyDB_DbChannel" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DbChannel" /><MSHelp:TOCTitle Title="DbChannel Properties " /><MSHelp:RLTitle Title="DbChannel Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DbChannel" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DbChannel class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel Properties </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_KeyRange" /><meta name="guid" content="AllMembers_T_BerkeleyDB_KeyRange" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.KeyRange" /><MSHelp:TOCTitle Title="KeyRange Members" /><MSHelp:RLTitle Title="KeyRange Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.KeyRange" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyRangeMembersTopic" /><MSHelp:Keyword Index="K" Term="KeyRange class" /><MSHelp:Keyword Index="K" Term="KeyRange class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.KeyRange class" /><MSHelp:Keyword Index="F" Term="KeyRange" /><MSHelp:Keyword

Index="F" Term="BerkeleyDB.KeyRange" /><MSHelp:Attr Name="HelpPriority"
Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox"
type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label
class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyRange Members</td></tr><tr id="headerTableRow3"><td align="left">KeyRange Class Methods Properties See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (String, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Remove_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Remove_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Remove(System.String,System.Boolean)" /><MSHelp:TOCTitle Title="Remove Method (String, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.Remove Method (String, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Remove(System.String,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Destroy a Berkeley DB environment if it is not currently in use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Remove Method (String, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbChannel Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DbChannel" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DbChannel" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DbChannel" /><MSHelp:TOCTitle Title="DbChannel Members" /><MSHelp:RLTitle Title="DbChannel Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DbChannel" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelMembersTopic" /><MSHelp:Keyword Index="K" Term="DbChannel class" /><MSHelp:Keyword Index="K" Term="DbChannel class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbChannel class" /><MSHelp:Keyword Index="F" Term="DbChannel" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbChannel" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel Members</td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class Methods Properties See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (DatabaseEntry, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultiple" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:TOCTitle Title="MoveMultiple Method (DatabaseEntry, Boolean)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (DatabaseEntry, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store that key and as many duplicate data items associated with the given key that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
  <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultiple Method (DatabaseEntry, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Version Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_Version" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_Version" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.Version" /><MSHelp:TOCTitle Title="Version Property " /><MSHelp:RLTitle Title="BTreeStats.Version Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.Version" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassVersionTopic" /><MSHelp:Keyword Index="K" Term="Version property"

/><MSHelp:Keyword Index="K" Term="BTreeStats.Version property" /><MSHelp:Keyword Index="F" Term="Version" /><MSHelp:Keyword Index="F" Term="BTreeStats.Version" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.Version"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.Version" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_Version" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Version number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.Version Property </td></tr><tr id="headerTableRow3"><td
align="left">BTreeStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Get" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Get(System.UInt32)" /><MSHelp:TOCTitle Title="Get Method (UInt32)" /><MSHelp:RLTitle Title="BTreeDatabase.Get Method (UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Get(System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key/data pair from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Get Method (UInt32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_OverflowPages" /><meta name="guid" content="P_BerkeleyDB_HashStats_OverflowPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.OverflowPages" /><MSHelp:TOCTitle Title="OverflowPages Property " /><MSHelp:RLTitle Title="HashStats.OverflowPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.OverflowPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassOverflowPagesTopic" /><MSHelp:Keyword Index="K" Term="OverflowPages property" /><MSHelp:Keyword Index="K" Term="HashStats.OverflowPages property" /><MSHelp:Keyword Index="F" Term="OverflowPages" /><MSHelp:Keyword Index="F" Term="HashStats.OverflowPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.OverflowPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.OverflowPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_OverflowPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of overflow pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">HashStats.<span
class="vb">.::.OverflowPages Property
</td></tr><tr
id="headerTableRow3"><td align="left">HashStats Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AllocatedLocks
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_AllocatedLocks" /><meta name="guid" content="P_BerkeleyDB_LockStats_AllocatedLocks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.AllocatedLocks" /><MSHelp:TOCTitle Title="AllocatedLocks Property " /><MSHelp:RLTitle Title="LockStats.AllocatedLocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.AllocatedLocks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassAllocatedLocksTopic" /><MSHelp:Keyword Index="K" Term="AllocatedLocks property" /><MSHelp:Keyword Index="K" Term="LockStats.AllocatedLocks property" /><MSHelp:Keyword Index="F" Term="AllocatedLocks" /><MSHelp:Keyword Index="F" Term="LockStats.AllocatedLocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.AllocatedLocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.AllocatedLocks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_AllocatedLocks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current number of locks allocated." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.AllocatedLocks Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationLease Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_ReplicationLease" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_ReplicationLease" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.ReplicationLease" /><MSHelp:TOCTitle Title="ReplicationLease Field" /><MSHelp:RLTitle Title="VerboseMessages.ReplicationLease Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationLease" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationLeaseTopic" /><MSHelp:Keyword Index="K" Term="ReplicationLease field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationLease field" /><MSHelp:Keyword Index="F" Term="ReplicationLease" /><MSHelp:Keyword Index="F" Term="VerboseMessages.ReplicationLease" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.ReplicationLease" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.ReplicationLease" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about replication master leases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.ReplicationLease Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="HeapDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Close method" /><MSHelp:Keyword Index="F"

Term="Close" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"

for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MovePrevDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="BTreeCursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMovePrevDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MovePrevDuplicate method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MovePrevDuplicate method" /><MSHelp:Keyword Index="F" Term="MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MovePrevDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Snapshot Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_SecondaryRecnoDatabase_Snapshot" /><meta name="guid"
content="P_BerkeleyDB_SecondaryRecnoDatabase_Snapshot" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryRecnoDatabase.Snapshot" /><MSHelp:TOCTitle Title="Snapshot Property "
/><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Snapshot Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabase.Snapshot" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassSnapshotTopic" /><MSHelp:Keyword Index="K"
Term="Snapshot property" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Snapshot property"
/><MSHelp:Keyword Index="F" Term="Snapshot" /><MSHelp:Keyword Index="F"
Term="SecondaryRecnoDatabase.Snapshot" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryRecnoDatabase.Snapshot" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabase.Snapshot" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabase.get_Snapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, any file
will be read in its entirety when is called. If false, may be read lazily." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Snapshot Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintMPoolSystemStats Method (Boolean, Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats_2" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats(System.Boolean,System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintMPoolSystemStats Method (Boolean, Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintMPoolSystemStats Method (Boolean, Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats(System.Boolean,System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the memory pool (that is, buffer cache) subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintMPoolSystemStats Method (Boolean, Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetBothMultiple_1" /><meta name="guid" content="M_BerkeleyDB_Database_GetBothMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Int32)" /><MSHelp:TOCTitle Title="GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32)" /><MSHelp:RLTitle Title="Database.GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If a key/data pair in the database matches and , return the key and all duplicate data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GroupCreator Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSiteConfig_GroupCreator" /><meta name="guid" content="P_BerkeleyDB_DbSiteConfig_GroupCreator" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSiteConfig.GroupCreator" /><MSHelp:TOCTitle Title="GroupCreator Property " /><MSHelp:RLTitle Title="DbSiteConfig.GroupCreator Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSiteConfig.GroupCreator" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassGroupCreatorTopic" /><MSHelp:Keyword Index="K" Term="GroupCreator property" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.GroupCreator property" /><MSHelp:Keyword Index="F" Term="GroupCreator" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.GroupCreator" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.GroupCreator" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.GroupCreator" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.get_GroupCreator" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.set_GroupCreator" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is a group creator." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.GroupCreator Property </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactData Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_CompactData" /><meta name="guid" content="Properties_T_BerkeleyDB_CompactData" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.CompactData" /><MSHelp:TOCTitle Title="CompactData Properties "

/><MSHelp:RLTitle Title="CompactData Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.CompactData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataPropertiesTopic" /><MSHelp:Keyword Index="K" Term="CompactData class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
 class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"
 cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
 style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
 data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"

onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
/> <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData Properties </td></tr><tr id="headerTableRow3"><td align="left">CompactData Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NCaches Field</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CacheInfo_NCaches" /><meta name="guid" content="F_BerkeleyDB_CacheInfo_NCaches" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CacheInfo.NCaches" /><MSHelp:TOCTitle Title="NCaches Field" /><MSHelp:RLTitle Title="CacheInfo.NCaches
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CacheInfo.NCaches" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoClassNCachesTopic" /><MSHelp:Keyword Index="K" Term="NCaches field" /><MSHelp:Keyword Index="K" Term="CacheInfo.NCaches field" /><MSHelp:Keyword Index="F" Term="NCaches" /><MSHelp:Keyword Index="F" Term="CacheInfo.NCaches" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CacheInfo.NCaches" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CacheInfo.NCaches" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of caches" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CacheInfo..::.NCaches Field</td></tr><tr id="headerTableRow3"><td align="left">CacheInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FileSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_FileSize" /><meta name="guid" content="P_BerkeleyDB_LogStats_FileSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.FileSize" /><MSHelp:TOCTitle Title="FileSize Property " /><MSHelp:RLTitle Title="LogStats.FileSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.FileSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassFileSizeTopic" /><MSHelp:Keyword Index="K" Term="FileSize property" /><MSHelp:Keyword Index="K" Term="LogStats.FileSize property" /><MSHelp:Keyword Index="F"

Term="FileSize" /><MSHelp:Keyword Index="F" Term="LogStats.FileSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.FileSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.FileSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_FileSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log file size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.FileSize Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMessageDispatch Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepMessageDispatch" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepMessageDispatch" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepMessageDispatch" /><MSHelp:TOCTitle Title="RepMessageDispatch Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMessageDispatch Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepMessageDispatch" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMessageDispatchTopic" /><MSHelp:Keyword Index="K" Term="RepMessageDispatch property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMessageDispatch property" /><MSHelp:Keyword Index="F" Term="RepMessageDispatch" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMessageDispatch" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMessageDispatch" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMessageDispatch" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepMessageDispatch" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepMessageDispatch" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the message dispatch function. It is responsible for receiving messages sent from remote sites using either or . If the message received by this function was sent using , then n ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMessageDispatch Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_Priority" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.Priority" /><MSHelp:TOCTitle Title="Priority Property " /><MSHelp:RLTitle Title="ActiveTransaction.Priority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.Priority property" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.Priority"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.Priority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Assigned priority used when resolving deadlocks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction..::.Priority Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseMVCC Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UseMVCC" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UseMVCC" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UseMVCC" /><MSHelp:TOCTitle Title="UseMVCC Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UseMVCC Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UseMVCC" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUseMVCCTopic" /><MSHelp:Keyword Index="K" Term="UseMVCC property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UseMVCC property" /><MSHelp:Keyword Index="F" Term="UseMVCC" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UseMVCC" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UseMVCC" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UseMVCC" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UseMVCC" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_UseMVCC" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, all databases in the environment will be opened as if was set." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UseMVCC Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationElection Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_ReplicationElection" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_ReplicationElection" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.ReplicationElection" /><MSHelp:TOCTitle Title="ReplicationElection Field" /><MSHelp:RLTitle Title="VerboseMessages.ReplicationElection Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationElection" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationElectionTopic" /><MSHelp:Keyword Index="K" Term="ReplicationElection field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationElection field" /><MSHelp:Keyword Index="F" Term="ReplicationElection" /><MSHelp:Keyword
Index="F" Term="VerboseMessages.ReplicationElection" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.ReplicationElection" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.VerboseMessages.ReplicationElection" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about replication elections." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.ReplicationElection Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryHashDatabaseConfig Methods " /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NSites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_NSites" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_NSites" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.NSites" /><MSHelp:TOCTitle Title="NSites Property " /><MSHelp:RLTitle Title="ReplicationConfig.NSites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.NSites" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassNSitesTopic" /><MSHelp:Keyword Index="K" Term="NSites property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.NSites property" /><MSHelp:Keyword Index="F" Term="NSites" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.NSites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.NSites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.NSites" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.ReplicationConfig.get_NSites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_NSites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The total number of sites in the replication group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.NSites Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapRecordId Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HeapRecordId" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HeapRecordId" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HeapRecordId" /><MSHelp:TOCTitle Title="HeapRecordId Members" /><MSHelp:RLTitle Title="HeapRecordId Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HeapRecordId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdMembersTopic" /><MSHelp:Keyword Index="K" Term="HeapRecordId class" /><MSHelp:Keyword Index="K" Term="HeapRecordId class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapRecordId class" /><MSHelp:Keyword Index="F" Term="HeapRecordId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId Members</td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class Constructors Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_MutexConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_MutexConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.MutexConfig" /><MSHelp:TOCTitle Title="MutexConfig Methods " /><MSHelp:RLTitle Title="MutexConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.MutexConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="MutexConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"

/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig

Methods </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepUseMasterLeases Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepUseMasterLeases" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepUseMasterLeases" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepUseMasterLeases" /><MSHelp:TOCTitle Title="RepUseMasterLeases Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepUseMasterLeases Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepUseMasterLeases" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepUseMasterLeasesTopic" /><MSHelp:Keyword Index="K" Term="RepUseMasterLeases property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepUseMasterLeases property" /><MSHelp:Keyword Index="F" Term="RepUseMasterLeases" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepUseMasterLeases" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepUseMasterLeases" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepUseMasterLeases" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepUseMasterLeases" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepUseMasterLeases" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, master leases will be used for this site (defaults to false)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepUseMasterLeases Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="RecnoDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="Overload:BerkeleyDB.RecnoDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input

id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox"
data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolFileStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_MPoolFileStats" /><meta name="guid" content="Methods_T_BerkeleyDB_MPoolFileStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.MPoolFileStats" /><MSHelp:TOCTitle Title="MPoolFileStats Methods " /><MSHelp:RLTitle Title="MPoolFileStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.MPoolFileStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="MPoolFileStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats Methods </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BigPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_BigPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_HashStats_BigPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.BigPagesFreeBytes" /><MSHelp:TOCTitle Title="BigPagesFreeBytes Property " /><MSHelp:RLTitle Title="HashStats.BigPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.BigPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassBigPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="BigPagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="HashStats.BigPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="BigPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="HashStats.BigPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.BigPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.BigPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_BigPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free on big item pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.BigPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockResolution Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LockingConfig_DeadlockResolution" /><meta name="guid" content="F_BerkeleyDB_LockingConfig_DeadlockResolution" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LockingConfig.DeadlockResolution" /><MSHelp:TOCTitle Title="DeadlockResolution Field" /><MSHelp:RLTitle Title="LockingConfig.DeadlockResolution Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LockingConfig.DeadlockResolution" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigClassDeadlockResolutionTopic" /><MSHelp:Keyword Index="K" Term="DeadlockResolution field" /><MSHelp:Keyword Index="K" Term="LockingConfig.DeadlockResolution field" /><MSHelp:Keyword Index="F" Term="DeadlockResolution" /><MSHelp:Keyword Index="F" Term="LockingConfig.DeadlockResolution" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.DeadlockResolution" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.DeadlockResolution" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If non-null, the deadlock detector is to be run whenever a lock conflict occurs, lock request(s) should be rejected according to the specified policy." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.DeadlockResolution Field</td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Remove_1" /><meta name="guid" content="M_BerkeleyDB_Sequence_Remove_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Remove(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Remove Method (Transaction)" /><MSHelp:RLTitle Title="Sequence.Remove Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Remove(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the sequence from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Remove Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoLocking Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoLocking" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoLocking" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.NoLocking" /><MSHelp:TOCTitle Title="NoLocking Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.NoLocking Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.NoLocking" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassNoLockingTopic" /><MSHelp:Keyword Index="K" Term="NoLocking field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.NoLocking field" /><MSHelp:Keyword Index="F" Term="NoLocking" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.NoLocking" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.NoLocking" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.NoLocking" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will grant all requested mutual exclusion mutexes and database locks without regard for their actual availability. This functionality should never be used for purposes other th ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.NoLocking Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ActiveTransaction Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_ActiveTransaction" /><meta name="guid" content="Properties_T_BerkeleyDB_ActiveTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.ActiveTransaction" /><MSHelp:TOCTitle Title="ActiveTransaction Properties " /><MSHelp:RLTitle Title="ActiveTransaction Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.ActiveTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="ActiveTransaction class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction Properties </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EId Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RepMgrSite_EId" /><meta name="guid" content="F_BerkeleyDB_RepMgrSite_EId" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RepMgrSite.EId" /><MSHelp:TOCTitle Title="EId Field" /><MSHelp:RLTitle Title="RepMgrSite.EId Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepMgrSite.EId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrSiteClassEIdTopic" /><MSHelp:Keyword Index="K" Term="EId field" /><MSHelp:Keyword Index="K" Term="RepMgrSite.EId field" /><MSHelp:Keyword Index="F" Term="EId" /><MSHelp:Keyword Index="F" Term="RepMgrSite.EId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrSite.EId" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrSite.EId" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Environment ID assigned by the replication manager. This is the same value that is passed to for the event." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrSite..::.EId Field</td></tr><tr id="headerTableRow3"><td align="left">RepMgrSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Records Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_Records" /><meta name="guid" content="P_BerkeleyDB_LogStats_Records" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.Records" /><MSHelp:TOCTitle Title="Records Property " /><MSHelp:RLTitle Title="LogStats.Records Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.Records" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassRecordsTopic" /><MSHelp:Keyword Index="K" Term="Records property" /><MSHelp:Keyword Index="K" Term="LogStats.Records property" /><MSHelp:Keyword Index="F" Term="Records" /><MSHelp:Keyword Index="F" Term="LogStats.Records" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.Records" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.Records" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_Records" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Records entered into the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.Records Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_KeyRange_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_KeyRange_1" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.BTreeDatabase.KeyRange(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)"
/><MSHelp:TOCTitle Title="KeyRange Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle
Title="BTreeDatabase.KeyRange Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.BTreeDatabase.KeyRange(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.KeyRange"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Return an estimate of the proportion of keys that are less than, equal to,
and greater than the specified key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeDatabase.<span
class="vb">.::.KeyRange

Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbThreadID Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_DbThreadID" /><meta name="guid" content="Fields_T_BerkeleyDB_DbThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.DbThreadID" /><MSHelp:TOCTitle Title="DbThreadID Fields" /><MSHelp:RLTitle Title="DbThreadID Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.DbThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbThreadIDFieldsTopic" /><MSHelp:Keyword Index="K" Term="DbThreadID class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label

id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID Fields</td></tr><tr id="headerTableRow3"><td align="left">DbThreadID Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (DatabaseEntry, Boolean, Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (DatabaseEntry, Boolean, Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (DatabaseEntry, Boolean, Int32,

LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey"
/><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store that key and as many ensuing key/data pairs that can fit in a buffer the size of in ."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">Cursor.<span
class="vb">.::.MoveMultipleKey Method
(DatabaseEntry, Boolean, Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabase_Duplicates" /><meta name="guid" content="P_BerkeleyDB_HashDatabase_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabase.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Property " /><MSHelp:RLTitle Title="HashDatabase.Duplicates Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabase.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates property" /><MSHelp:Keyword Index="K" Term="HashDatabase.Duplicates property" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="HashDatabase.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Duplicates" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.get_Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the insertion of duplicate data items in the database is permitted, and whether duplicates items are sorted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Duplicates Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Locks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_Locks" /><meta name="guid" content="P_BerkeleyDB_LockStats_Locks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.Locks" /><MSHelp:TOCTitle Title="Locks Property " /><MSHelp:RLTitle Title="LockStats.Locks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.Locks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLocksTopic" /><MSHelp:Keyword Index="K" Term="Locks property" /><MSHelp:Keyword Index="K" Term="LockStats.Locks property" /><MSHelp:Keyword Index="F" Term="Locks" /><MSHelp:Keyword Index="F" Term="LockStats.Locks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.Locks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.Locks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_Locks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current number of locks."

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.Locks Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirst_3" /><meta
name="guid" content="M_BerkeleyDB_Cursor_MoveFirst_3" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveFirst(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirst
Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveFirst Method (LockingInfo) (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirst(BerkeleyDB.LockingInfo)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirst"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store
that pair in . If the first key has duplicate values, the first data item in the set of duplicates is stored in . ..."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirst Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_Refresh" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="Cursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.Refresh" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassRefreshTopic" /><MSHelp:Keyword Index="K" Term="Refresh method" /><MSHelp:Keyword Index="K" Term="Cursor.Refresh method" /><MSHelp:Keyword Index="F" Term="Refresh" /><MSHelp:Keyword Index="F" Term="Cursor.Refresh" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.Refresh Method
</td></tr><tr id="headerTableRow3"><td align="left">Cursor
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReverseSplit
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_ReverseSplit" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_ReverseSplit" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.ReverseSplit" /><MSHelp:TOCTitle Title="ReverseSplit Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.ReverseSplit Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.ReverseSplit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassReverseSplitTopic" /><MSHelp:Keyword Index="K" Term="ReverseSplit property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.ReverseSplit property" /><MSHelp:Keyword Index="F" Term="ReverseSplit" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.ReverseSplit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.ReverseSplit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.ReverseSplit" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_ReverseSplit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If false, empty pages will not be coalesced into higher-level pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryBTreeDatabase.<span
class="vb">.::.ReverseSplit Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryBTreeDatabase.htm">SecondaryBTreeDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>RepMgrStartMaster Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_RepMgrStartMaster"
/><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrStartMaster"
/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrStartMaster(System.Int32)" /><MSHelp:TOCTitle
Title="RepMgrStartMaster Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrStartMaster
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrStartMaster(System.Int32)" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrStartMasterTopic" /><MSHelp:Keyword Index="K"
Term="RepMgrStartMaster method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepMgrStartMaster method" /><MSHelp:Keyword Index="F"
Term="RepMgrStartMaster" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrStartMaster"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrStartMaster" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepMgrStartMaster" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Start the replication manager as a master site, and do not call for an election." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrStartMaster Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cachesize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Cachesize" /><meta name="guid" content="P_BerkeleyDB_Sequence_Cachesize" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.Sequence.Cachesize" /><MSHelp:TOCTitle Title="Cachesize Property " /><MSHelp:RLTitle Title="Sequence.Cachesize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Cachesize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassCachesizeTopic" /><MSHelp:Keyword Index="K" Term="Cachesize property" /><MSHelp:Keyword Index="K" Term="Sequence.Cachesize property" /><MSHelp:Keyword Index="F" Term="Cachesize" /><MSHelp:Keyword
Index="F" Term="Sequence.Cachesize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Cachesize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Cachesize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Cachesize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The current cache size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">Sequence..::.Cachesize Property </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (UInt32, Int32, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_GetMultiple_2" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_GetMultiple_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32,System.Int32,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="GetMultiple Method (UInt32, Int32, Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.GetMultiple Method (UInt32, Int32, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32,System.Int32,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.GetMultiple Method (UInt32, Int32, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Primary Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryDatabaseConfig_Primary" /><meta name="guid" content="P_BerkeleyDB_SecondaryDatabaseConfig_Primary" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabaseConfig.Primary" /><MSHelp:TOCTitle Title="Primary Property " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.Primary Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryDatabaseConfig.Primary" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassPrimaryTopic" /><MSHelp:Keyword Index="K" Term="Primary property" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.Primary property" /><MSHelp:Keyword Index="F" Term="Primary" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig.Primary" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.Primary" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.Primary" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.SecondaryDatabaseConfig.get_Primary" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.set_Primary" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="All updates to Primary will be automatically reflected in the secondary and all reads from the secondary will return corresponding data from Primary." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.Primary Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>toArray Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_HeapRecordId_toArray" /><meta name="guid"
content="M_BerkeleyDB_HeapRecordId_toArray" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HeapRecordId.toArray" /><MSHelp:TOCTitle Title="toArray Method "
/><MSHelp:RLTitle Title="HeapRecordId.toArray Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.HeapRecordId.toArray" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapRecordId.toArray" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return a byte
array representing this record id." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.toArray Method </td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoMMap Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_NoMMap" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_NoMMap" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.NoMMap" /><MSHelp:TOCTitle Title="NoMMap Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.NoMMap Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.NoMMap" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassNoMMapTopic" /><MSHelp:Keyword Index="K" Term="NoMMap property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.NoMMap property" /><MSHelp:Keyword Index="F" Term="NoMMap" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.NoMMap" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.NoMMap" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.NoMMap" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_NoMMap" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_NoMMap" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will copy read-only database files into the local cache instead of potentially mapping them into process memory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.NoMMap Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BerkeleyDB Namespace</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="N_BerkeleyDB" /><meta name="guid"
content="N_BerkeleyDB" /><xml><MSHelp:Attr Name="AssetID" Value="N:BerkeleyDB" /><MSHelp:TOCTitle
Title="BerkeleyDB Namespace" /><MSHelp:RLTitle Title="BerkeleyDB Namespace ()" /><MSHelp:Keyword
Index="A" Term="N:BerkeleyDB" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDB"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB namespace" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value=" " /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">BerkeleyDB
Namespace</td></tr><tr id="headerTableRow3"><td align="left">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nData Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_HashStats_nData" /><meta name="guid" content="P_BerkeleyDB_HashStats_nData"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.nData" /><MSHelp:TOCTitle
Title="nData Property " /><MSHelp:RLTitle Title="HashStats.nData Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.nData" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashStatsClassnDataTopic" /><MSHelp:Keyword Index="K" Term="nData
property" /><MSHelp:Keyword Index="K" Term="HashStats.nData property" /><MSHelp:Keyword Index="F"
Term="nData" /><MSHelp:Keyword Index="F" Term="HashStats.nData" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashStats.nData" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HashStats.nData" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HashStats.get_nData" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of data items."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats<span
class="languageSpecificText">..::.nData Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css"
href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_LogConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_LogConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.LogConfig.#ctor" /><MSHelp:TOCTitle Title="LogConfig Constructor " /><MSHelp:RLTitle Title="LogConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LogConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="LogConfig class, constructor" /><MSHelp:Keyword Index="K" Term="LogConfig.LogConfig constructor" /><MSHelp:Keyword Index="F" Term="LogConfig" /><MSHelp:Keyword Index="F" Term="LogConfig.LogConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.LogConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">LogConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TimeNotGranted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_DatabaseEnvironment_TimeNotGranted" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_TimeNotGranted" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.TimeNotGranted" /><MSHelp:TOCTitle Title="TimeNotGranted
Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TimeNotGranted Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TimeNotGranted"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTimeNotGrantedTopic"
/><MSHelp:Keyword Index="K" Term="TimeNotGranted property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.TimeNotGranted property" /><MSHelp:Keyword Index="F"
Term="TimeNotGranted" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TimeNotGranted"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TimeNotGranted" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TimeNotGranted"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TimeNotGranted"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TimeNotGranted"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, database calls timing out based on lock or transaction timeout values will throw
instead of ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TimeNotGranted Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DataPagesBytesFree Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_DataPagesBytesFree" /><meta name="guid" content="P_BerkeleyDB_QueueStats_DataPagesBytesFree" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.DataPagesBytesFree" /><MSHelp:TOCTitle Title="DataPagesBytesFree Property " /><MSHelp:RLTitle Title="QueueStats.DataPagesBytesFree Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.DataPagesBytesFree" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassDataPagesBytesFreeTopic" /><MSHelp:Keyword Index="K" Term="DataPagesBytesFree property" /><MSHelp:Keyword Index="K" Term="QueueStats.DataPagesBytesFree property" /><MSHelp:Keyword Index="F" Term="DataPagesBytesFree" /><MSHelp:Keyword Index="F" Term="QueueStats.DataPagesBytesFree" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.DataPagesBytesFree" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.DataPagesBytesFree" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_DataPagesBytesFree" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in data pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.DataPagesBytesFree Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbThreadID Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DbThreadID__ctor" /><meta name="guid"
content="M_BerkeleyDB_DbThreadID__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DbThreadID.#ctor(System.Int32,System.UInt32)" /><MSHelp:TOCTitle
Title="DbThreadID Constructor " /><MSHelp:RLTitle Title="DbThreadID Constructor (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbThreadID.#ctor(System.Int32,System.UInt32)"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbThreadIDClassctorTopic" /><MSHelp:Keyword
Index="K" Term="DbThreadID class, constructor" /><MSHelp:Keyword Index="K"
Term="DbThreadID.DbThreadID
 constructor" /><MSHelp:Keyword Index="F" Term="DbThreadID" /><MSHelp:Keyword Index="F"
Term="DbThreadID.DbThreadID" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DbThreadID.DbThreadID" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbThreadID..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new DbThreadID
object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
 title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)"
 tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
 none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID Constructor </td></tr><tr id="headerTableRow3"><td align="left">DbThreadID Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_ThreadCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_ThreadCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.ThreadCount" /><MSHelp:TOCTitle Title="ThreadCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.ThreadCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.ThreadCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassThreadCountTopic" /><MSHelp:Keyword Index="K" Term="ThreadCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.ThreadCount property" /><MSHelp:Keyword Index="F" Term="ThreadCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.ThreadCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.ThreadCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.ThreadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_ThreadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.set_ThreadCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An approximate number of threads in the database environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.ThreadCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_LockingConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_LockingConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.LockingConfig.#ctor" /><MSHelp:TOCTitle Title="LockingConfig Constructor " /><MSHelp:RLTitle Title="LockingConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.LockingConfig.#ctor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="LockingConfig
class, constructor" /><MSHelp:Keyword Index="K" Term="LockingConfig.LockingConfig constructor"
/><MSHelp:Keyword Index="F" Term="LockingConfig" /><MSHelp:Keyword Index="F"
Term="LockingConfig.LockingConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockingConfig.LockingConfig" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig
Constructor </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_LockingConfig.htm">LockingConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_CompactConfig" /><meta name="guid" content="T_BerkeleyDB_CompactConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.CompactConfig" /><MSHelp:TOCTitle Title="CompactConfig Class" /><MSHelp:RLTitle Title="CompactConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.CompactConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassTopic" /><MSHelp:Keyword Index="K" Term="CompactConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CompactConfig class" /><MSHelp:Keyword Index="K" Term="CompactConfig class, about CompactConfig class" /><MSHelp:Keyword Index="F" Term="CompactConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class to represent configuration settings for and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForcedRerequests Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ForcedRerequests" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ForcedRerequests" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ForcedRerequests" /><MSHelp:TOCTitle Title="ForcedRerequests Property " /><MSHelp:RLTitle Title="ReplicationStats.ForcedRerequests Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ForcedRerequests" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassForcedRerequestsTopic" /><MSHelp:Keyword Index="K" Term="ForcedRerequests property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ForcedRerequests property" /><MSHelp:Keyword Index="F" Term="ForcedRerequests" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ForcedRerequests" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ForcedRerequests" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ForcedRerequests" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ForcedRerequests" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of forced rerequests." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ForcedRerequests Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashCursor Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HashCursor" /><meta name="guid" content="Methods_T_BerkeleyDB_HashCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HashCursor" /><MSHelp:TOCTitle Title="HashCursor Methods " /><MSHelp:RLTitle Title="HashCursor Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HashCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="HashCursor class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple
</nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor Methods </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="HashDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="HashDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase.<span

class="vb">.::.Exists Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashDatabase.htm">HashDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>ErrorPrefix Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_BaseDatabase_ErrorPrefix" /><meta name="guid"
 content="P_BerkeleyDB_BaseDatabase_ErrorPrefix" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BaseDatabase.ErrorPrefix" /><MSHelp:TOCTitle Title="ErrorPrefix Property "
/><MSHelp:RLTitle Title="BaseDatabase.ErrorPrefix Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.ErrorPrefix" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassErrorPrefixTopic" /><MSHelp:Keyword Index="K" Term="ErrorPrefix
property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.ErrorPrefix property" /><MSHelp:Keyword
Index="F" Term="ErrorPrefix" /><MSHelp:Keyword Index="F" Term="BaseDatabase.ErrorPrefix"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.ErrorPrefix" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.ErrorPrefix" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BaseDatabase.get_ErrorPrefix" /><MSHelp:Attr Name="APIName"
 Value="BerkeleyDB.BaseDatabase.set_ErrorPrefix" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The prefix string
that appears before error messages issued by Berkeley DB." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none;
 height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.ErrorPrefix Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockModes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockModes" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockModes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockModes" /><MSHelp:TOCTitle Title="LockModes Property " /><MSHelp:RLTitle Title="LockStats.LockModes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockModes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockModesTopic" /><MSHelp:Keyword Index="K" Term="LockModes property" /><MSHelp:Keyword Index="K" Term="LockStats.LockModes property" /><MSHelp:Keyword

Index="F" Term="LockModes" /><MSHelp:Keyword Index="F" Term="LockStats.LockModes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockModes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockModes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockModes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lock modes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockModes Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoMMap Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoMMap" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoMMap" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.NoMMap" /><MSHelp:TOCTitle Title="NoMMap Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.NoMMap Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.NoMMap" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassNoMMapTopic" /><MSHelp:Keyword Index="K" Term="NoMMap field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.NoMMap field" /><MSHelp:Keyword Index="F" Term="NoMMap" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.NoMMap" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.NoMMap" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.NoMMap" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will copy read-only database files into the local cache instead of potentially mapping them into process memory (see for further information)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.NoMMap Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_MPoolSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_MPoolSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:TOCTitle Title="MPoolSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.MPoolSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The memory pool (that is, the buffer cache) subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MPoolSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeafPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_LeafPages" /><meta
name="guid" content="P_BerkeleyDB_RecnoStats_LeafPages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.RecnoStats.LeafPages" /><MSHelp:TOCTitle Title="LeafPages Property "
/><MSHelp:RLTitle Title="RecnoStats.LeafPages Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.LeafPages" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoStatsClassLeafPagesTopic" /><MSHelp:Keyword Index="K" Term="LeafPages
property" /><MSHelp:Keyword Index="K" Term="RecnoStats.LeafPages property" /><MSHelp:Keyword
Index="F" Term="LeafPages" /><MSHelp:Keyword Index="F" Term="RecnoStats.LeafPages"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.LeafPages" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RecnoStats.LeafPages" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoStats.get_LeafPages" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Leaf pages."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RecnoStats.<span
class="vb">.::.LeafPages Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoStats.htm">RecnoStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorCodes
Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_ErrorCodes__ctor" /><meta name="guid"
content="M_BerkeleyDB_ErrorCodes__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.ErrorCodes.#ctor"
/><MSHelp:TOCTitle Title="ErrorCodes Constructor " /><MSHelp:RLTitle Title="ErrorCodes Constructor
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ErrorCodes.#ctor" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBErrorCodesClassctorTopic" /><MSHelp:Keyword Index="K"
Term="ErrorCodes class, constructor" /><MSHelp:Keyword Index="K" Term="ErrorCodes.ErrorCodes
constructor" /><MSHelp:Keyword Index="F" Term="ErrorCodes" /><MSHelp:Keyword Index="F"
Term="ErrorCodes.ErrorCodes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.ErrorCodes"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes..ctor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes Constructor </td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_QueueStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_QueueStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.QueueStats" /><MSHelp:TOCTitle Title="QueueStats Members" /><MSHelp:RLTitle Title="QueueStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.QueueStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="QueueStats class" /><MSHelp:Keyword Index="K" Term="QueueStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.QueueStats class" /><MSHelp:Keyword Index="F" Term="QueueStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats" /><MSHelp:Attr

Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats
Members</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_QueueStats.htm">QueueStats Class <a href="#methodTableToggle"
onclick="OpenSection(methodTableToggle)">Methods <a href="#propertyTableToggle"
onclick="OpenSection(propertyTableToggle)">Properties <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method
(Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey_2" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey_2"
/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey(System.Int32)" /><MSHelp:TOCTitle
Title="MoveNextUniqueMultipleKey Method (Int32)" /><MSHelp:RLTitle
Title="Cursor.MoveNextUniqueMultipleKey Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey(System.Int32)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultipleKey is identical to .
Otherwise, move the cursor to the next non-duplicate key in the
database, and store that key and associated datum a ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span
class="languageSpecificText">..<span
class="cpp">::.MoveNextUniqueMultipleKey Method
(Int32)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>PartialLen Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEntry_PartialLen" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEntry_PartialLen"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEntry.PartialLen" /><MSHelp:TOCTitle
Title="PartialLen Property " /><MSHelp:RLTitle Title="DatabaseEntry.PartialLen Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEntry.PartialLen" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassPartialLenTopic" /><MSHelp:Keyword Index="K"

Term="PartialLen property" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.PartialLen property" /><MSHelp:Keyword Index="F" Term="PartialLen" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.PartialLen" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry.PartialLen" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.PartialLen" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.get_PartialLen" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.set_PartialLen" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The byte length of the partial record being read or written by the application" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry..::.PartialLen Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_DatabaseEntry.htm">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method (CompactConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Compact_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Compact_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Compact(BerkeleyDB.CompactConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Compact Method (CompactConfig, Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.Compact Method (CompactConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Compact(BerkeleyDB.CompactConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Compact the database, and optionally return unused database pages to the underlying filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Compact Method (CompactConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Stats" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="QueueDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Stats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (UInt32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey_1"
/><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey_1" /><xml><MSHelp:Attr
Name="AssetID"
Value="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32,BerkeleyDB.LockingInfo)"
/><MSHelp:TOCTitle Title="MoveMultipleKey Method (UInt32, LockingInfo)" /><MSHelp:RLTitle
Title="BTreeCursor.MoveMultipleKey Method (UInt32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32,BerkeleyDB.LockingInfo)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific
key/data pair in the database, and store the key/data pair and as many ensuing key/data pairs that can fit in a buffer
the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultipleKey Method (UInt32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorCodes Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ErrorCodes" /><meta name="guid" content="T_BerkeleyDB_ErrorCodes" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ErrorCodes" /><MSHelp:TOCTitle Title="ErrorCodes Class" /><MSHelp:RLTitle Title="ErrorCodes Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ErrorCodes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassTopic" /><MSHelp:Keyword Index="K" Term="ErrorCodes class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ErrorCodes class" /><MSHelp:Keyword Index="K" Term="ErrorCodes class, about ErrorCodes class" /><MSHelp:Keyword Index="F" Term="ErrorCodes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Constants representing error codes returned by the Berkeley DB library." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_Cursor" /><meta name="guid" content="T_BerkeleyDB_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Cursor" /><MSHelp:TOCTitle Title="Cursor Class" /><MSHelp:RLTitle Title="Cursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassTopic" /><MSHelp:Keyword Index="K" Term="Cursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Cursor class" /><MSHelp:Keyword Index="K" Term="Cursor class, about Cursor class" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing database cursors, which allow for traversal of database records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"

CONTENT="history" /><title>DB_REP_NOTPERM Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_NOTPERM" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_NOTPERM" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_NOTPERM" /><MSHelp:TOCTitle Title="DB_REP_NOTPERM Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_NOTPERM Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_NOTPERM" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_NOTPERMTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_NOTPERM field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_NOTPERM field" /><MSHelp:Keyword Index="F" Term="DB_REP_NOTPERM" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_NOTPERM" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_NOTPERM" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_NOTPERM" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Permanent log record not written." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_NOTPERM Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbName Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_DbName" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_DbName" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.DbName" /><MSHelp:TOCTitle Title="DbName Property " /><MSHelp:RLTitle Title="LogVerifyConfig.DbName Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.DbName" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassDbNameTopic" /><MSHelp:Keyword Index="K" Term="DbName property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.DbName property" /><MSHelp:Keyword Index="F" Term="DbName" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.DbName" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.DbName" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.DbName" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_DbName" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_DbName" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database name whose logs are to be verified." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.DbName Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxBufferWrites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="P_BerkeleyDB_MPoolStats_MaxBufferWrites" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxBufferWrites" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxBufferWrites" /><MSHelp:TOCTitle Title="MaxBufferWrites Property " /><MSHelp:RLTitle Title="MPoolStats.MaxBufferWrites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxBufferWrites" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxBufferWritesTopic" /><MSHelp:Keyword Index="K" Term="MaxBufferWrites property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxBufferWrites property" /><MSHelp:Keyword Index="F" Term="MaxBufferWrites" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxBufferWrites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxBufferWrites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxBufferWrites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxBufferWrites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum buffers to write." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxBufferWrites Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignConflictException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ForeignConflictException__ctor" /><meta name="guid" content="M_BerkeleyDB_ForeignConflictException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ForeignConflictException.#ctor" /><MSHelp:TOCTitle Title="ForeignConflictException Constructor
" /><MSHelp:RLTitle Title="ForeignConflictException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ForeignConflictException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBForeignConflictExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="ForeignConflictException class, constructor" /><MSHelp:Keyword Index="K" Term="ForeignConflictException.ForeignConflictException constructor" /><MSHelp:Keyword Index="F" Term="ForeignConflictException" /><MSHelp:Keyword Index="F" Term="ForeignConflictException.ForeignConflictException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignConflictException.ForeignConflictException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignConflictException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the ForeignConflictException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0;

width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignConflictException Constructor </td></tr><tr id="headerTableRow3"><td align="left">ForeignConflictException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BlockedOperations Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_BlockedOperations" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_BlockedOperations" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.BlockedOperations" /><MSHelp:TOCTitle Title="BlockedOperations Property " /><MSHelp:RLTitle Title="MPoolStats.BlockedOperations Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.BlockedOperations"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassBlockedOperationsTopic" /><MSHelp:Keyword Index="K" Term="BlockedOperations property" /><MSHelp:Keyword Index="K" Term="MPoolStats.BlockedOperations property" /><MSHelp:Keyword Index="F" Term="BlockedOperations" /><MSHelp:Keyword Index="F" Term="MPoolStats.BlockedOperations" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.BlockedOperations" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.BlockedOperations" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_BlockedOperations" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Thread waited on buffer I/O." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.BlockedOperations Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_MPoolStats.htm">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dir Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LogConfig_Dir" /><meta name="guid" content="F_BerkeleyDB_LogConfig_Dir" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LogConfig.Dir" /><MSHelp:TOCTitle Title="Dir Field" /><MSHelp:RLTitle Title="LogConfig.Dir Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LogConfig.Dir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassDirTopic" /><MSHelp:Keyword Index="K" Term="Dir field" /><MSHelp:Keyword Index="K" Term="LogConfig.Dir field" /><MSHelp:Keyword Index="F" Term="Dir" /><MSHelp:Keyword Index="F" Term="LogConfig.Dir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.Dir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.Dir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of a directory to be used as the location of logging files. Log files created by the Log Manager subsystem will be created in this directory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.Dir Field</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EId Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_EId" /><meta name="guid" content="P_BerkeleyDB_DbSite_EId" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSite.EId" /><MSHelp:TOCTitle Title="EId Property " /><MSHelp:RLTitle Title="DbSite.EId Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSite.EId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassEIdTopic" /><MSHelp:Keyword Index="K" Term="EId property" /><MSHelp:Keyword Index="K" Term="DbSite.EId property" /><MSHelp:Keyword Index="F" Term="EId" /><MSHelp:Keyword Index="F" Term="DbSite.EId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.EId" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.EId" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.get_EId" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The eid of the site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.EId Property </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLoggingSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintLoggingSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintLoggingSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintLoggingSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLoggingSystemStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats(System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the logging subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLoggingSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EventNotify Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_EventNotify" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_EventNotify" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.EventNotify" /><MSHelp:TOCTitle Title="EventNotify Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.EventNotify Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.EventNotify" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassEventNotifyTopic" /><MSHelp:Keyword Index="K" Term="EventNotify property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.EventNotify property" /><MSHelp:Keyword Index="F" Term="EventNotify" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.EventNotify" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.EventNotify" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.EventNotify" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_EventNotify" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_EventNotify" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A delegate which is called to notify the process of specific Berkeley DB events." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.EventNotify Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReadUncommitted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_ReadUncommitted" /><meta

name="guid" content="P_BerkeleyDB_BaseDatabase_ReadUncommitted" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.ReadUncommitted" /><MSHelp:TOCTitle Title="ReadUncommitted Property " /><MSHelp:RLTitle Title="BaseDatabase.ReadUncommitted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.ReadUncommitted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassReadUncommittedTopic" /><MSHelp:Keyword Index="K" Term="ReadUncommitted property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.ReadUncommitted property" /><MSHelp:Keyword Index="F" Term="ReadUncommitted" /><MSHelp:Keyword Index="F" Term="BaseDatabase.ReadUncommitted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.ReadUncommitted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.ReadUncommitted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_ReadUncommitted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, this database supports transactional read operations with degree 1 isolation. Read operations on the database may request the return of modified but not yet committed data." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.ReadUncommitted Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transaction Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_Transaction" /><meta name="guid" content="AllMembers_T_BerkeleyDB_Transaction" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.Transaction" /><MSHelp:TOCTitle Title="Transaction Members" /><MSHelp:RLTitle Title="Transaction Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.Transaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionMembersTopic" /><MSHelp:Keyword Index="K" Term="Transaction class" /><MSHelp:Keyword Index="K" Term="Transaction class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Transaction class" /><MSHelp:Keyword Index="F" Term="Transaction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction Members</td></tr><tr id="headerTableRow3"><td align="left">Transaction Class Methods
Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:TOCTitle Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store the secondary key and primary key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Status Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_Status" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_Status" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.Status" /><MSHelp:TOCTitle Title="Status Property " /><MSHelp:RLTitle Title="ReplicationStats.Status Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.Status" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassStatusTopic" /><MSHelp:Keyword Index="K" Term="Status property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.Status property" /><MSHelp:Keyword Index="F" Term="Status" /><MSHelp:Keyword Index="F" Term="ReplicationStats.Status" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.Status" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.Status" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_Status" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current replication status." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">ReplicationStats..::.Status Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbThreadID Class</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DbThreadID" /><meta name="guid" content="T_BerkeleyDB_DbThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DbThreadID" /><MSHelp:TOCTitle Title="DbThreadID Class" /><MSHelp:RLTitle Title="DbThreadID Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="T:BerkeleyDB.DbThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbThreadIDClassTopic" /><MSHelp:Keyword Index="K" Term="DbThreadID class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbThreadID class" /><MSHelp:Keyword Index="K" Term="DbThreadID class, about DbThreadID class" /><MSHelp:Keyword Index="F" Term="DbThreadID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbThreadID" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbThreadID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a unique identifier for a thread of control in a Berkeley DB application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID Class</td></tr><tr id="headerTableRow3"><td align="left">Members <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepHeartbeatSend Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepHeartbeatSend" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepHeartbeatSend" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepHeartbeatSend" /><MSHelp:TOCTitle Title="RepHeartbeatSend Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepHeartbeatSend Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepHeartbeatSend" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepHeartbeatSendTopic" /><MSHelp:Keyword Index="K" Term="RepHeartbeatSend property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepHeartbeatSend property" /><MSHelp:Keyword Index="F" Term="RepHeartbeatSend" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepHeartbeatSend" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepHeartbeatSend" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepHeartbeatSend" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepHeartbeatSend" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepHeartbeatSend" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The frequency at which the replication manager, running at a master site, broadcasts a heartbeat message in an otherwise idle system. When 0 (the default), no heartbeat messages will be sent." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepHeartbeatSend Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintMPoolSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintMPoolSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintMPoolSystemStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats(System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the memory pool (that is, buffer cache) subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintMPoolSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="HeapDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span

id="memberOptionsDropdown" class="filter" tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepSetTransport Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepSetTransport" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepSetTransport" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepSetTransport(System.Int32,BerkeleyDB.ReplicationTransportDelegate)" /><MSHelp:TOCTitle Title="RepSetTransport Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepSetTransport Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepSetTransport(System.Int32,BerkeleyDB.ReplicationTransportDelegate)"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepSetTransportTopic" /><MSHelp:Keyword Index="K" Term="RepSetTransport method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepSetTransport method" /><MSHelp:Keyword Index="F" Term="RepSetTransport" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepSetTransport" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepSetTransport" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepSetTransport" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize the communication infrastructure for a database environment participating in a replicated application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepSetTransport Method </td></tr><tr id="headerTableRow3"><td

align="left">DatabaseEnvironment Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ToString Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseType_ToString" /><meta name="guid" content="M_BerkeleyDB_DatabaseType_ToString" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseType.ToString" /><MSHelp:TOCTitle Title="ToString Method " /><MSHelp:RLTitle Title="DatabaseType.ToString Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseType.ToString" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassToStringTopic" /><MSHelp:Keyword Index="K" Term="ToString method" /><MSHelp:Keyword Index="K" Term="DatabaseType.ToString method" /><MSHelp:Keyword Index="F" Term="ToString" /><MSHelp:Keyword Index="F" Term="DatabaseType.ToString" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.ToString" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.ToString" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Convert this instance of DatabaseType to its string representation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseType.<span
class="vb">.::.ToString Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseType.htm">DatabaseType Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>WriteCursor
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CursorConfig_WriteCursor" /><meta
name="guid" content="F_BerkeleyDB_CursorConfig_WriteCursor" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.CursorConfig.WriteCursor" /><MSHelp:TOCTitle Title="WriteCursor Field"
/><MSHelp:RLTitle Title="CursorConfig.WriteCursor Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.CursorConfig.WriteCursor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCursorConfigClassWriteCursorTopic" /><MSHelp:Keyword Index="K"
Term="WriteCursor field" /><MSHelp:Keyword Index="K" Term="CursorConfig.WriteCursor field"
/><MSHelp:Keyword Index="F" Term="WriteCursor" /><MSHelp:Keyword Index="F"
Term="CursorConfig.WriteCursor" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.CursorConfig.WriteCursor" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CursorConfig.WriteCursor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, specify that the cursor will be used to update the database. The underlying database environment must have been opened with set." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig..::.WriteCursor Field</td></tr><tr id="headerTableRow3"><td align="left">CursorConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MMapSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolConfig_MMapSize" /><meta name="guid" content="P_BerkeleyDB_MPoolConfig_MMapSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolConfig.MMapSize" /><MSHelp:TOCTitle Title="MMapSize Property " /><MSHelp:RLTitle Title="MPoolConfig.MMapSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolConfig.MMapSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassMMapSizeTopic" /><MSHelp:Keyword Index="K" Term="MMapSize property" /><MSHelp:Keyword Index="K" Term="MPoolConfig.MMapSize property" /><MSHelp:Keyword Index="F" Term="MMapSize" /><MSHelp:Keyword Index="F" Term="MPoolConfig.MMapSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.MMapSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.MMapSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.get_MMapSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.set_MMapSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum file size, in bytes, for a file to be mapped into the process address space. If no value is specified, it defaults to 10MB." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.MMapSize Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoMMap Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_NoMMap" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_NoMMap" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.NoMMap" /><MSHelp:TOCTitle Title="NoMMap Property " /><MSHelp:RLTitle Title="BaseDatabase.NoMMap Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.NoMMap" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassNoMMapTopic" /><MSHelp:Keyword Index="K" Term="NoMMap property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.NoMMap property" /><MSHelp:Keyword Index="F" Term="NoMMap" /><MSHelp:Keyword Index="F" Term="BaseDatabase.NoMMap" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.NoMMap" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.NoMMap" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_NoMMap" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, this database is not mapped into process memory. See for further information." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.NoMMap Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_RegionSize" /><meta name="guid" content="P_BerkeleyDB_HeapStats_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="HeapStats.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="HeapStats.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="HeapStats.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The region size of the Heap database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingInfo Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_LockingInfo__ctor" /><meta name="guid" content="M_BerkeleyDB_LockingInfo__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.LockingInfo.#ctor" /><MSHelp:TOCTitle Title="LockingInfo Constructor " /><MSHelp:RLTitle Title="LockingInfo Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LockingInfo.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingInfoClassctorTopic" /><MSHelp:Keyword Index="K" Term="LockingInfo class, constructor" /><MSHelp:Keyword Index="K" Term="LockingInfo.LockingInfo constructor" /><MSHelp:Keyword Index="F" Term="LockingInfo" /><MSHelp:Keyword Index="F" Term="LockingInfo.LockingInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingInfo.LockingInfo" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingInfo..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new LockingInfo object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingInfo Constructor </td></tr><tr id="headerTableRow3"><td align="left">LockingInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_Duplicates" /><meta name="guid" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryHashDatabaseConfig.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Field"

/><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.Duplicates Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryHashDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates field" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.Duplicates field" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Policy for duplicate data items in the database; that is, insertion when the key of the key/data pair being inserted already exists in the database will be successful." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">SecondaryHashDatabaseConfig..::.Duplicates Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionConfig.LogFlush Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_TransactionConfig_LogFlush" /><meta name="guid" content="T_BerkeleyDB_TransactionConfig_LogFlush" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.TransactionConfig.LogFlush" /><MSHelp:TOCTitle Title="TransactionConfig.LogFlush Enumeration" /><MSHelp:RLTitle Title="TransactionConfig.LogFlush Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.TransactionConfig.LogFlush" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.LogFlush.DEFAULT" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.LogFlush.NOSYNC" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.LogFlush.WRITE_NOSYNC" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.LogFlush.SYNC" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigLogFlushClassTopic" /><MSHelp:Keyword Index="K" Term="TransactionConfig.LogFlush enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.TransactionConfig.LogFlush enumeration" /><MSHelp:Keyword Index="K" Term="DEFAULT enumeration member" /><MSHelp:Keyword Index="K" Term="NOSYNC enumeration member" /><MSHelp:Keyword Index="K" Term="WRITE_NOSYNC enumeration member" /><MSHelp:Keyword Index="K" Term="SYNC enumeration member" /><MSHelp:Keyword Index="F" Term="TransactionConfig.LogFlush" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.LogFlush" /><MSHelp:Keyword Index="F" Term="TransactionConfig.LogFlush.DEFAULT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.LogFlush.DEFAULT" /><MSHelp:Keyword Index="F" Term="TransactionConfig.LogFlush.NOSYNC" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.LogFlush.NOSYNC" /><MSHelp:Keyword Index="F" Term="TransactionConfig.LogFlush.WRITE_NOSYNC" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.LogFlush.WRITE_NOSYNC" /><MSHelp:Keyword Index="F" Term="TransactionConfig.LogFlush.SYNC" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.LogFlush.SYNC" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogFlush" /><MSHelp:Attr

Name="APIName" Value="BerkeleyDB.TransactionConfig.LogFlush.DEFAULT" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.LogFlush.NOSYNC" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.LogFlush.WRITE_NOSYNC" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.LogFlush.SYNC" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies the log flushing behavior on transaction commit" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.LogFlush Enumeration</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MessageDispatchDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MessageDispatchDelegate" /><meta name="guid" content="T_BerkeleyDB_MessageDispatchDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MessageDispatchDelegate" /><MSHelp:TOCTitle Title="MessageDispatchDelegate Delegate" /><MSHelp:RLTitle Title="MessageDispatchDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MessageDispatchDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMessageDispatchDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="MessageDispatchDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MessageDispatchDelegate delegate" /><MSHelp:Keyword Index="F" Term="MessageDispatchDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MessageDispatchDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MessageDispatchDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MessageDispatchDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MessageDispatchDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MessageDispatchDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MessageDispatchDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Application-specific function used to handle messages
sent over Replication Manager message channels." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span

onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">MessageDispatchDelegate Delegate</td></tr><tr id="headerTableRow3"><td
align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>NumTestAndSetSpins Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_NumTestAndSetSpins" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_NumTestAndSetSpins" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.NumTestAndSetSpins" /><MSHelp:TOCTitle
Title="NumTestAndSetSpins Property
" /><MSHelp:RLTitle Title="DatabaseEnvironment.NumTestAndSetSpins Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.NumTestAndSetSpins"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassNumTestAndSetSpinsTopic"
/><MSHelp:Keyword Index="K" Term="NumTestAndSetSpins property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.NumTestAndSetSpins property" /><MSHelp:Keyword Index="F"

Term="NumTestAndSetSpins" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.NumTestAndSetSpins" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.NumTestAndSetSpins" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.NumTestAndSetSpins" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_NumTestAndSetSpins" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_NumTestAndSetSpins"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The number of times that test-and-set mutexes should spin without
blocking. The value defaults to 1 on uniprocessor systems and to 50 times the number of processors on
multiprocessor systems." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span

class="vb">.::.NumTestAndSetSpins Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HeapStats" /><meta name="guid" content="Properties_T_BerkeleyDB_HeapStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HeapStats" /><MSHelp:TOCTitle Title="HeapStats Properties " /><MSHelp:RLTitle Title="HeapStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HeapStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="HeapStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats Properties </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_TransactionStats" /><meta name="guid" content="Properties_T_BerkeleyDB_TransactionStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.TransactionStats" /><MSHelp:TOCTitle Title="TransactionStats Properties " /><MSHelp:RLTitle Title="TransactionStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="Properties.T:BerkeleyDB.TransactionStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="TransactionStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats Properties </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePages Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_DuplicatePages" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_DuplicatePages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.DuplicatePages" /><MSHelp:TOCTitle Title="DuplicatePages Property " /><MSHelp:RLTitle Title="RecnoStats.DuplicatePages
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.DuplicatePages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassDuplicatePagesTopic" /><MSHelp:Keyword Index="K" Term="DuplicatePages property" /><MSHelp:Keyword Index="K" Term="RecnoStats.DuplicatePages property" /><MSHelp:Keyword Index="F" Term="DuplicatePages" /><MSHelp:Keyword Index="F" Term="RecnoStats.DuplicatePages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.DuplicatePages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.DuplicatePages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_DuplicatePages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Duplicate pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.DuplicatePages Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="QueueDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats"

/><MSHelp:Keyword Index="F" Term="QueueDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"

type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey_7" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultipleKey_7" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database, and store that key/data pair and as many ensuing key/data pairs that can fit in a buffer the size of in . The cursor is positioned t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DatabaseException" /><meta name="guid" content="Properties_T_BerkeleyDB_DatabaseException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DatabaseException" /><MSHelp:TOCTitle Title="DatabaseException Properties " /><MSHelp:RLTitle Title="DatabaseException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DatabaseException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DatabaseException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"

type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException Properties </td></tr><tr id="headerTableRow3"><td align="left">DatabaseException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxObjectSteals Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxObjectSteals" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxObjectSteals" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxObjectSteals" /><MSHelp:TOCTitle Title="MaxObjectSteals Property " /><MSHelp:RLTitle Title="LockStats.MaxObjectSteals Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxObjectSteals" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxObjectStealsTopic" /><MSHelp:Keyword Index="K" Term="MaxObjectSteals property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxObjectSteals property" /><MSHelp:Keyword Index="F" Term="MaxObjectSteals" /><MSHelp:Keyword Index="F" Term="LockStats.MaxObjectSteals" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxObjectSteals" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxObjectSteals" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxObjectSteals" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of steals in any partition." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxObjectSteals Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSite Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DbSite" /><meta name="guid" content="T_BerkeleyDB_DbSite" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DbSite" /><MSHelp:TOCTitle

Title="DbSite Class" /><MSHelp:RLTitle Title="DbSite Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DbSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassTopic" /><MSHelp:Keyword Index="K" Term="DbSite class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbSite class" /><MSHelp:Keyword Index="K" Term="DbSite class, about DbSite class" /><MSHelp:Keyword Index="F" Term="DbSite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a site in Berkeley DB HA replication manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite Class</td></tr><tr id="headerTableRow3"><td align="left">Members <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method (DatabaseEntry,
DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)"
/><MSHelp:TOCTitle Title="MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique
is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store the secondary key and primary key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_LockWait" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_LockWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.LockWait" /><MSHelp:TOCTitle Title="LockWait Property " /><MSHelp:RLTitle Title="SequenceStats.LockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.LockWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassLockWaitTopic" /><MSHelp:Keyword Index="K" Term="LockWait property" /><MSHelp:Keyword Index="K" Term="SequenceStats.LockWait property" /><MSHelp:Keyword Index="F" Term="LockWait" /><MSHelp:Keyword Index="F" Term="SequenceStats.LockWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.LockWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.LockWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_LockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Sequence lock granted w/o wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats..::.LockWait Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitFileId Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_InitFileId" /><meta name="guid" content="P_BerkeleyDB_LogStats_InitFileId" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.InitFileId" /><MSHelp:TOCTitle Title="InitFileId Property " /><MSHelp:RLTitle Title="LogStats.InitFileId Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.InitFileId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassInitFileIdTopic" /><MSHelp:Keyword Index="K" Term="InitFileId property" /><MSHelp:Keyword Index="K" Term="LogStats.InitFileId property" /><MSHelp:Keyword Index="F" Term="InitFileId" /><MSHelp:Keyword Index="F" Term="LogStats.InitFileId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.InitFileId" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.InitFileId" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_InitFileId" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initial fileid allocation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.InitFileId Property </td></tr><tr id="headerTableRow3"><td
align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyEmptyException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_KeyEmptyException" /><meta name="guid" content="Fields_T_BerkeleyDB_KeyEmptyException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.KeyEmptyException" /><MSHelp:TOCTitle Title="KeyEmptyException Fields" /><MSHelp:RLTitle Title="KeyEmptyException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.KeyEmptyException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyEmptyExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0;

width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyEmptyException Fields</td></tr><tr id="headerTableRow3"><td align="left">KeyEmptyException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DataDirs Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_DataDirs" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_DataDirs" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.DataDirs" /><MSHelp:TOCTitle Title="DataDirs Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.DataDirs Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.DataDirs" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassDataDirsTopic" /><MSHelp:Keyword Index="K" Term="DataDirs property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.DataDirs property" /><MSHelp:Keyword Index="F" Term="DataDirs" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.DataDirs" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.DataDirs" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.DataDirs" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_DataDirs" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The array of directories where database files are stored." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.DataDirs Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext
Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_MoveNext_1" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveNext_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)"
/><MSHelp:TOCTitle Title="MoveNext Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle
Title="Cursor.MoveNext Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNext"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise,
move the cursor to the next key/data pair of the database, and store that pair in . In the presence of duplicate key val
..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNext Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID"

Value="Overload:BerkeleyDB.SecondaryHashDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DatabaseEntry" /><meta name="guid" content="Methods_T_BerkeleyDB_DatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DatabaseEntry" /><MSHelp:TOCTitle Title="DatabaseEntry Methods " /><MSHelp:RLTitle Title="DatabaseEntry Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryMethodsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Methods </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="T_BerkeleyDB_TransactionStats" /><meta name="guid"
content="T_BerkeleyDB_TransactionStats" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.TransactionStats" /><MSHelp:TOCTitle Title="TransactionStats Class"
/><MSHelp:RLTitle Title="TransactionStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="T:BerkeleyDB.TransactionStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionStatsClassTopic" /><MSHelp:Keyword Index="K" Term="TransactionStats
class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.TransactionStats class" /><MSHelp:Keyword
Index="K" Term="TransactionStats class, about TransactionStats class" /><MSHelp:Keyword Index="F"
Term="TransactionStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats" /><MSHelp:Attr
Name="HelpPriority"
Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Statistical information about the transaction subsystem"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLockers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxLockers" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxLockers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxLockers" /><MSHelp:TOCTitle Title="MaxLockers Property " /><MSHelp:RLTitle Title="LockStats.MaxLockers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxLockers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxLockersTopic" /><MSHelp:Keyword Index="K" Term="MaxLockers property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxLockers property" /><MSHelp:Keyword Index="F" Term="MaxLockers" /><MSHelp:Keyword Index="F" Term="LockStats.MaxLockers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxLockers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxLockers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxLockers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of lockers so far." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxLockers Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepTransport Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepTransport" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepTransport" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepTransport" /><MSHelp:TOCTitle Title="RepTransport Property "

/><MSHelp:RLTitle Title="DatabaseEnvironment.RepTransport Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepTransport" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepTransportTopic" /><MSHelp:Keyword Index="K" Term="RepTransport
property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepTransport property" /><MSHelp:Keyword Index="F" Term="RepTransport" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepTransport" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepTransport" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepTransport" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepTransport" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The delegate used to transmit data using the replication application's communication infrastructure." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepTransport Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EXPIRE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_EXPIRE" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_EXPIRE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.EXPIRE" /><MSHelp:TOCTitle Title="EXPIRE Field" /><MSHelp:RLTitle Title="DeadlockPolicy.EXPIRE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DeadlockPolicy.EXPIRE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassEXPIRETopic" /><MSHelp:Keyword Index="K" Term="EXPIRE field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.EXPIRE field" /><MSHelp:Keyword Index="F" Term="EXPIRE" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.EXPIRE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.EXPIRE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.EXPIRE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject lock requests which have timed out. No other deadlock detection is performed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span

onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DeadlockPolicy<span
class="cs">..::<span
class="nu">.EXPIRE Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DeadlockPolicy.htm">DeadlockPolicy Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>VersionMismatchException Fields</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Fields_T_BerkeleyDB_VersionMismatchException" /><meta name="guid"
content="Fields_T_BerkeleyDB_VersionMismatchException" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.VersionMismatchException" /><MSHelp:TOCTitle
Title="VersionMismatchException Fields" /><MSHelp:RLTitle Title="VersionMismatchException Fields
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.VersionMismatchException"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVersionMismatchExceptionFieldsTopic"
/><MSHelp:Keyword Index="K" Term="VersionMismatchException class, fields" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"

cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VersionMismatchException Fields</td></tr><tr id="headerTableRow3"><td align="left">VersionMismatchException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactData Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_CompactData" /><meta name="guid" content="T_BerkeleyDB_CompactData" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.CompactData" /><MSHelp:TOCTitle Title="CompactData Class" /><MSHelp:RLTitle Title="CompactData Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.CompactData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassTopic" /><MSHelp:Keyword Index="K" Term="CompactData class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CompactData class" /><MSHelp:Keyword Index="K" Term="CompactData class, about CompactData class" /><MSHelp:Keyword Index="F" Term="CompactData" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class for representing compact operation statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EndTime Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_EndTime" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_EndTime" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.EndTime" /><MSHelp:TOCTitle Title="EndTime Property " /><MSHelp:RLTitle Title="LogVerifyConfig.EndTime Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.EndTime" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassEndTimeTopic" /><MSHelp:Keyword Index="K" Term="EndTime property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.EndTime property" /><MSHelp:Keyword Index="F" Term="EndTime" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.EndTime" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.EndTime" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.EndTime" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.LogVerifyConfig.get_EndTime" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_EndTime" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The ending time to verify." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.EndTime Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Get_3" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Get_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Get Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="BaseDatabase.Get Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database. In the presence of duplicate key values, Get will return the first data item for . If the data is a partial , bytes starting bytes ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolFileStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MPoolFileStats" /><meta name="guid" content="Properties_T_BerkeleyDB_MPoolFileStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MPoolFileStats" /><MSHelp:TOCTitle Title="MPoolFileStats Properties " /><MSHelp:RLTitle Title="MPoolFileStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MPoolFileStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MPoolFileStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats Properties </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapStats Members</title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HeapStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HeapStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HeapStats" /><MSHelp:TOCTitle Title="HeapStats Members" /><MSHelp:RLTitle Title="HeapStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HeapStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="HeapStats class" /><MSHelp:Keyword Index="K" Term="HeapStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapStats class" /><MSHelp:Keyword Index="F" Term="HeapStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats Members</td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="HeapDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr

Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">HeapDatabase..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RepMgrSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_RepMgrSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:TOCTitle Title="RepMgrSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="RepMgrSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrSystemStats method" /><MSHelp:Keyword Index="F" Term="RepMgrSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_Move_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_Move_2"
/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:TOCTitle
Title="Move Method (DatabaseEntry, Boolean)" /><MSHelp:RLTitle Title="Cursor.Move Method (DatabaseEntry,
Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Move" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Set the cursor to refer to , and store the datum associated with the given key in . In the presence of duplicate
key values, the first data item in the set of duplicates is stored in ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method (DatabaseEntry, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
 xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetThreadIDDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
 </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SetThreadIDDelegate" /><meta name="guid" content="T_BerkeleyDB_SetThreadIDDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SetThreadIDDelegate" /><MSHelp:TOCTitle Title="SetThreadIDDelegate Delegate" /><MSHelp:RLTitle Title="SetThreadIDDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SetThreadIDDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSetThreadIDDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="SetThreadIDDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SetThreadIDDelegate delegate" /><MSHelp:Keyword Index="F" Term="SetThreadIDDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SetThreadIDDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
 /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadIDDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadIDDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadIDDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadIDDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadIDDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function which returns a unique identifier pair for a thread of control in a Berkeley DB application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
 id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SetThreadIDDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseExpiredException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LeaseExpiredException" /><meta name="guid" content="Properties_T_BerkeleyDB_LeaseExpiredException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:TOCTitle Title="LeaseExpiredException Properties " /><MSHelp:RLTitle Title="LeaseExpiredException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBLeaseExpiredExceptionPropertiesTopic" /><MSHelp:Keyword
Index="K" Term="LeaseExpiredException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"

onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LeaseExpiredException Properties </td></tr><tr id="headerTableRow3"><td align="left">LeaseExpiredException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="QueueDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.GetBoth" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="QueueDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.GetBoth" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ZeroOnCreate Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_LogConfig_ZeroOnCreate" /><meta name="guid"
content="F_BerkeleyDB_LogConfig_ZeroOnCreate" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.LogConfig.ZeroOnCreate" /><MSHelp:TOCTitle Title="ZeroOnCreate Field"
/><MSHelp:RLTitle Title="LogConfig.ZeroOnCreate Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.LogConfig.ZeroOnCreate" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogConfigClassZeroOnCreateTopic" /><MSHelp:Keyword Index="K"
Term="ZeroOnCreate field" /><MSHelp:Keyword Index="K" Term="LogConfig.ZeroOnCreate field"
/><MSHelp:Keyword Index="F" Term="ZeroOnCreate" /><MSHelp:Keyword Index="F"
Term="LogConfig.ZeroOnCreate" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LogConfig.ZeroOnCreate" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.ZeroOnCreate" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, zero all pages of a log file when that log file is created." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.ZeroOnCreate Field</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapFullException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HeapFullException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HeapFullException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HeapFullException" /><MSHelp:TOCTitle Title="HeapFullException Members" /><MSHelp:RLTitle Title="HeapFullException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HeapFullException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapFullExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="HeapFullException class" /><MSHelp:Keyword Index="K" Term="HeapFullException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapFullException class" /><MSHelp:Keyword Index="F" Term="HeapFullException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapFullException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapFullException Members</td></tr><tr id="headerTableRow3"><td align="left">HeapFullException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolConfig

Members</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_MPoolConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_MPoolConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.MPoolConfig" /><MSHelp:TOCTitle Title="MPoolConfig Members" /><MSHelp:RLTitle Title="MPoolConfig
Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.MPoolConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="MPoolConfig class" /><MSHelp:Keyword Index="K" Term="MPoolConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MPoolConfig class" /><MSHelp:Keyword Index="F" Term="MPoolConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig Members</td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_LockTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_LockTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.LockTimeout" /><MSHelp:TOCTitle Title="LockTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.LockTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.LockTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassLockTimeoutTopic" /><MSHelp:Keyword Index="K"

Term="LockTimeout property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.LockTimeout property" /><MSHelp:Keyword Index="F"
Term="LockTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.LockTimeout"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.LockTimeout" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.LockTimeout" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.get_LockTimeout" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.set_LockTimeout" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="A value, in microseconds, representing lock timeouts." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironmentConfig.<span

class="vb">.::.LockTimeout Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Database
Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_Database" /><meta name="guid"
content="T_BerkeleyDB_Database" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Database"
/><MSHelp:TOCTitle Title="Database Class" /><MSHelp:RLTitle Title="Database Class (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.Database" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="Database class"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.Database class" /><MSHelp:Keyword Index="K"
Term="Database class, about Database class" /><MSHelp:Keyword Index="F" Term="Database"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A class representing a Berkeley DB database, a base class for access method specific
classes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TruncateUnusedPages Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_TruncateUnusedPages" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_TruncateUnusedPages" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:TOCTitle Title="TruncateUnusedPages Method " /><MSHelp:RLTitle Title="HashDatabase.TruncateUnusedPages Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassTruncateUnusedPagesTopic" /><MSHelp:Keyword Index="K" Term="TruncateUnusedPages method" /><MSHelp:Keyword Index="K" Term="HashDatabase.TruncateUnusedPages method" /><MSHelp:Keyword Index="F" Term="TruncateUnusedPages" /><MSHelp:Keyword Index="F" Term="HashDatabase.TruncateUnusedPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase<span

class="cs">..::.TruncateUnusedPages Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyExistException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_KeyExistException" /><meta name="guid" content="Properties_T_BerkeleyDB_KeyExistException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.KeyExistException" /><MSHelp:TOCTitle Title="KeyExistException Properties " /><MSHelp:RLTitle Title="KeyExistException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.KeyExistException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyExistExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="KeyExistException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyExistException Properties </td></tr><tr id="headerTableRow3"><td align="left">KeyExistException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ReplicationHostAddress" /><meta name="guid" content="Methods_T_BerkeleyDB_ReplicationHostAddress" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:TOCTitle Title="ReplicationHostAddress Methods " /><MSHelp:RLTitle Title="ReplicationHostAddress Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressMethodsTopic" /><MSHelp:Keyword Index="K"

Term="ReplicationHostAddress class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">ReplicationHostAddress Methods </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ReplicationHostAddress.htm">ReplicationHostAddress Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
 xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method
(DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_RecnoDatabase_Append" /><meta name="guid"
content="M_BerkeleyDB_RecnoDatabase_Append" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.RecnoDatabase.Append(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle
Title="Append Method (DatabaseEntry)" /><MSHelp:RLTitle Title="RecnoDatabase.Append Method
(DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.RecnoDatabase.Append(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RecnoDatabase.Append" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
 Name="Abstract" Value="Append the data item to the end of the database." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
 image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Append Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_KeyRange" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_KeyRange" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.KeyRange" /><MSHelp:TOCTitle Title="KeyRange Method " /><MSHelp:RLTitle Title="BTreeDatabase.KeyRange Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.KeyRange" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassKeyRangeTopic" /><MSHelp:Keyword Index="K" Term="KeyRange method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.KeyRange method" /><MSHelp:Keyword Index="F" Term="KeyRange" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.KeyRange" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.KeyRange" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase<span

class="cs">..::.KeyRange Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SyncAction Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_TransactionConfig_SyncAction" /><meta name="guid" content="F_BerkeleyDB_TransactionConfig_SyncAction" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.TransactionConfig.SyncAction" /><MSHelp:TOCTitle Title="SyncAction Field" /><MSHelp:RLTitle Title="TransactionConfig.SyncAction Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.SyncAction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassSyncActionTopic" /><MSHelp:Keyword Index="K" Term="SyncAction field" /><MSHelp:Keyword Index="K" Term="TransactionConfig.SyncAction field" /><MSHelp:Keyword Index="F" Term="SyncAction" /><MSHelp:Keyword Index="F" Term="TransactionConfig.SyncAction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.SyncAction" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.SyncAction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log sync behavior on transaction commit or prepare." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.SyncAction Field</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HashDatabase" /><meta name="guid" content="T_BerkeleyDB_HashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HashDatabase" /><MSHelp:TOCTitle Title="HashDatabase Class" /><MSHelp:RLTitle Title="HashDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="HashDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashDatabase class" /><MSHelp:Keyword Index="K" Term="HashDatabase class, about HashDatabase class" /><MSHelp:Keyword Index="F" Term="HashDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a HashDatabase. The Hash format is an extensible, dynamic hashing scheme." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method

(DatabaseEntry, DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Put_1" /><meta name="guid" content="M_BerkeleyDB_Database_Put_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Put(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Put Method (DatabaseEntry, DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="Database.Put Method (DatabaseEntry, DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Put(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair in the database, replacing any previously existing key if duplicates are disallowed, or adding a duplicate data item if duplicates are allowed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">..<span
class="cpp">::.Put Method (DatabaseEntry, DatabaseEntry,
Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFlush
Method (LSN)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_LogFlush_1" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_LogFlush_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.LogFlush(BerkeleyDB.LSN)" /><MSHelp:TOCTitle
Title="LogFlush Method (LSN)" /><MSHelp:RLTitle Title="DatabaseEnvironment.LogFlush Method (LSN)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.LogFlush(BerkeleyDB.LSN)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Write log records to disk."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogFlush Method (LSN)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ALL Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_AckPolicy_ALL" /><meta name="guid" content="F_BerkeleyDB_AckPolicy_ALL" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.AckPolicy.ALL" /><MSHelp:TOCTitle Title="ALL Field" /><MSHelp:RLTitle

Title="AckPolicy.ALL Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.AckPolicy.ALL" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBAckPolicyClassALLTopic" /><MSHelp:Keyword Index="K" Term="ALL field"
/><MSHelp:Keyword Index="K" Term="AckPolicy.ALL field" /><MSHelp:Keyword Index="F" Term="ALL"
/><MSHelp:Keyword Index="F" Term="AckPolicy.ALL" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.AckPolicy.ALL" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.AckPolicy.ALL" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The master should
wait until all replication clients have acknowledged each permanent replication message." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">AckPolicy.<span
class="vb">.::.ALL

Field</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MutexConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_MutexConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MutexConfig" /><MSHelp:TOCTitle Title="MutexConfig Properties " /><MSHelp:RLTitle Title="MutexConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MutexConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MutexConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SequenceStats" /><meta name="guid" content="T_BerkeleyDB_SequenceStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SequenceStats" /><MSHelp:TOCTitle Title="SequenceStats Class" /><MSHelp:RLTitle Title="SequenceStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SequenceStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassTopic" /><MSHelp:Keyword Index="K" Term="SequenceStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SequenceStats class"

/><MSHelp:Keyword Index="K" Term="SequenceStats class, about SequenceStats class" /><MSHelp:Keyword Index="F" Term="SequenceStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about a Sequence" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStartMaster Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepStartMaster" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepStartMaster" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:TOCTitle Title="RepStartMaster Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStartMaster Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure the database environment as a master in a group of replicated database environments." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepStartMaster Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BaseDatabase" /><meta name="guid" content="T_BerkeleyDB_BaseDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BaseDatabase" /><MSHelp:TOCTitle Title="BaseDatabase Class" /><MSHelp:RLTitle Title="BaseDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BaseDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="BaseDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BaseDatabase class" /><MSHelp:Keyword Index="K" Term="BaseDatabase class, about BaseDatabase class" /><MSHelp:Keyword Index="F" Term="BaseDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The base class from which all database classes inherit" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseException Constructor </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseException__ctor" /><meta name="guid"

content="M_BerkeleyDB_DatabaseException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseException.#ctor(System.Int32)" /><MSHelp:TOCTitle Title="DatabaseException Constructor " /><MSHelp:RLTitle Title="DatabaseException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseException.#ctor(System.Int32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="DatabaseException class, constructor" /><MSHelp:Keyword Index="K" Term="DatabaseException.DatabaseException constructor" /><MSHelp:Keyword Index="F" Term="DatabaseException" /><MSHelp:Keyword Index="F" Term="DatabaseException.DatabaseException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseException.DatabaseException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new DatabaseException, encapsulating a specific error code." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException Constructor </td></tr><tr id="headerTableRow3"><td align="left">DatabaseException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoBuffer Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LogConfig_NoBuffer" /><meta name="guid" content="F_BerkeleyDB_LogConfig_NoBuffer" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LogConfig.NoBuffer" /><MSHelp:TOCTitle Title="NoBuffer Field" /><MSHelp:RLTitle Title="LogConfig.NoBuffer Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LogConfig.NoBuffer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassNoBufferTopic" /><MSHelp:Keyword Index="K" Term="NoBuffer field" /><MSHelp:Keyword Index="K" Term="LogConfig.NoBuffer field" /><MSHelp:Keyword Index="F" Term="NoBuffer" /><MSHelp:Keyword Index="F" Term="LogConfig.NoBuffer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.NoBuffer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.NoBuffer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, turn off system buffering of Berkeley DB log files to avoid double caching." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.NoBuffer Field</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Stats" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="BTreeDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassStatsTopic" /><MSHelp:Keyword Index="K" Term="Stats method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Stats method" /><MSHelp:Keyword Index="F" Term="Stats" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Stats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label

class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitMutexes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_InitMutexes"
/><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitMutexes" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitMutexes" /><MSHelp:TOCTitle
Title="InitMutexes Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitMutexes Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitMutexes"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitMutexesTopic"
/><MSHelp:Keyword Index="K" Term="InitMutexes property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.InitMutexes property" /><MSHelp:Keyword Index="F" Term="InitMutexes"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitMutexes" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.InitMutexes" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.InitMutexes"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitMutexes"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitMutexes" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The initial number of mutexes allocated" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitMutexes Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SnapshotReads Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_SnapshotReads" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_SnapshotReads" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.SnapshotReads" /><MSHelp:TOCTitle Title="SnapshotReads Property " /><MSHelp:RLTitle Title="ActiveTransaction.SnapshotReads Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.SnapshotReads" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassSnapshotReadsTopic" /><MSHelp:Keyword Index="K" Term="SnapshotReads property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.SnapshotReads property" /><MSHelp:Keyword Index="F" Term="SnapshotReads" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.SnapshotReads" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.SnapshotReads" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.SnapshotReads" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_SnapshotReads" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The log sequence number of reads for snapshot transactions." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction..::.SnapshotReads Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_MutexSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_MutexSystemStats"

/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:TOCTitle Title="MutexSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.MutexSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mutex subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MutexSystemStats Method </td></tr><tr

id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verify Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
 type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_Database_Verify" /><meta name="guid"
content="Overload_BerkeleyDB_Database_Verify" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.Database.Verify" /><MSHelp:TOCTitle Title="Verify Method "
/><MSHelp:RLTitle Title="Database.Verify Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.Database.Verify"
 /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassVerifyTopic" /><MSHelp:Keyword
Index="K" Term="Verify method" /><MSHelp:Keyword Index="K" Term="Database.Verify method"
/><MSHelp:Keyword Index="F" Term="Verify" /><MSHelp:Keyword Index="F" Term="Database.Verify"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Verify" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
 title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
 for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="cs">..::.Verify Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FillPercentage Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactConfig_FillPercentage" /><meta name="guid" content="P_BerkeleyDB_CompactConfig_FillPercentage" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactConfig.FillPercentage" /><MSHelp:TOCTitle Title="FillPercentage Property "

/><MSHelp:RLTitle Title="CompactConfig.FillPercentage Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactConfig.FillPercentage" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassFillPercentageTopic" /><MSHelp:Keyword Index="K" Term="FillPercentage property" /><MSHelp:Keyword Index="K" Term="CompactConfig.FillPercentage property" /><MSHelp:Keyword Index="F" Term="FillPercentage" /><MSHelp:Keyword Index="F" Term="CompactConfig.FillPercentage" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.FillPercentage" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.FillPercentage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.get_FillPercentage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.set_FillPercentage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If non-zero, this provides the goal for filling pages, specified as a percentage between 1 and 100. Any page not at or above this percentage full will be considered for compaction. The default beha ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.FillPercentage Property </td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreePages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_FreePages" /><meta name="guid" content="P_BerkeleyDB_HashStats_FreePages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.FreePages" /><MSHelp:TOCTitle Title="FreePages Property " /><MSHelp:RLTitle Title="HashStats.FreePages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.FreePages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassFreePagesTopic" /><MSHelp:Keyword Index="K" Term="FreePages property" /><MSHelp:Keyword Index="K" Term="HashStats.FreePages property" /><MSHelp:Keyword Index="F" Term="FreePages" /><MSHelp:Keyword Index="F" Term="HashStats.FreePages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.FreePages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.HashStats.FreePages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_FreePages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages on the free list." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.FreePages Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepInMemory Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepInMemory" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepInMemory" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepInMemory" /><MSHelp:TOCTitle Title="RepInMemory Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepInMemory Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepInMemory" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepInMemoryTopic" /><MSHelp:Keyword Index="K"

Term="RepInMemory property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepInMemory property" /><MSHelp:Keyword Index="F" Term="RepInMemory" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepInMemory" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepInMemory" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepInMemory" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepInMemory" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, replication only stores the internal information in-memory and cannot keep persistent state across a site crash or reboot. By default, it is false and replication creates files in the envi ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment<span

class="languageSpecificText">..::.RepInMemory Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Index Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapRecordId_Index" /><meta name="guid" content="P_BerkeleyDB_HeapRecordId_Index" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapRecordId.Index" /><MSHelp:TOCTitle Title="Index Property " /><MSHelp:RLTitle Title="HeapRecordId.Index Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapRecordId.Index" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdClassIndexTopic" /><MSHelp:Keyword Index="K" Term="Index property" /><MSHelp:Keyword Index="K" Term="HeapRecordId.Index property" /><MSHelp:Keyword Index="F" Term="Index" /><MSHelp:Keyword Index="F" Term="HeapRecordId.Index" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId.Index" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.Index" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.get_Index" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.set_Index" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Index in the offset table where the record can be found." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.Index Property </td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_PrintFastStats_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_PrintFastStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.PrintFastStats(System.Boolean)" /><MSHelp:TOCTitle Title="PrintFastStats Method (Boolean)" /><MSHelp:RLTitle Title="BaseDatabase.PrintFastStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.PrintFastStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display
the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.PrintFastStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoCursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RecnoCursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RecnoCursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RecnoCursor" /><MSHelp:TOCTitle Title="RecnoCursor Members" /><MSHelp:RLTitle Title="RecnoCursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RecnoCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="RecnoCursor class" /><MSHelp:Keyword Index="K" Term="RecnoCursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoCursor class" /><MSHelp:Keyword Index="F" Term="RecnoCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor Members</td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AllFileOps Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_AllFileOps" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_AllFileOps" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.AllFileOps" /><MSHelp:TOCTitle Title="AllFileOps Field" /><MSHelp:RLTitle Title="VerboseMessages.AllFileOps Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.AllFileOps" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassAllFileOpsTopic" /><MSHelp:Keyword Index="K" Term="AllFileOps field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.AllFileOps field" /><MSHelp:Keyword Index="F" Term="AllFileOps" /><MSHelp:Keyword Index="F" Term="VerboseMessages.AllFileOps" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.AllFileOps" /><MSHelp:Attr Name="APIType" Value="Managed"

/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.AllFileOps" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display additional information when performing all filesystem operations, including read and write. May not be available on all platforms." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.AllFileOps Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>LockNotGrantedException Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_LockNotGrantedException__ctor" /><meta name="guid"
content="M_BerkeleyDB_LockNotGrantedException__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.LockNotGrantedException.#ctor" /><MSHelp:TOCTitle Title="LockNotGrantedException
Constructor " /><MSHelp:RLTitle Title="LockNotGrantedException Constructor (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LockNotGrantedException.#ctor" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBLockNotGrantedExceptionClassctorTopic" /><MSHelp:Keyword Index="K"
Term="LockNotGrantedException class, constructor" /><MSHelp:Keyword Index="K"
Term="LockNotGrantedException.LockNotGrantedException constructor"
/><MSHelp:Keyword Index="F" Term="LockNotGrantedException" /><MSHelp:Keyword Index="F"
Term="LockNotGrantedException.LockNotGrantedException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockNotGrantedException.LockNotGrantedException" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockNotGrantedException..ctor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Initialize a new instance of the LockNotGrantedException" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">LockNotGrantedException
Constructor </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LockNotGrantedException.htm">LockNotGrantedException Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Renumber
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_Renumber" /><meta name="guid"
content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_Renumber" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.Renumber" /><MSHelp:TOCTitle Title="Renumber Field"
/><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.Renumber Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.Renumber" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassRenumberTopic"
/><MSHelp:Keyword Index="K" Term="Renumber field" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig.Renumber field" /><MSHelp:Keyword Index="F" Term="Renumber"
/><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.Renumber" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.Renumber" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.Renumber" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="Abstract" Value="Cause the logical record numbers to be mutable, and change as records are added to and deleted from the database."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig..::.Renumber Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseException Members</title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DatabaseException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DatabaseException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DatabaseException" /><MSHelp:TOCTitle Title="DatabaseException Members" /><MSHelp:RLTitle Title="DatabaseException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DatabaseException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="DatabaseException class" /><MSHelp:Keyword Index="K" Term="DatabaseException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseException class" /><MSHelp:Keyword Index="F" Term="DatabaseException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException Members</td></tr><tr id="headerTableRow3"><td align="left">DatabaseException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RenameDB Method (String, String, Boolean, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="RenameDB Method (String, String, Boolean, Transaction)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RenameDB Method (String, String, Boolean, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.Boolean,BerkeleyD

B.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the underlying file represented by using the value supplied to , incidentally renaming all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RenameDB Method (String, String, Boolean, Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Version Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_Version" /><meta name="guid" content="P_BerkeleyDB_LogStats_Version" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.Version" /><MSHelp:TOCTitle Title="Version Property " /><MSHelp:RLTitle Title="LogStats.Version Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.Version" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassVersionTopic" /><MSHelp:Keyword Index="K" Term="Version property" /><MSHelp:Keyword Index="K" Term="LogStats.Version property" /><MSHelp:Keyword Index="F" Term="Version" /><MSHelp:Keyword Index="F" Term="LogStats.Version" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.Version" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.Version" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_Version" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log file version number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.Version Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryQueueDatabase_PadByte" /><meta name="guid" content="P_BerkeleyDB_SecondaryQueueDatabase_PadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryQueueDatabase.PadByte" /><MSHelp:TOCTitle Title="PadByte Property " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.PadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryQueueDatabase.PadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassPadByteTopic" />
<MSHelp:Keyword Index="K" Term="PadByte property" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.PadByte property" /><MSHelp:Keyword Index="F" Term="PadByte" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.PadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.PadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.get_PadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetEnumerator Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_GetEnumerator" /><meta name="guid" content="M_BerkeleyDB_Cursor_GetEnumerator" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.GetEnumerator" /><MSHelp:TOCTitle Title="GetEnumerator Method " /><MSHelp:RLTitle Title="Cursor.GetEnumerator Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.GetEnumerator" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassGetEnumeratorTopic" /><MSHelp:Keyword Index="K" Term="GetEnumerator method" /><MSHelp:Keyword Index="K" Term="Cursor.GetEnumerator method" /><MSHelp:Keyword Index="F" Term="GetEnumerator" /><MSHelp:Keyword Index="F" Term="Cursor.GetEnumerator" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.GetEnumerator" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.GetEnumerator" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Returns an enumerator that iterates through the ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.GetEnumerator Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UNKNOWN Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseType_UNKNOWN" /><meta name="guid" content="F_BerkeleyDB_DatabaseType_UNKNOWN" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseType.UNKNOWN" /><MSHelp:TOCTitle Title="UNKNOWN Field" /><MSHelp:RLTitle Title="DatabaseType.UNKNOWN Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseType.UNKNOWN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassUNKNOWNTopic" /><MSHelp:Keyword Index="K" Term="UNKNOWN field" /><MSHelp:Keyword Index="K" Term="DatabaseType.UNKNOWN field" /><MSHelp:Keyword Index="F" Term="UNKNOWN" /><MSHelp:Keyword Index="F" Term="DatabaseType.UNKNOWN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.UNKNOWN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.UNKNOWN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Unknown access method" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType..::.UNKNOWN Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method "

/><MSHelp:RLTitle Title="BaseDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.GetBoth" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="BaseDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox"
data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"
for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">BaseDatabase<span
class="cs">..::<span
class="nu">.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BaseDatabase.htm">BaseDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BufferSize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta
name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogConfig_BufferSize"
/><meta name="guid" content="P_BerkeleyDB_LogConfig_BufferSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LogConfig.BufferSize" /><MSHelp:TOCTitle Title="BufferSize Property "
/><MSHelp:RLTitle Title="LogConfig.BufferSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LogConfig.BufferSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogConfigClassBufferSizeTopic" /><MSHelp:Keyword Index="K" Term="BufferSize
property" /><MSHelp:Keyword Index="K" Term="LogConfig.BufferSize property" /><MSHelp:Keyword
Index="F" Term="BufferSize" /><MSHelp:Keyword Index="F" Term="LogConfig.BufferSize"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.BufferSize" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LogConfig.BufferSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogConfig.get_BufferSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogConfig.set_BufferSize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the in-
memory log buffer, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.BufferSize Property </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_RefreshMultiple" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_RefreshMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.RefreshMultiple" /><MSHelp:TOCTitle Title="RefreshMultiple Method " /><MSHelp:RLTitle Title="RecnoCursor.RefreshMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.RefreshMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassRefreshMultipleTopic" /><MSHelp:Keyword Index="K" Term="RefreshMultiple method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.RefreshMultiple method" /><MSHelp:Keyword Index="F"
Term="RefreshMultiple" /><MSHelp:Keyword Index="F" Term="RecnoCursor.RefreshMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.RefreshMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.RefreshMultiple Method </td></tr><tr id="headerTableRow3"><td
align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Overwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Overwrite" /><meta name="guid" content="M_BerkeleyDB_Cursor_Overwrite" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Overwrite(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Overwrite Method " /><MSHelp:RLTitle Title="Cursor.Overwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Overwrite(BerkeleyDB.DatabaseEntry)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassOverwriteTopic" /><MSHelp:Keyword Index="K" Term="Overwrite method" /><MSHelp:Keyword Index="K" Term="Cursor.Overwrite
method" /><MSHelp:Keyword Index="F" Term="Overwrite" /><MSHelp:Keyword Index="F" Term="Cursor.Overwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Overwrite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Overwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Overwrite the data of the key/data pair to which the cursor refers with the specified data item." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">Cursor<span
class="cs">..::<span
class="nu">.Overwrite Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CursorConfig
Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_CursorConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_CursorConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.CursorConfig" /><MSHelp:TOCTitle Title="CursorConfig Members" /><MSHelp:RLTitle Title="CursorConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.CursorConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="CursorConfig class" /><MSHelp:Keyword Index="K" Term="CursorConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CursorConfig class" /><MSHelp:Keyword Index="F" Term="CursorConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CursorConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">CursorConfig
Members</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_CursorConfig.htm">CursorConfig Class <a href="#constructorTableToggle"
onclick="OpenSection(constructorTableToggle)">Constructors <a href="#methodTableToggle"
onclick="OpenSection(methodTableToggle)">Methods <a href="#fieldTableToggle"
onclick="OpenSection(fieldTableToggle)">Fields <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>ForeignKeyDeleteAction
Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="T_BerkeleyDB_ForeignKeyDeleteAction" /><meta name="guid"
content="T_BerkeleyDB_ForeignKeyDeleteAction" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.ForeignKeyDeleteAction" /><MSHelp:TOCTitle Title="ForeignKeyDeleteAction
Enumeration" /><MSHelp:RLTitle Title="ForeignKeyDeleteAction Enumeration (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ForeignKeyDeleteAction" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.ForeignKeyDeleteAction.ABORT" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.ForeignKeyDeleteAction.CASCADE" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.ForeignKeyDeleteAction.NULLIFY" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBForeignKeyDeleteActionClassTopic" /><MSHelp:Keyword Index="K"
Term="ForeignKeyDeleteAction enumeration" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.ForeignKeyDeleteAction enumeration" /><MSHelp:Keyword Index="K" Term="ABORT
enumeration member" /><MSHelp:Keyword Index="K" Term="CASCADE enumeration member"

/><MSHelp:Keyword Index="K" Term="NULLIFY enumeration member" /><MSHelp:Keyword Index="F" Term="ForeignKeyDeleteAction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignKeyDeleteAction" /><MSHelp:Keyword Index="F" Term="ForeignKeyDeleteAction.ABORT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignKeyDeleteAction.ABORT" /><MSHelp:Keyword Index="F" Term="ForeignKeyDeleteAction.CASCADE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignKeyDeleteAction.CASCADE" /><MSHelp:Keyword Index="F" Term="ForeignKeyDeleteAction.NULLIFY" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ForeignKeyDeleteAction.NULLIFY" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyDeleteAction" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyDeleteAction.ABORT" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyDeleteAction.CASCADE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignKeyDeleteAction.NULLIFY" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies the action to take when deleting a foreign key" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignKeyDeleteAction Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (UInt32, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_GetMultiple_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_GetMultiple_1" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32,System.Int32)" /><MSHelp:TOCTitle Title="GetMultiple Method (UInt32, Int32)" /><MSHelp:RLTitle Title="BTreeDatabase.GetMultiple Method (UInt32, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.GetMultiple(System.UInt32,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.GetMultiple Method (UInt32, Int32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EncryptAlgorithm Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_EncryptAlgorithm" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_EncryptAlgorithm" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.EncryptAlgorithm" /><MSHelp:TOCTitle Title="EncryptAlgorithm Property " /><MSHelp:RLTitle Title="BaseDatabase.EncryptAlgorithm Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.EncryptAlgorithm" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassEncryptAlgorithmTopic" /><MSHelp:Keyword Index="K" Term="EncryptAlgorithm property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.EncryptAlgorithm property" /><MSHelp:Keyword Index="F" Term="EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="BaseDatabase.EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.EncryptAlgorithm" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.EncryptAlgorithm" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_EncryptAlgorithm" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The algorithm used by the Berkeley DB library to perform encryption and decryption."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BaseDatabase.<span
class="vb">.::.EncryptAlgorithm Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BaseDatabase.htm">BaseDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ProcessID

Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_ProcessID" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_ProcessID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.ProcessID" /><MSHelp:TOCTitle Title="ProcessID Property " /><MSHelp:RLTitle Title="ActiveTransaction.ProcessID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.ProcessID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassProcessIDTopic" /><MSHelp:Keyword Index="K" Term="ProcessID property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.ProcessID property" /><MSHelp:Keyword Index="F" Term="ProcessID" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.ProcessID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.ProcessID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.ProcessID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_ProcessID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The process ID of the originator of the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ActiveTransaction.<span
class="vb">.::.ProcessID Property
</td></tr><tr id="headerTableRow3"><td
align="left">ActiveTransaction Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_GetBoth" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method "
/><MSHelp:RLTitle Title="SecondaryBTreeDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.GetBoth" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K"
Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.GetBoth method"
/><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabase.GetBoth" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase.<span
class="vb">.::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HashStats" /><meta name="guid" content="T_BerkeleyDB_HashStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HashStats" /><MSHelp:TOCTitle Title="HashStats Class" /><MSHelp:RLTitle Title="HashStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HashStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassTopic" /><MSHelp:Keyword Index="K" Term="HashStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashStats class" /><MSHelp:Keyword Index="K" Term="HashStats class, about HashStats class" /><MSHelp:Keyword Index="F" Term="HashStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about a HashDatabase" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InternalPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_InternalPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_InternalPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.InternalPagesFreeBytes" /><MSHelp:TOCTitle Title="InternalPagesFreeBytes Property " /><MSHelp:RLTitle Title="RecnoStats.InternalPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.InternalPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassInternalPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="InternalPagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="RecnoStats.InternalPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="InternalPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="RecnoStats.InternalPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.InternalPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.InternalPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_InternalPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in internal pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.InternalPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapFullException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HeapFullException" /><meta name="guid" content="Properties_T_BerkeleyDB_HeapFullException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HeapFullException" /><MSHelp:TOCTitle Title="HeapFullException Properties " /><MSHelp:RLTitle Title="HeapFullException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HeapFullException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapFullExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="HeapFullException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapFullException Properties </td></tr><tr id="headerTableRow3"><td align="left">HeapFullException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TxnTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TxnTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TxnTimeout" /><MSHelp:TOCTitle Title="TxnTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TxnTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TxnTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTxnTimeoutTopic" /><MSHelp:Keyword Index="K" Term="TxnTimeout property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TxnTimeout property" /><MSHelp:Keyword Index="F" Term="TxnTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TxnTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TxnTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TxnTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TxnTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TxnTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A value, in microseconds, representing transaction timeouts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TxnTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Increment Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="P_BerkeleyDB_SequenceConfig_Increment" /><meta name="guid"
content="P_BerkeleyDB_SequenceConfig_Increment" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SequenceConfig.Increment" /><MSHelp:TOCTitle Title="Increment Property "
/><MSHelp:RLTitle Title="SequenceConfig.Increment Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SequenceConfig.Increment" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSequenceConfigClassIncrementTopic" /><MSHelp:Keyword Index="K" Term="Increment
property" /><MSHelp:Keyword Index="K" Term="SequenceConfig.Increment property" /><MSHelp:Keyword
Index="F" Term="Increment" /><MSHelp:Keyword Index="F" Term="SequenceConfig.Increment"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.Increment" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.Increment" /><MSHelp:Attr
Name="APIName"
Value="BerkeleyDB.SequenceConfig.get_Increment" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SequenceConfig.set_Increment" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the
sequence will be incremented. This is the default." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"

type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.Increment Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrev" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method " /><MSHelp:RLTitle Title="Cursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrev" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store that pair in . In the presence of duplicate key ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PreparedTransaction Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_PreparedTransaction" /><meta name="guid" content="Properties_T_BerkeleyDB_PreparedTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.PreparedTransaction" /><MSHelp:TOCTitle Title="PreparedTransaction Properties " /><MSHelp:RLTitle Title="PreparedTransaction Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.PreparedTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPreparedTransactionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="PreparedTransaction class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PreparedTransaction Properties </td></tr><tr id="headerTableRow3"><td align="left">PreparedTransaction Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseExpiredException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_LeaseExpiredException__ctor" /><meta name="guid" content="M_BerkeleyDB_LeaseExpiredException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.LeaseExpiredException.#ctor" /><MSHelp:TOCTitle Title="LeaseExpiredException Constructor " /><MSHelp:RLTitle Title="LeaseExpiredException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LeaseExpiredException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLeaseExpiredExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException class, constructor" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException.LeaseExpiredException constructor" /><MSHelp:Keyword Index="F" Term="LeaseExpiredException" /><MSHelp:Keyword Index="F" Term="LeaseExpiredException.LeaseExpiredException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LeaseExpiredException.LeaseExpiredException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LeaseExpiredException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the LeaseExpiredException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"

class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LeaseExpiredException Constructor </td></tr><tr id="headerTableRow3"><td align="left">LeaseExpiredException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolFileStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_MPoolFileStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_MPoolFileStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.MPoolFileStats" /><MSHelp:TOCTitle Title="MPoolFileStats Members" /><MSHelp:RLTitle Title="MPoolFileStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.MPoolFileStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="MPoolFileStats class" /><MSHelp:Keyword Index="K" Term="MPoolFileStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MPoolFileStats class" /><MSHelp:Keyword Index="F" Term="MPoolFileStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MPoolFileStats Members</td></tr><tr id="headerTableRow3"><td
align="left">MPoolFileStats Class <a
href="#methodTableToggle" onclick="OpenSection(methodTableToggle)">Methods <a
href="#propertyTableToggle" onclick="OpenSection(propertyTableToggle)">Properties <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Port Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationHostAddress_Port" /><meta name="guid" content="F_BerkeleyDB_ReplicationHostAddress_Port" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationHostAddress.Port" /><MSHelp:TOCTitle Title="Port Field" /><MSHelp:RLTitle Title="ReplicationHostAddress.Port Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationHostAddress.Port" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressClassPortTopic" /><MSHelp:Keyword Index="K" Term="Port field" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress.Port field" /><MSHelp:Keyword Index="F" Term="Port" /><MSHelp:Keyword Index="F" Term="ReplicationHostAddress.Port" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationHostAddress.Port" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationHostAddress.Port" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The port number on which the site is receiving." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress..::.Port Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VersionMismatchException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_VersionMismatchException__ctor" /><meta name="guid" content="M_BerkeleyDB_VersionMismatchException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.VersionMismatchException.#ctor" /><MSHelp:TOCTitle Title="VersionMismatchException Constructor " /><MSHelp:RLTitle Title="VersionMismatchException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.VersionMismatchException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVersionMismatchExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class, constructor" /><MSHelp:Keyword Index="K" Term="VersionMismatchException.VersionMismatchException constructor" /><MSHelp:Keyword Index="F" Term="VersionMismatchException" /><MSHelp:Keyword Index="F" Term="VersionMismatchException.VersionMismatchException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VersionMismatchException.VersionMismatchException" /><MSHelp:Attr Name="APIType"

Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VersionMismatchException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the VersionMismatchException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VersionMismatchException Constructor </td></tr><tr id="headerTableRow3"><td align="left">VersionMismatchException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_NEWSITE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_NEWSITE" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_NEWSITE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_NEWSITE" /><MSHelp:TOCTitle Title="DB_REP_NEWSITE Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_NEWSITE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_NEWSITE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_NEWSITETopic" /><MSHelp:Keyword Index="K" Term="DB_REP_NEWSITE field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_NEWSITE field" /><MSHelp:Keyword Index="F" Term="DB_REP_NEWSITE" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_NEWSITE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_NEWSITE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_NEWSITE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="New site entered system." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_NEWSITE Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextDuplicateMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextDuplicateMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextDuplicateMultipleKey" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextDuplicateMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextDuplicateMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::<span

class="nu">.MoveNextDuplicateMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SendRequest Method (DatabaseEntry[], UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbChannel_SendRequest_1" /><meta name="guid" content="M_BerkeleyDB_DbChannel_SendRequest_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbChannel.SendRequest(BerkeleyDB.DatabaseEntry[],System.UInt32)" /><MSHelp:TOCTitle Title="SendRequest Method (DatabaseEntry[], UInt32)" /><MSHelp:RLTitle Title="DbChannel.SendRequest Method (DatabaseEntry[], UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbChannel.SendRequest(BerkeleyDB.DatabaseEntry[],System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.SendRequest" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Send a message on the message channel. The message is sent synchronously. The method blocks waiting for a response before returning. If a response is not received within the timeout value configur ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.SendRequest Method (array<DatabaseEntry>[]()[], UInt32)</td></tr><tr id="headerTableRow3"><td
align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HeapStats" /><meta name="guid" content="T_BerkeleyDB_HeapStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HeapStats" /><MSHelp:TOCTitle Title="HeapStats Class" /><MSHelp:RLTitle Title="HeapStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HeapStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassTopic" /><MSHelp:Keyword Index="K" Term="HeapStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapStats class" /><MSHelp:Keyword Index="K" Term="HeapStats class, about HeapStats class" /><MSHelp:Keyword
Index="F" Term="HeapStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr

Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about a QueueDatabase" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyEmptyException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_KeyEmptyException" /><meta name="guid" content="Methods_T_BerkeleyDB_KeyEmptyException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.KeyEmptyException" /><MSHelp:TOCTitle Title="KeyEmptyException Methods " /><MSHelp:RLTitle Title="KeyEmptyException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.KeyEmptyException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyEmptyExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyEmptyException Methods </td></tr><tr id="headerTableRow3"><td align="left">KeyEmptyException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_SecondaryHashDatabase.htm">SecondaryHashDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorPrefix Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_ErrorPrefix" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_ErrorPrefix" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.ErrorPrefix" /><MSHelp:TOCTitle Title="ErrorPrefix Field" /><MSHelp:RLTitle Title="DatabaseConfig.ErrorPrefix Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.ErrorPrefix" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassErrorPrefixTopic" /><MSHelp:Keyword Index="K" Term="ErrorPrefix field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.ErrorPrefix field" /><MSHelp:Keyword Index="F" Term="ErrorPrefix" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.ErrorPrefix" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.ErrorPrefix" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.ErrorPrefix" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The prefix string that appears before error messages issued by Berkeley DB." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.ErrorPrefix Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseMVCC Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_UseMVCC" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_UseMVCC" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.UseMVCC" /><MSHelp:TOCTitle Title="UseMVCC Field" /><MSHelp:RLTitle Title="DatabaseConfig.UseMVCC Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.UseMVCC" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassUseMVCCTopic" /><MSHelp:Keyword Index="K" Term="UseMVCC field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.UseMVCC field" /><MSHelp:Keyword Index="F" Term="UseMVCC" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.UseMVCC" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.DatabaseConfig.UseMVCC" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.UseMVCC" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Open the database with support for multiversion concurrency control." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.UseMVCC Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_Open_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryDatabase.Open Method (String, String, SecondaryDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryDatabase object, open the database represented by and associate the database with the primary index. The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Open Method (String, String, SecondaryDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method (LockingInfo)</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_RefreshMultiple_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_RefreshMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.RefreshMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="RefreshMultiple Method
(LockingInfo)" /><MSHelp:RLTitle Title="Cursor.RefreshMultiple Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.RefreshMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultiple Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VersionMismatchException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_VersionMismatchException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_VersionMismatchException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.VersionMismatchException" /><MSHelp:TOCTitle Title="VersionMismatchException Members" /><MSHelp:RLTitle Title="VersionMismatchException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.VersionMismatchException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVersionMismatchExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.VersionMismatchException class" /><MSHelp:Keyword Index="F" Term="VersionMismatchException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VersionMismatchException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VersionMismatchException Members</td></tr><tr id="headerTableRow3"><td align="left">VersionMismatchException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RetLsn Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RepProcMsgResult_RetLsn" /><meta name="guid" content="F_BerkeleyDB_RepProcMsgResult_RetLsn" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RepProcMsgResult.RetLsn" /><MSHelp:TOCTitle Title="RetLsn Field" /><MSHelp:RLTitle Title="RepProcMsgResult.RetLsn Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.RetLsn" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultClassRetLsnTopic" /><MSHelp:Keyword Index="K" Term="RetLsn field" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult.RetLsn field" /><MSHelp:Keyword Index="F" Term="RetLsn" /><MSHelp:Keyword Index="F" Term="RepProcMsgResult.RetLsn" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepProcMsgResult.RetLsn" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.RepProcMsgResult.RetLsn" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The log sequence number of the permanent log message that could not be written to disk if is . The largest log sequence number of the permanent records that are now written to disk as ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepProcMsgResult..::.RetLsn Field</td></tr><tr id="headerTableRow3"><td align="left">RepProcMsgResult Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_MutexStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_MutexStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.MutexStats" /><MSHelp:TOCTitle Title="MutexStats Members" /><MSHelp:RLTitle Title="MutexStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.MutexStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="MutexStats class" /><MSHelp:Keyword Index="K" Term="MutexStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MutexStats class" /><MSHelp:Keyword Index="F" Term="MutexStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats
Members</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_MutexStats.htm">MutexStats Class <a href="#methodTableToggle"
onclick="OpenSection(methodTableToggle)">Methods
Properties <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TableSize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_LockingConfig_TableSize" /><meta name="guid"
content="P_BerkeleyDB_LockingConfig_TableSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockingConfig.TableSize" /><MSHelp:TOCTitle Title="TableSize Property "
/><MSHelp:RLTitle Title="LockingConfig.TableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockingConfig.TableSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingConfigClassTableSizeTopic" /><MSHelp:Keyword Index="K" Term="TableSize
property" /><MSHelp:Keyword Index="K" Term="LockingConfig.TableSize
property" /><MSHelp:Keyword Index="F" Term="TableSize" /><MSHelp:Keyword Index="F"
Term="LockingConfig.TableSize" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.LockingConfig.TableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.get_TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.set_TableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the number of buckets in the lock object hash table in the Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.TableSize Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig

Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RemoveDB Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RemoveDB" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_RemoveDB" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:TOCTitle Title="RemoveDB Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RemoveDB Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRemoveDBTopic" /><MSHelp:Keyword Index="K" Term="RemoveDB method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RemoveDB method" /><MSHelp:Keyword Index="F" Term="RemoveDB" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RemoveDB" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RemoveDB Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Compact" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Compact"

/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Compact" /><MSHelp:TOCTitle Title="Compact Method " /><MSHelp:RLTitle Title="BTreeDatabase.Compact Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Compact" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassCompactTopic" /><MSHelp:Keyword Index="K" Term="Compact method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Compact method" /><MSHelp:Keyword Index="F" Term="Compact" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Compact" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Compact Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_RegionLockNoWait" /><meta
name="guid" content="P_BerkeleyDB_LogStats_RegionLockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.RegionLockNoWait" /><MSHelp:TOCTitle Title="RegionLockNoWait Property " /><MSHelp:RLTitle Title="LogStats.RegionLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.RegionLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassRegionLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionLockNoWait property" /><MSHelp:Keyword Index="K" Term="LogStats.RegionLockNoWait property" /><MSHelp:Keyword Index="F" Term="RegionLockNoWait" /><MSHelp:Keyword Index="F" Term="LogStats.RegionLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.RegionLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.RegionLockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_RegionLockNoWait"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.RegionLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseConfig_PageSize" /><meta name="guid"
content="P_BerkeleyDB_DatabaseConfig_PageSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseConfig.PageSize" /><MSHelp:TOCTitle Title="PageSize Property "
/><MSHelp:RLTitle Title="DatabaseConfig.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseConfig.PageSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseConfigClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize
property" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.PageSize property" /><MSHelp:Keyword
Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.PageSize"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.PageSize" /><MSHelp:Attr
Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseConfig.PageSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseConfig.get_PageSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseConfig.set_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the
pages used to hold items in the database, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Throttled Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_Throttled" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_Throttled" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.Throttled" /><MSHelp:TOCTitle Title="Throttled Property " /><MSHelp:RLTitle Title="ReplicationStats.Throttled Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.Throttled" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassThrottledTopic"
/><MSHelp:Keyword Index="K" Term="Throttled property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.Throttled property" /><MSHelp:Keyword Index="F" Term="Throttled" /><MSHelp:Keyword Index="F" Term="ReplicationStats.Throttled" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.Throttled" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.Throttled" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_Throttled" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of times we were throttled." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.Throttled Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PageSize" /><meta name="guid"

content="P_BerkeleyDB_MPoolStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="MPoolStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="MPoolStats.PageSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Assumed page size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PageSize Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_Remove" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_Remove"
 /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.Remove" /><MSHelp:TOCTitle Title="Remove Method " /><MSHelp:RLTitle Title="BaseDatabase.Remove Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Remove" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassRemoveTopic" /><MSHelp:Keyword Index="K" Term="Remove method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Remove method" /><MSHelp:Keyword Index="F" Term="Remove" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Remove" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
 type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table
 id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Remove Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Snapshot Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_TransactionConfig_Snapshot" /><meta name="guid"
content="F_BerkeleyDB_TransactionConfig_Snapshot"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.TransactionConfig.Snapshot"
/><MSHelp:TOCTitle Title="Snapshot Field" /><MSHelp:RLTitle Title="TransactionConfig.Snapshot Field
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.Snapshot"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassSnapshotTopic"
/><MSHelp:Keyword Index="K" Term="Snapshot field" /><MSHelp:Keyword Index="K"
Term="TransactionConfig.Snapshot field" /><MSHelp:Keyword Index="F" Term="Snapshot"
/><MSHelp:Keyword Index="F" Term="TransactionConfig.Snapshot" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.TransactionConfig.Snapshot" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionConfig.Snapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, this
transaction will execute with snapshot isolation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.Snapshot Field</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Peer Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_Peer" /><meta name="guid" content="P_BerkeleyDB_DbSite_Peer" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSite.Peer" /><MSHelp:TOCTitle Title="Peer Property " /><MSHelp:RLTitle Title="DbSite.Peer Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSite.Peer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassPeerTopic" /><MSHelp:Keyword Index="K" Term="Peer property" /><MSHelp:Keyword Index="K" Term="DbSite.Peer property" /><MSHelp:Keyword Index="F" Term="Peer" /><MSHelp:Keyword Index="F" Term="DbSite.Peer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.Peer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.Peer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.get_Peer" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSite.set_Peer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is peer to local site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.Peer Property </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSizeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapDatabaseConfig_MaxSizeBytes" /><meta name="guid" content="P_BerkeleyDB_HeapDatabaseConfig_MaxSizeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapDatabaseConfig.MaxSizeBytes" /><MSHelp:TOCTitle Title="MaxSizeBytes Property " /><MSHelp:RLTitle Title="HeapDatabaseConfig.MaxSizeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapDatabaseConfig.MaxSizeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigClassMaxSizeBytesTopic" /><MSHelp:Keyword Index="K" Term="MaxSizeBytes property" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig.MaxSizeBytes property" /><MSHelp:Keyword Index="F" Term="MaxSizeBytes" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig.MaxSizeBytes" /><MSHelp:Keyword

Index="F" Term="BerkeleyDB.HeapDatabaseConfig.MaxSizeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig.MaxSizeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig.get_MaxSizeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The bytes component of the maximum on-disk database file size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig..::.MaxSizeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentFile Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_CurrentFile" /><meta name="guid" content="P_BerkeleyDB_LogStats_CurrentFile" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.CurrentFile" /><MSHelp:TOCTitle Title="CurrentFile Property " /><MSHelp:RLTitle Title="LogStats.CurrentFile Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.CurrentFile" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassCurrentFileTopic" /><MSHelp:Keyword Index="K" Term="CurrentFile property" /><MSHelp:Keyword Index="K" Term="LogStats.CurrentFile property" /><MSHelp:Keyword Index="F" Term="CurrentFile" /><MSHelp:Keyword Index="F" Term="LogStats.CurrentFile" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.CurrentFile" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.CurrentFile" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_CurrentFile" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current log file number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.CurrentFile Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="BTreeDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey
Method (DatabaseEntry, Boolean, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultipleKey_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (DatabaseEntry, Boolean, Int32)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (DatabaseEntry, Boolean, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store that key and as many ensuing key/data pairs that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method (DatabaseEntry, Boolean, Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BeginTransaction Method (TransactionConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_BeginTransaction_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_BeginTransaction_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.BeginTransaction(BerkeleyDB.TransactionConfig)" /><MSHelp:TOCTitle Title="BeginTransaction Method (TransactionConfig)" /><MSHelp:RLTitle Title="DatabaseEnvironment.BeginTransaction Method (TransactionConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.BeginTransaction(BerkeleyDB.TransactionConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new transaction in the environment." /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BeginTransaction Method (TransactionConfig)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AckPolicy Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_AckPolicy" /><meta name="guid" content="AllMembers_T_BerkeleyDB_AckPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.AckPolicy" /><MSHelp:TOCTitle Title="AckPolicy Members" /><MSHelp:RLTitle Title="AckPolicy Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.AckPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyMembersTopic" /><MSHelp:Keyword Index="K" Term="AckPolicy class" /><MSHelp:Keyword Index="K" Term="AckPolicy class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.AckPolicy class" /><MSHelp:Keyword Index="F" Term="AckPolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy Members</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Id Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Transaction_Id" /><meta name="guid" content="P_BerkeleyDB_Transaction_Id" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Transaction.Id" /><MSHelp:TOCTitle Title="Id Property " /><MSHelp:RLTitle Title="Transaction.Id Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Transaction.Id" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassIdTopic" /><MSHelp:Keyword Index="K" Term="Id property" /><MSHelp:Keyword Index="K" Term="Transaction.Id property" /><MSHelp:Keyword Index="F" Term="Id" /><MSHelp:Keyword Index="F" Term="Transaction.Id" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Id" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Id" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.get_Id" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The unique transaction id associated with this transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Id Property </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoDuplicate Method </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_PutNoDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_PutNoDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.PutNoDuplicate" /><MSHelp:TOCTitle Title="PutNoDuplicate Method " /><MSHelp:RLTitle Title="BTreeDatabase.PutNoDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.PutNoDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassPutNoDuplicateTopic" /><MSHelp:Keyword Index="K" Term="PutNoDuplicate method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.PutNoDuplicate method" /><MSHelp:Keyword Index="F" Term="PutNoDuplicate" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.PutNoDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.PutNoDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.PutNoDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepProcMsgResult.ProcMsgResult Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RepProcMsgResult_ProcMsgResult" /><meta name="guid" content="T_BerkeleyDB_RepProcMsgResult_ProcMsgResult" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RepProcMsgResult.ProcMsgResult" /><MSHelp:TOCTitle Title="RepProcMsgResult.ProcMsgResult Enumeration" /><MSHelp:RLTitle Title="RepProcMsgResult.ProcMsgResult Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RepProcMsgResult.ProcMsgResult" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.DUPLICATE_MASTER" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.ERROR" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.HOLD_ELECTION" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.IGNORED" /><MSHelp:Keyword Index="A"

Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.IS_PERMANENT"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.JOIN_FAILURE"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.NEW_SITE"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.NOT_PERMANENT"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepProcMsgResult.ProcMsgResult.SUCCESS"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultProcMsgResultClassTopic"
/><MSHelp:Keyword Index="K" Term="RepProcMsgResult.ProcMsgResult enumeration" /><MSHelp:Keyword
Index="K" Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult enumeration" /><MSHelp:Keyword Index="K"
Term="DUPLICATE_MASTER enumeration member" /><MSHelp:Keyword Index="K" Term="ERROR
enumeration member" /><MSHelp:Keyword Index="K" Term="HOLD_ELECTION enumeration member"
/><MSHelp:Keyword Index="K" Term="IGNORED enumeration member" /><MSHelp:Keyword Index="K"
Term="IS_PERMANENT enumeration member" /><MSHelp:Keyword
Index="K" Term="JOIN_FAILURE enumeration member" /><MSHelp:Keyword Index="K" Term="NEW_SITE
enumeration member" /><MSHelp:Keyword Index="K" Term="NOT_PERMANENT enumeration member"
/><MSHelp:Keyword Index="K" Term="SUCCESS enumeration member" /><MSHelp:Keyword Index="F"
Term="RepProcMsgResult.ProcMsgResult" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult" /><MSHelp:Keyword Index="F"
Term="RepProcMsgResult.ProcMsgResult.DUPLICATE_MASTER" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.DUPLICATE_MASTER" /><MSHelp:Keyword
Index="F" Term="RepProcMsgResult.ProcMsgResult.ERROR" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.ERROR" /><MSHelp:Keyword Index="F"
Term="RepProcMsgResult.ProcMsgResult.HOLD_ELECTION" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.HOLD_ELECTION" /><MSHelp:Keyword Index="F"
Term="RepProcMsgResult.ProcMsgResult.IGNORED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.IGNORED"
/><MSHelp:Keyword Index="F" Term="RepProcMsgResult.ProcMsgResult.IS_PERMANENT"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.IS_PERMANENT"
/><MSHelp:Keyword Index="F" Term="RepProcMsgResult.ProcMsgResult.JOIN_FAILURE"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.JOIN_FAILURE"
/><MSHelp:Keyword Index="F" Term="RepProcMsgResult.ProcMsgResult.NEW_SITE" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.NEW_SITE" /><MSHelp:Keyword Index="F"
Term="RepProcMsgResult.ProcMsgResult.NOT_PERMANENT" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.NOT_PERMANENT" /><MSHelp:Keyword Index="F"
Term="RepProcMsgResult.ProcMsgResult.SUCCESS" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepProcMsgResult.ProcMsgResult.SUCCESS" /><MSHelp:Attr Name="HelpPriority"
Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ProcMsgResult"
/><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.DUPLICATE_MASTER" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.ERROR" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.HOLD_ELECTION" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.IGNORED" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.IS_PERMANENT" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.JOIN_FAILURE" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.NEW_SITE" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.NOT_PERMANENT"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepProcMsgResult.ProcMsgResult.SUCCESS"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The result of processing an incoming replication message." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepProcMsgResult..::.ProcMsgResult Enumeration</td></tr><tr id="headerTableRow3"><td align="left">RepProcMsgResult Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceConfig

Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SequenceConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SequenceConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SequenceConfig" /><MSHelp:TOCTitle Title="SequenceConfig Members" /><MSHelp:RLTitle Title="SequenceConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SequenceConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="SequenceConfig class" /><MSHelp:Keyword Index="K" Term="SequenceConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SequenceConfig class" /><MSHelp:Keyword Index="F" Term="SequenceConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig Members</td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class Constructors Methods Fields
Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_IBackup_Close" /><meta name="guid" content="M_BerkeleyDB_IBackup_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.IBackup.Close(System.String)" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="IBackup.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.IBackup.Close(System.String)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIBackupClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="IBackup.Close method" /><MSHelp:Keyword Index="F"

Term="Close" /><MSHelp:Keyword Index="F" Term="IBackup.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.IBackup.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.IBackup.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Called when ending a backup and closing a backup target." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">IBackup..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">IBackup Interface See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryRecnoDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryRecnoDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:TOCTitle Title="SecondaryRecnoDatabase Methods " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span

id="memberOptionsDropdown" class="filter" tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_nPages" /><meta name="guid" content="P_BerkeleyDB_HashStats_nPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.nPages" /><MSHelp:TOCTitle Title="nPages Property " /><MSHelp:RLTitle Title="HashStats.nPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.nPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassnPagesTopic" /><MSHelp:Keyword Index="K" Term="nPages property" /><MSHelp:Keyword Index="K" Term="HashStats.nPages property" /><MSHelp:Keyword Index="F" Term="nPages" /><MSHelp:Keyword Index="F" Term="HashStats.nPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.nPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.nPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_nPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Page count." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.nPages Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogWrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_LogWrite" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_LogWrite" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.LogWrite(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:TOCTitle Title="LogWrite Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogWrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LogWrite(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogWriteTopic" /><MSHelp:Keyword Index="K" Term="LogWrite method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogWrite
method" /><MSHelp:Keyword Index="F" Term="LogWrite" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogWrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogWrite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogWrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append a record to the log" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogWrite Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecovery Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RunRecovery" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RunRecovery" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RunRecovery" /><MSHelp:TOCTitle Title="RunRecovery Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RunRecovery Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RunRecovery" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRunRecoveryTopic" /><MSHelp:Keyword Index="K" Term="RunRecovery property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RunRecovery property" /><MSHelp:Keyword Index="F" Term="RunRecovery" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RunRecovery" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RunRecovery" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RunRecovery" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RunRecovery" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"

Value="If true, normal recovery was run on this environment before opening it for normal use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RunRecovery Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MagicNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_HashStats_MagicNumber"
/><meta name="guid" content="P_BerkeleyDB_HashStats_MagicNumber" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.HashStats.MagicNumber" /><MSHelp:TOCTitle Title="MagicNumber
Property " /><MSHelp:RLTitle Title="HashStats.MagicNumber Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.HashStats.MagicNumber" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashStatsClassMagicNumberTopic" /><MSHelp:Keyword Index="K"
Term="MagicNumber property" /><MSHelp:Keyword Index="K" Term="HashStats.MagicNumber property"
/><MSHelp:Keyword Index="F" Term="MagicNumber" /><MSHelp:Keyword Index="F"
Term="HashStats.MagicNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.MagicNumber"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.MagicNumber"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_MagicNumber" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Magic number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.MagicNumber Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CheckpointDelay Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_CheckpointDelay" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_CheckpointDelay" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.CheckpointDelay" /><MSHelp:TOCTitle Title="CheckpointDelay Property " /><MSHelp:RLTitle Title="ReplicationConfig.CheckpointDelay Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.CheckpointDelay" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassCheckpointDelayTopic" /><MSHelp:Keyword Index="K" Term="CheckpointDelay property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.CheckpointDelay property" /><MSHelp:Keyword Index="F" Term="CheckpointDelay" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.CheckpointDelay" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.CheckpointDelay" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.CheckpointDelay" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_CheckpointDelay" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_CheckpointDelay" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time a master site will delay between completing a checkpoint and writing a checkpoint record into the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"

title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td
align="left">ReplicationConfig<span
class="cs">..::<span
class="nu">.CheckpointDelay Property </td></tr><tr id="headerTableRow3"><td
align="left">ReplicationConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Gigabytes
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CacheInfo_Gigabytes" /><meta name="guid" content="F_BerkeleyDB_CacheInfo_Gigabytes" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CacheInfo.Gigabytes" /><MSHelp:TOCTitle Title="Gigabytes Field" /><MSHelp:RLTitle Title="CacheInfo.Gigabytes Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CacheInfo.Gigabytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoClassGigabytesTopic" /><MSHelp:Keyword Index="K" Term="Gigabytes field" /><MSHelp:Keyword Index="K" Term="CacheInfo.Gigabytes field" /><MSHelp:Keyword Index="F" Term="Gigabytes" /><MSHelp:Keyword Index="F" Term="CacheInfo.Gigabytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CacheInfo.Gigabytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CacheInfo.Gigabytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of gigabytes in the cache" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">CacheInfo<span
class="languageSpecificText">..<span
class="cpp">::.Gigabytes Field</td></tr><tr
id="headerTableRow3"><td align="left">CacheInfo Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryQueueDatabase
Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Properties_T_BerkeleyDB_SecondaryQueueDatabase" /><meta name="guid"
content="Properties_T_BerkeleyDB_SecondaryQueueDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.SecondaryQueueDatabase"
/><MSHelp:TOCTitle Title="SecondaryQueueDatabase Properties " /><MSHelp:RLTitle
Title="SecondaryQueueDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Properties.T:BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryQueueDatabasePropertiesTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryQueueDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MinKeysPerPage Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabaseConfig_MinKeysPerPage" /><meta name="guid"

content="P_BerkeleyDB_BTreeDatabaseConfig_MinKeysPerPage" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:TOCTitle Title="MinKeysPerPage Property " /><MSHelp:RLTitle Title="BTreeDatabaseConfig.MinKeysPerPage Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassMinKeysPerPageTopic" /><MSHelp:Keyword Index="K" Term="MinKeysPerPage property" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.MinKeysPerPage property" /><MSHelp:Keyword Index="F" Term="MinKeysPerPage" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.get_MinKeysPerPage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.set_MinKeysPerPage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The minimum number of key/data pairs intended to be stored on any single Btree leaf page." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.MinKeysPerPage Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (Int32, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Get_1" /><meta name="guid" content="M_BerkeleyDB_Sequence_Get_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Get(System.Int32,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Get Method (Int32, Transaction)" /><MSHelp:RLTitle Title="Sequence.Get Method (Int32, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Get(System.Int32,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the next available element in the sequence and change the sequence value by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Get Method (Int32, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextMultiple" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextMultiple" /><MSHelp:TOCTitle Title="MoveNextMultiple Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextMultiple method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextMultiple"

/><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox"

data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveNextMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta
name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbSite_Remove" /><meta name="guid" content="M_BerkeleyDB_DbSite_Remove" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbSite.Remove" /><MSHelp:TOCTitle Title="Remove Method " /><MSHelp:RLTitle Title="DbSite.Remove Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbSite.Remove" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassRemoveTopic" /><MSHelp:Keyword Index="K" Term="Remove method" /><MSHelp:Keyword Index="K" Term="DbSite.Remove method" /><MSHelp:Keyword Index="F" Term="Remove" /><MSHelp:Keyword Index="F" Term="DbSite.Remove" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.Remove" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the site from the replication manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table

id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.Remove Method </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Remove_2" /><meta name="guid" content="M_BerkeleyDB_Sequence_Remove_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Remove(System.Boolean)" /><MSHelp:TOCTitle Title="Remove Method (Boolean)" /><MSHelp:RLTitle Title="Sequence.Remove Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Remove(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the sequence from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Remove Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8"

/><META NAME="save" CONTENT="history" /><title>KeyGen Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryDatabase_KeyGen" /><meta name="guid" content="P_BerkeleyDB_SecondaryDatabase_KeyGen" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabase.KeyGen" /><MSHelp:TOCTitle Title="KeyGen Property " /><MSHelp:RLTitle Title="SecondaryDatabase.KeyGen Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryDatabase.KeyGen" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassKeyGenTopic" /><MSHelp:Keyword Index="K" Term="KeyGen property" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.KeyGen property" /><MSHelp:Keyword Index="F" Term="KeyGen" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.KeyGen" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.KeyGen" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.KeyGen" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.get_KeyGen" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.set_KeyGen" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The delegate that creates the set of secondary keys corresponding to a given primary key and data pair." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.KeyGen Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_OverflowPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_OverflowPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.OverflowPagesFreeBytes" /><MSHelp:TOCTitle Title="OverflowPagesFreeBytes Property " /><MSHelp:RLTitle Title="RecnoStats.OverflowPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.OverflowPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassOverflowPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="OverflowPagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="RecnoStats.OverflowPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="OverflowPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="RecnoStats.OverflowPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.OverflowPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.OverflowPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_OverflowPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="Abstract" Value="Bytes free in overflow pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.OverflowPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabase Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryDatabase" /><meta
name="guid" content="Properties_T_BerkeleyDB_SecondaryDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.SecondaryDatabase" /><MSHelp:TOCTitle Title="SecondaryDatabase Properties
" /><MSHelp:RLTitle Title="SecondaryDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Properties.T:BerkeleyDB.SecondaryDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabasePropertiesTopic"
/><MSHelp:Keyword Index="K" Term="SecondaryDatabase class, properties" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input

id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DataPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_DataPages" /><meta name="guid" content="P_BerkeleyDB_QueueStats_DataPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.DataPages" /><MSHelp:TOCTitle Title="DataPages Property " /><MSHelp:RLTitle Title="QueueStats.DataPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.DataPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassDataPagesTopic" /><MSHelp:Keyword Index="K" Term="DataPages property" /><MSHelp:Keyword Index="K" Term="QueueStats.DataPages property" /><MSHelp:Keyword Index="F" Term="DataPages" /><MSHelp:Keyword Index="F" Term="QueueStats.DataPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.DataPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.DataPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_DataPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Data pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.DataPages Property </td></tr><tr
id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ByteOrder Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script

type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_ByteOrder" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_ByteOrder" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.ByteOrder" /><MSHelp:TOCTitle Title="ByteOrder Field" /><MSHelp:RLTitle Title="DatabaseConfig.ByteOrder Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.ByteOrder" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassByteOrderTopic" /><MSHelp:Keyword Index="K" Term="ByteOrder field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.ByteOrder field" /><MSHelp:Keyword Index="F" Term="ByteOrder" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.ByteOrder" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.ByteOrder" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.ByteOrder" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The byte order for integers in the stored database metadata. The host byte order of the machine where the Berkeley DB library was compiled is the default value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.ByteOrder Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey

Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveFirstMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveFirstMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveFirstMultipleKey" /><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveFirstMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveFirstMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveFirstMultipleKey method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveFirstMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultipleKey" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveFirstMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimeouts Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_TxnTimeouts" /><meta name="guid" content="P_BerkeleyDB_LockStats_TxnTimeouts" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.TxnTimeouts" /><MSHelp:TOCTitle Title="TxnTimeouts Property " /><MSHelp:RLTitle Title="LockStats.TxnTimeouts Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.TxnTimeouts" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassTxnTimeoutsTopic" /><MSHelp:Keyword Index="K" Term="TxnTimeouts property" /><MSHelp:Keyword Index="K" Term="LockStats.TxnTimeouts property" /><MSHelp:Keyword Index="F" Term="TxnTimeouts" /><MSHelp:Keyword Index="F" Term="LockStats.TxnTimeouts" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.TxnTimeouts" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr

Name="APIName" Value="BerkeleyDB.LockStats.TxnTimeouts" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_TxnTimeouts" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of transaction timeouts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.TxnTimeouts Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="BaseDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="BaseDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HIGH Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CachePriority_HIGH" /><meta name="guid" content="F_BerkeleyDB_CachePriority_HIGH" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CachePriority.HIGH" /><MSHelp:TOCTitle Title="HIGH Field" /><MSHelp:RLTitle Title="CachePriority.HIGH Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CachePriority.HIGH" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityClassHIGHTopic" /><MSHelp:Keyword Index="K" Term="HIGH field" /><MSHelp:Keyword Index="K" Term="CachePriority.HIGH field" /><MSHelp:Keyword Index="F" Term="HIGH" /><MSHelp:Keyword Index="F" Term="CachePriority.HIGH" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CachePriority.HIGH" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr

Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CachePriority.HIGH" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The next highest priority." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority..::.HIGH Field</td></tr><tr id="headerTableRow3"><td align="left">CachePriority Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats
Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BaseDatabase_PrintStats_1" /><meta name="guid"
content="M_BerkeleyDB_BaseDatabase_PrintStats_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseDatabase.PrintStats(System.Boolean)" /><MSHelp:TOCTitle Title="PrintStats Method
(Boolean)" /><MSHelp:RLTitle Title="BaseDatabase.PrintStats Method (Boolean) (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.PrintStats(System.Boolean)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.PrintStats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Display the database statistical information." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.PrintStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicate_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicate_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair in . MoveNextDupli ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrStartClient Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RepMgrStartClient" /><meta name="guid"

content="Overload_BerkeleyDB_DatabaseEnvironment_RepMgrStartClient" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RepMgrStartClient" /><MSHelp:TOCTitle Title="RepMgrStartClient Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrStartClient Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RepMgrStartClient" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrStartClientTopic" /><MSHelp:Keyword Index="K" Term="RepMgrStartClient method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrStartClient method" /><MSHelp:Keyword Index="F" Term="RepMgrStartClient" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrStartClient" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrStartClient" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span
class="nu">.RepMgrStartClient Method </td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css"
href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_HashDatabase_GetMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_HashDatabase_GetMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashDatabase.GetMultiple" /><MSHelp:TOCTitle Title="GetMultiple Method "
/><MSHelp:RLTitle Title="HashDatabase.GetMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.HashDatabase.GetMultiple" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashDatabaseClassGetMultipleTopic" /><MSHelp:Keyword Index="K"
Term="GetMultiple method" /><MSHelp:Keyword Index="K" Term="HashDatabase.GetMultiple method"
/><MSHelp:Keyword Index="F" Term="GetMultiple" /><MSHelp:Keyword Index="F"
Term="HashDatabase.GetMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">HashDatabase..::.GetMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_GetBoth"
/><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_GetBoth"
/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.GetBoth"
/><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle
Title="SecondaryQueueDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.SecondaryQueueDatabase.GetBoth" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K"
Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.GetBoth method"
/><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F"
Term="SecondaryQueueDatabase.GetBoth" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryQueueDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="QueueDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.PrintStats" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBQueueDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="QueueDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"

for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryHashDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryHashDatabase_Open_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryHashDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryHashDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryHashDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryHashDatabase.Open Method (String, String, SecondaryHashDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryHashDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryHashDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Open Method (String, String, SecondaryHashDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_RegionLockNoWait" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_RegionLockNoWait" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.TransactionStats.RegionLockNoWait" /><MSHelp:TOCTitle Title="RegionLockNoWait Property " /><MSHelp:RLTitle Title="TransactionStats.RegionLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.RegionLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassRegionLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionLockNoWait property" /><MSHelp:Keyword Index="K" Term="TransactionStats.RegionLockNoWait property" /><MSHelp:Keyword Index="F" Term="RegionLockNoWait" /><MSHelp:Keyword Index="F" Term="TransactionStats.RegionLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.RegionLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.RegionLockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_RegionLockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.RegionLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RepMgrStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RepMgrStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RepMgrStats" /><MSHelp:TOCTitle Title="RepMgrStats Members" /><MSHelp:RLTitle Title="RepMgrStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RepMgrStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="RepMgrStats class" /><MSHelp:Keyword Index="K" Term="RepMgrStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RepMgrStats class" /><MSHelp:Keyword Index="F" Term="RepMgrStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats Members</td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats
Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_PutNoOverwrite" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.PutNoOverwrite" /><MSHelp:TOCTitle Title="PutNoOverwrite Method " /><MSHelp:RLTitle Title="RecnoDatabase.PutNoOverwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassPutNoOverwriteTopic" /><MSHelp:Keyword Index="K" Term="PutNoOverwrite method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.PutNoOverwrite method" /><MSHelp:Keyword Index="F" Term="PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.PutNoOverwrite Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Peer Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSiteConfig_Peer" /><meta name="guid" content="P_BerkeleyDB_DbSiteConfig_Peer" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSiteConfig.Peer" /><MSHelp:TOCTitle Title="Peer Property " /><MSHelp:RLTitle Title="DbSiteConfig.Peer Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSiteConfig.Peer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassPeerTopic" /><MSHelp:Keyword Index="K" Term="Peer property" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.Peer property" /><MSHelp:Keyword Index="F" Term="Peer" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.Peer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.Peer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.Peer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.get_Peer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig.set_Peer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the site is peer to local site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.Peer Property </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerificationException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_VerificationException__ctor" /><meta name="guid"
content="M_BerkeleyDB_VerificationException__ctor"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.VerificationException.#ctor"
/><MSHelp:TOCTitle Title="VerificationException Constructor " /><MSHelp:RLTitle
Title="VerificationException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.VerificationException.#ctor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBVerificationExceptionClassctorTopic" /><MSHelp:Keyword Index="K"
Term="VerificationException class, constructor" /><MSHelp:Keyword Index="K"
Term="VerificationException.VerificationException constructor" /><MSHelp:Keyword Index="F"
Term="VerificationException" /><MSHelp:Keyword Index="F"
Term="VerificationException.VerificationException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.VerificationException.VerificationException" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.VerificationException..ctor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Initialize a new instance of the VerificationException" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerificationException Constructor </td></tr><tr id="headerTableRow3"><td align="left">VerificationException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LastCheckpointTime Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_LastCheckpointTime" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_LastCheckpointTime" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.LastCheckpointTime" /><MSHelp:TOCTitle Title="LastCheckpointTime Property " /><MSHelp:RLTitle Title="TransactionStats.LastCheckpointTime Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.LastCheckpointTime" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassLastCheckpointTimeTopic" /><MSHelp:Keyword Index="K" Term="LastCheckpointTime property" /><MSHelp:Keyword Index="K" Term="TransactionStats.LastCheckpointTime property" /><MSHelp:Keyword Index="F" Term="LastCheckpointTime" /><MSHelp:Keyword Index="F" Term="TransactionStats.LastCheckpointTime" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.LastCheckpointTime" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.LastCheckpointTime" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_LastCheckpointTime" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Time of last checkpoint" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">TransactionStats.<span
class="vb">.::.LastCheckpointTime Property
</td></tr><tr
id="headerTableRow3"><td align="left">TransactionStats
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStartMaster
Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepStartMaster_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepStartMaster_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepStartMaster(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="RepStartMaster Method (DatabaseEntry)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStartMaster Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepStartMaster(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure the database environment as a master in a group of replicated database environments." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::<span

class="nu">.RepStartMaster Method (DatabaseEntry)</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevUnique" /><meta
name="guid" content="M_BerkeleyDB_Cursor_MovePrevUnique" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:TOCTitle Title="MovePrevUnique Method "
/><MSHelp:RLTitle Title="Cursor.MovePrevUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not
yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the
database, and store that key and associated datum in . Mo ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label> <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Move" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean)" /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the primary key/data pair associated with the given secondary key in . In the presence of duplicate key values, the first data item in the set of duplicates i

..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor<span
class="languageSpecificText">..::.Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FillFactor

Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_FillFactor" /><meta name="guid" content="P_BerkeleyDB_HashStats_FillFactor" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.FillFactor" /><MSHelp:TOCTitle Title="FillFactor Property " /><MSHelp:RLTitle Title="HashStats.FillFactor Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.FillFactor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassFillFactorTopic" /><MSHelp:Keyword Index="K" Term="FillFactor property" /><MSHelp:Keyword Index="K" Term="HashStats.FillFactor property" /><MSHelp:Keyword Index="F" Term="FillFactor" /><MSHelp:Keyword Index="F" Term="HashStats.FillFactor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.FillFactor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.FillFactor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_FillFactor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Fill factor specified
at create." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.FillFactor Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AutoCommit Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_AutoCommit" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_AutoCommit" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.AutoCommit" /><MSHelp:TOCTitle Title="AutoCommit Field" /><MSHelp:RLTitle Title="DatabaseConfig.AutoCommit Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.AutoCommit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassAutoCommitTopic" /><MSHelp:Keyword Index="K" Term="AutoCommit field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.AutoCommit field" /><MSHelp:Keyword Index="F" Term="AutoCommit" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.AutoCommit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.AutoCommit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.AutoCommit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Enclose the open call within a transaction. If the call succeeds, the open operation will be recoverable and all subsequent database modification operations based on this handle will be transactionally ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.AutoCommit Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GlobalIdLength Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_Transaction_GlobalIdLength" /><meta name="guid" content="F_BerkeleyDB_Transaction_GlobalIdLength" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.Transaction.GlobalIdLength" /><MSHelp:TOCTitle Title="GlobalIdLength Field" /><MSHelp:RLTitle Title="Transaction.GlobalIdLength Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Transaction.GlobalIdLength" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassGlobalIdLengthTopic" /><MSHelp:Keyword Index="K" Term="GlobalIdLength field" /><MSHelp:Keyword Index="K" Term="Transaction.GlobalIdLength field" /><MSHelp:Keyword Index="F" Term="GlobalIdLength" /><MSHelp:Keyword Index="F" Term="Transaction.GlobalIdLength" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.GlobalIdLength" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.GlobalIdLength" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the global transaction ID" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.GlobalIdLength Field</td></tr><tr id="headerTableRow3"><td align="left">Transaction Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OldVersionException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_OldVersionException" /><meta name="guid" content="Methods_T_BerkeleyDB_OldVersionException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.OldVersionException" /><MSHelp:TOCTitle Title="OldVersionException Methods " /><MSHelp:RLTitle Title="OldVersionException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.OldVersionException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBOldVersionExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="OldVersionException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">OldVersionException Methods </td></tr><tr id="headerTableRow3"><td
align="left">OldVersionException Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockCount
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta
name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_LockingConfig_InitLockCount" /><meta name="guid"
content="P_BerkeleyDB_LockingConfig_InitLockCount" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.LockingConfig.InitLockCount" /><MSHelp:TOCTitle Title="InitLockCount Property " /><MSHelp:RLTitle Title="LockingConfig.InitLockCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockingConfig.InitLockCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigClassInitLockCountTopic" /><MSHelp:Keyword Index="K" Term="InitLockCount property" /><MSHelp:Keyword Index="K" Term="LockingConfig.InitLockCount property" /><MSHelp:Keyword Index="F" Term="InitLockCount" /><MSHelp:Keyword Index="F" Term="LockingConfig.InitLockCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.InitLockCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.InitLockCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.get_InitLockCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.set_InitLockCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of locks created by the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.InitLockCount Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LockStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LockStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LockStats" /><MSHelp:TOCTitle Title="LockStats Members" /><MSHelp:RLTitle Title="LockStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LockStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="LockStats class" /><MSHelp:Keyword Index="K" Term="LockStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockStats class" /><MSHelp:Keyword Index="F" Term="LockStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats Members</td></tr><tr id="headerTableRow3"><td align="left">LockStats Class Methods
  Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Alignment Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_Alignment" /><meta name="guid" content="P_BerkeleyDB_MutexStats_Alignment" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.Alignment" /><MSHelp:TOCTitle Title="Alignment Property " /><MSHelp:RLTitle Title="MutexStats.Alignment Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.Alignment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassAlignmentTopic" /><MSHelp:Keyword Index="K" Term="Alignment property" /><MSHelp:Keyword
Index="K" Term="MutexStats.Alignment property" /><MSHelp:Keyword Index="F" Term="Alignment" /><MSHelp:Keyword Index="F" Term="MutexStats.Alignment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.Alignment" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.Alignment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_Alignment" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutex alignment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.Alignment Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MissedLogRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_MissedLogRecords" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MissedLogRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MissedLogRecords" /><MSHelp:TOCTitle Title="MissedLogRecords Property " /><MSHelp:RLTitle Title="ReplicationStats.MissedLogRecords Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MissedLogRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMissedLogRecordsTopic" /><MSHelp:Keyword Index="K" Term="MissedLogRecords property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MissedLogRecords property" /><MSHelp:Keyword Index="F" Term="MissedLogRecords" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MissedLogRecords" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MissedLogRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MissedLogRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MissedLogRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log recs. missed and requested." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;

height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MissedLogRecords Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockPolicy Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DeadlockPolicy" /><meta name="guid" content="Methods_T_BerkeleyDB_DeadlockPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DeadlockPolicy" /><MSHelp:TOCTitle Title="DeadlockPolicy Methods " /><MSHelp:RLTitle Title="DeadlockPolicy Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="Methods.T:BerkeleyDB.DeadlockPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyMethodsTopic" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include

Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
 align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy Methods </td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VersionMismatchException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
 /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_VersionMismatchException" /><meta name="guid" content="Properties_T_BerkeleyDB_VersionMismatchException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.VersionMismatchException" /><MSHelp:TOCTitle Title="VersionMismatchException Properties " /><MSHelp:RLTitle Title="VersionMismatchException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.VersionMismatchException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVersionMismatchExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
 style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:

none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VersionMismatchException Properties </td></tr><tr id="headerTableRow3"><td align="left">VersionMismatchException Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="M_BerkeleyDB_RecnoDatabase_Stats_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Stats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Stats Method (Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Stats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Stats Method

(Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoDatabase.htm">RecnoDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
 Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SyncInterrupted
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
 </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_MPoolStats_SyncInterrupted" /><meta name="guid"
content="P_BerkeleyDB_MPoolStats_SyncInterrupted" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MPoolStats.SyncInterrupted" /><MSHelp:TOCTitle Title="SyncInterrupted Property "
/><MSHelp:RLTitle Title="MPoolStats.SyncInterrupted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.MPoolStats.SyncInterrupted" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMPoolStatsClassSyncInterruptedTopic" /><MSHelp:Keyword Index="K"
Term="SyncInterrupted property" /><MSHelp:Keyword Index="K" Term="MPoolStats.SyncInterrupted property"
/><MSHelp:Keyword Index="F" Term="SyncInterrupted" /><MSHelp:Keyword
 Index="F" Term="MPoolStats.SyncInterrupted" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MPoolStats.SyncInterrupted" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.SyncInterrupted" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.get_SyncInterrupted" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of times
sync interrupted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
 title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,

event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.SyncInterrupted Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CachePriority Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_CachePriority" /><meta name="guid" content="AllMembers_T_BerkeleyDB_CachePriority" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.CachePriority" /><MSHelp:TOCTitle Title="CachePriority Members" /><MSHelp:RLTitle Title="CachePriority Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.CachePriority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityMembersTopic" /><MSHelp:Keyword Index="K" Term="CachePriority class" /><MSHelp:Keyword Index="K" Term="CachePriority class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CachePriority class" /><MSHelp:Keyword Index="F" Term="CachePriority" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.CachePriority" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label

class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority
Members</td></tr><tr id="headerTableRow3"><td align="left">CachePriority Class Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IsolationDegree Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_TransactionConfig_IsolationDegree" /><meta name="guid" content="F_BerkeleyDB_TransactionConfig_IsolationDegree" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.TransactionConfig.IsolationDegree" /><MSHelp:TOCTitle Title="IsolationDegree Field" /><MSHelp:RLTitle Title="TransactionConfig.IsolationDegree
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionConfig.IsolationDegree" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassIsolationDegreeTopic" /><MSHelp:Keyword Index="K" Term="IsolationDegree field" /><MSHelp:Keyword Index="K" Term="TransactionConfig.IsolationDegree field" /><MSHelp:Keyword Index="F" Term="IsolationDegree" /><MSHelp:Keyword Index="F" Term="TransactionConfig.IsolationDegree" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.IsolationDegree" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.IsolationDegree" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The degree of isolation for this transaction" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.IsolationDegree Field</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecoveryException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RunRecoveryException__ctor" /><meta name="guid" content="M_BerkeleyDB_RunRecoveryException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RunRecoveryException.#ctor" /><MSHelp:TOCTitle Title="RunRecoveryException Constructor " /><MSHelp:RLTitle Title="RunRecoveryException Constructor

(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RunRecoveryException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRunRecoveryExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class, constructor" /><MSHelp:Keyword Index="K" Term="RunRecoveryException.RunRecoveryException constructor" /><MSHelp:Keyword Index="F" Term="RunRecoveryException" /><MSHelp:Keyword Index="F" Term="RunRecoveryException.RunRecoveryException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RunRecoveryException.RunRecoveryException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RunRecoveryException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the RunRecoveryException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RunRecoveryException Constructor </td></tr><tr id="headerTableRow3"><td

align="left">RunRecoveryException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InternalPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_RecnoStats_InternalPages" /><meta name="guid"
content="P_BerkeleyDB_RecnoStats_InternalPages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.RecnoStats.InternalPages" /><MSHelp:TOCTitle Title="InternalPages Property "
/><MSHelp:RLTitle Title="RecnoStats.InternalPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.RecnoStats.InternalPages" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoStatsClassInternalPagesTopic" /><MSHelp:Keyword Index="K"
Term="InternalPages property" /><MSHelp:Keyword Index="K" Term="RecnoStats.InternalPages property"
/><MSHelp:Keyword Index="F" Term="InternalPages" /><MSHelp:Keyword Index="F"
Term="RecnoStats.InternalPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.InternalPages"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.InternalPages" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RecnoStats.get_InternalPages" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Internal pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.InternalPages Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="RecnoDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">RecnoDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbFile Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_DbFile" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_DbFile" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.DbFile" /><MSHelp:TOCTitle Title="DbFile Property " /><MSHelp:RLTitle Title="LogVerifyConfig.DbFile Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.DbFile" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassDbFileTopic" /><MSHelp:Keyword Index="K" Term="DbFile property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.DbFile property" /><MSHelp:Keyword Index="F" Term="DbFile" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.DbFile" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.DbFile" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.DbFile" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_DbFile" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_DbFile" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database file name whose logs are to be verified." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.DbFile Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (DatabaseEntry, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Get_5" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Get_5" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Get Method (DatabaseEntry, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="BaseDatabase.Get Method (DatabaseEntry, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.Locki

ngInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database. In the presence of duplicate key values, Get will return the first data item for ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method (DatabaseEntry, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, BTreeDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Open_3" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Open(System.String,System.String,BerkeleyDB.BTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, BTreeDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.Open Method (String, String, BTreeDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Open(System.String,System.String,BerkeleyDB.BTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new BTreeDatabase object and open the database represented by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeDatabase.<span
class="vb">.::.Open Method (String, String,
BTreeDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeDatabase.htm">BTreeDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>FailedConnections Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_RepMgrStats_FailedConnections" /><meta name="guid"
content="P_BerkeleyDB_RepMgrStats_FailedConnections"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RepMgrStats.FailedConnections"
/><MSHelp:TOCTitle Title="FailedConnections Property " /><MSHelp:RLTitle
Title="RepMgrStats.FailedConnections Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.RepMgrStats.FailedConnections" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRepMgrStatsClassFailedConnectionsTopic" /><MSHelp:Keyword Index="K"
Term="FailedConnections property" /><MSHelp:Keyword Index="K" Term="RepMgrStats.FailedConnections
property" /><MSHelp:Keyword Index="F" Term="FailedConnections" /><MSHelp:Keyword Index="F"
Term="RepMgrStats.FailedConnections" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepMgrStats.FailedConnections" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RepMgrStats.FailedConnections" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RepMgrStats.get_FailedConnections"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Failed new connection attempts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats..::.FailedConnections Property </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveLast_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveLast_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveLast(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveLast Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveLast Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveLast(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store the secondary key and primary key/data pair in . If the last key has duplicate values, the last data item in the set of ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveLast Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_HEAP_FULL Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_HEAP_FULL" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_HEAP_FULL" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_HEAP_FULL" /><MSHelp:TOCTitle Title="DB_HEAP_FULL Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_HEAP_FULL Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_HEAP_FULL" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_HEAP_FULLTopic" /><MSHelp:Keyword Index="K" Term="DB_HEAP_FULL field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_HEAP_FULL field" /><MSHelp:Keyword Index="F" Term="DB_HEAP_FULL" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_HEAP_FULL" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_HEAP_FULL" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_HEAP_FULL" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Heap database full." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">ErrorCodes<span
class="cs">..::<span
class="nu">.DB_HEAP_FULL Field</td></tr><tr id="headerTableRow3"><td
align="left">ErrorCodes Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Recno Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_BTreeCursor_Recno" /><meta name="guid"

content="Overload_BerkeleyDB_BTreeCursor_Recno" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.Recno" /><MSHelp:TOCTitle Title="Recno Method " /><MSHelp:RLTitle Title="BTreeCursor.Recno Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.Recno" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassRecnoTopic" /><MSHelp:Keyword Index="K" Term="Recno method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.Recno method" /><MSHelp:Keyword Index="F" Term="Recno" /><MSHelp:Keyword Index="F" Term="BTreeCursor.Recno" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.Recno" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Recno Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ActiveTransaction Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ActiveTransaction" /><meta name="guid" content="Methods_T_BerkeleyDB_ActiveTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ActiveTransaction" /><MSHelp:TOCTitle Title="ActiveTransaction Methods " /><MSHelp:RLTitle Title="ActiveTransaction Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.ActiveTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionMethodsTopic" /><MSHelp:Keyword Index="K" Term="ActiveTransaction class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;

height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction Methods </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DroppedMessages Property </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RepMgrStats_DroppedMessages" /><meta name="guid" content="P_BerkeleyDB_RepMgrStats_DroppedMessages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RepMgrStats.DroppedMessages" /><MSHelp:TOCTitle Title="DroppedMessages Property " /><MSHelp:RLTitle Title="RepMgrStats.DroppedMessages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RepMgrStats.DroppedMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsClassDroppedMessagesTopic" /><MSHelp:Keyword Index="K" Term="DroppedMessages property" /><MSHelp:Keyword Index="K" Term="RepMgrStats.DroppedMessages property" /><MSHelp:Keyword Index="F" Term="DroppedMessages" /><MSHelp:Keyword Index="F" Term="RepMgrStats.DroppedMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats.DroppedMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.DroppedMessages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.get_DroppedMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# msgs discarded due to excessive queue length." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats..::.DroppedMessages Property </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorCodes Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_ErrorCodes" /><meta name="guid" content="Fields_T_BerkeleyDB_ErrorCodes" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.ErrorCodes" /><MSHelp:TOCTitle Title="ErrorCodes Fields" /><MSHelp:RLTitle Title="ErrorCodes Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.ErrorCodes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesFieldsTopic" /><MSHelp:Keyword Index="K" Term="ErrorCodes class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes Fields</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (String)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Remove" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Remove" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Remove(System.String)" /><MSHelp:TOCTitle Title="Remove Method (String)" /><MSHelp:RLTitle Title="DatabaseEnvironment.Remove Method (String) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Remove(System.String)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Destroy a Berkeley DB environment if it is not currently in use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Remove Method (String)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey_5" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultipleKey_5" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database, and store that key/data pair and as many ensuing key/data pairs that can fit in a buffer the size of one database page in . The curso ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequentialWritePause Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script

type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolConfig_SequentialWritePause" /><meta name="guid" content="P_BerkeleyDB_MPoolConfig_SequentialWritePause" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolConfig.SequentialWritePause" /><MSHelp:TOCTitle Title="SequentialWritePause Property " /><MSHelp:RLTitle Title="MPoolConfig.SequentialWritePause Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolConfig.SequentialWritePause" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassSequentialWritePauseTopic" /><MSHelp:Keyword Index="K" Term="SequentialWritePause property" /><MSHelp:Keyword Index="K" Term="MPoolConfig.SequentialWritePause property" /><MSHelp:Keyword Index="F" Term="SequentialWritePause" /><MSHelp:Keyword Index="F" Term="MPoolConfig.SequentialWritePause" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.SequentialWritePause" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.SequentialWritePause" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.get_SequentialWritePause" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of microseconds
the thread of control should pause before scheduling further write operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple
</nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.SequentialWritePause Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultipleKey(System.Int32)" /><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method (Int32)" /><MSHelp:RLTitle Title="Cursor.MoveFirstMultipleKey Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultipleKey(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair and as many ensuing key/data pairs that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultipleKey Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Greater Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_KeyRange_Greater" /><meta name="guid" content="P_BerkeleyDB_KeyRange_Greater"

/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.KeyRange.Greater" /><MSHelp:TOCTitle Title="Greater Property " /><MSHelp:RLTitle Title="KeyRange.Greater Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.KeyRange.Greater" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyRangeClassGreaterTopic" /><MSHelp:Keyword Index="K" Term="Greater property" /><MSHelp:Keyword Index="K" Term="KeyRange.Greater property" /><MSHelp:Keyword Index="F" Term="Greater" /><MSHelp:Keyword Index="F" Term="KeyRange.Greater" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyRange.Greater" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange.Greater" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange.get_Greater" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A value between 0 and 1, the proportion of keys greater than the specified key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">KeyRange..::.Greater Property </td></tr><tr id="headerTableRow3"><td align="left">KeyRange Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RetransmissionRequestMax Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_RetransmissionRequestMax" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_RetransmissionRequestMax" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.RetransmissionRequestMax" /><MSHelp:TOCTitle Title="RetransmissionRequestMax Property " /><MSHelp:RLTitle Title="ReplicationConfig.RetransmissionRequestMax Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.RetransmissionRequestMax" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassRetransmissionRequestMaxTopic" /><MSHelp:Keyword Index="K" Term="RetransmissionRequestMax property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.RetransmissionRequestMax property" /><MSHelp:Keyword Index="F" Term="RetransmissionRequestMax" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.RetransmissionRequestMax" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.RetransmissionRequestMax" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.RetransmissionRequestMax" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_RetransmissionRequestMax" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum number of microseconds a client waits before requesting retransmission." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.RetransmissionRequestMax Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataFlags Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_MetadataFlags" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_MetadataFlags" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.MetadataFlags" /><MSHelp:TOCTitle Title="MetadataFlags Property "

/><MSHelp:RLTitle Title="RecnoStats.MetadataFlags Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.MetadataFlags" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassMetadataFlagsTopic" /><MSHelp:Keyword Index="K" Term="MetadataFlags property" /><MSHelp:Keyword Index="K" Term="RecnoStats.MetadataFlags property" /><MSHelp:Keyword Index="F" Term="MetadataFlags" /><MSHelp:Keyword Index="F" Term="RecnoStats.MetadataFlags" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.MetadataFlags" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.MetadataFlags" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_MetadataFlags" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Metadata flags." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats.<span

class="vb">.::.MetadataFlags Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DupCompare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabase_DupCompare" /><meta name="guid" content="P_BerkeleyDB_HashDatabase_DupCompare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabase.DupCompare" /><MSHelp:TOCTitle Title="DupCompare Property " /><MSHelp:RLTitle Title="HashDatabase.DupCompare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabase.DupCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassDupCompareTopic" /><MSHelp:Keyword Index="K" Term="DupCompare property" /><MSHelp:Keyword Index="K" Term="HashDatabase.DupCompare property" /><MSHelp:Keyword Index="F" Term="DupCompare" /><MSHelp:Keyword Index="F" Term="HashDatabase.DupCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.DupCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.get_DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.set_DupCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.DupCompare Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RenameDB Method (String, String, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RenameDB" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.Boolean)" /><MSHelp:TOCTitle Title="RenameDB Method (String, String, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RenameDB Method (String, String, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.RenameDB(System.String,System.String,System.Boolean)"

/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the underlying file represented by using the value supplied to , incidentally renaming all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RenameDB Method (String, String, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Home Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Home" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Home" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Home" /><MSHelp:TOCTitle Title="Home Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Home Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Home" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassHomeTopic" /><MSHelp:Keyword Index="K" Term="Home property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Home property" /><MSHelp:Keyword Index="F" Term="Home" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Home" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Home" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Home" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Home" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database environment home directory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Home Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MPoolStats" /><meta name="guid" content="T_BerkeleyDB_MPoolStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MPoolStats" /><MSHelp:TOCTitle Title="MPoolStats Class" /><MSHelp:RLTitle Title="MPoolStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MPoolStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassTopic" /><MSHelp:Keyword Index="K" Term="MPoolStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MPoolStats class" /><MSHelp:Keyword Index="K" Term="MPoolStats class, about MPoolStats class" /><MSHelp:Keyword Index="F" Term="MPoolStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about the

memory pool subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepSetClockskew Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script

type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepSetClockskew" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepSetClockskew" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepSetClockskew(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="RepSetClockskew Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepSetClockskew Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepSetClockskew(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepSetClockskewTopic" /><MSHelp:Keyword Index="K" Term="RepSetClockskew method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepSetClockskew method" /><MSHelp:Keyword Index="F" Term="RepSetClockskew" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepSetClockskew" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepSetClockskew" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepSetClockskew" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the clock skew ratio among replication group members based on the fastest and slowest measurements among the group for
use with master leases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepSetClockskew Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ParentID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_ParentID" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_ParentID"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.ParentID" /><MSHelp:TOCTitle Title="ParentID Property " /><MSHelp:RLTitle Title="ActiveTransaction.ParentID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.ParentID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassParentIDTopic" /><MSHelp:Keyword Index="K" Term="ParentID property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.ParentID property" /><MSHelp:Keyword Index="F" Term="ParentID" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.ParentID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.ParentID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.ParentID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_ParentID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The transaction ID of the parent transaction (or 0, if no parent)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction..::.ParentID Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ByteOrder Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_ByteOrder" /><meta name="guid" content="T_BerkeleyDB_ByteOrder"
/><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ByteOrder" /><MSHelp:TOCTitle
Title="ByteOrder Class" /><MSHelp:RLTitle Title="ByteOrder Class (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="T:BerkeleyDB.ByteOrder" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBByteOrderClassTopic" /><MSHelp:Keyword Index="K" Term="ByteOrder class"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.ByteOrder class" /><MSHelp:Keyword Index="K"
Term="ByteOrder class, about ByteOrder class" /><MSHelp:Keyword Index="F" Term="ByteOrder"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.ByteOrder" /><MSHelp:Attr Name="HelpPriority"
Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ByteOrder" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="A class to represent the database byte order." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">ByteOrder Class</td></tr><tr id="headerTableRow3"><td
align="left">Members <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RefreshMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_HashCursor_RefreshMultipleKey" /><meta name="guid"
content="Overload_BerkeleyDB_HashCursor_RefreshMultipleKey" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashCursor.RefreshMultipleKey" /><MSHelp:TOCTitle
Title="RefreshMultipleKey Method " /><MSHelp:RLTitle Title="HashCursor.RefreshMultipleKey Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.RefreshMultipleKey"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassRefreshMultipleKeyTopic"
/><MSHelp:Keyword Index="K" Term="RefreshMultipleKey method" /><MSHelp:Keyword Index="K"
Term="HashCursor.RefreshMultipleKey method" /><MSHelp:Keyword Index="F" Term="RefreshMultipleKey"
/><MSHelp:Keyword Index="F" Term="HashCursor.RefreshMultipleKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashCursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.RefreshMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyExistException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_KeyExistException" /><meta name="guid" content="T_BerkeleyDB_KeyExistException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.KeyExistException" /><MSHelp:TOCTitle Title="KeyExistException Class" /><MSHelp:RLTitle Title="KeyExistException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.KeyExistException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyExistExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="KeyExistException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.KeyExistException class" /><MSHelp:Keyword Index="K" Term="KeyExistException class, about KeyExistException class" /><MSHelp:Keyword Index="F" Term="KeyExistException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyExistException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyExistException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A key/data pair was inserted into the database using and the key already exists in the database, or using or and the key/data pair already exists in the database. ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyExistException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_GetBothMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.GetBothMultiple" /><MSHelp:TOCTitle Title="GetBothMultiple Method " /><MSHelp:RLTitle Title="HeapDatabase.GetBothMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.GetBothMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassGetBothMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetBothMultiple method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.GetBothMultiple method" /><MSHelp:Keyword Index="F" Term="GetBothMultiple" /><MSHelp:Keyword Index="F" Term="HeapDatabase.GetBothMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.GetBothMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignConflictException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="T_BerkeleyDB_ForeignConflictException" /><meta name="guid"
content="T_BerkeleyDB_ForeignConflictException" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.ForeignConflictException" /><MSHelp:TOCTitle Title="ForeignConflictException Class"
/><MSHelp:RLTitle Title="ForeignConflictException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="T:BerkeleyDB.ForeignConflictException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBForeignConflictExceptionClassTopic"
/><MSHelp:Keyword Index="K" Term="ForeignConflictException class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.ForeignConflictException class" /><MSHelp:Keyword Index="K"
Term="ForeignConflictException class, about ForeignConflictException class" /><MSHelp:Keyword Index="F"
Term="ForeignConflictException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ForeignConflictException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ForeignConflictException" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C#
</nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
 align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignConflictException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLogIdCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitLogIdCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitLogIdCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitLogIdCount" /><MSHelp:TOCTitle Title="InitLogIdCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitLogIdCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitLogIdCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitLogIdCountTopic" /><MSHelp:Keyword Index="K" Term="InitLogIdCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitLogIdCount property" /><MSHelp:Keyword Index="F" Term="InitLogIdCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitLogIdCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitLogIdCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitLogIdCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitLogIdCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitLogIdCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
 Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of log identifier objects allocated when the environment is created" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitLogIdCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_SequenceConfig__ctor" /><meta name="guid"
content="M_BerkeleyDB_SequenceConfig__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SequenceConfig.#ctor" /><MSHelp:TOCTitle Title="SequenceConfig Constructor "
/><MSHelp:RLTitle Title="SequenceConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SequenceConfig.#ctor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSequenceConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="SequenceConfig
class, constructor" /><MSHelp:Keyword Index="K" Term="SequenceConfig.SequenceConfig constructor"
/><MSHelp:Keyword Index="F" Term="SequenceConfig" /><MSHelp:Keyword Index="F"
Term="SequenceConfig.SequenceConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SequenceConfig.SequenceConfig" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig..ctor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockNotGrantedException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LockNotGrantedException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LockNotGrantedException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:TOCTitle Title="LockNotGrantedException Members" /><MSHelp:RLTitle Title="LockNotGrantedException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockNotGrantedExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockNotGrantedException class" /><MSHelp:Keyword Index="F" Term="LockNotGrantedException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockNotGrantedException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockNotGrantedException Members</td></tr><tr id="headerTableRow3"><td align="left">LockNotGrantedException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoBlocking Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_NoBlocking" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_NoBlocking" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.NoBlocking" /><MSHelp:TOCTitle Title="NoBlocking Field" /><MSHelp:RLTitle Title="ReplicationConfig.NoBlocking Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.NoBlocking" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassNoBlockingTopic" /><MSHelp:Keyword Index="K" Term="NoBlocking field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.NoBlocking field" /><MSHelp:Keyword Index="F" Term="NoBlocking" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.NoBlocking" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.NoBlocking" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.NoBlocking" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB method calls that would normally
block while clients are in recovery will return errors immediately (defaults to false)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.NoBlocking Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MoveFirst" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMoveFirstTopic" /><MSHelp:Keyword Index="K" Term="MoveFirst method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MoveFirst method" /><MSHelp:Keyword Index="F" Term="MoveFirst" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MoveFirst" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveFirst Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogNoBuffer Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogNoBuffer" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogNoBuffer" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogNoBuffer" /><MSHelp:TOCTitle Title="LogNoBuffer Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogNoBuffer Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogNoBuffer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogNoBufferTopic" /><MSHelp:Keyword Index="K" Term="LogNoBuffer property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogNoBuffer property" /><MSHelp:Keyword Index="F" Term="LogNoBuffer" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogNoBuffer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogNoBuffer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogNoBuffer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogNoBuffer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogNoBuffer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, system buffering is turned off for Berkeley DB log files to avoid double caching." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogNoBuffer Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ClockskewSlow Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_ClockskewSlow" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_ClockskewSlow" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.ClockskewSlow" /><MSHelp:TOCTitle Title="ClockskewSlow Property " /><MSHelp:RLTitle Title="ReplicationConfig.ClockskewSlow Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.ClockskewSlow" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassClockskewSlowTopic" /><MSHelp:Keyword Index="K" Term="ClockskewSlow property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.ClockskewSlow property" /><MSHelp:Keyword Index="F" Term="ClockskewSlow" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.ClockskewSlow" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.ClockskewSlow" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.ClockskewSlow" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_ClockskewSlow" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The value of the slowest clock in the group of sites." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.ClockskewSlow Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_RefreshMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_RefreshMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:TOCTitle Title="RefreshMultiple Method " /><MSHelp:RLTitle Title="Cursor.RefreshMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassRefreshMultipleTopic" /><MSHelp:Keyword Index="K" Term="RefreshMultiple method" /><MSHelp:Keyword Index="K" Term="Cursor.RefreshMultiple method" /><MSHelp:Keyword Index="F" Term="RefreshMultiple" /><MSHelp:Keyword Index="F" Term="Cursor.RefreshMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSizeGBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapDatabaseConfig_MaxSizeGBytes" /><meta name="guid" content="P_BerkeleyDB_HeapDatabaseConfig_MaxSizeGBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapDatabaseConfig.MaxSizeGBytes" /><MSHelp:TOCTitle Title="MaxSizeGBytes Property " /><MSHelp:RLTitle Title="HeapDatabaseConfig.MaxSizeGBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapDatabaseConfig.MaxSizeGBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigClassMaxSizeGBytesTopic" /><MSHelp:Keyword Index="K" Term="MaxSizeGBytes property" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig.MaxSizeGBytes property" /><MSHelp:Keyword Index="F" Term="MaxSizeGBytes" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig.MaxSizeGBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabaseConfig.MaxSizeGBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig.MaxSizeGBytes" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.HeapDatabaseConfig.get_MaxSizeGBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The gigabytes component of the maximum on-disk database file size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig..::.MaxSizeGBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexAlignment Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MutexAlignment" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MutexAlignment" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MutexAlignment" /><MSHelp:TOCTitle Title="MutexAlignment Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MutexAlignment Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MutexAlignment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMutexAlignmentTopic" /><MSHelp:Keyword Index="K" Term="MutexAlignment property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MutexAlignment property" /><MSHelp:Keyword Index="F" Term="MutexAlignment" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MutexAlignment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MutexAlignment" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MutexAlignment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MutexAlignment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MutexAlignment" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mutex alignment, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MutexAlignment Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxHashLockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MaxHashLockWait" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxHashLockWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxHashLockWait" /><MSHelp:TOCTitle Title="MaxHashLockWait Property " /><MSHelp:RLTitle Title="MPoolStats.MaxHashLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxHashLockWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxHashLockWaitTopic" /><MSHelp:Keyword Index="K" Term="MaxHashLockWait property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxHashLockWait property" /><MSHelp:Keyword Index="F" Term="MaxHashLockWait" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxHashLockWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxHashLockWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxHashLockWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxHashLockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max hash lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxHashLockWait Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TASSpins Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_TASSpins" /><meta name="guid" content="P_BerkeleyDB_MutexStats_TASSpins" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.TASSpins" /><MSHelp:TOCTitle Title="TASSpins Property " /><MSHelp:RLTitle Title="MutexStats.TASSpins Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.TASSpins" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassTASSpinsTopic" /><MSHelp:Keyword Index="K" Term="TASSpins property" /><MSHelp:Keyword Index="K" Term="MutexStats.TASSpins property" /><MSHelp:Keyword Index="F" Term="TASSpins" /><MSHelp:Keyword Index="F" Term="MutexStats.TASSpins" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.TASSpins" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.TASSpins" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_TASSpins" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutex test-and-set spins" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.TASSpins Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GlobalID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_PreparedTransaction_GlobalID" /><meta name="guid" content="P_BerkeleyDB_PreparedTransaction_GlobalID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.PreparedTransaction.GlobalID" /><MSHelp:TOCTitle Title="GlobalID Property " /><MSHelp:RLTitle Title="PreparedTransaction.GlobalID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.PreparedTransaction.GlobalID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPreparedTransactionClassGlobalIDTopic" /><MSHelp:Keyword Index="K" Term="GlobalID property" /><MSHelp:Keyword Index="K" Term="PreparedTransaction.GlobalID property" /><MSHelp:Keyword Index="F" Term="GlobalID" /><MSHelp:Keyword Index="F" Term="PreparedTransaction.GlobalID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.PreparedTransaction.GlobalID"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.PreparedTransaction.GlobalID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.PreparedTransaction.get_GlobalID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The global transaction ID for the transaction. The global transaction ID is the one specified when the transaction was prepared. The application is responsible for ensuring uniqueness among global ..." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PreparedTransaction<span
class="languageSpecificText">..::.GlobalID Property </td></tr><tr id="headerTableRow3"><td align="left">PreparedTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorPrefix Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_ErrorPrefix" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_ErrorPrefix" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.ErrorPrefix" /><MSHelp:TOCTitle Title="ErrorPrefix Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.ErrorPrefix Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.ErrorPrefix" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassErrorPrefixTopic" /><MSHelp:Keyword Index="K" Term="ErrorPrefix field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.ErrorPrefix field" /><MSHelp:Keyword Index="F" Term="ErrorPrefix" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.ErrorPrefix" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.ErrorPrefix" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.ErrorPrefix" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The prefix string that appears before error messages issued by Berkeley DB." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.ErrorPrefix Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Levels Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_Levels" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_Levels" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.Levels" /><MSHelp:TOCTitle Title="Levels Property " /><MSHelp:RLTitle Title="BTreeStats.Levels Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.Levels" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassLevelsTopic" /><MSHelp:Keyword Index="K" Term="Levels property" /><MSHelp:Keyword Index="K" Term="BTreeStats.Levels property" /><MSHelp:Keyword Index="F" Term="Levels" /><MSHelp:Keyword Index="F" Term="BTreeStats.Levels" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.Levels" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.Levels" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_Levels" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Tree levels." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeStats.<span
class="vb">.::.Levels Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeStats.htm">BTreeStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Partial Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEntry_Partial" /><meta name="guid"

content="P_BerkeleyDB_DatabaseEntry_Partial" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEntry.Partial" /><MSHelp:TOCTitle Title="Partial Property " /><MSHelp:RLTitle Title="DatabaseEntry.Partial Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEntry.Partial" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassPartialTopic" /><MSHelp:Keyword Index="K" Term="Partial property" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.Partial property" /><MSHelp:Keyword Index="F" Term="Partial" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.Partial" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry.Partial" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.Partial" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.get_Partial" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.set_Partial" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the DatabaseEntry is partial record." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry..::.Partial Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockConflictsWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockConflictsWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockConflictsWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockConflictsWait" /><MSHelp:TOCTitle Title="LockConflictsWait Property " /><MSHelp:RLTitle Title="LockStats.LockConflictsWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockConflictsWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockConflictsWaitTopic" /><MSHelp:Keyword Index="K" Term="LockConflictsWait property" /><MSHelp:Keyword Index="K" Term="LockStats.LockConflictsWait property" /><MSHelp:Keyword Index="F" Term="LockConflictsWait" /><MSHelp:Keyword Index="F" Term="LockStats.LockConflictsWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockConflictsWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockConflictsWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockConflictsWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Lock conflicts w/ subsequent wait" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockConflictsWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_Cursor" /><meta name="guid" content="Methods_T_BerkeleyDB_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.Cursor" /><MSHelp:TOCTitle Title="Cursor Methods " /><MSHelp:RLTitle Title="Cursor Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="Cursor class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"

/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor Methods </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Move" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Move(System.UInt32)" /><MSHelp:TOCTitle Title="Move Method (UInt32)" /><MSHelp:RLTitle Title="BTreeCursor.Move Method (UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Move(System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Move Method (UInt32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SequenceConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_SequenceConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SequenceConfig" /><MSHelp:TOCTitle Title="SequenceConfig Methods " /><MSHelp:RLTitle Title="SequenceConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SequenceConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="SequenceConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InMemory Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"

/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LogConfig_InMemory" /><meta name="guid" content="F_BerkeleyDB_LogConfig_InMemory" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LogConfig.InMemory" /><MSHelp:TOCTitle Title="InMemory Field" /><MSHelp:RLTitle Title="LogConfig.InMemory Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LogConfig.InMemory" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassInMemoryTopic" /><MSHelp:Keyword Index="K" Term="InMemory field" /><MSHelp:Keyword Index="K" Term="LogConfig.InMemory field" /><MSHelp:Keyword Index="F" Term="InMemory" /><MSHelp:Keyword Index="F" Term="LogConfig.InMemory" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.InMemory" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.InMemory" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, maintain transaction logs in memory rather than on disk." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.InMemory Field</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_RUNRECOVERY Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_RUNRECOVERY" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_RUNRECOVERY" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_RUNRECOVERY" /><MSHelp:TOCTitle Title="DB_RUNRECOVERY Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_RUNRECOVERY Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_RUNRECOVERY" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_RUNRECOVERYTopic" /><MSHelp:Keyword Index="K" Term="DB_RUNRECOVERY field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_RUNRECOVERY field" /><MSHelp:Keyword Index="F" Term="DB_RUNRECOVERY" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_RUNRECOVERY" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_RUNRECOVERY" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_RUNRECOVERY" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Panic return." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_RUNRECOVERY Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DroppedConnections Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RepMgrStats_DroppedConnections" /><meta name="guid" content="P_BerkeleyDB_RepMgrStats_DroppedConnections" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RepMgrStats.DroppedConnections" /><MSHelp:TOCTitle Title="DroppedConnections Property " /><MSHelp:RLTitle Title="RepMgrStats.DroppedConnections Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RepMgrStats.DroppedConnections" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsClassDroppedConnectionsTopic" /><MSHelp:Keyword Index="K" Term="DroppedConnections property" /><MSHelp:Keyword Index="K" Term="RepMgrStats.DroppedConnections property" /><MSHelp:Keyword Index="F" Term="DroppedConnections" /><MSHelp:Keyword Index="F" Term="RepMgrStats.DroppedConnections" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats.DroppedConnections" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.DroppedConnections" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.get_DroppedConnections" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Existing connections dropped." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"

value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats..::.DroppedConnections Property </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, BTreeDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Open(System.String,BerkeleyDB.BTreeDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, BTreeDatabaseConfig)" /><MSHelp:RLTitle Title="BTreeDatabase.Open Method (String, BTreeDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Open(System.String,BerkeleyDB.BTreeDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new BTreeDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Open Method (String, BTreeDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeafPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_LeafPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_LeafPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.LeafPagesFreeBytes" /><MSHelp:TOCTitle Title="LeafPagesFreeBytes Property " /><MSHelp:RLTitle Title="BTreeStats.LeafPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.LeafPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassLeafPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="LeafPagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="BTreeStats.LeafPagesFreeBytes

property" /><MSHelp:Keyword Index="F" Term="LeafPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BTreeStats.LeafPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.LeafPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.LeafPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_LeafPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in leaf pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.LeafPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (String, DatabaseEnvironment)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Remove_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Remove_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Remove(System.String,BerkeleyDB.DatabaseEnvironment)" /><MSHelp:TOCTitle Title="Remove Method (String, DatabaseEnvironment)" /><MSHelp:RLTitle Title="BaseDatabase.Remove Method (String, DatabaseEnvironment) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Remove(System.String,BerkeleyDB.DatabaseEnvironment)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the underlying file represented by , incidentally removing all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Remove Method (String, DatabaseEnvironment)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageNotFoundException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_PageNotFoundException" /><meta name="guid" content="Methods_T_BerkeleyDB_PageNotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.PageNotFoundException" /><MSHelp:TOCTitle Title="PageNotFoundException Methods " /><MSHelp:RLTitle Title="PageNotFoundException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.PageNotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPageNotFoundExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="PageNotFoundException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PageNotFoundException Methods </td></tr><tr id="headerTableRow3"><td align="left">PageNotFoundException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Close" /><meta name="guid" content="Overload_BerkeleyDB_Database_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="Database.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="Database.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="Database.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Elections Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_Elections" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_Elections" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.Elections" /><MSHelp:TOCTitle Title="Elections Property " /><MSHelp:RLTitle Title="ReplicationStats.Elections Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.Elections" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionsTopic" /><MSHelp:Keyword Index="K" Term="Elections property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.Elections property" /><MSHelp:Keyword Index="F" Term="Elections" /><MSHelp:Keyword Index="F" Term="ReplicationStats.Elections" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.Elections" /><MSHelp:Attr Name="APIType"

Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.Elections" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_Elections" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of elections held." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.Elections Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ReplicationStats.htm">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryHashDatabase Class</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="T_BerkeleyDB_SecondaryHashDatabase" /><meta name="guid"
content="T_BerkeleyDB_SecondaryHashDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:TOCTitle Title="SecondaryHashDatabase Class"
/><MSHelp:RLTitle Title="SecondaryHashDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryHashDatabaseClassTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryHashDatabase class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryHashDatabase
class" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase class, about SecondaryHashDatabase
class" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A class representing a SecondaryHashDatabase. The Hash format is an extensible,
dynamic hashing scheme." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreeThreaded Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_FreeThreaded" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_FreeThreaded" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.FreeThreaded" /><MSHelp:TOCTitle Title="FreeThreaded Property " /><MSHelp:RLTitle Title="BaseDatabase.FreeThreaded Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.FreeThreaded" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassFreeThreadedTopic" /><MSHelp:Keyword Index="K" Term="FreeThreaded property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.FreeThreaded property" /><MSHelp:Keyword Index="F" Term="FreeThreaded" /><MSHelp:Keyword Index="F" Term="BaseDatabase.FreeThreaded" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.FreeThreaded" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.FreeThreaded" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_FreeThreaded" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the object

is free-threaded;
 that is, concurrently usable by multiple threads in the address space." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.FreeThreaded Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashCursor Properties </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HashCursor" /><meta name="guid" content="Properties_T_BerkeleyDB_HashCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HashCursor" /><MSHelp:TOCTitle Title="HashCursor Properties " /><MSHelp:RLTitle Title="HashCursor Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HashCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorPropertiesTopic" /><MSHelp:Keyword Index="K" Term="HashCursor class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">HashCursor Properties </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HashStats" /><meta name="guid" content="Properties_T_BerkeleyDB_HashStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HashStats" /><MSHelp:TOCTitle Title="HashStats Properties " /><MSHelp:RLTitle Title="HashStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HashStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsPropertiesTopic" /><MSHelp:Keyword
Index="K" Term="HashStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;

width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats Properties </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Compact" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Compact" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Compact" /><MSHelp:TOCTitle Title="Compact Method " /><MSHelp:RLTitle Title="RecnoDatabase.Compact Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Compact" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassCompactTopic" /><MSHelp:Keyword Index="K" Term="Compact method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Compact method" /><MSHelp:Keyword Index="F" Term="Compact" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Compact" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Compact Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RemoveDB Method (String, Boolean, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="RemoveDB Method (String, Boolean, Transaction)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RemoveDB Method (String, Boolean, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the underlying file represented by , incidentally removing all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RemoveDB Method (String, Boolean, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Levels Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_CompactData_Levels" /><meta name="guid"
content="P_BerkeleyDB_CompactData_Levels" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.CompactData.Levels" /><MSHelp:TOCTitle Title="Levels Property " /><MSHelp:RLTitle
Title="CompactData.Levels Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.CompactData.Levels" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCompactDataClassLevelsTopic" /><MSHelp:Keyword Index="K" Term="Levels property"
/><MSHelp:Keyword Index="K" Term="CompactData.Levels property" /><MSHelp:Keyword Index="F"
Term="Levels" /><MSHelp:Keyword Index="F" Term="CompactData.Levels" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.CompactData.Levels"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.Levels"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.get_Levels" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The number of levels removed from the Btree or Recno database during the compaction
phase." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData..::.Levels Property </td></tr><tr id="headerTableRow3"><td align="left">CompactData Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_TransactionStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_TransactionStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.TransactionStats" /><MSHelp:TOCTitle Title="TransactionStats Members" /><MSHelp:RLTitle Title="TransactionStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.TransactionStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="TransactionStats class" /><MSHelp:Keyword Index="K" Term="TransactionStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.TransactionStats class" /><MSHelp:Keyword Index="F" Term="TransactionStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"

title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">TransactionStats Members</td></tr><tr
id="headerTableRow3"><td align="left">TransactionStats
Class Methods <a
href="#propertyTableToggle" onclick="OpenSection(propertyTableToggle)">Properties <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Stats_1" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Stats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Stats Method (Transaction)" /><MSHelp:RLTitle Title="HeapDatabase.Stats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Stats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoBuffer Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoBuffer" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoBuffer" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.NoBuffer" /><MSHelp:TOCTitle Title="NoBuffer Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.NoBuffer Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.NoBuffer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassNoBufferTopic" /><MSHelp:Keyword Index="K" Term="NoBuffer field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.NoBuffer field" /><MSHelp:Keyword Index="F" Term="NoBuffer" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.NoBuffer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.NoBuffer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.NoBuffer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, turn off system buffering of Berkeley DB database files to avoid double caching." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.NoBuffer Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Delete_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Delete_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Delete(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Delete Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="BaseDatabase.Delete Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Delete(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove key/data pairs from the database. If is DatabaseEntry, the key/data pair associated with is discarded from the database. In the presence of duplicate key values, all records associated wi ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">BaseDatabase..::.Delete Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Snapshot Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_Snapshot" /><meta name="guid" content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_Snapshot" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.Snapshot" /><MSHelp:TOCTitle Title="Snapshot Field" /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.Snapshot Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.Snapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassSnapshotTopic" /><MSHelp:Keyword Index="K" Term="Snapshot field" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig.Snapshot field" /><MSHelp:Keyword Index="F" Term="Snapshot" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.Snapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.Snapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.Snapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, any file will be read in its entirety when is called. If false, may be read lazily." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig..::.Snapshot Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FileName Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_FileName" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_FileName" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.FileName" /><MSHelp:TOCTitle Title="FileName Property " /><MSHelp:RLTitle Title="BaseDatabase.FileName Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.FileName" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassFileNameTopic" /><MSHelp:Keyword Index="K" Term="FileName property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.FileName property" /><MSHelp:Keyword

Index="F" Term="FileName" /><MSHelp:Keyword Index="F" Term="BaseDatabase.FileName" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.FileName" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.FileName" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_FileName" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The filename of this database, if it has one." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.FileName Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerificationException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_VerificationException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_VerificationException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.VerificationException" /><MSHelp:TOCTitle Title="VerificationException Members" /><MSHelp:RLTitle Title="VerificationException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.VerificationException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerificationExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="VerificationException class" /><MSHelp:Keyword Index="K" Term="VerificationException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.VerificationException class" /><MSHelp:Keyword Index="F" Term="VerificationException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerificationException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerificationException Members</td></tr><tr id="headerTableRow3"><td align="left">VerificationException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentGenerationNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_CurrentGenerationNumber" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_CurrentGenerationNumber"

/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.CurrentGenerationNumber" /><MSHelp:TOCTitle Title="CurrentGenerationNumber Property " /><MSHelp:RLTitle Title="ReplicationStats.CurrentGenerationNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.CurrentGenerationNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassCurrentGenerationNumberTopic" /><MSHelp:Keyword Index="K" Term="CurrentGenerationNumber property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.CurrentGenerationNumber property" /><MSHelp:Keyword Index="F" Term="CurrentGenerationNumber" /><MSHelp:Keyword Index="F" Term="ReplicationStats.CurrentGenerationNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.CurrentGenerationNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.CurrentGenerationNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_CurrentGenerationNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current generation number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
 style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
    <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
 id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.CurrentGenerationNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorCodes Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ErrorCodes" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ErrorCodes" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ErrorCodes" /><MSHelp:TOCTitle Title="ErrorCodes Members" /><MSHelp:RLTitle Title="ErrorCodes Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ErrorCodes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesMembersTopic" /><MSHelp:Keyword Index="K" Term="ErrorCodes class" /><MSHelp:Keyword Index="K" Term="ErrorCodes class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ErrorCodes class" /><MSHelp:Keyword Index="F" Term="ErrorCodes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes Members</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class Constructors Methods
  Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="T_BerkeleyDB_HeapDatabase" /><meta name="guid"
content="T_BerkeleyDB_HeapDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.HeapDatabase" /><MSHelp:TOCTitle Title="HeapDatabase Class" /><MSHelp:RLTitle
Title="HeapDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HeapDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassTopic" /><MSHelp:Keyword
Index="K" Term="HeapDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapDatabase
class" /><MSHelp:Keyword
Index="K" Term="HeapDatabase class, about HeapDatabase class" /><MSHelp:Keyword Index="F"
Term="HeapDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase" /><MSHelp:Attr
Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a
HeapDatabase." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase Class</td></tr><tr id="headerTableRow3"><td
align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Exists" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Exists(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Exists Method (DatabaseEntry)" /><MSHelp:RLTitle Title="BaseDatabase.Exists Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Exists(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Check whether appears in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Exists Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackingDatabase Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SequenceConfig_BackingDatabase" /><meta name="guid" content="F_BerkeleyDB_SequenceConfig_BackingDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SequenceConfig.BackingDatabase" /><MSHelp:TOCTitle Title="BackingDatabase Field" /><MSHelp:RLTitle Title="SequenceConfig.BackingDatabase Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SequenceConfig.BackingDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassBackingDatabaseTopic" /><MSHelp:Keyword Index="K" Term="BackingDatabase field" /><MSHelp:Keyword Index="K" Term="SequenceConfig.BackingDatabase field" /><MSHelp:Keyword Index="F" Term="BackingDatabase" /><MSHelp:Keyword Index="F" Term="SequenceConfig.BackingDatabase"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.BackingDatabase" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.BackingDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An open database which holds the persistent data for the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.BackingDatabase
Field</td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="BaseDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesInCache Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesInCache" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesInCache" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesInCache" /><MSHelp:TOCTitle Title="PagesInCache Property " /><MSHelp:RLTitle Title="MPoolStats.PagesInCache Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PagesInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesInCacheTopic" /><MSHelp:Keyword Index="K" Term="PagesInCache property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PagesInCache property" /><MSHelp:Keyword Index="F" Term="PagesInCache" /><MSHelp:Keyword Index="F" Term="MPoolStats.PagesInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PagesInCache" /><MSHelp:Attr Name="APIType" Value="Managed"

/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PagesInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PagesInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages found in the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PagesInCache Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Overwrite Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Overwrite" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Overwrite" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Overwrite" /><MSHelp:TOCTitle Title="Overwrite Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Overwrite Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Overwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassOverwriteTopic" /><MSHelp:Keyword Index="K" Term="Overwrite property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Overwrite property" /><MSHelp:Keyword Index="F" Term="Overwrite" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Overwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Overwrite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Overwrite" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Overwrite" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_Overwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, overwrite files stored in encrypted formats before deleting them." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label

id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Overwrite Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreeThreaded Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_FreeThreaded" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_FreeThreaded" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.FreeThreaded" /><MSHelp:TOCTitle Title="FreeThreaded Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.FreeThreaded Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.FreeThreaded" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassFreeThreadedTopic" /><MSHelp:Keyword Index="K" Term="FreeThreaded field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.FreeThreaded field" /><MSHelp:Keyword Index="F" Term="FreeThreaded" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.FreeThreaded" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.FreeThreaded" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.FreeThreaded" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"

Value="If true, the created object will be free-threaded; that is, concurrently usable by multiple threads in the address space." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.FreeThreaded Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_FastStats_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_FastStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.FastStats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.FastStats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Sequence_Remove" /><meta name="guid" content="Overload_BerkeleyDB_Sequence_Remove" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Sequence.Remove" /><MSHelp:TOCTitle Title="Remove Method " /><MSHelp:RLTitle Title="Sequence.Remove Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Sequence.Remove" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassRemoveTopic" /><MSHelp:Keyword Index="K" Term="Remove method" /><MSHelp:Keyword Index="K" Term="Sequence.Remove method" /><MSHelp:Keyword Index="F" Term="Remove" /><MSHelp:Keyword Index="F" Term="Sequence.Remove" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All
</nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Remove Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Sequence.htm">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nHashBuckets Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_nHashBuckets" /><meta name="guid" content="P_BerkeleyDB_HashStats_nHashBuckets" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.nHashBuckets" /><MSHelp:TOCTitle Title="nHashBuckets Property " /><MSHelp:RLTitle Title="HashStats.nHashBuckets Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.nHashBuckets" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassnHashBucketsTopic" /><MSHelp:Keyword Index="K" Term="nHashBuckets property" /><MSHelp:Keyword Index="K" Term="HashStats.nHashBuckets property" /><MSHelp:Keyword
Index="F" Term="nHashBuckets" /><MSHelp:Keyword Index="F" Term="HashStats.nHashBuckets" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.nHashBuckets" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.nHashBuckets" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_nHashBuckets" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of hash buckets." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.nHashBuckets Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_Truncate" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.Truncate" /><MSHelp:TOCTitle Title="Truncate Field" /><MSHelp:RLTitle Title="DatabaseConfig.Truncate Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.Truncate field" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.Truncate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Physically truncate the underlying file, discarding all previous databases it might have held." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.Truncate Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockDeadlocks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockDeadlocks" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockDeadlocks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockDeadlocks" /><MSHelp:TOCTitle Title="LockDeadlocks

Property " /><MSHelp:RLTitle Title="LockStats.LockDeadlocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockDeadlocks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockDeadlocksTopic" /><MSHelp:Keyword Index="K" Term="LockDeadlocks property" /><MSHelp:Keyword Index="K" Term="LockStats.LockDeadlocks property" /><MSHelp:Keyword Index="F" Term="LockDeadlocks" /><MSHelp:Keyword Index="F" Term="LockStats.LockDeadlocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockDeadlocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockDeadlocks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockDeadlocks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lock deadlocks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">LockStats..::.LockDeadlocks Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="RecnoDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RecnoDatabase<span
class="cs">..::<span
class="nu">.Open Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoDatabase.htm">RecnoDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_Cursor_MoveNextUnique"
/><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUnique" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:TOCTitle
Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="Cursor.MoveNextUnique Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique is identical to . Otherwise, move the
cursor to the next non-duplicate key in the database, and store
that key and associated datum in . MoveNe ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Cursor<span
class="cs">..::<span

class="nu">.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td
align="left">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>DoChecksum Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_BaseDatabase_DoChecksum" /><meta name="guid"
content="P_BerkeleyDB_BaseDatabase_DoChecksum"
 /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.DoChecksum"
/><MSHelp:TOCTitle Title="DoChecksum Property " /><MSHelp:RLTitle Title="BaseDatabase.DoChecksum
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.DoChecksum"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassDoChecksumTopic"
/><MSHelp:Keyword Index="K" Term="DoChecksum property" /><MSHelp:Keyword Index="K"
Term="BaseDatabase.DoChecksum property" /><MSHelp:Keyword Index="F" Term="DoChecksum"
/><MSHelp:Keyword Index="F" Term="BaseDatabase.DoChecksum" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseDatabase.DoChecksum" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.DoChecksum" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_DoChecksum" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
 Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, do checksum verification of pages read into the cache from the backing filestore."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
 /><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.DoChecksum Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabaseConfig_Length" /><meta name="guid" content="P_BerkeleyDB_QueueDatabaseConfig_Length" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueDatabaseConfig.Length" /><MSHelp:TOCTitle Title="Length Property " /><MSHelp:RLTitle Title="QueueDatabaseConfig.Length Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabaseConfig.Length" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassLengthTopic" /><MSHelp:Keyword Index="K" Term="Length property" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig.Length property" /><MSHelp:Keyword Index="F" Term="Length" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig.Length" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig.Length" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr

Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.get_Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.set_Length" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify the length of records in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transaction
Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_Transaction" /><meta name="guid" content="T_BerkeleyDB_Transaction"
/><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Transaction" /><MSHelp:TOCTitle
Title="Transaction Class" /><MSHelp:RLTitle Title="Transaction Class (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="T:BerkeleyDB.Transaction" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionClassTopic" /><MSHelp:Keyword Index="K" Term="Transaction class"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.Transaction
class" /><MSHelp:Keyword Index="K" Term="Transaction class, about Transaction class" /><MSHelp:Keyword
Index="F" Term="Transaction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction"
/><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Transaction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing Berkeley DB
transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NextLSN Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_NextLSN" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_NextLSN" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.NextLSN" /><MSHelp:TOCTitle Title="NextLSN Property " /><MSHelp:RLTitle Title="ReplicationStats.NextLSN Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.NextLSN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassNextLSNTopic" /><MSHelp:Keyword Index="K" Term="NextLSN property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.NextLSN property" /><MSHelp:Keyword Index="F" Term="NextLSN" /><MSHelp:Keyword Index="F" Term="ReplicationStats.NextLSN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.NextLSN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.NextLSN" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_NextLSN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Next LSN to use or expect." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.NextLSN Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepPriority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepPriority"
/><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepPriority" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepPriority" /><MSHelp:TOCTitle
Title="RepPriority Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepPriority
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.RepPriority" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepPriorityTopic" /><MSHelp:Keyword Index="K"
Term="RepPriority property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepPriority property"
/><MSHelp:Keyword Index="F" Term="RepPriority" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepPriority" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepPriority" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepPriority" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_RepPriority" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.set_RepPriority" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database
environment's priority in replication group elections. A special value of 0 indicates that this environment cannot be a
replication group master. If not configured, then a default value ..." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.RepPriority Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeStats
Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BTreeStats" /><meta name="guid"
content="T_BerkeleyDB_BTreeStats" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.BTreeStats" /><MSHelp:TOCTitle Title="BTreeStats Class" /><MSHelp:RLTitle
Title="BTreeStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BTreeStats"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassTopic" /><MSHelp:Keyword Index="K"
Term="BTreeStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeStats class"
/><MSHelp:Keyword Index="K" Term="BTreeStats class, about BTreeStats class" /><MSHelp:Keyword
Index="F" Term="BTreeStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats" /><MSHelp:Attr
Name="HelpPriority" Value="2" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Statistical information about a BTreeDatabase" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_PrintFastStats" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="BaseDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:Attr Name="APIType" Value="Managed"

/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxCacheSize Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_MPoolConfig_MaxCacheSize" /><meta name="guid" content="F_BerkeleyDB_MPoolConfig_MaxCacheSize" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.MPoolConfig.MaxCacheSize" /><MSHelp:TOCTitle Title="MaxCacheSize Field" /><MSHelp:RLTitle Title="MPoolConfig.MaxCacheSize Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.MPoolConfig.MaxCacheSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassMaxCacheSizeTopic" /><MSHelp:Keyword Index="K" Term="MaxCacheSize field" /><MSHelp:Keyword Index="K" Term="MPoolConfig.MaxCacheSize field" /><MSHelp:Keyword Index="F" Term="MaxCacheSize" /><MSHelp:Keyword Index="F" Term="MPoolConfig.MaxCacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.MaxCacheSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.MaxCacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum cache size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.MaxCacheSize Field</td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Stats" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="HashDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Stats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassStatsTopic" /><MSHelp:Keyword Index="K" Term="Stats method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Stats method" /><MSHelp:Keyword Index="F" Term="Stats" /><MSHelp:Keyword Index="F" Term="HashDatabase.Stats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method (MultipleKeyDatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Put_2" /><meta name="guid" content="M_BerkeleyDB_Database_Put_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Database.Put(BerkeleyDB.MultipleKeyDatabaseEntry)" /><MSHelp:TOCTitle Title="Put Method (MultipleKeyDatabaseEntry)" /><MSHelp:RLTitle Title="Database.Put Method (MultipleKeyDatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Put(BerkeleyDB.MultipleKeyDatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store multiple data items using keys from the buffer to which the key parameter refers and data values from the buffer to which the data parameter refers. A successful bulk operation is logically ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Put Method (MultipleKeyDatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockSystemCfg Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_LockSystemCfg" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_LockSystemCfg" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.LockSystemCfg" /><MSHelp:TOCTitle Title="LockSystemCfg Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.LockSystemCfg Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.LockSystemCfg" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassLockSystemCfgTopic" /><MSHelp:Keyword Index="K" Term="LockSystemCfg field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.LockSystemCfg field" /><MSHelp:Keyword Index="F" Term="LockSystemCfg" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.LockSystemCfg" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.LockSystemCfg" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.LockSystemCfg" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="Abstract" Value="Configuration for the locking subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.LockSystemCfg Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BTreeDatabase_Cursor_3" /><meta name="guid"
content="M_BerkeleyDB_BTreeDatabase_Cursor_3" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeDatabase.Cursor(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor
Method (Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.Cursor Method (Transaction) (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Cursor(BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected
database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Cursor Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Open" /><meta name="guid" content="Overload_BerkeleyDB_Database_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="Database.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="Database.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="Database.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (DatabaseEntry, Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_Cursor_MoveMultipleKey_1" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveMultipleKey_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.Lockin
gInfo)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (DatabaseEntry, Boolean, LockingInfo)"
/><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (DatabaseEntry, Boolean, LockingInfo)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.Lockin
gInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Set the cursor to refer to , and store that key and as many ensuing key/data pairs that can
fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span

class="languageSpecificText">..::.MoveMultipleKey Method (DatabaseEntry, Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td
align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.Open(System.String,BerkeleyDB.SecondaryDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryDatabase.Open Method (String, SecondaryDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.Open(System.String,BerkeleyDB.SecondaryDatabaseConfig,BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryDatabase object, open the database represented by and associate the database with the primary index. The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)"

tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Open Method (String, SecondaryDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryQueueDatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_SecondaryQueueDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryQueueDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:TOCTitle Title="SecondaryQueueDatabaseConfig Constructor " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryQueueDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig.SecondaryQueueDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig.SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig.SecondaryQueueDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryQueueDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_SecondaryQueueDatabaseConfig.htm">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUnique_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUnique_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveNextUnique Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MoveNextUnique Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum in . MoveNe ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img id="devlangsDropdownImage"

src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUnique Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockResolution Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_DeadlockResolution" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_DeadlockResolution" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.DeadlockResolution" /><MSHelp:TOCTitle Title="DeadlockResolution Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.DeadlockResolution Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.DeadlockResolution" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassDeadlockResolutionTopic" /><MSHelp:Keyword Index="K" Term="DeadlockResolution property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.DeadlockResolution property" /><MSHelp:Keyword Index="F" Term="DeadlockResolution" /><MSHelp:Keyword Index="F"

Term="DatabaseEnvironment.DeadlockResolution" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.DeadlockResolution" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.DeadlockResolution" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_DeadlockResolution" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_DeadlockResolution" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The deadlock detector configuration, specifying what lock request(s) should be rejected. As transactions acquire locks on behalf of a single locker ID, rejecting a lock request associated with a tr ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.DeadlockResolution Property </td></tr><tr id="headerTableRow3"><td

align="left">DatabaseEnvironment Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OldVersionException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_OldVersionException__ctor" /><meta name="guid" content="M_BerkeleyDB_OldVersionException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.OldVersionException.#ctor" /><MSHelp:TOCTitle Title="OldVersionException Constructor " /><MSHelp:RLTitle Title="OldVersionException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.OldVersionException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBOldVersionExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="OldVersionException class, constructor" /><MSHelp:Keyword Index="K" Term="OldVersionException.OldVersionException constructor" /><MSHelp:Keyword Index="F" Term="OldVersionException" /><MSHelp:Keyword Index="F" Term="OldVersionException.OldVersionException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.OldVersionException.OldVersionException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.OldVersionException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the OldVersionException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">OldVersionException Constructor </td></tr><tr id="headerTableRow3"><td align="left">OldVersionException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintMPoolSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintMPoolSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:TOCTitle Title="PrintMPoolSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintMPoolSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintMPoolSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintMPoolSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.PrintMPoolSystemStats method" /><MSHelp:Keyword Index="F" Term="PrintMPoolSystemStats" /><MSHelp:Keyword Index="F"

Term="DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintMPoolSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintMPoolSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LongestHashChainSearch Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_LongestHashChainSearch" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_LongestHashChainSearch" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.LongestHashChainSearch" /><MSHelp:TOCTitle Title="LongestHashChainSearch Property " /><MSHelp:RLTitle Title="MPoolStats.LongestHashChainSearch Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.LongestHashChainSearch" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassLongestHashChainSearchTopic" /><MSHelp:Keyword Index="K" Term="LongestHashChainSearch property" /><MSHelp:Keyword Index="K" Term="MPoolStats.LongestHashChainSearch property" /><MSHelp:Keyword Index="F" Term="LongestHashChainSearch" /><MSHelp:Keyword Index="F" Term="MPoolStats.LongestHashChainSearch" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.LongestHashChainSearch" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.LongestHashChainSearch" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_LongestHashChainSearch" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Longest hash chain searched." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.LongestHashChainSearch Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_CompactConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_CompactConfig" /><xml><MSHelp:Attr Name="AssetID"

Value="Properties.T:BerkeleyDB.CompactConfig" /><MSHelp:TOCTitle Title="CompactConfig Properties " /><MSHelp:RLTitle Title="CompactConfig
Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.CompactConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="CompactConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div

id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">CompactConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Rename Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_Rename" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_Rename" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.Rename" /><MSHelp:TOCTitle Title="Rename Method " /><MSHelp:RLTitle Title="BaseDatabase.Rename Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Rename" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassRenameTopic" /><MSHelp:Keyword Index="K" Term="Rename method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Rename method" /><MSHelp:Keyword Index="F" Term="Rename"
/><MSHelp:Keyword Index="F" Term="BaseDatabase.Rename" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Rename" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Rename Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrChannel Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrChannel" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrChannel" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrChannel(System.Int32)" /><MSHelp:TOCTitle Title="RepMgrChannel Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrChannel Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrChannel(System.Int32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrChannelTopic" /><MSHelp:Keyword Index="K" Term="RepMgrChannel method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrChannel method" /><MSHelp:Keyword Index="F" Term="RepMgrChannel" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrChannel" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrChannel" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrChannel" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create DbChannel with given eid." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrChannel Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLoggingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintLoggingSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintLoggingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:TOCTitle Title="PrintLoggingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLoggingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the logging subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLoggingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintReplicationSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_DatabaseEnvironment_PrintReplicationSystemStats" /><meta name="guid"
content="Overload_BerkeleyDB_DatabaseEnvironment_PrintReplicationSystemStats" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats"
/><MSHelp:TOCTitle Title="PrintReplicationSystemStats
Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintReplicationSystemStats Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintReplicationSystemStatsTopic"
/><MSHelp:Keyword Index="K" Term="PrintReplicationSystemStats method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.PrintReplicationSystemStats method" /><MSHelp:Keyword Index="F"
Term="PrintReplicationSystemStats" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.PrintReplicationSystemStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered
</nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this,
'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment<span
class="languageSpecificText">..<span
class="cpp">::.PrintReplicationSystemStats Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>BTreeStats Properties </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_BTreeStats" /><meta
name="guid" content="Properties_T_BerkeleyDB_BTreeStats" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.BTreeStats" /><MSHelp:TOCTitle Title="BTreeStats Properties "
/><MSHelp:RLTitle Title="BTreeStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Properties.T:BerkeleyDB.BTreeStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="BTreeStats class,
properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"

title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats
Properties </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeStats.htm">BTreeStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LastCheckpoint
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_LastCheckpoint" /><meta
name="guid" content="P_BerkeleyDB_TransactionStats_LastCheckpoint" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.TransactionStats.LastCheckpoint" /><MSHelp:TOCTitle
Title="LastCheckpoint Property " /><MSHelp:RLTitle Title="TransactionStats.LastCheckpoint Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.LastCheckpoint"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassLastCheckpointTopic"
/><MSHelp:Keyword Index="K" Term="LastCheckpoint property" /><MSHelp:Keyword Index="K"
Term="TransactionStats.LastCheckpoint property" /><MSHelp:Keyword Index="F" Term="LastCheckpoint"
/><MSHelp:Keyword Index="F" Term="TransactionStats.LastCheckpoint" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.TransactionStats.LastCheckpoint" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionStats.LastCheckpoint" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionStats.get_LastCheckpoint" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="LSN of the last checkpoint" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.LastCheckpoint Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbThreadID Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DbThreadID" /><meta name="guid" content="Methods_T_BerkeleyDB_DbThreadID" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DbThreadID" /><MSHelp:TOCTitle Title="DbThreadID Methods " /><MSHelp:RLTitle Title="DbThreadID Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DbThreadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbThreadIDMethodsTopic" /><MSHelp:Keyword Index="K" Term="DbThreadID class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID Methods </td></tr><tr id="headerTableRow3"><td align="left">DbThreadID Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupOptions

Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BackupOptions" /><meta name="guid" content="AllMembers_T_BerkeleyDB_BackupOptions" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.BackupOptions" /><MSHelp:TOCTitle Title="BackupOptions Members" /><MSHelp:RLTitle Title="BackupOptions Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BackupOptions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsMembersTopic" /><MSHelp:Keyword Index="K" Term="BackupOptions class" /><MSHelp:Keyword Index="K" Term="BackupOptions class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BackupOptions class" /><MSHelp:Keyword Index="F" Term="BackupOptions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label

id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions Members</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullLogBufferException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_FullLogBufferException" /><meta name="guid" content="T_BerkeleyDB_FullLogBufferException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.FullLogBufferException" /><MSHelp:TOCTitle Title="FullLogBufferException Class" /><MSHelp:RLTitle Title="FullLogBufferException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.FullLogBufferException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBFullLogBufferExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.FullLogBufferException class" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class, about FullLogBufferException class" /><MSHelp:Keyword Index="F"

Term="FullLogBufferException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.FullLogBufferException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.FullLogBufferException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="In-memory logs are configured and no more log buffer space is available." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">FullLogBufferException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStartMaster Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RepStartMaster" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_RepStartMaster" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:TOCTitle Title="RepStartMaster Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStartMaster Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepStartMasterTopic" /><MSHelp:Keyword Index="K" Term="RepStartMaster method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepStartMaster method" /><MSHelp:Keyword Index="F" Term="RepStartMaster" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepStartMaster" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepStartMaster" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepStartMaster Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNext_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNext_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNext Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNext Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.Cursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair in . In the presence of duplicate key val ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNext Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See

Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_QueueStats" /><meta name="guid" content="Properties_T_BerkeleyDB_QueueStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.QueueStats" /><MSHelp:TOCTitle Title="QueueStats Properties " /><MSHelp:RLTitle Title="QueueStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.QueueStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="QueueStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats Properties </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_GetBoth_2" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_GetBoth_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.GetBoth(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="BaseDatabase.GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.GetBoth(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyD

B.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database which matches and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.GetBoth Method (DatabaseEntry, DatabaseEntry, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Truncate" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method
" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Truncate" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K"
Term="Truncate method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Truncate method"
/><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabase.Truncate" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabase.Truncate" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLocks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxLocks" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxLocks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxLocks" /><MSHelp:TOCTitle Title="MaxLocks Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxLocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxLocks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxLocksTopic" /><MSHelp:Keyword Index="K"

Term="MaxLocks property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxLocks property" /><MSHelp:Keyword Index="F" Term="MaxLocks" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxLocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxLocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxLocks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxLocks" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxLocks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum number of locks supported by the Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxLocks Property

</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSnapshot Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_MaxSnapshot" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_MaxSnapshot" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.MaxSnapshot" /><MSHelp:TOCTitle Title="MaxSnapshot Property " /><MSHelp:RLTitle Title="TransactionStats.MaxSnapshot Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.MaxSnapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassMaxSnapshotTopic" /><MSHelp:Keyword Index="K" Term="MaxSnapshot property" /><MSHelp:Keyword Index="K" Term="TransactionStats.MaxSnapshot property" /><MSHelp:Keyword Index="F" Term="MaxSnapshot" /><MSHelp:Keyword Index="F" Term="TransactionStats.MaxSnapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.MaxSnapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.MaxSnapshot" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_MaxSnapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum snapshot transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.MaxSnapshot Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LocalSite Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbSite_LocalSite"
/><meta name="guid" content="P_BerkeleyDB_DbSite_LocalSite" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSite.LocalSite" /><MSHelp:TOCTitle Title="LocalSite Property " /><MSHelp:RLTitle Title="DbSite.LocalSite Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSite.LocalSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassLocalSiteTopic" /><MSHelp:Keyword Index="K" Term="LocalSite property" /><MSHelp:Keyword Index="K" Term="DbSite.LocalSite property" /><MSHelp:Keyword Index="F" Term="LocalSite" /><MSHelp:Keyword Index="F" Term="DbSite.LocalSite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.LocalSite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.LocalSite" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.DbSite.get_LocalSite" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSite.set_LocalSite" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Whether it is local site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DbSite.<span
class="vb">.::.LocalSite Property
</td></tr><tr id="headerTableRow3"><td align="left">DbSite
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Outdated Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_Outdated" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_Outdated" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.Outdated" /><MSHelp:TOCTitle Title="Outdated Property " /><MSHelp:RLTitle Title="ReplicationStats.Outdated Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.Outdated" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassOutdatedTopic" /><MSHelp:Keyword Index="K" Term="Outdated property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.Outdated property" /><MSHelp:Keyword Index="F" Term="Outdated" /><MSHelp:Keyword Index="F" Term="ReplicationStats.Outdated" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.Outdated" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.Outdated" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_Outdated" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of times we detected and returned an OUTDATED condition." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.Outdated Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveFirstMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveFirstMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:TOCTitle Title="MoveFirstMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveFirstMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveFirstMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveFirstMultiple method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveFirstMultiple method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultiple" /><MSHelp:Keyword Index="F" Term="Cursor.MoveFirstMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MAX_WRITE
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_MAX_WRITE" /><meta
name="guid" content="F_BerkeleyDB_DeadlockPolicy_MAX_WRITE" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DeadlockPolicy.MAX_WRITE" /><MSHelp:TOCTitle Title="MAX_WRITE Field"
/><MSHelp:RLTitle Title="DeadlockPolicy.MAX_WRITE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.DeadlockPolicy.MAX_WRITE" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDeadlockPolicyClassMAX_WRITETopic" /><MSHelp:Keyword Index="K"
Term="MAX_WRITE
field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.MAX_WRITE field" /><MSHelp:Keyword
Index="F" Term="MAX_WRITE" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.MAX_WRITE"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.MAX_WRITE" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.MAX_WRITE" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Reject the lock request for the locker ID with the most write locks." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DeadlockPolicy..::.MAX_WRITE Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Get_4" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Get_4" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Get Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="BaseDatabase.Get Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database. In the presence of duplicate key values, Get will return the first data item for ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BIG_ENDIAN Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ByteOrder_BIG_ENDIAN" /><meta name="guid" content="F_BerkeleyDB_ByteOrder_BIG_ENDIAN" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ByteOrder.BIG_ENDIAN" /><MSHelp:TOCTitle Title="BIG_ENDIAN Field" /><MSHelp:RLTitle Title="ByteOrder.BIG_ENDIAN Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ByteOrder.BIG_ENDIAN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBByteOrderClassBIG_ENDIANTopic" /><MSHelp:Keyword Index="K" Term="BIG_ENDIAN field" /><MSHelp:Keyword Index="K" Term="ByteOrder.BIG_ENDIAN field" /><MSHelp:Keyword Index="F" Term="BIG_ENDIAN" /><MSHelp:Keyword Index="F" Term="ByteOrder.BIG_ENDIAN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ByteOrder.BIG_ENDIAN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ByteOrder.BIG_ENDIAN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Big endian byte order" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder..::.BIG_ENDIAN Field</td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultiple_5" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultiple_5" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultiple(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database, and store that key/data pair and as many duplicate data items associated with the given key that can fit in a buffer the size of one database ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultiple Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_Compare" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_Compare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.Compare" /><MSHelp:TOCTitle Title="Compare Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Compare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.Compare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare
property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Compare property" /><MSHelp:Keyword Index="F" Term="Compare" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.Compare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.Compare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.set_Compare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree key comparison function. The comparison function is
called whenever it is necessary to compare a key specified by the application with a key currently stored in the tree." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Compare Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.Open(System.String,BerkeleyDB.SecondaryDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryDatabase.Open Method (String, SecondaryDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.Open(System.String,BerkeleyDB.SecondaryDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryDatabase object, open the database represented by and associate the database with the primary index. The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Open Method (String, SecondaryDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashBuckets Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_HashBuckets" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_HashBuckets" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.HashBuckets" /><MSHelp:TOCTitle Title="HashBuckets Property "

/><MSHelp:RLTitle Title="MPoolStats.HashBuckets Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.HashBuckets" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassHashBucketsTopic" /><MSHelp:Keyword Index="K" Term="HashBuckets property" /><MSHelp:Keyword Index="K" Term="MPoolStats.HashBuckets property" /><MSHelp:Keyword Index="F" Term="HashBuckets" /><MSHelp:Keyword Index="F" Term="MPoolStats.HashBuckets" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.HashBuckets" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.HashBuckets" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_HashBuckets" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of hash buckets." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">MPoolStats..::.HashBuckets Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_MutexSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_MutexSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.MutexSystemStats(System.Boolean)" /><MSHelp:TOCTitle Title="MutexSystemStats Method (Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.MutexSystemStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.MutexSystemStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MutexSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mutex subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MutexSystemStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MinKeysPerPage Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabaseConfig_MinKeysPerPage" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabaseConfig_MinKeysPerPage" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:TOCTitle Title="MinKeysPerPage Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.MinKeysPerPage Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassMinKeysPerPageTopic" /><MSHelp:Keyword Index="K" Term="MinKeysPerPage property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.MinKeysPerPage property" /><MSHelp:Keyword

Index="F" Term="MinKeysPerPage" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.MinKeysPerPage" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.get_MinKeysPerPage" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.set_MinKeysPerPage" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The minimum number of key/data pairs intended to be stored on any single Btree leaf
page."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryBTreeDatabaseConfig<span
class="cs">..::<span

class="nu">.MinKeysPerPage Property </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryBTreeDatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>ForceFlush Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_ForceFlush" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_ForceFlush"
 /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.ForceFlush"
/><MSHelp:TOCTitle Title="ForceFlush Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.ForceFlush
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.ForceFlush" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassForceFlushTopic" /><MSHelp:Keyword Index="K"
Term="ForceFlush property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ForceFlush property"
/><MSHelp:Keyword Index="F" Term="ForceFlush" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.ForceFlush" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.ForceFlush" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.ForceFlush" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_ForceFlush"
 /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_ForceFlush" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, flush database writes to the backing disk before returning from the write system
call, rather than flushing database writes explicitly in a separate system call, as necessary." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
 Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ForceFlush Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogSystemCfg Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_LogSystemCfg" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_LogSystemCfg" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.LogSystemCfg" /><MSHelp:TOCTitle Title="LogSystemCfg Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.LogSystemCfg Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.LogSystemCfg" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassLogSystemCfgTopic" /><MSHelp:Keyword Index="K" Term="LogSystemCfg field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.LogSystemCfg field" /><MSHelp:Keyword Index="F"

Term="LogSystemCfg" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.LogSystemCfg" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.LogSystemCfg" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.LogSystemCfg" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration for the logging subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.LogSystemCfg Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSizeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapDatabase_MaxSizeBytes" /><meta name="guid" content="P_BerkeleyDB_HeapDatabase_MaxSizeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapDatabase.MaxSizeBytes" /><MSHelp:TOCTitle Title="MaxSizeBytes Property " /><MSHelp:RLTitle Title="HeapDatabase.MaxSizeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapDatabase.MaxSizeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassMaxSizeBytesTopic" /><MSHelp:Keyword Index="K" Term="MaxSizeBytes property" /><MSHelp:Keyword Index="K" Term="HeapDatabase.MaxSizeBytes property" /><MSHelp:Keyword Index="F" Term="MaxSizeBytes" /><MSHelp:Keyword Index="F" Term="HeapDatabase.MaxSizeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.MaxSizeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.MaxSizeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.get_MaxSizeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The bytes component of the maximum on-disk database file size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HeapDatabase.<span
class="vb">.::.MaxSizeBytes Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HeapDatabase.htm">HeapDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MMapSize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta
name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_MMapSize" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_MMapSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.MMapSize" /><MSHelp:TOCTitle Title="MMapSize Property "
/><MSHelp:RLTitle Title="DatabaseEnvironment.MMapSize Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MMapSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassMMapSizeTopic" /><MSHelp:Keyword Index="K"
Term="MMapSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MMapSize property"
/><MSHelp:Keyword Index="F" Term="MMapSize" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.MMapSize" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.MMapSize" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.MMapSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_MMapSize" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.DatabaseEnvironment.set_MMapSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum file size, in bytes, for a file to be mapped into the process address space. If no value is specified, it defaults to 10MB." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::<span
class="nu">.MMapSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, BTreeDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Open(System.String,BerkeleyDB.BTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, BTreeDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.Open Method (String, BTreeDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Open(System.String,BerkeleyDB.BTreeDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new BTreeDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeDatabase.<span
class="vb">.<span
class="cpp">::.Open Method (String, BTreeDatabaseConfig,
Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeDatabase.htm">BTreeDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryDatabase" /><meta
name="guid" content="Methods_T_BerkeleyDB_SecondaryDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.SecondaryDatabase" /><MSHelp:TOCTitle Title="SecondaryDatabase Methods "
/><MSHelp:RLTitle Title="SecondaryDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Methods.T:BerkeleyDB.SecondaryDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseMethodsTopic"
/><MSHelp:Keyword Index="K" Term="SecondaryDatabase class, methods" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
 class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show
 All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
 class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See
 Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitialValue Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceConfig_InitialValue" /><meta name="guid" content="P_BerkeleyDB_SequenceConfig_InitialValue" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceConfig.InitialValue" /><MSHelp:TOCTitle Title="InitialValue Property " /><MSHelp:RLTitle Title="SequenceConfig.InitialValue Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceConfig.InitialValue" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassInitialValueTopic" /><MSHelp:Keyword Index="K" Term="InitialValue property" /><MSHelp:Keyword Index="K" Term="SequenceConfig.InitialValue property" /><MSHelp:Keyword Index="F" Term="InitialValue" /><MSHelp:Keyword Index="F" Term="SequenceConfig.InitialValue" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.InitialValue" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.InitialValue" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.get_InitialValue" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.set_InitialValue" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial value for a sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SequenceConfig<span
class="languageSpecificText">..<span
class="cpp">::.InitialValue Property </td></tr><tr
id="headerTableRow3"><td align="left">SequenceConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetEnumerator
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css"
href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BaseCursor_GetEnumerator" /><meta name="guid"
content="M_BerkeleyDB_BaseCursor_GetEnumerator" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseCursor.GetEnumerator" /><MSHelp:TOCTitle Title="GetEnumerator Method "
/><MSHelp:RLTitle Title="BaseCursor.GetEnumerator Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseCursor.GetEnumerator"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorClassGetEnumeratorTopic"
/><MSHelp:Keyword Index="K" Term="GetEnumerator method" /><MSHelp:Keyword Index="K"
Term="BaseCursor.GetEnumerator method" /><MSHelp:Keyword Index="F" Term="GetEnumerator"
/><MSHelp:Keyword Index="F" Term="BaseCursor.GetEnumerator" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseCursor.GetEnumerator" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseCursor.GetEnumerator" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Returns an

enumerator that iterates through the cursor." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">BaseCursor<span
class="languageSpecificText">..<span
class="cpp">::.GetEnumerator Method </td></tr><tr
id="headerTableRow3"><td align="left">BaseCursor Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META
NAME="save" CONTENT="history" /><title>ErrorFeedback Field</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_ErrorFeedback" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_ErrorFeedback" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.ErrorFeedback"
/><MSHelp:TOCTitle Title="ErrorFeedback Field" /><MSHelp:RLTitle
Title="DatabaseEnvironmentConfig.ErrorFeedback Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.DatabaseEnvironmentConfig.ErrorFeedback" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassErrorFeedbackTopic" /><MSHelp:Keyword Index="K"
Term="ErrorFeedback field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.ErrorFeedback
field" /><MSHelp:Keyword Index="F" Term="ErrorFeedback" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.ErrorFeedback" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.ErrorFeedback" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.ErrorFeedback" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The mechanism for reporting detailed error messages to the
application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.ErrorFeedback Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method (MultipleKeyDatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_PutNoOverwrite_2" /><meta name="guid" content="M_BerkeleyDB_Database_PutNoOverwrite_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.MultipleKeyDatabaseEntry)" /><MSHelp:TOCTitle Title="PutNoOverwrite Method (MultipleKeyDatabaseEntry)" /><MSHelp:RLTitle Title="Database.PutNoOverwrite Method (MultipleKeyDatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.PutNoOverwrite(BerkeleyDB.MultipleKeyDatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pairs in the database, only if the key does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.PutNoOverwrite Method (MultipleKeyDatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordNumbers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_RecordNumbers" /><meta name="guid" content="P_BerkeleyDB_BTreeDatabase_RecordNumbers" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.BTreeDatabase.RecordNumbers" /><MSHelp:TOCTitle Title="RecordNumbers Property " /><MSHelp:RLTitle Title="BTreeDatabase.RecordNumbers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.RecordNumbers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassRecordNumbersTopic" /><MSHelp:Keyword Index="K" Term="RecordNumbers property" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.RecordNumbers property" /><MSHelp:Keyword Index="F" Term="RecordNumbers" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.RecordNumbers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.RecordNumbers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.RecordNumbers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.get_RecordNumbers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, this object supports retrieval from the Btree using record numbers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.RecordNumbers Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxCacheSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxCacheSize" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxCacheSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxCacheSize" /><MSHelp:TOCTitle Title="MaxCacheSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxCacheSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxCacheSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxCacheSizeTopic" /><MSHelp:Keyword Index="K" Term="MaxCacheSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxCacheSize property" /><MSHelp:Keyword Index="F" Term="MaxCacheSize" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxCacheSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxCacheSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxCacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxCacheSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxCacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum cache size" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxCacheSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Lockers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_Lockers" /><meta name="guid" content="P_BerkeleyDB_LockStats_Lockers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.Lockers" /><MSHelp:TOCTitle Title="Lockers Property " /><MSHelp:RLTitle Title="LockStats.Lockers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.Lockers" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBLockStatsClassLockersTopic" /><MSHelp:Keyword Index="K" Term="Lockers property" /><MSHelp:Keyword Index="K" Term="LockStats.Lockers property" /><MSHelp:Keyword Index="F" Term="Lockers" /><MSHelp:Keyword Index="F" Term="LockStats.Lockers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.Lockers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.Lockers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_Lockers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current number of lockers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.Lockers Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_RepMgrStats" /><meta name="guid" content="Properties_T_BerkeleyDB_RepMgrStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.RepMgrStats" /><MSHelp:TOCTitle Title="RepMgrStats Properties " /><MSHelp:RLTitle Title="RepMgrStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.RepMgrStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="RepMgrStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span

id="memberOptionsDropdown" class="filter" tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats Properties </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey_6" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultipleKey_6" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,System.Int32)" /><MSHelp:Attr Name="APIType"

Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move
the cursor to the specified key/data pair of the database, and store that key/data pair and as many ensuing key/data pairs that can fit in a buffer the size of in . The cursor is positioned t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, Int32)</td></tr><tr

id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepConnectionRetry Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_RepConnectionRetry" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_RepConnectionRetry" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.RepConnectionRetry" /><MSHelp:TOCTitle
Title="RepConnectionRetry Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepConnectionRetry Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.RepConnectionRetry" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepConnectionRetryTopic" /><MSHelp:Keyword Index="K"
Term="RepConnectionRetry property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepConnectionRetry property" /><MSHelp:Keyword Index="F"
Term="RepConnectionRetry" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepConnectionRetry" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepConnectionRetry" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepConnectionRetry" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepConnectionRetry" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepConnectionRetry" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract"
Value="The amount of time the replication manager will wait before trying to re-establish a connection to another site after a communication failure. The default wait time is 30 seconds." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepConnectionRetry Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:TOCTitle

Title="SecondaryRecnoDatabaseConfig Properties " /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox"

data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryHashDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryHashDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_SecondaryHashDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,BerkeleyDB.SecondaryHashDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryHashDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryHashDatabase.Open Method (String, SecondaryHashDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,BerkeleyDB.SecondaryHashDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryHashDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;

height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Open Method (String, SecondaryHashDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextUnique_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntr

y,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUnique is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store the secondary key and primary key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor.<span

class="vb">.::.MoveNextUnique Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveFirstMultipleKey Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair and as many ensuing key/data pairs that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultipleKey Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RepMgrSite" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RepMgrSite" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RepMgrSite" /><MSHelp:TOCTitle Title="RepMgrSite Members" /><MSHelp:RLTitle Title="RepMgrSite Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RepMgrSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrSiteMembersTopic" /><MSHelp:Keyword Index="K" Term="RepMgrSite class" /><MSHelp:Keyword Index="K" Term="RepMgrSite class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RepMgrSite class" /><MSHelp:Keyword Index="F" Term="RepMgrSite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrSite" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrSite Members</td></tr><tr id="headerTableRow3"><td

align="left">RepMgrSite Class Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_HashDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_HashDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.HashDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="HashDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.HashDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_GetBoth" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.GetBoth(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="GetBoth Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="BaseDatabase.GetBoth Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.GetBoth(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database which matches and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.GetBoth Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxUnusedID Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxUnusedID" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxUnusedID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxUnusedID" /><MSHelp:TOCTitle Title="MaxUnusedID Property " /><MSHelp:RLTitle
Title="LockStats.MaxUnusedID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxUnusedID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxUnusedIDTopic" /><MSHelp:Keyword Index="K" Term="MaxUnusedID property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxUnusedID property" /><MSHelp:Keyword Index="F" Term="MaxUnusedID" /><MSHelp:Keyword Index="F" Term="LockStats.MaxUnusedID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxUnusedID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxUnusedID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxUnusedID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current maximum unused ID." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxUnusedID Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseMasterLeases Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_UseMasterLeases" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_UseMasterLeases" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.UseMasterLeases" /><MSHelp:TOCTitle Title="UseMasterLeases Field" /><MSHelp:RLTitle Title="ReplicationConfig.UseMasterLeases Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.UseMasterLeases" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassUseMasterLeasesTopic" /><MSHelp:Keyword Index="K" Term="UseMasterLeases field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.UseMasterLeases field" /><MSHelp:Keyword Index="F" Term="UseMasterLeases" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.UseMasterLeases" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.UseMasterLeases" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.UseMasterLeases" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, master leases will be used for this site (defaults to false)." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.UseMasterLeases Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseDatabase Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_BaseDatabase" /><meta name="guid" content="Properties_T_BerkeleyDB_BaseDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.BaseDatabase" /><MSHelp:TOCTitle Title="BaseDatabase Properties " /><MSHelp:RLTitle Title="BaseDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.BaseDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="BaseDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited"
value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"
for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">BaseDatabase Properties </td></tr><tr id="headerTableRow3"><td
align="left">BaseDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>PageNotFoundException Fields</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Fields_T_BerkeleyDB_PageNotFoundException" /><meta name="guid"
content="Fields_T_BerkeleyDB_PageNotFoundException"
/><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.PageNotFoundException"
/><MSHelp:TOCTitle Title="PageNotFoundException Fields" /><MSHelp:RLTitle
Title="PageNotFoundException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.PageNotFoundException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBPageNotFoundExceptionFieldsTopic" /><MSHelp:Keyword Index="K"
Term="PageNotFoundException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PageNotFoundException Fields</td></tr><tr id="headerTableRow3"><td align="left">PageNotFoundException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats

Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultiple Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultiple_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirstMultiple Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveFirstMultiple Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that key and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultiple Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultiple Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultiple Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultiple is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUniqueMultiple Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EncryptAlgorithm Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseConfig_EncryptAlgorithm" /><meta name="guid" content="P_BerkeleyDB_DatabaseConfig_EncryptAlgorithm" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseConfig.EncryptAlgorithm" /><MSHelp:TOCTitle Title="EncryptAlgorithm Property " /><MSHelp:RLTitle Title="DatabaseConfig.EncryptAlgorithm Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseConfig.EncryptAlgorithm" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassEncryptAlgorithmTopic" /><MSHelp:Keyword Index="K" Term="EncryptAlgorithm property" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.EncryptAlgorithm property" /><MSHelp:Keyword Index="F" Term="EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.EncryptAlgorithm" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.EncryptAlgorithm" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.get_EncryptAlgorithm" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The algorithm used to perform encryption and decryption." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.EncryptAlgorithm Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryQueueDatabase_Delete" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryQueueDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method "
/><MSHelp:RLTitle Title="SecondaryQueueDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Delete" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K"
Term="Delete method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Delete method"
/><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword
Index="F" Term="SecondaryQueueDatabase.Delete" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryQueueDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CachePriority Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_CachePriority" /><meta name="guid" content="Fields_T_BerkeleyDB_CachePriority" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.CachePriority" /><MSHelp:TOCTitle Title="CachePriority Fields" /><MSHelp:RLTitle Title="CachePriority Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.CachePriority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityFieldsTopic" /><MSHelp:Keyword Index="K" Term="CachePriority class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority Fields</td></tr><tr id="headerTableRow3"><td align="left">CachePriority Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (CursorConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Cursor_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Cursor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:TOCTitle Title="Cursor Method (CursorConfig)" /><MSHelp:RLTitle Title="BTreeDatabase.Cursor Method (CursorConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Cursor Method (CursorConfig)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupReadCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_BackupReadCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_BackupReadCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.BackupReadCount" /><MSHelp:TOCTitle Title="BackupReadCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.BackupReadCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.BackupReadCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupReadCountTopic" /><MSHelp:Keyword Index="K" Term="BackupReadCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BackupReadCount property" /><MSHelp:Keyword Index="F" Term="BackupReadCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BackupReadCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BackupReadCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BackupReadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_BackupReadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_BackupReadCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of pages to read before pausing during the hot backup. Increasing this value increases the amount of I/O the backup process performs for any given time interval. If your application is ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::<span
class="nu">.BackupReadCount Property </td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MaxBufferWritesSleep Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_MPoolStats_MaxBufferWritesSleep" /><meta name="guid"
content="P_BerkeleyDB_MPoolStats_MaxBufferWritesSleep" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MPoolStats.MaxBufferWritesSleep" /><MSHelp:TOCTitle Title="MaxBufferWritesSleep
Property " /><MSHelp:RLTitle Title="MPoolStats.MaxBufferWritesSleep Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxBufferWritesSleep"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxBufferWritesSleepTopic"
/><MSHelp:Keyword Index="K" Term="MaxBufferWritesSleep property" /><MSHelp:Keyword Index="K"
Term="MPoolStats.MaxBufferWritesSleep property" /><MSHelp:Keyword Index="F"
Term="MaxBufferWritesSleep" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxBufferWritesSleep"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxBufferWritesSleep" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxBufferWritesSleep" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxBufferWritesSleep" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract"
Value="Sleep after writing max buffers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxBufferWritesSleep Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LastID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_LastID" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_LastID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.LastID" /><MSHelp:TOCTitle Title="LastID Property " /><MSHelp:RLTitle Title="TransactionStats.LastID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.LastID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassLastIDTopic" /><MSHelp:Keyword Index="K" Term="LastID property" /><MSHelp:Keyword Index="K" Term="TransactionStats.LastID property" /><MSHelp:Keyword Index="F" Term="LastID" /><MSHelp:Keyword Index="F" Term="TransactionStats.LastID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.LastID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.LastID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_LastID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Last transaction id given out" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">TransactionStats.<span
class="vb">.::.LastID Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_TransactionStats.htm">TransactionStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryRecnoDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryRecnoDatabaseConfig__ctor"

/><meta name="guid" content="M_BerkeleyDB_SecondaryRecnoDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryRecnoDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:TOCTitle Title="SecondaryRecnoDatabaseConfig Constructor " /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryRecnoDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig.SecondaryRecnoDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.SecondaryRecnoDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryRecnoDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_PageSize" /><meta name="guid" content="P_BerkeleyDB_HeapStats_PageSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.PageSize" /><MSHelp:TOCTitle Title="PageSize Property " /><MSHelp:RLTitle Title="HeapStats.PageSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.PageSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassPageSizeTopic" /><MSHelp:Keyword Index="K" Term="PageSize property" /><MSHelp:Keyword Index="K" Term="HeapStats.PageSize property" /><MSHelp:Keyword Index="F" Term="PageSize" /><MSHelp:Keyword Index="F" Term="HeapStats.PageSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.PageSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.PageSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_PageSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The underlying database page (and bucket) size, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HeapStats.<span
class="vb">.::.PageSize Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HeapStats.htm">HeapStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseMVCC
Field</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseMVCC" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseMVCC" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseMVCC" /><MSHelp:TOCTitle Title="UseMVCC Field"
/><MSHelp:RLTitle

Title="DatabaseEnvironmentConfig.UseMVCC Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseMVCC" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseMVCCTopic" /><MSHelp:Keyword Index="K" Term="UseMVCC field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.UseMVCC field" /><MSHelp:Keyword Index="F" Term="UseMVCC" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.UseMVCC" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.UseMVCC" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseMVCC" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, all databases in the environment will be opened as if is passed to . This flag will be ignored for queue databases for which MVCC is not supported." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig.<span

class="vb">.::.UseMVCC Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QUEUE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseType_QUEUE" /><meta name="guid" content="F_BerkeleyDB_DatabaseType_QUEUE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseType.QUEUE" /><MSHelp:TOCTitle Title="QUEUE Field" /><MSHelp:RLTitle Title="DatabaseType.QUEUE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseType.QUEUE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassQUEUETopic" /><MSHelp:Keyword Index="K" Term="QUEUE field" /><MSHelp:Keyword Index="K" Term="DatabaseType.QUEUE field" /><MSHelp:Keyword Index="F" Term="QUEUE" /><MSHelp:Keyword Index="F" Term="DatabaseType.QUEUE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.QUEUE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.QUEUE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Queue access method" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType..::.QUEUE Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MoveNextDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MoveNextDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMoveNextDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicate method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MoveNextDuplicate method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MoveNextDuplicate"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">SecondaryCursor..::.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Encrypted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Encrypted" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_Encrypted" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.Encrypted" /><MSHelp:TOCTitle Title="Encrypted Property " /><MSHelp:RLTitle Title="BaseDatabase.Encrypted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.Encrypted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassEncryptedTopic" /><MSHelp:Keyword Index="K" Term="Encrypted property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Encrypted property" /><MSHelp:Keyword Index="F" Term="Encrypted" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Encrypted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Encrypted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Encrypted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_Encrypted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, encrypt all data stored in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Encrypted Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MovePrev" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method " /><MSHelp:RLTitle Title="SecondaryCursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMovePrevTopic" /><MSHelp:Keyword Index="K" Term="MovePrev method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MovePrev method" /><MSHelp:Keyword Index="F" Term="MovePrev"

/><MSHelp:Keyword Index="F" Term="SecondaryCursor.MovePrev" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RecnoDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_RecnoDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RecnoDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="RecnoDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RecnoDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><div

id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepDelayClientSync Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepDelayClientSync" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepDelayClientSync" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepDelayClientSync"

/><MSHelp:TOCTitle Title="RepDelayClientSync Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepDelayClientSync Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepDelayClientSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepDelayClientSyncTopic" /><MSHelp:Keyword Index="K" Term="RepDelayClientSync property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepDelayClientSync property" /><MSHelp:Keyword Index="F" Term="RepDelayClientSync" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepDelayClientSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepDelayClientSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepDelayClientSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepDelayClientSync" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepDelayClientSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the client should delay synchronizing to a newly declared master (defaults to false). Clients configured in this way will remain unsynchronized until the application calls ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepDelayClientSync Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_QueueDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_QueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:TOCTitle Title="QueueDatabaseConfig Class" /><MSHelp:RLTitle Title="QueueDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.QueueDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig class, about QueueDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicate" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the
cursor to the next key/data pair in the database, and store that pair in . MoveNextDupli ..." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">Cursor.<span
class="vb">.::<span
class="nu">.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td
align="left">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HEAP Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseType_HEAP" /><meta name="guid" content="F_BerkeleyDB_DatabaseType_HEAP" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseType.HEAP" /><MSHelp:TOCTitle Title="HEAP Field" /><MSHelp:RLTitle Title="DatabaseType.HEAP Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseType.HEAP" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassHEAPTopic" /><MSHelp:Keyword Index="K" Term="HEAP field" /><MSHelp:Keyword Index="K" Term="DatabaseType.HEAP field" /><MSHelp:Keyword Index="F" Term="HEAP" /><MSHelp:Keyword Index="F" Term="DatabaseType.HEAP" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.HEAP" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.HEAP" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Heap access method" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType..::.HEAP Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesCreatedInCache Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_PagesCreatedInCache" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_PagesCreatedInCache" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.PagesCreatedInCache" /><MSHelp:TOCTitle Title="PagesCreatedInCache Property " /><MSHelp:RLTitle Title="MPoolFileStats.PagesCreatedInCache Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.PagesCreatedInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassPagesCreatedInCacheTopic" /><MSHelp:Keyword Index="K" Term="PagesCreatedInCache property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.PagesCreatedInCache property" /><MSHelp:Keyword Index="F" Term="PagesCreatedInCache" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.PagesCreatedInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.PagesCreatedInCache" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.PagesCreatedInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_PagesCreatedInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Pages created in the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.PagesCreatedInCache Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepHoldElection Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RepHoldElection" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_RepHoldElection" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:TOCTitle Title="RepHoldElection Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepHoldElection Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepHoldElectionTopic" /><MSHelp:Keyword Index="K" Term="RepHoldElection method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepHoldElection method" /><MSHelp:Keyword Index="F" Term="RepHoldElection" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepHoldElection" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepHoldElection Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SequenceConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SequenceConfig" /><meta name="guid" content="T_BerkeleyDB_SequenceConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SequenceConfig" /><MSHelp:TOCTitle Title="SequenceConfig Class" /><MSHelp:RLTitle Title="SequenceConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SequenceConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassTopic" /><MSHelp:Keyword Index="K" Term="SequenceConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SequenceConfig class" /><MSHelp:Keyword Index="K" Term="SequenceConfig class, about SequenceConfig class" /><MSHelp:Keyword Index="F" Term="SequenceConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig" /><MSHelp:Attr

Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration properties for a Sequence" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>TransactionConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_TransactionConfig" /><meta name="guid" content="T_BerkeleyDB_TransactionConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.TransactionConfig" /><MSHelp:TOCTitle Title="TransactionConfig Class" /><MSHelp:RLTitle Title="TransactionConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.TransactionConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassTopic" /><MSHelp:Keyword Index="K" Term="TransactionConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.TransactionConfig class" /><MSHelp:Keyword Index="K" Term="TransactionConfig class, about TransactionConfig class" /><MSHelp:Keyword Index="F" Term="TransactionConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for a ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockConflictMatrix Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LockConflictMatrix" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LockConflictMatrix" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LockConflictMatrix" /><MSHelp:TOCTitle Title="LockConflictMatrix Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LockConflictMatrix Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LockConflictMatrix" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLockConflictMatrixTopic" /><MSHelp:Keyword Index="K" Term="LockConflictMatrix property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LockConflictMatrix property" /><MSHelp:Keyword Index="F" Term="LockConflictMatrix" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LockConflictMatrix" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LockConflictMatrix" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LockConflictMatrix" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LockConflictMatrix" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LockConflictMatrix" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The current lock conflicts array." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockConflictMatrix Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashCursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HashCursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HashCursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HashCursor" /><MSHelp:TOCTitle Title="HashCursor Members" /><MSHelp:RLTitle Title="HashCursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HashCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="HashCursor class" /><MSHelp:Keyword Index="K" Term="HashCursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashCursor class" /><MSHelp:Keyword Index="F" Term="HashCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor Members</td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabase Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HashDatabase" /><meta name="guid" content="Properties_T_BerkeleyDB_HashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HashDatabase" /><MSHelp:TOCTitle Title="HashDatabase Properties " /><MSHelp:RLTitle Title="HashDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="HashDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextUniqueMultiple Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_BTreeCursor_MoveNextUniqueMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_BTreeCursor_MoveNextUniqueMultiple" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextUniqueMultiple" /><MSHelp:TOCTitle
Title="MoveNextUniqueMultiple Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextUniqueMultiple
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.BTreeCursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeCursorClassMoveNextUniqueMultipleTopic" /><MSHelp:Keyword
Index="K" Term="MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="K"
Term="BTreeCursor.MoveNextUniqueMultiple method" /><MSHelp:Keyword Index="F"
Term="MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F"
Term="BTreeCursor.MoveNextUniqueMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeCursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
 tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
 for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor<span
 class="cs">..::.MoveNextUniqueMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegisteredSites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css"
 href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_RegisteredSites" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_RegisteredSites" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.RegisteredSites" /><MSHelp:TOCTitle Title="RegisteredSites Property "

/><MSHelp:RLTitle Title="ReplicationStats.RegisteredSites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.RegisteredSites" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassRegisteredSitesTopic" /><MSHelp:Keyword Index="K" Term="RegisteredSites property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.RegisteredSites property" /><MSHelp:Keyword Index="F" Term="RegisteredSites" /><MSHelp:Keyword Index="F" Term="ReplicationStats.RegisteredSites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.RegisteredSites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.RegisteredSites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_RegisteredSites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of "registered voters"." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">ReplicationStats..::.RegisteredSites Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveFirst" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="Cursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveFirst" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveFirstTopic" /><MSHelp:Keyword Index="K" Term="MoveFirst method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveFirst method" /><MSHelp:Keyword Index="F" Term="MoveFirst" /><MSHelp:Keyword Index="F" Term="Cursor.MoveFirst" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.MoveFirst Method
</td></tr><tr id="headerTableRow3"><td align="left">Cursor
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RegionLockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_RegionLockWait"

/><meta name="guid" content="P_BerkeleyDB_TransactionStats_RegionLockWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.RegionLockWait" /><MSHelp:TOCTitle Title="RegionLockWait Property " /><MSHelp:RLTitle Title="TransactionStats.RegionLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.RegionLockWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassRegionLockWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionLockWait property" /><MSHelp:Keyword Index="K" Term="TransactionStats.RegionLockWait property" /><MSHelp:Keyword Index="F" Term="RegionLockWait" /><MSHelp:Keyword Index="F" Term="TransactionStats.RegionLockWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.RegionLockWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.RegionLockWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_RegionLockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.RegionLockWait Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrLocalSite Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrLocalSite" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrLocalSite" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepMgrLocalSite" /><MSHelp:TOCTitle Title="RepMgrLocalSite Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrLocalSite Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepMgrLocalSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrLocalSiteTopic" /><MSHelp:Keyword Index="K" Term="RepMgrLocalSite property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrLocalSite property" /><MSHelp:Keyword Index="F" Term="RepMgrLocalSite" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrLocalSite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrLocalSite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrLocalSite" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepMgrLocalSite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The local site of the replication manager. Returns null if the local site has not been configured." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrLocalSite Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_QueueDatabaseConfig_Append" /><meta name="guid"

content="F_BerkeleyDB_QueueDatabaseConfig_Append" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.QueueDatabaseConfig.Append" /><MSHelp:TOCTitle Title="Append Field" /><MSHelp:RLTitle Title="QueueDatabaseConfig.Append Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.QueueDatabaseConfig.Append" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassAppendTopic" /><MSHelp:Keyword Index="K" Term="Append field" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig.Append field" /><MSHelp:Keyword Index="F" Term="Append" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig.Append" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig.Append" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function to call after the record number has been selected but before the data has been stored into the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig..::.Append Field</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>JoinCursor Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_JoinCursor" /><meta name="guid" content="T_BerkeleyDB_JoinCursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.JoinCursor" /><MSHelp:TOCTitle Title="JoinCursor Class" /><MSHelp:RLTitle Title="JoinCursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.JoinCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassTopic" /><MSHelp:Keyword Index="K" Term="JoinCursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.JoinCursor class" /><MSHelp:Keyword Index="K" Term="JoinCursor class, about JoinCursor class" /><MSHelp:Keyword Index="F" Term="JoinCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a join cursor, for use in performing equality or natural joins on secondary indices. For information on how to organize your data to use this functionality, see Equality join in the ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_Refresh" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="HashCursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.Refresh" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassRefreshTopic" /><MSHelp:Keyword Index="K" Term="Refresh method" /><MSHelp:Keyword Index="K" Term="HashCursor.Refresh method" /><MSHelp:Keyword Index="F" Term="Refresh" /><MSHelp:Keyword Index="F" Term="HashCursor.Refresh" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple
</nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">HashCursor..::.Refresh Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
 xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verify Method (String, DatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Verify" /><meta name="guid" content="M_BerkeleyDB_Database_Verify" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Verify(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:TOCTitle Title="Verify Method (String, DatabaseConfig)" /><MSHelp:RLTitle Title="Database.Verify Method (String, DatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Verify(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Verify" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
 /><MSHelp:Attr Name="Abstract" Value="Verify the integrity of all databases in the file specified by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
 title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Verify Method (String, DatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LogStats" /><meta name="guid" content="Properties_T_BerkeleyDB_LogStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LogStats" /><MSHelp:TOCTitle Title="LogStats Properties " /><MSHelp:RLTitle Title="LogStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LogStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="LogStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown"
class="filter" tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats
Properties </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LogStats.htm">LogStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TransactionSystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_TransactionSystemStats" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_TransactionSystemStats" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.TransactionSystemStats" /><MSHelp:TOCTitle
Title="TransactionSystemStats Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.TransactionSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.TransactionSystemStats" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TransactionSystemStats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The transaction subsystem statistics" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TransactionSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyEmptyException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_KeyEmptyException" /><meta name="guid" content="T_BerkeleyDB_KeyEmptyException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.KeyEmptyException" /><MSHelp:TOCTitle Title="KeyEmptyException Class" /><MSHelp:RLTitle Title="KeyEmptyException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.KeyEmptyException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyEmptyExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.KeyEmptyException class" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class, about KeyEmptyException class" /><MSHelp:Keyword Index="F" Term="KeyEmptyException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyEmptyException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyEmptyException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The requested key/data pair logically exists but was never explicitly created by the application, or that the requested key/data pair was deleted

and never re-created. In addition, the Queue access
method will ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyEmptyException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_BTreeDatabase_GetMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_BTreeDatabase_GetMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:TOCTitle Title="GetMultiple Method "
/><MSHelp:RLTitle
Title="BTreeDatabase.GetMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeDatabaseClassGetMultipleTopic" /><MSHelp:Keyword Index="K"
Term="GetMultiple method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.GetMultiple method"
/><MSHelp:Keyword Index="F" Term="GetMultiple" /><MSHelp:Keyword Index="F"
Term="BTreeDatabase.GetMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.GetMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TruncateUnusedPages Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_TruncateUnusedPages" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_TruncateUnusedPages" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.TruncateUnusedPages" /><MSHelp:TOCTitle Title="TruncateUnusedPages Method " /><MSHelp:RLTitle Title="RecnoDatabase.TruncateUnusedPages Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.TruncateUnusedPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassTruncateUnusedPagesTopic" /><MSHelp:Keyword Index="K" Term="TruncateUnusedPages method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.TruncateUnusedPages method" /><MSHelp:Keyword Index="F" Term="TruncateUnusedPages" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.TruncateUnusedPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr

id="headerTableRow2"><td align="left">RecnoDatabase<span
class="languageSpecificText">..<span
class="cpp">::.TruncateUnusedPages Method </td></tr><tr
id="headerTableRow3"><td align="left">RecnoDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
 xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Checkpoint Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
 content="M_BerkeleyDB_DatabaseEnvironment_Checkpoint" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_Checkpoint" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:TOCTitle Title="Checkpoint Method "
/><MSHelp:RLTitle Title="DatabaseEnvironment.Checkpoint Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Flush the underlying memory pool, write a checkpoint record to the log, and then flush
 the log, even if there has been no activity since the last checkpoint." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
 image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Checkpoint Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashChainSearches Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_HashChainSearches" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_HashChainSearches" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.HashChainSearches" /><MSHelp:TOCTitle Title="HashChainSearches Property " /><MSHelp:RLTitle Title="MPoolStats.HashChainSearches Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.HashChainSearches" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassHashChainSearchesTopic" /><MSHelp:Keyword Index="K" Term="HashChainSearches property" /><MSHelp:Keyword Index="K" Term="MPoolStats.HashChainSearches property" /><MSHelp:Keyword Index="F" Term="HashChainSearches" /><MSHelp:Keyword Index="F" Term="MPoolStats.HashChainSearches" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.HashChainSearches" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.HashChainSearches" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.MPoolStats.get_HashChainSearches" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total hash chain searches." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.HashChainSearches Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple

Method (UInt32, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultiple_2" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultiple_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32,System.Int32)" /><MSHelp:TOCTitle Title="MoveMultiple Method (UInt32, Int32)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultiple Method (UInt32, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"

data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultiple Method (UInt32, Int32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MinKeysPerPage Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_MinKeysPerPage" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_MinKeysPerPage" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.MinKeysPerPage" /><MSHelp:TOCTitle Title="MinKeysPerPage Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.MinKeysPerPage Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.MinKeysPerPage" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassMinKeysPerPageTopic" /><MSHelp:Keyword Index="K" Term="MinKeysPerPage property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.MinKeysPerPage property" /><MSHelp:Keyword Index="F" Term="MinKeysPerPage" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.MinKeysPerPage" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.MinKeysPerPage" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.MinKeysPerPage" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_MinKeysPerPage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The minimum number of key/data pairs intended to be stored on any single Btree leaf page." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.MinKeysPerPage Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullLogBufferException

Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_FullLogBufferException__ctor" /><meta name="guid" content="M_BerkeleyDB_FullLogBufferException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.FullLogBufferException.#ctor" /><MSHelp:TOCTitle Title="FullLogBufferException Constructor " /><MSHelp:RLTitle Title="FullLogBufferException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.FullLogBufferException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBFullLogBufferExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class, constructor" /><MSHelp:Keyword Index="K" Term="FullLogBufferException.FullLogBufferException constructor" /><MSHelp:Keyword Index="F" Term="FullLogBufferException" /><MSHelp:Keyword Index="F" Term="FullLogBufferException.FullLogBufferException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.FullLogBufferException.FullLogBufferException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.FullLogBufferException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the FullLogBufferException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">FullLogBufferException Constructor </td></tr><tr id="headerTableRow3"><td align="left">FullLogBufferException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Feedback Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Feedback" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Feedback" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Feedback" /><MSHelp:TOCTitle Title="Feedback Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Feedback Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Feedback" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassFeedbackTopic" /><MSHelp:Keyword Index="K" Term="Feedback field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Feedback field" /><MSHelp:Keyword Index="F" Term="Feedback" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.Feedback" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.Feedback" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.Feedback" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Monitor progress within long running operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.Feedback Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReceivedPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="P_BerkeleyDB_ReplicationStats_ReceivedPages" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ReceivedPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ReceivedPages" /><MSHelp:TOCTitle Title="ReceivedPages Property " /><MSHelp:RLTitle Title="ReplicationStats.ReceivedPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ReceivedPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassReceivedPagesTopic" /><MSHelp:Keyword Index="K" Term="ReceivedPages property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ReceivedPages property" /><MSHelp:Keyword Index="F" Term="ReceivedPages" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ReceivedPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ReceivedPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ReceivedPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ReceivedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages received and stored." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ReceivedPages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesNotInCache Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_PagesNotInCache" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_PagesNotInCache" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.PagesNotInCache" /><MSHelp:TOCTitle Title="PagesNotInCache Property " /><MSHelp:RLTitle Title="MPoolFileStats.PagesNotInCache Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.PagesNotInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassPagesNotInCacheTopic" /><MSHelp:Keyword Index="K" Term="PagesNotInCache property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.PagesNotInCache property" /><MSHelp:Keyword Index="F" Term="PagesNotInCache" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.PagesNotInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.PagesNotInCache" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.PagesNotInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_PagesNotInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages not found in the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;

height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.PagesNotInCache Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MappedPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MappedPages" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MappedPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MappedPages" /><MSHelp:TOCTitle Title="MappedPages Property " /><MSHelp:RLTitle Title="MPoolStats.MappedPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MappedPages" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBMPoolStatsClassMappedPagesTopic" /><MSHelp:Keyword Index="K"
Term="MappedPages property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MappedPages property"
/><MSHelp:Keyword Index="F" Term="MappedPages" /><MSHelp:Keyword Index="F"
Term="MPoolStats.MappedPages" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MPoolStats.MappedPages" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.MappedPages" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.get_MappedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Pages from mapped files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MPoolStats<span
class="cs">..::<span
class="nu">.MappedPages Property </td></tr><tr id="headerTableRow3"><td

align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevDuplicate Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and the secondary key and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"

/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevDuplicate Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_GetBothMultiple" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.GetBothMultiple" /><MSHelp:TOCTitle Title="GetBothMultiple Method " /><MSHelp:RLTitle Title="QueueDatabase.GetBothMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.GetBothMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassGetBothMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetBothMultiple method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.GetBothMultiple method" /><MSHelp:Keyword Index="F" Term="GetBothMultiple" /><MSHelp:Keyword Index="F" Term="QueueDatabase.GetBothMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase.<span

class="vb">.::.GetBothMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Sequence__ctor" /><meta name="guid" content="Overload_BerkeleyDB_Sequence__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Sequence.#ctor" /><MSHelp:TOCTitle Title="Sequence Constructor " /><MSHelp:RLTitle Title="Sequence Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Sequence.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassctorTopic" /><MSHelp:Keyword Index="K" Term="Sequence class, constructor" /><MSHelp:Keyword Index="K" Term="Sequence.Sequence constructor" /><MSHelp:Keyword Index="F" Term="Sequence" /><MSHelp:Keyword Index="F" Term="Sequence.Sequence" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Sequence" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence Constructor </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrev_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrev_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrev(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrev Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MovePrev Method (LockingInfo) (BerkeleyDB)"

/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrev(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store that pair in . In the presence of duplicate key ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrev Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_Dispose" /><meta name="guid" content="M_BerkeleyDB_JoinCursor_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="JoinCursor.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="JoinCursor.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="JoinCursor.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by this object, and close the cursor if it's still open." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MovePrevDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="HashCursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMovePrevDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MovePrevDuplicate method" /><MSHelp:Keyword Index="K" Term="HashCursor.MovePrevDuplicate method" /><MSHelp:Keyword Index="F" Term="MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="HashCursor.MovePrevDuplicate"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MovePrevDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor

Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_OverflowPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_HashStats_OverflowPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.OverflowPagesFreeBytes" /><MSHelp:TOCTitle Title="OverflowPagesFreeBytes Property " /><MSHelp:RLTitle Title="HashStats.OverflowPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.OverflowPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassOverflowPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="OverflowPagesFreeBytes property" /><MSHelp:Keyword
Index="K" Term="HashStats.OverflowPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="OverflowPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="HashStats.OverflowPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.OverflowPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.OverflowPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_OverflowPagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free on ovfl pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.OverflowPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerboseMessages Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_VerboseMessages" /><meta name="guid" content="Methods_T_BerkeleyDB_VerboseMessages" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.VerboseMessages" /><MSHelp:TOCTitle Title="VerboseMessages Methods " /><MSHelp:RLTitle Title="VerboseMessages Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.VerboseMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesMethodsTopic" /><MSHelp:Keyword Index="K" Term="VerboseMessages class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr

Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages Methods </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_VerboseMessages.htm">VerboseMessages
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Conflicts
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockingConfig_Conflicts" /><meta
name="guid" content="P_BerkeleyDB_LockingConfig_Conflicts" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockingConfig.Conflicts" /><MSHelp:TOCTitle Title="Conflicts Property "
/><MSHelp:RLTitle Title="LockingConfig.Conflicts Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockingConfig.Conflicts" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingConfigClassConflictsTopic" /><MSHelp:Keyword Index="K" Term="Conflicts
property" /><MSHelp:Keyword Index="K" Term="LockingConfig.Conflicts property" /><MSHelp:Keyword
Index="F" Term="Conflicts" /><MSHelp:Keyword Index="F" Term="LockingConfig.Conflicts"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.Conflicts" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.Conflicts" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockingConfig.get_Conflicts" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.set_Conflicts" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The locking
conflicts matrix." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml><link type="text/css"
rel="stylesheet" href="../styles/highlight.css" /><script type="text/javascript"
src="../scripts/highlight.js"></script></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.Conflicts Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FrozenBuffers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_FrozenBuffers" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_FrozenBuffers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.FrozenBuffers" /><MSHelp:TOCTitle Title="FrozenBuffers Property " /><MSHelp:RLTitle Title="MPoolStats.FrozenBuffers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.FrozenBuffers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassFrozenBuffersTopic" /><MSHelp:Keyword Index="K" Term="FrozenBuffers property" /><MSHelp:Keyword Index="K" Term="MPoolStats.FrozenBuffers property" /><MSHelp:Keyword Index="F" Term="FrozenBuffers" /><MSHelp:Keyword Index="F" Term="MPoolStats.FrozenBuffers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.FrozenBuffers" /><MSHelp:Attr Name="APIType" Value="Managed"

/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.FrozenBuffers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_FrozenBuffers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Buffers frozen." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.FrozenBuffers Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DupCompare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_DupCompare" /><meta name="guid" content="P_BerkeleyDB_BTreeDatabase_DupCompare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabase.DupCompare" /><MSHelp:TOCTitle Title="DupCompare Property " /><MSHelp:RLTitle Title="BTreeDatabase.DupCompare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.DupCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassDupCompareTopic" /><MSHelp:Keyword Index="K" Term="DupCompare property" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.DupCompare property" /><MSHelp:Keyword Index="F" Term="DupCompare" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.DupCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.DupCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.get_DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.set_DupCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.DupCompare Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BTreeDatabaseConfig_Duplicates" /><meta name="guid" content="F_BerkeleyDB_BTreeDatabaseConfig_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BTreeDatabaseConfig.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Field" /><MSHelp:RLTitle Title="BTreeDatabaseConfig.Duplicates Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BTreeDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.Duplicates field" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Policy for duplicate data items in the database; that is, insertion when the key of the key/data pair being inserted already exists

in the database will be successful." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.Duplicates Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Current Property </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Cursor_Current" /><meta name="guid" content="P_BerkeleyDB_Cursor_Current" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Cursor.Current" /><MSHelp:TOCTitle Title="Current Property " /><MSHelp:RLTitle Title="Cursor.Current Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.Cursor.Current" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassCurrentTopic" /><MSHelp:Keyword Index="K" Term="Current property" /><MSHelp:Keyword Index="K" Term="Cursor.Current property" /><MSHelp:Keyword Index="F" Term="Current" /><MSHelp:Keyword Index="F" Term="Cursor.Current" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Current" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Current" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.get_Current" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.set_Current" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The key/data pair at which the cursor currently points." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Current Property </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Private Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Private" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Private" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Private" /><MSHelp:TOCTitle Title="Private Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Private Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Private" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassPrivateTopic" /><MSHelp:Keyword Index="K" Term="Private field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Private field" /><MSHelp:Keyword Index="F" Term="Private" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.Private" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.Private" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.Private" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, allocate region memory from the heap instead of from memory backed by the filesystem or system shared memory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.Private Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="AllMembers_T_BerkeleyDB_MPoolStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_MPoolStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.MPoolStats" /><MSHelp:TOCTitle Title="MPoolStats Members" /><MSHelp:RLTitle Title="MPoolStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.MPoolStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="MPoolStats class" /><MSHelp:Keyword Index="K" Term="MPoolStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MPoolStats class" /><MSHelp:Keyword Index="F" Term="MPoolStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats Members</td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_Refresh" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="BTreeCursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.Refresh" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassRefreshTopic" /><MSHelp:Keyword Index="K" Term="Refresh method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.Refresh method" /><MSHelp:Keyword Index="F" Term="Refresh" /><MSHelp:Keyword Index="F" Term="BTreeCursor.Refresh" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Refresh Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxFileId Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_MaxFileId" /><meta name="guid" content="P_BerkeleyDB_LogStats_MaxFileId" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.MaxFileId" /><MSHelp:TOCTitle Title="MaxFileId Property " /><MSHelp:RLTitle Title="LogStats.MaxFileId Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.MaxFileId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassMaxFileIdTopic" /><MSHelp:Keyword Index="K" Term="MaxFileId property" /><MSHelp:Keyword Index="K" Term="LogStats.MaxFileId property" /><MSHelp:Keyword Index="F" Term="MaxFileId" /><MSHelp:Keyword Index="F" Term="LogStats.MaxFileId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.MaxFileId" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.MaxFileId" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_MaxFileId" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum fileids used." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.MaxFileId Property </td></tr><tr id="headerTableRow3"><td
align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNextUnique" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveNextUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextUnique" /><MSHelp:TOCTitle Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNextUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNextUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveNextUniqueTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUnique method" /><MSHelp:Keyword
Index="K" Term="RecnoCursor.MoveNextUnique method" /><MSHelp:Keyword Index="F" Term="MoveNextUnique" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveNextUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoCursor.<span
class="vb">.::<span
class="nu">.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td
align="left">RecnoCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BigPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_BigPages" /><meta name="guid" content="P_BerkeleyDB_HashStats_BigPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.BigPages" /><MSHelp:TOCTitle Title="BigPages Property " /><MSHelp:RLTitle Title="HashStats.BigPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.BigPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassBigPagesTopic" /><MSHelp:Keyword Index="K" Term="BigPages property" /><MSHelp:Keyword Index="K" Term="HashStats.BigPages property" /><MSHelp:Keyword Index="F" Term="BigPages" /><MSHelp:Keyword Index="F" Term="HashStats.BigPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.BigPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.BigPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_BigPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of big key/data pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.BigPages Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Constructor (Byte[])</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEntry__ctor_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEntry__ctor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEntry.#ctor(System.Byte[])" /><MSHelp:TOCTitle Title="DatabaseEntry Constructor (Byte[])" /><MSHelp:RLTitle Title="DatabaseEntry Constructor (Byte[]) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEntry.#ctor(System.Byte[])" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new DatabaseEntry object, with the specified data" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Constructor (array<Byte>[]()[])</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="Overload_BerkeleyDB_QueueDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="QueueDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">QueueDatabase<span
class="cs">..::<span
class="nu">.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_QueueDatabase.htm">QueueDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryCursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryHashDatabase_SecondaryCursor" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryHashDatabase_SecondaryCursor" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.SecondaryCursor" /><MSHelp:TOCTitle
Title="SecondaryCursor Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.SecondaryCursor Method
(BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.SecondaryCursor" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassSecondaryCursorTopic" /><MSHelp:Keyword
Index="K" Term="SecondaryCursor method" /><MSHelp:Keyword Index="K"
Term="SecondaryHashDatabase.SecondaryCursor method" /><MSHelp:Keyword Index="F"
Term="SecondaryCursor" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.SecondaryCursor"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.SecondaryCursor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.SecondaryCursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoMMap Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_NoMMap" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_NoMMap" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.NoMMap" /><MSHelp:TOCTitle Title="NoMMap Field" /><MSHelp:RLTitle Title="DatabaseConfig.NoMMap Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.NoMMap" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassNoMMapTopic" /><MSHelp:Keyword Index="K" Term="NoMMap field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.NoMMap field" /><MSHelp:Keyword Index="F" Term="NoMMap" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.NoMMap" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.NoMMap" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.NoMMap" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Do not map this database into process memory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.NoMMap Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_HeapDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabaseConfig.#ctor" /><MSHelp:TOCTitle Title="HeapDatabaseConfig Constructor " /><MSHelp:RLTitle Title="HeapDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabaseConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig.HeapDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig.HeapDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabaseConfig.HeapDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HeapDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>RepHoldElection Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepHoldElection" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepHoldElection" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:TOCTitle Title="RepHoldElection Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepHoldElection Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Hold an election for the master of a replication group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
/> <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepHoldElection Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeafPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_LeafPagesFreeBytes" /><meta name="guid"
content="P_BerkeleyDB_RecnoStats_LeafPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.LeafPagesFreeBytes" /><MSHelp:TOCTitle Title="LeafPagesFreeBytes Property " /><MSHelp:RLTitle Title="RecnoStats.LeafPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.LeafPagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassLeafPagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="LeafPagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="RecnoStats.LeafPagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="LeafPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="RecnoStats.LeafPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.LeafPagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.LeafPagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_LeafPagesFreeBytes"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in leaf pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.LeafPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EmptyBuckets Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactData_EmptyBuckets" /><meta name="guid" content="P_BerkeleyDB_CompactData_EmptyBuckets" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactData.EmptyBuckets" /><MSHelp:TOCTitle Title="EmptyBuckets Property "

/><MSHelp:RLTitle Title="CompactData.EmptyBuckets Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactData.EmptyBuckets" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassEmptyBucketsTopic" /><MSHelp:Keyword Index="K" Term="EmptyBuckets property" /><MSHelp:Keyword Index="K" Term="CompactData.EmptyBuckets property" /><MSHelp:Keyword Index="F" Term="EmptyBuckets" /><MSHelp:Keyword Index="F" Term="CompactData.EmptyBuckets" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData.EmptyBuckets" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.EmptyBuckets" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.get_EmptyBuckets" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of empty hash buckets that were found the compaction phase." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData..::.EmptyBuckets Property </td></tr><tr id="headerTableRow3"><td align="left">CompactData Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordLength Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_RecordLength" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_RecordLength" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.RecordLength" /><MSHelp:TOCTitle Title="RecordLength Property " /><MSHelp:RLTitle Title="RecnoStats.RecordLength Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.RecordLength" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassRecordLengthTopic" /><MSHelp:Keyword Index="K" Term="RecordLength property" /><MSHelp:Keyword Index="K" Term="RecnoStats.RecordLength property" /><MSHelp:Keyword Index="F" Term="RecordLength" /><MSHelp:Keyword Index="F" Term="RecnoStats.RecordLength" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.RecordLength" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.RecordLength" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_RecordLength" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Fixed-length record length." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoStats.<span
class="vb">.::.RecordLength Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoStats.htm">RecnoStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>QueueDatabaseConfig Constructor </title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_QueueDatabaseConfig__ctor" /><meta name="guid"
content="M_BerkeleyDB_QueueDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.QueueDatabaseConfig.#ctor" /><MSHelp:TOCTitle Title="QueueDatabaseConfig
Constructor
" /><MSHelp:RLTitle Title="QueueDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.QueueDatabaseConfig.#ctor" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBQueueDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K"
Term="QueueDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K"
Term="QueueDatabaseConfig.QueueDatabaseConfig constructor" /><MSHelp:Keyword Index="F"
Term="QueueDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="QueueDatabaseConfig.QueueDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.QueueDatabaseConfig.QueueDatabaseConfig" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new
QueueDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">QueueDatabaseConfig Constructor </td></tr><tr
id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_QueueDatabaseConfig.htm">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transport Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_Transport" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_Transport" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.Transport" /><MSHelp:TOCTitle Title="Transport Field" /><MSHelp:RLTitle Title="ReplicationConfig.Transport Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.Transport" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassTransportTopic" /><MSHelp:Keyword Index="K" Term="Transport field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.Transport field" /><MSHelp:Keyword Index="F" Term="Transport" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.Transport" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.Transport" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.Transport" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The delegate used to transmit data using the replication application's communication infrastructure." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">ReplicationConfig<span
class="cs">..::<span
class="nu">.Transport Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ReplicationConfig.htm">ReplicationConfig Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MultipleDatabaseEntry Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_MultipleDatabaseEntry__ctor" /><meta name="guid"
content="Overload_BerkeleyDB_MultipleDatabaseEntry__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.MultipleDatabaseEntry.#ctor" /><MSHelp:TOCTitle Title="MultipleDatabaseEntry
Constructor " /><MSHelp:RLTitle Title="MultipleDatabaseEntry Constructor (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.MultipleDatabaseEntry.#ctor"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleDatabaseEntryClassctorTopic"
/><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry class, constructor" /><MSHelp:Keyword
Index="K" Term="MultipleDatabaseEntry.MultipleDatabaseEntry constructor" /><MSHelp:Keyword Index="F"
Term="MultipleDatabaseEntry" /><MSHelp:Keyword Index="F"
Term="MultipleDatabaseEntry.MultipleDatabaseEntry" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MultipleDatabaseEntry.MultipleDatabaseEntry"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Constructor </td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DupCompare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryBTreeDatabase_DupCompare" /><meta name="guid" content="P_BerkeleyDB_SecondaryBTreeDatabase_DupCompare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryBTreeDatabase.DupCompare" /><MSHelp:TOCTitle Title="DupCompare Property " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.DupCompare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryBTreeDatabase.DupCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassDupCompareTopic" /><MSHelp:Keyword Index="K" Term="DupCompare property" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.DupCompare property" /><MSHelp:Keyword Index="F" Term="DupCompare" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.DupCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.DupCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.get_DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.set_DupCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.DupCompare Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetCompression Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabaseConfig_SetCompression" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabaseConfig_SetCompression" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:TOCTitle Title="SetCompression Method " /><MSHelp:RLTitle Title="BTreeDatabaseConfig.SetCompression Method

(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Enable compression of the key/data pairs stored in the database, using the default compression and decompression functions." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.SetCompression Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>BTreeDatabaseConfig Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BTreeDatabaseConfig"
/><meta name="guid" content="AllMembers_T_BerkeleyDB_BTreeDatabaseConfig" /><xml><MSHelp:Attr
Name="AssetID" Value="AllMembers.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:TOCTitle
Title="BTreeDatabaseConfig Members" /><MSHelp:RLTitle Title="BTreeDatabaseConfig Members
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BTreeDatabaseConfig"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigMembersTopic"
/><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="BTreeDatabaseConfig class, all members" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.BTreeDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Attr
Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeDatabaseConfig.htm">BTreeDatabaseConfig Class <a
href="#constructorTableToggle" onclick="OpenSection(constructorTableToggle)">Constructors <a
href="#methodTableToggle" onclick="OpenSection(methodTableToggle)">Methods <a
href="#fieldTableToggle" onclick="OpenSection(fieldTableToggle)">Fields <a href="#propertyTableToggle"
onclick="OpenSection(propertyTableToggle)">Properties <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryDatabase_GetBoth"

/><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="SecondaryDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.GetBoth" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransmitLimitBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_TransmitLimitBytes" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_TransmitLimitBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.TransmitLimitBytes" /><MSHelp:TOCTitle Title="TransmitLimitBytes Property " /><MSHelp:RLTitle Title="ReplicationConfig.TransmitLimitBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.TransmitLimitBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassTransmitLimitBytesTopic" /><MSHelp:Keyword Index="K" Term="TransmitLimitBytes property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.TransmitLimitBytes property" /><MSHelp:Keyword Index="F" Term="TransmitLimitBytes" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.TransmitLimitBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.TransmitLimitBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.TransmitLimitBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_TransmitLimitBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The bytes component of the byte-count limit on the amount of data that will be transmitted from a site in response to a single message processed by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ReplicationConfig.<span
class="vb">.<span
class="cpp">::.TransmitLimitBytes Property </td></tr><tr
id="headerTableRow3"><td align="left">ReplicationConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheInfo
Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="AllMembers_T_BerkeleyDB_CacheInfo" /><meta name="guid"
content="AllMembers_T_BerkeleyDB_CacheInfo" /><xml><MSHelp:Attr Name="AssetID"
Value="AllMembers.T:BerkeleyDB.CacheInfo" /><MSHelp:TOCTitle Title="CacheInfo Members"
/><MSHelp:RLTitle Title="CacheInfo Members (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="AllMembers.T:BerkeleyDB.CacheInfo" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCacheInfoMembersTopic"
/><MSHelp:Keyword Index="K" Term="CacheInfo class" /><MSHelp:Keyword Index="K" Term="CacheInfo
class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CacheInfo class" /><MSHelp:Keyword
Index="F" Term="CacheInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CacheInfo" /><MSHelp:Attr
Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CacheInfo Members</td></tr><tr id="headerTableRow3"><td align="left">CacheInfo Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironmentConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_DatabaseEnvironmentConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_DatabaseEnvironmentConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:TOCTitle Title="DatabaseEnvironmentConfig Fields" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironmentConfig Fields</td></tr><tr
id="headerTableRow3"><td
align="left">DatabaseEnvironmentConfig Class
See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Populate Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryDatabaseConfig_Populate" /><meta name="guid" content="F_BerkeleyDB_SecondaryDatabaseConfig_Populate" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryDatabaseConfig.Populate" /><MSHelp:TOCTitle Title="Populate Field" /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.Populate Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryDatabaseConfig.Populate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassPopulateTopic" /><MSHelp:Keyword Index="K" Term="Populate field" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.Populate field" /><MSHelp:Keyword Index="F" Term="Populate" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig.Populate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.Populate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.Populate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true and the secondary database is empty, walk through Primary and create an index to it in the empty secondary. This operation is potentially very expensive." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.Populate Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DirtyPagesEvicted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_DirtyPagesEvicted" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_DirtyPagesEvicted" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.DirtyPagesEvicted" /><MSHelp:TOCTitle Title="DirtyPagesEvicted Property " /><MSHelp:RLTitle Title="MPoolStats.DirtyPagesEvicted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.DirtyPagesEvicted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassDirtyPagesEvictedTopic" /><MSHelp:Keyword Index="K" Term="DirtyPagesEvicted property" /><MSHelp:Keyword Index="K" Term="MPoolStats.DirtyPagesEvicted property" /><MSHelp:Keyword Index="F" Term="DirtyPagesEvicted" /><MSHelp:Keyword Index="F" Term="MPoolStats.DirtyPagesEvicted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.DirtyPagesEvicted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.MPoolStats.DirtyPagesEvicted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_DirtyPagesEvicted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Dirty pages forced from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.DirtyPagesEvicted Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>LITTLE_ENDIAN Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_ByteOrder_LITTLE_ENDIAN" /><meta name="guid"
content="F_BerkeleyDB_ByteOrder_LITTLE_ENDIAN" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.ByteOrder.LITTLE_ENDIAN" /><MSHelp:TOCTitle Title="LITTLE_ENDIAN Field"
/><MSHelp:RLTitle Title="ByteOrder.LITTLE_ENDIAN Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.ByteOrder.LITTLE_ENDIAN" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBByteOrderClassLITTLE_ENDIANTopic" /><MSHelp:Keyword Index="K"
Term="LITTLE_ENDIAN field" /><MSHelp:Keyword Index="K" Term="ByteOrder.LITTLE_ENDIAN field"
/><MSHelp:Keyword Index="F" Term="LITTLE_ENDIAN" /><MSHelp:Keyword Index="F"
Term="ByteOrder.LITTLE_ENDIAN" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ByteOrder.LITTLE_ENDIAN" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ByteOrder.LITTLE_ENDIAN" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Little endian byte order" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder..::.LITTLE_ENDIAN Field</td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_HeapDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_HeapDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HeapDatabase" /><MSHelp:TOCTitle Title="HeapDatabase Members" /><MSHelp:RLTitle Title="HeapDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HeapDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabase class" /><MSHelp:Keyword Index="K" Term="HeapDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapDatabase class" /><MSHelp:Keyword Index="F" Term="HeapDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MultipleKeyDatabaseEntry Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="AllMembers_T_BerkeleyDB_MultipleKeyDatabaseEntry" /><meta name="guid"
content="AllMembers_T_BerkeleyDB_MultipleKeyDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID"
Value="AllMembers.T:BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:TOCTitle
Title="MultipleKeyDatabaseEntry Members" /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Members
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.MultipleKeyDatabaseEntry"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryMembersTopic"
/><MSHelp:Keyword Index="K" Term="MultipleKeyDatabaseEntry class" /><MSHelp:Keyword Index="K"
Term="MultipleKeyDatabaseEntry class,
all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MultipleKeyDatabaseEntry class"
/><MSHelp:Keyword Index="F" Term="MultipleKeyDatabaseEntry" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:Attr Name="HelpPriority" Value="1"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleKeyDatabaseEntry Members</td></tr><tr id="headerTableRow3"><td align="left">MultipleKeyDatabaseEntry Class Constructors Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><meta name="guid"

content="T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:TOCTitle
Title="SecondaryRecnoDatabaseConfig Class" /><MSHelp:RLTitle
Title="SecondaryRecnoDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryRecnoDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig class, about SecondaryRecnoDatabaseConfig class" /><MSHelp:Keyword
Index="F" Term="SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_FastStats" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="HashDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.FastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassFastStatsTopic" /><MSHelp:Keyword Index="K" Term="FastStats method" /><MSHelp:Keyword Index="K" Term="HashDatabase.FastStats method" /><MSHelp:Keyword Index="F" Term="FastStats" /><MSHelp:Keyword Index="F" Term="HashDatabase.FastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrefixCompare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_BTreeDatabase_PrefixCompare"
/><meta name="guid" content="P_BerkeleyDB_BTreeDatabase_PrefixCompare" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.BTreeDatabase.PrefixCompare" /><MSHelp:TOCTitle
Title="PrefixCompare Property " /><MSHelp:RLTitle Title="BTreeDatabase.PrefixCompare Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.PrefixCompare"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassPrefixCompareTopic"
/><MSHelp:Keyword Index="K" Term="PrefixCompare property" /><MSHelp:Keyword Index="K"
Term="BTreeDatabase.PrefixCompare property" /><MSHelp:Keyword Index="F" Term="PrefixCompare"
/><MSHelp:Keyword Index="F" Term="BTreeDatabase.PrefixCompare" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeDatabase.PrefixCompare" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.PrefixCompare" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.get_PrefixCompare" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.set_PrefixCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree prefix
function. The prefix function is used to determine the amount by which keys stored on the Btree internal pages can
be safely truncated without losing their uniqueness." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.PrefixCompare Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecoveryException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_RunRecoveryException" /><meta name="guid" content="Fields_T_BerkeleyDB_RunRecoveryException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.RunRecoveryException" /><MSHelp:TOCTitle Title="RunRecoveryException Fields" /><MSHelp:RLTitle Title="RunRecoveryException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.RunRecoveryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRunRecoveryExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RunRecoveryException Fields</td></tr><tr id="headerTableRow3"><td align="left">RunRecoveryException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetTxnTimeout Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Transaction_SetTxnTimeout" /><meta name="guid"
content="M_BerkeleyDB_Transaction_SetTxnTimeout" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Transaction.SetTxnTimeout(System.UInt32)" /><MSHelp:TOCTitle Title="SetTxnTimeout
Method " /><MSHelp:RLTitle Title="Transaction.SetTxnTimeout Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.Transaction.SetTxnTimeout(System.UInt32)" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionClassSetTxnTimeoutTopic" /><MSHelp:Keyword Index="K"
Term="SetTxnTimeout method" /><MSHelp:Keyword Index="K" Term="Transaction.SetTxnTimeout method"
/><MSHelp:Keyword Index="F" Term="SetTxnTimeout" /><MSHelp:Keyword Index="F"
Term="Transaction.SetTxnTimeout" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Transaction.SetTxnTimeout"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.SetTxnTimeout"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Set the timeout value for transactions for this transaction."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"

value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.SetTxnTimeout Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabaseConfig_PadByte" /><meta name="guid" content="P_BerkeleyDB_QueueDatabaseConfig_PadByte" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueDatabaseConfig.PadByte" /><MSHelp:TOCTitle Title="PadByte Property " /><MSHelp:RLTitle Title="QueueDatabaseConfig.PadByte Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabaseConfig.PadByte" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassPadByteTopic" /><MSHelp:Keyword Index="K" Term="PadByte property" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig.PadByte property" /><MSHelp:Keyword Index="F" Term="PadByte" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig.PadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.get_PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.set_PadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_GetBothMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Database_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.GetBothMultiple" /><MSHelp:TOCTitle Title="GetBothMultiple Method " /><MSHelp:RLTitle Title="Database.GetBothMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.GetBothMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassGetBothMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetBothMultiple method" /><MSHelp:Keyword Index="K" Term="Database.GetBothMultiple method" /><MSHelp:Keyword Index="F" Term="GetBothMultiple" /><MSHelp:Keyword Index="F" Term="Database.GetBothMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetBothMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesInCache Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_PagesInCache" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_PagesInCache" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.PagesInCache" /><MSHelp:TOCTitle Title="PagesInCache Property " /><MSHelp:RLTitle Title="MPoolFileStats.PagesInCache Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.PagesInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassPagesInCacheTopic" /><MSHelp:Keyword Index="K" Term="PagesInCache property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.PagesInCache property" /><MSHelp:Keyword Index="F" Term="PagesInCache" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.PagesInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.PagesInCache" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.PagesInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_PagesInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages found in the cache."

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.PagesInCache Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LoggingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_LoggingSystemStats" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_LoggingSystemStats" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:TOCTitle
Title="LoggingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LoggingSystemStats
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LoggingSystemStats" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The logging subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LoggingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSite Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DbSite" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DbSite" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DbSite" /><MSHelp:TOCTitle Title="DbSite Members" /><MSHelp:RLTitle Title="DbSite Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DbSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteMembersTopic" /><MSHelp:Keyword Index="K" Term="DbSite class" /><MSHelp:Keyword Index="K" Term="DbSite class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbSite class" /><MSHelp:Keyword Index="F" Term="DbSite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this,
'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite Members</td></tr><tr id="headerTableRow3"><td align="left">DbSite Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method (Database, ForeignKeyDeleteAction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta
name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_SecondaryDatabaseConfig_SetForeignKeyConstraint" /><meta name="guid"
content="M_BerkeleyDB_SecondaryDatabaseConfig_SetForeignKeyConstraint" /><xml><MSHelp:Attr
Name="AssetID"
Value="M:BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint(BerkeleyDB.Database,BerkeleyDB.Fo
reignKeyDeleteAction)" /><MSHelp:TOCTitle Title="SetForeignKeyConstraint Method (Database,
ForeignKeyDeleteAction)" /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.SetForeignKeyConstraint
Method (Database, ForeignKeyDeleteAction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint(BerkeleyDB.Database,BerkeleyDB.Fo
reignKeyDeleteAction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr Name="DevLang"
Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify the action
taken when a referenced record in the foreign key database is deleted." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryDatabaseConfig.<span
class="vb">.::.SetForeignKeyConstraint
Method (Database, ForeignKeyDeleteAction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryDatabaseConfig.htm">SecondaryDatabaseConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFile Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_LogFile" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_LogFile" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.LogFile(BerkeleyDB.LSN)" /><MSHelp:TOCTitle Title="LogFile
Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogFile Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LogFile(BerkeleyDB.LSN)" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogFileTopic" /><MSHelp:Keyword Index="K"
Term="LogFile method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogFile method"
/><MSHelp:Keyword Index="F" Term="LogFile" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.LogFile"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogFile" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogFile" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Map an LSN object to a log filename" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;"

src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td>
<label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogFile Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method (String, DatabaseConfig, Boolean, Boolean, TextWriter)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Salvage_3" /><meta name="guid" content="M_BerkeleyDB_Database_Salvage_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean,System.Boolean,System.IO.TextWriter)" /><MSHelp:TOCTitle Title="Salvage Method (String, DatabaseConfig, Boolean, Boolean, TextWriter)" /><MSHelp:RLTitle Title="Database.Salvage Method (String, DatabaseConfig, Boolean, Boolean, TextWriter) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean,System.Boolean,System.IO.TextWriter)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Salvage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Write the key/data pairs from all databases in the file to . Key values are written for Btree, Hash and Queue databases, but not for Recno databases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">Database.<span
class="vb">.::.Salvage Method (String,
DatabaseConfig, Boolean, Boolean, TextWriter)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method
</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Exists" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method "
/><MSHelp:RLTitle
Title="SecondaryBTreeDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Exists" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K"
Term="Exists method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Exists method"
/><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabase.Exists" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseFeedbackDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="T_BerkeleyDB_DatabaseFeedbackDelegate" /><meta name="guid"
content="T_BerkeleyDB_DatabaseFeedbackDelegate" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.DatabaseFeedbackDelegate" /><MSHelp:TOCTitle Title="DatabaseFeedbackDelegate
Delegate" /><MSHelp:RLTitle Title="DatabaseFeedbackDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="T:BerkeleyDB.DatabaseFeedbackDelegate" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseFeedbackDelegateClassTopic" /><MSHelp:Keyword Index="K"
Term="DatabaseFeedbackDelegate delegate" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.DatabaseFeedbackDelegate delegate" /><MSHelp:Keyword Index="F"
Term="DatabaseFeedbackDelegate" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseFeedbackDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackDelegate"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackDelegate.ctor" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseFeedbackDelegate.Invoke"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackDelegate.BeginInvoke"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackDelegate.EndInvoke" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The application-specified feedback function called to report Berkeley DB operation
progress." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseFeedbackDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevUnique_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevUnique_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MovePrevUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and store that key and associated datum in . Mo ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevUnique Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunFatalRecovery Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RunFatalRecovery" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RunFatalRecovery" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RunFatalRecovery" /><MSHelp:TOCTitle Title="RunFatalRecovery Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RunFatalRecovery Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RunFatalRecovery" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRunFatalRecoveryTopic" /><MSHelp:Keyword Index="K" Term="RunFatalRecovery property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RunFatalRecovery property" /><MSHelp:Keyword Index="F" Term="RunFatalRecovery" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RunFatalRecovery" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RunFatalRecovery" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RunFatalRecovery" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RunFatalRecovery" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, catastrophic recovery was run on this environment before opening it for normal use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment<span
class="languageSpecificText">..<span
class="cpp">::.RunFatalRecovery Property </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MutexIncrement Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_MutexIncrement" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_MutexIncrement" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.MutexIncrement" /><MSHelp:TOCTitle Title="MutexIncrement
Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MutexIncrement Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MutexIncrement"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMutexIncrementTopic"
/><MSHelp:Keyword Index="K" Term="MutexIncrement property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.MutexIncrement property" /><MSHelp:Keyword Index="F"
Term="MutexIncrement" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MutexIncrement"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MutexIncrement" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MutexIncrement" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MutexIncrement" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MutexIncrement" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The number of additional mutexes allocated." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MutexIncrement Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"

Value="Methods.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryQueueDatabaseConfig Methods " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig
 class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"
 src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
 /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
 none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RemoveDB Method (String, String, Boolean, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB_3" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RemoveDB_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="RemoveDB Method (String, String, Boolean, Transaction)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RemoveDB Method (String, String, Boolean, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RemoveDB(System.String,System.String,System.Boolean,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RemoveDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the database specified by and . If no database is specified, the underlying file represented by is removed, incidentally removing all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RemoveDB Method (String, String, Boolean, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevDuplicate_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevDuplicate_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MovePrevDuplicate Method

(LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MovePrevDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrevDuplicate"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record
for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and that pair is stored
in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span
class="languageSpecificText">..<span
class="cpp">::.MovePrevDuplicate
Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveFirstMultiple" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveFirstMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveFirstMultiple" /><MSHelp:TOCTitle Title="MoveFirstMultiple Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveFirstMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveFirstMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveFirstMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveFirstMultiple method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveFirstMultiple method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultiple" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveFirstMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveFirstMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveFirstMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_Move" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.Move" /><MSHelp:TOCTitle Title="Move Method " /><MSHelp:RLTitle Title="RecnoCursor.Move Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.Move" /><MSHelp:Keyword

Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveTopic" /><MSHelp:Keyword Index="K" Term="Move method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.Move method" /><MSHelp:Keyword Index="F" Term="Move" /><MSHelp:Keyword Index="F" Term="RecnoCursor.Move" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input

id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.Move Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and the secondary key and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"

title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironment Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DatabaseEnvironment" /><meta name="guid" content="Methods_T_BerkeleyDB_DatabaseEnvironment" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:TOCTitle Title="DatabaseEnvironment Methods " /><MSHelp:RLTitle Title="DatabaseEnvironment Methods (BerkeleyDB)" /><MSHelp:Keyword

Index="A" Term="Methods.T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentMethodsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"

/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment Methods </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, HeapDatabaseConfig)</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Open(System.String,BerkeleyDB.HeapDatabaseConfig)" /><MSHelp:TOCTitle Title="Open
Method (String, HeapDatabaseConfig)" /><MSHelp:RLTitle Title="HeapDatabase.Open Method (String, HeapDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Open(System.String,BerkeleyDB.HeapDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HeapDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HeapDatabase.<span
class="vb">.::.Open Method (String,
HeapDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HeapDatabase.htm">HeapDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabase_Duplicates"
/><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabase_Duplicates" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabase.Duplicates" /><MSHelp:TOCTitle
Title="Duplicates Property " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Duplicates
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SecondaryHashDatabase.Duplicates" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryHashDatabaseClassDuplicatesTopic" /><MSHelp:Keyword Index="K"

Term="Duplicates property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Duplicates property" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.Duplicates" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.get_Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the insertion of duplicate data items in the database is permitted, and whether duplicates items are sorted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Duplicates Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_SecondaryHashDatabase.htm">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Name Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ActiveTransaction_Name" /><meta name="guid"
content="P_BerkeleyDB_ActiveTransaction_Name" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ActiveTransaction.Name" /><MSHelp:TOCTitle Title="Name Property "
/><MSHelp:RLTitle Title="ActiveTransaction.Name Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ActiveTransaction.Name" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBActiveTransactionClassNameTopic" /><MSHelp:Keyword Index="K" Term="Name
property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.Name property" /><MSHelp:Keyword
Index="F" Term="Name" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.Name" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.ActiveTransaction.Name" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ActiveTransaction.Name"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_Name" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If a name was specified for the transaction, up to the first 50 bytes of that name."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"

style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction..::.Name Property </td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="BTreeDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase<span

class="cs">..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Discard Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Transaction_Discard" /><meta name="guid" content="M_BerkeleyDB_Transaction_Discard" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Transaction.Discard" /><MSHelp:TOCTitle Title="Discard Method " /><MSHelp:RLTitle Title="Transaction.Discard Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Transaction.Discard" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassDiscardTopic" /><MSHelp:Keyword Index="K" Term="Discard method" /><MSHelp:Keyword Index="K" Term="Transaction.Discard method" /><MSHelp:Keyword Index="F" Term="Discard" /><MSHelp:Keyword Index="F" Term="Transaction.Discard" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Discard" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Discard" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Free up all the per-process resources associated with the specified Transaction instance, neither committing nor aborting the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Discard Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_nRecords" /><meta name="guid" content="P_BerkeleyDB_HeapStats_nRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.nRecords" /><MSHelp:TOCTitle Title="nRecords Property " /><MSHelp:RLTitle Title="HeapStats.nRecords Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.nRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassnRecordsTopic" /><MSHelp:Keyword Index="K" Term="nRecords property" /><MSHelp:Keyword Index="K" Term="HeapStats.nRecords property" /><MSHelp:Keyword Index="F" Term="nRecords" /><MSHelp:Keyword Index="F" Term="HeapStats.nRecords"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.nRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.nRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_nRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reports the number of records in the Heap database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats..::.nRecords Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_NOSERVER Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_NOSERVER" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_NOSERVER" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_NOSERVER" /><MSHelp:TOCTitle Title="DB_NOSERVER Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_NOSERVER Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_NOSERVER" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_NOSERVERTopic" /><MSHelp:Keyword Index="K" Term="DB_NOSERVER field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_NOSERVER field" /><MSHelp:Keyword Index="F" Term="DB_NOSERVER" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_NOSERVER" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_NOSERVER" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_NOSERVER" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Server panic return." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_NOSERVER Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_PutNoDuplicate_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_PutNoDuplicate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.PutNoDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair in the database only if it does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultipleKey is identical to . Otherwise, move the cursor to the next non-duplicate key in the database, and store that key and associated datum a ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUniqueMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MinKey Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_MinKey" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_MinKey" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.MinKey" /><MSHelp:TOCTitle Title="MinKey Property " /><MSHelp:RLTitle Title="RecnoStats.MinKey Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.MinKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassMinKeyTopic" /><MSHelp:Keyword Index="K" Term="MinKey property" /><MSHelp:Keyword Index="K" Term="RecnoStats.MinKey property" /><MSHelp:Keyword Index="F" Term="MinKey" /><MSHelp:Keyword Index="F" Term="RecnoStats.MinKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.MinKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.MinKey" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_MinKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Minkey value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.MinKey Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SystemMemory Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_SystemMemory" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_SystemMemory" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.DatabaseEnvironment.SystemMemory" /><MSHelp:TOCTitle Title="SystemMemory Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.SystemMemory Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.SystemMemory" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassSystemMemoryTopic" /><MSHelp:Keyword Index="K" Term="SystemMemory property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.SystemMemory property" /><MSHelp:Keyword Index="F" Term="SystemMemory" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.SystemMemory" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.SystemMemory" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SystemMemory" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_SystemMemory" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, allocate region memory from system shared memory instead of from heap memory or memory backed by the filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SystemMemory Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_DuplicatePages" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_DuplicatePages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.DuplicatePages" /><MSHelp:TOCTitle Title="DuplicatePages Property " /><MSHelp:RLTitle Title="ReplicationStats.DuplicatePages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.DuplicatePages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassDuplicatePagesTopic" /><MSHelp:Keyword Index="K" Term="DuplicatePages property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.DuplicatePages property" /><MSHelp:Keyword Index="F" Term="DuplicatePages" /><MSHelp:Keyword Index="F" Term="ReplicationStats.DuplicatePages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.DuplicatePages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.DuplicatePages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_DuplicatePages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages received multiply."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"

src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.DuplicatePages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveLast" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveLast" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:TOCTitle Title="MoveLast Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveLast Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr

Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store the secondary key and primary key/data pair in . If the last key has duplicate values, the last data item in the set of ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveLast Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_MoveNext" /><meta name="guid" content="M_BerkeleyDB_JoinCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="JoinCursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Iterate over the values associated with the keys to which each passed to was initialized. Any data value that appears in all s is then used as a key into the primary, and the key/da ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EndLsn Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_EndLsn" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_EndLsn" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.EndLsn" /><MSHelp:TOCTitle Title="EndLsn Property " /><MSHelp:RLTitle Title="LogVerifyConfig.EndLsn Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.EndLsn" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassEndLsnTopic" /><MSHelp:Keyword Index="K" Term="EndLsn property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.EndLsn property" /><MSHelp:Keyword Index="F" Term="EndLsn" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.EndLsn" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.EndLsn" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.EndLsn" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_EndLsn" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_EndLsn" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The ending lsn to verify." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.EndLsn Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Timeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DbChannel_Timeout" /><meta name="guid" content="P_BerkeleyDB_DbChannel_Timeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbChannel.Timeout" /><MSHelp:TOCTitle Title="Timeout Property " /><MSHelp:RLTitle Title="DbChannel.Timeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbChannel.Timeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelClassTimeoutTopic" /><MSHelp:Keyword Index="K" Term="Timeout property" /><MSHelp:Keyword Index="K" Term="DbChannel.Timeout property" /><MSHelp:Keyword Index="F" Term="Timeout" /><MSHelp:Keyword Index="F" Term="DbChannel.Timeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbChannel.Timeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.Timeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.get_Timeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.set_Timeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the default timeout value. It is used by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.Timeout Property </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Database Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_Database" /><meta name="guid" content="Properties_T_BerkeleyDB_Database" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.Database" /><MSHelp:TOCTitle Title="Database Properties " /><MSHelp:RLTitle Title="Database Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.Database" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="Database class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database Properties </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Feedback Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Feedback" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_Feedback" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.BaseDatabase.Feedback" /><MSHelp:TOCTitle Title="Feedback Property "
/><MSHelp:RLTitle
Title="BaseDatabase.Feedback Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.Feedback" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassFeedbackTopic" /><MSHelp:Keyword Index="K" Term="Feedback
property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Feedback property" /><MSHelp:Keyword
Index="F" Term="Feedback" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Feedback"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Feedback" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BaseDatabase.Feedback" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_Feedback" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.set_Feedback" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Monitor progress within long running operations." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Feedback Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UsingMPool Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UsingMPool" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UsingMPool" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UsingMPool" /><MSHelp:TOCTitle Title="UsingMPool Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UsingMPool Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UsingMPool" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUsingMPoolTopic" /><MSHelp:Keyword Index="K" Term="UsingMPool property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UsingMPool property" /><MSHelp:Keyword Index="F" Term="UsingMPool" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UsingMPool" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UsingMPool" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UsingMPool" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UsingMPool" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the shared memory buffer pool subsystem was initialized." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UsingMPool Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogAutoRemove Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogAutoRemove" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogAutoRemove" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogAutoRemove" /><MSHelp:TOCTitle Title="LogAutoRemove Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogAutoRemove Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogAutoRemove" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogAutoRemoveTopic"

/><MSHelp:Keyword Index="K" Term="LogAutoRemove property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogAutoRemove property" /><MSHelp:Keyword Index="F" Term="LogAutoRemove" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogAutoRemove" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogAutoRemove" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogAutoRemove" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogAutoRemove" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogAutoRemove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will automatically remove log files that are no longer needed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment<span

class="cs">..::.LogAutoRemove Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNextDuplicateMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNextDuplicateMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextDuplicateMultiple" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultiple Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextDuplicateMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextDuplicateMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected
Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextDuplicateMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesCheckedDuringAlloc Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesCheckedDuringAlloc"
/><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesCheckedDuringAlloc" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesCheckedDuringAlloc" /><MSHelp:TOCTitle
Title="PagesCheckedDuringAlloc Property " /><MSHelp:RLTitle Title="MPoolStats.PagesCheckedDuringAlloc
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.MPoolStats.PagesCheckedDuringAlloc" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMPoolStatsClassPagesCheckedDuringAllocTopic" /><MSHelp:Keyword Index="K"
Term="PagesCheckedDuringAlloc property" /><MSHelp:Keyword Index="K"
Term="MPoolStats.PagesCheckedDuringAlloc property" /><MSHelp:Keyword Index="F"
Term="PagesCheckedDuringAlloc" /><MSHelp:Keyword Index="F"
Term="MPoolStats.PagesCheckedDuringAlloc" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.MPoolStats.PagesCheckedDuringAlloc"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.PagesCheckedDuringAlloc" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MPoolStats.get_PagesCheckedDuringAlloc" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Pages checked during allocation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label> <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">MPoolStats.<span
class="vb">.::<span
class="nu">.PagesCheckedDuringAlloc Property </td></tr><tr
id="headerTableRow3"><td align="left">MPoolStats Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MultipleKeyDatabaseEntry Methods </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_MultipleKeyDatabaseEntry" /><meta name="guid"
content="Methods_T_BerkeleyDB_MultipleKeyDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:TOCTitle
Title="MultipleKeyDatabaseEntry Methods " /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Methods
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.MultipleKeyDatabaseEntry"
/><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryMethodsTopic" /><MSHelp:Keyword Index="K"
Term="MultipleKeyDatabaseEntry class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown"
 class="filter" tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All
 </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
 for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MultipleKeyDatabaseEntry Methods </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_MultipleKeyDatabaseEntry.htm">MultipleKeyDatabaseEntry Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See
 Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintMutexSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintMutexSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintMutexSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:TOCTitle Title="PrintMutexSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintMutexSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the mutex subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintMutexSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetThreadName Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_SetThreadName" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_SetThreadName" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.SetThreadName" /><MSHelp:TOCTitle Title="SetThreadName Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.SetThreadName Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.SetThreadName" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassSetThreadNameTopic" /><MSHelp:Keyword Index="K" Term="SetThreadName property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.SetThreadName property" /><MSHelp:Keyword Index="F" Term="SetThreadName" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.SetThreadName" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.SetThreadName" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SetThreadName" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_SetThreadName" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_SetThreadName" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A delegate that formats a process ID and thread ID identifier pair." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input

type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SetThreadName Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleDatabaseEntry Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_MultipleDatabaseEntry" /><meta name="guid"
content="Methods_T_BerkeleyDB_MultipleDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:TOCTitle Title="MultipleDatabaseEntry
Methods " /><MSHelp:RLTitle Title="MultipleDatabaseEntry Methods (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Methods.T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMultipleDatabaseEntryMethodsTopic" /><MSHelp:Keyword Index="K"
Term="MultipleDatabaseEntry class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Methods </td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicateCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_HashDatabaseConfig_DuplicateCompare" /><meta name="guid" content="F_BerkeleyDB_HashDatabaseConfig_DuplicateCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.HashDatabaseConfig.DuplicateCompare" /><MSHelp:TOCTitle Title="DuplicateCompare Field" /><MSHelp:RLTitle Title="HashDatabaseConfig.DuplicateCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.HashDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassDuplicateCompareTopic" /><MSHelp:Keyword Index="K" Term="DuplicateCompare field" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.DuplicateCompare field" /><MSHelp:Keyword Index="F" Term="DuplicateCompare" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..::.DuplicateCompare Field</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockPuts Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockPuts" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockPuts" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockPuts" /><MSHelp:TOCTitle Title="LockPuts Property " /><MSHelp:RLTitle
Title="LockStats.LockPuts Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockPuts" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockPutsTopic" /><MSHelp:Keyword Index="K" Term="LockPuts property" /><MSHelp:Keyword Index="K" Term="LockStats.LockPuts property" /><MSHelp:Keyword Index="F" Term="LockPuts" /><MSHelp:Keyword Index="F" Term="LockStats.LockPuts" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockPuts" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockPuts" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockPuts" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Number of lock puts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockPuts Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSettings Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_CacheSettings" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_CacheSettings" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.CacheSettings" /><MSHelp:TOCTitle Title="CacheSettings Property " /><MSHelp:RLTitle Title="MPoolStats.CacheSettings Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.CacheSettings" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassCacheSettingsTopic" /><MSHelp:Keyword Index="K" Term="CacheSettings property" /><MSHelp:Keyword Index="K" Term="MPoolStats.CacheSettings property" /><MSHelp:Keyword Index="F" Term="CacheSettings" /><MSHelp:Keyword Index="F" Term="MPoolStats.CacheSettings" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.CacheSettings" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.CacheSettings" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_CacheSettings" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total cache size and number of regions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.CacheSettings Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryRecnoDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryRecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryRecnoDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Open Method (String, String, SecondaryRecnoDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryRecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryRecnoDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">SecondaryRecnoDatabase..::.Open Method (String, String, SecondaryRecnoDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Refresh" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="SecondaryCursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the secondary key and primary key/data pair to which the cursor refers in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Refresh Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TimeNotGranted Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TimeNotGranted" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TimeNotGranted" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.TimeNotGranted" /><MSHelp:TOCTitle Title="TimeNotGranted Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TimeNotGranted Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.TimeNotGranted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTimeNotGrantedTopic" /><MSHelp:Keyword Index="K" Term="TimeNotGranted field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TimeNotGranted field" /><MSHelp:Keyword Index="F" Term="TimeNotGranted" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TimeNotGranted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TimeNotGranted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TimeNotGranted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, database calls timing out based on lock or transaction timeout values will throw instead of . This allows applications to distinguish between operations which have deadlocked and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TimeNotGranted Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_SecondaryRecnoDatabaseConfig_Length" /><meta name="guid"
content="P_BerkeleyDB_SecondaryRecnoDatabaseConfig_Length" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryRecnoDatabaseConfig.Length" /><MSHelp:TOCTitle
Title="Length Property " /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.Length Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabaseConfig.Length"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassLengthTopic"
/><MSHelp:Keyword Index="K" Term="Length property" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig.Length property" /><MSHelp:Keyword Index="F" Term="Length"
/><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.Length" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.Length" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.Length" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.get_Length" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.set_Length"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Specify that the records are fixed-length, not byte-delimited, and are of
length Length." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Clockskew Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationConfig_Clockskew" /><meta name="guid" content="M_BerkeleyDB_ReplicationConfig_Clockskew" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationConfig.Clockskew(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="Clockskew Method " /><MSHelp:RLTitle Title="ReplicationConfig.Clockskew Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationConfig.Clockskew(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassClockskewTopic" /><MSHelp:Keyword Index="K" Term="Clockskew method" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.Clockskew method" /><MSHelp:Keyword Index="F" Term="Clockskew" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.Clockskew" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.Clockskew" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.Clockskew" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the clock skew ratio among replication group members based on the fastest and slowest measurements among the group for use with master leases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.Clockskew Method </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_ReplicationSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_ReplicationSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats(System.Boolean)" /><MSHelp:TOCTitle Title="ReplicationSystemStats Method (Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.ReplicationSystemStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The replication subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ReplicationSystemStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicateCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_DuplicateCompare" /><meta name="guid" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_DuplicateCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryHashDatabaseConfig.DuplicateCompare" /><MSHelp:TOCTitle Title="DuplicateCompare Field" /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.DuplicateCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryHashDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassDuplicateCompareTopic" /><MSHelp:Keyword Index="K" Term="DuplicateCompare field" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.DuplicateCompare field" /><MSHelp:Keyword Index="F" Term="DuplicateCompare" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.DuplicateCompare Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_Database_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="Database.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="Database.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="Database.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered
</nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">..<span
class="cpp">::.PrintFastStats Method </td></tr><tr
id="headerTableRow3"><td align="left">Database Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MaxObjectsInBucket Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxObjectsInBucket" /><meta
name="guid" content="P_BerkeleyDB_LockStats_MaxObjectsInBucket" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.MaxObjectsInBucket" /><MSHelp:TOCTitle Title="MaxObjectsInBucket
Property " /><MSHelp:RLTitle Title="LockStats.MaxObjectsInBucket Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxObjectsInBucket" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxObjectsInBucketTopic" /><MSHelp:Keyword Index="K"
Term="MaxObjectsInBucket property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxObjectsInBucket
property" /><MSHelp:Keyword Index="F" Term="MaxObjectsInBucket" /><MSHelp:Keyword Index="F"
Term="LockStats.MaxObjectsInBucket" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockStats.MaxObjectsInBucket" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockStats.MaxObjectsInBucket" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.get_MaxObjectsInBucket" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of objectsin any bucket." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxObjectsInBucket Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>HashDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_HashDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_HashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:TOCTitle Title="HashDatabaseConfig Properties " /><MSHelp:RLTitle Title="HashDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_Cursor" /><meta name="guid" content="Properties_T_BerkeleyDB_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.Cursor" /><MSHelp:TOCTitle Title="Cursor Properties " /><MSHelp:RLTitle Title="Cursor Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorPropertiesTopic" /><MSHelp:Keyword Index="K" Term="Cursor class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor Properties </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="RecnoDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_ReplicationConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_ReplicationConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.ReplicationConfig" /><MSHelp:TOCTitle Title="ReplicationConfig Fields" /><MSHelp:RLTitle Title="ReplicationConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.ReplicationConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Bytes Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CacheInfo_Bytes" /><meta name="guid" content="F_BerkeleyDB_CacheInfo_Bytes" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CacheInfo.Bytes" /><MSHelp:TOCTitle Title="Bytes Field" /><MSHelp:RLTitle Title="CacheInfo.Bytes Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CacheInfo.Bytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoClassBytesTopic" /><MSHelp:Keyword Index="K" Term="Bytes field" /><MSHelp:Keyword Index="K" Term="CacheInfo.Bytes field" /><MSHelp:Keyword Index="F" Term="Bytes" /><MSHelp:Keyword Index="F" Term="CacheInfo.Bytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CacheInfo.Bytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CacheInfo.Bytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of bytes in the cache" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"

/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CacheInfo..::.Bytes Field</td></tr><tr id="headerTableRow3"><td align="left">CacheInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirst_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirst_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirst Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveFirst Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirst(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirst"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair in . If the first key has duplicate values, the first data item in the set of duplicates is stored in . If e ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirst Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLockers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxLockers" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxLockers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxLockers" /><MSHelp:TOCTitle Title="MaxLockers Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxLockers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxLockers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxLockersTopic" /><MSHelp:Keyword Index="K" Term="MaxLockers property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxLockers property" /><MSHelp:Keyword Index="F" Term="MaxLockers" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxLockers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxLockers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxLockers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxLockers" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxLockers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum number of locking entities supported by the Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label

id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxLockers Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Refresh_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Refresh_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Refresh(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Refresh Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.Refresh Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Refresh(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the secondary key and primary key/data pair to which the cursor refers in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Refresh Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="P_BerkeleyDB_BaseDatabase_Creation" /><meta name="guid"
content="P_BerkeleyDB_BaseDatabase_Creation" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BaseDatabase.Creation" /><MSHelp:TOCTitle Title="Creation Property "
/><MSHelp:RLTitle Title="BaseDatabase.Creation Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.Creation" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation
property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Creation property" /><MSHelp:Keyword
Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Creation"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Creation" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BaseDatabase.Creation" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_Creation"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The CreatePolicy with which this database was opened."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Creation Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesRead Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesRead" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesRead" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesRead" /><MSHelp:TOCTitle Title="PagesRead Property " /><MSHelp:RLTitle Title="MPoolStats.PagesRead Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PagesRead" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesReadTopic" /><MSHelp:Keyword Index="K" Term="PagesRead property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PagesRead property" /><MSHelp:Keyword Index="F" Term="PagesRead" /><MSHelp:Keyword Index="F" Term="MPoolStats.PagesRead" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PagesRead" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PagesRead" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PagesRead" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages read in." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PagesRead Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_Sequence" /><meta name="guid" content="Methods_T_BerkeleyDB_Sequence" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.Sequence" /><MSHelp:TOCTitle Title="Sequence Methods " /><MSHelp:RLTitle Title="Sequence Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.Sequence" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceMethodsTopic" /><MSHelp:Keyword Index="K" Term="Sequence class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence

Methods </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerificationException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_VerificationException" /><meta name="guid" content="Fields_T_BerkeleyDB_VerificationException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.VerificationException" /><MSHelp:TOCTitle Title="VerificationException Fields" /><MSHelp:RLTitle Title="VerificationException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.VerificationException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerificationExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="VerificationException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">VerificationException Fields</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_VerificationException.htm">VerificationException Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryRecnoDatabaseConfig_PadByte"
/><meta name="guid" content="P_BerkeleyDB_SecondaryRecnoDatabaseConfig_PadByte" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.SecondaryRecnoDatabaseConfig.PadByte" /><MSHelp:TOCTitle
Title="PadByte Property " /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.PadByte
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SecondaryRecnoDatabaseConfig.PadByte" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassPadByteTopic" /><MSHelp:Keyword Index="K" Term="PadByte property" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig.PadByte property" /><MSHelp:Keyword Index="F" Term="PadByte" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.PadByte" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.get_PadByte" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.set_PadByte" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig<span

class="cs">..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockerCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockingConfig_InitLockerCount" /><meta name="guid" content="P_BerkeleyDB_LockingConfig_InitLockerCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockingConfig.InitLockerCount" /><MSHelp:TOCTitle Title="InitLockerCount Property " /><MSHelp:RLTitle Title="LockingConfig.InitLockerCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockingConfig.InitLockerCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigClassInitLockerCountTopic" /><MSHelp:Keyword Index="K" Term="InitLockerCount property" /><MSHelp:Keyword Index="K" Term="LockingConfig.InitLockerCount property" /><MSHelp:Keyword Index="F" Term="InitLockerCount" /><MSHelp:Keyword Index="F" Term="LockingConfig.InitLockerCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.InitLockerCount"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.InitLockerCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.get_InitLockerCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.set_InitLockerCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of simultaneous locking entities created by the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.InitLockerCount Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseCursor_Delete" /><meta name="guid" content="M_BerkeleyDB_BaseCursor_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseCursor.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="BaseCursor.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseCursor.Delete" /><MSHelp:Keyword

Index="A" Term="frlrfBerkeleyDBBaseCursorClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="BaseCursor.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="BaseCursor.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseCursor.Delete" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseCursor.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Delete the key/data pair to which the cursor refers. When called on a SecondaryCursor, delete the key/data pair from the primary database and all secondary indices. ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_BaseCursor.htm">BaseCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8"
/><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryHashDatabase_GetBoth" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryHashDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryHashDatabase.GetBoth"
/><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.GetBoth
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.SecondaryHashDatabase.GetBoth" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryHashDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K"
Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.GetBoth method"
/><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F"
Term="SecondaryHashDatabase.GetBoth" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryHashDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultiple Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_Cursor_MoveFirstMultiple_2"
/><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultiple_2" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultiple(System.Int32)" /><MSHelp:TOCTitle
Title="MoveFirstMultiple Method (Int32)" /><MSHelp:RLTitle Title="Cursor.MoveFirstMultiple Method (Int32)
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultiple(System.Int32)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultiple"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store
that key and as many duplicate
data items that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span
class="languageSpecificText">..<span

class="cpp">::.MoveFirstMultiple Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSequentialWrites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolConfig_MaxSequentialWrites" /><meta name="guid" content="P_BerkeleyDB_MPoolConfig_MaxSequentialWrites"
 /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolConfig.MaxSequentialWrites" /><MSHelp:TOCTitle Title="MaxSequentialWrites Property " /><MSHelp:RLTitle Title="MPoolConfig.MaxSequentialWrites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolConfig.MaxSequentialWrites" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassMaxSequentialWritesTopic" /><MSHelp:Keyword Index="K" Term="MaxSequentialWrites property" /><MSHelp:Keyword Index="K" Term="MPoolConfig.MaxSequentialWrites property" /><MSHelp:Keyword Index="F" Term="MaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="MPoolConfig.MaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.MaxSequentialWrites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.MaxSequentialWrites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig.get_MaxSequentialWrites"
 /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of sequential write operations scheduled by the library when flushing dirty pages from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
 id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig..::.MaxSequentialWrites Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatesPolicy Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DuplicatesPolicy" /><meta name="guid" content="T_BerkeleyDB_DuplicatesPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DuplicatesPolicy" /><MSHelp:TOCTitle Title="DuplicatesPolicy Enumeration" /><MSHelp:RLTitle Title="DuplicatesPolicy Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DuplicatesPolicy" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DuplicatesPolicy.NONE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DuplicatesPolicy.SORTED" /><MSHelp:Keyword Index="A"

Term="F:BerkeleyDB.DuplicatesPolicy.UNSORTED" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDuplicatesPolicyClassTopic" /><MSHelp:Keyword Index="K" Term="DuplicatesPolicy enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DuplicatesPolicy enumeration" /><MSHelp:Keyword Index="K" Term="NONE enumeration member" /><MSHelp:Keyword Index="K" Term="SORTED enumeration member" /><MSHelp:Keyword Index="K" Term="UNSORTED enumeration member" /><MSHelp:Keyword Index="F" Term="DuplicatesPolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DuplicatesPolicy" /><MSHelp:Keyword Index="F" Term="DuplicatesPolicy.NONE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DuplicatesPolicy.NONE" /><MSHelp:Keyword Index="F" Term="DuplicatesPolicy.SORTED" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DuplicatesPolicy.SORTED" /><MSHelp:Keyword Index="F" Term="DuplicatesPolicy.UNSORTED" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DuplicatesPolicy.UNSORTED" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DuplicatesPolicy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DuplicatesPolicy.NONE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DuplicatesPolicy.SORTED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DuplicatesPolicy.UNSORTED" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Policy for duplicate data items in the database; that is, whether insertion when the key of the key/data pair being inserted already exists in the database will be successful." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DuplicatesPolicy Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepProcMsgResult Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RepProcMsgResult" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RepProcMsgResult" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RepProcMsgResult" /><MSHelp:TOCTitle Title="RepProcMsgResult Members" /><MSHelp:RLTitle Title="RepProcMsgResult Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RepProcMsgResult" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultMembersTopic" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult class" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RepProcMsgResult class" /><MSHelp:Keyword Index="F" Term="RepProcMsgResult" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepProcMsgResult" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepProcMsgResult Members</td></tr><tr id="headerTableRow3"><td align="left">RepProcMsgResult Class
  Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NotFoundException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_NotFoundException" /><meta name="guid" content="Properties_T_BerkeleyDB_NotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.NotFoundException" /><MSHelp:TOCTitle Title="NotFoundException Properties " /><MSHelp:RLTitle Title="NotFoundException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.NotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotFoundExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="NotFoundException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">NotFoundException Properties </td></tr><tr id="headerTableRow3"><td align="left">NotFoundException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PreparedTransaction Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_PreparedTransaction" /><meta name="guid" content="Methods_T_BerkeleyDB_PreparedTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.PreparedTransaction" /><MSHelp:TOCTitle Title="PreparedTransaction Methods " /><MSHelp:RLTitle Title="PreparedTransaction Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.PreparedTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPreparedTransactionMethodsTopic" /><MSHelp:Keyword Index="K" Term="PreparedTransaction class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox"
data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PreparedTransaction Methods </td></tr><tr id="headerTableRow3"><td align="left">PreparedTransaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogInMemory Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogInMemory" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogInMemory" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogInMemory" /><MSHelp:TOCTitle Title="LogInMemory Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogInMemory Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogInMemory" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogInMemoryTopic" /><MSHelp:Keyword Index="K" Term="LogInMemory property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogInMemory property" /><MSHelp:Keyword Index="F" Term="LogInMemory" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogInMemory" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogInMemory" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogInMemory" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogInMemory" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, transaction logs are maintained in memory rather than on disk. This means that transactions exhibit the ACI (atomicity, consistency, and isolation) properties, but not D (durability)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogInMemory Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>toArray Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapRecordId_toArray" /><meta name="guid" content="Overload_BerkeleyDB_HeapRecordId_toArray" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapRecordId.toArray" /><MSHelp:TOCTitle Title="toArray Method " /><MSHelp:RLTitle Title="HeapRecordId.toArray Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapRecordId.toArray" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdClasstoArrayTopic" /><MSHelp:Keyword Index="K" Term="toArray method" /><MSHelp:Keyword Index="K" Term="HeapRecordId.toArray method" /><MSHelp:Keyword Index="F" Term="toArray" /><MSHelp:Keyword Index="F" Term="HeapRecordId.toArray" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId.toArray" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.toArray Method </td></tr><tr id="headerTableRow3"><td
align="left">HeapRecordId Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintTransactionSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintTransactionSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintTransactionSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:TOCTitle Title="PrintTransactionSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintTransactionSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintTransactionSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintTransactionSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.PrintTransactionSystemStats method" /><MSHelp:Keyword Index="F" Term="PrintTransactionSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintTransactionSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8"
/><META NAME="save" CONTENT="history" /><title>Cursor Method (CursorConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Cursor_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Cursor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:TOCTitle Title="Cursor Method (CursorConfig)" /><MSHelp:RLTitle Title="HashDatabase.Cursor Method (CursorConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HashDatabase.<span
class="vb">.::.Cursor Method
(CursorConfig)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HashDatabase.htm">HashDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThrowException
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseException_ThrowException"
/><meta name="guid" content="M_BerkeleyDB_DatabaseException_ThrowException" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.DatabaseException.ThrowException(System.Int32)"
/><MSHelp:TOCTitle Title="ThrowException Method " /><MSHelp:RLTitle
Title="DatabaseException.ThrowException
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseException.ThrowException(System.Int32)" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseExceptionClassThrowExceptionTopic" /><MSHelp:Keyword Index="K"
Term="ThrowException method" /><MSHelp:Keyword Index="K" Term="DatabaseException.ThrowException
method" /><MSHelp:Keyword Index="F" Term="ThrowException" /><MSHelp:Keyword Index="F"
Term="DatabaseException.ThrowException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseException.ThrowException" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseException.ThrowException" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Throw an exception which corresponds to the specified Berkeley DB
error code." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table

id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException..::.ThrowException Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Txn Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_PreparedTransaction_Txn" /><meta name="guid" content="P_BerkeleyDB_PreparedTransaction_Txn" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.PreparedTransaction.Txn" /><MSHelp:TOCTitle Title="Txn Property " /><MSHelp:RLTitle Title="PreparedTransaction.Txn Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.PreparedTransaction.Txn" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPreparedTransactionClassTxnTopic" /><MSHelp:Keyword Index="K" Term="Txn property" /><MSHelp:Keyword Index="K" Term="PreparedTransaction.Txn property" /><MSHelp:Keyword

Index="F" Term="Txn" /><MSHelp:Keyword Index="F" Term="PreparedTransaction.Txn" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.PreparedTransaction.Txn" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.PreparedTransaction.Txn" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.PreparedTransaction.get_Txn" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The transaction which must be committed, aborted or discarded." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PreparedTransaction..::.Txn Property </td></tr><tr id="headerTableRow3"><td align="left">PreparedTransaction Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (DatabaseEntry, Int32, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetMultiple_2" /><meta name="guid" content="M_BerkeleyDB_Database_GetMultiple_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="GetMultiple Method (DatabaseEntry, Int32, Transaction)" /><MSHelp:RLTitle Title="Database.GetMultiple Method (DatabaseEntry, Int32, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetMultiple Method (DatabaseEntry, Int32, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EncryptionAlgorithm Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_EncryptionAlgorithm" /><meta name="guid" content="T_BerkeleyDB_EncryptionAlgorithm" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EncryptionAlgorithm" /><MSHelp:TOCTitle Title="EncryptionAlgorithm Enumeration" /><MSHelp:RLTitle Title="EncryptionAlgorithm Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EncryptionAlgorithm" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.EncryptionAlgorithm.DEFAULT" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.EncryptionAlgorithm.AES" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEncryptionAlgorithmClassTopic" /><MSHelp:Keyword Index="K" Term="EncryptionAlgorithm enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EncryptionAlgorithm enumeration" /><MSHelp:Keyword Index="K" Term="DEFAULT enumeration member" /><MSHelp:Keyword Index="K" Term="AES enumeration member" /><MSHelp:Keyword Index="F" Term="EncryptionAlgorithm" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EncryptionAlgorithm" /><MSHelp:Keyword Index="F" Term="EncryptionAlgorithm.DEFAULT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EncryptionAlgorithm.DEFAULT" /><MSHelp:Keyword Index="F" Term="EncryptionAlgorithm.AES" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.EncryptionAlgorithm.AES" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EncryptionAlgorithm" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EncryptionAlgorithm.DEFAULT" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EncryptionAlgorithm.AES" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies an algorithm used for encryption and decryption" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EncryptionAlgorithm Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Consume Method (Boolean, Transaction, LockingInfo)</title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_QueueDatabase_Consume_2" /><meta name="guid"
content="M_BerkeleyDB_QueueDatabase_Consume_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.QueueDatabase.Consume(System.Boolean,BerkeleyDB.Transaction,BerkeleyDB.LockingI
nfo)" /><MSHelp:TOCTitle Title="Consume Method (Boolean, Transaction, LockingInfo)" /><MSHelp:RLTitle
Title="QueueDatabase.Consume Method (Boolean, Transaction, LockingInfo) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.QueueDatabase.Consume(System.Boolean,BerkeleyDB.Transaction,BerkeleyDB.LockingIn
fo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Consume"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Return the
record number and data from the available record closest to the head of the queue, and delete the record."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Consume Method (Boolean, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OverflowPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_OverflowPages" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_OverflowPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.OverflowPages" /><MSHelp:TOCTitle Title="OverflowPages Property " /><MSHelp:RLTitle Title="BTreeStats.OverflowPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.OverflowPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassOverflowPagesTopic" /><MSHelp:Keyword Index="K" Term="OverflowPages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.OverflowPages property" /><MSHelp:Keyword Index="F" Term="OverflowPages" /><MSHelp:Keyword Index="F" Term="BTreeStats.OverflowPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.OverflowPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.OverflowPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_OverflowPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Overflow pages." /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.OverflowPages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashFunction Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabase_HashFunction" /><meta name="guid" content="P_BerkeleyDB_HashDatabase_HashFunction" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabase.HashFunction" /><MSHelp:TOCTitle Title="HashFunction Property " /><MSHelp:RLTitle Title="HashDatabase.HashFunction Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabase.HashFunction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassHashFunctionTopic" /><MSHelp:Keyword Index="K" Term="HashFunction property" /><MSHelp:Keyword Index="K" Term="HashDatabase.HashFunction property" /><MSHelp:Keyword Index="F" Term="HashFunction" /><MSHelp:Keyword Index="F" Term="HashDatabase.HashFunction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.HashFunction"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.HashFunction" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.get_HashFunction" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.set_HashFunction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A user-defined hash function; if no hash function is specified, a default hash function is used." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.HashFunction Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveFirst" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveFirst" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveFirstTopic" /><MSHelp:Keyword Index="K" Term="MoveFirst method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveFirst method" /><MSHelp:Keyword Index="F" Term="MoveFirst" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveFirst" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveFirst Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>DB_DONOTINDEX Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css"
href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_ErrorCodes_DB_DONOTINDEX" /><meta name="guid"
content="F_BerkeleyDB_ErrorCodes_DB_DONOTINDEX" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.ErrorCodes.DB_DONOTINDEX" /><MSHelp:TOCTitle Title="DB_DONOTINDEX Field"
/><MSHelp:RLTitle Title="ErrorCodes.DB_DONOTINDEX Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_DONOTINDEX"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_DONOTINDEXTopic"
/><MSHelp:Keyword Index="K" Term="DB_DONOTINDEX field" /><MSHelp:Keyword Index="K"
Term="ErrorCodes.DB_DONOTINDEX field" /><MSHelp:Keyword Index="F" Term="DB_DONOTINDEX"
/><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_DONOTINDEX" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ErrorCodes.DB_DONOTINDEX" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ErrorCodes.DB_DONOTINDEX" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value=""Null" return from 2ndary callbk." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_DONOTINDEX Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sync Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Sync" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Sync" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Sync" /><MSHelp:TOCTitle Title="Sync Method " /><MSHelp:RLTitle Title="BaseDatabase.Sync Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Sync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassSyncTopic" /><MSHelp:Keyword Index="K" Term="Sync method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Sync method" /><MSHelp:Keyword Index="F" Term="Sync" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Sync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Sync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Sync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Flush any cached information to disk." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Sync Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNext_1" /><meta
name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNext_1"
/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berke
leyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveNext Method (DatabaseEntry, DatabaseEntry,
DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNext Method (DatabaseEntry, DatabaseEntry,
DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MoveNext(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkel
eyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If
the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor to the next key/data pair of
the database, and store the secondary key and primary key/data pair in . In ..." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNext Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_JoinCursor_MoveNext" /><meta name="guid" content="Overload_BerkeleyDB_JoinCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="JoinCursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassMoveNextTopic" /><MSHelp:Keyword Index="K" Term="MoveNext method" /><MSHelp:Keyword Index="K" Term="JoinCursor.MoveNext method" /><MSHelp:Keyword Index="F" Term="MoveNext" /><MSHelp:Keyword Index="F" Term="JoinCursor.MoveNext" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected
Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextDuplicateMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"

style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_LOCKOUT Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_LOCKOUT" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_LOCKOUT" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_LOCKOUT" /><MSHelp:TOCTitle Title="DB_REP_LOCKOUT Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_LOCKOUT Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_LOCKOUT" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_LOCKOUTTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_LOCKOUT field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_LOCKOUT field" /><MSHelp:Keyword Index="F" Term="DB_REP_LOCKOUT" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_LOCKOUT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_LOCKOUT" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.ErrorCodes.DB_REP_LOCKOUT" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="API/Replication lockout now." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_LOCKOUT
Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogBufferSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogBufferSize" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogBufferSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogBufferSize" /><MSHelp:TOCTitle Title="LogBufferSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogBufferSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogBufferSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogBufferSizeTopic" /><MSHelp:Keyword Index="K" Term="LogBufferSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogBufferSize property" /><MSHelp:Keyword Index="F" Term="LogBufferSize" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogBufferSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogBufferSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogBufferSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogBufferSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogBufferSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the in-memory log buffer, in bytes" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogBufferSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Snapshot Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_Snapshot" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_Snapshot" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.Snapshot" /><MSHelp:TOCTitle Title="Snapshot Property " /><MSHelp:RLTitle Title="TransactionStats.Snapshot Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.Snapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassSnapshotTopic" /><MSHelp:Keyword Index="K" Term="Snapshot property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Snapshot property" /><MSHelp:Keyword Index="F" Term="Snapshot" /><MSHelp:Keyword Index="F" Term="TransactionStats.Snapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.Snapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.Snapshot" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Snapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of snapshot transactions" /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.Snapshot Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox"
type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label
class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryRecnoDatabase<span
class="cs">..::<span
class="nu">.Open Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryRecnoDatabase.htm">SecondaryRecnoDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_Sequence_PrintStats" /><meta name="guid"
content="Overload_BerkeleyDB_Sequence_PrintStats" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.Sequence.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method "
/><MSHelp:RLTitle Title="Sequence.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.Sequence.PrintStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSequenceClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats
method" /><MSHelp:Keyword Index="K" Term="Sequence.PrintStats method" /><MSHelp:Keyword Index="F"
Term="PrintStats" /><MSHelp:Keyword Index="F" Term="Sequence.PrintStats" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.Sequence.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.PrintStats Method </td></tr><tr

id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheInfo Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_CacheInfo" /><meta name="guid" content="Methods_T_BerkeleyDB_CacheInfo" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.CacheInfo" /><MSHelp:TOCTitle Title="CacheInfo Methods " /><MSHelp:RLTitle Title="CacheInfo Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.CacheInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoMethodsTopic" /><MSHelp:Keyword Index="K" Term="CacheInfo class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label

id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox"
data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CacheInfo Methods </td></tr><tr id="headerTableRow3"><td align="left">CacheInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (DatabaseEntry, Int32, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetMultiple_3" /><meta
name="guid" content="M_BerkeleyDB_Database_GetMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="GetMultiple Method (DatabaseEntry, Int32, Transaction,

LockingInfo)" /><MSHelp:RLTitle Title="Database.GetMultiple Method (DatabaseEntry, Int32, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetMultiple Method (DatabaseEntry, Int32, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockNotGrantedException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_LockNotGrantedException" /><meta name="guid" content="Properties_T_BerkeleyDB_LockNotGrantedException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:TOCTitle Title="LockNotGrantedException Properties " /><MSHelp:RLTitle Title="LockNotGrantedException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockNotGrantedExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockNotGrantedException Properties </td></tr><tr id="headerTableRow3"><td align="left">LockNotGrantedException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RecnoDatabaseConfig_Append" /><meta name="guid" content="F_BerkeleyDB_RecnoDatabaseConfig_Append" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RecnoDatabaseConfig.Append" /><MSHelp:TOCTitle Title="Append Field" /><MSHelp:RLTitle Title="RecnoDatabaseConfig.Append Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RecnoDatabaseConfig.Append" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassAppendTopic" /><MSHelp:Keyword Index="K" Term="Append field" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.Append field" /><MSHelp:Keyword Index="F" Term="Append"

/><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.Append" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.Append" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function to call after the record number has been selected but before the data has been stored into the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig..::.Append Field</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Truncate_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Truncate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Truncate(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Truncate Method (Transaction)" /><MSHelp:RLTitle Title="BaseDatabase.Truncate Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Truncate(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Empty the database, discarding all records it contains." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Truncate Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveMultipleKey" /><MSHelp:TOCTitle Title="MoveMultipleKey Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveMultipleKey method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveMultipleKey" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Open" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryQueueDatabase_Open" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Open" /><MSHelp:TOCTitle Title="Open Method "
/><MSHelp:RLTitle Title="SecondaryQueueDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Open" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open
method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Open method" /><MSHelp:Keyword
Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Open"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Open" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecoveryException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RunRecoveryException" /><meta name="guid" content="T_BerkeleyDB_RunRecoveryException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RunRecoveryException" /><MSHelp:TOCTitle Title="RunRecoveryException Class" /><MSHelp:RLTitle Title="RunRecoveryException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RunRecoveryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRunRecoveryExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class" /><MSHelp:Keyword Index="K"

Term="BerkeleyDB.RunRecoveryException class" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class, about RunRecoveryException class" /><MSHelp:Keyword Index="F" Term="RunRecoveryException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RunRecoveryException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RunRecoveryException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Berkeley DB has encountered an error it considers fatal to an entire environment. Once a RunRecoveryException has been thrown by any interface, it will be returned from all subsequent Berkeley DB calls ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RunRecoveryException Class</td></tr><tr id="headerTableRow3"><td align="left">Members

See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>YieldCPU Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_YieldCPU" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_YieldCPU" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.YieldCPU" /><MSHelp:TOCTitle Title="YieldCPU Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.YieldCPU Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.YieldCPU" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassYieldCPUTopic" /><MSHelp:Keyword Index="K" Term="YieldCPU property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.YieldCPU property" /><MSHelp:Keyword Index="F" Term="YieldCPU" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.YieldCPU" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.YieldCPU" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.YieldCPU" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_YieldCPU" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_YieldCPU" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will yield the processor immediately after each page or mutex acquisition." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.YieldCPU Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RepMgrStats" /><meta name="guid" content="Methods_T_BerkeleyDB_RepMgrStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RepMgrStats" /><MSHelp:TOCTitle Title="RepMgrStats Methods " /><MSHelp:RLTitle Title="RepMgrStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RepMgrStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="RepMgrStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats Methods </td></tr><tr id="headerTableRow3"><td

align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockTableSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LockTableSize" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LockTableSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LockTableSize" /><MSHelp:TOCTitle Title="LockTableSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LockTableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LockTableSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLockTableSizeTopic" /><MSHelp:Keyword Index="K" Term="LockTableSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LockTableSize property" /><MSHelp:Keyword Index="F" Term="LockTableSize" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LockTableSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LockTableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LockTableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LockTableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LockTableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the lock table in the Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockTableSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolSystemCfg Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_MPoolSystemCfg" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_MPoolSystemCfg"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.MPoolSystemCfg" /><MSHelp:TOCTitle Title="MPoolSystemCfg Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.MPoolSystemCfg Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.MPoolSystemCfg" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassMPoolSystemCfgTopic" /><MSHelp:Keyword Index="K" Term="MPoolSystemCfg field" /><MSHelp:Keyword Index="K"

Term="DatabaseEnvironmentConfig.MPoolSystemCfg field" /><MSHelp:Keyword Index="F"
Term="MPoolSystemCfg" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.MPoolSystemCfg" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.MPoolSystemCfg" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.MPoolSystemCfg"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Configuration for the memory pool subsystem" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironmentConfig.<span
class="vb">.::.MPoolSystemCfg
Field</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransmitLimit Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationConfig_TransmitLimit" /><meta name="guid" content="M_BerkeleyDB_ReplicationConfig_TransmitLimit" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationConfig.TransmitLimit(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="TransmitLimit Method " /><MSHelp:RLTitle Title="ReplicationConfig.TransmitLimit Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationConfig.TransmitLimit(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassTransmitLimitTopic" /><MSHelp:Keyword Index="K" Term="TransmitLimit method" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.TransmitLimit method" /><MSHelp:Keyword Index="F" Term="TransmitLimit" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.TransmitLimit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.TransmitLimit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.TransmitLimit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set a byte-count limit on the amount of data that will be transmitted from a site in response to a single message processed by . The limit is not a hard limit, and the record that exceeds the limit ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.TransmitLimit Method </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PreparedTransaction Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_PreparedTransaction" /><meta name="guid" content="AllMembers_T_BerkeleyDB_PreparedTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.PreparedTransaction" /><MSHelp:TOCTitle Title="PreparedTransaction Members" /><MSHelp:RLTitle Title="PreparedTransaction Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.PreparedTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPreparedTransactionMembersTopic" /><MSHelp:Keyword Index="K" Term="PreparedTransaction class" /><MSHelp:Keyword Index="K" Term="PreparedTransaction class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.PreparedTransaction class" /><MSHelp:Keyword Index="F" Term="PreparedTransaction" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.PreparedTransaction" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input

id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PreparedTransaction Members</td></tr><tr id="headerTableRow3"><td align="left">PreparedTransaction Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLockingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:TOCTitle Title="PrintLockingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLockingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintLockingSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintLockingSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.PrintLockingSystemStats method" /><MSHelp:Keyword Index="F" Term="PrintLockingSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLockingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MaxLocksInBucket Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxLocksInBucket" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxLocksInBucket" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxLocksInBucket" /><MSHelp:TOCTitle Title="MaxLocksInBucket Property " /><MSHelp:RLTitle Title="LockStats.MaxLocksInBucket Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxLocksInBucket" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxLocksInBucketTopic" /><MSHelp:Keyword Index="K" Term="MaxLocksInBucket property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxLocksInBucket property" /><MSHelp:Keyword Index="F" Term="MaxLocksInBucket" /><MSHelp:Keyword Index="F" Term="LockStats.MaxLocksInBucket" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.LockStats.MaxLocksInBucket" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxLocksInBucket" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxLocksInBucket" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum number of locks in any bucket." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxLocksInBucket Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_KeyRange" /><meta name="guid" content="Methods_T_BerkeleyDB_KeyRange" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.KeyRange" /><MSHelp:TOCTitle Title="KeyRange Methods " /><MSHelp:RLTitle Title="KeyRange Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.KeyRange" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyRangeMethodsTopic" /><MSHelp:Keyword Index="K" Term="KeyRange class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyRange Methods </td></tr><tr id="headerTableRow3"><td align="left">KeyRange Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MaxLockersInTable Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxLockersInTable" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxLockersInTable" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxLockersInTable" /><MSHelp:TOCTitle Title="MaxLockersInTable Property " /><MSHelp:RLTitle Title="LockStats.MaxLockersInTable Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxLockersInTable" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxLockersInTableTopic" /><MSHelp:Keyword Index="K" Term="MaxLockersInTable property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxLockersInTable property" /><MSHelp:Keyword Index="F" Term="MaxLockersInTable" /><MSHelp:Keyword Index="F" Term="LockStats.MaxLockersInTable" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxLockersInTable" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxLockersInTable" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxLockersInTable" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum num of lockers in table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxLockersInTable Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogVerify Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_LogVerify" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_LogVerify" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.LogVerify(BerkeleyDB.LogVerifyConfig)" /><MSHelp:TOCTitle Title="LogVerify Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogVerify Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LogVerify(BerkeleyDB.LogVerifyConfig)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogVerifyTopic" /><MSHelp:Keyword Index="K" Term="LogVerify method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogVerify method" /><MSHelp:Keyword Index="F" Term="LogVerify" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogVerify" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogVerify" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogVerify" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Verify log records of this environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogVerify Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEntry__ctor" /><meta name="guid" content="M_BerkeleyDB_DatabaseEntry__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEntry.#ctor" /><MSHelp:TOCTitle Title="DatabaseEntry Constructor " /><MSHelp:RLTitle Title="DatabaseEntry Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEntry.#ctor"
 /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new, empty DatabaseEntry object." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
 style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
 All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
 onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Constructor </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_RegionSize" /><meta name="guid" content="P_BerkeleyDB_LogStats_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="LogStats.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="LogStats.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="LogStats.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">LogStats.<span
class="vb">.::.RegionSize Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LogStats.htm">LogStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_PrintStats" /><meta
name="guid" content="M_BerkeleyDB_BaseDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method "
/><MSHelp:RLTitle Title="BaseDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseDatabase.PrintStats" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the

database statistical information." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_Priority" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.Priority" /><MSHelp:TOCTitle Title="Priority Property " /><MSHelp:RLTitle Title="ReplicationConfig.Priority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.Priority property" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.Priority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.Priority" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database environment's priority in replication group elections. A special value of 0 indicates that this environment cannot be a replication group master. If not configured, then a default value ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.Priority Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Recovery Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_Recovery" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_Recovery" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.Recovery" /><MSHelp:TOCTitle Title="Recovery Field" /><MSHelp:RLTitle Title="VerboseMessages.Recovery Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.Recovery" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassRecoveryTopic" /><MSHelp:Keyword Index="K" Term="Recovery field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.Recovery field" /><MSHelp:Keyword Index="F" Term="Recovery" /><MSHelp:Keyword Index="F" Term="VerboseMessages.Recovery" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.Recovery" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.Recovery" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display additional information when performing recovery." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.Recovery Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compress Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_Compress" /><meta name="guid"

content="P_BerkeleyDB_BTreeDatabase_Compress" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BTreeDatabase.Compress"
/><MSHelp:TOCTitle Title="Compress Property " /><MSHelp:RLTitle Title="BTreeDatabase.Compress Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.Compress"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassCompressTopic"
/><MSHelp:Keyword Index="K" Term="Compress property" /><MSHelp:Keyword Index="K"
Term="BTreeDatabase.Compress property" /><MSHelp:Keyword Index="F" Term="Compress"
/><MSHelp:Keyword Index="F" Term="BTreeDatabase.Compress" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeDatabase.Compress" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.Compress" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.get_Compress" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.set_Compress" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The compression function used to store key/data pairs in the database."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Compress Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
 xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
 type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Stats" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="HeapDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Stats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical
 information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;
 height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleKeyDatabaseEntry Constructor (IEnumerable(KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MultipleKeyDatabaseEntry__ctor_1" /><meta name="guid" content="M_BerkeleyDB_MultipleKeyDatabaseEntry__ctor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MultipleKeyDatabaseEntry.#ctor(System.Collections.Generic.IEnumerable{System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry}},System.Boolean)" /><MSHelp:TOCTitle Title="MultipleKeyDatabaseEntry Constructor (IEnumerable(KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean)" /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Constructor (IEnumerable(KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MultipleKeyDatabaseEntry.#ctor(System.Collections.Generic.IEnumerable{System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry}},System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.MultipleKeyDatabaseEntry..ctor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Construct a new bulk buffer for key/data pairs." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleKeyDatabaseEntry Constructor (IEnumerable<(Of <(KeyValuePair<(Of <<span
class="nu">(DatabaseEntry, DatabaseEntry<span
class="cs">>)><span
class="nu">)><span
class="vb">)>),
Boolean)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_MultipleKeyDatabaseEntry.htm">MultipleKeyDatabaseEntry Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Commit Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Transaction_Commit_1" /><meta name="guid" content="M_BerkeleyDB_Transaction_Commit_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Transaction.Commit(System.Boolean)" /><MSHelp:TOCTitle Title="Commit Method (Boolean)" /><MSHelp:RLTitle Title="Transaction.Commit Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Transaction.Commit(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Commit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="End the transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Commit Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentQueuedLogRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_CurrentQueuedLogRecords" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_CurrentQueuedLogRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.CurrentQueuedLogRecords" /><MSHelp:TOCTitle Title="CurrentQueuedLogRecords Property " /><MSHelp:RLTitle Title="ReplicationStats.CurrentQueuedLogRecords Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.CurrentQueuedLogRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassCurrentQueuedLogRecordsTopic" /><MSHelp:Keyword Index="K" Term="CurrentQueuedLogRecords property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.CurrentQueuedLogRecords property" /><MSHelp:Keyword Index="F" Term="CurrentQueuedLogRecords" /><MSHelp:Keyword Index="F" Term="ReplicationStats.CurrentQueuedLogRecords" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.CurrentQueuedLogRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.CurrentQueuedLogRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_CurrentQueuedLogRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log records currently queued." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.CurrentQueuedLogRecords Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Available Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="P_BerkeleyDB_MutexStats_Available" /><meta name="guid"
content="P_BerkeleyDB_MutexStats_Available" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MutexStats.Available" /><MSHelp:TOCTitle Title="Available Property "
/><MSHelp:RLTitle Title="MutexStats.Available Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.MutexStats.Available" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMutexStatsClassAvailableTopic" /><MSHelp:Keyword Index="K" Term="Available
property" /><MSHelp:Keyword Index="K" Term="MutexStats.Available property" /><MSHelp:Keyword
Index="F" Term="Available" /><MSHelp:Keyword Index="F" Term="MutexStats.Available"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.Available" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.MutexStats.Available" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MutexStats.get_Available"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Available mutexes" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">MutexStats.<span
class="vb">.::.Available Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_MutexStats.htm">MutexStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite
Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RepMgrSite" /><meta name="guid"
content="T_BerkeleyDB_RepMgrSite" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.RepMgrSite" /><MSHelp:TOCTitle Title="RepMgrSite Class" /><MSHelp:RLTitle
Title="RepMgrSite Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RepMgrSite"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrSiteClassTopic" /><MSHelp:Keyword
Index="K" Term="RepMgrSite class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RepMgrSite class"
/><MSHelp:Keyword Index="K" Term="RepMgrSite class, about RepMgrSite class" /><MSHelp:Keyword
Index="F" Term="RepMgrSite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrSite"
/><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrSite" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="A class representing a replication site used by Replication Manager" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrSite Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DatabaseEntry" /><meta name="guid" content="T_BerkeleyDB_DatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DatabaseEntry" /><MSHelp:TOCTitle Title="DatabaseEntry Class" /><MSHelp:RLTitle

Title="DatabaseEntry Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseEntry class" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class, about DatabaseEntry class" /><MSHelp:Keyword Index="F" Term="DatabaseEntry" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a key or data item in a Berkeley DB database" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Class</td></tr><tr id="headerTableRow3"><td align="left"><a

href="AllMembers_T_BerkeleyDB_DatabaseEntry.htm">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="RecnoDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_PrintFastStats" /><meta name="guid"

content="Overload_BerkeleyDB_SecondaryHashDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
/> <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NotFoundException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_NotFoundException" /><meta name="guid" content="Fields_T_BerkeleyDB_NotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.NotFoundException" /><MSHelp:TOCTitle Title="NotFoundException Fields" /><MSHelp:RLTitle Title="NotFoundException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.NotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotFoundExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="NotFoundException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" />
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">NotFoundException Fields</td></tr><tr id="headerTableRow3"><td align="left">NotFoundException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Sequence_Stats" /><meta name="guid" content="Overload_BerkeleyDB_Sequence_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Sequence.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="Sequence.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Sequence.Stats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassStatsTopic" /><MSHelp:Keyword Index="K" Term="Stats method" /><MSHelp:Keyword Index="K" Term="Sequence.Stats method" /><MSHelp:Keyword Index="F" Term="Stats" /><MSHelp:Keyword Index="F" Term="Sequence.Stats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetBothMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Database_GetBothMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="Database.GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetBothMultiple" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If a key/data pair in the database matches and , return the key and all duplicate data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VERY_LOW Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CachePriority_VERY_LOW" /><meta name="guid" content="F_BerkeleyDB_CachePriority_VERY_LOW" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CachePriority.VERY_LOW" /><MSHelp:TOCTitle Title="VERY_LOW Field" /><MSHelp:RLTitle Title="CachePriority.VERY_LOW Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CachePriority.VERY_LOW" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityClassVERY_LOWTopic" /><MSHelp:Keyword Index="K" Term="VERY_LOW field" /><MSHelp:Keyword Index="K" Term="CachePriority.VERY_LOW field" /><MSHelp:Keyword Index="F" Term="VERY_LOW" /><MSHelp:Keyword Index="F" Term="CachePriority.VERY_LOW" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CachePriority.VERY_LOW" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CachePriority.VERY_LOW" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The lowest priority: pages are the most likely to be discarded." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority..::.VERY_LOW Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_CachePriority.htm">CachePriority Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UsingTxns Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UsingTxns" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UsingTxns" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UsingTxns" /><MSHelp:TOCTitle Title="UsingTxns Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UsingTxns Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UsingTxns" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUsingTxnsTopic" /><MSHelp:Keyword Index="K" Term="UsingTxns property" /><MSHelp:Keyword
Index="K" Term="DatabaseEnvironment.UsingTxns property" /><MSHelp:Keyword Index="F" Term="UsingTxns" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UsingTxns" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UsingTxns" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UsingTxns" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UsingTxns" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the transaction subsystem was initialized." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UsingTxns Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>PageNotFoundException Constructor
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_PageNotFoundException__ctor" /><meta name="guid"
content="M_BerkeleyDB_PageNotFoundException__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.PageNotFoundException.#ctor" /><MSHelp:TOCTitle Title="PageNotFoundException
Constructor " /><MSHelp:RLTitle Title="PageNotFoundException Constructor (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.PageNotFoundException.#ctor" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBPageNotFoundExceptionClassctorTopic" /><MSHelp:Keyword Index="K"
Term="PageNotFoundException class, constructor" /><MSHelp:Keyword Index="K"
Term="PageNotFoundException.PageNotFoundException constructor" /><MSHelp:Keyword Index="F"
Term="PageNotFoundException" /><MSHelp:Keyword Index="F"
Term="PageNotFoundException.PageNotFoundException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.PageNotFoundException.PageNotFoundException" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.PageNotFoundException..ctor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PageNotFoundException Constructor </td></tr><tr id="headerTableRow3"><td align="left">PageNotFoundException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EventNotifyDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_EventNotifyDelegate" /><meta name="guid" content="T_BerkeleyDB_EventNotifyDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EventNotifyDelegate" /><MSHelp:TOCTitle Title="EventNotifyDelegate Delegate" /><MSHelp:RLTitle Title="EventNotifyDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EventNotifyDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEventNotifyDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="EventNotifyDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EventNotifyDelegate delegate" /><MSHelp:Keyword Index="F" Term="EventNotifyDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EventNotifyDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EventNotifyDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EventNotifyDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EventNotifyDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EventNotifyDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EventNotifyDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The application's event notification function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EventNotifyDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair and as many duplicate data ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationMessages Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_ReplicationMessages" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_ReplicationMessages" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.ReplicationMessages" /><MSHelp:TOCTitle Title="ReplicationMessages Field" /><MSHelp:RLTitle Title="VerboseMessages.ReplicationMessages Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationMessagesTopic" /><MSHelp:Keyword Index="K" Term="ReplicationMessages field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationMessages field" /><MSHelp:Keyword Index="F" Term="ReplicationMessages" /><MSHelp:Keyword Index="F" Term="VerboseMessages.ReplicationMessages" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.VerboseMessages.ReplicationMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.ReplicationMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about replication message processing." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">VerboseMessages.<span
class="vb">.::.ReplicationMessages
Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_VerboseMessages.htm">VerboseMessages Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry
Constructor (Byte[], UInt32, UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEntry__ctor_2" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEntry__ctor_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEntry.#ctor(System.Byte[],System.UInt32,System.UInt32)" /><MSHelp:TOCTitle
Title="DatabaseEntry Constructor (Byte[], UInt32, UInt32)" /><MSHelp:RLTitle Title="DatabaseEntry Constructor
(Byte[], UInt32, UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEntry.#ctor(System.Byte[],System.UInt32,System.UInt32)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry..ctor"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new partial DatabaseEntry object, with the specified data" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Constructor (array<Byte>[]()[], UInt32, UInt32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TableSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_TableSize" /><meta name="guid" content="P_BerkeleyDB_LockStats_TableSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.TableSize" /><MSHelp:TOCTitle Title="TableSize Property " /><MSHelp:RLTitle Title="LockStats.TableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.TableSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassTableSizeTopic" /><MSHelp:Keyword
Index="K" Term="TableSize property" /><MSHelp:Keyword Index="K" Term="LockStats.TableSize property" /><MSHelp:Keyword Index="F" Term="TableSize" /><MSHelp:Keyword Index="F" Term="LockStats.TableSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.TableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_TableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Size of object hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input
type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.TableSize Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironmentConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DatabaseEnvironmentConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_DatabaseEnvironmentConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:TOCTitle Title="DatabaseEnvironmentConfig Properties " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironmentConfig
Properties </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Close" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="BaseDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Flush any cached database information to disk, close any open objects, free any allocated resources, and close any underlying files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbChannel Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DbChannel" /><meta name="guid" content="T_BerkeleyDB_DbChannel" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DbChannel" /><MSHelp:TOCTitle Title="DbChannel Class" /><MSHelp:RLTitle Title="DbChannel Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DbChannel" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelClassTopic" /><MSHelp:Keyword Index="K" Term="DbChannel class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbChannel class" /><MSHelp:Keyword Index="K" Term="DbChannel class, about DbChannel class" /><MSHelp:Keyword Index="F" Term="DbChannel" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbChannel" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a channel in Berkeley DB HA replication manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Upgrade Method (String, DatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Upgrade" /><meta name="guid" content="M_BerkeleyDB_Database_Upgrade" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Upgrade(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:TOCTitle Title="Upgrade Method (String, DatabaseConfig)" /><MSHelp:RLTitle Title="Database.Upgrade Method (String,

DatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Database.Upgrade(System.String,BerkeleyDB.DatabaseConfig)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Upgrade" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Upgrade all of the databases included in the file , if necessary. If no
upgrade is necessary, Upgrade always returns successfully." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">..<span
class="cpp">::.Upgrade Method (String,
DatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorFeedback Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_ErrorFeedback" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_ErrorFeedback" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.ErrorFeedback" /><MSHelp:TOCTitle Title="ErrorFeedback Field" /><MSHelp:RLTitle Title="DatabaseConfig.ErrorFeedback Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.ErrorFeedback" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassErrorFeedbackTopic" /><MSHelp:Keyword Index="K" Term="ErrorFeedback field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.ErrorFeedback field" /><MSHelp:Keyword Index="F" Term="ErrorFeedback" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.ErrorFeedback" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.ErrorFeedback"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.ErrorFeedback" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mechanism for reporting error messages to the application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.ErrorFeedback Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_FastStats" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="HeapDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassFastStatsTopic" /><MSHelp:Keyword Index="K" Term="FastStats method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.FastStats method" /><MSHelp:Keyword Index="F" Term="FastStats" /><MSHelp:Keyword Index="F" Term="HeapDatabase.FastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.FastStats

Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ReplicationConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_ReplicationConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ReplicationConfig" /><MSHelp:TOCTitle Title="ReplicationConfig Methods " /><MSHelp:RLTitle Title="ReplicationConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.ReplicationConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="ReplicationConfig
class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
<label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, RecnoDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Open_3" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Open(System.String,System.String,BerkeleyDB.RecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, RecnoDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Open Method (String, String, RecnoDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Open(System.String,System.String,BerkeleyDB.RecnoDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr

Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.Open"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Instantiate a new RecnoDatabase object and open the database
represented by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoDatabase.<span
class="vb">.::.Open Method (String, String,
RecnoDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoDatabase.htm">RecnoDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFiles
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_LogFiles" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_LogFiles" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.LogFiles(System.Boolean)" /><MSHelp:TOCTitle Title="LogFiles
Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogFiles Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LogFiles(System.Boolean)"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogFilesTopic"
/><MSHelp:Keyword Index="K" Term="LogFiles method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.LogFiles method" /><MSHelp:Keyword Index="F" Term="LogFiles"
/><MSHelp:Keyword
Index="F" Term="DatabaseEnvironment.LogFiles" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.LogFiles" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.LogFiles" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The names of all
of the log files" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogFiles Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Database Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_Database" /><meta name="guid" content="AllMembers_T_BerkeleyDB_Database" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.Database" /><MSHelp:TOCTitle Title="Database Members" /><MSHelp:RLTitle Title="Database Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.Database" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="Database class" /><MSHelp:Keyword Index="K" Term="Database class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Database class" /><MSHelp:Keyword Index="F" Term="Database" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database Members</td></tr><tr id="headerTableRow3"><td align="left">Database

Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrStartClient Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrStartClient" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrStartClient" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrStartClient(System.Int32)" /><MSHelp:TOCTitle Title="RepMgrStartClient Method (Int32)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrStartClient Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrStartClient(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrStartClient" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Start the replication manager as a client site, and do not call for an election." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrStartClient Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AckPolicy Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_AckPolicy" /><meta name="guid" content="Fields_T_BerkeleyDB_AckPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.AckPolicy" /><MSHelp:TOCTitle Title="AckPolicy Fields" /><MSHelp:RLTitle Title="AckPolicy Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.AckPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyFieldsTopic" /><MSHelp:Keyword Index="K" Term="AckPolicy class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy Fields</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePages
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_HashStats_DuplicatePages" /><meta name="guid"
content="P_BerkeleyDB_HashStats_DuplicatePages" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.HashStats.DuplicatePages" /><MSHelp:TOCTitle Title="DuplicatePages Property "
/><MSHelp:RLTitle Title="HashStats.DuplicatePages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.HashStats.DuplicatePages" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashStatsClassDuplicatePagesTopic" /><MSHelp:Keyword Index="K"
Term="DuplicatePages property" /><MSHelp:Keyword Index="K" Term="HashStats.DuplicatePages property"
/><MSHelp:Keyword Index="F" Term="DuplicatePages" /><MSHelp:Keyword Index="F"
Term="HashStats.DuplicatePages" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashStats.DuplicatePages" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.HashStats.DuplicatePages" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HashStats.get_DuplicatePages" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of dup
pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.DuplicatePages Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_GetBothMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_GetBothMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.GetBothMultiple" /><MSHelp:TOCTitle Title="GetBothMultiple Method " /><MSHelp:RLTitle Title="HashDatabase.GetBothMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.GetBothMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassGetBothMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetBothMultiple method" /><MSHelp:Keyword Index="K" Term="HashDatabase.GetBothMultiple method" /><MSHelp:Keyword Index="F" Term="GetBothMultiple" /><MSHelp:Keyword Index="F" Term="HashDatabase.GetBothMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.GetBothMultiple Method

</td></tr><tr
id="headerTableRow3"><td align="left">HashDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>ForeignConflictException Fields</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Fields_T_BerkeleyDB_ForeignConflictException" /><meta name="guid"
content="Fields_T_BerkeleyDB_ForeignConflictException" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.ForeignConflictException" /><MSHelp:TOCTitle Title="ForeignConflictException Fields" /><MSHelp:RLTitle Title="ForeignConflictException Fields (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Fields.T:BerkeleyDB.ForeignConflictException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBForeignConflictExceptionFieldsTopic" /><MSHelp:Keyword Index="K"
Term="ForeignConflictException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignConflictException Fields</td></tr><tr id="headerTableRow3"><td align="left">ForeignConflictException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabaseConfig_SetForeignKeyConstraint" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabaseConfig_SetForeignKeyConstraint" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:TOCTitle Title="SetForeignKeyConstraint Method " /><MSHelp:RLTitle

Title="SecondaryDatabaseConfig.SetForeignKeyConstraint Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassSetForeignKeyConstraintTopic" /><MSHelp:Keyword Index="K" Term="SetForeignKeyConstraint method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.SetForeignKeyConstraint method" /><MSHelp:Keyword Index="F" Term="SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..<span
class="cpp">::.SetForeignKeyConstraint Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_QueueDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_QueueDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.QueueDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="QueueDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.QueueDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="QueueDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_Cursor_RefreshMultiple_2" /><meta name="guid"
content="M_BerkeleyDB_Cursor_RefreshMultiple_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.RefreshMultiple(System.Int32)" /><MSHelp:TOCTitle
Title="RefreshMultiple Method (Int32)" /><MSHelp:RLTitle Title="Cursor.RefreshMultiple Method (Int32)
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.RefreshMultiple(System.Int32)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultiple"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers and as many duplicate
data items that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.RefreshMultiple Method
(Int32)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveMultipleKey"
/><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveMultipleKey" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:TOCTitle
Title="MoveMultipleKey Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveMultipleKey
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeCursorClassMoveMultipleKeyTopic" /><MSHelp:Keyword Index="K"
Term="MoveMultipleKey method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveMultipleKey
method" /><MSHelp:Keyword Index="F" Term="MoveMultipleKey" /><MSHelp:Keyword Index="F"
Term="BTreeCursor.MoveMultipleKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label

id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">BTreeCursor<span
class="languageSpecificText">..<span
class="cpp">::.MoveMultipleKey Method </td></tr><tr
id="headerTableRow3"><td align="left">BTreeCursor Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RetransmissionRequestMin Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_RetransmissionRequestMin" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_RetransmissionRequestMin" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.RetransmissionRequestMin" /><MSHelp:TOCTitle Title="RetransmissionRequestMin Property " /><MSHelp:RLTitle Title="ReplicationConfig.RetransmissionRequestMin Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.RetransmissionRequestMin" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassRetransmissionRequestMinTopic" /><MSHelp:Keyword Index="K" Term="RetransmissionRequestMin property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.RetransmissionRequestMin property" /><MSHelp:Keyword Index="F" Term="RetransmissionRequestMin" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.RetransmissionRequestMin" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.RetransmissionRequestMin" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.RetransmissionRequestMin" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_RetransmissionRequestMin" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The minimum number of microseconds a client waits before requesting retransmission." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.RetransmissionRequestMin Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryBTreeDatabase" /><meta name="guid" content="T_BerkeleyDB_SecondaryBTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabase Class" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryBTreeDatabase class" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase
class, about SecondaryBTreeDatabase class" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a SecondaryBTreeDatabase. The Btree format is a representation of a sorted, balanced tree structure." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLogIdCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="P_BerkeleyDB_LogConfig_InitLogIdCount" /><meta name="guid" content="P_BerkeleyDB_LogConfig_InitLogIdCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogConfig.InitLogIdCount" /><MSHelp:TOCTitle Title="InitLogIdCount Property " /><MSHelp:RLTitle Title="LogConfig.InitLogIdCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogConfig.InitLogIdCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassInitLogIdCountTopic" /><MSHelp:Keyword Index="K" Term="InitLogIdCount property" /><MSHelp:Keyword Index="K" Term="LogConfig.InitLogIdCount property" /><MSHelp:Keyword Index="F" Term="InitLogIdCount" /><MSHelp:Keyword Index="F" Term="LogConfig.InitLogIdCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.InitLogIdCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.InitLogIdCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.get_InitLogIdCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.set_InitLogIdCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of log identifier entities created by the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.InitLogIdCount Property </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetBothMultiple_2" /><meta name="guid" content="M_BerkeleyDB_Database_GetBothMultiple_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction)" /><MSHelp:RLTitle Title="Database.GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetBothMultiple(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Int32,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetBothMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If a key/data pair in the database matches and , return the key and all duplicate data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;

height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.GetBothMultiple Method (DatabaseEntry, DatabaseEntry, Int32, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultiple Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirstMultiple Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveFirstMultiple Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.Cursor.MoveFirstMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that key and as many duplicate data items that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultiple Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesWritten Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_PagesWritten" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_PagesWritten" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.PagesWritten" /><MSHelp:TOCTitle Title="PagesWritten Property " /><MSHelp:RLTitle Title="MPoolFileStats.PagesWritten Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.PagesWritten" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassPagesWrittenTopic" /><MSHelp:Keyword Index="K" Term="PagesWritten property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.PagesWritten property" /><MSHelp:Keyword Index="F" Term="PagesWritten" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.PagesWritten" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.PagesWritten" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.PagesWritten" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_PagesWritten" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages written out." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.PagesWritten Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
<label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..<span

class="cpp">::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextDuplicate" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicate method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextDuplicate method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">BTreeCursor..::.MoveNextDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePages Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_DuplicatePages" /><meta name="guid"

content="P_BerkeleyDB_BTreeStats_DuplicatePages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.DuplicatePages" /><MSHelp:TOCTitle Title="DuplicatePages Property " /><MSHelp:RLTitle Title="BTreeStats.DuplicatePages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.DuplicatePages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassDuplicatePagesTopic" /><MSHelp:Keyword Index="K" Term="DuplicatePages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.DuplicatePages property" /><MSHelp:Keyword Index="F" Term="DuplicatePages" /><MSHelp:Keyword Index="F" Term="BTreeStats.DuplicatePages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.DuplicatePages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.DuplicatePages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_DuplicatePages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Duplicate pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.DuplicatePages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InMemory Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_InMemory" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_InMemory" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.InMemory" /><MSHelp:TOCTitle Title="InMemory Field" /><MSHelp:RLTitle Title="ReplicationConfig.InMemory Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.InMemory" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassInMemoryTopic" /><MSHelp:Keyword Index="K" Term="InMemory field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.InMemory field" /><MSHelp:Keyword Index="F" Term="InMemory" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.InMemory" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.InMemory" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.InMemory" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, replication only stores the internal information in-memory and cannot keep persistent state across a site crash or reboot. By default, it is false and replication creates files in the envi ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.InMemory Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>StartLsn Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_StartLsn" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_StartLsn" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.StartLsn" /><MSHelp:TOCTitle Title="StartLsn Property " /><MSHelp:RLTitle Title="LogVerifyConfig.StartLsn Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.StartLsn" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassStartLsnTopic" /><MSHelp:Keyword Index="K" Term="StartLsn property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.StartLsn property" /><MSHelp:Keyword

Index="F" Term="StartLsn" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.StartLsn" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.StartLsn" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.StartLsn" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_StartLsn" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_StartLsn" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The starting lsn to verify." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.StartLsn Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig

Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FullLogBufferException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_FullLogBufferException" /><meta name="guid" content="Fields_T_BerkeleyDB_FullLogBufferException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.FullLogBufferException" /><MSHelp:TOCTitle Title="FullLogBufferException Fields" /><MSHelp:RLTitle Title="FullLogBufferException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.FullLogBufferException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBFullLogBufferExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="FullLogBufferException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">FullLogBufferException Fields</td></tr><tr id="headerTableRow3"><td align="left">FullLogBufferException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackingDatabase Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_BackingDatabase" /><meta name="guid" content="P_BerkeleyDB_Sequence_BackingDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.BackingDatabase" /><MSHelp:TOCTitle Title="BackingDatabase Property " /><MSHelp:RLTitle Title="Sequence.BackingDatabase Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.BackingDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassBackingDatabaseTopic" /><MSHelp:Keyword Index="K" Term="BackingDatabase property" /><MSHelp:Keyword Index="K" Term="Sequence.BackingDatabase property"

/><MSHelp:Keyword Index="F" Term="BackingDatabase" /><MSHelp:Keyword Index="F" Term="Sequence.BackingDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.BackingDatabase" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.BackingDatabase" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_BackingDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database used by the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.BackingDatabase Property </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Recno Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MultipleDatabaseEntry_Recno" /><meta name="guid" content="P_BerkeleyDB_MultipleDatabaseEntry_Recno" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MultipleDatabaseEntry.Recno" /><MSHelp:TOCTitle Title="Recno Property " /><MSHelp:RLTitle Title="MultipleDatabaseEntry.Recno Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MultipleDatabaseEntry.Recno" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleDatabaseEntryClassRecnoTopic"
/><MSHelp:Keyword Index="K" Term="Recno property" /><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry.Recno property" /><MSHelp:Keyword Index="F" Term="Recno" /><MSHelp:Keyword Index="F" Term="MultipleDatabaseEntry.Recno" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MultipleDatabaseEntry.Recno" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry.Recno" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry.get_Recno" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether the bulk buffer is for recno or queue database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry..::.Recno Property </td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (UInt32, Transaction, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Get_2" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Get_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Get(System.UInt32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Get Method (UInt32, Transaction, LockingInfo)" /><MSHelp:RLTitle Title="BTreeDatabase.Get Method (UInt32, Transaction, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Get(System.UInt32,BerkeleyDB.Transaction,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key/data pair from the database." />
<MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Get Method (UInt32, Transaction, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8"

/><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryHashDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryHashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:TOCTitle Title="SecondaryHashDatabase Methods " /><MSHelp:RLTitle Title="SecondaryHashDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryHashDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingInfo Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LockingInfo" /><meta name="guid" content="Methods_T_BerkeleyDB_LockingInfo" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LockingInfo" /><MSHelp:TOCTitle Title="LockingInfo Methods " /><MSHelp:RLTitle Title="LockingInfo Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LockingInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingInfoMethodsTopic" /><MSHelp:Keyword
Index="K" Term="LockingInfo class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingInfo Methods </td></tr><tr id="headerTableRow3"><td align="left">LockingInfo Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EnvPriority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_EnvPriority" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_EnvPriority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.EnvPriority" /><MSHelp:TOCTitle Title="EnvPriority Property " /><MSHelp:RLTitle Title="ReplicationStats.EnvPriority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.EnvPriority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassEnvPriorityTopic" /><MSHelp:Keyword Index="K" Term="EnvPriority property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.EnvPriority property" /><MSHelp:Keyword Index="F" Term="EnvPriority" /><MSHelp:Keyword Index="F" Term="ReplicationStats.EnvPriority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.EnvPriority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.EnvPriority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_EnvPriority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current environment priority." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.EnvPriority Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method (CursorConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor(BerkeleyDB.CursorConfig)" /><MSHelp:TOCTitle Title="SecondaryCursor Method (CursorConfig)" /><MSHelp:RLTitle Title="SecondaryDatabase.SecondaryCursor Method (CursorConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor(BerkeleyDB.CursorConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a secondary database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryDatabase.<span
class="vb">.::.SecondaryCursor Method
(CursorConfig)</td></tr><tr id="headerTableRow3"><td
align="left">SecondaryDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepMgrAckPolicy Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrAckPolicy" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepMgrAckPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepMgrAckPolicy" /><MSHelp:TOCTitle Title="RepMgrAckPolicy Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrAckPolicy Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepMgrAckPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrAckPolicyTopic" /><MSHelp:Keyword
Index="K" Term="RepMgrAckPolicy property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrAckPolicy property" /><MSHelp:Keyword Index="F" Term="RepMgrAckPolicy" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepMgrAckPolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepMgrAckPolicy" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrAckPolicy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepMgrAckPolicy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepMgrAckPolicy" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Specify how master and client sites will handle acknowledgment of replication messages which are necessary for "permanent" records. The current implementation requires all sites in a replication group ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrAckPolicy Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveMultiple" /><MSHelp:TOCTitle Title="MoveMultiple Method " /><MSHelp:RLTitle Title="HashCursor.MoveMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveMultiple method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveMultiple method" /><MSHelp:Keyword Index="F" Term="MoveMultiple" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EntryComparisonDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_EntryComparisonDelegate" /><meta name="guid" content="T_BerkeleyDB_EntryComparisonDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EntryComparisonDelegate" /><MSHelp:TOCTitle Title="EntryComparisonDelegate Delegate" /><MSHelp:RLTitle Title="EntryComparisonDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EntryComparisonDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEntryComparisonDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="EntryComparisonDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EntryComparisonDelegate delegate" /><MSHelp:Keyword Index="F" Term="EntryComparisonDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EntryComparisonDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryComparisonDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryComparisonDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryComparisonDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryComparisonDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryComparisonDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An application-specified comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EntryComparisonDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheInfo Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_CacheInfo" /><meta name="guid" content="Fields_T_BerkeleyDB_CacheInfo" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.CacheInfo" /><MSHelp:TOCTitle Title="CacheInfo Fields" /><MSHelp:RLTitle Title="CacheInfo Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.CacheInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCacheInfoFieldsTopic" /><MSHelp:Keyword Index="K" Term="CacheInfo class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">CacheInfo Fields</td></tr><tr id="headerTableRow3"><td
align="left">CacheInfo Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nData Property

</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_nData" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_nData" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.nData" /><MSHelp:TOCTitle Title="nData Property " /><MSHelp:RLTitle Title="RecnoStats.nData Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.nData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassnDataTopic" /><MSHelp:Keyword Index="K" Term="nData property" /><MSHelp:Keyword Index="K" Term="RecnoStats.nData property" /><MSHelp:Keyword Index="F" Term="nData" /><MSHelp:Keyword Index="F" Term="RecnoStats.nData" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.nData" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.nData" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_nData" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of data items." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.nData Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDecompressDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BTreeDecompressDelegate" /><meta name="guid" content="T_BerkeleyDB_BTreeDecompressDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BTreeDecompressDelegate" /><MSHelp:TOCTitle Title="BTreeDecompressDelegate Delegate" /><MSHelp:RLTitle Title="BTreeDecompressDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BTreeDecompressDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDecompressDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="BTreeDecompressDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeDecompressDelegate delegate" /><MSHelp:Keyword Index="F" Term="BTreeDecompressDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDecompressDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDecompressDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDecompressDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDecompressDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDecompressDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDecompressDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function to decompress a key/data pair from a supplied buffer." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDecompressDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ReplicationHostAddress" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ReplicationHostAddress" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:TOCTitle Title="ReplicationHostAddress Members" /><MSHelp:RLTitle Title="ReplicationHostAddress Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressMembersTopic" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress class" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ReplicationHostAddress class" /><MSHelp:Keyword Index="F" Term="ReplicationHostAddress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationHostAddress" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress Members</td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleDatabaseEntry Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MultipleDatabaseEntry" /><meta name="guid" content="T_BerkeleyDB_MultipleDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:TOCTitle Title="MultipleDatabaseEntry Class" /><MSHelp:RLTitle Title="MultipleDatabaseEntry Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleDatabaseEntryClassTopic" /><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MultipleDatabaseEntry class" /><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry class, about MultipleDatabaseEntry class" /><MSHelp:Keyword Index="F" Term="MultipleDatabaseEntry" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class providing access to multiple objects." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitThreadCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_InitThreadCount"
/><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_InitThreadCount"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.InitThreadCount"
/><MSHelp:TOCTitle Title="InitThreadCount Property " /><MSHelp:RLTitle
Title="DatabaseEnvironmentConfig.InitThreadCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironmentConfig.InitThreadCount" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassInitThreadCountTopic" /><MSHelp:Keyword Index="K"
Term="InitThreadCount property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.InitThreadCount property" /><MSHelp:Keyword Index="F"
Term="InitThreadCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.InitThreadCount"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.InitThreadCount"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.InitThreadCount"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_InitThreadCount"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.set_InitThreadCount"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The initial number of concurrent threads catered for by the Berkeley DB
environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.InitThreadCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IsTransactionApplied Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_IsTransactionApplied" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_IsTransactionApplied" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.IsTransactionApplied(System.Byte[],System.UInt32)" /><MSHelp:TOCTitle Title="IsTransactionApplied Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.IsTransactionApplied Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.IsTransactionApplied(System.Byte[],System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassIsTransactionAppliedTopic" /><MSHelp:Keyword Index="K" Term="IsTransactionApplied method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.IsTransactionApplied method" /><MSHelp:Keyword Index="F" Term="IsTransactionApplied" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.IsTransactionApplied" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.IsTransactionApplied" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.IsTransactionApplied" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr

Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="This method checks to see if a specified transaction has been replicated from the master of a replication group. It may be called by applications using either the Base API or the Replication Manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.IsTransactionApplied Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>NotificationEvent Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_NotificationEvent" /><meta name="guid" content="T_BerkeleyDB_NotificationEvent" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.NotificationEvent" /><MSHelp:TOCTitle Title="NotificationEvent Enumeration" /><MSHelp:RLTitle Title="NotificationEvent Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.NotificationEvent" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.PANIC" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_CLIENT" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_CONNECT_BROKEN" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_CONNECT_ESTD" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_CONNECT_TRY_FAILED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_DUPMASTER" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_ELECTED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_ELECTION_FAILED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_INIT_DONE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_JOIN_FAILURE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_LOCAL_SITE_REMOVED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_MASTER" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_MASTER_FAILURE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_NEWMASTER" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_PERM_FAILED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_STARTUPDONE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_SITE_ADDED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.REP_SITE_REMOVED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.NotificationEvent.WRITE_FAILED" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotificationEventClassTopic" /><MSHelp:Keyword Index="K" Term="NotificationEvent enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.NotificationEvent enumeration" /><MSHelp:Keyword Index="K" Term="PANIC enumeration member" /><MSHelp:Keyword Index="K" Term="REP_CLIENT enumeration member" /><MSHelp:Keyword Index="K" Term="REP_CONNECT_BROKEN enumeration member" /><MSHelp:Keyword Index="K" Term="REP_CONNECT_ESTD enumeration member" /><MSHelp:Keyword Index="K" Term="REP_CONNECT_TRY_FAILED enumeration member" /><MSHelp:Keyword Index="K" Term="REP_DUPMASTER enumeration member" /><MSHelp:Keyword Index="K" Term="REP_ELECTED enumeration member" /><MSHelp:Keyword Index="K" Term="REP_ELECTION_FAILED enumeration member" /><MSHelp:Keyword Index="K" Term="REP_INIT_DONE enumeration member" /><MSHelp:Keyword Index="K" Term="REP_JOIN_FAILURE enumeration member" /><MSHelp:Keyword Index="K" Term="REP_LOCAL_SITE_REMOVED enumeration member" /><MSHelp:Keyword Index="K" Term="REP_MASTER enumeration member" /><MSHelp:Keyword Index="K" Term="REP_MASTER_FAILURE enumeration member" /><MSHelp:Keyword Index="K" Term="REP_NEWMASTER enumeration member" /><MSHelp:Keyword Index="K" Term="REP_PERM_FAILED enumeration member" /><MSHelp:Keyword Index="K"

Term="REP_STARTUPDONE enumeration member" /><MSHelp:Keyword Index="K"
Term="REP_SITE_ADDED enumeration member" /><MSHelp:Keyword Index="K"
Term="REP_SITE_REMOVED enumeration member" /><MSHelp:Keyword Index="K" Term="WRITE_FAILED
enumeration member" /><MSHelp:Keyword Index="F" Term="NotificationEvent" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.NotificationEvent" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.PANIC" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.PANIC" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_CLIENT" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_CLIENT"
/><MSHelp:Keyword Index="F" Term="NotificationEvent.REP_CONNECT_BROKEN" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.NotificationEvent.REP_CONNECT_BROKEN" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_CONNECT_ESTD" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_CONNECT_ESTD" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_CONNECT_TRY_FAILED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_CONNECT_TRY_FAILED" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_DUPMASTER" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_DUPMASTER" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_ELECTED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_ELECTED" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_ELECTION_FAILED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_ELECTION_FAILED" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_INIT_DONE"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.NotificationEvent.REP_INIT_DONE" /><MSHelp:Keyword
Index="F" Term="NotificationEvent.REP_JOIN_FAILURE" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_JOIN_FAILURE" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_LOCAL_SITE_REMOVED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_LOCAL_SITE_REMOVED" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_MASTER" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_MASTER" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_MASTER_FAILURE" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_MASTER_FAILURE" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_NEWMASTER" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_NEWMASTER" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_PERM_FAILED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_PERM_FAILED" /><MSHelp:Keyword
Index="F" Term="NotificationEvent.REP_STARTUPDONE" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_STARTUPDONE" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_SITE_ADDED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_SITE_ADDED" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.REP_SITE_REMOVED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.REP_SITE_REMOVED" /><MSHelp:Keyword Index="F"
Term="NotificationEvent.WRITE_FAILED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.NotificationEvent.WRITE_FAILED" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.PANIC" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_CLIENT" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.NotificationEvent.REP_CONNECT_BROKEN"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_CONNECT_ESTD" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_CONNECT_TRY_FAILED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_DUPMASTER" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_ELECTED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_ELECTION_FAILED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_INIT_DONE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_JOIN_FAILURE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_LOCAL_SITE_REMOVED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_MASTER" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_MASTER_FAILURE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_NEWMASTER" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_PERM_FAILED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_STARTUPDONE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_SITE_ADDED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.REP_SITE_REMOVED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.NotificationEvent.WRITE_FAILED" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify a Berkeley DB event" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">NotificationEvent Enumeration</td></tr><tr id="headerTableRow3"><td align="left"><a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IBackup Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_IBackup" /><meta name="guid" content="Methods_T_BerkeleyDB_IBackup" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.IBackup" /><MSHelp:TOCTitle Title="IBackup Methods " /><MSHelp:RLTitle Title="IBackup Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.IBackup" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIBackupMethodsTopic" /><MSHelp:Keyword Index="K" Term="IBackup interface, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">IBackup Methods </td></tr><tr id="headerTableRow3"><td align="left">IBackup Interface See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LocalSite Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="P_BerkeleyDB_DbSiteConfig_LocalSite" /><meta name="guid"
content="P_BerkeleyDB_DbSiteConfig_LocalSite"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DbSiteConfig.LocalSite" /><MSHelp:TOCTitle
Title="LocalSite Property " /><MSHelp:RLTitle Title="DbSiteConfig.LocalSite Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DbSiteConfig.LocalSite" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDbSiteConfigClassLocalSiteTopic" /><MSHelp:Keyword Index="K" Term="LocalSite
property" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.LocalSite property" /><MSHelp:Keyword
Index="F" Term="LocalSite" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.LocalSite"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.LocalSite" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DbSiteConfig.LocalSite" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSiteConfig.get_LocalSite" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSiteConfig.set_LocalSite" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Whether it is local site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.LocalSite Property </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ResetFileID Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_ResetFileID" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_ResetFileID" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.ResetFileID(System.String,System.Boolean)" /><MSHelp:TOCTitle Title="ResetFileID Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.ResetFileID Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.ResetFileID(System.String,System.Boolean)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassResetFileIDTopic" /><MSHelp:Keyword Index="K" Term="ResetFileID method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ResetFileID method" /><MSHelp:Keyword Index="F" Term="ResetFileID" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ResetFileID" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DatabaseEnvironment.ResetFileID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ResetFileID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Allow database files to be copied, and then the copy used in the same database environment as the original." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::<span
class="nu">.ResetFileID Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword

Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNext" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="Cursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNext" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextTopic" /><MSHelp:Keyword Index="K" Term="MoveNext method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNext method" /><MSHelp:Keyword Index="F" Term="MoveNext" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNext" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Cursor" /><meta
name="guid" content="Overload_BerkeleyDB_HashDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method "
/><MSHelp:RLTitle Title="HashDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.HashDatabase.Cursor"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassCursorTopic" /><MSHelp:Keyword
Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Cursor method"
/><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="HashDatabase.Cursor"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Cursor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase<span
class="languageSpecificText">..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveFirst" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveFirst"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveFirstTopic" /><MSHelp:Keyword Index="K" Term="MoveFirst method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveFirst method" /><MSHelp:Keyword Index="F" Term="MoveFirst" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveFirst" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">BTreeCursor..::.MoveFirst Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="HashDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="HashDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="HashDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">HashDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="Overload_BerkeleyDB_BaseDatabase_Truncate" /><meta name="guid"
content="Overload_BerkeleyDB_BaseDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.BaseDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method "
/><MSHelp:RLTitle Title="BaseDatabase.Truncate
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Truncate"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassTruncateTopic" /><MSHelp:Keyword
Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Truncate method"
/><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F"
Term="BaseDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Truncate"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label> <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabase Properties
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryBTreeDatabase" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryBTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:TOCTitle
Title="SecondaryBTreeDatabase Properties " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabasePropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoReverseSplitting Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_NoReverseSplitting" /><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_NoReverseSplitting" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:TOCTitle Title="NoReverseSplitting Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.NoReverseSplitting Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassNoReverseSplittingTopic" /><MSHelp:Keyword Index="K" Term="NoReverseSplitting field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.NoReverseSplitting field" /><MSHelp:Keyword Index="F" Term="NoReverseSplitting" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.NoReverseSplitting" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Turn reverse splitting in the Btree on or off." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label

id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig..::.NoReverseSplitting Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_LockingConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_LockingConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.LockingConfig" /><MSHelp:TOCTitle Title="LockingConfig Fields" /><MSHelp:RLTitle Title="LockingConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.LockingConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="LockingConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeafPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_LeafPages" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_LeafPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.LeafPages" /><MSHelp:TOCTitle Title="LeafPages Property " /><MSHelp:RLTitle Title="BTreeStats.LeafPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.LeafPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassLeafPagesTopic" /><MSHelp:Keyword Index="K" Term="LeafPages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.LeafPages property" /><MSHelp:Keyword Index="F" Term="LeafPages" /><MSHelp:Keyword Index="F" Term="BTreeStats.LeafPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.LeafPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.LeafPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_LeafPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Leaf pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.LeafPages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Pages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactConfig_Pages" /><meta name="guid" content="P_BerkeleyDB_CompactConfig_Pages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactConfig.Pages" /><MSHelp:TOCTitle Title="Pages Property " /><MSHelp:RLTitle Title="CompactConfig.Pages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactConfig.Pages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassPagesTopic" /><MSHelp:Keyword Index="K" Term="Pages property" /><MSHelp:Keyword Index="K" Term="CompactConfig.Pages property" /><MSHelp:Keyword Index="F" Term="Pages" /><MSHelp:Keyword Index="F" Term="CompactConfig.Pages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.Pages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.Pages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.get_Pages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.set_Pages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If non-zero, compaction will complete after the specified number of pages have been freed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.Pages Property </td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Get" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Get Method (DatabaseEntry)" /><MSHelp:RLTitle Title="BaseDatabase.Get Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Get(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key/data pair from the database. In the presence of duplicate key values, Get will return the first data item for ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Get Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ALL_PEERS Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_AckPolicy_ALL_PEERS" /><meta name="guid" content="F_BerkeleyDB_AckPolicy_ALL_PEERS"
 /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.AckPolicy.ALL_PEERS" /><MSHelp:TOCTitle Title="ALL_PEERS Field" /><MSHelp:RLTitle Title="AckPolicy.ALL_PEERS Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.AckPolicy.ALL_PEERS" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyClassALL_PEERSTopic" /><MSHelp:Keyword Index="K" Term="ALL_PEERS field" /><MSHelp:Keyword Index="K" Term="AckPolicy.ALL_PEERS field" /><MSHelp:Keyword Index="F" Term="ALL_PEERS" /><MSHelp:Keyword Index="F" Term="AckPolicy.ALL_PEERS" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy.ALL_PEERS" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.AckPolicy.ALL_PEERS" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
 Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The master should wait until all electable peers have acknowledged each permanent replication message (where "electable peer" means a client capable of being subsequently elected master of the repl ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
 height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy..::.ALL_PEERS Field</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogDir Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LogDir" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LogDir" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LogDir" /><MSHelp:TOCTitle Title="LogDir Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogDir Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LogDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLogDirTopic" /><MSHelp:Keyword Index="K" Term="LogDir property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LogDir property" /><MSHelp:Keyword

Index="F" Term="LogDir" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LogDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LogDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogDir" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LogDir" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LogDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of a directory to be used as the location of logging files. Log files created by the Log Manager subsystem will be created in this directory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment<span

class="cs">..::.LogDir Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryQueueDatabaseConfig_Length" /><meta name="guid" content="P_BerkeleyDB_SecondaryQueueDatabaseConfig_Length" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryQueueDatabaseConfig.Length" /><MSHelp:TOCTitle Title="Length Property " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig.Length Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryQueueDatabaseConfig.Length" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassLengthTopic" /><MSHelp:Keyword Index="K" Term="Length property" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig.Length property" /><MSHelp:Keyword Index="F" Term="Length" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig.Length" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig.Length" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.get_Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.set_Length" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify the length of records in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:TOCTitle Title="MoveMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveMultipleKey method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveMultipleKey method"

/><MSHelp:Keyword Index="F" Term="MoveMultipleKey" /><MSHelp:Keyword Index="F" Term="Cursor.MoveMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label

class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CursorConfig_Priority" /><meta name="guid" content="F_BerkeleyDB_CursorConfig_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CursorConfig.Priority" /><MSHelp:TOCTitle Title="Priority Field" /><MSHelp:RLTitle Title="CursorConfig.Priority Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CursorConfig.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorConfigClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority field" /><MSHelp:Keyword Index="K" Term="CursorConfig.Priority field" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="CursorConfig.Priority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CursorConfig.Priority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CursorConfig.Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The cache priority for pages referenced by the cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig..::.Priority Field</td></tr><tr id="headerTableRow3"><td align="left">CursorConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NextRecordNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_NextRecordNumber" /><meta name="guid" content="P_BerkeleyDB_QueueStats_NextRecordNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.NextRecordNumber" /><MSHelp:TOCTitle Title="NextRecordNumber Property " /><MSHelp:RLTitle Title="QueueStats.NextRecordNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.NextRecordNumber" /><MSHelp:Keyword

Index="A" Term="frlrfBerkeleyDBQueueStatsClassNextRecordNumberTopic" /><MSHelp:Keyword Index="K" Term="NextRecordNumber property" /><MSHelp:Keyword Index="K" Term="QueueStats.NextRecordNumber property" /><MSHelp:Keyword Index="F" Term="NextRecordNumber" /><MSHelp:Keyword Index="F" Term="QueueStats.NextRecordNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.NextRecordNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.NextRecordNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_NextRecordNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Next available record number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..<span

class="cpp">::.NextRecordNumber Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nKeys Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_nKeys" /><meta name="guid" content="P_BerkeleyDB_HashStats_nKeys" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.nKeys" /><MSHelp:TOCTitle Title="nKeys Property " /><MSHelp:RLTitle Title="HashStats.nKeys Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.nKeys" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassnKeysTopic" /><MSHelp:Keyword Index="K" Term="nKeys property" /><MSHelp:Keyword Index="K" Term="HashStats.nKeys property" /><MSHelp:Keyword Index="F" Term="nKeys" /><MSHelp:Keyword Index="F" Term="HashStats.nKeys" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.nKeys" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.nKeys" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_nKeys" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of unique keys." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.nKeys Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Move_5" /><meta name="guid" content="M_BerkeleyDB_Cursor_Move_5" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.Move Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database. The cursor is positioned to a key/data pair if both the key and data match the values provided on the key and data parameters." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><div id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FillFactor Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabaseConfig_FillFactor" /><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabaseConfig_FillFactor" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabaseConfig.FillFactor" /><MSHelp:TOCTitle Title="FillFactor Property " /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.FillFactor Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryHashDatabaseConfig.FillFactor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassFillFactorTopic" /><MSHelp:Keyword Index="K" Term="FillFactor property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.FillFactor property" /><MSHelp:Keyword Index="F" Term="FillFactor" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.FillFactor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.FillFactor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.FillFactor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.get_FillFactor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.set_FillFactor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The desired density within the hash table. If no value is specified, the fill factor will be selected dynamically as pages are filled." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.FillFactor Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, HashDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Open_3" /><meta
name="guid" content="M_BerkeleyDB_HashDatabase_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Open(System.String,System.String,BerkeleyDB.HashDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, HashDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="HashDatabase.Open Method (String, String, HashDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Open(System.String,System.String,BerkeleyDB.HashDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"

/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HashDatabase object and open the database represented by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Open Method (String, String, HashDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Register Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Register" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_Register" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Register" /><MSHelp:TOCTitle Title="Register Field"
/><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Register Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Register" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassRegisterTopic" /><MSHelp:Keyword Index="K"
Term="Register field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Register field"
/><MSHelp:Keyword Index="F" Term="Register" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.Register" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.Register" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.Register"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, check to see if recovery needs to be performed before opening
the database environment. (For this check to be accurate, all processes using the environment must specify it when
opening the ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.Register Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sequence Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_Sequence" /><meta name="guid" content="AllMembers_T_BerkeleyDB_Sequence" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.Sequence" /><MSHelp:TOCTitle Title="Sequence Members" /><MSHelp:RLTitle Title="Sequence Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.Sequence" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceMembersTopic" /><MSHelp:Keyword Index="K" Term="Sequence class" /><MSHelp:Keyword Index="K" Term="Sequence class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Sequence class" /><MSHelp:Keyword Index="F" Term="Sequence" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence Members</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class Constructors
  Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (DatabaseEntry, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (DatabaseEntry, Boolean)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (DatabaseEntry, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultipleKey(BerkeleyDB.DatabaseEntry,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store that key and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method (DatabaseEntry, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Dispose" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="BaseDatabase.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by this object, and close the database if it's still open." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryCursor" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Properties " /><MSHelp:RLTitle
Title="SecondaryCursor Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorPropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryCursor class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupSpins Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_BackupSpins" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_BackupSpins" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.BackupSpins" /><MSHelp:TOCTitle Title="BackupSpins Property " /><MSHelp:RLTitle Title="MPoolFileStats.BackupSpins Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.BackupSpins" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassBackupSpinsTopic" /><MSHelp:Keyword Index="K" Term="BackupSpins property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.BackupSpins property" /><MSHelp:Keyword Index="F" Term="BackupSpins" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.BackupSpins" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.BackupSpins" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.BackupSpins" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_BackupSpins" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of spins

by a backup." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.BackupSpins Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxFileSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogConfig_MaxFileSize" /><meta
name="guid" content="P_BerkeleyDB_LogConfig_MaxFileSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LogConfig.MaxFileSize" /><MSHelp:TOCTitle Title="MaxFileSize Property "
/><MSHelp:RLTitle Title="LogConfig.MaxFileSize Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.LogConfig.MaxFileSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogConfigClassMaxFileSizeTopic" /><MSHelp:Keyword Index="K" Term="MaxFileSize
property" /><MSHelp:Keyword Index="K" Term="LogConfig.MaxFileSize property" /><MSHelp:Keyword
Index="F" Term="MaxFileSize" /><MSHelp:Keyword Index="F" Term="LogConfig.MaxFileSize"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.MaxFileSize" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LogConfig.MaxFileSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogConfig.get_MaxFileSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogConfig.set_MaxFileSize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum size of a single file in the log, in bytes.
Because is an unsigned four-byte value, MaxFileSize may not be larger than the maximum unsigned four-byte
value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.MaxFileSize Property </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryQueueDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_SecondaryQueueDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryQueueDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryQueueDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryQueueDatabaseConfig<span
class="cs">..::<span
class="nu">.Creation Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryQueueDatabaseConfig.htm">SecondaryQueueDatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryBTreeDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_SecondaryBTreeDatabaseConfig__ctor" /><meta name="guid"
content="M_BerkeleyDB_SecondaryBTreeDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryBTreeDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyG
enDelegate)" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabaseConfig Constructor " /><MSHelp:RLTitle
Title="SecondaryBTreeDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryBTreeDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyG
enDelegate)" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassctorTopic" /><MSHelp:Keyword
Index="K" Term="SecondaryBTreeDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K"
Term="SecondaryBTreeDatabaseConfig.SecondaryBTreeDatabaseConfig constructor" /><MSHelp:Keyword
Index="F" Term="SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabaseConfig.SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.SecondaryBTreeDatabaseConfig" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig..ctor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Create a new SecondaryBTreeDatabaseConfig object" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AwaitedLSN Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_AwaitedLSN" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_AwaitedLSN" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.AwaitedLSN" /><MSHelp:TOCTitle Title="AwaitedLSN Property " /><MSHelp:RLTitle Title="ReplicationStats.AwaitedLSN Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.AwaitedLSN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassAwaitedLSNTopic" /><MSHelp:Keyword Index="K" Term="AwaitedLSN property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.AwaitedLSN property" /><MSHelp:Keyword Index="F" Term="AwaitedLSN" /><MSHelp:Keyword Index="F" Term="ReplicationStats.AwaitedLSN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.AwaitedLSN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.AwaitedLSN" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_AwaitedLSN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="LSN we're awaiting, if any." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;

height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.AwaitedLSN Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_RegionSize" /><meta name="guid" content="P_BerkeleyDB_LockStats_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="LockStats.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.RegionSize" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBLockStatsClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="LockStats.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="LockStats.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_LockStats.htm">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AutoCommit Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_AutoCommit" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_AutoCommit" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.AutoCommit" /><MSHelp:TOCTitle Title="AutoCommit Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.AutoCommit Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.AutoCommit" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassAutoCommitTopic" /><MSHelp:Keyword Index="K" Term="AutoCommit property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.AutoCommit property" /><MSHelp:Keyword Index="F" Term="AutoCommit" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.AutoCommit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.AutoCommit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.AutoCommit" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_AutoCommit" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_AutoCommit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, database operations for which no explicit transaction handle was specified, and which modify databases in the database environment, will be automatically enclosed within a transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.AutoCommit Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (UInt32, Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey_3" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (UInt32, Int32, LockingInfo)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultipleKey Method (UInt32, Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the
cursor at a specific key/data pair in the database, and store the key/data pair
and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeCursor.<span
class="vb">.::.MoveMultipleKey Method
(UInt32, Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeCursor.htm">BTreeCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>BulkBufferOverflows Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_ReplicationStats_BulkBufferOverflows"
/><meta name="guid" content="P_BerkeleyDB_ReplicationStats_BulkBufferOverflows" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.BulkBufferOverflows" /><MSHelp:TOCTitle
Title="BulkBufferOverflows Property " /><MSHelp:RLTitle Title="ReplicationStats.BulkBufferOverflows
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ReplicationStats.BulkBufferOverflows" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBReplicationStatsClassBulkBufferOverflowsTopic" /><MSHelp:Keyword Index="K"
Term="BulkBufferOverflows property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.BulkBufferOverflows property" /><MSHelp:Keyword Index="F"
Term="BulkBufferOverflows" /><MSHelp:Keyword Index="F" Term="ReplicationStats.BulkBufferOverflows"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.BulkBufferOverflows" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.BulkBufferOverflows" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ReplicationStats.get_BulkBufferOverflows" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Bulk buffer overflows." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.BulkBufferOverflows Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Less Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_KeyRange_Less" /><meta name="guid" content="P_BerkeleyDB_KeyRange_Less" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.KeyRange.Less" /><MSHelp:TOCTitle Title="Less Property " /><MSHelp:RLTitle Title="KeyRange.Less Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.KeyRange.Less" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyRangeClassLessTopic" /><MSHelp:Keyword Index="K" Term="Less property" /><MSHelp:Keyword Index="K" Term="KeyRange.Less property" /><MSHelp:Keyword Index="F" Term="Less" /><MSHelp:Keyword Index="F" Term="KeyRange.Less" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyRange.Less" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange.Less" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange.get_Less" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A value between 0 and 1, the

proportion of keys less than the specified key." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyRange..::.Less Property </td></tr><tr id="headerTableRow3"><td align="left">KeyRange Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_GetMultiple"
/><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_GetMultiple" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.GetMultiple" /><MSHelp:TOCTitle
Title="GetMultiple Method " /><MSHelp:RLTitle Title="QueueDatabase.GetMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.GetMultiple"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassGetMultipleTopic"
/><MSHelp:Keyword Index="K" Term="GetMultiple method" /><MSHelp:Keyword Index="K"
Term="QueueDatabase.GetMultiple method" /><MSHelp:Keyword Index="F" Term="GetMultiple"
/><MSHelp:Keyword Index="F" Term="QueueDatabase.GetMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.QueueDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.GetMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryCursor" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Methods " /><MSHelp:RLTitle Title="SecondaryCursor Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryCursor class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Name Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Transaction_Name" /><meta name="guid" content="P_BerkeleyDB_Transaction_Name" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Transaction.Name" /><MSHelp:TOCTitle Title="Name Property " /><MSHelp:RLTitle Title="Transaction.Name Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Transaction.Name" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassNameTopic" /><MSHelp:Keyword Index="K" Term="Name property" /><MSHelp:Keyword Index="K" Term="Transaction.Name property" /><MSHelp:Keyword Index="F" Term="Name" /><MSHelp:Keyword Index="F" Term="Transaction.Name" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Name" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Name" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.get_Name" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.set_Name" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The transaction's name. The name is returned by and displayed by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Name Property </td></tr><tr
id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevDuplicate_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevDuplicate_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.Cursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record

for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and that pair is stored in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseCursor_Dispose" /><meta name="guid" content="M_BerkeleyDB_BaseCursor_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseCursor.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="BaseCursor.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseCursor.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="BaseCursor.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="BaseCursor.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseCursor.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseCursor.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by this object, and close the cursor if it's still open." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">BaseCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxSequentialWrites Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxSequentialWrites" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxSequentialWrites" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxSequentialWrites" /><MSHelp:TOCTitle Title="MaxSequentialWrites Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxSequentialWrites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxSequentialWrites" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxSequentialWritesTopic" /><MSHelp:Keyword Index="K" Term="MaxSequentialWrites property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxSequentialWrites property" /><MSHelp:Keyword Index="F" Term="MaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxSequentialWrites" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxSequentialWrites" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxSequentialWrites" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxSequentialWrites" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of sequential write operations scheduled by the library when flushing dirty pages from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxSequentialWrites Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSiteConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DbSiteConfig" /><meta name="guid" content="T_BerkeleyDB_DbSiteConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DbSiteConfig" /><MSHelp:TOCTitle Title="DbSiteConfig Class" /><MSHelp:RLTitle Title="DbSiteConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DbSiteConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassTopic" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DbSiteConfig class" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class, about DbSiteConfig class" /><MSHelp:Keyword Index="F" Term="DbSiteConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSiteConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration properties for a site in replication manager." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CursorConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_CursorConfig" /><meta name="guid" content="T_BerkeleyDB_CursorConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.CursorConfig" /><MSHelp:TOCTitle Title="CursorConfig Class" /><MSHelp:RLTitle Title="CursorConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.CursorConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorConfigClassTopic" /><MSHelp:Keyword Index="K" Term="CursorConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CursorConfig class" /><MSHelp:Keyword Index="K" Term="CursorConfig class, about CursorConfig class" /><MSHelp:Keyword Index="F" Term="CursorConfig" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.CursorConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CursorConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_GetMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_GetMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.GetMultiple" /><MSHelp:TOCTitle Title="GetMultiple Method " /><MSHelp:RLTitle Title="HeapDatabase.GetMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.GetMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassGetMultipleTopic" /><MSHelp:Keyword Index="K" Term="GetMultiple method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.GetMultiple method" /><MSHelp:Keyword Index="F" Term="GetMultiple" /><MSHelp:Keyword Index="F"

Term="HeapDatabase.GetMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HeapDatabase.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label

class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.GetMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ReplicationHostAddress" /><meta name="guid" content="T_BerkeleyDB_ReplicationHostAddress" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:TOCTitle Title="ReplicationHostAddress Class" /><MSHelp:RLTitle Title="ReplicationHostAddress Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ReplicationHostAddress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressClassTopic" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ReplicationHostAddress class" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress class, about ReplicationHostAddress class" /><MSHelp:Keyword Index="F" Term="ReplicationHostAddress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationHostAddress" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationHostAddress" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing the address of a replication site used by Berkeley DB HA." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveFirstMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveFirstMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveFirstMultipleKey" /><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method " /><MSHelp:RLTitle Title="HashCursor.MoveFirstMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveFirstMultipleKey"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveFirstMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveFirstMultipleKey method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveFirstMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultipleKey" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div

id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveFirstMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignConflictException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_ForeignConflictException" /><meta name="guid" content="Properties_T_BerkeleyDB_ForeignConflictException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.ForeignConflictException" /><MSHelp:TOCTitle Title="ForeignConflictException Properties " /><MSHelp:RLTitle Title="ForeignConflictException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.ForeignConflictException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBForeignConflictExceptionPropertiesTopic" /><MSHelp:Keyword Index="K" Term="ForeignConflictException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignConflictException Properties </td></tr><tr id="headerTableRow3"><td align="left">ForeignConflictException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DeadlockException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DeadlockException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DeadlockException" /><MSHelp:TOCTitle Title="DeadlockException Members" /><MSHelp:RLTitle Title="DeadlockException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DeadlockException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="DeadlockException class" /><MSHelp:Keyword Index="K" Term="DeadlockException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DeadlockException class" /><MSHelp:Keyword Index="F" Term="DeadlockException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockException Members</td></tr><tr id="headerTableRow3"><td align="left">DeadlockException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogConfig_RegionSize" /><meta name="guid" content="P_BerkeleyDB_LogConfig_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogConfig.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="LogConfig.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogConfig.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="LogConfig.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="LogConfig.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.RegionSize" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.LogConfig.get_RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.set_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Te size of the underlying logging area of the Berkeley DB environment, in bytes." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveFirst_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveFirst_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveFirst(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveFirst Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveFirst Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveFirst(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store the secondary key along with the corresponding primary key/data pair in . If the first key has duplicate values, the f ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveFirst Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_HashDatabaseConfig_Duplicates" /><meta name="guid" content="F_BerkeleyDB_HashDatabaseConfig_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.HashDatabaseConfig.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Field" /><MSHelp:RLTitle Title="HashDatabaseConfig.Duplicates Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.HashDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates field" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.Duplicates field" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.Duplicates"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Policy for duplicate data items in the database; that is, insertion when the key of the key/data pair being inserted already exists in the database will be successful." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..::.Duplicates Field</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryBTreeDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryBTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabase Members" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase class" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryBTreeDatabase class" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">SecondaryBTreeDatabase Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleKeyDatabaseEntry
Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MultipleKeyDatabaseEntry" /><meta name="guid" content="Properties_T_BerkeleyDB_MultipleKeyDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MultipleKeyDatabaseEntry"
/><MSHelp:TOCTitle Title="MultipleKeyDatabaseEntry Properties " /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MultipleKeyDatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MultipleKeyDatabaseEntry class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">MultipleKeyDatabaseEntry Properties </td></tr><tr id="headerTableRow3"><td align="left">MultipleKeyDatabaseEntry Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSiteConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DbSiteConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_DbSiteConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DbSiteConfig" /><MSHelp:TOCTitle Title="DbSiteConfig Methods " /><MSHelp:RLTitle Title="DbSiteConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DbSiteConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="DbSiteConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_KeyRange" /><meta name="guid" content="Properties_T_BerkeleyDB_KeyRange" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.KeyRange" /><MSHelp:TOCTitle Title="KeyRange Properties " /><MSHelp:RLTitle Title="KeyRange Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.KeyRange" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyRangePropertiesTopic" /><MSHelp:Keyword Index="K" Term="KeyRange class,

properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"

for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyRange Properties </td></tr><tr id="headerTableRow3"><td align="left">KeyRange Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FreePages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_FreePages" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_FreePages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.FreePages" /><MSHelp:TOCTitle Title="FreePages Property " /><MSHelp:RLTitle Title="BTreeStats.FreePages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.FreePages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassFreePagesTopic" /><MSHelp:Keyword Index="K" Term="FreePages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.FreePages property" /><MSHelp:Keyword Index="F" Term="FreePages" /><MSHelp:Keyword Index="F" Term="BTreeStats.FreePages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.FreePages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.FreePages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_FreePages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages on the free list." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.FreePages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogVerifyConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_LogVerifyConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_LogVerifyConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.LogVerifyConfig.#ctor" /><MSHelp:TOCTitle Title="LogVerifyConfig Constructor " /><MSHelp:RLTitle Title="LogVerifyConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.LogVerifyConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig class, constructor" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.LogVerifyConfig constructor" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.LogVerifyConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.LogVerifyConfig" /><MSHelp:Attr

Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new LogVerifyConfig object, with the default configuration settings." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryHashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryHashDatabaseConfig Properties " /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryDatabaseConfig Methods " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley

DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionTimeUSec Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionTimeUSec" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionTimeUSec" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionTimeUSec" /><MSHelp:TOCTitle Title="ElectionTimeUSec Property " /><MSHelp:RLTitle Title="ReplicationStats.ElectionTimeUSec Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionTimeUSec" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionTimeUSecTopic" /><MSHelp:Keyword Index="K" Term="ElectionTimeUSec property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionTimeUSec property" /><MSHelp:Keyword Index="F" Term="ElectionTimeUSec" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionTimeUSec" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionTimeUSec" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionTimeUSec" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionTimeUSec" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Last election time useconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionTimeUSec Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>WaitsForTable Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_WaitsForTable" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_WaitsForTable" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.WaitsForTable" /><MSHelp:TOCTitle Title="WaitsForTable Field" /><MSHelp:RLTitle Title="VerboseMessages.WaitsForTable Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.WaitsForTable" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassWaitsForTableTopic" /><MSHelp:Keyword Index="K" Term="WaitsForTable field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.WaitsForTable field" /><MSHelp:Keyword Index="F" Term="WaitsForTable" /><MSHelp:Keyword Index="F" Term="VerboseMessages.WaitsForTable" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.VerboseMessages.WaitsForTable" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.WaitsForTable" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the waits-for table when doing deadlock detection." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.WaitsForTable Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitTxnCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_InitTxnCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_InitTxnCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.InitTxnCount" /><MSHelp:TOCTitle Title="InitTxnCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.InitTxnCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.InitTxnCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassInitTxnCountTopic" /><MSHelp:Keyword Index="K" Term="InitTxnCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.InitTxnCount property" /><MSHelp:Keyword Index="F" Term="InitTxnCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.InitTxnCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.InitTxnCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.InitTxnCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_InitTxnCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.set_InitTxnCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of transactions catered for by the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.InitTxnCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxHashLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_MaxHashLockNoWait" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_MaxHashLockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.MaxHashLockNoWait" /><MSHelp:TOCTitle Title="MaxHashLockNoWait Property " /><MSHelp:RLTitle Title="MPoolStats.MaxHashLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.MaxHashLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassMaxHashLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="MaxHashLockNoWait property" /><MSHelp:Keyword Index="K" Term="MPoolStats.MaxHashLockNoWait property" /><MSHelp:Keyword Index="F" Term="MaxHashLockNoWait" /><MSHelp:Keyword Index="F" Term="MPoolStats.MaxHashLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.MaxHashLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.MaxHashLockNoWait" /><MSHelp:Attr

Name="APIName" Value="BerkeleyDB.MPoolStats.get_MaxHashLockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max hash lock granted with nowait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.MaxHashLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SyncMemPool
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_SyncMemPool" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_SyncMemPool" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.SyncMemPool" /><MSHelp:TOCTitle Title="SyncMemPool
Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.SyncMemPool Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.SyncMemPool" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.SyncMemPool" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Flush all modified pages in the cache to their backing files." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.SyncMemPool Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (DatabaseEntry, Boolean, Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultiple Method (DatabaseEntry, Boolean, Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveMultiple Method (DatabaseEntry, Boolean, Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveMultiple(BerkeleyDB.DatabaseEntry,System.Boolean,System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store that key and as many duplicate data items associated with the given key that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span
class="languageSpecificText">..<span
class="cpp">::.MoveMultiple Method (DatabaseEntry, Boolean, Int32,
LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReverseSplit
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_ReverseSplit" /><meta
name="guid" content="P_BerkeleyDB_BTreeDatabase_ReverseSplit" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.BTreeDatabase.ReverseSplit" /><MSHelp:TOCTitle Title="ReverseSplit Property "
/><MSHelp:RLTitle Title="BTreeDatabase.ReverseSplit Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.BTreeDatabase.ReverseSplit" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeDatabaseClassReverseSplitTopic" /><MSHelp:Keyword Index="K"
Term="ReverseSplit property" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.ReverseSplit property"
/><MSHelp:Keyword Index="F" Term="ReverseSplit" /><MSHelp:Keyword Index="F"
Term="BTreeDatabase.ReverseSplit" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeDatabase.ReverseSplit" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.ReverseSplit" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.get_ReverseSplit" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If false, empty
pages will not be coalesced into higher-level pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.ReverseSplit Property </td></tr><tr id="headerTableRow3"><td
 align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
 </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ReplicationStats" /><meta name="guid" content="Methods_T_BerkeleyDB_ReplicationStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ReplicationStats" /><MSHelp:TOCTitle Title="ReplicationStats Methods " /><MSHelp:RLTitle Title="ReplicationStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.ReplicationStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="ReplicationStats class, methods" /><MSHelp:Attr Name="DevLang"
 Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
 style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats Methods </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockPolicy Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DeadlockPolicy" /><meta name="guid" content="T_BerkeleyDB_DeadlockPolicy" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DeadlockPolicy" /><MSHelp:TOCTitle Title="DeadlockPolicy Class" /><MSHelp:RLTitle

Title="DeadlockPolicy Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DeadlockPolicy" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassTopic" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DeadlockPolicy class" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy class, about DeadlockPolicy class" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class to represent what lock request(s) should be rejected during deadlock resolution." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">DeadlockPolicy Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Exists_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Exists_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Exists(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Exists Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="BaseDatabase.Exists Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Exists(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Check whether appears in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Exists Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Stats_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Stats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Stats Method (Transaction)" /><MSHelp:RLTitle Title="HashDatabase.Stats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Stats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Dispose Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEntry_Dispose" /><meta name="guid" content="M_BerkeleyDB_DatabaseEntry_Dispose" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEntry.Dispose" /><MSHelp:TOCTitle Title="Dispose Method " /><MSHelp:RLTitle Title="DatabaseEntry.Dispose Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEntry.Dispose" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassDisposeTopic" /><MSHelp:Keyword Index="K" Term="Dispose method" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.Dispose method" /><MSHelp:Keyword Index="F" Term="Dispose" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.Dispose" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry.Dispose" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.Dispose" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Release the resources held by the underlying C library." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry..::.Dispose Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>StartTime Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_StartTime" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_StartTime" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogVerifyConfig.StartTime" /><MSHelp:TOCTitle Title="StartTime Property " /><MSHelp:RLTitle Title="LogVerifyConfig.StartTime Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.StartTime" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassStartTimeTopic" /><MSHelp:Keyword Index="K" Term="StartTime property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.StartTime property" /><MSHelp:Keyword Index="F" Term="StartTime" /><MSHelp:Keyword Index="F" Term="LogVerifyConfig.StartTime" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogVerifyConfig.StartTime" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.StartTime" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_StartTime" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_StartTime" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The starting time to verify." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.StartTime Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists

method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"

onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_FastStats_1" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_FastStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction)" /><MSHelp:RLTitle Title="HeapDatabase.FastStats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.FastStats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrefixCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_PrefixCompare" /><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_PrefixCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.PrefixCompare" /><MSHelp:TOCTitle Title="PrefixCompare Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.PrefixCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.PrefixCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassPrefixCompareTopic" /><MSHelp:Keyword Index="K" Term="PrefixCompare field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.PrefixCompare field" /><MSHelp:Keyword Index="F" Term="PrefixCompare" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig.PrefixCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.PrefixCompare"

/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.PrefixCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree prefix function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig..::.PrefixCompare Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabase
Properties </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Properties_T_BerkeleyDB_HeapDatabase" /><meta name="guid"
content="Properties_T_BerkeleyDB_HeapDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.HeapDatabase" /><MSHelp:TOCTitle Title="HeapDatabase Properties "
/><MSHelp:RLTitle Title="HeapDatabase
Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.HeapDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabasePropertiesTopic" /><MSHelp:Keyword
Index="K" Term="HeapDatabase class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepProcMsgResult Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script
type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_RepProcMsgResult" /><meta name="guid" content="Fields_T_BerkeleyDB_RepProcMsgResult" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.RepProcMsgResult" /><MSHelp:TOCTitle Title="RepProcMsgResult Fields" /><MSHelp:RLTitle Title="RepProcMsgResult Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.RepProcMsgResult" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultFieldsTopic" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RepProcMsgResult Fields</td></tr><tr id="headerTableRow3"><td
align="left">RepProcMsgResult Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Current Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="P_BerkeleyDB_SecondaryCursor_Current" /><meta name="guid"
content="P_BerkeleyDB_SecondaryCursor_Current" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryCursor.Current" /><MSHelp:TOCTitle Title="Current Property "
/><MSHelp:RLTitle Title="SecondaryCursor.Current Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SecondaryCursor.Current" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryCursorClassCurrentTopic" /><MSHelp:Keyword Index="K" Term="Current property" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.Current property" /><MSHelp:Keyword Index="F" Term="Current" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.Current"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.Current" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Current" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryCursor.get_Current"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.set_Current" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The secondary key and primary key/data pair at which the cursor currently points."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"

style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Current Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicateCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BTreeDatabaseConfig_DuplicateCompare" /><meta name="guid" content="F_BerkeleyDB_BTreeDatabaseConfig_DuplicateCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BTreeDatabaseConfig.DuplicateCompare" /><MSHelp:TOCTitle Title="DuplicateCompare Field" /><MSHelp:RLTitle Title="BTreeDatabaseConfig.DuplicateCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassDuplicateCompareTopic" /><MSHelp:Keyword Index="K" Term="DuplicateCompare field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.DuplicateCompare field" /><MSHelp:Keyword Index="F" Term="DuplicateCompare" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.DuplicateCompare Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepAckTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepAckTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepAckTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepAckTimeout" /><MSHelp:TOCTitle Title="RepAckTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepAckTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepAckTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepAckTimeoutTopic" /><MSHelp:Keyword Index="K" Term="RepAckTimeout property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepAckTimeout property" /><MSHelp:Keyword Index="F" Term="RepAckTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepAckTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepAckTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepAckTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepAckTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepAckTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time the replication manager's transport function waits to collect enough acknowledgments from replication group clients, before giving up and returning a failure indication. The defa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepAckTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationHostAddress__ctor" /><meta name="guid" content="M_BerkeleyDB_ReplicationHostAddress__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationHostAddress.#ctor" /><MSHelp:TOCTitle Title="ReplicationHostAddress Constructor " /><MSHelp:RLTitle Title="ReplicationHostAddress Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationHostAddress.#ctor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationHostAddress..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new, empty address" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress Constructor </td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryRecnoDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="M_BerkeleyDB_SecondaryRecnoDatabase_Open" /><meta name="guid"
content="M_BerkeleyDB_SecondaryRecnoDatabase_Open" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,BerkeleyDB.SecondaryRecnoDatabaseConf
ig)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryRecnoDatabaseConfig)" /><MSHelp:RLTitle
Title="SecondaryRecnoDatabase.Open Method (String, SecondaryRecnoDatabaseConfig) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryRecnoDatabase.Open(System.String,BerkeleyDB.SecondaryRecnoDatabaseConfi
g)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryRecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new
SecondaryRecnoDatabase object, open the database represented by and associate the database with the primary
index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Open Method (String, SecondaryRecnoDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>StoredValue Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_StoredValue" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_StoredValue" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.StoredValue" /><MSHelp:TOCTitle Title="StoredValue Property " /><MSHelp:RLTitle Title="SequenceStats.StoredValue Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.StoredValue" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassStoredValueTopic" /><MSHelp:Keyword Index="K" Term="StoredValue property" /><MSHelp:Keyword Index="K" Term="SequenceStats.StoredValue property" /><MSHelp:Keyword Index="F" Term="StoredValue" /><MSHelp:Keyword Index="F" Term="SequenceStats.StoredValue" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.StoredValue" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.StoredValue" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_StoredValue" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current value in db." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats..::.StoredValue Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryBTreeDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryBTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryBTreeDatabase" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabase Methods " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryBTreeDatabase"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase class, methods" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"

value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="HeapDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="HeapDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method (CompactConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_RecnoDatabase_Compact" /><meta name="guid"
content="M_BerkeleyDB_RecnoDatabase_Compact" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.RecnoDatabase.Compact(BerkeleyDB.CompactConfig)" /><MSHelp:TOCTitle
Title="Compact Method (CompactConfig)" /><MSHelp:RLTitle Title="RecnoDatabase.Compact Method
(CompactConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.RecnoDatabase.Compact(BerkeleyDB.CompactConfig)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Compact" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Compact the database, and optionally return unused database pages to the underlying filesystem."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Compact Method (CompactConfig)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNextMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveNextMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextMultipleKey" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNextMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveNextMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextMultipleKey method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveNextMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveNextMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Min Property

</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Min" /><meta name="guid" content="P_BerkeleyDB_Sequence_Min" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.Min" /><MSHelp:TOCTitle Title="Min Property " /><MSHelp:RLTitle Title="Sequence.Min Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Min" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassMinTopic" /><MSHelp:Keyword Index="K" Term="Min property" /><MSHelp:Keyword Index="K" Term="Sequence.Min property" /><MSHelp:Keyword Index="F" Term="Min" /><MSHelp:Keyword Index="F" Term="Sequence.Min" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Min" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Min" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Min" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The minimum value in the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Min Property </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashLockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_HashLockWait" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_HashLockWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.HashLockWait" /><MSHelp:TOCTitle Title="HashLockWait Property " /><MSHelp:RLTitle Title="MPoolStats.HashLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.HashLockWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassHashLockWaitTopic" /><MSHelp:Keyword Index="K" Term="HashLockWait property" /><MSHelp:Keyword Index="K" Term="MPoolStats.HashLockWait property" /><MSHelp:Keyword Index="F" Term="HashLockWait" /><MSHelp:Keyword Index="F" Term="MPoolStats.HashLockWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.HashLockWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.HashLockWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_HashLockWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Hash lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">MPoolStats<span
class="cs">..::<span
class="nu">.HashLockWait Property </td></tr><tr id="headerTableRow3"><td
align="left">MPoolStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MovePrev" /><meta
name="guid" content="Overload_BerkeleyDB_RecnoCursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.RecnoCursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method "

/><MSHelp:RLTitle Title="RecnoCursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MovePrev" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMovePrevTopic" /><MSHelp:Keyword Index="K" Term="MovePrev method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MovePrev method" /><MSHelp:Keyword Index="F" Term="MovePrev" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MovePrev" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetMultiple Method (DatabaseEntry, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_GetMultiple_1" /><meta name="guid" content="M_BerkeleyDB_Database_GetMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry,System.Int32)" /><MSHelp:TOCTitle Title="GetMultiple Method (DatabaseEntry, Int32)" /><MSHelp:RLTitle Title="Database.GetMultiple Method (DatabaseEntry, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.GetMultiple(BerkeleyDB.DatabaseEntry,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.GetMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a key and all duplicate data items from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::<span
class="nu">.GetMultiple Method (DatabaseEntry, Int32)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_SecondaryHashDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID"

Value="F:BerkeleyDB.SecondaryHashDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryHashDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td

align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_HOLDELECTION Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_HOLDELECTION" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_HOLDELECTION" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_HOLDELECTION" /><MSHelp:TOCTitle Title="DB_REP_HOLDELECTION Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_HOLDELECTION Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_HOLDELECTION" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_HOLDELECTIONTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_HOLDELECTION field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_HOLDELECTION field" /><MSHelp:Keyword Index="F" Term="DB_REP_HOLDELECTION" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_HOLDELECTION" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_HOLDELECTION" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_HOLDELECTION" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Time to hold an election." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_HOLDELECTION Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_LeaseTimeout" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_LeaseTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.LeaseTimeout" /><MSHelp:TOCTitle Title="LeaseTimeout Property "

/><MSHelp:RLTitle Title="ReplicationConfig.LeaseTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.LeaseTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassLeaseTimeoutTopic" /><MSHelp:Keyword Index="K" Term="LeaseTimeout property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.LeaseTimeout property" /><MSHelp:Keyword Index="F" Term="LeaseTimeout" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.LeaseTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.LeaseTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
 /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.LeaseTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_LeaseTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_LeaseTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time a client grants its master lease to a master. When using master leases all sites in a replication group must use the same lease timeout value. There is no default value. If leases ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
 height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
 event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
 for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.LeaseTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DeadlockException" /><meta name="guid" content="Methods_T_BerkeleyDB_DeadlockException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DeadlockException" /><MSHelp:TOCTitle Title="DeadlockException Methods " /><MSHelp:RLTitle Title="DeadlockException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DeadlockException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="DeadlockException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockException Methods </td></tr><tr id="headerTableRow3"><td align="left">DeadlockException Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_Cursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.Cursor" /><MSHelp:TOCTitle Title="Cursor Members" /><MSHelp:RLTitle Title="Cursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="Cursor class" /><MSHelp:Keyword Index="K" Term="Cursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Cursor class" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor Members</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class Methods Properties See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DiskFileNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_DiskFileNumber" /><meta name="guid" content="P_BerkeleyDB_LogStats_DiskFileNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.DiskFileNumber" /><MSHelp:TOCTitle Title="DiskFileNumber Property " /><MSHelp:RLTitle Title="LogStats.DiskFileNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.DiskFileNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassDiskFileNumberTopic" /><MSHelp:Keyword Index="K" Term="DiskFileNumber property" /><MSHelp:Keyword Index="K" Term="LogStats.DiskFileNumber property" /><MSHelp:Keyword Index="F" Term="DiskFileNumber" /><MSHelp:Keyword Index="F" Term="LogStats.DiskFileNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.DiskFileNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.DiskFileNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_DiskFileNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Known on disk log file number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.DiskFileNumber Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_HashCursor_Duplicate" /><meta name="guid"
content="M_BerkeleyDB_HashCursor_Duplicate" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashCursor.Duplicate(System.Boolean)" /><MSHelp:TOCTitle Title="Duplicate Method "
/><MSHelp:RLTitle Title="HashCursor.Duplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.HashCursor.Duplicate(System.Boolean)" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashCursorClassDuplicateTopic"
/><MSHelp:Keyword Index="K" Term="Duplicate method" /><MSHelp:Keyword Index="K"
Term="HashCursor.Duplicate method" /><MSHelp:Keyword Index="F" Term="Duplicate" /><MSHelp:Keyword
Index="F" Term="HashCursor.Duplicate" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashCursor.Duplicate" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HashCursor.Duplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new cursor that uses the
same transaction and locker ID as the original cursor." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.Duplicate Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintTransactionSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintTransactionSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintTransactionSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:TOCTitle Title="PrintTransactionSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintTransactionSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintTransactionSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the transaction subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span
class="nu">.PrintTransactionSystemStats Method </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>EntryPrefixComparisonDelegate Delegate</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_EntryPrefixComparisonDelegate" /><meta name="guid"

content="T_BerkeleyDB_EntryPrefixComparisonDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EntryPrefixComparisonDelegate" /><MSHelp:TOCTitle Title="EntryPrefixComparisonDelegate Delegate" /><MSHelp:RLTitle Title="EntryPrefixComparisonDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EntryPrefixComparisonDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEntryPrefixComparisonDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="EntryPrefixComparisonDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EntryPrefixComparisonDelegate delegate" /><MSHelp:Keyword Index="F" Term="EntryPrefixComparisonDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EntryPrefixComparisonDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryPrefixComparisonDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryPrefixComparisonDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryPrefixComparisonDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryPrefixComparisonDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EntryPrefixComparisonDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An application-specified prefix comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EntryPrefixComparisonDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepRetransmissionRequestMin Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepRetransmissionRequestMin" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepRetransmissionRequestMin" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMin" /><MSHelp:TOCTitle Title="RepRetransmissionRequestMin Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepRetransmissionRequestMin Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMin" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepRetransmissionRequestMinTopic" /><MSHelp:Keyword Index="K" Term="RepRetransmissionRequestMin property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepRetransmissionRequestMin property" /><MSHelp:Keyword Index="F" Term="RepRetransmissionRequestMin" />
<MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepRetransmissionRequestMin" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMin" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepRetransmissionRequestMin" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepRetransmissionRequestMin" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The minimum number of microseconds a client waits before requesting retransmission." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepRetransmissionRequestMin Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EnvironmentFeedbackEvent Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_EnvironmentFeedbackEvent" /><meta name="guid" content="T_BerkeleyDB_EnvironmentFeedbackEvent" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.EnvironmentFeedbackEvent" /><MSHelp:TOCTitle Title="EnvironmentFeedbackEvent Enumeration" /><MSHelp:RLTitle Title="EnvironmentFeedbackEvent Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.EnvironmentFeedbackEvent" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.EnvironmentFeedbackEvent.RECOVERY" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBEnvironmentFeedbackEventClassTopic" /><MSHelp:Keyword Index="K" Term="EnvironmentFeedbackEvent enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.EnvironmentFeedbackEvent enumeration" /><MSHelp:Keyword Index="K" Term="RECOVERY enumeration member" /><MSHelp:Keyword Index="F" Term="EnvironmentFeedbackEvent" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentFeedbackEvent" /><MSHelp:Keyword Index="F" Term="EnvironmentFeedbackEvent.RECOVERY" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.EnvironmentFeedbackEvent.RECOVERY" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackEvent" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.EnvironmentFeedbackEvent.RECOVERY" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies the environment operation whose progress is being reported" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">EnvironmentFeedbackEvent Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupOptions Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_BackupOptions" /><meta name="guid" content="Fields_T_BerkeleyDB_BackupOptions" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.BackupOptions" /><MSHelp:TOCTitle Title="BackupOptions Fields" /><MSHelp:RLTitle Title="BackupOptions Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.BackupOptions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsFieldsTopic" /><MSHelp:Keyword Index="K" Term="BackupOptions class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions Fields</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FillFactor Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashDatabase_FillFactor" /><meta name="guid" content="P_BerkeleyDB_HashDatabase_FillFactor" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashDatabase.FillFactor" /><MSHelp:TOCTitle Title="FillFactor Property " /><MSHelp:RLTitle Title="HashDatabase.FillFactor Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashDatabase.FillFactor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassFillFactorTopic" /><MSHelp:Keyword Index="K" Term="FillFactor property" /><MSHelp:Keyword Index="K" Term="HashDatabase.FillFactor property" /><MSHelp:Keyword Index="F" Term="FillFactor" /><MSHelp:Keyword Index="F" Term="HashDatabase.FillFactor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.FillFactor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.FillFactor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.get_FillFactor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The desired density within the hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.FillFactor Property </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Current Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_JoinCursor_Current" /><meta name="guid" content="P_BerkeleyDB_JoinCursor_Current" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.JoinCursor.Current" /><MSHelp:TOCTitle Title="Current Property " /><MSHelp:RLTitle Title="JoinCursor.Current Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.JoinCursor.Current" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBJoinCursorClassCurrentTopic" /><MSHelp:Keyword Index="K" Term="Current property" /><MSHelp:Keyword Index="K" Term="JoinCursor.Current property" /><MSHelp:Keyword Index="F" Term="Current" /><MSHelp:Keyword Index="F" Term="JoinCursor.Current" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.JoinCursor.Current" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.Current" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.get_Current" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.set_Current" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The key/data pair at which the cursor currently points." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">JoinCursor.<span
class="vb">.::.Current Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_JoinCursor.htm">JoinCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolConfig
Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MPoolConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_MPoolConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MPoolConfig.#ctor" /><MSHelp:TOCTitle Title="MPoolConfig Constructor " /><MSHelp:RLTitle Title="MPoolConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MPoolConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="MPoolConfig class, constructor" /><MSHelp:Keyword Index="K" Term="MPoolConfig.MPoolConfig constructor" /><MSHelp:Keyword Index="F" Term="MPoolConfig" /><MSHelp:Keyword Index="F" Term="MPoolConfig.MPoolConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig.MPoolConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Strict2Site Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_Strict2Site" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_Strict2Site" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.Strict2Site" /><MSHelp:TOCTitle Title="Strict2Site Field" /><MSHelp:RLTitle Title="ReplicationConfig.Strict2Site Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.Strict2Site" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassStrict2SiteTopic" /><MSHelp:Keyword Index="K" Term="Strict2Site field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.Strict2Site field" /><MSHelp:Keyword Index="F" Term="Strict2Site" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.Strict2Site" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.Strict2Site" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.Strict2Site" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the Replication Manager will observe the strict "majority" rule in managing elections, even in a group with only 2 sites. This means the client in a 2-site group will be unable to take over as ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.Strict2Site Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultipleKey Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_RefreshMultipleKey_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_RefreshMultipleKey_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.RefreshMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="RefreshMultipleKey Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.RefreshMultipleKey

Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.RefreshMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultipleKey Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (UInt32, Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey_2" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32,System.Int32)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (UInt32, Int32)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultipleKey Method (UInt32, Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32,System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultipleKey Method (UInt32, Int32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_Database_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="Database.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="Database.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="Database.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse

image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Database..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolConfig
Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_MPoolConfig" /><meta
name="guid" content="Methods_T_BerkeleyDB_MPoolConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.MPoolConfig" /><MSHelp:TOCTitle Title="MPoolConfig Methods "
/><MSHelp:RLTitle Title="MPoolConfig Methods (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Methods.T:BerkeleyDB.MPoolConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMPoolConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="MPoolConfig class,
methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">MPoolConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseExpiredException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_LeaseExpiredException" /><meta name="guid" content="Methods_T_BerkeleyDB_LeaseExpiredException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:TOCTitle Title="LeaseExpiredException Methods " /><MSHelp:RLTitle Title="LeaseExpiredException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LeaseExpiredException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLeaseExpiredExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="LeaseExpiredException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LeaseExpiredException Methods </td></tr><tr id="headerTableRow3"><td align="left">LeaseExpiredException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EncryptionPassword Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_EncryptionPassword" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_EncryptionPassword" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.EncryptionPassword" /><MSHelp:TOCTitle Title="EncryptionPassword Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.EncryptionPassword Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.EncryptionPassword" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassEncryptionPasswordTopic" /><MSHelp:Keyword Index="K" Term="EncryptionPassword property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.EncryptionPassword property" /><MSHelp:Keyword Index="F" Term="EncryptionPassword" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.EncryptionPassword" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.EncryptionPassword" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.EncryptionPassword" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_EncryptionPassword" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The password used to perform encryption and decryption." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.EncryptionPassword Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionStatus Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionStatus" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionStatus" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionStatus" /><MSHelp:TOCTitle Title="ElectionStatus Property " /><MSHelp:RLTitle Title="ReplicationStats.ElectionStatus Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionStatus" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionStatusTopic" /><MSHelp:Keyword Index="K" Term="ElectionStatus property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionStatus property" /><MSHelp:Keyword Index="F" Term="ElectionStatus" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionStatus" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionStatus" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionStatus" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionStatus" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current election status." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionStatus Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FailCheck Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_FailCheck" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_FailCheck" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.FailCheck" /><MSHelp:TOCTitle Title="FailCheck Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.FailCheck Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.FailCheck" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassFailCheckTopic" /><MSHelp:Keyword Index="K" Term="FailCheck method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.FailCheck method" /><MSHelp:Keyword Index="F" Term="FailCheck" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.FailCheck" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.FailCheck" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.FailCheck" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Check for threads of control (either a true thread or a process) that have exited while manipulating Berkeley DB library data structures, while holding a logical database lock, or with an unresolve ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.FailCheck Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Host Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationHostAddress_Host" /><meta name="guid" content="F_BerkeleyDB_ReplicationHostAddress_Host" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationHostAddress.Host" /><MSHelp:TOCTitle Title="Host Field" /><MSHelp:RLTitle Title="ReplicationHostAddress.Host Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationHostAddress.Host" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationHostAddressClassHostTopic" /><MSHelp:Keyword Index="K" Term="Host field" /><MSHelp:Keyword Index="K" Term="ReplicationHostAddress.Host field" /><MSHelp:Keyword Index="F" Term="Host" /><MSHelp:Keyword Index="F" Term="ReplicationHostAddress.Host" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationHostAddress.Host" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationHostAddress.Host" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The site's host identification string, generally a TCP/IP host name." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">ReplicationHostAddress..::.Host Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationHostAddress Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionThreads Property </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RepMgrStats_ElectionThreads" /><meta name="guid" content="P_BerkeleyDB_RepMgrStats_ElectionThreads" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RepMgrStats.ElectionThreads" /><MSHelp:TOCTitle Title="ElectionThreads Property "

/><MSHelp:RLTitle
Title="RepMgrStats.ElectionThreads Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.RepMgrStats.ElectionThreads" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRepMgrStatsClassElectionThreadsTopic" /><MSHelp:Keyword Index="K"
Term="ElectionThreads property" /><MSHelp:Keyword Index="K" Term="RepMgrStats.ElectionThreads
property" /><MSHelp:Keyword Index="F" Term="ElectionThreads" /><MSHelp:Keyword Index="F"
Term="RepMgrStats.ElectionThreads" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RepMgrStats.ElectionThreads" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RepMgrStats.ElectionThreads" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RepMgrStats.get_ElectionThreads" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Number of currently active election threads" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats..::.ElectionThreads Property </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimestamp Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TxnTimestamp" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TxnTimestamp" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TxnTimestamp" /><MSHelp:TOCTitle Title="TxnTimestamp Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TxnTimestamp Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TxnTimestamp" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTxnTimestampTopic" /><MSHelp:Keyword Index="K" Term="TxnTimestamp property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TxnTimestamp property" /><MSHelp:Keyword Index="F" Term="TxnTimestamp" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TxnTimestamp" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TxnTimestamp" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TxnTimestamp" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TxnTimestamp" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TxnTimestamp" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The recovery timestamp" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TxnTimestamp Property </td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnNoWait Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnNoWait" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnNoWait" /><MSHelp:TOCTitle Title="TxnNoWait Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TxnNoWait Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTxnNoWaitTopic" /><MSHelp:Keyword

Index="K" Term="TxnNoWait field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TxnNoWait field" /><MSHelp:Keyword Index="F" Term="TxnNoWait" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TxnNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TxnNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TxnNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true and a lock is unavailable for any Berkeley DB operation performed in the context of a transaction, cause the operation to throw (or if is set." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TxnNoWait Field</td></tr><tr

id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html;
 charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>AllocatedLockers Property </title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_LockStats_AllocatedLockers" /><meta name="guid"
content="P_BerkeleyDB_LockStats_AllocatedLockers" /><xml><MSHelp:Attr Name="AssetID"
 Value="P:BerkeleyDB.LockStats.AllocatedLockers" /><MSHelp:TOCTitle Title="AllocatedLockers Property "
/><MSHelp:RLTitle Title="LockStats.AllocatedLockers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LockStats.AllocatedLockers" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassAllocatedLockersTopic" /><MSHelp:Keyword Index="K"
Term="AllocatedLockers property" /><MSHelp:Keyword Index="K" Term="LockStats.AllocatedLockers property"
/><MSHelp:Keyword Index="F" Term="AllocatedLockers" /><MSHelp:Keyword Index="F"
Term="LockStats.AllocatedLockers" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockStats.AllocatedLockers" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.AllocatedLockers" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.get_AllocatedLockers" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang"
 Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Current number of lockers allocated." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage"
 style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.AllocatedLockers Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimestamp Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_TxnTimestamp" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_TxnTimestamp" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.TxnTimestamp" /><MSHelp:TOCTitle Title="TxnTimestamp Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TxnTimestamp Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.TxnTimestamp" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTxnTimestampTopic" /><MSHelp:Keyword Index="K" Term="TxnTimestamp property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TxnTimestamp property" /><MSHelp:Keyword Index="F" Term="TxnTimestamp" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TxnTimestamp"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TxnTimestamp" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TxnTimestamp" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_TxnTimestamp" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.set_TxnTimestamp" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Recover to the time specified by timestamp rather than to the most current possible date." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TxnTimestamp Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Feedback Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Feedback" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Feedback" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Feedback" /><MSHelp:TOCTitle Title="Feedback Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Feedback Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Feedback" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassFeedbackTopic" /><MSHelp:Keyword Index="K" Term="Feedback property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Feedback property" /><MSHelp:Keyword Index="F" Term="Feedback" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Feedback" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Feedback" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Feedback" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Feedback" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_Feedback" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Monitor progress within long running operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Feedback Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_Move" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.Move" /><MSHelp:TOCTitle Title="Move Method " /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMoveTopic" /><MSHelp:Keyword Index="K" Term="Move method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.Move method" /><MSHelp:Keyword Index="F" Term="Move" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.Move" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor<span

class="cs">..::.Move Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationSync Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_VerboseMessages_ReplicationSync" /><meta name="guid"
content="F_BerkeleyDB_VerboseMessages_ReplicationSync" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.VerboseMessages.ReplicationSync" /><MSHelp:TOCTitle Title="ReplicationSync Field"
/><MSHelp:RLTitle Title="VerboseMessages.ReplicationSync Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationSync" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBVerboseMessagesClassReplicationSyncTopic" /><MSHelp:Keyword Index="K"
Term="ReplicationSync field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationSync field"
/><MSHelp:Keyword Index="F" Term="ReplicationSync" /><MSHelp:Keyword Index="F"
Term="VerboseMessages.ReplicationSync" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.VerboseMessages.ReplicationSync" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr
 Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.VerboseMessages.ReplicationSync" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about replication client synchronization." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
 /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.ReplicationSync Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Backup Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_Backup" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_Backup" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.Backup" /><MSHelp:TOCTitle Title="Backup Field" /><MSHelp:RLTitle Title="VerboseMessages.Backup Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.Backup" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassBackupTopic" /><MSHelp:Keyword Index="K" Term="Backup field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.Backup field" /><MSHelp:Keyword Index="F" Term="Backup" /><MSHelp:Keyword Index="F" Term="VerboseMessages.Backup" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.Backup" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.Backup" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display additional information when performing hot backup." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.Backup Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrevDuplicate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrevDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the previous key/data pair of the database is a duplicate data record for the current key/data pair, the cursor is moved to the previous key/data pair of the database, and the secondary key and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirst" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="Cursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirst" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair in . If the first key has duplicate values, the first data item in the set of duplicates is stored in . ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr
id="headerTableRow2"><td align="left">Cursor<span
class="cs">..::<span
class="nu">.MoveFirst Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepSystemCfg
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_RepSystemCfg" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_RepSystemCfg" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.RepSystemCfg" /><MSHelp:TOCTitle Title="RepSystemCfg Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.RepSystemCfg Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.RepSystemCfg" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassRepSystemCfgTopic" /><MSHelp:Keyword Index="K" Term="RepSystemCfg field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.RepSystemCfg field" /><MSHelp:Keyword Index="F" Term="RepSystemCfg" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.RepSystemCfg" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.RepSystemCfg" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.RepSystemCfg" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configuration for the replication subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironmentConfig<span
class="cs">..::<span
class="nu">.RepSystemCfg Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MaxBucketLength Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="P_BerkeleyDB_LockStats_MaxBucketLength" /><meta name="guid"
content="P_BerkeleyDB_LockStats_MaxBucketLength" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.MaxBucketLength" /><MSHelp:TOCTitle Title="MaxBucketLength Property "
/><MSHelp:RLTitle Title="LockStats.MaxBucketLength Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.LockStats.MaxBucketLength" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassMaxBucketLengthTopic" /><MSHelp:Keyword Index="K"
Term="MaxBucketLength property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxBucketLength
property" /><MSHelp:Keyword Index="F" Term="MaxBucketLength" /><MSHelp:Keyword Index="F"
Term="LockStats.MaxBucketLength" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LockStats.MaxBucketLength" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.MaxBucketLength"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxBucketLength" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Max length of bucket." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxBucketLength Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DeadlockException" /><meta name="guid" content="T_BerkeleyDB_DeadlockException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DeadlockException" /><MSHelp:TOCTitle Title="DeadlockException Class" /><MSHelp:RLTitle Title="DeadlockException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DeadlockException" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBDeadlockExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="DeadlockException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DeadlockException class" /><MSHelp:Keyword Index="K" Term="DeadlockException class, about DeadlockException class" /><MSHelp:Keyword Index="F" Term="DeadlockException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="When multiple threads of control are modifying the database, there is normally the potential for deadlock. In Berkeley DB, deadlock is signified by a DeadlockException thrown from the Berkeley DB function. ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">DeadlockException
Class</td></tr><tr id="headerTableRow3"><td align="left"><a
href="AllMembers_T_BerkeleyDB_DeadlockException.htm">Members <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveNextDuplicateMultiple Method (Int32)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script
type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple_2" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultiple_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple(System.Int32)" /><MSHelp:TOCTitle
Title="MoveNextDuplicateMultiple Method (Int32)" /><MSHelp:RLTitle
Title="Cursor.MoveNextDuplicateMultiple Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultiple(System.Int32)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data
pair, then move cursor to the next key/data pair in the database, and store that pair and as many duplicate data ..."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultiple Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapRecordId Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HeapRecordId" /><meta name="guid" content="Methods_T_BerkeleyDB_HeapRecordId" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HeapRecordId" /><MSHelp:TOCTitle Title="HeapRecordId Methods " /><MSHelp:RLTitle Title="HeapRecordId Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HeapRecordId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdMethodsTopic" /><MSHelp:Keyword Index="K" Term="HeapRecordId class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId Methods </td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_ThreadCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_ThreadCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.ThreadCount" /><MSHelp:TOCTitle Title="ThreadCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.ThreadCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.ThreadCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassThreadCountTopic" /><MSHelp:Keyword Index="K" Term="ThreadCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ThreadCount property" /><MSHelp:Keyword Index="F" Term="ThreadCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ThreadCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ThreadCount"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ThreadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_ThreadCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_ThreadCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An approximate number of threads in the database environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ThreadCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_Cursor" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="BaseDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Cursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase<span

class="languageSpecificText">..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compact Method (CompactConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Compact_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Compact_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Compact(BerkeleyDB.CompactConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Compact Method (CompactConfig, Transaction)" /><MSHelp:RLTitle Title="HashDatabase.Compact Method (CompactConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Compact(BerkeleyDB.CompactConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Compact" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Compact the database, and optionally return unused database pages to the underlying filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Compact Method (CompactConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextMultipleKey Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultipleKey is identical to . Otherwise,

move the cursor to the next key/data pair of the database, and store that pair and as many ensuing key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultipleKey Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TempDir Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"

/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TempDir" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TempDir" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TempDir" /><MSHelp:TOCTitle Title="TempDir Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TempDir Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TempDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTempDirTopic" /><MSHelp:Keyword Index="K" Term="TempDir property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TempDir property" /><MSHelp:Keyword Index="F" Term="TempDir" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TempDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TempDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TempDir" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TempDir" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TempDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of a directory to be used as the location of temporary files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TempDir Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NonDurableTxns Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_NonDurableTxns" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_NonDurableTxns" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.NonDurableTxns" /><MSHelp:TOCTitle Title="NonDurableTxns Property " /><MSHelp:RLTitle Title="BaseDatabase.NonDurableTxns Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.NonDurableTxns" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassNonDurableTxnsTopic" /><MSHelp:Keyword Index="K" Term="NonDurableTxns property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.NonDurableTxns property" /><MSHelp:Keyword Index="F" Term="NonDurableTxns" /><MSHelp:Keyword Index="F" Term="BaseDatabase.NonDurableTxns" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.NonDurableTxns" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.NonDurableTxns" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_NonDurableTxns" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will not write log records for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.NonDurableTxns Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MovePrev" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MovePrev" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MovePrev" /><MSHelp:TOCTitle Title="MovePrev Method " /><MSHelp:RLTitle Title="HashCursor.MovePrev Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MovePrev" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMovePrevTopic" /><MSHelp:Keyword Index="K" Term="MovePrev method" /><MSHelp:Keyword Index="K" Term="HashCursor.MovePrev method" /><MSHelp:Keyword Index="F" Term="MovePrev"
/><MSHelp:Keyword Index="F" Term="HashCursor.MovePrev" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
 class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
 id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input

id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MovePrev Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (CursorConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Cursor_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Cursor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:TOCTitle Title="Cursor Method (CursorConfig)" /><MSHelp:RLTitle Title="BaseDatabase.Cursor Method (CursorConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Cursor(BerkeleyDB.CursorConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Cursor Method (CursorConfig)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EnvHome Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogVerifyConfig_EnvHome" /><meta name="guid" content="P_BerkeleyDB_LogVerifyConfig_EnvHome" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.LogVerifyConfig.EnvHome" /><MSHelp:TOCTitle Title="EnvHome Property "
/><MSHelp:RLTitle Title="LogVerifyConfig.EnvHome Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LogVerifyConfig.EnvHome" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogVerifyConfigClassEnvHomeTopic" /><MSHelp:Keyword Index="K"
Term="EnvHome property" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig.EnvHome property"
/><MSHelp:Keyword Index="F" Term="EnvHome" /><MSHelp:Keyword Index="F"
Term="LogVerifyConfig.EnvHome" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LogVerifyConfig.EnvHome"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.EnvHome"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogVerifyConfig.get_EnvHome" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LogVerifyConfig.set_EnvHome" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The home directory of the Berkeley DB environment to be used internally during log verification."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.EnvHome Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"

/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Helper Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_DbSiteConfig_Helper" /><meta name="guid"
content="P_BerkeleyDB_DbSiteConfig_Helper" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DbSiteConfig.Helper" /><MSHelp:TOCTitle Title="Helper Property " /><MSHelp:RLTitle
Title="DbSiteConfig.Helper Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DbSiteConfig.Helper"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteConfigClassHelperTopic" /><MSHelp:Keyword
Index="K" Term="Helper property" /><MSHelp:Keyword Index="K" Term="DbSiteConfig.Helper property"
/><MSHelp:Keyword Index="F" Term="Helper" /><MSHelp:Keyword Index="F" Term="DbSiteConfig.Helper"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSiteConfig.Helper" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DbSiteConfig.Helper" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSiteConfig.get_Helper" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DbSiteConfig.set_Helper" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Whether the site is a helper site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSiteConfig..::.Helper Property </td></tr><tr id="headerTableRow3"><td align="left">DbSiteConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Database.VerifyOperation Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_Database_VerifyOperation" /><meta name="guid" content="T_BerkeleyDB_Database_VerifyOperation" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Database.VerifyOperation" /><MSHelp:TOCTitle Title="Database.VerifyOperation Enumeration" /><MSHelp:RLTitle Title="Database.VerifyOperation Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.Database.VerifyOperation" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Database.VerifyOperation.DEFAULT" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Database.VerifyOperation.ORDER_CHECK_ONLY" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Database.VerifyOperation.NO_ORDER_CHECK" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseVerifyOperationClassTopic" /><MSHelp:Keyword Index="K" Term="Database.VerifyOperation enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Database.VerifyOperation enumeration" /><MSHelp:Keyword Index="K" Term="DEFAULT enumeration member" /><MSHelp:Keyword Index="K" Term="ORDER_CHECK_ONLY enumeration member" /><MSHelp:Keyword Index="K" Term="NO_ORDER_CHECK enumeration member" /><MSHelp:Keyword Index="F" Term="Database.VerifyOperation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.VerifyOperation" /><MSHelp:Keyword Index="F" Term="Database.VerifyOperation.DEFAULT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.VerifyOperation.DEFAULT" /><MSHelp:Keyword Index="F" Term="Database.VerifyOperation.ORDER_CHECK_ONLY" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.VerifyOperation.ORDER_CHECK_ONLY" /><MSHelp:Keyword Index="F" Term="Database.VerifyOperation.NO_ORDER_CHECK" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.VerifyOperation.NO_ORDER_CHECK" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerifyOperation"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.VerifyOperation.DEFAULT" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.VerifyOperation.ORDER_CHECK_ONLY" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.VerifyOperation.NO_ORDER_CHECK" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies the type of verification to perform" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.VerifyOperation Enumeration</td></tr><tr id="headerTableRow3"><td align="left">Database Class See

Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store the secondary key and primary ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="QueueDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Open" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase<span

class="languageSpecificText">..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Add Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_Add" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_Add" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.Add" /><MSHelp:TOCTitle Title="Add Method " /><MSHelp:RLTitle Title="BTreeCursor.Add Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.Add" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassAddTopic" /><MSHelp:Keyword Index="K" Term="Add method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.Add method" /><MSHelp:Keyword Index="F" Term="Add" /><MSHelp:Keyword Index="F" Term="BTreeCursor.Add" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.Add" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Add Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Get" /><MSHelp:TOCTitle Title="Get Method "

/><MSHelp:RLTitle Title="BTreeDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionAppliedStatus Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_TransactionAppliedStatus" /><meta name="guid" content="T_BerkeleyDB_TransactionAppliedStatus" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.TransactionAppliedStatus" /><MSHelp:TOCTitle Title="TransactionAppliedStatus Enumeration" /><MSHelp:RLTitle Title="TransactionAppliedStatus Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.TransactionAppliedStatus" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionAppliedStatus.APPLIED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionAppliedStatus.TIMEOUT" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionAppliedStatus.EMPTY_TRANSACTION" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.TransactionAppliedStatus.NOTFOUND" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionAppliedStatusClassTopic" /><MSHelp:Keyword Index="K" Term="TransactionAppliedStatus enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.TransactionAppliedStatus enumeration" /><MSHelp:Keyword Index="K" Term="APPLIED enumeration member" /><MSHelp:Keyword Index="K" Term="TIMEOUT enumeration member" /><MSHelp:Keyword Index="K" Term="EMPTY_TRANSACTION enumeration member" /><MSHelp:Keyword Index="K" Term="NOTFOUND enumeration member" /><MSHelp:Keyword Index="F" Term="TransactionAppliedStatus" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionAppliedStatus" /><MSHelp:Keyword Index="F" Term="TransactionAppliedStatus.APPLIED"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionAppliedStatus.APPLIED" /><MSHelp:Keyword Index="F" Term="TransactionAppliedStatus.TIMEOUT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionAppliedStatus.TIMEOUT" /><MSHelp:Keyword Index="F" Term="TransactionAppliedStatus.EMPTY_TRANSACTION" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionAppliedStatus.EMPTY_TRANSACTION" /><MSHelp:Keyword Index="F" Term="TransactionAppliedStatus.NOTFOUND" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionAppliedStatus.NOTFOUND" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionAppliedStatus" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionAppliedStatus.APPLIED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionAppliedStatus.TIMEOUT" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionAppliedStatus.EMPTY_TRANSACTION" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionAppliedStatus.NOTFOUND" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Status values from transaction application checking operations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionAppliedStatus Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_RegionNoWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_RegionNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.RegionNoWait" /><MSHelp:TOCTitle Title="RegionNoWait Property " /><MSHelp:RLTitle Title="LockStats.RegionNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.RegionNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassRegionNoWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionNoWait property" /><MSHelp:Keyword Index="K" Term="LockStats.RegionNoWait property" /><MSHelp:Keyword Index="F" Term="RegionNoWait" /><MSHelp:Keyword Index="F" Term="LockStats.RegionNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.RegionNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.RegionNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_RegionNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.RegionNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_SecondaryCursor" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.SecondaryCursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassSecondaryCursorTopic" /><MSHelp:Keyword Index="K"

Term="SecondaryCursor
method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.SecondaryCursor method"
/><MSHelp:Keyword Index="F" Term="SecondaryCursor" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabase.SecondaryCursor" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.SecondaryCursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="SecondaryDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">SecondaryDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoDuplicate

Method (DatabaseEntry,
DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_HashDatabase_PutNoDuplicate" /><meta name="guid"
content="M_BerkeleyDB_HashDatabase_PutNoDuplicate" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)"
/><MSHelp:TOCTitle Title="PutNoDuplicate Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle
Title="HashDatabase.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.HashDatabase.PutNoDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HashDatabase.PutNoDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data
pair in the database only if it does not already appear in the database." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.PutNoDuplicate Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextUniqueMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextUniqueMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUniqueMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MaxActive Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_TransactionStats_MaxActive" /><meta name="guid"
content="P_BerkeleyDB_TransactionStats_MaxActive" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.TransactionStats.MaxActive" /><MSHelp:TOCTitle Title="MaxActive Property "
/><MSHelp:RLTitle Title="TransactionStats.MaxActive Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.TransactionStats.MaxActive" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionStatsClassMaxActiveTopic" /><MSHelp:Keyword Index="K"
Term="MaxActive property" /><MSHelp:Keyword Index="K" Term="TransactionStats.MaxActive property"
/><MSHelp:Keyword Index="F" Term="MaxActive" /><MSHelp:Keyword Index="F"
Term="TransactionStats.MaxActive" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.TransactionStats.MaxActive" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionStats.MaxActive" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionStats.get_MaxActive" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum active
transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.MaxActive Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (UInt32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Move_1" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Move_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Move(System.UInt32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (UInt32, LockingInfo)" /><MSHelp:RLTitle Title="BTreeCursor.Move Method (UInt32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Move(System.UInt32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">BTreeCursor<span
class="cs">..::<span
class="nu">.Move Method (UInt32, LockingInfo)</td></tr><tr
id="headerTableRow3"><td align="left">BTreeCursor Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Cursor"
/><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Cursor" /><xml><MSHelp:Attr

Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Cursor" /><MSHelp:TOCTitle
Title="Cursor Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Cursor Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Cursor"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassCursorTopic"
/><MSHelp:Keyword Index="K" Term="Cursor method" /><MSHelp:Keyword Index="K"
Term="SecondaryBTreeDatabase.Cursor method" /><MSHelp:Keyword Index="F" Term="Cursor"
/><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.Cursor" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabase.Cursor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CDB_ALLDB Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_CDB_ALLDB" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_CDB_ALLDB" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.CDB_ALLDB" /><MSHelp:TOCTitle Title="CDB_ALLDB Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.CDB_ALLDB Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.CDB_ALLDB" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassCDB_ALLDBTopic" /><MSHelp:Keyword Index="K" Term="CDB_ALLDB field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.CDB_ALLDB field" /><MSHelp:Keyword Index="F" Term="CDB_ALLDB" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.CDB_ALLDB" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.CDB_ALLDB" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.CDB_ALLDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB Concurrent Data Store applications will perform locking on an environment-wide basis rather than on a per-database basis." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironmentConfig<span
class="languageSpecificText">..<span
class="cpp">::.CDB_ALLDB Field</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CacheSize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_CacheSize" /><meta
name="guid" content="P_BerkeleyDB_DatabaseEnvironment_CacheSize" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.CacheSize" /><MSHelp:TOCTitle
Title="CacheSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.CacheSize Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.CacheSize"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassCacheSizeTopic"
/><MSHelp:Keyword Index="K" Term="CacheSize property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.CacheSize property" /><MSHelp:Keyword Index="F" Term="CacheSize"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.CacheSize" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.CacheSize" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.CacheSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_CacheSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.set_CacheSize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType"
Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the shared memory buffer pool -- that is, the
cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.CacheSize Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryQueueDatabaseConfig Fields" /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"

src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_LockingConfig" /><meta name="guid"
content="Methods_T_BerkeleyDB_LockingConfig"
/><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LockingConfig" /><MSHelp:TOCTitle
Title="LockingConfig Methods " /><MSHelp:RLTitle Title="LockingConfig Methods (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LockingConfig" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBLockingConfigMethodsTopic" /><MSHelp:Keyword Index="K"
Term="LockingConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label>
  <img
id="memberOptionsDropdownImage" src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationSystemInfo Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_ReplicationSystemInfo" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_ReplicationSystemInfo" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.ReplicationSystemInfo" /><MSHelp:TOCTitle Title="ReplicationSystemInfo Field" /><MSHelp:RLTitle Title="VerboseMessages.ReplicationSystemInfo Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationSystemInfo" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationSystemInfoTopic" /><MSHelp:Keyword Index="K" Term="ReplicationSystemInfo field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationSystemInfo field" /><MSHelp:Keyword Index="F" Term="ReplicationSystemInfo" /><MSHelp:Keyword Index="F" Term="VerboseMessages.ReplicationSystemInfo" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.ReplicationSystemInfo" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.ReplicationSystemInfo" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Saves replication system information to a system-owned

file. This value is on by default." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.ReplicationSystemInfo Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CachedValue Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_CachedValue" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_CachedValue" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.CachedValue" /><MSHelp:TOCTitle Title="CachedValue Property " /><MSHelp:RLTitle Title="SequenceStats.CachedValue Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.CachedValue" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassCachedValueTopic" /><MSHelp:Keyword Index="K" Term="CachedValue property" /><MSHelp:Keyword Index="K" Term="SequenceStats.CachedValue property" /><MSHelp:Keyword Index="F" Term="CachedValue" /><MSHelp:Keyword Index="F" Term="SequenceStats.CachedValue" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.CachedValue" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.CachedValue" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_CachedValue" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current cached value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats..::.CachedValue Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MovePrevUnique" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MovePrevUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MovePrevUnique" /><MSHelp:TOCTitle Title="MovePrevUnique Method " /><MSHelp:RLTitle Title="HashCursor.MovePrevUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MovePrevUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMovePrevUniqueTopic" /><MSHelp:Keyword Index="K" Term="MovePrevUnique method" /><MSHelp:Keyword Index="K" Term="HashCursor.MovePrevUnique method" /><MSHelp:Keyword Index="F" Term="MovePrevUnique" /><MSHelp:Keyword Index="F" Term="HashCursor.MovePrevUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;

height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageAllocations

Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PageAllocations" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PageAllocations" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PageAllocations" /><MSHelp:TOCTitle Title="PageAllocations Property " /><MSHelp:RLTitle Title="MPoolStats.PageAllocations Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PageAllocations" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPageAllocationsTopic" /><MSHelp:Keyword Index="K" Term="PageAllocations property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PageAllocations property" /><MSHelp:Keyword Index="F" Term="PageAllocations" /><MSHelp:Keyword Index="F" Term="MPoolStats.PageAllocations" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PageAllocations" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PageAllocations" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PageAllocations" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of page allocations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PageAllocations Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryRecnoDatabaseConfig Methods " /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Pages Property

</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_Pages" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_Pages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.Pages" /><MSHelp:TOCTitle Title="Pages Property " /><MSHelp:RLTitle Title="MPoolStats.Pages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.Pages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesTopic" /><MSHelp:Keyword Index="K" Term="Pages property" /><MSHelp:Keyword Index="K" Term="MPoolStats.Pages property" /><MSHelp:Keyword Index="F" Term="Pages" /><MSHelp:Keyword Index="F" Term="MPoolStats.Pages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.Pages"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.Pages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_Pages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total number of pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"

value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.Pages Property </td></tr><tr id="headerTableRow3"><td
align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionDataGeneration Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionDataGeneration" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionDataGeneration" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionDataGeneration" /><MSHelp:TOCTitle Title="ElectionDataGeneration Property " /><MSHelp:RLTitle Title="ReplicationStats.ElectionDataGeneration Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionDataGeneration" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionDataGenerationTopic" /><MSHelp:Keyword Index="K" Term="ElectionDataGeneration property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionDataGeneration property" /><MSHelp:Keyword Index="F" Term="ElectionDataGeneration" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionDataGeneration" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionDataGeneration" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionDataGeneration" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionDataGeneration" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Winner data generation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionDataGeneration Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleKeyDatabaseEntry Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_MultipleKeyDatabaseEntry__ctor" /><meta name="guid" content="Overload_BerkeleyDB_MultipleKeyDatabaseEntry__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.MultipleKeyDatabaseEntry.#ctor" /><MSHelp:TOCTitle Title="MultipleKeyDatabaseEntry Constructor " /><MSHelp:RLTitle Title="MultipleKeyDatabaseEntry Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.MultipleKeyDatabaseEntry.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleKeyDatabaseEntryClassctorTopic" /><MSHelp:Keyword Index="K" Term="MultipleKeyDatabaseEntry class, constructor" /><MSHelp:Keyword Index="K" Term="MultipleKeyDatabaseEntry.MultipleKeyDatabaseEntry constructor" /><MSHelp:Keyword Index="F" Term="MultipleKeyDatabaseEntry" /><MSHelp:Keyword Index="F" Term="MultipleKeyDatabaseEntry.MultipleKeyDatabaseEntry" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MultipleKeyDatabaseEntry.MultipleKeyDatabaseEntry" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered
</nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleKeyDatabaseEntry Constructor </td></tr><tr id="headerTableRow3"><td align="left">MultipleKeyDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="P_BerkeleyDB_Transaction_Priority" /><meta name="guid" content="P_BerkeleyDB_Transaction_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Transaction.Priority" /><MSHelp:TOCTitle Title="Priority Property " /><MSHelp:RLTitle Title="Transaction.Priority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Transaction.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority property" /><MSHelp:Keyword Index="K" Term="Transaction.Priority property" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="Transaction.Priority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Priority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.get_Priority"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.set_Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The deadlock priority for this transaction. The deadlock detector will reject lock requests from lower priority transactions before those from higher priority transactions." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Priority Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Transaction.htm">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveFirstMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_HashCursor_MoveFirstMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_HashCursor_MoveFirstMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashCursor.MoveFirstMultiple" /><MSHelp:TOCTitle Title="MoveFirstMultiple
Method " /><MSHelp:RLTitle Title="HashCursor.MoveFirstMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveFirstMultiple"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveFirstMultipleTopic"
/><MSHelp:Keyword Index="K" Term="MoveFirstMultiple
method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveFirstMultiple method" /><MSHelp:Keyword
Index="F" Term="MoveFirstMultiple" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveFirstMultiple"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveFirstMultiple" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveFirstMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_RefreshMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_RefreshMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.RefreshMultipleKey" /><MSHelp:TOCTitle Title="RefreshMultipleKey Method " /><MSHelp:RLTitle Title="RecnoCursor.RefreshMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.RefreshMultipleKey"

/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassRefreshMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="RefreshMultipleKey method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.RefreshMultipleKey method" /><MSHelp:Keyword Index="F" Term="RefreshMultipleKey" /><MSHelp:Keyword Index="F" Term="RecnoCursor.RefreshMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.RefreshMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MovePrevDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MovePrevDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:TOCTitle Title="MovePrevDuplicate Method " /><MSHelp:RLTitle Title="SecondaryCursor.MovePrevDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMovePrevDuplicateTopic" /><MSHelp:Keyword Index="K" Term="MovePrevDuplicate method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MovePrevDuplicate method" /><MSHelp:Keyword Index="F" Term="MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MovePrevDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MovePrevDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrevDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>DeadlockException Fields</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Fields_T_BerkeleyDB_DeadlockException" /><meta name="guid"
content="Fields_T_BerkeleyDB_DeadlockException"
/><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.DeadlockException"
/><MSHelp:TOCTitle Title="DeadlockException Fields" /><MSHelp:RLTitle Title="DeadlockException Fields
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.DeadlockException"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockExceptionFieldsTopic" /><MSHelp:Keyword
Index="K" Term="DeadlockException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DeadlockException Fields</td></tr><tr id="headerTableRow3"><td align="left">DeadlockException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultiple_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultiple_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextMultiple Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextMultiple Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultiple(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultiple is identical to .

Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many duplicate data items t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultiple Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HashStats" /><meta name="guid" content="Methods_T_BerkeleyDB_HashStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HashStats" /><MSHelp:TOCTitle Title="HashStats Methods " /><MSHelp:RLTitle Title="HashStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HashStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="HashStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats Methods </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextDuplicateMultiple" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextDuplicateMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextDuplicateMultipleTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextDuplicateMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextDuplicateMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextDuplicateMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultiple Method
</td></tr><tr
id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorCode Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseException_ErrorCode" /><meta name="guid" content="F_BerkeleyDB_DatabaseException_ErrorCode" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseException.ErrorCode" /><MSHelp:TOCTitle Title="ErrorCode Field" /><MSHelp:RLTitle Title="DatabaseException.ErrorCode Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseException.ErrorCode" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseExceptionClassErrorCodeTopic" /><MSHelp:Keyword Index="K" Term="ErrorCode field" /><MSHelp:Keyword Index="K" Term="DatabaseException.ErrorCode field" /><MSHelp:Keyword Index="F" Term="ErrorCode" /><MSHelp:Keyword Index="F" Term="DatabaseException.ErrorCode" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseException.ErrorCode" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseException.ErrorCode" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The underlying error code from the Berkeley DB C library." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseException..::.ErrorCode Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compress Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabaseConfig_Compress" /><meta name="guid" content="P_BerkeleyDB_BTreeDatabaseConfig_Compress" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabaseConfig.Compress" /><MSHelp:TOCTitle Title="Compress Property " /><MSHelp:RLTitle Title="BTreeDatabaseConfig.Compress Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabaseConfig.Compress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassCompressTopic" /><MSHelp:Keyword Index="K" Term="Compress property" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.Compress property" /><MSHelp:Keyword Index="F" Term="Compress" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.Compress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.Compress" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.Compress" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.get_Compress" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The compression function used to store key/data pairs in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.Compress Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (Int32, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link

rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Get_2" /><meta name="guid" content="M_BerkeleyDB_Sequence_Get_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Get(System.Int32,System.Boolean)" /><MSHelp:TOCTitle Title="Get Method (Int32, Boolean)" /><MSHelp:RLTitle Title="Sequence.Get Method (Int32, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Get(System.Int32,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the next available element in the sequence and change the sequence value by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Get Method (Int32, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Endianness Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Endianness" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_Endianness" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.Endianness" /><MSHelp:TOCTitle Title="Endianness Property " /><MSHelp:RLTitle Title="BaseDatabase.Endianness Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.Endianness" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassEndiannessTopic" /><MSHelp:Keyword Index="K" Term="Endianness property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Endianness property" /><MSHelp:Keyword Index="F" Term="Endianness" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Endianness" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Endianness" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Endianness" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_Endianness" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database byte order." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;

height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Endianness Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Truncate" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="BaseDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.BaseDatabase.Truncate" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Empty the database, discarding all records it contains." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RefreshMultipleKey
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_Cursor_RefreshMultipleKey" /><meta name="guid"
content="M_BerkeleyDB_Cursor_RefreshMultipleKey" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:TOCTitle Title="RefreshMultipleKey
Method " /><MSHelp:RLTitle Title="Cursor.RefreshMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Store the key/data pair to which the cursor refers and as many ensuing key/data pairs that can fit in a buffer
the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_LOCK_DEADLOCK Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_LOCK_DEADLOCK" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_LOCK_DEADLOCK" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_LOCK_DEADLOCK" /><MSHelp:TOCTitle Title="DB_LOCK_DEADLOCK Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_LOCK_DEADLOCK Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_LOCK_DEADLOCK" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_LOCK_DEADLOCKTopic" /><MSHelp:Keyword Index="K" Term="DB_LOCK_DEADLOCK field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_LOCK_DEADLOCK field" /><MSHelp:Keyword Index="F" Term="DB_LOCK_DEADLOCK" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_LOCK_DEADLOCK" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_LOCK_DEADLOCK" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_LOCK_DEADLOCK" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Deadlock." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"

src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_LOCK_DEADLOCK Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerboseMessages Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_VerboseMessages__ctor" /><meta name="guid"
content="M_BerkeleyDB_VerboseMessages__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.VerboseMessages.#ctor" /><MSHelp:TOCTitle
Title="VerboseMessages Constructor " /><MSHelp:RLTitle Title="VerboseMessages Constructor (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.VerboseMessages.#ctor" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassctorTopic" /><MSHelp:Keyword Index="K"
Term="VerboseMessages class, constructor" /><MSHelp:Keyword Index="K"
Term="VerboseMessages.VerboseMessages constructor" /><MSHelp:Keyword Index="F"
Term="VerboseMessages" /><MSHelp:Keyword Index="F" Term="VerboseMessages.VerboseMessages"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.VerboseMessages" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages..ctor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initializes a new
instance of the class" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">VerboseMessages Constructor </td></tr><tr id="headerTableRow3"><td
align="left">VerboseMessages Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseEnvironmentVars Field</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseEnvironmentVars" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseEnvironmentVars"
/><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseEnvironmentVars" /><MSHelp:TOCTitle
Title="UseEnvironmentVars Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseEnvironmentVars
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseEnvironmentVars" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseEnvironmentVarsTopic" /><MSHelp:Keyword
Index="K" Term="UseEnvironmentVars field" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.UseEnvironmentVars field" /><MSHelp:Keyword Index="F"
Term="UseEnvironmentVars" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.UseEnvironmentVars" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.UseEnvironmentVars" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseEnvironmentVars"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, the Berkeley DB process' environment may be permitted to
specify information to be used when naming files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseEnvironmentVars Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Rename Method (String, String, DatabaseEnvironment)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Rename_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Rename_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String,BerkeleyDB.DatabaseEnvironment)"

/><MSHelp:TOCTitle Title="Rename Method (String, String, DatabaseEnvironment)" /><MSHelp:RLTitle Title="BaseDatabase.Rename Method (String, String, DatabaseEnvironment) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String,BerkeleyDB.DatabaseEnvironment)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Rename" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the underlying file represented by , incidentally renaming all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Rename Method (String, String, DatabaseEnvironment)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_BaseDatabase.htm">BaseDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Min Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceConfig_Min" /><meta
name="guid" content="P_BerkeleyDB_SequenceConfig_Min" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SequenceConfig.Min" /><MSHelp:TOCTitle Title="Min Property " /><MSHelp:RLTitle
Title="SequenceConfig.Min Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.SequenceConfig.Min" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSequenceConfigClassMinTopic" /><MSHelp:Keyword Index="K" Term="Min property"
/><MSHelp:Keyword Index="K" Term="SequenceConfig.Min property" /><MSHelp:Keyword Index="F"
Term="Min" /><MSHelp:Keyword Index="F"
Term="SequenceConfig.Min" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.Min"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.Min"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.get_Min" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The minimum value in the sequence." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.Min Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepBulkTransfer Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepBulkTransfer" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepBulkTransfer" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepBulkTransfer" /><MSHelp:TOCTitle Title="RepBulkTransfer Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepBulkTransfer Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepBulkTransfer" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepBulkTransferTopic" /><MSHelp:Keyword Index="K" Term="RepBulkTransfer property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepBulkTransfer property" /><MSHelp:Keyword Index="F" Term="RepBulkTransfer" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepBulkTransfer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepBulkTransfer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepBulkTransfer"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepBulkTransfer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepBulkTransfer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the replication master sends groups of records to the clients in a single network transfer" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepBulkTransfer Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TruncateUnusedPages Method (Transaction)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_BTreeDatabase_TruncateUnusedPages_1" /><meta name="guid"
content="M_BerkeleyDB_BTreeDatabase_TruncateUnusedPages_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeDatabase.TruncateUnusedPages(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle
Title="TruncateUnusedPages Method (Transaction)" /><MSHelp:RLTitle
Title="BTreeDatabase.TruncateUnusedPages Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.BTreeDatabase.TruncateUnusedPages(BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Return pages to the filesystem that are already free and at the end of the file."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.TruncateUnusedPages Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_TxnTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_TxnTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.TxnTimeout" /><MSHelp:TOCTitle Title="TxnTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TxnTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.TxnTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTxnTimeoutTopic" /><MSHelp:Keyword Index="K" Term="TxnTimeout property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TxnTimeout property" /><MSHelp:Keyword Index="F" Term="TxnTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TxnTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TxnTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TxnTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_TxnTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.set_TxnTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A value, in microseconds, representing transaction timeouts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TxnTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RenameDB Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RenameDB" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_RenameDB" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:TOCTitle Title="RenameDB Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RenameDB Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRenameDBTopic" /><MSHelp:Keyword Index="K" Term="RenameDB method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RenameDB method" /><MSHelp:Keyword Index="F" Term="RenameDB" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RenameDB" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RenameDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RenameDB Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BulkTransfer Field</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_BulkTransfer" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_BulkTransfer" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.BulkTransfer" /><MSHelp:TOCTitle Title="BulkTransfer Field" /><MSHelp:RLTitle Title="ReplicationConfig.BulkTransfer
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.BulkTransfer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassBulkTransferTopic" /><MSHelp:Keyword Index="K" Term="BulkTransfer field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.BulkTransfer field" /><MSHelp:Keyword Index="F" Term="BulkTransfer" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.BulkTransfer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.BulkTransfer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.BulkTransfer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, the replication master will send groups of records to the clients in a single network transfer" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.BulkTransfer Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LastCachedValue Property </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_LastCachedValue" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_LastCachedValue" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.LastCachedValue" /><MSHelp:TOCTitle Title="LastCachedValue Property " /><MSHelp:RLTitle Title="SequenceStats.LastCachedValue Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.LastCachedValue" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassLastCachedValueTopic" /><MSHelp:Keyword Index="K" Term="LastCachedValue property" /><MSHelp:Keyword Index="K" Term="SequenceStats.LastCachedValue property" /><MSHelp:Keyword Index="F" Term="LastCachedValue" /><MSHelp:Keyword Index="F" Term="SequenceStats.LastCachedValue" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.LastCachedValue" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.LastCachedValue" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_LastCachedValue" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Last cached value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats..::.LastCachedValue Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Increment Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Increment" /><meta name="guid" content="P_BerkeleyDB_Sequence_Increment" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.Increment" /><MSHelp:TOCTitle Title="Increment Property " /><MSHelp:RLTitle Title="Sequence.Increment Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Increment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassIncrementTopic" /><MSHelp:Keyword Index="K" Term="Increment property" /><MSHelp:Keyword Index="K" Term="Sequence.Increment property" /><MSHelp:Keyword Index="F" Term="Increment" /><MSHelp:Keyword Index="F" Term="Sequence.Increment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Increment"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Increment" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Increment" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the sequence will be incremented. This is the default." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence<span
class="languageSpecificText">..<span
class="cpp">::.Increment
Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Sequence.htm">Sequence Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>IntermediateDirMode Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_IntermediateDirMode" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_IntermediateDirMode" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.IntermediateDirMode" /><MSHelp:TOCTitle
Title="IntermediateDirMode Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.IntermediateDirMode
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.DatabaseEnvironment.IntermediateDirMode" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassIntermediateDirModeTopic"
/><MSHelp:Keyword Index="K" Term="IntermediateDirMode property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.IntermediateDirMode property" /><MSHelp:Keyword Index="F"
Term="IntermediateDirMode" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.IntermediateDirMode" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.IntermediateDirMode" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.IntermediateDirMode" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_IntermediateDirMode" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_IntermediateDirMode" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The intermediate directory permissions." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.IntermediateDirMode Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupReadSleepDuration Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_BackupReadSleepDuration" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_BackupReadSleepDuration" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.BackupReadSleepDuration" /><MSHelp:TOCTitle Title="BackupReadSleepDuration Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.BackupReadSleepDuration Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.BackupReadSleepDuration" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupReadSleepDurationTopic" /><MSHelp:Keyword Index="K" Term="BackupReadSleepDuration property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BackupReadSleepDuration property" /><MSHelp:Keyword Index="F" Term="BackupReadSleepDuration" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BackupReadSleepDuration" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BackupReadSleepDuration" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BackupReadSleepDuration" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_BackupReadSleepDuration" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_BackupReadSleepDuration" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"

Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of microseconds to sleep between batches of reads during a hot backup. Increasing this value decreases the amount of I/O the backup process performs for any given time inte ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BackupReadSleepDuration Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ConnectionRetry Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_ConnectionRetry" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_ConnectionRetry" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.ConnectionRetry" /><MSHelp:TOCTitle Title="ConnectionRetry Property " /><MSHelp:RLTitle Title="ReplicationConfig.ConnectionRetry Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.ConnectionRetry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassConnectionRetryTopic" /><MSHelp:Keyword Index="K" Term="ConnectionRetry property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.ConnectionRetry property" /><MSHelp:Keyword Index="F" Term="ConnectionRetry" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.ConnectionRetry" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.ConnectionRetry" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.ConnectionRetry" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_ConnectionRetry" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_ConnectionRetry" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The amount of time the replication manager will wait before trying to re-establish a connection to another site after a communication failure. The default wait time is 30 seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.ConnectionRetry Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BeginTransaction Method (TransactionConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_BeginTransaction_2" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_BeginTransaction_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.BeginTransaction(BerkeleyDB.TransactionConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="BeginTransaction Method (TransactionConfig, Transaction)" /><MSHelp:RLTitle Title="DatabaseEnvironment.BeginTransaction Method (TransactionConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.BeginTransaction(BerkeleyDB.TransactionConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BeginTransaction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new transaction in the environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.BeginTransaction Method (TransactionConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MBytesSinceCheckpoint Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_MBytesSinceCheckpoint" /><meta name="guid" content="P_BerkeleyDB_LogStats_MBytesSinceCheckpoint" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.MBytesSinceCheckpoint" /><MSHelp:TOCTitle Title="MBytesSinceCheckpoint Property " /><MSHelp:RLTitle Title="LogStats.MBytesSinceCheckpoint Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.MBytesSinceCheckpoint" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassMBytesSinceCheckpointTopic" /><MSHelp:Keyword Index="K" Term="MBytesSinceCheckpoint property" /><MSHelp:Keyword Index="K" Term="LogStats.MBytesSinceCheckpoint property" /><MSHelp:Keyword Index="F" Term="MBytesSinceCheckpoint" /><MSHelp:Keyword Index="F" Term="LogStats.MBytesSinceCheckpoint" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.MBytesSinceCheckpoint" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.MBytesSinceCheckpoint" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_MBytesSinceCheckpoint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Megabytes
to log since checkpoint." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.MBytesSinceCheckpoint Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Stats" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="RecnoDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassStatsTopic" /><MSHelp:Keyword Index="K" Term="Stats method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Stats method" /><MSHelp:Keyword Index="F" Term="Stats" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Stats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Stats Method (Transaction)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BTreeDatabase_Stats_1" /><meta name="guid"
content="M_BerkeleyDB_BTreeDatabase_Stats_1"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Stats(BerkeleyDB.Transaction)"
/><MSHelp:TOCTitle Title="Stats Method (Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.Stats Method
(Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BTreeDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BTreeDatabase.Stats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Stats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MPoolConfig" /><meta name="guid" content="T_BerkeleyDB_MPoolConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MPoolConfig" /><MSHelp:TOCTitle Title="MPoolConfig Class" /><MSHelp:RLTitle Title="MPoolConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MPoolConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigClassTopic" /><MSHelp:Keyword Index="K" Term="MPoolConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MPoolConfig class" /><MSHelp:Keyword Index="K" Term="MPoolConfig class, about MPoolConfig class" /><MSHelp:Keyword Index="F" Term="MPoolConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for a 's memory pool subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DeadlockException Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DeadlockException__ctor" /><meta name="guid" content="M_BerkeleyDB_DeadlockException__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DeadlockException.#ctor" /><MSHelp:TOCTitle Title="DeadlockException Constructor "

/><MSHelp:RLTitle Title="DeadlockException
Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DeadlockException.#ctor"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockExceptionClassctorTopic"
/><MSHelp:Keyword Index="K" Term="DeadlockException class, constructor" /><MSHelp:Keyword Index="K"
Term="DeadlockException.DeadlockException constructor" /><MSHelp:Keyword Index="F"
Term="DeadlockException" /><MSHelp:Keyword Index="F" Term="DeadlockException.DeadlockException"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockException.DeadlockException" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockException..ctor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the DeadlockException" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DeadlockException Constructor </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_DeadlockException.htm">DeadlockException Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNextDuplicateMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_MoveNextDuplicateMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MoveNextDuplicateMultipleKey" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNextDuplicateMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMoveNextDuplicateMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveNextDuplicateMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MutexConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_MutexConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MutexConfig.#ctor" /><MSHelp:TOCTitle Title="MutexConfig Constructor " /><MSHelp:RLTitle Title="MutexConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MutexConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="MutexConfig class, constructor" /><MSHelp:Keyword Index="K" Term="MutexConfig.MutexConfig constructor" /><MSHelp:Keyword Index="F" Term="MutexConfig" /><MSHelp:Keyword Index="F" Term="MutexConfig.MutexConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig.MutexConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initializes a new instance of the class" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RefreshMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_Cursor_RefreshMultipleKey" /><meta name="guid"
content="Overload_BerkeleyDB_Cursor_RefreshMultipleKey" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:TOCTitle Title="RefreshMultipleKey
Method " /><MSHelp:RLTitle Title="Cursor.RefreshMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCursorClassRefreshMultipleKeyTopic" /><MSHelp:Keyword Index="K"
Term="RefreshMultipleKey method" /><MSHelp:Keyword Index="K" Term="Cursor.RefreshMultipleKey
method" /><MSHelp:Keyword Index="F" Term="RefreshMultipleKey" /><MSHelp:Keyword Index="F"
Term="Cursor.RefreshMultipleKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang"
 Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
 /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.RefreshMultipleKey Method
</td></tr><tr id="headerTableRow3"><td align="left">Cursor
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>HeapDatabaseConfig Members</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="AllMembers_T_BerkeleyDB_HeapDatabaseConfig" /><meta name="guid"

content="AllMembers_T_BerkeleyDB_HeapDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:TOCTitle Title="HeapDatabaseConfig Members" /><MSHelp:RLTitle Title="HeapDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecovery Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_RunRecovery" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_RunRecovery" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.RunRecovery" /><MSHelp:TOCTitle Title="RunRecovery Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.RunRecovery Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.RunRecovery" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassRunRecoveryTopic" /><MSHelp:Keyword Index="K" Term="RunRecovery field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.RunRecovery field" /><MSHelp:Keyword Index="F" Term="RunRecovery" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.RunRecovery" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.RunRecovery" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.RunRecovery" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, normal recovery will be run on this environment before opening it for normal use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.RunRecovery Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TrickleCleanMemPool Method </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_TrickleCleanMemPool" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_TrickleCleanMemPool" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.TrickleCleanMemPool(System.Int32)" /><MSHelp:TOCTitle Title="TrickleCleanMemPool Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.TrickleCleanMemPool Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.TrickleCleanMemPool(System.Int32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTrickleCleanMemPoolTopic" /><MSHelp:Keyword Index="K" Term="TrickleCleanMemPool method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TrickleCleanMemPool method" /><MSHelp:Keyword Index="F" Term="TrickleCleanMemPool" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TrickleCleanMemPool" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TrickleCleanMemPool" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TrickleCleanMemPool" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Ensure that a specified percent of the pages in the cache are clean, by writing dirty pages to their backing files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TrickleCleanMemPool Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_KEYEXIST Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_KEYEXIST" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_KEYEXIST" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_KEYEXIST" /><MSHelp:TOCTitle Title="DB_KEYEXIST Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_KEYEXIST Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_KEYEXIST" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_KEYEXISTTopic" /><MSHelp:Keyword Index="K" Term="DB_KEYEXIST field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_KEYEXIST field" /><MSHelp:Keyword Index="F" Term="DB_KEYEXIST" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_KEYEXIST" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_KEYEXIST" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_KEYEXIST" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The key/data pair already exists." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ErrorCodes.<span
class="vb">.::.DB_KEYEXIST
Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ErrorCodes.htm">ErrorCodes Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionsWon
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ElectionsWon" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ElectionsWon" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ElectionsWon" /><MSHelp:TOCTitle Title="ElectionsWon Property " /><MSHelp:RLTitle Title="ReplicationStats.ElectionsWon Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ElectionsWon" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassElectionsWonTopic" /><MSHelp:Keyword Index="K" Term="ElectionsWon property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ElectionsWon property" /><MSHelp:Keyword Index="F" Term="ElectionsWon" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ElectionsWon" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ElectionsWon" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ElectionsWon" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ElectionsWon" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of elections won by this site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ElectionsWon Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LeaseCheckedNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_LeaseCheckedNumber" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_LeaseCheckedNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.LeaseCheckedNumber" /><MSHelp:TOCTitle Title="LeaseCheckedNumber Property " /><MSHelp:RLTitle Title="ReplicationStats.LeaseCheckedNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.LeaseCheckedNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassLeaseCheckedNumberTopic" /><MSHelp:Keyword Index="K" Term="LeaseCheckedNumber property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.LeaseCheckedNumber property" /><MSHelp:Keyword Index="F" Term="LeaseCheckedNumber" /><MSHelp:Keyword Index="F" Term="ReplicationStats.LeaseCheckedNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.LeaseCheckedNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.LeaseCheckedNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_LeaseCheckedNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lease validity checks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.LeaseCheckedNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HasMultiple Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_HasMultiple" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_HasMultiple" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.BaseDatabase.HasMultiple" /><MSHelp:TOCTitle Title="HasMultiple Property "
/><MSHelp:RLTitle Title="BaseDatabase.HasMultiple Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.HasMultiple" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassHasMultipleTopic" /><MSHelp:Keyword Index="K"
Term="HasMultiple property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.HasMultiple property"
/><MSHelp:Keyword Index="F" Term="HasMultiple" /><MSHelp:Keyword Index="F"
Term="BaseDatabase.HasMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseDatabase.HasMultiple" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BaseDatabase.HasMultiple" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_HasMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the object
references a physical file supporting multiple databases." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.HasMultiple Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Count Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseCursor_Count" /><meta name="guid" content="M_BerkeleyDB_BaseCursor_Count" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseCursor.Count" /><MSHelp:TOCTitle Title="Count Method " /><MSHelp:RLTitle Title="BaseCursor.Count Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseCursor.Count" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorClassCountTopic" /><MSHelp:Keyword Index="K" Term="Count method" /><MSHelp:Keyword Index="K" Term="BaseCursor.Count method" /><MSHelp:Keyword Index="F" Term="Count" /><MSHelp:Keyword Index="F" Term="BaseCursor.Count" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseCursor.Count" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseCursor.Count" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Returns a count of the number of data items for the key to which the cursor refers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor..<span
class="cpp">::.Count Method </td></tr><tr id="headerTableRow3"><td align="left">BaseCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassCloseTopic"
/><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword

Index="F" Term="SecondaryDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, DatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Open_1" /><meta name="guid" content="M_BerkeleyDB_Database_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Open(System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, DatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="Database.Open Method (String, DatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Open(System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new Database object and open the database represented by . The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,

event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Open Method (String, DatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicate_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicate_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair in . MoveNextDupli ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext
Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_RecnoCursor_MoveNext" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.RecnoCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext
Method " /><MSHelp:RLTitle Title="RecnoCursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MoveNext" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoCursorClassMoveNextTopic" /><MSHelp:Keyword Index="K" Term="MoveNext
method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MoveNext method" /><MSHelp:Keyword
Index="F" Term="MoveNext" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MoveNext"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MoveNext" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrev_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrev_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrev Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrev Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkel

eyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store the secondary key and primary key/data pair in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrev Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transaction Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_Transaction" /><meta name="guid" content="Fields_T_BerkeleyDB_Transaction" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.Transaction" /><MSHelp:TOCTitle Title="Transaction Fields" /><MSHelp:RLTitle Title="Transaction Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.Transaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionFieldsTopic" /><MSHelp:Keyword Index="K" Term="Transaction class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction Fields</td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyEmptyException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_KeyEmptyException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_KeyEmptyException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.KeyEmptyException" /><MSHelp:TOCTitle Title="KeyEmptyException Members" /><MSHelp:RLTitle Title="KeyEmptyException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.KeyEmptyException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyEmptyExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class" /><MSHelp:Keyword Index="K" Term="KeyEmptyException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.KeyEmptyException class" /><MSHelp:Keyword Index="F" Term="KeyEmptyException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyEmptyException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"

/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyEmptyException Members</td></tr><tr id="headerTableRow3"><td align="left">KeyEmptyException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReadOnly Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEntry_ReadOnly" /><meta name="guid" content="P_BerkeleyDB_DatabaseEntry_ReadOnly" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEntry.ReadOnly" /><MSHelp:TOCTitle Title="ReadOnly Property " /><MSHelp:RLTitle Title="DatabaseEntry.ReadOnly Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEntry.ReadOnly" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassReadOnlyTopic" /><MSHelp:Keyword Index="K" Term="ReadOnly property" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.ReadOnly property" /><MSHelp:Keyword Index="F" Term="ReadOnly" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.ReadOnly" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry.ReadOnly" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.ReadOnly" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.get_ReadOnly" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEntry.set_ReadOnly" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set this DatabaseEntry as read only - that is Berkeley DB will not alter the entry." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry..::.ReadOnly Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DupMasters Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_DupMasters" /><meta name="guid"

content="P_BerkeleyDB_ReplicationStats_DupMasters" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.DupMasters" /><MSHelp:TOCTitle Title="DupMasters Property " /><MSHelp:RLTitle Title="ReplicationStats.DupMasters Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.DupMasters" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassDupMastersTopic" /><MSHelp:Keyword Index="K" Term="DupMasters property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.DupMasters property" /><MSHelp:Keyword Index="F" Term="DupMasters" /><MSHelp:Keyword Index="F" Term="ReplicationStats.DupMasters" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.DupMasters" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.DupMasters" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_DupMasters" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of times a duplicate master condition was detected." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr

id="headerTableRow2"><td align="left">ReplicationStats..::.DupMasters Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_Priority" /><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.Priority" /><MSHelp:TOCTitle Title="Priority Field" /><MSHelp:RLTitle Title="DatabaseConfig.Priority Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority field" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.Priority field" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.Priority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.Priority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The cache priority for pages referenced by the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.Priority Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>threadID Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DbThreadID_threadID" /><meta name="guid" content="F_BerkeleyDB_DbThreadID_threadID" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DbThreadID.threadID"
/><MSHelp:TOCTitle Title="threadID Field" /><MSHelp:RLTitle Title="DbThreadID.threadID Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DbThreadID.threadID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbThreadIDClassthreadIDTopic" /><MSHelp:Keyword Index="K" Term="threadID field" /><MSHelp:Keyword Index="K" Term="DbThreadID.threadID field" /><MSHelp:Keyword Index="F" Term="threadID" /><MSHelp:Keyword Index="F" Term="DbThreadID.threadID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbThreadID.threadID"

/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbThreadID.threadID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Thread ID of the thread of control" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbThreadID..::.threadID Field</td></tr><tr id="headerTableRow3"><td align="left">DbThreadID Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>RecnoDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_RecnoDatabaseConfig__ctor" /><meta name="guid"
content="M_BerkeleyDB_RecnoDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.RecnoDatabaseConfig.#ctor" /><MSHelp:TOCTitle Title="RecnoDatabaseConfig
Constructor " /><MSHelp:RLTitle Title="RecnoDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.RecnoDatabaseConfig.#ctor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBRecnoDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K"
Term="RecnoDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K"
Term="RecnoDatabaseConfig.RecnoDatabaseConfig constructor" /><MSHelp:Keyword Index="F"
Term="RecnoDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="RecnoDatabaseConfig.RecnoDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.RecnoDatabaseConfig.RecnoDatabaseConfig" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig..ctor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Instantiate a new RecnoDatabaseConfig object" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DupCompare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabase_DupCompare" /><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabase_DupCompare" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabase.DupCompare" /><MSHelp:TOCTitle Title="DupCompare Property " /><MSHelp:RLTitle Title="SecondaryHashDatabase.DupCompare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryHashDatabase.DupCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassDupCompareTopic" /><MSHelp:Keyword Index="K" Term="DupCompare property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.DupCompare property" /><MSHelp:Keyword Index="F" Term="DupCompare" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.DupCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.DupCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.get_DupCompare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabase.set_DupCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.DupCompare Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CursorConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_CursorConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_CursorConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.CursorConfig" /><MSHelp:TOCTitle Title="CursorConfig Methods " /><MSHelp:RLTitle Title="CursorConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.CursorConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="CursorConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"

/><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show
All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">CursorConfig Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>YieldCPU Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_YieldCPU" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_YieldCPU" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.YieldCPU" /><MSHelp:TOCTitle Title="YieldCPU Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.YieldCPU Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.YieldCPU" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassYieldCPUTopic" /><MSHelp:Keyword Index="K" Term="YieldCPU field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.YieldCPU field" /><MSHelp:Keyword Index="F" Term="YieldCPU" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.YieldCPU" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.YieldCPU" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.YieldCPU" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will yield the processor immediately after each page or mutex acquisition. This functionality should never be used for purposes other than stress testing." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig<span
class="languageSpecificText">..::.YieldCPU Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoCursor_Refresh" /><meta name="guid" content="Overload_BerkeleyDB_RecnoCursor_Refresh" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.Refresh" /><MSHelp:TOCTitle Title="Refresh Method " /><MSHelp:RLTitle Title="RecnoCursor.Refresh Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.Refresh" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassRefreshTopic" /><MSHelp:Keyword Index="K" Term="Refresh method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.Refresh method" /><MSHelp:Keyword Index="F" Term="Refresh" /><MSHelp:Keyword Index="F" Term="RecnoCursor.Refresh" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr

Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">RecnoCursor..::.Refresh Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_REP_ISPERM Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_REP_ISPERM" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_REP_ISPERM" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_REP_ISPERM" /><MSHelp:TOCTitle Title="DB_REP_ISPERM Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_REP_ISPERM Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_REP_ISPERM" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_REP_ISPERMTopic" /><MSHelp:Keyword Index="K" Term="DB_REP_ISPERM field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_REP_ISPERM field" /><MSHelp:Keyword Index="F" Term="DB_REP_ISPERM" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_REP_ISPERM" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_REP_ISPERM" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_REP_ISPERM" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Cached not written perm written." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_REP_ISPERM Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Put" /><meta name="guid" content="M_BerkeleyDB_Database_Put" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Put(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Put Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Database.Put Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Put(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair in the database, replacing any previously existing key if duplicates are disallowed, or adding a duplicate data item if duplicates are allowed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Put Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8"
/><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_HashCursor_MoveNextMultiple" /><meta name="guid"
content="Overload_BerkeleyDB_HashCursor_MoveNextMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.HashCursor.MoveNextMultiple" /><MSHelp:TOCTitle Title="MoveNextMultiple
Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextMultiple"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextMultipleTopic"
/><MSHelp:Keyword Index="K" Term="MoveNextMultiple method" /><MSHelp:Keyword Index="K"
Term="HashCursor.MoveNextMultiple method" /><MSHelp:Keyword Index="F" Term="MoveNextMultiple"
/><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashCursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PreparedTransaction Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_PreparedTransaction" /><meta name="guid" content="T_BerkeleyDB_PreparedTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.PreparedTransaction" /><MSHelp:TOCTitle Title="PreparedTransaction Class" /><MSHelp:RLTitle Title="PreparedTransaction Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.PreparedTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPreparedTransactionClassTopic" /><MSHelp:Keyword Index="K" Term="PreparedTransaction class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.PreparedTransaction class" /><MSHelp:Keyword Index="K" Term="PreparedTransaction class, about PreparedTransaction class"

/><MSHelp:Keyword Index="F" Term="PreparedTransaction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.PreparedTransaction" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.PreparedTransaction" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a transaction that must be resolved by the application following ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PreparedTransaction Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseMPool
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta
name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseMPool" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseMPool" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseMPool" /><MSHelp:TOCTitle Title="UseMPool Field"
/><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseMPool Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseMPool" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseMPoolTopic" /><MSHelp:Keyword Index="K"
Term="UseMPool field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.UseMPool field"
/><MSHelp:Keyword Index="F" Term="UseMPool" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.UseMPool" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.UseMPool" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseMPool"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, initialize the shared memory buffer pool subsystem."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseMPool Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method (DatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Append_1" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Append_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Append(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Append Method (DatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="QueueDatabase.Append Method (DatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Append(BerkeleyDB.DatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append the data item to the end of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Append Method (DatabaseEntry, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_RecnoDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_RecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:TOCTitle Title="RecnoDatabaseConfig Properties " /><MSHelp:RLTitle Title="RecnoDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Replication Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_Replication" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_Replication" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.Replication" /><MSHelp:TOCTitle Title="Replication Field" /><MSHelp:RLTitle Title="VerboseMessages.Replication Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.Replication" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationTopic" /><MSHelp:Keyword Index="K" Term="Replication field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.Replication field" /><MSHelp:Keyword Index="F" Term="Replication" /><MSHelp:Keyword Index="F" Term="VerboseMessages.Replication" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.Replication" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.Replication" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display all detailed information about replication. This includes the information displayed by all of the other Replication* and RepMgr* values." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.Replication Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryQueueDatabaseConfig Members" /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryQueueDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_RegionLockNoWait" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_RegionLockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.RegionLockNoWait" /><MSHelp:TOCTitle Title="RegionLockNoWait Property " /><MSHelp:RLTitle Title="MPoolStats.RegionLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.RegionLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassRegionLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionLockNoWait property" /><MSHelp:Keyword Index="K" Term="MPoolStats.RegionLockNoWait property" /><MSHelp:Keyword Index="F" Term="RegionLockNoWait" /><MSHelp:Keyword Index="F" Term="MPoolStats.RegionLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.RegionLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed"

/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.RegionLockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_RegionLockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted with nowait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.RegionLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>ReadUncommitted Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseConfig_ReadUncommitted"
/><meta name="guid" content="F_BerkeleyDB_DatabaseConfig_ReadUncommitted" /><xml><MSHelp:Attr
Name="AssetID" Value="F:BerkeleyDB.DatabaseConfig.ReadUncommitted" /><MSHelp:TOCTitle
Title="ReadUncommitted Field" /><MSHelp:RLTitle Title="DatabaseConfig.ReadUncommitted Field
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseConfig.ReadUncommitted"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassReadUncommittedTopic"
/><MSHelp:Keyword Index="K" Term="ReadUncommitted field" /><MSHelp:Keyword Index="K"
Term="DatabaseConfig.ReadUncommitted field" /><MSHelp:Keyword Index="F" Term="ReadUncommitted"
/><MSHelp:Keyword Index="F" Term="DatabaseConfig.ReadUncommitted" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseConfig.ReadUncommitted" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseConfig.ReadUncommitted" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Support transactional read operations with degree 1 isolation." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.ReadUncommitted Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Writes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_Writes" /><meta name="guid" content="P_BerkeleyDB_LogStats_Writes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.Writes" /><MSHelp:TOCTitle Title="Writes Property " /><MSHelp:RLTitle Title="LogStats.Writes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.Writes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassWritesTopic" /><MSHelp:Keyword Index="K" Term="Writes property" /><MSHelp:Keyword Index="K" Term="LogStats.Writes property" /><MSHelp:Keyword Index="F" Term="Writes" /><MSHelp:Keyword Index="F" Term="LogStats.Writes"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.Writes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.Writes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_Writes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total I/O writes to the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.Writes Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbSite_Close" /><meta name="guid" content="M_BerkeleyDB_DbSite_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbSite.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="DbSite.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbSite.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSiteClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="DbSite.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="DbSite.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbSite.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbSite.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Close the site." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbSite..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">DbSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Duplicates Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_Duplicates" /><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_Duplicates" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.Duplicates" /><MSHelp:TOCTitle Title="Duplicates Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.Duplicates Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassDuplicatesTopic" /><MSHelp:Keyword Index="K" Term="Duplicates field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.Duplicates field" /><MSHelp:Keyword Index="F" Term="Duplicates" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig.Duplicates" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.Duplicates" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.Duplicates" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Policy for duplicate data items in the database; that is, insertion when the key of the key/data pair being inserted already exists in the database will be successful." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig..::.Duplicates Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nRegions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_nRegions" /><meta name="guid" content="P_BerkeleyDB_HeapStats_nRegions"

/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.nRegions" /><MSHelp:TOCTitle Title="nRegions Property " /><MSHelp:RLTitle Title="HeapStats.nRegions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.nRegions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassnRegionsTopic" /><MSHelp:Keyword Index="K" Term="nRegions property" /><MSHelp:Keyword Index="K" Term="HeapStats.nRegions property" /><MSHelp:Keyword Index="F" Term="nRegions" /><MSHelp:Keyword Index="F" Term="HeapStats.nRegions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.nRegions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.nRegions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_nRegions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of regions in the Heap database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">HeapStats..::.nRegions Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveLast_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveLast_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveLast(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveLast Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveLast Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveLast(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store that pair in . If the last key has duplicate values, the last data item in the set of duplicates is stored in . ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveLast Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Stats" /><meta name="guid" content="M_BerkeleyDB_Sequence_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="Sequence.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Stats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return statistical information for this sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input

type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MinCommitsPerFlush Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_MinCommitsPerFlush" /><meta name="guid" content="P_BerkeleyDB_LogStats_MinCommitsPerFlush" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.MinCommitsPerFlush" /><MSHelp:TOCTitle Title="MinCommitsPerFlush Property " /><MSHelp:RLTitle Title="LogStats.MinCommitsPerFlush Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.MinCommitsPerFlush" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassMinCommitsPerFlushTopic" /><MSHelp:Keyword Index="K" Term="MinCommitsPerFlush property" /><MSHelp:Keyword Index="K" Term="LogStats.MinCommitsPerFlush property" /><MSHelp:Keyword Index="F" Term="MinCommitsPerFlush" /><MSHelp:Keyword Index="F" Term="LogStats.MinCommitsPerFlush" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.MinCommitsPerFlush" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.MinCommitsPerFlush" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_MinCommitsPerFlush" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Min number of commits in a flush." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">LogStats.<span
class="vb">.::.MinCommitsPerFlush
Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LogStats.htm">LogStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>CachePriority Class</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_CachePriority"
/><meta name="guid" content="T_BerkeleyDB_CachePriority" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.CachePriority" /><MSHelp:TOCTitle Title="CachePriority Class" /><MSHelp:RLTitle
Title="CachePriority Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.CachePriority"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityClassTopic" /><MSHelp:Keyword
Index="K" Term="CachePriority class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CachePriority class"
/><MSHelp:Keyword Index="K" Term="CachePriority class, about CachePriority class" /><MSHelp:Keyword
Index="F" Term="CachePriority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CachePriority"
/><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.CachePriority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="A class to represent cache priority for database pages" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataDir Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MetadataDir"
/><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MetadataDir" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MetadataDir" /><MSHelp:TOCTitle Title="MetadataDir Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MetadataDir Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MetadataDir" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMetadataDirTopic"

/><MSHelp:Keyword Index="K" Term="MetadataDir property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MetadataDir property" /><MSHelp:Keyword Index="F" Term="MetadataDir" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MetadataDir" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MetadataDir" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MetadataDir"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MetadataDir" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The path of directory to store the persistent metadata." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MetadataDir Property

</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TruncateUnusedPages Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_TruncateUnusedPages_1" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_TruncateUnusedPages_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.TruncateUnusedPages(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="TruncateUnusedPages Method (Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.TruncateUnusedPages Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.TruncateUnusedPages(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return pages to the filesystem that are already free and at the end of the file." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.TruncateUnusedPages Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CommitToken Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Transaction_CommitToken" /><meta name="guid" content="P_BerkeleyDB_Transaction_CommitToken" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Transaction.CommitToken" /><MSHelp:TOCTitle Title="CommitToken Property " /><MSHelp:RLTitle Title="Transaction.CommitToken Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Transaction.CommitToken" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassCommitTokenTopic" /><MSHelp:Keyword Index="K" Term="CommitToken property" /><MSHelp:Keyword Index="K" Term="Transaction.CommitToken property" /><MSHelp:Keyword Index="F" Term="CommitToken" /><MSHelp:Keyword Index="F" Term="Transaction.CommitToken" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.CommitToken" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.CommitToken" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.get_CommitToken" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The commit token generated at the commit time of this transaction. This operation can only be performed after this transaction has committed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.CommitToken Property </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockTimeouts Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockTimeouts" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockTimeouts" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockTimeouts" /><MSHelp:TOCTitle Title="LockTimeouts Property " /><MSHelp:RLTitle Title="LockStats.LockTimeouts Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockTimeouts" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockTimeoutsTopic" /><MSHelp:Keyword Index="K" Term="LockTimeouts property" /><MSHelp:Keyword Index="K" Term="LockStats.LockTimeouts property" /><MSHelp:Keyword Index="F" Term="LockTimeouts" /><MSHelp:Keyword Index="F" Term="LockStats.LockTimeouts" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockTimeouts" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockTimeouts" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockTimeouts" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of lock timeouts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockTimeouts Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RecnoDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_RecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:TOCTitle Title="RecnoDatabaseConfig Methods " /><MSHelp:RLTitle Title="RecnoDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecordLength Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_QueueStats_RecordLength" /><meta name="guid"
content="P_BerkeleyDB_QueueStats_RecordLength" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.QueueStats.RecordLength" /><MSHelp:TOCTitle Title="RecordLength Property "
/><MSHelp:RLTitle Title="QueueStats.RecordLength Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.QueueStats.RecordLength" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBQueueStatsClassRecordLengthTopic"
/><MSHelp:Keyword Index="K" Term="RecordLength property" /><MSHelp:Keyword Index="K"
Term="QueueStats.RecordLength property" /><MSHelp:Keyword Index="F" Term="RecordLength"
/><MSHelp:Keyword Index="F" Term="QueueStats.RecordLength" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.QueueStats.RecordLength" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.QueueStats.RecordLength" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.QueueStats.get_RecordLength" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Fixed-length
record length." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.RecordLength Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultiple_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextMultiple Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextMultiple Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultiple(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultiple is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many duplicate data items t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultiple Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_MPoolConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_MPoolConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.MPoolConfig" /><MSHelp:TOCTitle

Title="MPoolConfig Fields" /><MSHelp:RLTitle Title="MPoolConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.MPoolConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="MPoolConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"

for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolConfig Fields</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_MPoolConfig.htm">MPoolConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>WriteToLog Method (String)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_WriteToLog" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_WriteToLog" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.WriteToLog(System.String)" /><MSHelp:TOCTitle Title="WriteToLog Method (String)" /><MSHelp:RLTitle Title="DatabaseEnvironment.WriteToLog Method (String) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.WriteToLog(System.String)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.WriteToLog" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append an informational message to the Berkeley DB database environment log files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
  <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.WriteToLog Method (String)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ReplicationConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ReplicationConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ReplicationConfig" /><MSHelp:TOCTitle Title="ReplicationConfig Members" /><MSHelp:RLTitle Title="ReplicationConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ReplicationConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class, all members"

/><MSHelp:Keyword Index="K" Term="BerkeleyDB.ReplicationConfig
class" /><MSHelp:Keyword Index="F" Term="ReplicationConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>
  <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label
id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"

for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig Members</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockPartitions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LockPartitions" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LockPartitions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LockPartitions" /><MSHelp:TOCTitle Title="LockPartitions Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LockPartitions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LockPartitions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLockPartitionsTopic" /><MSHelp:Keyword Index="K" Term="LockPartitions property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LockPartitions property" /><MSHelp:Keyword Index="F" Term="LockPartitions" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LockPartitions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LockPartitions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LockPartitions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LockPartitions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LockPartitions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of lock table partitions used in the Berkeley DB environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockPartitions Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"

src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryRecnoDatabaseConfig_SetForeignKeyConstraint" /><meta
name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabaseConfig_SetForeignKeyConstraint"
/><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryRecnoDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:TOCTitle
Title="SetForeignKeyConstraint Method " /><MSHelp:RLTitle
Title="SecondaryRecnoDatabaseConfig.SetForeignKeyConstraint Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabaseConfig.SetForeignKeyConstraint"
/><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassSetForeignKeyConstraintTopic"
/><MSHelp:Keyword Index="K" Term="SetForeignKeyConstraint method" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabaseConfig.SetForeignKeyConstraint
method" /><MSHelp:Keyword Index="F" Term="SetForeignKeyConstraint" /><MSHelp:Keyword Index="F"
Term="SecondaryRecnoDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage" src="../icons/dropdown.gif"
/> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig..::.SetForeignKeyConstraint Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoCursor Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RecnoCursor" /><meta name="guid" content="Methods_T_BerkeleyDB_RecnoCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RecnoCursor" /><MSHelp:TOCTitle Title="RecnoCursor Methods " /><MSHelp:RLTitle Title="RecnoCursor Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RecnoCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="RecnoCursor class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor Methods </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintStats(System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackupHandler Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_BackupHandler" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_BackupHandler" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.BackupHandler" /><MSHelp:TOCTitle Title="BackupHandler Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.BackupHandler Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.BackupHandler" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupHandlerTopic" /><MSHelp:Keyword Index="K" Term="BackupHandler property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BackupHandler property" /><MSHelp:Keyword Index="F" Term="BackupHandler" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BackupHandler" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BackupHandler" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BackupHandler" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_BackupHandler" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_BackupHandler" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Sets the interface to be used when performing hot backups. This interface is used to override the default behavior used by the and methods." /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.BackupHandler Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>Prepare Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Transaction_Prepare" /><meta name="guid" content="M_BerkeleyDB_Transaction_Prepare" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Transaction.Prepare(System.Byte[])" /><MSHelp:TOCTitle Title="Prepare Method " /><MSHelp:RLTitle Title="Transaction.Prepare Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Transaction.Prepare(System.Byte[])" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassPrepareTopic" /><MSHelp:Keyword Index="K" Term="Prepare method" /><MSHelp:Keyword Index="K" Term="Transaction.Prepare method" /><MSHelp:Keyword Index="F" Term="Prepare" /><MSHelp:Keyword Index="F" Term="Transaction.Prepare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.Prepare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.Prepare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initiate the beginning of a two-phase commit." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
/> <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Prepare Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultiple Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextUniqueMultiple_2"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple(System.Int32)" /><MSHelp:TOCTitle Title="MoveNextUniqueMultiple Method (Int32)" /><MSHelp:RLTitle Title="Cursor.MoveNextUniqueMultiple Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextUniqueMultiple(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextUniqueMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextUniqueMultiple is identical to . Otherwise, move the cursor to the next non-duplicate
key in the database, and store that key and associated datum and ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy

image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span
class="languageSpecificText">..<span
class="cpp">::.MoveNextUniqueMultiple Method
(Int32)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_SequenceConfig_Creation" /><meta name="guid"
content="F_BerkeleyDB_SequenceConfig_Creation"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SequenceConfig.Creation" /><MSHelp:TOCTitle
Title="Creation Field" /><MSHelp:RLTitle Title="SequenceConfig.Creation Field (BerkeleyDB)"

/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SequenceConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="SequenceConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="SequenceConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle sequence creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BackupOptions_Creation" /><meta name="guid" content="F_BerkeleyDB_BackupOptions_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BackupOptions.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="BackupOptions.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BackupOptions.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="BackupOptions.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="BackupOptions.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify whether the target directory will be created if it does not already exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method (UInt32, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Get_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Get_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Get(System.UInt32,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Get Method (UInt32, Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.Get Method (UInt32, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Get(System.UInt32,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Retrieve a specific numbered key/data pair from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Get Method (UInt32, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey_3" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey(System.Int32,BerkeleyDB.LockingInfo)"
/><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method (Int32, LockingInfo)" /><MSHelp:RLTitle
Title="Cursor.MoveNextDuplicateMultipleKey Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey(System.Int32,BerkeleyDB.LockingInfo)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the
current key/data pair, move the cursor to the next key/data pair in the database, and store that pair and as many
duplicate data ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>
<img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultipleKey Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignConflictException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_ForeignConflictException" /><meta name="guid" content="Methods_T_BerkeleyDB_ForeignConflictException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.ForeignConflictException" /><MSHelp:TOCTitle Title="ForeignConflictException Methods " /><MSHelp:RLTitle Title="ForeignConflictException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.ForeignConflictException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBForeignConflictExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="ForeignConflictException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ForeignConflictException Methods </td></tr><tr id="headerTableRow3"><td align="left">ForeignConflictException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitLockCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitLockCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitLockCount" /><MSHelp:TOCTitle Title="InitLockCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitLockCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitLockCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitLockCountTopic" /><MSHelp:Keyword Index="K" Term="InitLockCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitLockCount property" /><MSHelp:Keyword Index="F" Term="InitLockCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitLockCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitLockCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitLockCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitLockCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitLockCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of locks allocated when the environment is created" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitLockCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Cursor" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="BaseDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"

src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Close" /><meta name="guid" content="M_BerkeleyDB_Sequence_Close" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.Sequence.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="Sequence.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="Sequence.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="Sequence.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Close the sequence handle. Any unused cached values are lost." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">Sequence..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Salvage Method (String, DatabaseConfig, Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Salvage_2" /><meta name="guid" content="M_BerkeleyDB_Database_Salvage_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="Salvage Method (String, DatabaseConfig, Boolean, Boolean)" /><MSHelp:RLTitle Title="Database.Salvage Method (String, DatabaseConfig, Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Salvage(System.String,BerkeleyDB.DatabaseConfig,System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Salvage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Write the key/data pairs from all databases in the file to . Key values are written for Btree, Hash and Queue databases, but not for Recno databases." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label

id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Salvage Method (String, DatabaseConfig, Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HashDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_HashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:TOCTitle Title="HashDatabaseConfig Class" /><MSHelp:RLTitle Title="HashDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class, about HashDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig"

/><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig
Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryQueueDatabase Class</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryQueueDatabase" /><meta
name="guid" content="T_BerkeleyDB_SecondaryQueueDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="T:BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:TOCTitle Title="SecondaryQueueDatabase Class"
/><MSHelp:RLTitle Title="SecondaryQueueDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="T:BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryQueueDatabase
class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryQueueDatabase class"
/><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase class, about SecondaryQueueDatabase class"
/><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A class representing a SecondaryQueueDatabase. The Queue format supports fast access
to fixed-length records accessed sequentially or by logical
record number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Rename Method (String, String, String)</title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Rename_2" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Rename_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String,System.String)" /><MSHelp:TOCTitle
Title="Rename Method (String, String, String)" /><MSHelp:RLTitle Title="BaseDatabase.Rename Method (String, String, String) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String,System.String)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Rename" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the database specified by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Rename Method (String, String, String)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockTimeoutLength Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LockTimeoutLength" /><meta name="guid" content="P_BerkeleyDB_LockStats_LockTimeoutLength" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LockTimeoutLength" /><MSHelp:TOCTitle Title="LockTimeoutLength Property " /><MSHelp:RLTitle Title="LockStats.LockTimeoutLength Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LockTimeoutLength" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLockTimeoutLengthTopic" /><MSHelp:Keyword Index="K" Term="LockTimeoutLength property" /><MSHelp:Keyword Index="K" Term="LockStats.LockTimeoutLength property" /><MSHelp:Keyword Index="F" Term="LockTimeoutLength" /><MSHelp:Keyword Index="F" Term="LockStats.LockTimeoutLength" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LockTimeoutLength" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LockTimeoutLength" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LockTimeoutLength" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Lock timeout." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LockTimeoutLength Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Stats_1" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Stats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Stats Method (Transaction)" /><MSHelp:RLTitle Title="QueueDatabase.Stats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Stats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Stats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultipleKey(System.Int32,BerkeleyDB.LockingInfo)"

/><MSHelp:TOCTitle Title="MoveNextMultipleKey Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextMultipleKey Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultipleKey is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many ensuing key/data
pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultipleKey Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_Cursor.htm">Cursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
 CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MoveFirstMultipleKey Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_Cursor_MoveFirstMultipleKey" /><meta name="guid"
content="Overload_BerkeleyDB_Cursor_MoveFirstMultipleKey"
 /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveFirstMultipleKey"
/><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method " /><MSHelp:RLTitle
Title="Cursor.MoveFirstMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCursorClassMoveFirstMultipleKeyTopic" /><MSHelp:Keyword Index="K"
Term="MoveFirstMultipleKey method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveFirstMultipleKey
method" /><MSHelp:Keyword Index="F" Term="MoveFirstMultipleKey" /><MSHelp:Keyword Index="F"
Term="Cursor.MoveFirstMultipleKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref"
 /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;"
 src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this,
'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogVerifyConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="Methods_T_BerkeleyDB_LogVerifyConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_LogVerifyConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.LogVerifyConfig" /><MSHelp:TOCTitle Title="LogVerifyConfig Methods " /><MSHelp:RLTitle Title="LogVerifyConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.LogVerifyConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="LogVerifyConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"

type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_LockingSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_LockingSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.LockingSystemStats(System.Boolean)" /><MSHelp:TOCTitle Title="LockingSystemStats Method (Boolean)" /><MSHelp:RLTitle
Title="DatabaseEnvironment.LockingSystemStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LockingSystemStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LockingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The locking subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockingSystemStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (CursorConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Cursor_2" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Cursor_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor Method (CursorConfig, Transaction)" /><MSHelp:RLTitle

Title="BaseDatabase.Cursor Method (CursorConfig,
Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseDatabase.Cursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Cursor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor with the given
configuration." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BaseDatabase.<span
class="vb">.::.Cursor Method
(CursorConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BaseDatabase.htm">BaseDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="RecnoDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicateLogRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_DuplicateLogRecords" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_DuplicateLogRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.DuplicateLogRecords" /><MSHelp:TOCTitle Title="DuplicateLogRecords Property " /><MSHelp:RLTitle Title="ReplicationStats.DuplicateLogRecords Property (BerkeleyDB)"

/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.DuplicateLogRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassDuplicateLogRecordsTopic" /><MSHelp:Keyword Index="K" Term="DuplicateLogRecords property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.DuplicateLogRecords property" /><MSHelp:Keyword Index="F" Term="DuplicateLogRecords" /><MSHelp:Keyword Index="F" Term="ReplicationStats.DuplicateLogRecords" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.DuplicateLogRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.DuplicateLogRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_DuplicateLogRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log records received multiply." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats.<span

class="vb">.::.DuplicateLogRecords Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabaseConfig Methods " /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryRecnoDatabase" /><meta name="guid" content="T_BerkeleyDB_SecondaryRecnoDatabase" /><xml><MSHelp:Attr Name="AssetID"

Value="T:BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:TOCTitle
Title="SecondaryRecnoDatabase Class" /><MSHelp:RLTitle Title="SecondaryRecnoDatabase Class
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SecondaryRecnoDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassTopic"
/><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryRecnoDatabase class" /><MSHelp:Keyword Index="K"
Term="SecondaryRecnoDatabase class, about SecondaryRecnoDatabase class" /><MSHelp:Keyword Index="F"
Term="SecondaryRecnoDatabase" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a
RecnoDatabase. The Recno format supports fixed- or variable-length records, accessed sequentially or by logical
record number, and optionally backed by a flat text file." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>WriteToLog Method (String, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_WriteToLog_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_WriteToLog_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.WriteToLog(System.String,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="WriteToLog Method (String, Transaction)" /><MSHelp:RLTitle Title="DatabaseEnvironment.WriteToLog Method (String, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.WriteToLog(System.String,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.WriteToLog" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append an informational message to the Berkeley DB database environment log files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.WriteToLog Method (String, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockers Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_InitLockers" /><meta name="guid" content="P_BerkeleyDB_LockStats_InitLockers" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.InitLockers" /><MSHelp:TOCTitle Title="InitLockers Property " /><MSHelp:RLTitle Title="LockStats.InitLockers Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.InitLockers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassInitLockersTopic" /><MSHelp:Keyword Index="K" Term="InitLockers property" /><MSHelp:Keyword Index="K" Term="LockStats.InitLockers property" /><MSHelp:Keyword Index="F" Term="InitLockers" /><MSHelp:Keyword Index="F" Term="LockStats.InitLockers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.InitLockers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr

Name="APIName"
Value="BerkeleyDB.LockStats.InitLockers" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockStats.get_InitLockers" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initial number of
lockers allocated." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">LockStats.<span
class="vb">.::.InitLockers Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_LockStats.htm">LockStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStartClient Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepStartClient_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepStartClient_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepStartClient(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="RepStartClient Method (DatabaseEntry)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStartClient Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepStartClient(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Configure the database environment as a client in a group of replicated database environments." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepStartClient Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironment Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DatabaseEnvironment" /><meta name="guid" content="T_BerkeleyDB_DatabaseEnvironment" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:TOCTitle Title="DatabaseEnvironment Class" /><MSHelp:RLTitle Title="DatabaseEnvironment Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseEnvironment class" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment class, about DatabaseEnvironment class" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a Berkeley DB database environment - a collection including support for some or all of caching, locking, logging and transaction subsystems, as well as databases and log files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment Class</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="AllMembers_T_BerkeleyDB_DatabaseEnvironment.htm">Members <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Sites Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_ReplicationStats_Sites" /><meta name="guid"
content="P_BerkeleyDB_ReplicationStats_Sites" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.ReplicationStats.Sites" /><MSHelp:TOCTitle Title="Sites Property " /><MSHelp:RLTitle
Title="ReplicationStats.Sites Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ReplicationStats.Sites" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBReplicationStatsClassSitesTopic"
/><MSHelp:Keyword Index="K" Term="Sites property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.Sites property" /><MSHelp:Keyword Index="F" Term="Sites" /><MSHelp:Keyword
Index="F" Term="ReplicationStats.Sites" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationStats.Sites" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationStats.Sites" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationStats.get_Sites" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current number
of sites we will assume during elections." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.Sites Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultipleKey Method (Int32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_RefreshMultipleKey_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_RefreshMultipleKey_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.RefreshMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="RefreshMultipleKey Method (Int32, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.RefreshMultipleKey Method (Int32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.RefreshMultipleKey(System.Int32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers and as many ensuing key/data pairs that can fit in a buffer the size of in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultipleKey Method (Int32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrMisc Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_RepMgrMisc" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_RepMgrMisc" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.RepMgrMisc"

/><MSHelp:TOCTitle Title="RepMgrMisc Field" /><MSHelp:RLTitle Title="VerboseMessages.RepMgrMisc Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.RepMgrMisc" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassRepMgrMiscTopic" /><MSHelp:Keyword Index="K" Term="RepMgrMisc field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.RepMgrMisc field" /><MSHelp:Keyword Index="F" Term="RepMgrMisc" /><MSHelp:Keyword Index="F" Term="VerboseMessages.RepMgrMisc" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.RepMgrMisc" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.RepMgrMisc" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display detailed information about general Replication Manager processing." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">VerboseMessages..::.RepMgrMisc Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_RecnoDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_RecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:TOCTitle Title="RecnoDatabaseConfig Fields" /><MSHelp:RLTitle Title="RecnoDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerboseMessages Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_VerboseMessages" /><meta name="guid" content="Fields_T_BerkeleyDB_VerboseMessages" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.VerboseMessages" /><MSHelp:TOCTitle Title="VerboseMessages Fields" /><MSHelp:RLTitle Title="VerboseMessages Fields

(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.VerboseMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesFieldsTopic" /><MSHelp:Keyword Index="K" Term="VerboseMessages class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"

/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages Fields</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseLocking Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseLocking" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseLocking" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseLocking" /><MSHelp:TOCTitle Title="UseLocking Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseLocking Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseLocking" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseLockingTopic" /><MSHelp:Keyword Index="K" Term="UseLocking field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.UseLocking field" /><MSHelp:Keyword Index="F" Term="UseLocking" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.UseLocking" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.UseLocking" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseLocking" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, initialize the locking subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,

event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseLocking Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DatabaseEntry" /><meta name="guid" content="Properties_T_BerkeleyDB_DatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DatabaseEntry" /><MSHelp:TOCTitle Title="DatabaseEntry Properties " /><MSHelp:RLTitle Title="DatabaseEntry Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"

/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">DatabaseEntry Properties </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNext" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNext" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassMoveNextTopic" /><MSHelp:Keyword Index="K" Term="MoveNext method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNext method" /><MSHelp:Keyword Index="F" Term="MoveNext" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNext" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_VERIFY_BAD Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="F_BerkeleyDB_ErrorCodes_DB_VERIFY_BAD" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_VERIFY_BAD" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_VERIFY_BAD" /><MSHelp:TOCTitle Title="DB_VERIFY_BAD Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_VERIFY_BAD Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_VERIFY_BAD" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_VERIFY_BADTopic" /><MSHelp:Keyword Index="K" Term="DB_VERIFY_BAD field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_VERIFY_BAD field" /><MSHelp:Keyword Index="F" Term="DB_VERIFY_BAD" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_VERIFY_BAD" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_VERIFY_BAD" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_VERIFY_BAD" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Verify failed; bad format." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_VERIFY_BAD Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DiskOffset Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_DiskOffset" /><meta name="guid" content="P_BerkeleyDB_LogStats_DiskOffset" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.DiskOffset" /><MSHelp:TOCTitle Title="DiskOffset Property " /><MSHelp:RLTitle Title="LogStats.DiskOffset Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.DiskOffset" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassDiskOffsetTopic" /><MSHelp:Keyword Index="K" Term="DiskOffset property" /><MSHelp:Keyword Index="K" Term="LogStats.DiskOffset property" /><MSHelp:Keyword Index="F" Term="DiskOffset" /><MSHelp:Keyword Index="F" Term="LogStats.DiskOffset" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.DiskOffset" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.DiskOffset" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_DiskOffset" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Known on disk log file offset." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.DiskOffset Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSite" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSite" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrSite(System.Int32)" /><MSHelp:TOCTitle Title="RepMgrSite Method (Int32)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrSite Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrSite(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.DatabaseEnvironment.RepMgrSite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create DbSite with the given eid." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrSite Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="SecondaryDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <img id="memberOptionsDropdownImage"

src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Put" /><meta name="guid" content="Overload_BerkeleyDB_Database_Put" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.Put" /><MSHelp:TOCTitle Title="Put Method " /><MSHelp:RLTitle Title="Database.Put Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Put" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassPutTopic" /><MSHelp:Keyword Index="K" Term="Put method" /><MSHelp:Keyword Index="K" Term="Database.Put method" /><MSHelp:Keyword Index="F" Term="Put" /><MSHelp:Keyword Index="F" Term="Database.Put" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Put" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Put Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Put" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Put" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Put" /><MSHelp:TOCTitle Title="Put Method " /><MSHelp:RLTitle Title="BTreeDatabase.Put Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Put" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassPutTopic" /><MSHelp:Keyword Index="K" Term="Put method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Put method" /><MSHelp:Keyword Index="F" Term="Put" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Put" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Put Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoBuffer Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_NoBuffer" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_NoBuffer" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.NoBuffer" /><MSHelp:TOCTitle Title="NoBuffer Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.NoBuffer Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.NoBuffer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassNoBufferTopic" /><MSHelp:Keyword Index="K" Term="NoBuffer property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.NoBuffer property" /><MSHelp:Keyword Index="F" Term="NoBuffer" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.NoBuffer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.NoBuffer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.NoBuffer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_NoBuffer" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_NoBuffer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, turn off system buffering of Berkeley DB database
files to avoid double caching." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span
class="nu">.NoBuffer Property </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Create Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseEnvironment_Create" /><meta name="guid"
content="P_BerkeleyDB_DatabaseEnvironment_Create"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Create"
/><MSHelp:TOCTitle Title="Create Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Create Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Create"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassCreateTopic"
/><MSHelp:Keyword Index="K" Term="Create property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.Create property" /><MSHelp:Keyword Index="F" Term="Create"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Create" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.Create" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.Create" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_Create" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB subsystems
will create any underlying files, as necessary." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0;
width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Create Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OLDEST Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_OLDEST" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_OLDEST" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.OLDEST" /><MSHelp:TOCTitle Title="OLDEST Field" /><MSHelp:RLTitle Title="DeadlockPolicy.OLDEST Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="F:BerkeleyDB.DeadlockPolicy.OLDEST" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassOLDESTTopic" /><MSHelp:Keyword Index="K" Term="OLDEST field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.OLDEST field" /><MSHelp:Keyword Index="F" Term="OLDEST" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.OLDEST" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.OLDEST" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.OLDEST" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject the lock request for the locker ID with the oldest lock." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy..::.OLDEST

Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DeadlockPolicy.htm">DeadlockPolicy Class <a href="#seeAlsoToggle"
 onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
 </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_BaseDatabase_Delete" /><meta name="guid"
content="Overload_BerkeleyDB_BaseDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.BaseDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method "
/><MSHelp:RLTitle Title="BaseDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.BaseDatabase.Delete" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method"
/><MSHelp:Keyword Index="K" Term="BaseDatabase.Delete method" /><MSHelp:Keyword Index="F"
Term="Delete" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Delete" /><MSHelp:Keyword
 Index="F" Term="BerkeleyDB.BaseDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0;
 width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif"

/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationStats Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="Properties_T_BerkeleyDB_ReplicationStats" /><meta name="guid"
content="Properties_T_BerkeleyDB_ReplicationStats" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.ReplicationStats" /><MSHelp:TOCTitle Title="ReplicationStats Properties "
/><MSHelp:RLTitle Title="ReplicationStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Properties.T:BerkeleyDB.ReplicationStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBReplicationStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="ReplicationStats
class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats Properties </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method (DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_Append" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_Append" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.Append(BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Append Method (DatabaseEntry)" /><MSHelp:RLTitle Title="QueueDatabase.Append Method (DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.Append(BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.Append" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Append the data item to the end of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">QueueDatabase<span
class="cs">..::<span
class="nu">.Append Method (DatabaseEntry)</td></tr><tr id="headerTableRow3"><td
align="left">QueueDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>MovePrevUnique Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_RecnoCursor_MovePrevUnique" /><meta name="guid"
content="Overload_BerkeleyDB_RecnoCursor_MovePrevUnique"
/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoCursor.MovePrevUnique"
/><MSHelp:TOCTitle Title="MovePrevUnique Method " /><MSHelp:RLTitle

Title="RecnoCursor.MovePrevUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoCursor.MovePrevUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassMovePrevUniqueTopic" /><MSHelp:Keyword Index="K" Term="MovePrevUnique method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.MovePrevUnique method" /><MSHelp:Keyword Index="F" Term="MovePrevUnique" /><MSHelp:Keyword Index="F" Term="RecnoCursor.MovePrevUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.MovePrevUnique Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_TransactionConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_TransactionConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.TransactionConfig" /><MSHelp:TOCTitle Title="TransactionConfig Methods " /><MSHelp:RLTitle Title="TransactionConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.TransactionConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="TransactionConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">TransactionConfig Methods </td></tr><tr
id="headerTableRow3"><td align="left">TransactionConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>returnEnd
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CompactConfig_returnEnd" /><meta name="guid" content="F_BerkeleyDB_CompactConfig_returnEnd" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CompactConfig.returnEnd" /><MSHelp:TOCTitle Title="returnEnd Field" /><MSHelp:RLTitle Title="CompactConfig.returnEnd Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CompactConfig.returnEnd" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassreturnEndTopic" /><MSHelp:Keyword Index="K" Term="returnEnd field" /><MSHelp:Keyword Index="K" Term="CompactConfig.returnEnd field" /><MSHelp:Keyword Index="F" Term="returnEnd" /><MSHelp:Keyword Index="F" Term="CompactConfig.returnEnd" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.returnEnd" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.returnEnd" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database key marking the end of the compaction operation in a Btree or Recno database. This is generally the first key of the page where the operation stopped." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.returnEnd Field</td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Isolation Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_Isolation" /><meta name="guid" content="T_BerkeleyDB_Isolation" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Isolation" /><MSHelp:TOCTitle Title="Isolation Enumeration" /><MSHelp:RLTitle Title="Isolation Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.Isolation" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Isolation.DEGREE_ONE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Isolation.DEGREE_TWO" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Isolation.DEGREE_THREE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIsolationClassTopic" /><MSHelp:Keyword Index="K" Term="Isolation enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Isolation enumeration" /><MSHelp:Keyword Index="K" Term="DEGREE_ONE enumeration member" /><MSHelp:Keyword Index="K" Term="DEGREE_TWO enumeration member" /><MSHelp:Keyword Index="K" Term="DEGREE_THREE enumeration member" /><MSHelp:Keyword Index="F" Term="Isolation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Isolation" /><MSHelp:Keyword Index="F" Term="Isolation.DEGREE_ONE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Isolation.DEGREE_ONE" /><MSHelp:Keyword Index="F" Term="Isolation.DEGREE_TWO" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Isolation.DEGREE_TWO" /><MSHelp:Keyword Index="F" Term="Isolation.DEGREE_THREE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Isolation.DEGREE_THREE" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Isolation" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Isolation.DEGREE_ONE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Isolation.DEGREE_TWO" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.Isolation.DEGREE_THREE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify the degree of isolation for transactional operations" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Isolation Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSystemStats Method </title><link

rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:TOCTitle Title="RepMgrSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The replication manager statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirstMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:TOCTitle Title="MoveFirstMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveFirstMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store that pair and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Upgrade Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Upgrade" /><meta name="guid" content="Overload_BerkeleyDB_Database_Upgrade" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.Upgrade" /><MSHelp:TOCTitle Title="Upgrade Method " /><MSHelp:RLTitle Title="Database.Upgrade Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Upgrade" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassUpgradeTopic"

/><MSHelp:Keyword Index="K" Term="Upgrade method" /><MSHelp:Keyword Index="K" Term="Database.Upgrade method" /><MSHelp:Keyword Index="F" Term="Upgrade" /><MSHelp:Keyword Index="F" Term="Database.Upgrade" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Upgrade" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"

type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Upgrade Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Insert Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashCursor_Insert" /><meta name="guid" content="M_BerkeleyDB_HashCursor_Insert" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashCursor.Insert(BerkeleyDB.DatabaseEntry,BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:TOCTitle Title="Insert Method " /><MSHelp:RLTitle Title="HashCursor.Insert Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashCursor.Insert(BerkeleyDB.DatabaseEntry,BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBHashCursorClassInsertTopic" /><MSHelp:Keyword Index="K" Term="Insert method" /><MSHelp:Keyword Index="K" Term="HashCursor.Insert method" /><MSHelp:Keyword Index="F" Term="Insert" /><MSHelp:Keyword Index="F" Term="HashCursor.Insert" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.Insert" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashCursor.Insert" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Insert the data element as a duplicate element of the key to which the cursor refers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.Insert Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:TOCTitle

Title="SecondaryBTreeDatabaseConfig
Class" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K"
Term="SecondaryBTreeDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.SecondaryBTreeDatabaseConfig class" /><MSHelp:Keyword Index="K"
Term="SecondaryBTreeDatabaseConfig class, about SecondaryBTreeDatabaseConfig class" /><MSHelp:Keyword
Index="F" Term="SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_PrintStats" /><meta name="guid" content="M_BerkeleyDB_Sequence_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="Sequence.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.PrintStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Print diagnostic information." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Update Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BackupOptions_Update" /><meta name="guid" content="F_BerkeleyDB_BackupOptions_Update" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BackupOptions.Update" /><MSHelp:TOCTitle Title="Update Field" /><MSHelp:RLTitle Title="BackupOptions.Update Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BackupOptions.Update" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBackupOptionsClassUpdateTopic" /><MSHelp:Keyword Index="K" Term="Update field" /><MSHelp:Keyword Index="K" Term="BackupOptions.Update field" /><MSHelp:Keyword Index="F" Term="Update" /><MSHelp:Keyword Index="F" Term="BackupOptions.Update" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BackupOptions.Update" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BackupOptions.Update" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, perform an incremental back up, instead of a full back up. When this option is specified, only log files are copied to the target directory." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BackupOptions..::.Update Field</td></tr><tr id="headerTableRow3"><td align="left">BackupOptions Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Delete" /><meta name="guid" content="M_BerkeleyDB_Cursor_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="Cursor.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="Cursor.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="Cursor.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Delete" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Delete the key/data pair to which the cursor refers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_Open_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryDatabase.Open Method (String, String, SecondaryDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryDatabase object, open the database represented by and associate the database with the primary index. The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.Open Method (String, String, SecondaryDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationHostAddress Constructor (String)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationHostAddress__ctor_1" /><meta name="guid" content="M_BerkeleyDB_ReplicationHostAddress__ctor_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationHostAddress.#ctor(System.String)" /><MSHelp:TOCTitle Title="ReplicationHostAddress Constructor (String)" /><MSHelp:RLTitle Title="ReplicationHostAddress Constructor (String) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationHostAddress.#ctor(System.String)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationHostAddress..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new address, parsing the host and port from the given string" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationHostAddress Constructor (String)</td></tr><tr

id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ReplicationHostAddress.htm">ReplicationHostAddress Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>NONE Field</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_AckPolicy_NONE" /><meta name="guid" content="F_BerkeleyDB_AckPolicy_NONE"
/><xml><MSHelp:Attr Name="AssetID"
 Value="F:BerkeleyDB.AckPolicy.NONE" /><MSHelp:TOCTitle Title="NONE Field" /><MSHelp:RLTitle
Title="AckPolicy.NONE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.AckPolicy.NONE" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBAckPolicyClassNONETopic" /><MSHelp:Keyword Index="K" Term="NONE field"
/><MSHelp:Keyword Index="K" Term="AckPolicy.NONE field" /><MSHelp:Keyword Index="F" Term="NONE"
/><MSHelp:Keyword Index="F" Term="AckPolicy.NONE" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.AckPolicy.NONE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.AckPolicy.NONE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The
 master should not wait for any client replication message acknowledgments." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
 image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy..::.NONE Field</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxOpenFiles Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxOpenFiles" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxOpenFiles" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxOpenFiles" /><MSHelp:TOCTitle Title="MaxOpenFiles Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxOpenFiles Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxOpenFiles" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxOpenFilesTopic" /><MSHelp:Keyword Index="K" Term="MaxOpenFiles property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxOpenFiles property" /><MSHelp:Keyword Index="F" Term="MaxOpenFiles" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxOpenFiles" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxOpenFiles" /><MSHelp:Attr Name="APIType" Value="Managed"

/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxOpenFiles" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxOpenFiles" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxOpenFiles" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of file descriptors the library will open concurrently when flushing dirty pages from the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxOpenFiles Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_HashDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_HashDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:TOCTitle Title="HashDatabaseConfig Fields" /><MSHelp:RLTitle Title="HashDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.HashDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
 for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
 value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Exists"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transactions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_Transactions" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_Transactions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.Transactions" /><MSHelp:TOCTitle Title="Transactions Property " /><MSHelp:RLTitle Title="TransactionStats.Transactions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.Transactions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassTransactionsTopic" /><MSHelp:Keyword Index="K" Term="Transactions property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Transactions property" /><MSHelp:Keyword Index="F" Term="Transactions" /><MSHelp:Keyword Index="F" Term="TransactionStats.Transactions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.Transactions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.Transactions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Transactions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="List of active transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.Transactions Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrev_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrev_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrev Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MovePrev Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)"

/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrev" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store that pair in . In the presence of duplicate key ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrev Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BaseCursor Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_BaseCursor" /><meta name="guid" content="Methods_T_BerkeleyDB_BaseCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.BaseCursor" /><MSHelp:TOCTitle Title="BaseCursor Methods " /><MSHelp:RLTitle Title="BaseCursor Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.BaseCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="BaseCursor class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"

tabindex="0"> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor Methods </td></tr><tr id="headerTableRow3"><td align="left">BaseCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoCursor Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_RecnoCursor" /><meta name="guid" content="Properties_T_BerkeleyDB_RecnoCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.RecnoCursor" /><MSHelp:TOCTitle Title="RecnoCursor Properties " /><MSHelp:RLTitle Title="RecnoCursor Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.RecnoCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorPropertiesTopic" /><MSHelp:Keyword Index="K" Term="RecnoCursor class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor Properties </td></tr><tr id="headerTableRow3"><td

align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnSnapshot Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_TxnSnapshot" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_TxnSnapshot" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.TxnSnapshot" /><MSHelp:TOCTitle Title="TxnSnapshot Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.TxnSnapshot Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.TxnSnapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassTxnSnapshotTopic" /><MSHelp:Keyword Index="K" Term="TxnSnapshot property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.TxnSnapshot property" /><MSHelp:Keyword Index="F" Term="TxnSnapshot" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.TxnSnapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.TxnSnapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.TxnSnapshot" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_TxnSnapshot" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_TxnSnapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, all transactions in the environment will be started as if was passed to , and all non-transactional cursors will be opened as if was passed to ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.TxnSnapshot Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoDuplicate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_PutNoDuplicate" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_PutNoDuplicate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.PutNoDuplicate" /><MSHelp:TOCTitle Title="PutNoDuplicate Method " /><MSHelp:RLTitle Title="HashDatabase.PutNoDuplicate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.PutNoDuplicate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassPutNoDuplicateTopic" /><MSHelp:Keyword Index="K" Term="PutNoDuplicate method" /><MSHelp:Keyword Index="K" Term="HashDatabase.PutNoDuplicate method" /><MSHelp:Keyword Index="F" Term="PutNoDuplicate"

/><MSHelp:Keyword Index="F" Term="HashDatabase.PutNoDuplicate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.PutNoDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table

id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.PutNoDuplicate Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Cursor" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method " /><MSHelp:RLTitle Title="BTreeDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate"

/><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include

Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td
 align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageNotFoundException Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
 </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_PageNotFoundException" /><meta name="guid" content="Properties_T_BerkeleyDB_PageNotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.PageNotFoundException" /><MSHelp:TOCTitle Title="PageNotFoundException Properties " /><MSHelp:RLTitle Title="PageNotFoundException Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.PageNotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPageNotFoundExceptionPropertiesTopic" /><MSHelp:Keyword
 Index="K" Term="PageNotFoundException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
 height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label
class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">PageNotFoundException Properties </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_PageNotFoundException.htm">PageNotFoundException Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method
(DatabaseEntry, Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="M_BerkeleyDB_SecondaryCursor_Move_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Move_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, Boolean, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (DatabaseEntry, Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the primary key/data pair associated with the given secondary key in . In the presence of duplicate key values, the first data item in the set of duplicates i ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">SecondaryCursor..::.Move Method (DatabaseEntry, Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_FastStats" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="RecnoDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassFastStatsTopic" /><MSHelp:Keyword Index="K" Term="FastStats method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.FastStats method" /><MSHelp:Keyword Index="F" Term="FastStats" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.FastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.FastStats Method </td></tr><tr
id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultipleKey(System.Int32)" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method (Int32)" /><MSHelp:RLTitle Title="Cursor.MoveNextMultipleKey Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultipleKey(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultipleKey is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many ensuing key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor<span

class="languageSpecificText">..::.MoveNextMultipleKey Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReceivedLogRecords Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ReceivedLogRecords" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ReceivedLogRecords" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ReceivedLogRecords" /><MSHelp:TOCTitle Title="ReceivedLogRecords Property " /><MSHelp:RLTitle Title="ReplicationStats.ReceivedLogRecords Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ReceivedLogRecords" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassReceivedLogRecordsTopic" /><MSHelp:Keyword Index="K" Term="ReceivedLogRecords property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ReceivedLogRecords property" /><MSHelp:Keyword Index="F" Term="ReceivedLogRecords" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ReceivedLogRecords" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ReceivedLogRecords" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ReceivedLogRecords" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ReceivedLogRecords" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log records received and put." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ReceivedLogRecords Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockNoWait Property </title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_LockNoWait" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_LockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.LockNoWait" /><MSHelp:TOCTitle Title="LockNoWait Property " /><MSHelp:RLTitle Title="SequenceStats.LockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.LockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="LockNoWait property" /><MSHelp:Keyword Index="K" Term="SequenceStats.LockNoWait property" /><MSHelp:Keyword Index="F" Term="LockNoWait" /><MSHelp:Keyword Index="F" Term="SequenceStats.LockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.LockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.LockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_LockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Sequence lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats..::.LockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeCursor Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BTreeCursor" /><meta name="guid" content="T_BerkeleyDB_BTreeCursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BTreeCursor" /><MSHelp:TOCTitle Title="BTreeCursor Class" /><MSHelp:RLTitle Title="BTreeCursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BTreeCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassTopic" /><MSHelp:Keyword Index="K" Term="BTreeCursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeCursor class" /><MSHelp:Keyword Index="K" Term="BTreeCursor class, about BTreeCursor class" /><MSHelp:Keyword Index="F" Term="BTreeCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class for traversing the records of a" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Compare Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_Compare" /><meta name="guid" content="P_BerkeleyDB_BTreeDatabase_Compare"

/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabase.Compare" /><MSHelp:TOCTitle Title="Compare Property " /><MSHelp:RLTitle Title="BTreeDatabase.Compare Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.Compare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare property" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Compare property" /><MSHelp:Keyword Index="F" Term="Compare" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Compare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Compare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.get_Compare" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.set_Compare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree key comparison function. The comparison function is called whenever it is necessary to compare a key specified by the application with a key currently stored in the tree." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Compare Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitTransactionCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionConfig_InitTransactionCount" /><meta name="guid" content="P_BerkeleyDB_TransactionConfig_InitTransactionCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionConfig.InitTransactionCount" /><MSHelp:TOCTitle Title="InitTransactionCount Property " /><MSHelp:RLTitle Title="TransactionConfig.InitTransactionCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionConfig.InitTransactionCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionConfigClassInitTransactionCountTopic" /><MSHelp:Keyword Index="K" Term="InitTransactionCount property" /><MSHelp:Keyword Index="K" Term="TransactionConfig.InitTransactionCount
property" /><MSHelp:Keyword Index="F" Term="InitTransactionCount" /><MSHelp:Keyword Index="F" Term="TransactionConfig.InitTransactionCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionConfig.InitTransactionCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.InitTransactionCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.get_InitTransactionCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionConfig.set_InitTransactionCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The initial number of simultaneous transactions that will be allocated for in the Berkeley DB environment" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.InitTransactionCount Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionRetry Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_ElectionRetry" /><meta name="guid"

content="P_BerkeleyDB_ReplicationConfig_ElectionRetry"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.ElectionRetry"
/><MSHelp:TOCTitle Title="ElectionRetry Property " /><MSHelp:RLTitle Title="ReplicationConfig.ElectionRetry
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.ElectionRetry"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassElectionRetryTopic"
/><MSHelp:Keyword Index="K" Term="ElectionRetry property" /><MSHelp:Keyword Index="K"
Term="ReplicationConfig.ElectionRetry property" /><MSHelp:Keyword Index="F" Term="ElectionRetry"
/><MSHelp:Keyword Index="F" Term="ReplicationConfig.ElectionRetry" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationConfig.ElectionRetry" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationConfig.ElectionRetry" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationConfig.get_ElectionRetry"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_ElectionRetry" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Configure the amount of time the replication manager will wait before retrying a failed
election. The default wait time is 10 seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label> <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.ElectionRetry Property </td></tr><tr id="headerTableRow3"><td
 align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
 type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="HeapDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Get method" /><MSHelp:Keyword
 Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
 /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepProcessMessage Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_RepProcessMessage" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_RepProcessMessage" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.RepProcessMessage(BerkeleyDB.DatabaseEntry,BerkeleyDB.Datab
aseEntry,System.Int32)" /><MSHelp:TOCTitle Title="RepProcessMessage Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepProcessMessage Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.RepProcessMessage(BerkeleyDB.DatabaseEntry,BerkeleyDB.Databa
seEntry,System.Int32)" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepProcessMessageTopic" /><MSHelp:Keyword
Index="K" Term="RepProcessMessage method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepProcessMessage method" /><MSHelp:Keyword Index="F"
Term="RepProcessMessage" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepProcessMessage"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepProcessMessage" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepProcessMessage"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Process an incoming replication message sent by a member of
the replication group to the local database environment." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepProcessMessage Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Checkpoint Method (UInt32, UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Checkpoint_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Checkpoint_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Checkpoint(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="Checkpoint Method (UInt32, UInt32)" /><MSHelp:RLTitle Title="DatabaseEnvironment.Checkpoint Method (UInt32, UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Checkpoint(System.UInt32,System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Checkpoint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If there has been any logging activity in
the database environment since the last checkpoint, flush the underlying memory pool, write a checkpoint record to the log, and then flush the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Checkpoint Method (UInt32, UInt32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BackingFile Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB"

/><meta name="file" content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_BackingFile" /><meta name="guid" content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_BackingFile" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.BackingFile" /><MSHelp:TOCTitle Title="BackingFile Field" /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.BackingFile Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.BackingFile" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassBackingFileTopic" /><MSHelp:Keyword Index="K" Term="BackingFile field" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig.BackingFile field" /><MSHelp:Keyword Index="F" Term="BackingFile" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.BackingFile" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.BackingFile" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.BackingFile" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The underlying source file for the Recno access method." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig..::.BackingFile Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RecnoStats" /><meta name="guid" content="Methods_T_BerkeleyDB_RecnoStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RecnoStats" /><MSHelp:TOCTitle Title="RecnoStats Methods " /><MSHelp:RLTitle Title="RecnoStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RecnoStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="RecnoStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats Methods </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabaseConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="T_BerkeleyDB_RecnoDatabaseConfig" /><meta name="guid" content="T_BerkeleyDB_RecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:TOCTitle Title="RecnoDatabaseConfig Class" /><MSHelp:RLTitle Title="RecnoDatabaseConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class, about RecnoDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ThreadIsAlive Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_ThreadIsAlive" /><meta name="guid"
content="F_BerkeleyDB_DatabaseEnvironmentConfig_ThreadIsAlive" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.DatabaseEnvironmentConfig.ThreadIsAlive" /><MSHelp:TOCTitle Title="ThreadIsAlive Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.ThreadIsAlive Field (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.ThreadIsAlive"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassThreadIsAliveTopic"
/><MSHelp:Keyword Index="K" Term="ThreadIsAlive field" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.ThreadIsAlive field" /><MSHelp:Keyword Index="F" Term="ThreadIsAlive"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.ThreadIsAlive" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.ThreadIsAlive"
 /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironmentConfig.ThreadIsAlive" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="A delegate that returns if a thread of control (either a true thread or a process) is still running."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
 title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.ThreadIsAlive Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_Remove" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_Remove" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.Remove" /><MSHelp:TOCTitle Title="Remove Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Remove Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.Remove" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRemoveTopic" /><MSHelp:Keyword Index="K" Term="Remove method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Remove method" /><MSHelp:Keyword Index="F" Term="Remove" /><MSHelp:Keyword Index="F"

Term="DatabaseEnvironment.Remove" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox"
type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label

class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Remove Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TruncateUnusedPages Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_TruncateUnusedPages" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_TruncateUnusedPages" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.TruncateUnusedPages" /><MSHelp:TOCTitle Title="TruncateUnusedPages Method " /><MSHelp:RLTitle Title="BTreeDatabase.TruncateUnusedPages Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.TruncateUnusedPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassTruncateUnusedPagesTopic" /><MSHelp:Keyword Index="K" Term="TruncateUnusedPages method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.TruncateUnusedPages method" /><MSHelp:Keyword Index="F" Term="TruncateUnusedPages" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.TruncateUnusedPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.TruncateUnusedPages Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_InitCount" /><meta name="guid" content="P_BerkeleyDB_MutexStats_InitCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.InitCount" /><MSHelp:TOCTitle Title="InitCount Property " /><MSHelp:RLTitle Title="MutexStats.InitCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.InitCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassInitCountTopic" /><MSHelp:Keyword Index="K" Term="InitCount property" /><MSHelp:Keyword Index="K" Term="MutexStats.InitCount property" /><MSHelp:Keyword Index="F" Term="InitCount" /><MSHelp:Keyword Index="F" Term="MutexStats.InitCount" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.InitCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.InitCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_InitCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Mutex initial count" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.InitCount Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DEFAULT Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CachePriority_DEFAULT" /><meta name="guid" content="F_BerkeleyDB_CachePriority_DEFAULT" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CachePriority.DEFAULT" /><MSHelp:TOCTitle Title="DEFAULT Field" /><MSHelp:RLTitle Title="CachePriority.DEFAULT Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CachePriority.DEFAULT" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityClassDEFAULTTopic" /><MSHelp:Keyword Index="K" Term="DEFAULT field" /><MSHelp:Keyword Index="K" Term="CachePriority.DEFAULT field" /><MSHelp:Keyword Index="F" Term="DEFAULT" /><MSHelp:Keyword Index="F" Term="CachePriority.DEFAULT" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CachePriority.DEFAULT" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CachePriority.DEFAULT" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The default priority." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority..::.DEFAULT Field</td></tr><tr id="headerTableRow3"><td align="left">CachePriority Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CachePriority Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB"

/><meta name="file" content="Methods_T_BerkeleyDB_CachePriority" /><meta name="guid" content="Methods_T_BerkeleyDB_CachePriority" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.CachePriority" /><MSHelp:TOCTitle Title="CachePriority Methods " /><MSHelp:RLTitle Title="CachePriority Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.CachePriority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityMethodsTopic" /><MSHelp:Keyword Index="K" Term="CachePriority class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"

type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority Methods </td></tr><tr id="headerTableRow3"><td align="left">CachePriority Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link
rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_BTreeDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_BTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:TOCTitle Title="BTreeDatabaseConfig Properties " /><MSHelp:RLTitle Title="BTreeDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FirstRecordNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_FirstRecordNumber" /><meta name="guid" content="P_BerkeleyDB_QueueStats_FirstRecordNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.FirstRecordNumber" /><MSHelp:TOCTitle Title="FirstRecordNumber Property " /><MSHelp:RLTitle Title="QueueStats.FirstRecordNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.FirstRecordNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassFirstRecordNumberTopic" /><MSHelp:Keyword Index="K" Term="FirstRecordNumber property" /><MSHelp:Keyword Index="K" Term="QueueStats.FirstRecordNumber property" /><MSHelp:Keyword Index="F" Term="FirstRecordNumber" /><MSHelp:Keyword Index="F" Term="QueueStats.FirstRecordNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.FirstRecordNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.FirstRecordNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_FirstRecordNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="First not deleted record." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.FirstRecordNumber Property </td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentElectionGenerationNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_CurrentElectionGenerationNumber" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_CurrentElectionGenerationNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.CurrentElectionGenerationNumber" /><MSHelp:TOCTitle Title="CurrentElectionGenerationNumber Property " /><MSHelp:RLTitle Title="ReplicationStats.CurrentElectionGenerationNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.CurrentElectionGenerationNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassCurrentElectionGenerationNumberTopic" /><MSHelp:Keyword Index="K" Term="CurrentElectionGenerationNumber property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.CurrentElectionGenerationNumber property" /><MSHelp:Keyword Index="F" Term="CurrentElectionGenerationNumber" /><MSHelp:Keyword Index="F" Term="ReplicationStats.CurrentElectionGenerationNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.CurrentElectionGenerationNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.CurrentElectionGenerationNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_CurrentElectionGenerationNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current election gen number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.CurrentElectionGenerationNumber Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleDatabaseEntry Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MultipleDatabaseEntry" /><meta name="guid" content="Properties_T_BerkeleyDB_MultipleDatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:TOCTitle Title="MultipleDatabaseEntry Properties " /><MSHelp:RLTitle Title="MultipleDatabaseEntry Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MultipleDatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMultipleDatabaseEntryPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MultipleDatabaseEntry class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Properties </td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_MPoolSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_MPoolSystemStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.MPoolSystemStats(System.Boolean)" /><MSHelp:TOCTitle Title="MPoolSystemStats Method (Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.MPoolSystemStats Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.MPoolSystemStats(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MPoolSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The memory pool (that is, the buffer cache) subsystem statistics" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DatabaseEnvironment<span
class="cs">..::<span
class="nu">.MPoolSystemStats Method (Boolean)</td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>HeapFullException Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="M_BerkeleyDB_HeapFullException__ctor" /><meta name="guid"
content="M_BerkeleyDB_HeapFullException__ctor" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.HeapFullException.#ctor" /><MSHelp:TOCTitle Title="HeapFullException Constructor " /><MSHelp:RLTitle Title="HeapFullException Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapFullException.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapFullExceptionClassctorTopic" /><MSHelp:Keyword Index="K" Term="HeapFullException class, constructor" /><MSHelp:Keyword Index="K" Term="HeapFullException.HeapFullException constructor" /><MSHelp:Keyword Index="F" Term="HeapFullException" /><MSHelp:Keyword Index="F" Term="HeapFullException.HeapFullException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapFullException.HeapFullException" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapFullException..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initialize a new instance of the HeapFullException" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapFullException Constructor </td></tr><tr id="headerTableRow3"><td align="left">HeapFullException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>fromArray Method (Byte[])</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
 type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapRecordId_fromArray" /><meta
name="guid" content="M_BerkeleyDB_HeapRecordId_fromArray" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HeapRecordId.fromArray(System.Byte[])" /><MSHelp:TOCTitle Title="fromArray Method (Byte[])" /><MSHelp:RLTitle Title="HeapRecordId.fromArray Method (Byte[]) (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapRecordId.fromArray(System.Byte[])"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.fromArray"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
 /><MSHelp:Attr Name="Abstract" Value="Construct a HeapRecordId from a byte array, typically ."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
 title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:

Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.fromArray Method (array<Byte>[]()[])</td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoPanic Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoPanic" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_NoPanic" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.NoPanic" /><MSHelp:TOCTitle Title="NoPanic Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.NoPanic Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.NoPanic" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassNoPanicTopic" /><MSHelp:Keyword Index="K" Term="NoPanic field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.NoPanic field" /><MSHelp:Keyword Index="F" Term="NoPanic" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.NoPanic" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.NoPanic" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.NoPanic" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will ignore any panic state in the database environment. (Database environments in a panic state normally refuse all attempts to call Berkeley DB functions, throwing . This fun ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.NoPanic Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Recno Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Recno_1" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Recno_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Recno(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Recno Method (LockingInfo)" /><MSHelp:RLTitle Title="BTreeCursor.Recno Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Recno(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Recno" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the record number associated with the cursor's current position." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.Recno Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td
 align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapFullException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
 type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HeapFullException" /><meta name="guid" content="Methods_T_BerkeleyDB_HeapFullException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HeapFullException" /><MSHelp:TOCTitle Title="HeapFullException Methods " /><MSHelp:RLTitle Title="HeapFullException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HeapFullException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapFullExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="HeapFullException class, methods" /><MSHelp:Attr
 Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
 style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapFullException Methods </td></tr><tr id="headerTableRow3"><td align="left">HeapFullException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorFeedback Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_ErrorFeedback" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_ErrorFeedback" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.ErrorFeedback" /><MSHelp:TOCTitle Title="ErrorFeedback Property " /><MSHelp:RLTitle Title="BaseDatabase.ErrorFeedback Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.ErrorFeedback" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassErrorFeedbackTopic" /><MSHelp:Keyword Index="K" Term="ErrorFeedback property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.ErrorFeedback property" /><MSHelp:Keyword Index="F" Term="ErrorFeedback" /><MSHelp:Keyword Index="F" Term="BaseDatabase.ErrorFeedback" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.ErrorFeedback" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.ErrorFeedback" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_ErrorFeedback" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.set_ErrorFeedback" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mechanism for reporting detailed error messages to the application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.ErrorFeedback Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Cursor_3" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Cursor_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Cursor(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor Method (Transaction)" /><MSHelp:RLTitle Title="RecnoDatabase.Cursor Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Cursor(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Cursor Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentMultiple Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Cursor_CurrentMultiple" /><meta name="guid" content="P_BerkeleyDB_Cursor_CurrentMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Cursor.CurrentMultiple" /><MSHelp:TOCTitle Title="CurrentMultiple Property " /><MSHelp:RLTitle Title="Cursor.CurrentMultiple Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Cursor.CurrentMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassCurrentMultipleTopic" /><MSHelp:Keyword Index="K" Term="CurrentMultiple property" /><MSHelp:Keyword Index="K" Term="Cursor.CurrentMultiple property"

/><MSHelp:Keyword Index="F" Term="CurrentMultiple"
/><MSHelp:Keyword Index="F" Term="Cursor.CurrentMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Cursor.CurrentMultiple" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.CurrentMultiple" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.get_CurrentMultiple" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.set_CurrentMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The key and
multiple data items at which the cursor currently points." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.CurrentMultiple Property
</td></tr><tr id="headerTableRow3"><td align="left">Cursor
Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IBackup Interface</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_IBackup" /><meta name="guid" content="T_BerkeleyDB_IBackup" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.IBackup" /><MSHelp:TOCTitle Title="IBackup Interface" /><MSHelp:RLTitle Title="IBackup Interface (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.IBackup" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIBackupClassTopic" /><MSHelp:Keyword Index="K" Term="IBackup interface" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.IBackup interface" /><MSHelp:Keyword Index="K" Term="IBackup interface, about IBackup interface" /><MSHelp:Keyword Index="F" Term="IBackup" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.IBackup" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.IBackup" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An interface that can optionally be used to override the default behavior performed by the and methods. Implementation of this interface is required if the DatabaseEnvironment.backup or ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">IBackup Interface</td></tr><tr
id="headerTableRow3"><td align="left">Members <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TruncateUnusedPages Method </title><link
rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_HashDatabase_TruncateUnusedPages" /><meta name="guid"
content="M_BerkeleyDB_HashDatabase_TruncateUnusedPages" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:TOCTitle Title="TruncateUnusedPages
Method " /><MSHelp:RLTitle Title="HashDatabase.TruncateUnusedPages Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.TruncateUnusedPages" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Return pages to the filesystem that are already free and at the end of the file."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.TruncateUnusedPages Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSystemStats Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSystemStats_1" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_RepMgrSystemStats_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats(System.Boolean)" /><MSHelp:TOCTitle
Title="RepMgrSystemStats Method (Boolean)" /><MSHelp:RLTitle
Title="DatabaseEnvironment.RepMgrSystemStats
Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats(System.Boolean)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepMgrSystemStats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The replication manager statistics" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.<span

class="cpp">::.RepMgrSystemStats Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RecnoDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:TOCTitle Title="RecnoDatabaseConfig Members" /><MSHelp:RLTitle Title="RecnoDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand

All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_Cursor_RefreshMultiple" /><meta
name="guid" content="M_BerkeleyDB_Cursor_RefreshMultiple" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:TOCTitle Title="RefreshMultiple Method "
/><MSHelp:RLTitle Title="Cursor.RefreshMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.RefreshMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data
pair to which the cursor refers and as many duplicate data items that can fit in a buffer the size of one database page
in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td

align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_CompactConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_CompactConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.CompactConfig.#ctor" /><MSHelp:TOCTitle Title="CompactConfig Constructor " /><MSHelp:RLTitle Title="CompactConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.CompactConfig.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="CompactConfig class, constructor" /><MSHelp:Keyword Index="K" Term="CompactConfig.CompactConfig constructor" /><MSHelp:Keyword Index="F" Term="CompactConfig" /><MSHelp:Keyword Index="F" Term="CompactConfig.CompactConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.CompactConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a new CompactConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>HeapFullException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HeapFullException" /><meta name="guid" content="T_BerkeleyDB_HeapFullException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HeapFullException" /><MSHelp:TOCTitle
Title="HeapFullException Class" /><MSHelp:RLTitle Title="HeapFullException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HeapFullException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapFullExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="HeapFullException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HeapFullException class" /><MSHelp:Keyword Index="K" Term="HeapFullException class, about HeapFullException class" /><MSHelp:Keyword Index="F" Term="HeapFullException" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.HeapFullException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapFullException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An attempt was made to add or update a record in a . However, the size of the database was constrained using , and that limit has been reached." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapFullException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_DatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_DatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.DatabaseConfig" /><MSHelp:TOCTitle Title="DatabaseConfig Fields" /><MSHelp:RLTitle Title="DatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.DatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Register Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Register" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Register" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Register" /><MSHelp:TOCTitle Title="Register Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Register Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Register" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRegisterTopic" /><MSHelp:Keyword Index="K" Term="Register property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Register property" /><MSHelp:Keyword Index="F" Term="Register" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Register" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Register" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Register" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Register" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will have checked
to see if recovery needed to be performed before opening the database environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Register Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexConfig

Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_MutexConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_MutexConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.MutexConfig" /><MSHelp:TOCTitle Title="MutexConfig Members" /><MSHelp:RLTitle Title="MutexConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.MutexConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="MutexConfig class" /><MSHelp:Keyword Index="K" Term="MutexConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MutexConfig class" /><MSHelp:Keyword Index="F" Term="MutexConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig Members</td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class Constructors Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepSetRetransmissionRequest Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepSetRetransmissionRequest" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepSetRetransmissionRequest" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepSetRetransmissionRequest(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="RepSetRetransmissionRequest Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepSetRetransmissionRequest Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepSetRetransmissionRequest(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepSetRetransmissionRequestTopic" /><MSHelp:Keyword

Index="K" Term="RepSetRetransmissionRequest method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepSetRetransmissionRequest method" /><MSHelp:Keyword Index="F" Term="RepSetRetransmissionRequest" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepSetRetransmissionRequest" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepSetRetransmissionRequest" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepSetRetransmissionRequest" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set a threshold for the minimum and maximum time that a client waits before requesting retransmission of a missing message." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepSetRetransmissionRequest Method

</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicatePagesFreeBytes
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_DuplicatePagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_DuplicatePagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.DuplicatePagesFreeBytes" /><MSHelp:TOCTitle
Title="DuplicatePagesFreeBytes Property " /><MSHelp:RLTitle Title="RecnoStats.DuplicatePagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassDuplicatePagesFreeBytesTopic" /><MSHelp:Keyword Index="K" Term="DuplicatePagesFreeBytes property" /><MSHelp:Keyword Index="K" Term="RecnoStats.DuplicatePagesFreeBytes property" /><MSHelp:Keyword Index="F" Term="DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="F" Term="RecnoStats.DuplicatePagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.DuplicatePagesFreeBytes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.DuplicatePagesFreeBytes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_DuplicatePagesFreeBytes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in duplicate pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.DuplicatePagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HeapDatabase_Stats_2" /><meta name="guid" content="M_BerkeleyDB_HeapDatabase_Stats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="Stats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="HeapDatabase.Stats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapDatabase.Stats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this database."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">HeapDatabase.<span
class="vb">.::.Stats Method (Transaction,
Isolation)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_HeapDatabase.htm">HeapDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MoveFirstMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveFirstMultiple" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveFirstMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:TOCTitle Title="MoveFirstMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveFirstMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveFirstMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data
pair of the database, and store that key and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveFirstMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNextMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNextMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextMultipleKey" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextMultipleKey method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNextMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;

height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForeignKeyNullfier Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryDatabaseConfig_ForeignKeyNullfier" /><meta name="guid" content="P_BerkeleyDB_SecondaryDatabaseConfig_ForeignKeyNullfier" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyNullfier" /><MSHelp:TOCTitle Title="ForeignKeyNullfier Property " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.ForeignKeyNullfier Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyNullfier" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassForeignKeyNullfierTopic" /><MSHelp:Keyword Index="K" Term="ForeignKeyNullfier property" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.ForeignKeyNullfier property" /><MSHelp:Keyword Index="F" Term="ForeignKeyNullfier" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig.ForeignKeyNullfier" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyNullfier" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.ForeignKeyNullfier" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.get_ForeignKeyNullfier" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The nullifying function used to set the foreign key to null." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.ForeignKeyNullfier Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:TOCTitle Title="SecondaryDatabaseConfig Constructor " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.SecondaryDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig" /><MSHelp:Keyword Index="F"

Term="SecondaryDatabaseConfig.SecondaryDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.SecondaryDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryDatabaseConfig object, with the default configuration settings." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ByteOrder
Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_ByteOrder" /><meta name="guid"
content="Fields_T_BerkeleyDB_ByteOrder" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.ByteOrder" /><MSHelp:TOCTitle Title="ByteOrder Fields" /><MSHelp:RLTitle
Title="ByteOrder Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.ByteOrder"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBByteOrderFieldsTopic" /><MSHelp:Keyword Index="K"
Term="ByteOrder class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ByteOrder Fields</td></tr><tr id="headerTableRow3"><td align="left">ByteOrder Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Move_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Move_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the primary key/data pair associated with the given secondary key in . In the presence of duplicate key values, the first data item in the set of duplicates i ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Move Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Key Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Sequence_Key" /><meta name="guid" content="P_BerkeleyDB_Sequence_Key" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Sequence.Key" /><MSHelp:TOCTitle Title="Key Property " /><MSHelp:RLTitle Title="Sequence.Key Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Sequence.Key" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassKeyTopic" /><MSHelp:Keyword Index="K" Term="Key property" /><MSHelp:Keyword Index="K" Term="Sequence.Key property" /><MSHelp:Keyword Index="F" Term="Key" /><MSHelp:Keyword Index="F" Term="Sequence.Key" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Key" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Key" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.get_Key" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The key for the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Key Property </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxPartitionLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxPartitionLockNoWait" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxPartitionLockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxPartitionLockNoWait" /><MSHelp:TOCTitle Title="MaxPartitionLockNoWait Property " /><MSHelp:RLTitle Title="LockStats.MaxPartitionLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxPartitionLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxPartitionLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="MaxPartitionLockNoWait property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxPartitionLockNoWait property" /><MSHelp:Keyword Index="F" Term="MaxPartitionLockNoWait" /><MSHelp:Keyword Index="F" Term="LockStats.MaxPartitionLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxPartitionLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxPartitionLockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_MaxPartitionLockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max partition lock granted without wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxPartitionLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Cursor" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Cursor" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Cursor" /><MSHelp:TOCTitle Title="Cursor Method "
/><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Cursor Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Cursor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassCursorTopic" /><MSHelp:Keyword Index="K"
Term="Cursor method"
/><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Cursor method" /><MSHelp:Keyword
Index="F" Term="Cursor" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Cursor"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Cursor" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" />
<label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Cursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ClientStartupComplete Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ClientStartupComplete" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ClientStartupComplete" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ClientStartupComplete" /><MSHelp:TOCTitle Title="ClientStartupComplete Property " /><MSHelp:RLTitle Title="ReplicationStats.ClientStartupComplete Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ClientStartupComplete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassClientStartupCompleteTopic" /><MSHelp:Keyword Index="K" Term="ClientStartupComplete property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ClientStartupComplete property" /><MSHelp:Keyword Index="F" Term="ClientStartupComplete" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ClientStartupComplete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ClientStartupComplete" /><MSHelp:Attr

Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ClientStartupComplete" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ClientStartupComplete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Site completed client sync-up." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ClientStartupComplete Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>VerificationException Properties </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="Properties_T_BerkeleyDB_VerificationException" /><meta name="guid"
content="Properties_T_BerkeleyDB_VerificationException" /><xml><MSHelp:Attr Name="AssetID"
Value="Properties.T:BerkeleyDB.VerificationException" /><MSHelp:TOCTitle Title="VerificationException
Properties " /><MSHelp:RLTitle Title="VerificationException Properties (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Properties.T:BerkeleyDB.VerificationException" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBVerificationExceptionPropertiesTopic" /><MSHelp:Keyword Index="K"
Term="VerificationException class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerificationException Properties </td></tr><tr id="headerTableRow3"><td align="left">VerificationException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEntry__ctor" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEntry__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEntry.#ctor" /><MSHelp:TOCTitle Title="DatabaseEntry Constructor " /><MSHelp:RLTitle Title="DatabaseEntry Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEntry.#ctor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryClassctorTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class, constructor" /><MSHelp:Keyword Index="K" Term="DatabaseEntry.DatabaseEntry constructor" /><MSHelp:Keyword Index="F" Term="DatabaseEntry" /><MSHelp:Keyword Index="F" Term="DatabaseEntry.DatabaseEntry" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry.DatabaseEntry" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">DatabaseEntry Constructor </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveLast_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveLast_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store the secondary key and primary key/data pair in . If the last key has duplicate values, the last data item in the set of ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveLast Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepElectionTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepElectionTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepElectionTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepElectionTimeout" /><MSHelp:TOCTitle Title="RepElectionTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepElectionTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepElectionTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepElectionTimeoutTopic" /><MSHelp:Keyword Index="K" Term="RepElectionTimeout property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepElectionTimeout property" /><MSHelp:Keyword Index="F" Term="RepElectionTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepElectionTimeout"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepElectionTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepElectionTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The timeout period for an election. The default timeout is 2 seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepElectionTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class <a

href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>BadSecondaryException Constructor </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_BadSecondaryException__ctor" /><meta name="guid"
content="M_BerkeleyDB_BadSecondaryException__ctor" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BadSecondaryException.#ctor" /><MSHelp:TOCTitle Title="BadSecondaryException
Constructor " /><MSHelp:RLTitle Title="BadSecondaryException Constructor (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BadSecondaryException.#ctor" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBadSecondaryExceptionClassctorTopic" /><MSHelp:Keyword Index="K"
Term="BadSecondaryException class, constructor" /><MSHelp:Keyword Index="K"
Term="BadSecondaryException.BadSecondaryException constructor" /><MSHelp:Keyword Index="F"
Term="BadSecondaryException" /><MSHelp:Keyword Index="F"
Term="BadSecondaryException.BadSecondaryException" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BadSecondaryException.BadSecondaryException" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BadSecondaryException..ctor" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Initialize a new instance of the BadSecondaryException"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
 style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
 cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BadSecondaryException Constructor </td></tr><tr id="headerTableRow3"><td align="left">BadSecondaryException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionWait Property </title><link rel="stylesheet"
 type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_RegionWait" /><meta name="guid" content="P_BerkeleyDB_MutexStats_RegionWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.RegionWait" /><MSHelp:TOCTitle Title="RegionWait Property " /><MSHelp:RLTitle Title="MutexStats.RegionWait
 Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.RegionWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassRegionWaitTopic" /><MSHelp:Keyword Index="K" Term="RegionWait property" /><MSHelp:Keyword Index="K" Term="MutexStats.RegionWait property" /><MSHelp:Keyword Index="F" Term="RegionWait" /><MSHelp:Keyword Index="F" Term="MutexStats.RegionWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.RegionWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.RegionWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_RegionWait" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.RegionWait Property </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey(System.Int32)" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method (Int32)" /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultipleKey Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair and as many duplicate data ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultipleKey Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryQueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryQueueDatabaseConfig Properties " /><MSHelp:RLTitle Title="SecondaryQueueDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryQueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>MinKeysPerPage Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_MinKeysPerPage" /><meta
name="guid" content="P_BerkeleyDB_BTreeDatabase_MinKeysPerPage" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.BTreeDatabase.MinKeysPerPage" /><MSHelp:TOCTitle
Title="MinKeysPerPage Property " /><MSHelp:RLTitle Title="BTreeDatabase.MinKeysPerPage Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.MinKeysPerPage"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassMinKeysPerPageTopic"
/><MSHelp:Keyword Index="K" Term="MinKeysPerPage property" /><MSHelp:Keyword Index="K"
Term="BTreeDatabase.MinKeysPerPage property" /><MSHelp:Keyword Index="F" Term="MinKeysPerPage"
/><MSHelp:Keyword Index="F" Term="BTreeDatabase.MinKeysPerPage" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeDatabase.MinKeysPerPage" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.MinKeysPerPage" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabase.get_MinKeysPerPage" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The minimum
number of key/data pairs intended to be stored on any single Btree leaf page." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.MinKeysPerPage Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogFlush Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_LogFlush" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_LogFlush" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:TOCTitle Title="LogFlush Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.LogFlush Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LogFlush" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Write all log records to disk." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LogFlush Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseType Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta

name="file" content="Methods_T_BerkeleyDB_DatabaseType" /><meta name="guid" content="Methods_T_BerkeleyDB_DatabaseType" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DatabaseType" /><MSHelp:TOCTitle Title="DatabaseType Methods " /><MSHelp:RLTitle Title="DatabaseType Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DatabaseType" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeMethodsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseType class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType Methods </td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultipleKey Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair and as many duplicate data ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultipleKey Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentWinner Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_CurrentWinner" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_CurrentWinner" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.CurrentWinner" /><MSHelp:TOCTitle Title="CurrentWinner Property " /><MSHelp:RLTitle Title="ReplicationStats.CurrentWinner Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.ReplicationStats.CurrentWinner" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassCurrentWinnerTopic" /><MSHelp:Keyword Index="K" Term="CurrentWinner property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.CurrentWinner property" /><MSHelp:Keyword Index="F" Term="CurrentWinner" /><MSHelp:Keyword Index="F" Term="ReplicationStats.CurrentWinner" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.CurrentWinner" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.CurrentWinner" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_CurrentWinner" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current front-runner." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::<span

class="nu">.CurrentWinner Property </td></tr><tr id="headerTableRow3"><td
align="left">ReplicationStats Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Delete" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method "
/><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Delete" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K"
Term="Delete method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Delete method"
/><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabase.Delete" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB"
 /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
 /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label
class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryBTreeDatabase<span
class="cs">..::<span
class="nu">.Delete Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryBTreeDatabase.htm">SecondaryBTreeDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Add Method
(KeyValuePair(DatabaseEntry, DatabaseEntry), Cursor.InsertLocation)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashCursor_Add" /><meta name="guid"

content="M_BerkeleyDB_HashCursor_Add" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashCursor.Add(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,B
erkeleyDB.DatabaseEntry},BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:TOCTitle Title="Add Method
(KeyValuePair(DatabaseEntry, DatabaseEntry), Cursor.InsertLocation)" /><MSHelp:RLTitle
Title="HashCursor.Add Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Cursor.InsertLocation)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.HashCursor.Add(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,Be
rkeleyDB.DatabaseEntry},BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashCursor.Add" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Insert the specified key/data pair into the database." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">HashCursor..::.Add Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Cursor..::.InsertLocation)</td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BulkRecordsStored Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_BulkRecordsStored" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_BulkRecordsStored" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.BulkRecordsStored" /><MSHelp:TOCTitle Title="BulkRecordsStored Property " /><MSHelp:RLTitle Title="ReplicationStats.BulkRecordsStored Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.BulkRecordsStored" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassBulkRecordsStoredTopic" /><MSHelp:Keyword Index="K" Term="BulkRecordsStored property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.BulkRecordsStored property" /><MSHelp:Keyword Index="F" Term="BulkRecordsStored" /><MSHelp:Keyword Index="F" Term="ReplicationStats.BulkRecordsStored" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.BulkRecordsStored" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.BulkRecordsStored" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_BulkRecordsStored" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bulk records stored." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.BulkRecordsStored Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID"

Value="Overload:BerkeleyDB.SecondaryQueueDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationTest Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_ReplicationTest" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_ReplicationTest" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.ReplicationTest" /><MSHelp:TOCTitle Title="ReplicationTest Field" /><MSHelp:RLTitle Title="VerboseMessages.ReplicationTest Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.ReplicationTest" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassReplicationTestTopic" /><MSHelp:Keyword Index="K" Term="ReplicationTest field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.ReplicationTest field" /><MSHelp:Keyword Index="F" Term="ReplicationTest" /><MSHelp:Keyword Index="F" Term="VerboseMessages.ReplicationTest" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.ReplicationTest" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.ReplicationTest" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.ReplicationTest Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BaseDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_BaseDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BaseDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="BaseDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BaseDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="BaseDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="BaseDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BaseDatabase<span
class="cs">..::<span
class="nu">.Close Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BaseDatabase.htm">BaseDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Transactional
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_Transactional" /><meta
name="guid" content="P_BerkeleyDB_BaseDatabase_Transactional" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BaseDatabase.Transactional" /><MSHelp:TOCTitle Title="Transactional Property "
/><MSHelp:RLTitle Title="BaseDatabase.Transactional Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.Transactional"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassTransactionalTopic"
/><MSHelp:Keyword Index="K" Term="Transactional property" /><MSHelp:Keyword Index="K"
Term="BaseDatabase.Transactional property" /><MSHelp:Keyword Index="F" Term="Transactional"
/><MSHelp:Keyword Index="F" Term="BaseDatabase.Transactional" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseDatabase.Transactional" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.Transactional" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_Transactional" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true,
this database has been opened in a transactional mode." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Transactional Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Append Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_HeapDatabase_Append" /><meta name="guid"
content="Overload_BerkeleyDB_HeapDatabase_Append"
/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.Append"
/><MSHelp:TOCTitle Title="Append Method " /><MSHelp:RLTitle Title="HeapDatabase.Append Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.Append"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassAppendTopic" /><MSHelp:Keyword
Index="K" Term="Append method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.Append method"
/><MSHelp:Keyword Index="F" Term="Append" /><MSHelp:Keyword Index="F" Term="HeapDatabase.Append"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.Append" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.Append Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ErrorFeedback Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_ErrorFeedback" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_ErrorFeedback" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.ErrorFeedback" /><MSHelp:TOCTitle Title="ErrorFeedback Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.ErrorFeedback Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.ErrorFeedback" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassErrorFeedbackTopic" /><MSHelp:Keyword Index="K" Term="ErrorFeedback property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.ErrorFeedback property" /><MSHelp:Keyword Index="F" Term="ErrorFeedback" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.ErrorFeedback" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ErrorFeedback" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.ErrorFeedback" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.DatabaseEnvironment.get_ErrorFeedback" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_ErrorFeedback" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The mechanism for reporting detailed error messages to the application." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ErrorFeedback Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MultipleDatabaseEntry Constructor (Byte[], Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_MultipleDatabaseEntry__ctor" /><meta name="guid" content="M_BerkeleyDB_MultipleDatabaseEntry__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.MultipleDatabaseEntry.#ctor(System.Byte[],System.Boolean)" /><MSHelp:TOCTitle Title="MultipleDatabaseEntry Constructor (Byte[], Boolean)" /><MSHelp:RLTitle Title="MultipleDatabaseEntry Constructor (Byte[], Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.MultipleDatabaseEntry.#ctor(System.Byte[],System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MultipleDatabaseEntry..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Construct a new key or data bulk buffer with a formatted byte array." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div

id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MultipleDatabaseEntry Constructor (array<Byte>[]()[], Boolean)</td></tr><tr id="headerTableRow3"><td align="left">MultipleDatabaseEntry Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapDatabase_RegionSize" /><meta name="guid" content="P_BerkeleyDB_HeapDatabase_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapDatabase.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="HeapDatabase.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapDatabase.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassRegionSizeTopic" /><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="HeapDatabase.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="HeapDatabase.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabase.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of pages in a region of the database. It is set by when the heap database is opened." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (DatabaseEntry, DatabaseEntry, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_Move" /><meta name="guid" content="M_BerkeleyDB_Cursor_Move"
/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean)"
/><MSHelp:TOCTitle Title="Move Method (DatabaseEntry, DatabaseEntry, Boolean)" /><MSHelp:RLTitle
Title="Cursor.Move Method (DatabaseEntry, DatabaseEntry, Boolean) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.Cursor.Move(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,System.Boolean)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Move"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to , and store the datum associated with the given
key in . In the presence of duplicate key values, the first data item in the set of duplicates is stored in . If either ..."
/><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method (DatabaseEntry, DatabaseEntry, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method (MultipleKeyDatabaseEntry, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Put_3" /><meta name="guid" content="M_BerkeleyDB_Database_Put_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Put(BerkeleyDB.MultipleKeyDatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Put Method (MultipleKeyDatabaseEntry, Transaction)" /><MSHelp:RLTitle Title="Database.Put Method (MultipleKeyDatabaseEntry, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Put(BerkeleyDB.MultipleKeyDatabaseEntry,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store multiple data items using keys from the buffer to which the key parameter refers and data values from the buffer to which the data parameter refers. A successful bulk operation is logically ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database<span
class="languageSpecificText">..<span
class="cpp">::.Put Method (MultipleKeyDatabaseEntry,
Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_Database.htm">Database Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryCursor Method (CursorConfig, Transaction)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor_2"
/><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor_2" /><xml><MSHelp:Attr
Name="AssetID"

Value="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)
" /><MSHelp:TOCTitle Title="SecondaryCursor Method (CursorConfig, Transaction)" /><MSHelp:RLTitle
Title="SecondaryDatabase.SecondaryCursor Method (CursorConfig, Transaction) (BerkeleyDB)"
/><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor(BerkeleyDB.CursorConfig,BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected
secondary database cursor with the given configuration." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryDatabase.<span

class="vb">.::.SecondaryCursor Method (CursorConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="QueueDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Deadlock Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_VerboseMessages_Deadlock" /><meta name="guid" content="F_BerkeleyDB_VerboseMessages_Deadlock" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.VerboseMessages.Deadlock" /><MSHelp:TOCTitle Title="Deadlock Field" /><MSHelp:RLTitle Title="VerboseMessages.Deadlock Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.VerboseMessages.Deadlock" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassDeadlockTopic" /><MSHelp:Keyword Index="K" Term="Deadlock field" /><MSHelp:Keyword Index="K" Term="VerboseMessages.Deadlock field" /><MSHelp:Keyword Index="F" Term="Deadlock" /><MSHelp:Keyword Index="F" Term="VerboseMessages.Deadlock" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages.Deadlock" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages.Deadlock" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display additional information when doing deadlock detection." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages..::.Deadlock Field</td></tr><tr id="headerTableRow3"><td align="left">VerboseMessages Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ONE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_AckPolicy_ONE" /><meta name="guid" content="F_BerkeleyDB_AckPolicy_ONE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.AckPolicy.ONE" /><MSHelp:TOCTitle Title="ONE Field" /><MSHelp:RLTitle Title="AckPolicy.ONE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.AckPolicy.ONE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyClassONETopic" /><MSHelp:Keyword Index="K" Term="ONE field" /><MSHelp:Keyword Index="K" Term="AckPolicy.ONE field" /><MSHelp:Keyword Index="F" Term="ONE" /><MSHelp:Keyword Index="F" Term="AckPolicy.ONE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy.ONE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.AckPolicy.ONE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The master should wait until at least one client site has acknowledged each permanent replication message." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">AckPolicy..::.ONE Field</td></tr><tr id="headerTableRow3"><td align="left">AckPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironmentConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DatabaseEnvironmentConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_DatabaseEnvironmentConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:TOCTitle Title="DatabaseEnvironmentConfig Methods " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DatabaseEnvironmentConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr

Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">DatabaseEnvironmentConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Methods_T_BerkeleyDB_BTreeDatabase" /><meta name="guid"
content="Methods_T_BerkeleyDB_BTreeDatabase" /><xml><MSHelp:Attr Name="AssetID"
Value="Methods.T:BerkeleyDB.BTreeDatabase" /><MSHelp:TOCTitle Title="BTreeDatabase Methods "
/><MSHelp:RLTitle Title="BTreeDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Methods.T:BerkeleyDB.BTreeDatabase" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle"
 /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
 onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">BTreeDatabase Methods </td></tr><tr id="headerTableRow3"><td
align="left">BTreeDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>WriteToLog
Method </title><link rel="stylesheet"
type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="Overload_BerkeleyDB_DatabaseEnvironment_WriteToLog" /><meta name="guid"
content="Overload_BerkeleyDB_DatabaseEnvironment_WriteToLog" /><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.DatabaseEnvironment.WriteToLog" /><MSHelp:TOCTitle Title="WriteToLog

Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.WriteToLog Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.WriteToLog" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassWriteToLogTopic" /><MSHelp:Keyword Index="K" Term="WriteToLog method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.WriteToLog method" /><MSHelp:Keyword Index="F" Term="WriteToLog" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.WriteToLog" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.WriteToLog" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.WriteToLog Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerboseMessages Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_VerboseMessages" /><meta name="guid" content="T_BerkeleyDB_VerboseMessages" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.VerboseMessages" /><MSHelp:TOCTitle Title="VerboseMessages Class" /><MSHelp:RLTitle Title="VerboseMessages Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.VerboseMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerboseMessagesClassTopic" /><MSHelp:Keyword Index="K" Term="VerboseMessages class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.VerboseMessages class" /><MSHelp:Keyword Index="K" Term="VerboseMessages class, about VerboseMessages class" /><MSHelp:Keyword Index="F" Term="VerboseMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VerboseMessages" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VerboseMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Enable specific additional informational and debugging messages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"

/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerboseMessages Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepStartClient Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RepStartClient" /><meta name="guid"

content="Overload_BerkeleyDB_DatabaseEnvironment_RepStartClient" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:TOCTitle Title="RepStartClient Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepStartClient Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepStartClientTopic" /><MSHelp:Keyword Index="K" Term="RepStartClient method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepStartClient method" /><MSHelp:Keyword Index="F" Term="RepStartClient" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepStartClient" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepStartClient" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepStartClient Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_FastStats" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="BTreeDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassFastStatsTopic" /><MSHelp:Keyword Index="K" Term="FastStats method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.FastStats method" /><MSHelp:Keyword Index="F" Term="FastStats" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.FastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Snapshot Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RecnoDatabaseConfig_Snapshot" /><meta name="guid" content="F_BerkeleyDB_RecnoDatabaseConfig_Snapshot" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RecnoDatabaseConfig.Snapshot" /><MSHelp:TOCTitle Title="Snapshot Field" /><MSHelp:RLTitle Title="RecnoDatabaseConfig.Snapshot Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RecnoDatabaseConfig.Snapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassSnapshotTopic" /><MSHelp:Keyword Index="K" Term="Snapshot field" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.Snapshot field" /><MSHelp:Keyword Index="F" Term="Snapshot" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.Snapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.Snapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.Snapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, any file will be read in its entirety when is called. If false, may be read lazily." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig..::.Snapshot Field</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepFullElectionTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepFullElectionTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepFullElectionTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepFullElectionTimeout" /><MSHelp:TOCTitle Title="RepFullElectionTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepFullElectionTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.RepFullElectionTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepFullElectionTimeoutTopic" /><MSHelp:Keyword Index="K" Term="RepFullElectionTimeout property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepFullElectionTimeout property" /><MSHelp:Keyword Index="F" Term="RepFullElectionTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepFullElectionTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepFullElectionTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepFullElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepFullElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_RepFullElectionTimeout" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An optional configuration timeout period to wait for full election participation the first time the replication group finds a master. By default this option is turned off and normal election timeouts ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepFullElectionTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeDatabase Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BTreeDatabase" /><meta name="guid" content="T_BerkeleyDB_BTreeDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BTreeDatabase" /><MSHelp:TOCTitle Title="BTreeDatabase Class" /><MSHelp:RLTitle Title="BTreeDatabase Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BTreeDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabase class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeDatabase class" /><MSHelp:Keyword Index="K" Term="BTreeDatabase class, about BTreeDatabase class" /><MSHelp:Keyword Index="F" Term="BTreeDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing a BTreeDatabase. The Btree format is a representation of a sorted, balanced tree structure." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ClientServiceRequests Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_ClientServiceRequests" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_ClientServiceRequests" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.ClientServiceRequests" /><MSHelp:TOCTitle Title="ClientServiceRequests Property " /><MSHelp:RLTitle Title="ReplicationStats.ClientServiceRequests Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.ClientServiceRequests" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassClientServiceRequestsTopic" /><MSHelp:Keyword Index="K" Term="ClientServiceRequests property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.ClientServiceRequests property" /><MSHelp:Keyword Index="F" Term="ClientServiceRequests" /><MSHelp:Keyword Index="F" Term="ReplicationStats.ClientServiceRequests" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.ClientServiceRequests" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.ClientServiceRequests" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_ClientServiceRequests" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of client service requests received by this client." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.ClientServiceRequests Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry), Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_Cursor_MoveMultipleKey_4" /><meta name="guid"
content="M_BerkeleyDB_Cursor_MoveMultipleKey_4" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.Databas
eEntry,BerkeleyDB.DatabaseEntry},System.Boolean)"
/><MSHelp:TOCTitle Title="MoveMultipleKey Method (KeyValuePair(DatabaseEntry, DatabaseEntry),
Boolean)" /><MSHelp:RLTitle Title="Cursor.MoveMultipleKey Method (KeyValuePair(DatabaseEntry,
DatabaseEntry), Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.MoveMultipleKey(System.Collections.Generic.KeyValuePair{BerkeleyDB.Database
Entry,BerkeleyDB.DatabaseEntry},System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor
to the specified key/data
pair of the database, and store that key/data pair and as many ensuing key/data pairs that can fit in a buffer the size
of one database page in . The curso ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveMultipleKey Method (KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>), Boolean)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Overwrite Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Overwrite" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Overwrite" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Overwrite" /><MSHelp:TOCTitle Title="Overwrite Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Overwrite Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Overwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassOverwriteTopic" /><MSHelp:Keyword Index="K" Term="Overwrite field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Overwrite field" /><MSHelp:Keyword Index="F" Term="Overwrite" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.Overwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.Overwrite" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.Overwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, overwrite files stored in encrypted formats before deleting them." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.Overwrite Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">

</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_ReplicationConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_ReplicationConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.ReplicationConfig" /><MSHelp:TOCTitle Title="ReplicationConfig Properties " /><MSHelp:RLTitle Title="ReplicationConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.ReplicationConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="ReplicationConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"

type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashComparison Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_HashDatabaseConfig_HashComparison" /><meta name="guid" content="F_BerkeleyDB_HashDatabaseConfig_HashComparison" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.HashDatabaseConfig.HashComparison" /><MSHelp:TOCTitle Title="HashComparison Field" /><MSHelp:RLTitle Title="HashDatabaseConfig.HashComparison Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.HashDatabaseConfig.HashComparison" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassHashComparisonTopic" /><MSHelp:Keyword Index="K" Term="HashComparison field" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.HashComparison field" /><MSHelp:Keyword Index="F" Term="HashComparison" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.HashComparison" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.HashComparison" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.HashComparison" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Hash key comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..::.HashComparison Field</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Refresh_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_Refresh_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="Refresh Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.Refresh
Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Refresh(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers in . If either the key or the data is partial , its bytes starting bytes from the beginning of the retrieved data reco ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Refresh Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Syncs Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_Syncs" /><meta name="guid" content="P_BerkeleyDB_LogStats_Syncs" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.Syncs" /><MSHelp:TOCTitle Title="Syncs Property " /><MSHelp:RLTitle Title="LogStats.Syncs Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.Syncs" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassSyncsTopic" /><MSHelp:Keyword Index="K" Term="Syncs property" /><MSHelp:Keyword Index="K" Term="LogStats.Syncs property" /><MSHelp:Keyword Index="F" Term="Syncs" /><MSHelp:Keyword Index="F" Term="LogStats.Syncs" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.Syncs" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.Syncs" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_Syncs" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Total syncs to the log." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.Syncs Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel"

for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Database_Exists" /><meta name="guid" content="Overload_BerkeleyDB_Database_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Database.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="Database.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Database.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="Database.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="Database.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Database.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"

src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_DatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_DatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.DatabaseConfig" /><MSHelp:TOCTitle Title="DatabaseConfig Methods " /><MSHelp:RLTitle Title="DatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.DatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delimiter Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" />
<script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoDatabaseConfig_Delimiter" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabaseConfig_Delimiter" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabaseConfig.Delimiter" /><MSHelp:TOCTitle Title="Delimiter Property " /><MSHelp:RLTitle Title="RecnoDatabaseConfig.Delimiter Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabaseConfig.Delimiter" />
<MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassDelimiterTopic" /><MSHelp:Keyword Index="K" Term="Delimiter property" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.Delimiter property" /><MSHelp:Keyword Index="F" Term="Delimiter" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.Delimiter" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.Delimiter" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.Delimiter" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.get_Delimiter" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.set_Delimiter" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The delimiting byte used to mark the end of a record in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;

height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabaseConfig..::.Delimiter Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>toArray Method (ByteOrder)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_HeapRecordId_toArray_1" /><meta name="guid" content="M_BerkeleyDB_HeapRecordId_toArray_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HeapRecordId.toArray(BerkeleyDB.ByteOrder)" /><MSHelp:TOCTitle Title="toArray Method (ByteOrder)" /><MSHelp:RLTitle Title="HeapRecordId.toArray Method (ByteOrder) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HeapRecordId.toArray(BerkeleyDB.ByteOrder)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.toArray" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return a byte array representing this record id." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.toArray Method

(ByteOrder)</td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeCompressDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_BTreeCompressDelegate" /><meta name="guid" content="T_BerkeleyDB_BTreeCompressDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.BTreeCompressDelegate"
/><MSHelp:TOCTitle Title="BTreeCompressDelegate Delegate" /><MSHelp:RLTitle Title="BTreeCompressDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.BTreeCompressDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCompressDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="BTreeCompressDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeCompressDelegate delegate" /><MSHelp:Keyword Index="F" Term="BTreeCompressDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCompressDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCompressDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCompressDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCompressDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCompressDelegate.BeginInvoke"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCompressDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function to store a compressed key/data pair into a supplied buffer." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCompressDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetThreadNameDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_SetThreadNameDelegate" /><meta name="guid" content="T_BerkeleyDB_SetThreadNameDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.SetThreadNameDelegate" /><MSHelp:TOCTitle Title="SetThreadNameDelegate Delegate" /><MSHelp:RLTitle Title="SetThreadNameDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.SetThreadNameDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSetThreadNameDelegateClassTopic" /><MSHelp:Keyword Index="K" Term="SetThreadNameDelegate delegate" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SetThreadNameDelegate delegate" /><MSHelp:Keyword Index="F"

Term="SetThreadNameDelegate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SetThreadNameDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadNameDelegate" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadNameDelegate.ctor" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadNameDelegate.Invoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadNameDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SetThreadNameDelegate.EndInvoke" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A function which returns an identifier pair for a thread of control formatted for display." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic
</nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">SetThreadNameDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CreatePolicy Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_CreatePolicy" /><meta name="guid" content="T_BerkeleyDB_CreatePolicy" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.CreatePolicy" /><MSHelp:TOCTitle Title="CreatePolicy Enumeration" /><MSHelp:RLTitle Title="CreatePolicy Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.CreatePolicy" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CreatePolicy.NEVER" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CreatePolicy.IF_NEEDED" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CreatePolicy.ALWAYS" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCreatePolicyClassTopic" /><MSHelp:Keyword Index="K" Term="CreatePolicy enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CreatePolicy enumeration" /><MSHelp:Keyword Index="K" Term="NEVER enumeration member" /><MSHelp:Keyword Index="K" Term="IF_NEEDED enumeration member" /><MSHelp:Keyword Index="K" Term="ALWAYS enumeration member" /><MSHelp:Keyword Index="F" Term="CreatePolicy" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CreatePolicy" /><MSHelp:Keyword Index="F" Term="CreatePolicy.NEVER" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CreatePolicy.NEVER" /><MSHelp:Keyword Index="F" Term="CreatePolicy.IF_NEEDED" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CreatePolicy.IF_NEEDED" /><MSHelp:Keyword Index="F" Term="CreatePolicy.ALWAYS" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CreatePolicy.ALWAYS" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CreatePolicy" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CreatePolicy.NEVER" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CreatePolicy.IF_NEEDED" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CreatePolicy.ALWAYS" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CreatePolicy Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUniqueMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="Overload_BerkeleyDB_HashCursor_MoveNextUniqueMultipleKey" /><meta name="guid"
content="Overload_BerkeleyDB_HashCursor_MoveNextUniqueMultipleKey" /><xml><MSHelp:Attr
Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextUniqueMultipleKey"
/><MSHelp:TOCTitle Title="MoveNextUniqueMultipleKey Method " /><MSHelp:RLTitle
Title="HashCursor.MoveNextUniqueMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.HashCursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHashCursorClassMoveNextUniqueMultipleKeyTopic" /><MSHelp:Keyword Index="K"
Term="MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="K"
Term="HashCursor.MoveNextUniqueMultipleKey method" /><MSHelp:Keyword Index="F"
Term="MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F"
Term="HashCursor.MoveNextUniqueMultipleKey" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HashCursor.MoveNextUniqueMultipleKey" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"><img id="memberOptionsDropdownImage" src="../icons/dropdown.gif"
/> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextUniqueMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BadGenerationMessages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_BadGenerationMessages" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_BadGenerationMessages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.BadGenerationMessages" /><MSHelp:TOCTitle Title="BadGenerationMessages Property " /><MSHelp:RLTitle Title="ReplicationStats.BadGenerationMessages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.BadGenerationMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassBadGenerationMessagesTopic" /><MSHelp:Keyword Index="K" Term="BadGenerationMessages property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.BadGenerationMessages property" /><MSHelp:Keyword Index="F" Term="BadGenerationMessages" /><MSHelp:Keyword Index="F" Term="ReplicationStats.BadGenerationMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.BadGenerationMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.BadGenerationMessages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_BadGenerationMessages" /><MSHelp:Attr

Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Messages with a bad generation #." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.BadGenerationMessages Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"

CONTENT="history" /><title>SecondaryBTreeDatabaseConfig Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabaseConfig Properties " /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigPropertiesTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BeginCDSGroup Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_BeginCDSGroup" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_BeginCDSGroup" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.BeginCDSGroup" /><MSHelp:TOCTitle Title="BeginCDSGroup Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.BeginCDSGroup Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.BeginCDSGroup" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBeginCDSGroupTopic" /><MSHelp:Keyword Index="K" Term="BeginCDSGroup method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.BeginCDSGroup method" /><MSHelp:Keyword Index="F" Term="BeginCDSGroup" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.BeginCDSGroup" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.BeginCDSGroup" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.BeginCDSGroup" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"

/><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Allocate a locker ID in an environment configured for Berkeley DB Concurrent Data Store applications."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0">
<label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.::.BeginCDSGroup Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>RepHoldElection Method (UInt32, UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepHoldElection_2" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepHoldElection_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepHoldElection(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="RepHoldElection Method (UInt32, UInt32)" /><MSHelp:RLTitle Title="DatabaseEnvironment.RepHoldElection Method (UInt32, UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepHoldElection(System.UInt32,System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepHoldElection" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Hold an election for the master of a replication group." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepHoldElection Method (UInt32, UInt32)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, SecondaryBTreeDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryBTreeDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, SecondaryBTreeDatabaseConfig)" /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Open Method (String, String, SecondaryBTreeDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryBTreeDatabase.Open(System.String,System.String,BerkeleyDB.SecondaryBTreeDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryBTreeDatabase object, open the database represented by and associate the database with the primary index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Open Method (String, String, SecondaryBTreeDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxInUse Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_MaxInUse" /><meta name="guid" content="P_BerkeleyDB_MutexStats_MaxInUse" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.MaxInUse" /><MSHelp:TOCTitle Title="MaxInUse Property " /><MSHelp:RLTitle Title="MutexStats.MaxInUse Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.MutexStats.MaxInUse" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassMaxInUseTopic" /><MSHelp:Keyword Index="K" Term="MaxInUse property" /><MSHelp:Keyword Index="K" Term="MutexStats.MaxInUse property" /><MSHelp:Keyword Index="F" Term="MaxInUse" /><MSHelp:Keyword Index="F" Term="MutexStats.MaxInUse" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.MaxInUse" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.MaxInUse" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_MaxInUse" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum mutexes ever in use" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats.<span

class="vb">.<span
class="cpp">::.MaxInUse Property </td></tr><tr
id="headerTableRow3"><td align="left">MutexStats Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Rename Method
(String, String, String, DatabaseEnvironment)</title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Rename_3" /><meta
name="guid" content="M_BerkeleyDB_BaseDatabase_Rename_3" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String,System.String,BerkeleyDB.DatabaseE
nvironment)" /><MSHelp:TOCTitle Title="Rename Method (String, String, String, DatabaseEnvironment)"
/><MSHelp:RLTitle Title="BaseDatabase.Rename Method (String,
String, String, DatabaseEnvironment) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String,System.String,BerkeleyDB.DatabaseEn
vironment)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Rename"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Rename the database specified by and ." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)"
tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label> <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Rename Method (String, String, String, DatabaseEnvironment)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_HeapDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_HeapDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.HeapDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="HeapDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.HeapDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"

/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultiple" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:TOCTitle Title="MoveNextMultiple Method " /><MSHelp:RLTitle Title="Cursor.MoveNextMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultiple is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many duplicate data items t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RecnoDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_RecnoDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RecnoDatabase" /><MSHelp:TOCTitle Title="RecnoDatabase Methods " /><MSHelp:RLTitle Title="RecnoDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RecnoDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="RecnoDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnTimeoutLength Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script
type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_TxnTimeoutLength" /><meta
name="guid" content="P_BerkeleyDB_LockStats_TxnTimeoutLength" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LockStats.TxnTimeoutLength" /><MSHelp:TOCTitle Title="TxnTimeoutLength Property "
/><MSHelp:RLTitle Title="LockStats.TxnTimeoutLength Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.LockStats.TxnTimeoutLength" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockStatsClassTxnTimeoutLengthTopic" /><MSHelp:Keyword Index="K"
Term="TxnTimeoutLength property" /><MSHelp:Keyword Index="K" Term="LockStats.TxnTimeoutLength
property" /><MSHelp:Keyword
Index="F" Term="TxnTimeoutLength" /><MSHelp:Keyword Index="F" Term="LockStats.TxnTimeoutLength"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.TxnTimeoutLength" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.TxnTimeoutLength" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockStats.get_TxnTimeoutLength" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Transaction timeout." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input

id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.TxnTimeoutLength Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseCDB Field</title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseCDB" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseCDB" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseCDB" /><MSHelp:TOCTitle Title="UseCDB Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseCDB Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseCDB" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseCDBTopic" /><MSHelp:Keyword Index="K" Term="UseCDB field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.UseCDB field" /><MSHelp:Keyword Index="F" Term="UseCDB" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.UseCDB" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.UseCDB" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseCDB" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, initialize locking for the Berkeley DB Concurrent Data Store product." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseCDB Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapRecordId_PageNumber" /><meta name="guid" content="P_BerkeleyDB_HeapRecordId_PageNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapRecordId.PageNumber" /><MSHelp:TOCTitle Title="PageNumber Property " /><MSHelp:RLTitle Title="HeapRecordId.PageNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapRecordId.PageNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapRecordIdClassPageNumberTopic" /><MSHelp:Keyword Index="K" Term="PageNumber property" /><MSHelp:Keyword Index="K" Term="HeapRecordId.PageNumber property" /><MSHelp:Keyword Index="F" Term="PageNumber" /><MSHelp:Keyword Index="F" Term="HeapRecordId.PageNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapRecordId.PageNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.PageNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.get_PageNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapRecordId.set_PageNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database page number where the record is stored." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapRecordId..::.PageNumber Property </td></tr><tr id="headerTableRow3"><td align="left">HeapRecordId Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoWait Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_TransactionConfig_NoWait" /><meta name="guid"
content="F_BerkeleyDB_TransactionConfig_NoWait" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.TransactionConfig.NoWait" /><MSHelp:TOCTitle Title="NoWait Field"
/><MSHelp:RLTitle Title="TransactionConfig.NoWait Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.TransactionConfig.NoWait" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionConfigClassNoWaitTopic" /><MSHelp:Keyword Index="K" Term="NoWait
field" /><MSHelp:Keyword Index="K" Term="TransactionConfig.NoWait field" /><MSHelp:Keyword Index="F"
Term="NoWait" /><MSHelp:Keyword Index="F" Term="TransactionConfig.NoWait" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.TransactionConfig.NoWait" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.TransactionConfig.NoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true and a lock
is unavailable for any Berkeley DB operation performed in the context of a transaction, cause the operation to throw
a (or if configured with)." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig..::.NoWait Field</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Write Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_IBackup_Write" /><meta name="guid" content="M_BerkeleyDB_IBackup_Write" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.IBackup.Write(System.Byte[],System.Int64,System.Int32)" /><MSHelp:TOCTitle Title="Write Method " /><MSHelp:RLTitle Title="IBackup.Write Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.IBackup.Write(System.Byte[],System.Int64,System.Int32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBIBackupClassWriteTopic" /><MSHelp:Keyword Index="K" Term="Write method" /><MSHelp:Keyword Index="K" Term="IBackup.Write method" /><MSHelp:Keyword Index="F" Term="Write" /><MSHelp:Keyword Index="F" Term="IBackup.Write" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.IBackup.Write" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.IBackup.Write" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Called when writing data during a backup." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">IBackup..::.Write Method </td></tr><tr id="headerTableRow3"><td align="left">IBackup Interface See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyExistException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_KeyExistException" /><meta name="guid" content="Fields_T_BerkeleyDB_KeyExistException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.KeyExistException" /><MSHelp:TOCTitle Title="KeyExistException Fields"

/><MSHelp:RLTitle Title="KeyExistException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.KeyExistException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBKeyExistExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="KeyExistException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"

/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyExistException Fields</td></tr><tr id="headerTableRow3"><td align="left">KeyExistException Class <a href="#seeAlsoToggle"
 onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
 </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_BTreeStats" /><meta name="guid" content="Methods_T_BerkeleyDB_BTreeStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.BTreeStats" /><MSHelp:TOCTitle Title="BTreeStats Methods " /><MSHelp:RLTitle Title="BTreeStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.BTreeStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="BTreeStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
 Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
 image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats Methods </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegisteredSitesNeeded Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="P_BerkeleyDB_ReplicationStats_RegisteredSitesNeeded" /><meta
name="guid" content="P_BerkeleyDB_ReplicationStats_RegisteredSitesNeeded" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.RegisteredSitesNeeded" /><MSHelp:TOCTitle
Title="RegisteredSitesNeeded Property " /><MSHelp:RLTitle Title="ReplicationStats.RegisteredSitesNeeded
Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.ReplicationStats.RegisteredSitesNeeded" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBReplicationStatsClassRegisteredSitesNeededTopic" /><MSHelp:Keyword Index="K"
Term="RegisteredSitesNeeded property" /><MSHelp:Keyword Index="K"
Term="ReplicationStats.RegisteredSitesNeeded property" /><MSHelp:Keyword Index="F"
Term="RegisteredSitesNeeded" /><MSHelp:Keyword Index="F" Term="ReplicationStats.RegisteredSitesNeeded"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.RegisteredSitesNeeded" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationStats.RegisteredSitesNeeded" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationStats.get_RegisteredSitesNeeded" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="# of "registered voters" needed." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage"
style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.RegisteredSitesNeeded Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>isPeer Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_RepMgrSite_isPeer" /><meta name="guid" content="F_BerkeleyDB_RepMgrSite_isPeer" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.RepMgrSite.isPeer" /><MSHelp:TOCTitle Title="isPeer Field" /><MSHelp:RLTitle Title="RepMgrSite.isPeer Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.RepMgrSite.isPeer" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrSiteClassisPeerTopic" /><MSHelp:Keyword Index="K" Term="isPeer field" /><MSHelp:Keyword Index="K" Term="RepMgrSite.isPeer field" /><MSHelp:Keyword Index="F" Term="isPeer" /><MSHelp:Keyword Index="F" Term="RepMgrSite.isPeer" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrSite.isPeer" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrSite.isPeer" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the site is client-to-client peer." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrSite..::.isPeer Field</td></tr><tr id="headerTableRow3"><td align="left">RepMgrSite Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_MoveNextMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_MoveNextMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.MoveNextMultipleKey" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method " /><MSHelp:RLTitle Title="BTreeCursor.MoveNextMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBBTreeCursorClassMoveNextMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextMultipleKey method" /><MSHelp:Keyword Index="K" Term="BTreeCursor.MoveNextMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="BTreeCursor.MoveNextMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"

/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveNextMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MPoolFileStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MPoolFileStats" /><meta name="guid" content="T_BerkeleyDB_MPoolFileStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MPoolFileStats" /><MSHelp:TOCTitle Title="MPoolFileStats Class" /><MSHelp:RLTitle Title="MPoolFileStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MPoolFileStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassTopic" /><MSHelp:Keyword Index="K" Term="MPoolFileStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MPoolFileStats class" /><MSHelp:Keyword Index="K" Term="MPoolFileStats class, about MPoolFileStats class" /><MSHelp:Keyword Index="F" Term="MPoolFileStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about a file in the memory pool" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationTransportDelegate Delegate</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_ReplicationTransportDelegate" /><meta name="guid" content="T_BerkeleyDB_ReplicationTransportDelegate" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.ReplicationTransportDelegate" /><MSHelp:TOCTitle Title="ReplicationTransportDelegate Delegate" /><MSHelp:RLTitle Title="ReplicationTransportDelegate Delegate (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.ReplicationTransportDelegate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationTransportDelegateClassTopic" /><MSHelp:Keyword Index="K"

Term="ReplicationTransportDelegate delegate" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.ReplicationTransportDelegate delegate" /><MSHelp:Keyword Index="F"
Term="ReplicationTransportDelegate" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ReplicationTransportDelegate" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationTransportDelegate" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationTransportDelegate.ctor" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationTransportDelegate.Invoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationTransportDelegate.BeginInvoke" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ReplicationTransportDelegate.EndInvoke"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The function used to transmit data using the replication application's
communication infrastructure." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationTransportDelegate Delegate</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NotFoundException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_NotFoundException" /><meta name="guid" content="Methods_T_BerkeleyDB_NotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.NotFoundException" /><MSHelp:TOCTitle Title="NotFoundException Methods " /><MSHelp:RLTitle Title="NotFoundException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.NotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBNotFoundExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="NotFoundException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label

id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">NotFoundException Methods </td></tr><tr
id="headerTableRow3"><td align="left">NotFoundException
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>isConnected
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_RepMgrSite_isConnected" /><meta name="guid"
content="F_BerkeleyDB_RepMgrSite_isConnected" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.RepMgrSite.isConnected" /><MSHelp:TOCTitle Title="isConnected Field"
/><MSHelp:RLTitle
Title="RepMgrSite.isConnected Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.RepMgrSite.isConnected" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBRepMgrSiteClassisConnectedTopic" /><MSHelp:Keyword Index="K" Term="isConnected field" /><MSHelp:Keyword Index="K" Term="RepMgrSite.isConnected field" /><MSHelp:Keyword Index="F" Term="isConnected" /><MSHelp:Keyword Index="F" Term="RepMgrSite.isConnected" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrSite.isConnected" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrSite.isConnected" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the site is connected." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrSite..::.isConnected Field</td></tr><tr id="headerTableRow3"><td align="left">RepMgrSite Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintFastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_PrintFastStats" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_PrintFastStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.PrintFastStats" /><MSHelp:TOCTitle Title="PrintFastStats Method " /><MSHelp:RLTitle Title="RecnoDatabase.PrintFastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.PrintFastStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassPrintFastStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintFastStats method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.PrintFastStats method" /><MSHelp:Keyword Index="F" Term="PrintFastStats" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.PrintFastStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.PrintFastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.PrintFastStats Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoDatabaseConfig_Length" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabaseConfig_Length" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabaseConfig.Length" /><MSHelp:TOCTitle Title="Length Property " /><MSHelp:RLTitle Title="RecnoDatabaseConfig.Length Property (BerkeleyDB)"

/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabaseConfig.Length" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseConfigClassLengthTopic" /><MSHelp:Keyword Index="K" Term="Length property" /><MSHelp:Keyword Index="K" Term="RecnoDatabaseConfig.Length property" /><MSHelp:Keyword Index="F" Term="Length" /><MSHelp:Keyword Index="F" Term="RecnoDatabaseConfig.Length" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabaseConfig.Length" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.get_Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabaseConfig.set_Length" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify that the records are fixed-length, not byte-delimited, and are of length Length." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">RecnoDatabaseConfig..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_Move" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_Move" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.Move" /><MSHelp:TOCTitle Title="Move Method " /><MSHelp:RLTitle Title="Cursor.Move Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.Move" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveTopic" /><MSHelp:Keyword Index="K" Term="Move method" /><MSHelp:Keyword Index="K" Term="Cursor.Move method" /><MSHelp:Keyword Index="F" Term="Move" /><MSHelp:Keyword Index="F" Term="Cursor.Move" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"

/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Move Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Sequence_Get" /><meta name="guid" content="Overload_BerkeleyDB_Sequence_Get" /><xml><MSHelp:Attr Name="AssetID"

Value="Overload:BerkeleyDB.Sequence.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="Sequence.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Sequence.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="Sequence.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="Sequence.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Sequence.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryDatabase_SecondaryCursor" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryDatabase_SecondaryCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:TOCTitle Title="SecondaryCursor Method " /><MSHelp:RLTitle Title="SecondaryDatabase.SecondaryCursor Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseClassSecondaryCursorTopic" /><MSHelp:Keyword Index="K" Term="SecondaryCursor method" /><MSHelp:Keyword Index="K" Term="SecondaryDatabase.SecondaryCursor method" /><MSHelp:Keyword Index="F" Term="SecondaryCursor" /><MSHelp:Keyword Index="F" Term="SecondaryDatabase.SecondaryCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage"

style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.SecondaryCursor Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ALL_AVAILABLE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_AckPolicy_ALL_AVAILABLE" /><meta name="guid" content="F_BerkeleyDB_AckPolicy_ALL_AVAILABLE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.AckPolicy.ALL_AVAILABLE" /><MSHelp:TOCTitle Title="ALL_AVAILABLE Field" /><MSHelp:RLTitle Title="AckPolicy.ALL_AVAILABLE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.AckPolicy.ALL_AVAILABLE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBAckPolicyClassALL_AVAILABLETopic" /><MSHelp:Keyword Index="K" Term="ALL_AVAILABLE field" /><MSHelp:Keyword Index="K" Term="AckPolicy.ALL_AVAILABLE field" /><MSHelp:Keyword Index="F" Term="ALL_AVAILABLE" /><MSHelp:Keyword Index="F" Term="AckPolicy.ALL_AVAILABLE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.AckPolicy.ALL_AVAILABLE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.AckPolicy.ALL_AVAILABLE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The master should wait until all currently connected replication clients have acknowledged each permanent replication message." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">AckPolicy<span
class="cs">..::<span
class="nu">.ALL_AVAILABLE Field</td></tr><tr id="headerTableRow3"><td
align="left">AckPolicy Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingConfig
Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LockingConfig" /><meta
name="guid" content="AllMembers_T_BerkeleyDB_LockingConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="AllMembers.T:BerkeleyDB.LockingConfig" /><MSHelp:TOCTitle Title="LockingConfig Members"
/><MSHelp:RLTitle Title="LockingConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="AllMembers.T:BerkeleyDB.LockingConfig" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBLockingConfigMembersTopic" /><MSHelp:Keyword Index="K"
Term="LockingConfig class" /><MSHelp:Keyword Index="K" Term="LockingConfig class, all members"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockingConfig class" /><MSHelp:Keyword Index="F"
Term="LockingConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig" /><MSHelp:Attr
Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label>
 <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig Members</td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verbosity Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_Verbosity" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_Verbosity" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.Verbosity" /><MSHelp:TOCTitle Title="Verbosity Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.Verbosity Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.Verbosity" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassVerbosityTopic" /><MSHelp:Keyword Index="K" Term="Verbosity property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Verbosity property" /><MSHelp:Keyword Index="F" Term="Verbosity" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Verbosity" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Verbosity" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Verbosity" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_Verbosity" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_Verbosity" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specific additional informational and debugging messages in the Berkeley DB message output." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>

   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Verbosity Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CleanPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_CleanPages" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_CleanPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.CleanPages" /><MSHelp:TOCTitle Title="CleanPages Property " /><MSHelp:RLTitle Title="MPoolStats.CleanPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.CleanPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassCleanPagesTopic" /><MSHelp:Keyword Index="K" Term="CleanPages property" /><MSHelp:Keyword Index="K" Term="MPoolStats.CleanPages property" /><MSHelp:Keyword Index="F" Term="CleanPages" /><MSHelp:Keyword Index="F" Term="MPoolStats.CleanPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.CleanPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.CleanPages" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.MPoolStats.get_CleanPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Clean pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.CleanPages Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_2" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNextDuplicate_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNextDuplicate(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store the secondary key and primary ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNextDuplicate Method (DatabaseEntry, DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction, Isolation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_FastStats_2" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_FastStats_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction, Isolation)" /><MSHelp:RLTitle Title="RecnoDatabase.FastStats Method (Transaction, Isolation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.FastStats(BerkeleyDB.Transaction,BerkeleyDB.Isolation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.FastStats Method (Transaction, Isolation)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeCursor Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_BTreeCursor" /><meta name="guid" content="Methods_T_BerkeleyDB_BTreeCursor" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.BTreeCursor" /><MSHelp:TOCTitle Title="BTreeCursor Methods " /><MSHelp:RLTitle Title="BTreeCursor Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.BTreeCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorMethodsTopic" /><MSHelp:Keyword Index="K" Term="BTreeCursor class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"

data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor Methods </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BadSecondaryException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_BadSecondaryException" /><meta name="guid" content="Methods_T_BerkeleyDB_BadSecondaryException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.BadSecondaryException" /><MSHelp:TOCTitle Title="BadSecondaryException Methods " /><MSHelp:RLTitle Title="BadSecondaryException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.BadSecondaryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBadSecondaryExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="BadSecondaryException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
 class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All
 </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
 for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BadSecondaryException Methods </td></tr><tr id="headerTableRow3"><td align="left">BadSecondaryException Class See
 Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryCursor Method (Transaction)</title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabase_SecondaryCursor_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="SecondaryCursor Method (Transaction)" /><MSHelp:RLTitle Title="SecondaryDatabase.SecondaryCursor Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabase.SecondaryCursor(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabase.SecondaryCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected secondary database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabase..::.SecondaryCursor Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Open" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryBTreeDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:TOCTitle Title="Open Method " /><MSHelp:RLTitle Title="SecondaryBTreeDatabase.Open Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseClassOpenTopic" /><MSHelp:Keyword Index="K" Term="Open method" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabase.Open method" /><MSHelp:Keyword Index="F" Term="Open" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabase.Open" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.SecondaryBTreeDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabase..::.Open Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabase
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockNotGrantedException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script
type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_LockNotGrantedException" /><meta name="guid" content="Fields_T_BerkeleyDB_LockNotGrantedException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:TOCTitle Title="LockNotGrantedException Fields" /><MSHelp:RLTitle Title="LockNotGrantedException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.LockNotGrantedException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockNotGrantedExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="LockNotGrantedException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input

id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockNotGrantedException Fields</td></tr><tr id="headerTableRow3"><td align="left">LockNotGrantedException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TxnNoSync Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnNoSync" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_TxnNoSync" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnNoSync" /><MSHelp:TOCTitle Title="TxnNoSync Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.TxnNoSync Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.TxnNoSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassTxnNoSyncTopic" /><MSHelp:Keyword Index="K" Term="TxnNoSync field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.TxnNoSync field" /><MSHelp:Keyword Index="F" Term="TxnNoSync" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.TxnNoSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.TxnNoSync" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.TxnNoSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will not write or synchronously flush the log on transaction commit." /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.TxnNoSync Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironmentConfig.htm">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PadByte Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_SecondaryRecnoDatabase_PadByte" /><meta name="guid"
content="P_BerkeleyDB_SecondaryRecnoDatabase_PadByte" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.SecondaryRecnoDatabase.PadByte" /><MSHelp:TOCTitle Title="PadByte Property "
/><MSHelp:RLTitle Title="SecondaryRecnoDatabase.PadByte Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabase.PadByte" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassPadByteTopic" /><MSHelp:Keyword Index="K"
Term="PadByte property" /><MSHelp:Keyword
Index="K" Term="SecondaryRecnoDatabase.PadByte property" /><MSHelp:Keyword Index="F"
Term="PadByte" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.PadByte"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.PadByte" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.PadByte" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.get_PadByte" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The padding character for short, fixed-length records." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.PadByte Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Exists" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0; width:0;"

src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultipleKey Method (UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32)" /><MSHelp:TOCTitle Title="MoveMultipleKey Method (UInt32)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultipleKey Method (UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultipleKey(System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.MoveMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair and as many ensuing key/data pairs that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultipleKey Method (UInt32)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PutNoOverwrite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_PutNoOverwrite" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_PutNoOverwrite" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.PutNoOverwrite" /><MSHelp:TOCTitle Title="PutNoOverwrite Method " /><MSHelp:RLTitle Title="HeapDatabase.PutNoOverwrite Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassPutNoOverwriteTopic" /><MSHelp:Keyword Index="K" Term="PutNoOverwrite method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.PutNoOverwrite method" /><MSHelp:Keyword Index="F" Term="PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="HeapDatabase.PutNoOverwrite" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.PutNoOverwrite" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.PutNoOverwrite Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_MutexStats" /><meta name="guid" content="Methods_T_BerkeleyDB_MutexStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.MutexStats" /><MSHelp:TOCTitle Title="MutexStats Methods " /><MSHelp:RLTitle Title="MutexStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.MutexStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="MutexStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats Methods </td></tr><tr id="headerTableRow3"><td align="left">MutexStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicate Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicate_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicate_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNextDuplicate Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicate Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicate(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the

current key/data pair, move the cursor to the next key/data pair in the database, and store that pair in . MoveNextDupli ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicate Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_OLD_VERSION Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"

/><link rel="stylesheet" type="text/css"
href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="F_BerkeleyDB_ErrorCodes_DB_OLD_VERSION" /><meta name="guid"
content="F_BerkeleyDB_ErrorCodes_DB_OLD_VERSION" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.ErrorCodes.DB_OLD_VERSION" /><MSHelp:TOCTitle Title="DB_OLD_VERSION
Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_OLD_VERSION Field (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_OLD_VERSION"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_OLD_VERSIONTopic"
/><MSHelp:Keyword Index="K" Term="DB_OLD_VERSION field" /><MSHelp:Keyword Index="K"
Term="ErrorCodes.DB_OLD_VERSION field" /><MSHelp:Keyword Index="F" Term="DB_OLD_VERSION"
/><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_OLD_VERSION" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ErrorCodes.DB_OLD_VERSION" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.ErrorCodes.DB_OLD_VERSION" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Out-of-date
version." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_OLD_VERSION Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, DatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Open_3" /><meta name="guid" content="M_BerkeleyDB_Database_Open_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Open(System.String,System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, String, DatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="Database.Open Method (String, String, DatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Open(System.String,System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new Database object and open the database represented by and . The file specified by must exist." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Open Method (String, String, DatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_LOCK_NOTGRANTED Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="F_BerkeleyDB_ErrorCodes_DB_LOCK_NOTGRANTED" /><meta name="guid"
content="F_BerkeleyDB_ErrorCodes_DB_LOCK_NOTGRANTED" /><xml><MSHelp:Attr
Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_LOCK_NOTGRANTED" /><MSHelp:TOCTitle
Title="DB_LOCK_NOTGRANTED Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_LOCK_NOTGRANTED
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.ErrorCodes.DB_LOCK_NOTGRANTED" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBErrorCodesClassDB_LOCK_NOTGRANTEDTopic" /><MSHelp:Keyword Index="K"
Term="DB_LOCK_NOTGRANTED field" /><MSHelp:Keyword Index="K"
Term="ErrorCodes.DB_LOCK_NOTGRANTED field" /><MSHelp:Keyword Index="F"
Term="DB_LOCK_NOTGRANTED" /><MSHelp:Keyword Index="F"
Term="ErrorCodes.DB_LOCK_NOTGRANTED" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.ErrorCodes.DB_LOCK_NOTGRANTED" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_LOCK_NOTGRANTED" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Lock unavailable." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_LOCK_NOTGRANTED Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FailedMessages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RepMgrStats_FailedMessages" /><meta name="guid" content="P_BerkeleyDB_RepMgrStats_FailedMessages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RepMgrStats.FailedMessages" /><MSHelp:TOCTitle Title="FailedMessages Property " /><MSHelp:RLTitle Title="RepMgrStats.FailedMessages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RepMgrStats.FailedMessages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepMgrStatsClassFailedMessagesTopic" /><MSHelp:Keyword Index="K" Term="FailedMessages property" /><MSHelp:Keyword Index="K" Term="RepMgrStats.FailedMessages property" /><MSHelp:Keyword Index="F" Term="FailedMessages" /><MSHelp:Keyword Index="F" Term="RepMgrStats.FailedMessages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepMgrStats.FailedMessages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.FailedMessages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepMgrStats.get_FailedMessages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="# of insufficiently ack'ed msgs." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepMgrStats..::.FailedMessages Property </td></tr><tr id="headerTableRow3"><td align="left">RepMgrStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepClockskewSlow Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_RepClockskewSlow" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_RepClockskewSlow" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.RepClockskewSlow" /><MSHelp:TOCTitle Title="RepClockskewSlow Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepClockskewSlow Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="P:BerkeleyDB.DatabaseEnvironment.RepClockskewSlow" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepClockskewSlowTopic" /><MSHelp:Keyword Index="K"
Term="RepClockskewSlow property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepClockskewSlow
property" /><MSHelp:Keyword Index="F" Term="RepClockskewSlow" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepClockskewSlow" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepClockskewSlow" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepClockskewSlow" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_RepClockskewSlow" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The value of the slowest clock in the group of sites." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET

API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepClockskewSlow Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BulkBufferFills Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_BulkBufferFills" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_BulkBufferFills" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.BulkBufferFills" /><MSHelp:TOCTitle Title="BulkBufferFills Property " /><MSHelp:RLTitle Title="ReplicationStats.BulkBufferFills Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.BulkBufferFills" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassBulkBufferFillsTopic" /><MSHelp:Keyword Index="K" Term="BulkBufferFills property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.BulkBufferFills property" /><MSHelp:Keyword Index="F" Term="BulkBufferFills" /><MSHelp:Keyword Index="F" Term="ReplicationStats.BulkBufferFills" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.BulkBufferFills" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.BulkBufferFills" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_BulkBufferFills" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bulk buffer fills." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.BulkBufferFills Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEntry Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_DatabaseEntry" /><meta name="guid" content="AllMembers_T_BerkeleyDB_DatabaseEntry" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.DatabaseEntry" /><MSHelp:TOCTitle Title="DatabaseEntry Members" /><MSHelp:RLTitle Title="DatabaseEntry Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.DatabaseEntry" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEntryMembersTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class" /><MSHelp:Keyword Index="K" Term="DatabaseEntry class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseEntry class" /><MSHelp:Keyword Index="F" Term="DatabaseEntry"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEntry" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"

/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEntry Members</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEntry Class Constructors Methods Properties See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_RefreshMultiple" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_RefreshMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.RefreshMultiple" /><MSHelp:TOCTitle Title="RefreshMultiple Method " /><MSHelp:RLTitle Title="HashCursor.RefreshMultiple Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.RefreshMultiple" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassRefreshMultipleTopic" /><MSHelp:Keyword Index="K" Term="RefreshMultiple method" /><MSHelp:Keyword Index="K" Term="HashCursor.RefreshMultiple method" /><MSHelp:Keyword Index="F" Term="RefreshMultiple"
/><MSHelp:Keyword Index="F" Term="HashCursor.RefreshMultiple" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.RefreshMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.RefreshMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxMutexes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_MutexConfig_MaxMutexes" /><meta name="guid"
content="P_BerkeleyDB_MutexConfig_MaxMutexes" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.MutexConfig.MaxMutexes" /><MSHelp:TOCTitle Title="MaxMutexes Property "
/><MSHelp:RLTitle Title="MutexConfig.MaxMutexes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.MutexConfig.MaxMutexes" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBMutexConfigClassMaxMutexesTopic" /><MSHelp:Keyword Index="K"
Term="MaxMutexes property" /><MSHelp:Keyword Index="K" Term="MutexConfig.MaxMutexes property"
/><MSHelp:Keyword
Index="F" Term="MaxMutexes" /><MSHelp:Keyword Index="F" Term="MutexConfig.MaxMutexes"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig.MaxMutexes" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.MaxMutexes" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.MutexConfig.get_MaxMutexes" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.MutexConfig.set_MaxMutexes" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The total number
of mutexes to allocate." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MutexConfig..::.MaxMutexes Property </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RunRecoveryException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_RunRecoveryException" /><meta name="guid" content="Methods_T_BerkeleyDB_RunRecoveryException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.RunRecoveryException" /><MSHelp:TOCTitle Title="RunRecoveryException Methods " /><MSHelp:RLTitle Title="RunRecoveryException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.RunRecoveryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRunRecoveryExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="RunRecoveryException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="copyHoverImage" style="display:none; height:0;

width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RunRecoveryException Methods </td></tr><tr id="headerTableRow3"><td align="left">RunRecoveryException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_HeapDatabaseConfig_RegionSize" /><meta name="guid"
content="P_BerkeleyDB_HeapDatabaseConfig_RegionSize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.HeapDatabaseConfig.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property "
/><MSHelp:RLTitle Title="HeapDatabaseConfig.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.HeapDatabaseConfig.RegionSize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBHeapDatabaseConfigClassRegionSizeTopic" /><MSHelp:Keyword Index="K"
Term="RegionSize property" /><MSHelp:Keyword Index="K"
Term="HeapDatabaseConfig.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize"
/><MSHelp:Keyword Index="F" Term="HeapDatabaseConfig.RegionSize" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.HeapDatabaseConfig.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapDatabaseConfig.RegionSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapDatabaseConfig.get_RegionSize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.HeapDatabaseConfig.set_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of
pages in a region of the database. If this value is never set, the default region size for
the database's page size will be used. You can set the database page size using . ..." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label

id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextUnique Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_Cursor_MoveNextUnique" /><meta name="guid" content="Overload_BerkeleyDB_Cursor_MoveNextUnique" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:TOCTitle Title="MoveNextUnique Method " /><MSHelp:RLTitle Title="Cursor.MoveNextUnique Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassMoveNextUniqueTopic" /><MSHelp:Keyword Index="K" Term="MoveNextUnique method" /><MSHelp:Keyword Index="K" Term="Cursor.MoveNextUnique method" /><MSHelp:Keyword Index="F" Term="MoveNextUnique" /><MSHelp:Keyword Index="F" Term="Cursor.MoveNextUnique" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.MoveNextUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this,
'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextUnique Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"

xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepmgrSitesConfig Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_RepmgrSitesConfig" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_RepmgrSitesConfig" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.RepmgrSitesConfig" /><MSHelp:TOCTitle Title="RepmgrSitesConfig Field" /><MSHelp:RLTitle Title="ReplicationConfig.RepmgrSitesConfig Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.RepmgrSitesConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassRepmgrSitesConfigTopic" /><MSHelp:Keyword Index="K" Term="RepmgrSitesConfig field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.RepmgrSitesConfig field" /><MSHelp:Keyword Index="F" Term="RepmgrSitesConfig" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.RepmgrSitesConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.RepmgrSitesConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.RepmgrSitesConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A list of site configurations." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.RepmgrSitesConfig Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoWaitDbExclusiveLock Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BaseDatabase_NoWaitDbExclusiveLock" /><meta name="guid" content="P_BerkeleyDB_BaseDatabase_NoWaitDbExclusiveLock" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.NoWaitDbExclusiveLock" /><MSHelp:TOCTitle Title="NoWaitDbExclusiveLock Property " /><MSHelp:RLTitle Title="BaseDatabase.NoWaitDbExclusiveLock Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.NoWaitDbExclusiveLock" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassNoWaitDbExclusiveLockTopic" /><MSHelp:Keyword Index="K" Term="NoWaitDbExclusiveLock property" /><MSHelp:Keyword Index="K" Term="BaseDatabase.NoWaitDbExclusiveLock property" /><MSHelp:Keyword Index="F" Term="NoWaitDbExclusiveLock" /><MSHelp:Keyword Index="F" Term="BaseDatabase.NoWaitDbExclusiveLock" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BaseDatabase.NoWaitDbExclusiveLock" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.NoWaitDbExclusiveLock" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.get_NoWaitDbExclusiveLock" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr

Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, configure the database handle to obtain a write lock on the entire database. When the database is opened it will immediately throw if it cannot obtain the exclusive lock immediately. If F ..." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.NoWaitDbExclusiveLock Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseEnvironmentVars Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_UseEnvironmentVars" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_UseEnvironmentVars" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.UseEnvironmentVars" /><MSHelp:TOCTitle Title="UseEnvironmentVars Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.UseEnvironmentVars Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.UseEnvironmentVars" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassUseEnvironmentVarsTopic" /><MSHelp:Keyword Index="K" Term="UseEnvironmentVars property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.UseEnvironmentVars property" /><MSHelp:Keyword Index="F" Term="UseEnvironmentVars" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.UseEnvironmentVars" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.UseEnvironmentVars" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.UseEnvironmentVars" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_UseEnvironmentVars" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Berkeley DB process' environment may be permitted to specify information to be used when naming files; see Berkeley DB File Naming in the Programmer's Reference Guide for more information." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.UseEnvironmentVars Property </td></tr><tr id="headerTableRow3"><td
align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxTransactions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxTransactions" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxTransactions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxTransactions" /><MSHelp:TOCTitle Title="MaxTransactions Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxTransactions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxTransactions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxTransactionsTopic" /><MSHelp:Keyword Index="K" Term="MaxTransactions property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxTransactions property" /><MSHelp:Keyword Index="F" Term="MaxTransactions" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxTransactions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxTransactions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxTransactions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxTransactions"

/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxTransactions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The number of active transactions supported by the environment. This value bounds the size of the memory allocated for transactions. Child transactions are counted as active until they either commit or ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.MaxTransactions Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RemoveUnusedLogFiles Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_DatabaseEnvironment_RemoveUnusedLogFiles" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_RemoveUnusedLogFiles" /><xml><MSHelp:Attr
Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RemoveUnusedLogFiles" /><MSHelp:TOCTitle
Title="RemoveUnusedLogFiles Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.RemoveUnusedLogFiles Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.DatabaseEnvironment.RemoveUnusedLogFiles" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRemoveUnusedLogFilesTopic" /><MSHelp:Keyword
Index="K" Term="RemoveUnusedLogFiles method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RemoveUnusedLogFiles method" /><MSHelp:Keyword Index="F"
Term="RemoveUnusedLogFiles" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RemoveUnusedLogFiles" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DatabaseEnvironment.RemoveUnusedLogFiles" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RemoveUnusedLogFiles"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Remove log files that are no longer needed. Automatic log file removal
is likely to make catastrophic recovery impossible." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RemoveUnusedLogFiles Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseEnvironment Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DatabaseEnvironment" /><meta name="guid" content="Properties_T_BerkeleyDB_DatabaseEnvironment" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:TOCTitle Title="DatabaseEnvironment Properties " /><MSHelp:RLTitle Title="DatabaseEnvironment Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DatabaseEnvironment" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentPropertiesTopic" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment Properties </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrev_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MovePrev_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MovePrev(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MovePrev Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrev Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MovePrev(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous key/data pair of the database, and store the secondary key and primary key/data pair in ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrev Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TransactionStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_TransactionStats" /><meta name="guid" content="Methods_T_BerkeleyDB_TransactionStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.TransactionStats" /><MSHelp:TOCTitle Title="TransactionStats Methods " /><MSHelp:RLTitle Title="TransactionStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.TransactionStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="TransactionStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel"
for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats Methods </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>TruncateUnusedPages Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB"
/><meta name="file" content="M_BerkeleyDB_RecnoDatabase_TruncateUnusedPages" /><meta name="guid"
content="M_BerkeleyDB_RecnoDatabase_TruncateUnusedPages" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.RecnoDatabase.TruncateUnusedPages" /><MSHelp:TOCTitle
Title="TruncateUnusedPages Method " /><MSHelp:RLTitle Title="RecnoDatabase.TruncateUnusedPages Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.TruncateUnusedPages"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.RecnoDatabase.TruncateUnusedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return pages to
the filesystem that
are already free and at the end of the file." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.TruncateUnusedPages Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LastAllocatedLockerID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_LastAllocatedLockerID" /><meta name="guid" content="P_BerkeleyDB_LockStats_LastAllocatedLockerID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.LastAllocatedLockerID" /><MSHelp:TOCTitle Title="LastAllocatedLockerID Property " /><MSHelp:RLTitle Title="LockStats.LastAllocatedLockerID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.LastAllocatedLockerID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassLastAllocatedLockerIDTopic" /><MSHelp:Keyword Index="K" Term="LastAllocatedLockerID property" /><MSHelp:Keyword Index="K" Term="LockStats.LastAllocatedLockerID property" /><MSHelp:Keyword Index="F" Term="LastAllocatedLockerID" /><MSHelp:Keyword Index="F" Term="LockStats.LastAllocatedLockerID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.LastAllocatedLockerID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.LastAllocatedLockerID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_LastAllocatedLockerID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Last allocated locker ID." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.LastAllocatedLockerID Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Truncate Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Truncate" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Truncate" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Truncate" /><MSHelp:TOCTitle Title="Truncate Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Truncate Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Truncate" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassTruncateTopic" /><MSHelp:Keyword Index="K" Term="Truncate method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Truncate method" /><MSHelp:Keyword Index="F" Term="Truncate" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Truncate" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Truncate" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Truncate Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryCursor_MoveNext" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryCursor_MoveNext" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:TOCTitle Title="MoveNext Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveNext Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryCursorClassMoveNextTopic" /><MSHelp:Keyword Index="K" Term="MoveNext method" /><MSHelp:Keyword Index="K" Term="SecondaryCursor.MoveNext method" /><MSHelp:Keyword Index="F" Term="MoveNext" /><MSHelp:Keyword Index="F" Term="SecondaryCursor.MoveNext" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNext Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DirtyPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_DirtyPages" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_DirtyPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.DirtyPages" /><MSHelp:TOCTitle Title="DirtyPages Property " /><MSHelp:RLTitle Title="MPoolStats.DirtyPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.DirtyPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassDirtyPagesTopic" /><MSHelp:Keyword Index="K" Term="DirtyPages property" /><MSHelp:Keyword
Index="K" Term="MPoolStats.DirtyPages property" /><MSHelp:Keyword Index="F" Term="DirtyPages" /><MSHelp:Keyword Index="F" Term="MPoolStats.DirtyPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.DirtyPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.DirtyPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_DirtyPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Dirty pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label

id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.DirtyPages Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Refresh Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_Refresh_3" /><meta name="guid" content="M_BerkeleyDB_Cursor_Refresh_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.Refresh(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Refresh Method (LockingInfo)" /><MSHelp:RLTitle Title="Cursor.Refresh Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.Refresh(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Refresh" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Store the key/data pair to which the cursor refers in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"

id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox"
data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">Cursor.<span
class="vb">.::.Refresh Method
(LockingInfo)</td></tr><tr
id="headerTableRow3"><td align="left">Cursor Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryDatabaseConfig Properties </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryDatabaseConfig" /><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryDatabaseConfig Properties " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigPropertiesTopic" /><MSHelp:Keyword
Index="K" Term="SecondaryDatabaseConfig class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_QueueDatabase_FastStats" /><meta name="guid" content="M_BerkeleyDB_QueueDatabase_FastStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:TOCTitle Title="FastStats Method " /><MSHelp:RLTitle Title="QueueDatabase.FastStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.FastStats Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>nKeys Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_nKeys" /><meta name="guid" content="P_BerkeleyDB_QueueStats_nKeys" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.nKeys" /><MSHelp:TOCTitle Title="nKeys Property " /><MSHelp:RLTitle

Title="QueueStats.nKeys Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.nKeys" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassnKeysTopic" /><MSHelp:Keyword Index="K" Term="nKeys property" /><MSHelp:Keyword Index="K" Term="QueueStats.nKeys property" /><MSHelp:Keyword Index="F" Term="nKeys" /><MSHelp:Keyword Index="F" Term="QueueStats.nKeys" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.nKeys" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.nKeys" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_nKeys" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of unique keys." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueStats..::.nKeys Property

</td></tr><tr id="headerTableRow3"><td align="left">QueueStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
 xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script
 type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="HashDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="HashDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
 /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
 height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html
xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseRecordNumbers Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_UseRecordNumbers" /><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_UseRecordNumbers" /><xml><MSHelp:Attr

Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:TOCTitle Title="UseRecordNumbers Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.UseRecordNumbers Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassUseRecordNumbersTopic" /><MSHelp:Keyword Index="K" Term="UseRecordNumbers field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.UseRecordNumbers field" /><MSHelp:Keyword Index="F" Term="UseRecordNumbers" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.UseRecordNumbers" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, support retrieval from the Btree using record numbers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig..::.UseRecordNumbers Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:TOCTitle Title="MoveNextMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveNextMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultipleKey is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many ensuing key/data pa ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LogConfig" /><meta name="guid" content="T_BerkeleyDB_LogConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LogConfig" /><MSHelp:TOCTitle Title="LogConfig Class" /><MSHelp:RLTitle Title="LogConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LogConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassTopic" /><MSHelp:Keyword Index="K" Term="LogConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LogConfig
class" /><MSHelp:Keyword Index="K" Term="LogConfig class, about LogConfig class" /><MSHelp:Keyword Index="F" Term="LogConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr

Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for a 's logging subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_Creation" /><meta name="guid" content="F_BerkeleyDB_SecondaryRecnoDatabaseConfig_Creation" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.Creation" /><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig.Creation Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryRecnoDatabaseConfig.Creation" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K" Term="Creation field" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig.Creation field" /><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig.Creation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabaseConfig.Creation" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig..::.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryBTreeDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryBTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryBTreeDatabaseConfig Members" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"

class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_SecondaryBTreeDatabaseConfig.htm">SecondaryBTreeDatabaseConfig Class Constructors Methods Fields Properties See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EmptyPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_EmptyPages" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_EmptyPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.EmptyPages" /><MSHelp:TOCTitle Title="EmptyPages Property " /><MSHelp:RLTitle Title="BTreeStats.EmptyPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeStats.EmptyPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeStatsClassEmptyPagesTopic" /><MSHelp:Keyword Index="K" Term="EmptyPages property" /><MSHelp:Keyword Index="K" Term="BTreeStats.EmptyPages property" /><MSHelp:Keyword Index="F" Term="EmptyPages" /><MSHelp:Keyword Index="F" Term="BTreeStats.EmptyPages" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.BTreeStats.EmptyPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.EmptyPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.get_EmptyPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Empty pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable"

cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.EmptyPages Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, SecondaryHashDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryHashDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryHashDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,BerkeleyDB.SecondaryHashDatabaseConfig, BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, SecondaryHashDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="SecondaryHashDatabase.Open Method (String, SecondaryHashDatabaseConfig,

Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryHashDatabase.Open(System.String,BerkeleyDB.SecondaryHashDatabaseConfig,
BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.SecondaryHashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new
SecondaryHashDatabase object, open the database represented by and associate the database with the primary
index." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryHashDatabase<span
class="languageSpecificText">..<span
class="cpp">::.Open Method (String, SecondaryHashDatabaseConfig,
Transaction)</td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_SecondaryHashDatabase.htm">SecondaryHashDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>EncryptionPassword Property </title><link rel="stylesheet"
 type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_DatabaseConfig_EncryptionPassword" /><meta name="guid"
content="P_BerkeleyDB_DatabaseConfig_EncryptionPassword" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseConfig.EncryptionPassword" /><MSHelp:TOCTitle Title="EncryptionPassword
 Property " /><MSHelp:RLTitle Title="DatabaseConfig.EncryptionPassword Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseConfig.EncryptionPassword"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassEncryptionPasswordTopic"
/><MSHelp:Keyword Index="K" Term="EncryptionPassword property" /><MSHelp:Keyword Index="K"
Term="DatabaseConfig.EncryptionPassword property" /><MSHelp:Keyword Index="F"
Term="EncryptionPassword" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.EncryptionPassword"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.EncryptionPassword" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.EncryptionPassword" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseConfig.get_EncryptionPassword" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang"
 Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The password used to perform encryption and decryption." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
 style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"

style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.EncryptionPassword Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapStats Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HeapStats" /><meta name="guid" content="Methods_T_BerkeleyDB_HeapStats" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HeapStats" /><MSHelp:TOCTitle Title="HeapStats Methods " /><MSHelp:RLTitle Title="HeapStats Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HeapStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsMethodsTopic" /><MSHelp:Keyword Index="K" Term="HeapStats class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">HeapStats Methods </td></tr><tr id="headerTableRow3"><td
align="left">HeapStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method
(String, String)</title><link rel="stylesheet" type="text/css"
 href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BaseDatabase_Remove_2" /><meta name="guid"
content="M_BerkeleyDB_BaseDatabase_Remove_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseDatabase.Remove(System.String,System.String)" /><MSHelp:TOCTitle
Title="Remove Method (String, String)" /><MSHelp:RLTitle
 Title="BaseDatabase.Remove Method (String, String) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseDatabase.Remove(System.String,System.String)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BaseDatabase.Remove" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Remove the database specified by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image"
 /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
 class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Remove Method (String, String)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SourceFile Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoDatabase_SourceFile" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabase_SourceFile" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabase.SourceFile" /><MSHelp:TOCTitle Title="SourceFile Property " /><MSHelp:RLTitle Title="RecnoDatabase.SourceFile Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabase.SourceFile" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassSourceFileTopic" /><MSHelp:Keyword Index="K" Term="SourceFile property" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.SourceFile property" /><MSHelp:Keyword Index="F" Term="SourceFile" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.SourceFile" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.SourceFile" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.SourceFile" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.get_SourceFile" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.set_SourceFile" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The underlying source file
for the Recno access method." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.SourceFile Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultipleKey Method (Int32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Cursor_RefreshMultipleKey_2" /><meta name="guid"
content="M_BerkeleyDB_Cursor_RefreshMultipleKey_2"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.RefreshMultipleKey(System.Int32)"
/><MSHelp:TOCTitle Title="RefreshMultipleKey Method (Int32)" /><MSHelp:RLTitle
Title="Cursor.RefreshMultipleKey Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Cursor.RefreshMultipleKey(System.Int32)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.RefreshMultipleKey" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Store the key/data pair to which the cursor refers and as many ensuing key/data pairs that can fit in a buffer
the size of in ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td
align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.RefreshMultipleKey Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META
NAME="save" CONTENT="history" /><title>Recno Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_Recno" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_Recno" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.Recno" /><MSHelp:TOCTitle
Title="Recno Method " /><MSHelp:RLTitle Title="BTreeCursor.Recno Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.Recno" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.Recno" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the record number associated with the cursor's current position." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img

ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..<span
class="cpp">::.Recno Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, BTreeDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_Open_2" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.Open(System.String,System.String,BerkeleyDB.BTreeDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, String, BTreeDatabaseConfig)" /><MSHelp:RLTitle Title="BTreeDatabase.Open Method (String, String, BTreeDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.Open(System.String,System.String,BerkeleyDB.BTreeDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Open"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new BTreeDatabase object and open the database represented by and ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Open Method (String, String, BTreeDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Renumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryRecnoDatabase_Renumber" /><meta name="guid" content="P_BerkeleyDB_SecondaryRecnoDatabase_Renumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryRecnoDatabase.Renumber" /><MSHelp:TOCTitle Title="Renumber Property " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Renumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryRecnoDatabase.Renumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassRenumberTopic" /><MSHelp:Keyword Index="K" Term="Renumber property" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Renumber property" /><MSHelp:Keyword Index="F" Term="Renumber" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Renumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Renumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.Renumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryRecnoDatabase.get_Renumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true,
the logical record numbers are mutable, and change as records are added to and deleted from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Renumber Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Backup Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Backup" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Backup" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Backup(System.String,BerkeleyDB.BackupOptions)" /><MSHelp:TOCTitle Title="Backup Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Backup Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Backup(System.String,BerkeleyDB.BackupOptions)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassBackupTopic" /><MSHelp:Keyword Index="K" Term="Backup method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Backup method" /><MSHelp:Keyword Index="F" Term="Backup" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Backup" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Backup" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Backup"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Perform a hot back up of the open environment. All files used by the environment are backed up, so long as the normal rules for file placement are followed. For information on how fi ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Backup Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PageNotFoundException Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_PageNotFoundException" /><meta name="guid" content="AllMembers_T_BerkeleyDB_PageNotFoundException" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.PageNotFoundException" /><MSHelp:TOCTitle Title="PageNotFoundException Members" /><MSHelp:RLTitle Title="PageNotFoundException Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.PageNotFoundException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBPageNotFoundExceptionMembersTopic" /><MSHelp:Keyword Index="K" Term="PageNotFoundException class" /><MSHelp:Keyword Index="K" Term="PageNotFoundException class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.PageNotFoundException class" /><MSHelp:Keyword Index="F" Term="PageNotFoundException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.PageNotFoundException" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">PageNotFoundException Members</td></tr><tr id="headerTableRow3"><td align="left">PageNotFoundException Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseFeedbackEvent Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_DatabaseFeedbackEvent" /><meta name="guid" content="T_BerkeleyDB_DatabaseFeedbackEvent" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.DatabaseFeedbackEvent" /><MSHelp:TOCTitle

Title="DatabaseFeedbackEvent Enumeration" /><MSHelp:RLTitle Title="DatabaseFeedbackEvent Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.DatabaseFeedbackEvent" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseFeedbackEvent.UPGRADE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseFeedbackEvent.VERIFY" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseFeedbackEventClassTopic" /><MSHelp:Keyword Index="K" Term="DatabaseFeedbackEvent enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.DatabaseFeedbackEvent enumeration" /><MSHelp:Keyword Index="K" Term="UPGRADE enumeration member" /><MSHelp:Keyword Index="K" Term="VERIFY enumeration member" /><MSHelp:Keyword Index="F" Term="DatabaseFeedbackEvent" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseFeedbackEvent" /><MSHelp:Keyword Index="F" Term="DatabaseFeedbackEvent.UPGRADE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseFeedbackEvent.UPGRADE" /><MSHelp:Keyword Index="F" Term="DatabaseFeedbackEvent.VERIFY" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseFeedbackEvent.VERIFY" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackEvent" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackEvent.UPGRADE" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseFeedbackEvent.VERIFY" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies the database operation whose progress is being reported" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseFeedbackEvent Enumeration</td></tr><tr id="headerTableRow3"><td align="left">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Max Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceConfig_Max" /><meta name="guid" content="P_BerkeleyDB_SequenceConfig_Max" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceConfig.Max" /><MSHelp:TOCTitle Title="Max Property " /><MSHelp:RLTitle Title="SequenceConfig.Max Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceConfig.Max" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceConfigClassMaxTopic" /><MSHelp:Keyword Index="K" Term="Max property" /><MSHelp:Keyword Index="K" Term="SequenceConfig.Max property" /><MSHelp:Keyword Index="F" Term="Max" /><MSHelp:Keyword Index="F" Term="SequenceConfig.Max" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceConfig.Max" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.Max" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceConfig.get_Max" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum value in the sequence." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceConfig..::.Max Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RefreshMultiple Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeCursor_RefreshMultiple" /><meta name="guid" content="Overload_BerkeleyDB_BTreeCursor_RefreshMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeCursor.RefreshMultiple" /><MSHelp:TOCTitle Title="RefreshMultiple

Method " /><MSHelp:RLTitle Title="BTreeCursor.RefreshMultiple Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeCursor.RefreshMultiple"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorClassRefreshMultipleTopic"
/><MSHelp:Keyword Index="K" Term="RefreshMultiple method" /><MSHelp:Keyword Index="K"
Term="BTreeCursor.RefreshMultiple method" /><MSHelp:Keyword Index="F" Term="RefreshMultiple"
/><MSHelp:Keyword Index="F" Term="BTreeCursor.RefreshMultiple" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BTreeCursor.RefreshMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"

data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.RefreshMultiple Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Decompress Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeDatabase_Decompress" /><meta name="guid" content="P_BerkeleyDB_BTreeDatabase_Decompress" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeDatabase.Decompress" /><MSHelp:TOCTitle Title="Decompress Property " /><MSHelp:RLTitle Title="BTreeDatabase.Decompress Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BTreeDatabase.Decompress" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassDecompressTopic" /><MSHelp:Keyword Index="K" Term="Decompress property" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Decompress property" /><MSHelp:Keyword Index="F" Term="Decompress" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Decompress" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Decompress" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.Decompress" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.get_Decompress" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.set_Decompress" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The decompression function used to retrieve key/data pairs from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Decompress Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Stats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Stats" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Stats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:TOCTitle Title="Stats Method " /><MSHelp:RLTitle Title="RecnoDatabase.Stats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Stats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information for this
database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase<span

class="cs">..::.Stats Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NoLocking Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_NoLocking" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_NoLocking" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.NoLocking" /><MSHelp:TOCTitle Title="NoLocking Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.NoLocking Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.NoLocking" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassNoLockingTopic" /><MSHelp:Keyword Index="K" Term="NoLocking property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.NoLocking property" /><MSHelp:Keyword Index="F" Term="NoLocking" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.NoLocking" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.NoLocking" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.NoLocking" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_NoLocking" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_NoLocking" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will grant all requested mutual exclusion mutexes and database locks without regard for their actual availability. This functionality should never be used for purposes other th ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.NoLocking Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryDatabaseConfig Members" /><MSHelp:RLTitle Title="SecondaryDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig

class" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"

onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig
Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html;
charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ForceSync Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_LogConfig_ForceSync" /><meta name="guid" content="F_BerkeleyDB_LogConfig_ForceSync" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.LogConfig.ForceSync"
/><MSHelp:TOCTitle Title="ForceSync Field" /><MSHelp:RLTitle Title="LogConfig.ForceSync Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.LogConfig.ForceSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassForceSyncTopic" /><MSHelp:Keyword Index="K" Term="ForceSync field" /><MSHelp:Keyword Index="K" Term="LogConfig.ForceSync field" /><MSHelp:Keyword Index="F" Term="ForceSync" /><MSHelp:Keyword Index="F" Term="LogConfig.ForceSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.ForceSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.ForceSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB will flush log writes to the backing disk before returning from the write system call, rather than flushing log writes explicitly in a separate system call, as necessary." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig..::.ForceSync Field</td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTREE Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta

name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseType_BTREE" /><meta name="guid" content="F_BerkeleyDB_DatabaseType_BTREE" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseType.BTREE" /><MSHelp:TOCTitle Title="BTREE Field" /><MSHelp:RLTitle Title="DatabaseType.BTREE Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseType.BTREE" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassBTREETopic" /><MSHelp:Keyword Index="K" Term="BTREE field" /><MSHelp:Keyword Index="K" Term="DatabaseType.BTREE field" /><MSHelp:Keyword Index="F" Term="BTREE" /><MSHelp:Keyword Index="F" Term="DatabaseType.BTREE" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.BTREE" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.BTREE" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="BTree access method" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType..::.BTREE Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextDuplicateMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveNextDuplicateMultipleKey" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveNextDuplicateMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveNextDuplicateMultipleKey" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method " /><MSHelp:RLTitle Title="HashCursor.MoveNextDuplicateMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveNextDuplicateMultipleKeyTopic" /><MSHelp:Keyword Index="K" Term="MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveNextDuplicateMultipleKey method" /><MSHelp:Keyword Index="F" Term="MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveNextDuplicateMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabaseConfig Constructor </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryHashDatabaseConfig__ctor" /><meta name="guid" content="M_BerkeleyDB_SecondaryHashDatabaseConfig__ctor" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryHashDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:TOCTitle Title="SecondaryHashDatabaseConfig Constructor " /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig Constructor (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryHashDatabaseConfig.#ctor(BerkeleyDB.Database,BerkeleyDB.SecondaryKeyGenDelegate)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassctorTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig class, constructor" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.SecondaryHashDatabaseConfig constructor" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.SecondaryHashDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.SecondaryHashDatabaseConfig" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig..ctor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new SecondaryHashDatabaseConfig object" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig Constructor </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_CompactConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_CompactConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.CompactConfig" /><MSHelp:TOCTitle Title="CompactConfig Methods " /><MSHelp:RLTitle Title="CompactConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.CompactConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="CompactConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FastStats Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">

</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabase_FastStats_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabase_FastStats_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="FastStats Method (Transaction)" /><MSHelp:RLTitle Title="BTreeDatabase.FastStats Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeDatabase.FastStats(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabase.FastStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Return the database statistical information which does not require traversal of the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.FastStats Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Verify Method (String, DatabaseConfig, Database.VerifyOperation)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Database_Verify_1" /><meta name="guid" content="M_BerkeleyDB_Database_Verify_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Database.Verify(System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Database.VerifyOperation)" /><MSHelp:TOCTitle Title="Verify Method (String, DatabaseConfig, Database.VerifyOperation)" /><MSHelp:RLTitle Title="Database.Verify Method (String, DatabaseConfig, Database.VerifyOperation) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Database.Verify(System.String,BerkeleyDB.DatabaseConfig,BerkeleyDB.Database.VerifyOperation)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Database.Verify" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Verify the integrity of all databases in the file specified by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Database..::.Verify Method (String, DatabaseConfig, Database..::.VerifyOperation)</td></tr><tr id="headerTableRow3"><td align="left">Database Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ObjectSteals Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_ObjectSteals" /><meta name="guid" content="P_BerkeleyDB_LockStats_ObjectSteals" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.ObjectSteals" /><MSHelp:TOCTitle Title="ObjectSteals Property " /><MSHelp:RLTitle Title="LockStats.ObjectSteals Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.ObjectSteals" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassObjectStealsTopic"

/><MSHelp:Keyword Index="K" Term="ObjectSteals property" /><MSHelp:Keyword Index="K" Term="LockStats.ObjectSteals property" /><MSHelp:Keyword Index="F" Term="ObjectSteals" /><MSHelp:Keyword Index="F" Term="LockStats.ObjectSteals" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.ObjectSteals" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.ObjectSteals" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.get_ObjectSteals" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Number of objects steals so far." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.ObjectSteals Property </td></tr><tr

id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="BTreeDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FileMode Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogConfig_FileMode" /><meta name="guid" content="P_BerkeleyDB_LogConfig_FileMode" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogConfig.FileMode" /><MSHelp:TOCTitle Title="FileMode

Property " /><MSHelp:RLTitle Title="LogConfig.FileMode Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogConfig.FileMode" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigClassFileModeTopic" /><MSHelp:Keyword Index="K" Term="FileMode property" /><MSHelp:Keyword Index="K" Term="LogConfig.FileMode property" /><MSHelp:Keyword Index="F" Term="FileMode" /><MSHelp:Keyword Index="F" Term="LogConfig.FileMode" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig.FileMode" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.FileMode" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.get_FileMode" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogConfig.set_FileMode" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The absolute file mode for created log files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">LogConfig..::.FileMode Property </td></tr><tr id="headerTableRow3"><td align="left">LogConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveFirst" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="SecondaryCursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the first key/data pair of the database, and store the secondary key along with the corresponding primary key/data pair in . If the first key has duplicate values, the f ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"

src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveFirst Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxObjectsInTable Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_MaxObjectsInTable" /><meta name="guid" content="P_BerkeleyDB_LockStats_MaxObjectsInTable" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.MaxObjectsInTable" /><MSHelp:TOCTitle Title="MaxObjectsInTable Property " /><MSHelp:RLTitle Title="LockStats.MaxObjectsInTable Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.MaxObjectsInTable" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassMaxObjectsInTableTopic" /><MSHelp:Keyword Index="K" Term="MaxObjectsInTable property" /><MSHelp:Keyword Index="K" Term="LockStats.MaxObjectsInTable property" /><MSHelp:Keyword Index="F" Term="MaxObjectsInTable" /><MSHelp:Keyword Index="F" Term="LockStats.MaxObjectsInTable" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.MaxObjectsInTable" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.MaxObjectsInTable" /><MSHelp:Attr Name="APIName"

Value="BerkeleyDB.LockStats.get_MaxObjectsInTable" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum num of objects in table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.MaxObjectsInTable Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>ActiveTransaction Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ActiveTransaction" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ActiveTransaction" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ActiveTransaction" /><MSHelp:TOCTitle Title="ActiveTransaction Members" /><MSHelp:RLTitle Title="ActiveTransaction Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ActiveTransaction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionMembersTopic" /><MSHelp:Keyword Index="K" Term="ActiveTransaction class" /><MSHelp:Keyword Index="K" Term="ActiveTransaction class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ActiveTransaction class" /><MSHelp:Keyword Index="F" Term="ActiveTransaction" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.ActiveTransaction" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label

id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ActiveTransaction Members</td></tr><tr id="headerTableRow3"><td align="left">ActiveTransaction Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryHashDatabase Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryHashDatabase" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryHashDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:TOCTitle Title="SecondaryHashDatabase Members" /><MSHelp:RLTitle Title="SecondaryHashDatabase Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase class" /><MSHelp:Keyword

Index="K" Term="SecondaryHashDatabase class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryHashDatabase class" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"

/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase Members</td></tr><tr id="headerTableRow3"><td
 align="left">SecondaryHashDatabase Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VerificationException Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css"
 href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_VerificationException" /><meta name="guid" content="Methods_T_BerkeleyDB_VerificationException" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.VerificationException" /><MSHelp:TOCTitle Title="VerificationException Methods " /><MSHelp:RLTitle Title="VerificationException Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A"
 Term="Methods.T:BerkeleyDB.VerificationException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVerificationExceptionMethodsTopic" /><MSHelp:Keyword Index="K" Term="VerificationException class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
 /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VerificationException Methods </td></tr><tr id="headerTableRow3"><td align="left">VerificationException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TruncatePages Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_CompactConfig_TruncatePages" /><meta name="guid"
content="F_BerkeleyDB_CompactConfig_TruncatePages" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.CompactConfig.TruncatePages" /><MSHelp:TOCTitle Title="TruncatePages Field"
/><MSHelp:RLTitle Title="CompactConfig.TruncatePages Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.CompactConfig.TruncatePages" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCompactConfigClassTruncatePagesTopic" /><MSHelp:Keyword Index="K"
Term="TruncatePages field" /><MSHelp:Keyword Index="K" Term="CompactConfig.TruncatePages field"
/><MSHelp:Keyword Index="F"
Term="TruncatePages" /><MSHelp:Keyword Index="F" Term="CompactConfig.TruncatePages"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.TruncatePages" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.TruncatePages" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="If true, return pages to the filesystem when possible. If false, pages emptied as a result of
compaction will be placed on the free list for re-use, but never returned to the filesystem." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual

Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.TruncatePages Field</td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_LockTimeout" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_LockTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.LockTimeout" /><MSHelp:TOCTitle Title="LockTimeout Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.LockTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.LockTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassLockTimeoutTopic" /><MSHelp:Keyword Index="K" Term="LockTimeout property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.LockTimeout property" /><MSHelp:Keyword Index="F" Term="LockTimeout" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.LockTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.LockTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.LockTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_LockTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_LockTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A value, in microseconds, representing lock timeouts." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.LockTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Min Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_Min" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_Min" /><xml><MSHelp:Attr Name="AssetID"

Value="P:BerkeleyDB.SequenceStats.Min" /><MSHelp:TOCTitle Title="Min Property " /><MSHelp:RLTitle Title="SequenceStats.Min Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.Min" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassMinTopic" /><MSHelp:Keyword Index="K" Term="Min property" /><MSHelp:Keyword Index="K" Term="SequenceStats.Min property" /><MSHelp:Keyword Index="F" Term="Min" /><MSHelp:Keyword Index="F" Term="SequenceStats.Min" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.Min" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.Min" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_Min" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Minimum value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats.<span

class="vb">.::.Min Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SequenceStats.htm">SequenceStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>PrintRepMgrSystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintRepMgrSystemStats" /><meta
name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintRepMgrSystemStats"
/><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:TOCTitle
Title="PrintRepMgrSystemStats Method " /><MSHelp:RLTitle
Title="DatabaseEnvironment.PrintRepMgrSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintRepMgrSystemStatsTopic" /><MSHelp:Keyword
Index="K" Term="PrintRepMgrSystemStats method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.PrintRepMgrSystemStats
method" /><MSHelp:Keyword Index="F" Term="PrintRepMgrSystemStats" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.PrintRepMgrSystemStats" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage"
style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintRepMgrSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>FileId Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_FileId" /><meta name="guid" content="P_BerkeleyDB_LogStats_FileId" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.FileId" /><MSHelp:TOCTitle Title="FileId Property " /><MSHelp:RLTitle Title="LogStats.FileId Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.FileId" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassFileIdTopic" /><MSHelp:Keyword Index="K" Term="FileId property" /><MSHelp:Keyword Index="K" Term="LogStats.FileId property" /><MSHelp:Keyword Index="F" Term="FileId" /><MSHelp:Keyword Index="F" Term="LogStats.FileId" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.FileId" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.FileId" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_FileId" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Current fileids in use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.FileId Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>TableSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryHashDatabaseConfig_TableSize" /><meta name="guid" content="P_BerkeleyDB_SecondaryHashDatabaseConfig_TableSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryHashDatabaseConfig.TableSize" /><MSHelp:TOCTitle Title="TableSize Property " /><MSHelp:RLTitle Title="SecondaryHashDatabaseConfig.TableSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryHashDatabaseConfig.TableSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseConfigClassTableSizeTopic" /><MSHelp:Keyword Index="K" Term="TableSize property" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabaseConfig.TableSize property" /><MSHelp:Keyword Index="F" Term="TableSize" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabaseConfig.TableSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabaseConfig.TableSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.get_TableSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryHashDatabaseConfig.set_TableSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="An estimate of the final size of the hash table." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabaseConfig..::.TableSize Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MAX_LOCKS Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_MAX_LOCKS" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_MAX_LOCKS" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.MAX_LOCKS" /><MSHelp:TOCTitle Title="MAX_LOCKS Field"

/><MSHelp:RLTitle Title="DeadlockPolicy.MAX_LOCKS Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DeadlockPolicy.MAX_LOCKS" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassMAX_LOCKSTopic" /><MSHelp:Keyword Index="K" Term="MAX_LOCKS field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.MAX_LOCKS field" /><MSHelp:Keyword Index="F" Term="MAX_LOCKS" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.MAX_LOCKS" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.MAX_LOCKS" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.MAX_LOCKS" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject the lock request for the locker ID with the most locks." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">DeadlockPolicy..::.MAX_LOCKS Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LOW Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CachePriority_LOW" /><meta name="guid" content="F_BerkeleyDB_CachePriority_LOW" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CachePriority.LOW" /><MSHelp:TOCTitle Title="LOW Field" /><MSHelp:RLTitle Title="CachePriority.LOW Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CachePriority.LOW" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityClassLOWTopic" /><MSHelp:Keyword Index="K" Term="LOW field" /><MSHelp:Keyword Index="K" Term="CachePriority.LOW field" /><MSHelp:Keyword Index="F" Term="LOW" /><MSHelp:Keyword Index="F" Term="CachePriority.LOW" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CachePriority.LOW" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CachePriority.LOW" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The next lowest priority." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage"

class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CachePriority..::.LOW Field</td></tr><tr id="headerTableRow3"><td align="left">CachePriority Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_QueueDatabase_Close" /><meta name="guid" content="Overload_BerkeleyDB_QueueDatabase_Close" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.QueueDatabase.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="QueueDatabase.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.QueueDatabase.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="QueueDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="QueueDatabase.Close"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage" style="display:none;
height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Rename Method (String, String)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Rename" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Rename" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String)" /><MSHelp:TOCTitle Title="Rename Method (String, String)" /><MSHelp:RLTitle Title="BaseDatabase.Rename Method (String, String) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Rename(System.String,System.String)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Rename" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Rename the underlying file represented by , incidentally renaming all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Rename Method (String, String)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Close" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Close" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Close" /><MSHelp:TOCTitle Title="Close Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Close Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Close" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassCloseTopic" /><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Close method" /><MSHelp:Keyword Index="F" Term="Close" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Close" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Close" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"

/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="By closing the Berkeley DB environment you can free allocated resources and close any open databases along with the underlying subsystems." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexStats

Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_MutexStats" /><meta name="guid" content="Properties_T_BerkeleyDB_MutexStats" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.MutexStats" /><MSHelp:TOCTitle Title="MutexStats Properties " /><MSHelp:RLTitle Title="MutexStats Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.MutexStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsPropertiesTopic" /><MSHelp:Keyword Index="K" Term="MutexStats class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox"
type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label
class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">MutexStats Properties </td></tr><tr id="headerTableRow3"><td
align="left">MutexStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>TransactionConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Fields_T_BerkeleyDB_TransactionConfig" /><meta name="guid"
content="Fields_T_BerkeleyDB_TransactionConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.TransactionConfig" /><MSHelp:TOCTitle Title="TransactionConfig Fields"
/><MSHelp:RLTitle Title="TransactionConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.TransactionConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBTransactionConfigFieldsTopic" /><MSHelp:Keyword Index="K"
Term="TransactionConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img

id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">TransactionConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetForeignKeyConstraint Method (Database, ForeignKeyDeleteAction, ForeignKeyNullifyDelegate)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryDatabaseConfig_SetForeignKeyConstraint_1" /><meta name="guid" content="M_BerkeleyDB_SecondaryDatabaseConfig_SetForeignKeyConstraint_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint(BerkeleyDB.Database,BerkeleyDB.ForeignKeyDeleteAction,BerkeleyDB.ForeignKeyNullifyDelegate)" /><MSHelp:TOCTitle Title="SetForeignKeyConstraint Method (Database, ForeignKeyDeleteAction, ForeignKeyNullifyDelegate)" /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.SetForeignKeyConstraint Method (Database, ForeignKeyDeleteAction, ForeignKeyNullifyDelegate) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint(BerkeleyDB.Database,BerkeleyDB.ForeignKeyDeleteAction,BerkeleyDB.ForeignKeyNullifyDelegate)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.SetForeignKeyConstraint" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specify the action taken when a referenced record in the foreign key database is deleted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.SetForeignKeyConstraint Method (Database, ForeignKeyDeleteAction, ForeignKeyNullifyDelegate)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveFirst Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashCursor_MoveFirst" /><meta name="guid" content="Overload_BerkeleyDB_HashCursor_MoveFirst" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashCursor.MoveFirst" /><MSHelp:TOCTitle Title="MoveFirst Method " /><MSHelp:RLTitle Title="HashCursor.MoveFirst Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashCursor.MoveFirst" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassMoveFirstTopic" /><MSHelp:Keyword Index="K" Term="MoveFirst method" /><MSHelp:Keyword Index="K" Term="HashCursor.MoveFirst method" /><MSHelp:Keyword Index="F" Term="MoveFirst" /><MSHelp:Keyword Index="F" Term="HashCursor.MoveFirst" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor.MoveFirst" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor..::.MoveFirst Method </td></tr><tr id="headerTableRow3"><td align="left">HashCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesTruncated Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_CompactData_PagesTruncated" /><meta name="guid" content="P_BerkeleyDB_CompactData_PagesTruncated" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.CompactData.PagesTruncated" /><MSHelp:TOCTitle Title="PagesTruncated Property " /><MSHelp:RLTitle Title="CompactData.PagesTruncated Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.CompactData.PagesTruncated" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataClassPagesTruncatedTopic" /><MSHelp:Keyword Index="K" Term="PagesTruncated property" /><MSHelp:Keyword Index="K" Term="CompactData.PagesTruncated property" /><MSHelp:Keyword Index="F" Term="PagesTruncated" /><MSHelp:Keyword Index="F" Term="CompactData.PagesTruncated" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData.PagesTruncated" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.PagesTruncated" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactData.get_PagesTruncated" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of database pages returned to the filesystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"

style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData..<span
class="cpp">::.PagesTruncated Property </td></tr><tr id="headerTableRow3"><td align="left">CompactData Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Flags Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SequenceStats_Flags" /><meta name="guid" content="P_BerkeleyDB_SequenceStats_Flags" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SequenceStats.Flags" /><MSHelp:TOCTitle Title="Flags Property " /><MSHelp:RLTitle Title="SequenceStats.Flags Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SequenceStats.Flags" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSequenceStatsClassFlagsTopic" /><MSHelp:Keyword Index="K" Term="Flags property" /><MSHelp:Keyword Index="K" Term="SequenceStats.Flags property" /><MSHelp:Keyword Index="F" Term="Flags" /><MSHelp:Keyword Index="F" Term="SequenceStats.Flags" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SequenceStats.Flags" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.Flags" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SequenceStats.get_Flags" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Flag value." />
<MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SequenceStats..::.Flags Property </td></tr><tr id="headerTableRow3"><td align="left">SequenceStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepMgrSite Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"

src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_RepMgrSite"
/><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_RepMgrSite"
/><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.RepMgrSite"
/><MSHelp:TOCTitle Title="RepMgrSite Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepMgrSite
Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.DatabaseEnvironment.RepMgrSite" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepMgrSiteTopic" /><MSHelp:Keyword Index="K"
Term="RepMgrSite method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepMgrSite method"
/><MSHelp:Keyword Index="F" Term="RepMgrSite" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.RepMgrSite" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepMgrSite" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset"
/><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse
image" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:

none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepMgrSite Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_MoveNext_3" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_MoveNext_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.MoveNext(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNext Method (LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.MoveNext Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.MoveNext(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNext is identical to . Otherwise, move the cursor

to the next key/data pair of the database, and store the secondary key and primary key/data pair in . In ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MoveNext Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Partitions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_LockingConfig_Partitions" /><meta name="guid"
content="P_BerkeleyDB_LockingConfig_Partitions" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.LockingConfig.Partitions" /><MSHelp:TOCTitle Title="Partitions
Property " /><MSHelp:RLTitle Title="LockingConfig.Partitions Property (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="P:BerkeleyDB.LockingConfig.Partitions" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLockingConfigClassPartitionsTopic" /><MSHelp:Keyword Index="K" Term="Partitions
property" /><MSHelp:Keyword Index="K" Term="LockingConfig.Partitions property" /><MSHelp:Keyword
Index="F" Term="Partitions" /><MSHelp:Keyword Index="F" Term="LockingConfig.Partitions"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig.Partitions" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig.Partitions" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockingConfig.get_Partitions" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LockingConfig.set_Partitions" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The number of lock table partitions in the Berkeley DB environment." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label> <span id="devlangsDropdown" class="filter"
tabindex="0"><img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig..::.Partitions Property </td></tr><tr id="headerTableRow3"><td align="left">LockingConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepSetTransmitLimit Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_RepSetTransmitLimit" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_RepSetTransmitLimit" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.RepSetTransmitLimit(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="RepSetTransmitLimit Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.RepSetTransmitLimit Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepSetTransmitLimit(System.UInt32,System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepSetTransmitLimitTopic" /><MSHelp:Keyword Index="K" Term="RepSetTransmitLimit method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.RepSetTransmitLimit method" /><MSHelp:Keyword Index="F" Term="RepSetTransmitLimit" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepSetTransmitLimit" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.RepSetTransmitLimit" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.RepSetTransmitLimit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set a byte-count limit on the amount of data that will be transmitted from a site in response to a single message processed by . The limit is not a hard limit, and the record that exceeds the limit ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.RepSetTransmitLimit Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LSN Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="AllMembers_T_BerkeleyDB_LSN" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LSN"
/><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LSN" /><MSHelp:TOCTitle
Title="LSN Members"
/><MSHelp:RLTitle Title="LSN Members (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="AllMembers.T:BerkeleyDB.LSN" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLSNMembersTopic" /><MSHelp:Keyword Index="K" Term="LSN class"
/><MSHelp:Keyword Index="K" Term="LSN class, all members" /><MSHelp:Keyword Index="K"
Term="BerkeleyDB.LSN class" /><MSHelp:Keyword Index="F" Term="LSN" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LSN" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="expandImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LSN Members</td></tr><tr id="headerTableRow3"><td align="left">LSN Class Constructors Methods Fields See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="BTreeDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.GetBoth" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase.<span

class="vb">.::.GetBoth Method
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeDatabase.htm">BTreeDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
 CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_Close" /><meta name="guid"
content="Overload_BerkeleyDB_SecondaryHashDatabase_Close" /><xml><MSHelp:Attr
 Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.Close" /><MSHelp:TOCTitle
Title="Close Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.Close Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.Close"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassCloseTopic"
/><MSHelp:Keyword Index="K" Term="Close method" /><MSHelp:Keyword Index="K"
Term="SecondaryHashDatabase.Close method" /><MSHelp:Keyword Index="F" Term="Close"
/><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.Close" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryHashDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input
 type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table
 id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.Close Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Insert Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoCursor_Insert" /><meta name="guid"

content="M_BerkeleyDB_RecnoCursor_Insert" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoCursor.Insert(BerkeleyDB.DatabaseEntry,BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:TOCTitle Title="Insert Method " /><MSHelp:RLTitle Title="RecnoCursor.Insert Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoCursor.Insert(BerkeleyDB.DatabaseEntry,BerkeleyDB.Cursor.InsertLocation)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoCursorClassInsertTopic" /><MSHelp:Keyword Index="K" Term="Insert method" /><MSHelp:Keyword Index="K" Term="RecnoCursor.Insert method" /><MSHelp:Keyword Index="F" Term="Insert" /><MSHelp:Keyword Index="F" Term="RecnoCursor.Insert" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoCursor.Insert" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoCursor.Insert" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Insert the data element as a duplicate element of the key to which the cursor refers." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoCursor..::.Insert Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLockerCount Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_InitLockerCount" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_InitLockerCount" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.InitLockerCount" /><MSHelp:TOCTitle Title="InitLockerCount Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.InitLockerCount Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.InitLockerCount" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassInitLockerCountTopic" /><MSHelp:Keyword Index="K" Term="InitLockerCount property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.InitLockerCount property" /><MSHelp:Keyword Index="F" Term="InitLockerCount" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.InitLockerCount" /><MSHelp:Keyword
Index="F" Term="BerkeleyDB.DatabaseEnvironment.InitLockerCount" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.InitLockerCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_InitLockerCount" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_InitLockerCount" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The number of lockers allocated when the environment is created" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.InitLockerCount Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InternalPagesFreeBytes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_BTreeStats_InternalPagesFreeBytes" /><meta name="guid" content="P_BerkeleyDB_BTreeStats_InternalPagesFreeBytes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.BTreeStats.InternalPagesFreeBytes" /><MSHelp:TOCTitle Title="InternalPagesFreeBytes

Property " /><MSHelp:RLTitle
Title="BTreeStats.InternalPagesFreeBytes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BTreeStats.InternalPagesFreeBytes" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeStatsClassInternalPagesFreeBytesTopic" /><MSHelp:Keyword Index="K"
Term="InternalPagesFreeBytes property" /><MSHelp:Keyword Index="K"
Term="BTreeStats.InternalPagesFreeBytes property" /><MSHelp:Keyword Index="F"
Term="InternalPagesFreeBytes" /><MSHelp:Keyword Index="F" Term="BTreeStats.InternalPagesFreeBytes"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.InternalPagesFreeBytes" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.InternalPagesFreeBytes" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BTreeStats.get_InternalPagesFreeBytes" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Bytes free in
internal pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label> <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.InternalPagesFreeBytes Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ElectionTimeout Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationConfig_ElectionTimeout" /><meta name="guid" content="P_BerkeleyDB_ReplicationConfig_ElectionTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationConfig.ElectionTimeout" /><MSHelp:TOCTitle Title="ElectionTimeout Property " /><MSHelp:RLTitle Title="ReplicationConfig.ElectionTimeout Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationConfig.ElectionTimeout" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassElectionTimeoutTopic" /><MSHelp:Keyword Index="K" Term="ElectionTimeout property" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.ElectionTimeout property" /><MSHelp:Keyword Index="F" Term="ElectionTimeout" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.ElectionTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.ElectionTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.ElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.get_ElectionTimeout" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.set_ElectionTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The timeout period for an election. The default timeout is 2 seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.ElectionTimeout Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RegionSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MutexStats_RegionSize" /><meta name="guid" content="P_BerkeleyDB_MutexStats_RegionSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MutexStats.RegionSize" /><MSHelp:TOCTitle Title="RegionSize Property " /><MSHelp:RLTitle Title="MutexStats.RegionSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexStats.RegionSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassRegionSizeTopic"

/><MSHelp:Keyword Index="K" Term="RegionSize property" /><MSHelp:Keyword Index="K" Term="MutexStats.RegionSize property" /><MSHelp:Keyword Index="F" Term="RegionSize" /><MSHelp:Keyword Index="F" Term="MutexStats.RegionSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats.RegionSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.RegionSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats.get_RegionSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Region size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats..::.RegionSize Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_MutexStats.htm">MutexStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseLogging Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseLogging" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseLogging" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseLogging" /><MSHelp:TOCTitle Title="UseLogging Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseLogging Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseLogging" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseLoggingTopic" /><MSHelp:Keyword Index="K" Term="UseLogging field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.UseLogging field" /><MSHelp:Keyword Index="F" Term="UseLogging" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.UseLogging" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.UseLogging" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseLogging" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, initialize the logging subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseLogging Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_QueueDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_QueueDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.QueueDatabase" /><MSHelp:TOCTitle Title="QueueDatabase Methods " /><MSHelp:RLTitle Title="QueueDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.QueueDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class <a href="#seeAlsoToggle"

onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Version Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_Version" /><meta name="guid" content="P_BerkeleyDB_HeapStats_Version" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.Version" /><MSHelp:TOCTitle Title="Version Property " /><MSHelp:RLTitle Title="HeapStats.Version Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.Version" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassVersionTopic" /><MSHelp:Keyword Index="K" Term="Version property" /><MSHelp:Keyword Index="K" Term="HeapStats.Version property" /><MSHelp:Keyword Index="F" Term="Version" /><MSHelp:Keyword Index="F" Term="HeapStats.Version" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.Version" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.Version" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_Version" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The version of the Heap database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats..::.Version Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BadSecondaryException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"></script><script type="text/javascript" src="../scripts/Dropdown.js"></script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"></script><script type="text/javascript" src="../scripts/CheckboxMenu.js"></script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_BadSecondaryException" /><meta name="guid" content="Fields_T_BerkeleyDB_BadSecondaryException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.BadSecondaryException" /><MSHelp:TOCTitle Title="BadSecondaryException Fields" /><MSHelp:RLTitle Title="BadSecondaryException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.BadSecondaryException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBadSecondaryExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="BadSecondaryException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BadSecondaryException Fields</td></tr><tr id="headerTableRow3"><td align="left">BadSecondaryException Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LogStats" /><meta name="guid" content="T_BerkeleyDB_LogStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LogStats" /><MSHelp:TOCTitle Title="LogStats Class" /><MSHelp:RLTitle Title="LogStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LogStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassTopic" /><MSHelp:Keyword Index="K" Term="LogStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LogStats class" /><MSHelp:Keyword Index="K" Term="LogStats class, about LogStats class" /><MSHelp:Keyword Index="F" Term="LogStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about the logging subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MutexStats" /><meta name="guid" content="T_BerkeleyDB_MutexStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MutexStats" /><MSHelp:TOCTitle Title="MutexStats Class" /><MSHelp:RLTitle Title="MutexStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MutexStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexStatsClassTopic" /><MSHelp:Keyword Index="K" Term="MutexStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MutexStats class" /><MSHelp:Keyword Index="K" Term="MutexStats class, about MutexStats class" /><MSHelp:Keyword Index="F" Term="MutexStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about the mutex subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>UseTxns Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseTxns" /><meta name="guid"

content="F_BerkeleyDB_DatabaseEnvironmentConfig_UseTxns" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.UseTxns" /><MSHelp:TOCTitle Title="UseTxns Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.UseTxns Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.UseTxns" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassUseTxnsTopic" /><MSHelp:Keyword Index="K" Term="UseTxns field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.UseTxns field" /><MSHelp:Keyword Index="F" Term="UseTxns" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.UseTxns" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.UseTxns" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.UseTxns" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, initialize the transaction subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.UseTxns Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLeaseSec Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_MaxLeaseSec" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MaxLeaseSec" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MaxLeaseSec" /><MSHelp:TOCTitle Title="MaxLeaseSec Property " /><MSHelp:RLTitle Title="ReplicationStats.MaxLeaseSec Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MaxLeaseSec" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMaxLeaseSecTopic" /><MSHelp:Keyword Index="K" Term="MaxLeaseSec property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MaxLeaseSec property" /><MSHelp:Keyword Index="F" Term="MaxLeaseSec" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MaxLeaseSec" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MaxLeaseSec" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MaxLeaseSec" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MaxLeaseSec" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum lease timestamp seconds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"

onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MaxLeaseSec Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>OnForeignKeyDelete Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryDatabaseConfig_OnForeignKeyDelete" /><meta name="guid" content="P_BerkeleyDB_SecondaryDatabaseConfig_OnForeignKeyDelete" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabaseConfig.OnForeignKeyDelete" /><MSHelp:TOCTitle Title="OnForeignKeyDelete Property " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.OnForeignKeyDelete Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryDatabaseConfig.OnForeignKeyDelete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassOnForeignKeyDeleteTopic" /><MSHelp:Keyword Index="K" Term="OnForeignKeyDelete property" /><MSHelp:Keyword Index="K"

Term="SecondaryDatabaseConfig.OnForeignKeyDelete property" /><MSHelp:Keyword Index="F" Term="OnForeignKeyDelete" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig.OnForeignKeyDelete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.OnForeignKeyDelete" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.OnForeignKeyDelete" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.get_OnForeignKeyDelete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The action taken when a referenced record in is deleted." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.OnForeignKeyDelete Property </td></tr><tr id="headerTableRow3"><td align="left"><a

href="T_BerkeleyDB_SecondaryDatabaseConfig.htm">SecondaryDatabaseConfig Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesTrickled Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesTrickled" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesTrickled" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesTrickled" /><MSHelp:TOCTitle Title="PagesTrickled Property " /><MSHelp:RLTitle Title="MPoolStats.PagesTrickled Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PagesTrickled" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesTrickledTopic" /><MSHelp:Keyword Index="K" Term="PagesTrickled property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PagesTrickled property" /><MSHelp:Keyword Index="F" Term="PagesTrickled" /><MSHelp:Keyword Index="F" Term="MPoolStats.PagesTrickled" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PagesTrickled" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PagesTrickled" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PagesTrickled" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages written by memp_trickle." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PagesTrickled Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitTxns Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_InitTxns" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_InitTxns" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.InitTxns" /><MSHelp:TOCTitle Title="InitTxns Property " /><MSHelp:RLTitle Title="TransactionStats.InitTxns Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.InitTxns" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassInitTxnsTopic" /><MSHelp:Keyword Index="K" Term="InitTxns property" /><MSHelp:Keyword Index="K" Term="TransactionStats.InitTxns property" /><MSHelp:Keyword Index="F" Term="InitTxns" /><MSHelp:Keyword Index="F" Term="TransactionStats.InitTxns" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.InitTxns" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.InitTxns" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_InitTxns" /><MSHelp:Attr Name="DevLang"

Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initial number of transactions configured." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.InitTxns Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META

HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapFullException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_HeapFullException" /><meta name="guid" content="Fields_T_BerkeleyDB_HeapFullException" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.HeapFullException" /><MSHelp:TOCTitle Title="HeapFullException Fields" /><MSHelp:RLTitle Title="HeapFullException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.HeapFullException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapFullExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="HeapFullException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label

id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapFullException Fields</td></tr><tr id="headerTableRow3"><td align="left">HeapFullException Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryRecnoDatabaseConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_SecondaryRecnoDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:TOCTitle Title="SecondaryRecnoDatabaseConfig Members" /><MSHelp:RLTitle Title="SecondaryRecnoDatabaseConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig class" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabaseConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig class" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabaseConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabaseConfig" /><MSHelp:Attr Name="HelpPriority" Value="1"

/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable"

cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabaseConfig Members</td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabaseConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MappedPages Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolFileStats_MappedPages" /><meta name="guid" content="P_BerkeleyDB_MPoolFileStats_MappedPages" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolFileStats.MappedPages" /><MSHelp:TOCTitle Title="MappedPages Property " /><MSHelp:RLTitle Title="MPoolFileStats.MappedPages Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolFileStats.MappedPages" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolFileStatsClassMappedPagesTopic" /><MSHelp:Keyword Index="K" Term="MappedPages property" /><MSHelp:Keyword Index="K" Term="MPoolFileStats.MappedPages property" /><MSHelp:Keyword Index="F" Term="MappedPages" /><MSHelp:Keyword Index="F" Term="MPoolFileStats.MappedPages" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolFileStats.MappedPages" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.MappedPages" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolFileStats.get_MappedPages" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages from mapped files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolFileStats..::.MappedPages Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolFileStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintMutexSystemStats Method (Boolean, Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
 </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintMutexSystemStats_1" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintMutexSystemStats_1" /><xml><MSHelp:Attr Name="AssetID"

Value="M:BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats(System.Boolean,System.Boolean)" /><MSHelp:TOCTitle Title="PrintMutexSystemStats Method (Boolean, Boolean)" /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintMutexSystemStats Method (Boolean, Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats(System.Boolean,System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintMutexSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the mutex subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment.<span

class="vb">.::.PrintMutexSystemStats Method (Boolean, Boolean)</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashCursor Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_HashCursor" /><meta name="guid" content="T_BerkeleyDB_HashCursor" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.HashCursor" /><MSHelp:TOCTitle Title="HashCursor Class" /><MSHelp:RLTitle Title="HashCursor Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.HashCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashCursorClassTopic" /><MSHelp:Keyword Index="K" Term="HashCursor class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.HashCursor class" /><MSHelp:Keyword Index="K" Term="HashCursor class,
about HashCursor class" /><MSHelp:Keyword Index="F" Term="HashCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashCursor" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashCursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class for traversing the records of a" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashCursor Class</td></tr><tr id="headerTableRow3"><td align="left">Members
See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxTransactions Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_MaxTransactions" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_MaxTransactions" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.MaxTransactions" /><MSHelp:TOCTitle Title="MaxTransactions Property " /><MSHelp:RLTitle Title="TransactionStats.MaxTransactions Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.MaxTransactions" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassMaxTransactionsTopic" /><MSHelp:Keyword Index="K" Term="MaxTransactions property" /><MSHelp:Keyword Index="K" Term="TransactionStats.MaxTransactions property" /><MSHelp:Keyword Index="F" Term="MaxTransactions" /><MSHelp:Keyword Index="F" Term="TransactionStats.MaxTransactions" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.MaxTransactions" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.MaxTransactions" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_MaxTransactions" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"

/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Maximum txns possible" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.MaxTransactions Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SecondaryQueueDatabase Methods </title><link rel="stylesheet"

type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_SecondaryQueueDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_SecondaryQueueDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:TOCTitle Title="SecondaryQueueDatabase Methods " /><MSHelp:RLTitle Title="SecondaryQueueDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.SecondaryQueueDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">SecondaryQueueDatabase Methods </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_SecondaryQueueDatabase.htm">SecondaryQueueDatabase Class <a
href="#seeAlsoToggle" onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>ContinueAfterFail Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_LogVerifyConfig_ContinueAfterFail" /><meta name="guid"
content="P_BerkeleyDB_LogVerifyConfig_ContinueAfterFail" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LogVerifyConfig.ContinueAfterFail" /><MSHelp:TOCTitle Title="ContinueAfterFail
Property " /><MSHelp:RLTitle Title="LogVerifyConfig.ContinueAfterFail Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogVerifyConfig.ContinueAfterFail"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogVerifyConfigClassContinueAfterFailTopic"
/><MSHelp:Keyword Index="K" Term="ContinueAfterFail property" /><MSHelp:Keyword Index="K"
Term="LogVerifyConfig.ContinueAfterFail property" /><MSHelp:Keyword Index="F" Term="ContinueAfterFail"
/><MSHelp:Keyword Index="F" Term="LogVerifyConfig.ContinueAfterFail" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LogVerifyConfig.ContinueAfterFail" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogVerifyConfig.ContinueAfterFail" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogVerifyConfig.get_ContinueAfterFail" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.LogVerifyConfig.set_ContinueAfterFail" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Whether continue verifying after a failed check." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogVerifyConfig..::.ContinueAfterFail Property </td></tr><tr id="headerTableRow3"><td align="left">LogVerifyConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MutexConfig

Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_MutexConfig" /><meta name="guid" content="T_BerkeleyDB_MutexConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.MutexConfig" /><MSHelp:TOCTitle Title="MutexConfig Class" /><MSHelp:RLTitle Title="MutexConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.MutexConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigClassTopic" /><MSHelp:Keyword Index="K" Term="MutexConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.MutexConfig class" /><MSHelp:Keyword Index="K" Term="MutexConfig class, about MutexConfig class" /><MSHelp:Keyword Index="F" Term="MutexConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for a 's mutex subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, RecnoDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_RecnoDatabase_Open" /><meta name="guid" content="M_BerkeleyDB_RecnoDatabase_Open" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.RecnoDatabase.Open(System.String,BerkeleyDB.RecnoDatabaseConfig)" /><MSHelp:TOCTitle Title="Open Method (String, RecnoDatabaseConfig)" /><MSHelp:RLTitle Title="RecnoDatabase.Open Method (String, RecnoDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.RecnoDatabase.Open(System.String,BerkeleyDB.RecnoDatabaseConfig)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new RecnoDatabase object and open the database represented by
." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;"

src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Open Method (String, RecnoDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>GetBoth Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_GetBoth" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_GetBoth" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.GetBoth" /><MSHelp:TOCTitle Title="GetBoth Method " /><MSHelp:RLTitle Title="HeapDatabase.GetBoth Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.GetBoth" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBHeapDatabaseClassGetBothTopic" /><MSHelp:Keyword Index="K" Term="GetBoth method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.GetBoth method" /><MSHelp:Keyword Index="F" Term="GetBoth" /><MSHelp:Keyword Index="F" Term="HeapDatabase.GetBoth" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.GetBoth" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"

onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
/> <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.GetBoth Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Begun Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ActiveTransaction_Begun" /><meta name="guid" content="P_BerkeleyDB_ActiveTransaction_Begun"
/><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ActiveTransaction.Begun" /><MSHelp:TOCTitle Title="Begun Property " /><MSHelp:RLTitle Title="ActiveTransaction.Begun Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ActiveTransaction.Begun" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBActiveTransactionClassBegunTopic" /><MSHelp:Keyword Index="K" Term="Begun property" /><MSHelp:Keyword Index="K" Term="ActiveTransaction.Begun property" /><MSHelp:Keyword Index="F" Term="Begun" /><MSHelp:Keyword Index="F" Term="ActiveTransaction.Begun" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ActiveTransaction.Begun" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.Begun" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ActiveTransaction.get_Begun" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The current log sequence number when the transaction was begun." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ActiveTransaction.<span
class="vb">.::.Begun Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ActiveTransaction.htm">ActiveTransaction Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RepProcMsgResult Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RepProcMsgResult" /><meta name="guid"

content="T_BerkeleyDB_RepProcMsgResult" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RepProcMsgResult" /><MSHelp:TOCTitle Title="RepProcMsgResult Class" /><MSHelp:RLTitle Title="RepProcMsgResult Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RepProcMsgResult" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRepProcMsgResultClassTopic" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RepProcMsgResult class" /><MSHelp:Keyword Index="K" Term="RepProcMsgResult class, about RepProcMsgResult class" /><MSHelp:Keyword Index="F" Term="RepProcMsgResult" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RepProcMsgResult" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RepProcMsgResult" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing the return value of ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RepProcMsgResult Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_RecnoStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_RecnoStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.RecnoStats" /><MSHelp:TOCTitle Title="RecnoStats Members" /><MSHelp:RLTitle Title="RecnoStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.RecnoStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="RecnoStats class" /><MSHelp:Keyword Index="K" Term="RecnoStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.RecnoStats class" /><MSHelp:Keyword Index="F" Term="RecnoStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input id="ProtectedCheckbox" type="checkbox"
data="Protected" value="on" onClick="SetMemberOptions(this,
'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">RecnoStats Members</td></tr><tr id="headerTableRow3"><td
align="left">RecnoStats Class <a href="#methodTableToggle"
onclick="OpenSection(methodTableToggle)">Methods <a href="#propertyTableToggle"
onclick="OpenSection(propertyTableToggle)">Properties <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Exists Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_SecondaryQueueDatabase_Exists" /><meta name="guid"

content="Overload_BerkeleyDB_SecondaryQueueDatabase_Exists" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryQueueDatabase.Exists" /><MSHelp:TOCTitle Title="Exists Method " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Exists Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryQueueDatabase.Exists" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassExistsTopic" /><MSHelp:Keyword Index="K" Term="Exists method" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Exists method" /><MSHelp:Keyword Index="F" Term="Exists" /><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Exists" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Exists" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Exists Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DetectDeadlocks Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_DetectDeadlocks" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_DetectDeadlocks" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.DetectDeadlocks(BerkeleyDB.DeadlockPolicy)" /><MSHelp:TOCTitle Title="DetectDeadlocks Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.DetectDeadlocks Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.DetectDeadlocks(BerkeleyDB.DeadlockPolicy)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassDetectDeadlocksTopic" /><MSHelp:Keyword Index="K" Term="DetectDeadlocks method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.DetectDeadlocks method" /><MSHelp:Keyword Index="F" Term="DetectDeadlocks" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.DetectDeadlocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.DetectDeadlocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.DetectDeadlocks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Run one iteration of the deadlock detector. The deadlock detector traverses the lock table and marks one of the participating lock requesters for rejection in each deadlock it finds." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.DetectDeadlocks Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, String, RecnoDatabaseConfig)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_RecnoDatabase_Open_2" /><meta name="guid"
content="M_BerkeleyDB_RecnoDatabase_Open_2" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.RecnoDatabase.Open(System.String,System.String,BerkeleyDB.RecnoDatabaseConfig)"
/><MSHelp:TOCTitle Title="Open Method (String, String, RecnoDatabaseConfig)" /><MSHelp:RLTitle
Title="RecnoDatabase.Open Method (String, String, RecnoDatabaseConfig) (BerkeleyDB)" /><MSHelp:Keyword
Index="A"
Term="M:BerkeleyDB.RecnoDatabase.Open(System.String,System.String,BerkeleyDB.RecnoDatabaseConfig)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Open"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="Instantiate a new RecnoDatabase object and open the database
represented by and ." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Open Method (String, String, RecnoDatabaseConfig)</td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashLockNoWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_HashLockNoWait" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_HashLockNoWait" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.HashLockNoWait" /><MSHelp:TOCTitle Title="HashLockNoWait Property " /><MSHelp:RLTitle Title="MPoolStats.HashLockNoWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.HashLockNoWait" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassHashLockNoWaitTopic" /><MSHelp:Keyword Index="K" Term="HashLockNoWait property" /><MSHelp:Keyword Index="K" Term="MPoolStats.HashLockNoWait property" /><MSHelp:Keyword Index="F" Term="HashLockNoWait" /><MSHelp:Keyword Index="F" Term="MPoolStats.HashLockNoWait" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.HashLockNoWait" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.HashLockNoWait" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_HashLockNoWait" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Hash lock granted with nowait." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.HashLockNoWait Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Sequence_Remove" /><meta name="guid" content="M_BerkeleyDB_Sequence_Remove" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Sequence.Remove" /><MSHelp:TOCTitle Title="Remove Method " /><MSHelp:RLTitle

Title="Sequence.Remove Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Sequence.Remove" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Sequence.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Remove the sequence from the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Sequence..::.Remove Method </td></tr><tr id="headerTableRow3"><td align="left">Sequence Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"

xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>Compare Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_BaseCursor_Compare" /><meta name="guid"
content="M_BerkeleyDB_BaseCursor_Compare" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BaseCursor.Compare(BerkeleyDB.Cursor)"
/><MSHelp:TOCTitle Title="Compare Method " /><MSHelp:RLTitle Title="BaseCursor.Compare Method
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BaseCursor.Compare(BerkeleyDB.Cursor)" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseCursorClassCompareTopic" /><MSHelp:Keyword Index="K" Term="Compare
method" /><MSHelp:Keyword Index="K" Term="BaseCursor.Compare method" /><MSHelp:Keyword Index="F"
Term="Compare" /><MSHelp:Keyword Index="F" Term="BaseCursor.Compare" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseCursor.Compare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseCursor.Compare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Compare this cursor's position to another's." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy
image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label

id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseCursor..::.Compare Method </td></tr><tr id="headerTableRow3"><td align="left">BaseCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Begun Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_TransactionStats_Begun" /><meta name="guid" content="P_BerkeleyDB_TransactionStats_Begun" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.TransactionStats.Begun" /><MSHelp:TOCTitle Title="Begun Property " /><MSHelp:RLTitle Title="TransactionStats.Begun Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.TransactionStats.Begun" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionStatsClassBegunTopic" /><MSHelp:Keyword Index="K" Term="Begun property" /><MSHelp:Keyword Index="K" Term="TransactionStats.Begun property" /><MSHelp:Keyword Index="F" Term="Begun" /><MSHelp:Keyword Index="F" Term="TransactionStats.Begun" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.TransactionStats.Begun" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.Begun" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.TransactionStats.get_Begun" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="Abstract" Value="Number of begun transactions" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">TransactionStats..::.Begun Property </td></tr><tr id="headerTableRow3"><td align="left">TransactionStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyRange Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"

src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="T_BerkeleyDB_KeyRange" /><meta name="guid" content="T_BerkeleyDB_KeyRange"
/><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.KeyRange" /><MSHelp:TOCTitle
Title="KeyRange Class" /><MSHelp:RLTitle Title="KeyRange Class (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="T:BerkeleyDB.KeyRange" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBKeyRangeClassTopic" /><MSHelp:Keyword Index="K" Term="KeyRange class"
/><MSHelp:Keyword Index="K" Term="BerkeleyDB.KeyRange class" /><MSHelp:Keyword Index="K"
Term="KeyRange class, about KeyRange class" /><MSHelp:Keyword Index="F" Term="KeyRange"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.KeyRange" /><MSHelp:Attr Name="HelpPriority"
Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.KeyRange" /><MSHelp:Attr
Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class
representing an estimate of the proportion of keys that are less than, equal to, and greater than a given key. Values
are in the range of 0 to 1; for example, if the fi ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>
  <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">KeyRange Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Create Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Create" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_Create" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.Create" /><MSHelp:TOCTitle Title="Create Field" /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.Create Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseEnvironmentConfig.Create" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassCreateTopic" /><MSHelp:Keyword Index="K" Term="Create field" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.Create field" /><MSHelp:Keyword Index="F" Term="Create" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.Create" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.Create" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.Create" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB subsystems will create any underlying files, as necessary." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"

src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.Create Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_HeapDatabaseConfig" /><meta name="guid" content="Fields_T_BerkeleyDB_HeapDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Fields.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:TOCTitle Title="HeapDatabaseConfig Fields"

/><MSHelp:RLTitle Title="HeapDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.HeapDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabaseConfig class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"

onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">HeapDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactData Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_CompactData" /><meta name="guid" content="AllMembers_T_BerkeleyDB_CompactData" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.CompactData" /><MSHelp:TOCTitle Title="CompactData Members" /><MSHelp:RLTitle Title="CompactData Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.CompactData" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactDataMembersTopic" /><MSHelp:Keyword Index="K" Term="CompactData class" /><MSHelp:Keyword Index="K" Term="CompactData class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.CompactData class" /><MSHelp:Keyword Index="F" Term="CompactData" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactData" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span

onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered
</nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactData
Members</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_CompactData.htm">CompactData Class <a href="#methodTableToggle"
onclick="OpenSection(methodTableToggle)">Methods <a href="#propertyTableToggle"
onclick="OpenSection(propertyTableToggle)">Properties <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>SecondaryRecnoDatabase Properties </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-

help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_SecondaryRecnoDatabase"
/><meta name="guid" content="Properties_T_BerkeleyDB_SecondaryRecnoDatabase" /><xml><MSHelp:Attr
Name="AssetID" Value="Properties.T:BerkeleyDB.SecondaryRecnoDatabase" /><MSHelp:TOCTitle
Title="SecondaryRecnoDatabase Properties " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase Properties
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.SecondaryRecnoDatabase"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabasePropertiesTopic"
/><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase class, properties" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage"
style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /><div
id="header"><table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"

for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox"
data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase Properties </td></tr><tr id="headerTableRow3"><td align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Priority Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_Cursor_Priority" /><meta name="guid" content="P_BerkeleyDB_Cursor_Priority" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.Cursor.Priority" /><MSHelp:TOCTitle Title="Priority Property " /><MSHelp:RLTitle Title="Cursor.Priority Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.Cursor.Priority" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorClassPriorityTopic" /><MSHelp:Keyword Index="K" Term="Priority property" /><MSHelp:Keyword Index="K" Term="Cursor.Priority property" /><MSHelp:Keyword Index="F" Term="Priority" /><MSHelp:Keyword Index="F" Term="Cursor.Priority" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.Priority" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.get_Priority" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.set_Priority" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"

Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The cache priority for pages referenced by the cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.Priority Property </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>stop Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"

type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CompactConfig_stop" /><meta name="guid" content="F_BerkeleyDB_CompactConfig_stop" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CompactConfig.stop" /><MSHelp:TOCTitle Title="stop Field" /><MSHelp:RLTitle Title="CompactConfig.stop Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CompactConfig.stop" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCompactConfigClassstopTopic" /><MSHelp:Keyword Index="K" Term="stop field" /><MSHelp:Keyword Index="K" Term="CompactConfig.stop field" /><MSHelp:Keyword Index="F" Term="stop" /><MSHelp:Keyword Index="F" Term="CompactConfig.stop" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CompactConfig.stop" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CompactConfig.stop" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If non-null, the stopping point for compaction. For a Btree or Recno database compaction will stop at the page with the smallest key greater than the stopping point. For a Hash database compactio ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig..::.stop Field</td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Length Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryQueueDatabase_Length" /><meta name="guid" content="P_BerkeleyDB_SecondaryQueueDatabase_Length" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryQueueDatabase.Length" /><MSHelp:TOCTitle Title="Length Property " /><MSHelp:RLTitle Title="SecondaryQueueDatabase.Length Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryQueueDatabase.Length" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryQueueDatabaseClassLengthTopic" /><MSHelp:Keyword Index="K" Term="Length property" /><MSHelp:Keyword Index="K" Term="SecondaryQueueDatabase.Length property" /><MSHelp:Keyword Index="F" Term="Length"
/><MSHelp:Keyword Index="F" Term="SecondaryQueueDatabase.Length" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryQueueDatabase.Length" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.Length" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryQueueDatabase.get_Length" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The length of records in the database." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandAllImage"

style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryQueueDatabase..::.Length Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryQueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RepSync Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="M_BerkeleyDB_DatabaseEnvironment_RepSync" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_RepSync" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.RepSync" /><MSHelp:TOCTitle Title="RepSync Method "
/><MSHelp:RLTitle Title="DatabaseEnvironment.RepSync Method (BerkeleyDB)" /><MSHelp:Keyword
Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.RepSync"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassRepSyncTopic"
/><MSHelp:Keyword Index="K" Term="RepSync method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.RepSync method" /><MSHelp:Keyword Index="F" Term="RepSync"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.RepSync" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.RepSync" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.RepSync" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Force master
synchronization to begin for this client." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr

id="headerTableRow1"><td
 align="left">Berkeley DB .NET API Documentation</td></tr><tr
id="headerTableRow2"><td align="left">DatabaseEnvironment<span
class="languageSpecificText">..<span
class="cpp">::.RepSync Method </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html;
 charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>NumTestAndSetSpins Property
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_MutexConfig_NumTestAndSetSpins" /><meta name="guid"
content="P_BerkeleyDB_MutexConfig_NumTestAndSetSpins" /><xml><MSHelp:Attr Name="AssetID"
 Value="P:BerkeleyDB.MutexConfig.NumTestAndSetSpins" /><MSHelp:TOCTitle Title="NumTestAndSetSpins
Property " /><MSHelp:RLTitle Title="MutexConfig.NumTestAndSetSpins Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MutexConfig.NumTestAndSetSpins"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMutexConfigClassNumTestAndSetSpinsTopic"
/><MSHelp:Keyword Index="K" Term="NumTestAndSetSpins property" /><MSHelp:Keyword Index="K"
Term="MutexConfig.NumTestAndSetSpins property" /><MSHelp:Keyword Index="F"
Term="NumTestAndSetSpins" /><MSHelp:Keyword Index="F" Term="MutexConfig.NumTestAndSetSpins"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.MutexConfig.NumTestAndSetSpins" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MutexConfig.NumTestAndSetSpins" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.MutexConfig.get_NumTestAndSetSpins" /><MSHelp:Attr
Name="APIName"
 Value="BerkeleyDB.MutexConfig.set_NumTestAndSetSpins" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="The number of spins test-and-set mutexes should execute before blocking." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none;

height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MutexConfig..::.NumTestAndSetSpins Property </td></tr><tr id="headerTableRow3"><td align="left">MutexConfig Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataFlags Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file"

content="P_BerkeleyDB_BTreeStats_MetadataFlags" /><meta name="guid"
content="P_BerkeleyDB_BTreeStats_MetadataFlags" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BTreeStats.MetadataFlags" /><MSHelp:TOCTitle Title="MetadataFlags Property "
/><MSHelp:RLTitle Title="BTreeStats.MetadataFlags Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BTreeStats.MetadataFlags" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBTreeStatsClassMetadataFlagsTopic" /><MSHelp:Keyword Index="K"
Term="MetadataFlags property" /><MSHelp:Keyword Index="K" Term="BTreeStats.MetadataFlags property"
/><MSHelp:Keyword Index="F" Term="MetadataFlags" /><MSHelp:Keyword Index="F"
Term="BTreeStats.MetadataFlags"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeStats.MetadataFlags" /><MSHelp:Attr
Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeStats.MetadataFlags" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.BTreeStats.get_MetadataFlags" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="Metadata flags." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"

for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeStats..::.MetadataFlags Property </td></tr><tr id="headerTableRow3"><td align="left">BTreeStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Snapshot Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoDatabase_Snapshot" /><meta name="guid" content="P_BerkeleyDB_RecnoDatabase_Snapshot" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoDatabase.Snapshot" /><MSHelp:TOCTitle Title="Snapshot Property " /><MSHelp:RLTitle Title="RecnoDatabase.Snapshot Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoDatabase.Snapshot" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassSnapshotTopic" /><MSHelp:Keyword Index="K" Term="Snapshot property" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Snapshot property" /><MSHelp:Keyword Index="F" Term="Snapshot" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Snapshot" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Snapshot" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.Snapshot" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoDatabase.get_Snapshot" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, any file will be read in its entirety when is called. If false, may be read lazily." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley
DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">RecnoDatabase.<span
class="vb">.::.Snapshot Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_RecnoDatabase.htm">RecnoDatabase Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IsolationDegree
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_CursorConfig_IsolationDegree" /><meta name="guid"
content="F_BerkeleyDB_CursorConfig_IsolationDegree" /><xml><MSHelp:Attr Name="AssetID"
Value="F:BerkeleyDB.CursorConfig.IsolationDegree" /><MSHelp:TOCTitle
Title="IsolationDegree Field" /><MSHelp:RLTitle Title="CursorConfig.IsolationDegree Field (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CursorConfig.IsolationDegree" /><MSHelp:Keyword
Index="A" Term="frlrfBerkeleyDBCursorConfigClassIsolationDegreeTopic" /><MSHelp:Keyword Index="K"

Term="IsolationDegree field" /><MSHelp:Keyword Index="K" Term="CursorConfig.IsolationDegree field" /><MSHelp:Keyword Index="F" Term="IsolationDegree" /><MSHelp:Keyword Index="F" Term="CursorConfig.IsolationDegree" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CursorConfig.IsolationDegree" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CursorConfig.IsolationDegree" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The isolation degree the cursor should use." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CursorConfig..::.IsolationDegree Field</td></tr><tr id="headerTableRow3"><td align="left">CursorConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PagesCreatedInCache Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_MPoolStats_PagesCreatedInCache" /><meta name="guid" content="P_BerkeleyDB_MPoolStats_PagesCreatedInCache" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.MPoolStats.PagesCreatedInCache" /><MSHelp:TOCTitle Title="PagesCreatedInCache Property " /><MSHelp:RLTitle Title="MPoolStats.PagesCreatedInCache Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.MPoolStats.PagesCreatedInCache" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBMPoolStatsClassPagesCreatedInCacheTopic" /><MSHelp:Keyword Index="K" Term="PagesCreatedInCache property" /><MSHelp:Keyword Index="K" Term="MPoolStats.PagesCreatedInCache property" /><MSHelp:Keyword Index="F" Term="PagesCreatedInCache" /><MSHelp:Keyword Index="F" Term="MPoolStats.PagesCreatedInCache" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.MPoolStats.PagesCreatedInCache" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.PagesCreatedInCache" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.MPoolStats.get_PagesCreatedInCache" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Pages created in the cache." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>

   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">MPoolStats..::.PagesCreatedInCache Property </td></tr><tr id="headerTableRow3"><td align="left">MPoolStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ReplicationStats Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_ReplicationStats" /><meta name="guid" content="AllMembers_T_BerkeleyDB_ReplicationStats" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.ReplicationStats" /><MSHelp:TOCTitle Title="ReplicationStats Members" /><MSHelp:RLTitle Title="ReplicationStats Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.ReplicationStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsMembersTopic" /><MSHelp:Keyword Index="K" Term="ReplicationStats class" /><MSHelp:Keyword Index="K" Term="ReplicationStats class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.ReplicationStats class" /><MSHelp:Keyword Index="F" Term="ReplicationStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp"

/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members:
Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <div
id="memberOptionsMenu"><input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on"
onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats Members</td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class Methods
  Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RetransmissionRequest Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
 </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_ReplicationConfig_RetransmissionRequest" /><meta name="guid" content="M_BerkeleyDB_ReplicationConfig_RetransmissionRequest" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.ReplicationConfig.RetransmissionRequest(System.UInt32,System.UInt32)" /><MSHelp:TOCTitle Title="RetransmissionRequest Method " /><MSHelp:RLTitle Title="ReplicationConfig.RetransmissionRequest Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.ReplicationConfig.RetransmissionRequest(System.UInt32,System.UInt32)" /><MSHelp:Keyword
 Index="A" Term="frlrfBerkeleyDBReplicationConfigClassRetransmissionRequestTopic" /><MSHelp:Keyword Index="K" Term="RetransmissionRequest method" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.RetransmissionRequest method" /><MSHelp:Keyword Index="F" Term="RetransmissionRequest" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.RetransmissionRequest" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.RetransmissionRequest" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.RetransmissionRequest" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set a threshold for the minimum and maximum
 time that a client waits before requesting retransmission of a missing message." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple
</nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">ReplicationConfig.<span
class="vb">.::.RetransmissionRequest
Method </td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_ReplicationConfig.htm">ReplicationConfig Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Creation
Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_Creation"
/><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_Creation"
/><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.Creation"
/><MSHelp:TOCTitle Title="Creation Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.Creation

Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.Creation" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassCreationTopic" /><MSHelp:Keyword Index="K"
Term="Creation field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.Creation field"
/><MSHelp:Keyword Index="F" Term="Creation" /><MSHelp:Keyword Index="F"
Term="SecondaryBTreeDatabaseConfig.Creation" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.Creation" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.Creation"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The policy for how to handle database creation." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">SecondaryBTreeDatabaseConfig<span
class="cs">..::<span

class="nu">.Creation Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MagicNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueStats_MagicNumber" /><meta name="guid" content="P_BerkeleyDB_QueueStats_MagicNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueStats.MagicNumber" /><MSHelp:TOCTitle Title="MagicNumber Property " /><MSHelp:RLTitle Title="QueueStats.MagicNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueStats.MagicNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueStatsClassMagicNumberTopic" /><MSHelp:Keyword Index="K" Term="MagicNumber property" /><MSHelp:Keyword Index="K" Term="QueueStats.MagicNumber property" /><MSHelp:Keyword Index="F" Term="MagicNumber" /><MSHelp:Keyword Index="F" Term="QueueStats.MagicNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueStats.MagicNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.MagicNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueStats.get_MagicNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Magic number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <span

id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">QueueStats.<span
class="vb">.::.MagicNumber Property
</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_QueueStats.htm">QueueStats Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>QueueDatabaseConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Fields_T_BerkeleyDB_QueueDatabaseConfig" /><meta name="guid"
content="Fields_T_BerkeleyDB_QueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:TOCTitle Title="QueueDatabaseConfig Fields"
/><MSHelp:RLTitle Title="QueueDatabaseConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBQueueDatabaseConfigFieldsTopic" /><MSHelp:Keyword Index="K"
Term="QueueDatabaseConfig
class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"

id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Delete Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_BTreeDatabase_Delete" /><meta name="guid" content="Overload_BerkeleyDB_BTreeDatabase_Delete" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.BTreeDatabase.Delete" /><MSHelp:TOCTitle Title="Delete Method " /><MSHelp:RLTitle Title="BTreeDatabase.Delete Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.BTreeDatabase.Delete" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseClassDeleteTopic" /><MSHelp:Keyword Index="K" Term="Delete method" /><MSHelp:Keyword Index="K" Term="BTreeDatabase.Delete method" /><MSHelp:Keyword Index="F" Term="Delete" /><MSHelp:Keyword Index="F" Term="BTreeDatabase.Delete" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabase.Delete" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabase..::.Delete Method </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (UInt32, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultiple_1" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultiple_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveMultiple Method (UInt32, LockingInfo)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultiple Method (UInt32, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32,BerkeleyDB.LockingInfo)" /><MSHelp:Attr

Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor..::.MoveMultiple Method (UInt32, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>EncryptAlgorithm Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironmentConfig_EncryptAlgorithm" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironmentConfig_EncryptAlgorithm" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironmentConfig.EncryptAlgorithm" /><MSHelp:TOCTitle Title="EncryptAlgorithm Property " /><MSHelp:RLTitle Title="DatabaseEnvironmentConfig.EncryptAlgorithm Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironmentConfig.EncryptAlgorithm" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassEncryptAlgorithmTopic" /><MSHelp:Keyword Index="K" Term="EncryptAlgorithm property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironmentConfig.EncryptAlgorithm property" /><MSHelp:Keyword Index="F" Term="EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironmentConfig.EncryptAlgorithm" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironmentConfig.EncryptAlgorithm" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.EncryptAlgorithm" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.get_EncryptAlgorithm" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The algorithm used to perform encryption and decryption." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironmentConfig..::.EncryptAlgorithm Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MetadataFlags Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HashStats_MetadataFlags" /><meta name="guid" content="P_BerkeleyDB_HashStats_MetadataFlags" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HashStats.MetadataFlags" /><MSHelp:TOCTitle Title="MetadataFlags Property " /><MSHelp:RLTitle Title="HashStats.MetadataFlags Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HashStats.MetadataFlags" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashStatsClassMetadataFlagsTopic" /><MSHelp:Keyword Index="K" Term="MetadataFlags property" /><MSHelp:Keyword Index="K" Term="HashStats.MetadataFlags property" /><MSHelp:Keyword Index="F" Term="MetadataFlags" /><MSHelp:Keyword Index="F" Term="HashStats.MetadataFlags" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashStats.MetadataFlags" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.MetadataFlags" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashStats.get_MetadataFlags" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Metadata flags." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyImage" style="display:none;
height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashStats..::.MetadataFlags Property </td></tr><tr id="headerTableRow3"><td align="left">HashStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"

xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>DatabaseName Property </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="P_BerkeleyDB_BaseDatabase_DatabaseName"
/><meta name="guid" content="P_BerkeleyDB_BaseDatabase_DatabaseName" /><xml><MSHelp:Attr
Name="AssetID" Value="P:BerkeleyDB.BaseDatabase.DatabaseName" /><MSHelp:TOCTitle
Title="DatabaseName Property " /><MSHelp:RLTitle Title="BaseDatabase.DatabaseName Property
(BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.BaseDatabase.DatabaseName"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBaseDatabaseClassDatabaseNameTopic"
/><MSHelp:Keyword Index="K" Term="DatabaseName property" /><MSHelp:Keyword Index="K"
Term="BaseDatabase.DatabaseName property" /><MSHelp:Keyword Index="F" Term="DatabaseName"
/><MSHelp:Keyword Index="F" Term="BaseDatabase.DatabaseName" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseDatabase.DatabaseName" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.DatabaseName" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_DatabaseName"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="The name of this database, if it has one." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"

for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.DatabaseName Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockingConfig Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LockingConfig" /><meta name="guid" content="T_BerkeleyDB_LockingConfig" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LockingConfig" /><MSHelp:TOCTitle Title="LockingConfig Class" /><MSHelp:RLTitle Title="LockingConfig Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LockingConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockingConfigClassTopic" /><MSHelp:Keyword Index="K" Term="LockingConfig class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockingConfig class" /><MSHelp:Keyword Index="K" Term="LockingConfig class, about LockingConfig class" /><MSHelp:Keyword Index="F" Term="LockingConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockingConfig" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockingConfig" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A class representing configuration parameters for a 's locking subsystem." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input

type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse
All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockingConfig Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Encrypted Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">

</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseConfig_Encrypted" /><meta name="guid" content="P_BerkeleyDB_DatabaseConfig_Encrypted" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseConfig.Encrypted" /><MSHelp:TOCTitle Title="Encrypted Property " /><MSHelp:RLTitle Title="DatabaseConfig.Encrypted Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseConfig.Encrypted" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseConfigClassEncryptedTopic" /><MSHelp:Keyword Index="K" Term="Encrypted property" /><MSHelp:Keyword Index="K" Term="DatabaseConfig.Encrypted property" /><MSHelp:Keyword Index="F" Term="Encrypted" /><MSHelp:Keyword Index="F" Term="DatabaseConfig.Encrypted" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseConfig.Encrypted" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.Encrypted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.get_Encrypted" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseConfig.set_Encrypted" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Encrypt the database using the cryptographic password specified by DatabaseConfig.SetEncryption or DatabaseEnvironmentConfig.SetEncryption." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseConfig..::.Encrypted Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HeapDatabase Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_HeapDatabase" /><meta name="guid" content="Methods_T_BerkeleyDB_HeapDatabase" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.HeapDatabase" /><MSHelp:TOCTitle Title="HeapDatabase Methods " /><MSHelp:RLTitle Title="HeapDatabase Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.HeapDatabase" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseMethodsTopic" /><MSHelp:Keyword Index="K" Term="HeapDatabase class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel"

for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase Methods </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Move Method (KeyValuePair(DatabaseEntry, KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">

</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_SecondaryCursor_Move_5" /><meta name="guid" content="M_BerkeleyDB_SecondaryCursor_Move_5" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.SecondaryCursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry}},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="Move Method (KeyValuePair(DatabaseEntry, KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean, LockingInfo)" /><MSHelp:RLTitle Title="SecondaryCursor.Move Method (KeyValuePair(DatabaseEntry, KeyValuePair(DatabaseEntry, DatabaseEntry)), Boolean, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.SecondaryCursor.Move(System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,System.Collections.Generic.KeyValuePair{BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry}},System.Boolean,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryCursor.Move" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Move the cursor to the specified key/data pair of the database. The cursor is positioned to a key/data pair if both the key and data match the values provided on the key and data parameters." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"

type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
</div><table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.Move Method (KeyValuePair<(Of <(DatabaseEntry, KeyValuePair<(Of <(DatabaseEntry, DatabaseEntry>)>)>)>), Boolean, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RecnoStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_RecnoStats" /><meta name="guid" content="T_BerkeleyDB_RecnoStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.RecnoStats" /><MSHelp:TOCTitle Title="RecnoStats Class" /><MSHelp:RLTitle Title="RecnoStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.RecnoStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassTopic" /><MSHelp:Keyword Index="K" Term="RecnoStats class" /><MSHelp:Keyword
Index="K" Term="BerkeleyDB.RecnoStats class" /><MSHelp:Keyword Index="K" Term="RecnoStats class, about RecnoStats class" /><MSHelp:Keyword Index="F" Term="RecnoStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about a RecnoDatabase" /><MSHelp:Attr Name="AssemblyVersion"

Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CompactConfig Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"

src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_CompactConfig" /><meta
name="guid" content="Fields_T_BerkeleyDB_CompactConfig" /><xml><MSHelp:Attr Name="AssetID"
Value="Fields.T:BerkeleyDB.CompactConfig" /><MSHelp:TOCTitle Title="CompactConfig Fields"
/><MSHelp:RLTitle Title="CompactConfig Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Fields.T:BerkeleyDB.CompactConfig" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBCompactConfigFieldsTopic" /><MSHelp:Keyword Index="K" Term="CompactConfig
class, fields" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none;
height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0;
width:0;" src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table
id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label
id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
C++ </nobr></label> <span id="memberOptionsDropdown" class="filter"
tabindex="0"> <label
id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:
Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected"
value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">CompactConfig Fields</td></tr><tr id="headerTableRow3"><td align="left">CompactConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>ReplicationSystemStats Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_ReplicationSystemStats" /><meta
name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_ReplicationSystemStats"
/><xml><MSHelp:Attr Name="AssetID"
Value="Overload:BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats" /><MSHelp:TOCTitle
Title="ReplicationSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.ReplicationSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="Overload:BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentClassReplicationSystemStatsTopic" /><MSHelp:Keyword Index="K"
Term="ReplicationSystemStats method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.ReplicationSystemStats method" /><MSHelp:Keyword Index="F"
Term="ReplicationSystemStats" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironment.ReplicationSystemStats"
/><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.ReplicationSystemStats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.ReplicationSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLockingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_PrintLockingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:TOCTitle Title="PrintLockingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLockingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.PrintLockingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Display the locking subsystem statistical information, as described by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLockingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MagicNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_MagicNumber" /><meta name="guid" content="P_BerkeleyDB_LogStats_MagicNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LogStats.MagicNumber" /><MSHelp:TOCTitle Title="MagicNumber Property " /><MSHelp:RLTitle Title="LogStats.MagicNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LogStats.MagicNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogStatsClassMagicNumberTopic" /><MSHelp:Keyword Index="K" Term="MagicNumber property" /><MSHelp:Keyword Index="K" Term="LogStats.MagicNumber property" /><MSHelp:Keyword Index="F" Term="MagicNumber" /><MSHelp:Keyword Index="F" Term="LogStats.MagicNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogStats.MagicNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.MagicNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_MagicNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Log file magic number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse

image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.MagicNumber Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DbSite Properties </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Properties_T_BerkeleyDB_DbSite" /><meta name="guid" content="Properties_T_BerkeleyDB_DbSite" /><xml><MSHelp:Attr Name="AssetID" Value="Properties.T:BerkeleyDB.DbSite" /><MSHelp:TOCTitle Title="DbSite Properties " /><MSHelp:RLTitle Title="DbSite Properties (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Properties.T:BerkeleyDB.DbSite" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbSitePropertiesTopic" /><MSHelp:Keyword Index="K" Term="DbSite class, properties" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual

C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span
id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td
align="left">DbSite Properties </td></tr><tr id="headerTableRow3"><td
align="left">DbSite Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>RegionLockWait Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"
/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script
type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script
type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"
content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LogStats_RegionLockWait" /><meta
name="guid" content="P_BerkeleyDB_LogStats_RegionLockWait" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.LogStats.RegionLockWait" /><MSHelp:TOCTitle Title="RegionLockWait Property "
/><MSHelp:RLTitle Title="LogStats.RegionLockWait Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.LogStats.RegionLockWait" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBLogStatsClassRegionLockWaitTopic" /><MSHelp:Keyword Index="K"
Term="RegionLockWait property" /><MSHelp:Keyword Index="K" Term="LogStats.RegionLockWait property"
/><MSHelp:Keyword Index="F" Term="RegionLockWait" /><MSHelp:Keyword Index="F"
Term="LogStats.RegionLockWait" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.LogStats.RegionLockWait" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.RegionLockWait"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LogStats.get_RegionLockWait" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="Region lock granted after wait." /><MSHelp:Attr Name="AssemblyVersion"
Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle"
/><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0;
width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"

src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogStats..::.RegionLockWait Property </td></tr><tr id="headerTableRow3"><td align="left">LogStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryRecnoDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryRecnoDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="SecondaryRecnoDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword

Index="A" Term="Overload:BerkeleyDB.SecondaryRecnoDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryRecnoDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="SecondaryRecnoDatabase.Get method" /><MSHelp:Keyword Index="F"
Term="Get" /><MSHelp:Keyword Index="F" Term="SecondaryRecnoDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryRecnoDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show
All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryRecnoDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td
align="left">SecondaryRecnoDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VERY_HIGH Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script
type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_CachePriority_VERY_HIGH" /><meta name="guid" content="F_BerkeleyDB_CachePriority_VERY_HIGH" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.CachePriority.VERY_HIGH" /><MSHelp:TOCTitle Title="VERY_HIGH Field" /><MSHelp:RLTitle Title="CachePriority.VERY_HIGH Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.CachePriority.VERY_HIGH" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCachePriorityClassVERY_HIGHTopic" /><MSHelp:Keyword Index="K" Term="VERY_HIGH field" /><MSHelp:Keyword Index="K" Term="CachePriority.VERY_HIGH field" /><MSHelp:Keyword Index="F" Term="VERY_HIGH" /><MSHelp:Keyword Index="F" Term="CachePriority.VERY_HIGH" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.CachePriority.VERY_HIGH" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.CachePriority.VERY_HIGH" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The highest priority: pages are the least likely to be discarded." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
title="Collapse image" /><img id="collapseAllImage" style="display:none; height:0;

width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage,
event)" tabindex="0"> <label
id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">CachePriority<span
class="cs">..::<span
class="nu">.VERY_HIGH Field</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_CachePriority.htm">CachePriority Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"
/><title>BTreeDatabaseConfig Methods </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css"
/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript"
src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript"
src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container"

content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_BTreeDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_BTreeDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:TOCTitle Title="BTreeDatabaseConfig Methods " /><MSHelp:RLTitle Title="BTreeDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.BTreeDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MagicNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_RecnoStats_MagicNumber" /><meta name="guid" content="P_BerkeleyDB_RecnoStats_MagicNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.RecnoStats.MagicNumber" /><MSHelp:TOCTitle Title="MagicNumber Property " /><MSHelp:RLTitle Title="RecnoStats.MagicNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.RecnoStats.MagicNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoStatsClassMagicNumberTopic" /><MSHelp:Keyword Index="K" Term="MagicNumber property" /><MSHelp:Keyword Index="K" Term="RecnoStats.MagicNumber property" /><MSHelp:Keyword Index="F" Term="MagicNumber" /><MSHelp:Keyword Index="F" Term="RecnoStats.MagicNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoStats.MagicNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.MagicNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.RecnoStats.get_MagicNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Magic number." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="expandAllImage" style="display:none; height:0;

width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoStats..::.MagicNumber Property </td></tr><tr id="headerTableRow3"><td align="left">RecnoStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LockStats Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_LockStats" /><meta name="guid" content="T_BerkeleyDB_LockStats" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.LockStats"

/><MSHelp:TOCTitle Title="LockStats Class" /><MSHelp:RLTitle Title="LockStats Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.LockStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassTopic" /><MSHelp:Keyword Index="K" Term="LockStats class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LockStats class" /><MSHelp:Keyword Index="K" Term="LockStats class, about LockStats class" /><MSHelp:Keyword Index="F" Term="LockStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Statistical information about the locking subsystem" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats Class</td></tr><tr id="headerTableRow3"><td align="left"><a

href="AllMembers_T_BerkeleyDB_LockStats.htm">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>RANDOM Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DeadlockPolicy_RANDOM" /><meta name="guid" content="F_BerkeleyDB_DeadlockPolicy_RANDOM" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DeadlockPolicy.RANDOM" /><MSHelp:TOCTitle Title="RANDOM Field" /><MSHelp:RLTitle Title="DeadlockPolicy.RANDOM Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DeadlockPolicy.RANDOM" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDeadlockPolicyClassRANDOMTopic" /><MSHelp:Keyword Index="K" Term="RANDOM field" /><MSHelp:Keyword Index="K" Term="DeadlockPolicy.RANDOM field" /><MSHelp:Keyword Index="F" Term="RANDOM" /><MSHelp:Keyword Index="F" Term="DeadlockPolicy.RANDOM" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DeadlockPolicy.RANDOM" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DeadlockPolicy.RANDOM" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Reject the lock request for a random locker ID." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <img

id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DeadlockPolicy..::.RANDOM Field</td></tr><tr id="headerTableRow3"><td align="left">DeadlockPolicy Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>VersionMismatchException Class</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_VersionMismatchException" /><meta name="guid" content="T_BerkeleyDB_VersionMismatchException" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.VersionMismatchException" /><MSHelp:TOCTitle Title="VersionMismatchException Class" /><MSHelp:RLTitle Title="VersionMismatchException Class (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.VersionMismatchException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBVersionMismatchExceptionClassTopic" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.VersionMismatchException class" /><MSHelp:Keyword Index="K" Term="VersionMismatchException class, about VersionMismatchException class" /><MSHelp:Keyword Index="F" Term="VersionMismatchException" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.VersionMismatchException" /><MSHelp:Attr Name="HelpPriority" Value="2" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"

Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.VersionMismatchException" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The version of the Berkeley DB library doesn't match the version that created the database
environment." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none;
height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable"
cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">VersionMismatchException Class</td></tr><tr id="headerTableRow3"><td align="left">Members See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"

xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreePrefixCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_BTreeDatabaseConfig_BTreePrefixCompare" /><meta name="guid" content="F_BerkeleyDB_BTreeDatabaseConfig_BTreePrefixCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.BTreeDatabaseConfig.BTreePrefixCompare" /><MSHelp:TOCTitle Title="BTreePrefixCompare Field" /><MSHelp:RLTitle Title="BTreeDatabaseConfig.BTreePrefixCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.BTreeDatabaseConfig.BTreePrefixCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeDatabaseConfigClassBTreePrefixCompareTopic" /><MSHelp:Keyword Index="K" Term="BTreePrefixCompare field" /><MSHelp:Keyword Index="K" Term="BTreeDatabaseConfig.BTreePrefixCompare field" /><MSHelp:Keyword Index="F" Term="BTreePrefixCompare" /><MSHelp:Keyword Index="F" Term="BTreeDatabaseConfig.BTreePrefixCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeDatabaseConfig.BTreePrefixCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeDatabaseConfig.BTreePrefixCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The Btree prefix function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label

id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.BTreePrefixCompare Field</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MagicNumber Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_HeapStats_MagicNumber" /><meta name="guid" content="P_BerkeleyDB_HeapStats_MagicNumber" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.HeapStats.MagicNumber" /><MSHelp:TOCTitle Title="MagicNumber Property " /><MSHelp:RLTitle Title="HeapStats.MagicNumber Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.HeapStats.MagicNumber" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapStatsClassMagicNumberTopic" /><MSHelp:Keyword Index="K" Term="MagicNumber property" /><MSHelp:Keyword Index="K" Term="HeapStats.MagicNumber property" /><MSHelp:Keyword Index="F" Term="MagicNumber" /><MSHelp:Keyword Index="F" Term="HeapStats.MagicNumber" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapStats.MagicNumber" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.MagicNumber" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HeapStats.get_MagicNumber" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"

Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Magic number that identifies the file as a Heap file." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapStats..::.MagicNumber Property </td></tr><tr id="headerTableRow3"><td align="left">HeapStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history"

/><title>MoveNextDuplicateMultipleKey Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextDuplicateMultipleKey" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:TOCTitle Title="MoveNextDuplicateMultipleKey Method " /><MSHelp:RLTitle Title="Cursor.MoveNextDuplicateMultipleKey Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextDuplicateMultipleKey" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the next key/data pair of the database is a duplicate data record for the current key/data pair, move the cursor to the next key/data pair in the database, and store that pair and as many duplicate data ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"

type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextDuplicateMultipleKey Method </td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor.InsertLocation Enumeration</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="T_BerkeleyDB_Cursor_InsertLocation" /><meta name="guid" content="T_BerkeleyDB_Cursor_InsertLocation" /><xml><MSHelp:Attr Name="AssetID" Value="T:BerkeleyDB.Cursor.InsertLocation" /><MSHelp:TOCTitle Title="Cursor.InsertLocation Enumeration" /><MSHelp:RLTitle Title="Cursor.InsertLocation Enumeration (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="T:BerkeleyDB.Cursor.InsertLocation" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Cursor.InsertLocation.AFTER" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Cursor.InsertLocation.BEFORE" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Cursor.InsertLocation.FIRST" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.Cursor.InsertLocation.LAST" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBCursorInsertLocationClassTopic" /><MSHelp:Keyword Index="K" Term="Cursor.InsertLocation enumeration" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.Cursor.InsertLocation enumeration" /><MSHelp:Keyword Index="K" Term="AFTER enumeration member" /><MSHelp:Keyword Index="K" Term="BEFORE enumeration member" /><MSHelp:Keyword Index="K" Term="FIRST enumeration member" /><MSHelp:Keyword Index="K" Term="LAST enumeration member" /><MSHelp:Keyword Index="F" Term="Cursor.InsertLocation" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.InsertLocation" /><MSHelp:Keyword Index="F" Term="Cursor.InsertLocation.AFTER" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Cursor.InsertLocation.AFTER" /><MSHelp:Keyword Index="F" Term="Cursor.InsertLocation.BEFORE" /><MSHelp:Keyword Index="F"

Term="BerkeleyDB.Cursor.InsertLocation.BEFORE" /><MSHelp:Keyword Index="F"
Term="Cursor.InsertLocation.FIRST" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Cursor.InsertLocation.FIRST"
/><MSHelp:Keyword Index="F" Term="Cursor.InsertLocation.LAST" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.Cursor.InsertLocation.LAST" /><MSHelp:Attr Name="HelpPriority" Value="2"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.InsertLocation"
/><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.InsertLocation.AFTER" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.Cursor.InsertLocation.BEFORE" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.InsertLocation.FIRST" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Cursor.InsertLocation.LAST" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Specifies
where to place duplicate data elements of the key to which the cursor refers." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif"
title="Copy image" /><img id="copyHoverImage" style="display:none; height:0; width:0;"
src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable"
cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"
style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img
ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel"
for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"
for="toggleAllImage" style="display: none;">Expand All</label>   <span
id="devlangsDropdown" class="filter" tabindex="0"><img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API

Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.InsertLocation Enumeration</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
 HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNext Method (LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_JoinCursor_MoveNext_1" /><meta name="guid"
 content="M_BerkeleyDB_JoinCursor_MoveNext_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.JoinCursor.MoveNext(BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveNext Method (LockingInfo)" /><MSHelp:RLTitle Title="JoinCursor.MoveNext Method (LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.JoinCursor.MoveNext(BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.JoinCursor.MoveNext" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Iterate over the values associated with the keys to which each passed to was initialized. Any data value that appears in all s is then used
 as a key into the primary, and the key/da ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage"
 style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown" class="filter"

tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">JoinCursor..::.MoveNext Method (LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">JoinCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Get Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HashDatabase_Get" /><meta name="guid" content="Overload_BerkeleyDB_HashDatabase_Get" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HashDatabase.Get" /><MSHelp:TOCTitle Title="Get Method " /><MSHelp:RLTitle Title="HashDatabase.Get Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HashDatabase.Get" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseClassGetTopic" /><MSHelp:Keyword Index="K" Term="Get method" /><MSHelp:Keyword Index="K" Term="HashDatabase.Get method" /><MSHelp:Keyword Index="F" Term="Get" /><MSHelp:Keyword Index="F" Term="HashDatabase.Get" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabase.Get" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"

/></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td

align="left">HashDatabase..::.Get Method </td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HASH Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseType_HASH" /><meta name="guid" content="F_BerkeleyDB_DatabaseType_HASH" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseType.HASH" /><MSHelp:TOCTitle Title="HASH Field" /><MSHelp:RLTitle Title="DatabaseType.HASH Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.DatabaseType.HASH" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseTypeClassHASHTopic" /><MSHelp:Keyword Index="K" Term="HASH field" /><MSHelp:Keyword Index="K" Term="DatabaseType.HASH field" /><MSHelp:Keyword Index="F" Term="HASH" /><MSHelp:Keyword Index="F" Term="DatabaseType.HASH" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseType.HASH" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseType.HASH" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Hash access method" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span

id="devlangsDropdown" class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseType..::.HASH Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseType Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>LogConfig Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_LogConfig" /><meta name="guid" content="AllMembers_T_BerkeleyDB_LogConfig" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.LogConfig" /><MSHelp:TOCTitle Title="LogConfig Members" /><MSHelp:RLTitle Title="LogConfig Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.LogConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLogConfigMembersTopic" /><MSHelp:Keyword Index="K" Term="LogConfig class" /><MSHelp:Keyword Index="K" Term="LogConfig class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.LogConfig class" /><MSHelp:Keyword Index="F" Term="LogConfig" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LogConfig" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LogConfig Members</td></tr><tr

id="headerTableRow3"><td align="left">LogConfig Class Constructors Methods Fields Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>InitLocks Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_LockStats_InitLocks" /><meta name="guid" content="P_BerkeleyDB_LockStats_InitLocks" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.LockStats.InitLocks" /><MSHelp:TOCTitle Title="InitLocks Property " /><MSHelp:RLTitle Title="LockStats.InitLocks Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.LockStats.InitLocks" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBLockStatsClassInitLocksTopic" /><MSHelp:Keyword Index="K" Term="InitLocks property" /><MSHelp:Keyword Index="K" Term="LockStats.InitLocks property" /><MSHelp:Keyword Index="F" Term="InitLocks" /><MSHelp:Keyword Index="F" Term="LockStats.InitLocks" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.LockStats.InitLocks" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.LockStats.InitLocks" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.LockStats.get_InitLocks" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Initial number of locks allocated." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none; height:0; width:0;"
src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)"

style="cursor:default;" onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <span id="devlangsDropdown"
class="filter" tabindex="0"> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox"
data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">LockStats..::.InitLocks Property </td></tr><tr id="headerTableRow3"><td align="left">LockStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_HeapDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_HeapDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.HeapDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="HeapDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.HeapDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHeapDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="HeapDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="HeapDatabase.PrintStats"

/><MSHelp:Keyword Index="F" Term="BerkeleyDB.HeapDatabase.PrintStats"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif"
/><img id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"><img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label> <span
id="memberOptionsDropdown" class="filter" tabindex="0"><img id="memberOptionsDropdownImage"
src="../icons/dropdown.gif" /> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage"
style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel"
for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel"
for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label
id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display:
none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input
id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"
/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <input
id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"
/><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input
id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')"
/><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table
id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left"><span

id="runningHeaderText">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HeapDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">HeapDatabase Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveMultiple Method (UInt32)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeCursor_MoveMultiple" /><meta name="guid" content="M_BerkeleyDB_BTreeCursor_MoveMultiple" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32)" /><MSHelp:TOCTitle Title="MoveMultiple Method (UInt32)" /><MSHelp:RLTitle Title="BTreeCursor.MoveMultiple Method (UInt32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BTreeCursor.MoveMultiple(System.UInt32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BTreeCursor.MoveMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Position the cursor at a specific key/data pair in the database, and store the key/data pair and as many duplicate data items that can fit in a buffer the size of one database page in ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel"

for="toggleAllImage" style="display: none;">Expand All</label>
<img id="devlangsDropdownImage"
src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">BTreeCursor.<span
class="vb">.::.MoveMultiple Method
(UInt32)</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_BTreeCursor.htm">BTreeCursor Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method
(Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script
type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_HashDatabase_Cursor_3" /><meta name="guid"
content="M_BerkeleyDB_HashDatabase_Cursor_3" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.HashDatabase.Cursor(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor
Method (Transaction)" /><MSHelp:RLTitle Title="HashDatabase.Cursor Method (Transaction) (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Cursor(BerkeleyDB.Transaction)"
/><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation"
Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Cursor"
/><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB"
/><MSHelp:Attr

Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Cursor Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"

CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintLoggingSystemStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintLoggingSystemStats" /><meta name="guid" content="Overload_BerkeleyDB_DatabaseEnvironment_PrintLoggingSystemStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:TOCTitle Title="PrintLoggingSystemStats Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.PrintLoggingSystemStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPrintLoggingSystemStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintLoggingSystemStats method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.PrintLoggingSystemStats method" /><MSHelp:Keyword Index="F" Term="PrintLoggingSystemStats" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.PrintLoggingSystemStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual

Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.PrintLoggingSystemStats Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>HashFunction Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_HashDatabaseConfig_HashFunction" /><meta name="guid" content="F_BerkeleyDB_HashDatabaseConfig_HashFunction" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.HashDatabaseConfig.HashFunction" /><MSHelp:TOCTitle Title="HashFunction Field" /><MSHelp:RLTitle Title="HashDatabaseConfig.HashFunction Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.HashDatabaseConfig.HashFunction" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBHashDatabaseConfigClassHashFunctionTopic" /><MSHelp:Keyword Index="K"

Term="HashFunction
field" /><MSHelp:Keyword Index="K" Term="HashDatabaseConfig.HashFunction field" /><MSHelp:Keyword Index="F" Term="HashFunction" /><MSHelp:Keyword Index="F" Term="HashDatabaseConfig.HashFunction" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.HashDatabaseConfig.HashFunction" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabaseConfig.HashFunction" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="A user-defined hash function; if no hash function is specified, a default hash function is used." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabaseConfig..<span

class="cpp">::.HashFunction Field</td></tr><tr id="headerTableRow3"><td align="left">HashDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DuplicateCompare Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_DuplicateCompare" /><meta name="guid" content="F_BerkeleyDB_SecondaryBTreeDatabaseConfig_DuplicateCompare" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.DuplicateCompare" /><MSHelp:TOCTitle Title="DuplicateCompare Field" /><MSHelp:RLTitle Title="SecondaryBTreeDatabaseConfig.DuplicateCompare Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.SecondaryBTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryBTreeDatabaseConfigClassDuplicateCompareTopic" /><MSHelp:Keyword Index="K" Term="DuplicateCompare field" /><MSHelp:Keyword Index="K" Term="SecondaryBTreeDatabaseConfig.DuplicateCompare field" /><MSHelp:Keyword Index="F" Term="DuplicateCompare" /><MSHelp:Keyword Index="F" Term="SecondaryBTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryBTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryBTreeDatabaseConfig.DuplicateCompare" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The duplicate data item comparison function." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0"

cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryBTreeDatabaseConfig..::.DuplicateCompare Field</td></tr><tr id="headerTableRow3"><td align="left">SecondaryBTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrevUnique Method (DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script
type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MovePrevUnique_1" /><meta name="guid" content="M_BerkeleyDB_Cursor_MovePrevUnique_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MovePrevUnique Method (DatabaseEntry, DatabaseEntry)" /><MSHelp:RLTitle Title="Cursor.MovePrevUnique Method (DatabaseEntry, DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"

Term="M:BerkeleyDB.Cursor.MovePrevUnique(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MovePrevUnique" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MovePrevUnique is identical to . Otherwise, move the cursor to the previous non-duplicate key in the database, and store that key and associated datum in . Mo ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MovePrevUnique Method (DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See

Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SendMessage Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DbChannel_SendMessage" /><meta name="guid" content="M_BerkeleyDB_DbChannel_SendMessage" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DbChannel.SendMessage(BerkeleyDB.DatabaseEntry[])" /><MSHelp:TOCTitle Title="SendMessage Method " /><MSHelp:RLTitle Title="DbChannel.SendMessage Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DbChannel.SendMessage(BerkeleyDB.DatabaseEntry[])" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDbChannelClassSendMessageTopic" /><MSHelp:Keyword Index="K" Term="SendMessage method" /><MSHelp:Keyword Index="K" Term="DbChannel.SendMessage method" /><MSHelp:Keyword Index="F" Term="SendMessage" /><MSHelp:Keyword Index="F"
Term="DbChannel.SendMessage" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DbChannel.SendMessage" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DbChannel.SendMessage" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Send a message on the message channel. The message is sent asynchronously. The method does not wait for a response before returning. It usually completes quickly because it only waits for local TC ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DbChannel..::.SendMessage Method </td></tr><tr id="headerTableRow3"><td align="left">DbChannel Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Remove Method (String)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"></script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"></script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"></script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Remove" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Remove" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Remove(System.String)" /><MSHelp:TOCTitle Title="Remove Method (String)" /><MSHelp:RLTitle Title="BaseDatabase.Remove Method (String) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Remove(System.String)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Remove" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"

/><MSHelp:Attr Name="Abstract" Value="Remove the underlying file represented by , incidentally removing all of the databases it contained." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Remove Method (String)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveNextMultiple Method (Int32)</title><link rel="stylesheet" type="text/css"

href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveNextMultiple_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveNextMultiple_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveNextMultiple(System.Int32)" /><MSHelp:TOCTitle Title="MoveNextMultiple Method (Int32)" /><MSHelp:RLTitle Title="Cursor.MoveNextMultiple Method (Int32) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveNextMultiple(System.Int32)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveNextMultiple" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If the cursor is not yet initialized, MoveNextMultiple is identical to . Otherwise, move the cursor to the next key/data pair of the database, and store that pair and as many duplicate data items t ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input

id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveNextMultiple Method (Int32)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MoveLast Method (DatabaseEntry, DatabaseEntry, LockingInfo)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Cursor_MoveLast_2" /><meta name="guid" content="M_BerkeleyDB_Cursor_MoveLast_2" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Cursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:TOCTitle Title="MoveLast Method (DatabaseEntry, DatabaseEntry, LockingInfo)" /><MSHelp:RLTitle Title="Cursor.MoveLast Method (DatabaseEntry, DatabaseEntry, LockingInfo) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Cursor.MoveLast(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,BerkeleyDB.LockingInfo)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Cursor.MoveLast" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the cursor to refer to the last key/data pair of the database, and store that pair in . If the last key has duplicate values, the last data item in the set of duplicates is stored in . If eith ..." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Cursor..::.MoveLast Method (DatabaseEntry, DatabaseEntry, LockingInfo)</td></tr><tr id="headerTableRow3"><td align="left">Cursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetCompression Method (BTreeCompressDelegate, BTreeDecompressDelegate)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BTreeDatabaseConfig_SetCompression_1" /><meta name="guid" content="M_BerkeleyDB_BTreeDatabaseConfig_SetCompression_1"

/><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.BTreeDatabaseConfig.SetCompression(BerkeleyDB.BTreeCompressDelegate,BerkeleyDB.
BTreeDecompressDelegate)" /><MSHelp:TOCTitle
Title="SetCompression Method (BTreeCompressDelegate, BTreeDecompressDelegate)" /><MSHelp:RLTitle
Title="BTreeDatabaseConfig.SetCompression Method (BTreeCompressDelegate, BTreeDecompressDelegate)
(BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.BTreeDatabaseConfig.SetCompression(BerkeleyDB.BTreeCompressDelegate,BerkeleyDB.
BTreeDecompressDelegate)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr
Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BTreeDatabaseConfig.SetCompression" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Enable
compression of the key/data pairs stored in the database, using the specified compression and decompression
functions." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input
id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual
C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeDatabaseConfig..::.SetCompression Method (BTreeCompressDelegate, BTreeDecompressDelegate)</td></tr><tr id="headerTableRow3"><td align="left">BTreeDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CurrentWinnerMaxLSN Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_CurrentWinnerMaxLSN" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_CurrentWinnerMaxLSN" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.CurrentWinnerMaxLSN" /><MSHelp:TOCTitle Title="CurrentWinnerMaxLSN Property " /><MSHelp:RLTitle Title="ReplicationStats.CurrentWinnerMaxLSN Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.CurrentWinnerMaxLSN" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassCurrentWinnerMaxLSNTopic" /><MSHelp:Keyword Index="K" Term="CurrentWinnerMaxLSN property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.CurrentWinnerMaxLSN property" /><MSHelp:Keyword Index="F" Term="CurrentWinnerMaxLSN" /><MSHelp:Keyword Index="F" Term="ReplicationStats.CurrentWinnerMaxLSN" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.CurrentWinnerMaxLSN" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.CurrentWinnerMaxLSN" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_CurrentWinnerMaxLSN" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Max. LSN of current winner." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownHoverImage"

style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.CurrentWinnerMaxLSN Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DatabaseException Fields</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Fields_T_BerkeleyDB_DatabaseException" /><meta name="guid" content="Fields_T_BerkeleyDB_DatabaseException" /><xml><MSHelp:Attr Name="AssetID"

Value="Fields.T:BerkeleyDB.DatabaseException" /><MSHelp:TOCTitle Title="DatabaseException Fields" /><MSHelp:RLTitle Title="DatabaseException Fields (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Fields.T:BerkeleyDB.DatabaseException" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseExceptionFieldsTopic" /><MSHelp:Keyword Index="K" Term="DatabaseException class, fields" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')"

/><label class="checkboxLabel" for="ProtectedCheckbox">Include
Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on"
onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include
Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr
id="headerTableRow1"><td align="left">Berkeley DB .NET API
Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseException Fields</td></tr><tr id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseException.htm">DatabaseException Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5"
xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save"
CONTENT="history" /><title>CloseForceSync Method </title><link rel="stylesheet" type="text/css"
href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-
help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"
src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript"
src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">
</script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_DatabaseEnvironment_CloseForceSync" /><meta name="guid"
content="M_BerkeleyDB_DatabaseEnvironment_CloseForceSync" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.DatabaseEnvironment.CloseForceSync" /><MSHelp:TOCTitle Title="CloseForceSync
Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.CloseForceSync Method (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.CloseForceSync"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassCloseForceSyncTopic"
/><MSHelp:Keyword Index="K" Term="CloseForceSync method" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.CloseForceSync method" /><MSHelp:Keyword Index="F" Term="CloseForceSync"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.CloseForceSync" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.CloseForceSync" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.CloseForceSync" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Close the
Berkeley DB environment, freeing any allocated resources, closing any open databases as well as underlying
subsystems." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img

id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.CloseForceSync Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Votes Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_Votes" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_Votes" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.Votes" /><MSHelp:TOCTitle Title="Votes Property " /><MSHelp:RLTitle Title="ReplicationStats.Votes Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.Votes" /><MSHelp:Keyword Index="A"

Term="frlrfBerkeleyDBReplicationStatsClassVotesTopic" /><MSHelp:Keyword Index="K" Term="Votes property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.Votes property" /><MSHelp:Keyword Index="F" Term="Votes" /><MSHelp:Keyword Index="F" Term="ReplicationStats.Votes" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.Votes" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.Votes" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_Votes" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Votes received in this round." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..<span

class="cpp">::.Votes Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Cursor Method (Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Cursor_3" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Cursor_3" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Cursor(BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Cursor Method (Transaction)" /><MSHelp:RLTitle Title="BaseDatabase.Cursor Method (Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Cursor(BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Cursor" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Create a transactionally protected database cursor." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:

none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Cursor Method (Transaction)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>ExtentSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_QueueDatabase_ExtentSize" /><meta name="guid" content="P_BerkeleyDB_QueueDatabase_ExtentSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.QueueDatabase.ExtentSize" /><MSHelp:TOCTitle Title="ExtentSize Property " /><MSHelp:RLTitle Title="QueueDatabase.ExtentSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.QueueDatabase.ExtentSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseClassExtentSizeTopic" /><MSHelp:Keyword Index="K" Term="ExtentSize property" /><MSHelp:Keyword Index="K" Term="QueueDatabase.ExtentSize property" /><MSHelp:Keyword Index="F" Term="ExtentSize" /><MSHelp:Keyword Index="F" Term="QueueDatabase.ExtentSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.QueueDatabase.ExtentSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.ExtentSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.QueueDatabase.get_ExtentSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The size of the

extents used to hold pages in a , specified as a number of pages." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabase..::.ExtentSize Property </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>QueueDatabaseConfig Methods </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css"

/><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Methods_T_BerkeleyDB_QueueDatabaseConfig" /><meta name="guid" content="Methods_T_BerkeleyDB_QueueDatabaseConfig" /><xml><MSHelp:Attr Name="AssetID" Value="Methods.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:TOCTitle Title="QueueDatabaseConfig Methods " /><MSHelp:RLTitle Title="QueueDatabaseConfig Methods (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Methods.T:BerkeleyDB.QueueDatabaseConfig" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBQueueDatabaseConfigMethodsTopic" /><MSHelp:Keyword Index="K" Term="QueueDatabaseConfig class, methods" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members:

Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox"
type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">QueueDatabaseConfig Methods </td></tr><tr id="headerTableRow3"><td align="left">QueueDatabaseConfig
Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DB_LOG_BUFFER_FULL Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">
</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js">
</script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js">
</script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ErrorCodes_DB_LOG_BUFFER_FULL" /><meta name="guid" content="F_BerkeleyDB_ErrorCodes_DB_LOG_BUFFER_FULL" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ErrorCodes.DB_LOG_BUFFER_FULL" /><MSHelp:TOCTitle Title="DB_LOG_BUFFER_FULL Field" /><MSHelp:RLTitle Title="ErrorCodes.DB_LOG_BUFFER_FULL Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ErrorCodes.DB_LOG_BUFFER_FULL" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBErrorCodesClassDB_LOG_BUFFER_FULLTopic" /><MSHelp:Keyword Index="K" Term="DB_LOG_BUFFER_FULL field" /><MSHelp:Keyword Index="K" Term="ErrorCodes.DB_LOG_BUFFER_FULL
field" /><MSHelp:Keyword Index="F" Term="DB_LOG_BUFFER_FULL" /><MSHelp:Keyword Index="F" Term="ErrorCodes.DB_LOG_BUFFER_FULL" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ErrorCodes.DB_LOG_BUFFER_FULL" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ErrorCodes.DB_LOG_BUFFER_FULL" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr

Name="Abstract" Value="In-memory log buffer full." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ErrorCodes..::.DB_LOG_BUFFER_FULL Field</td></tr><tr id="headerTableRow3"><td align="left">ErrorCodes Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>KeyGen Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css"

/><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_SecondaryDatabaseConfig_KeyGen" /><meta name="guid" content="P_BerkeleyDB_SecondaryDatabaseConfig_KeyGen" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.SecondaryDatabaseConfig.KeyGen" /><MSHelp:TOCTitle Title="KeyGen Property " /><MSHelp:RLTitle Title="SecondaryDatabaseConfig.KeyGen Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.SecondaryDatabaseConfig.KeyGen" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryDatabaseConfigClassKeyGenTopic" /><MSHelp:Keyword Index="K" Term="KeyGen property" /><MSHelp:Keyword Index="K" Term="SecondaryDatabaseConfig.KeyGen property" /><MSHelp:Keyword Index="F" Term="KeyGen" /><MSHelp:Keyword Index="F" Term="SecondaryDatabaseConfig.KeyGen" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryDatabaseConfig.KeyGen" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.KeyGen" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.get_KeyGen" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.SecondaryDatabaseConfig.set_KeyGen" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The delegate that creates the set of secondary keys corresponding to a given primary key and data pair." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryDatabaseConfig..::.KeyGen Property </td></tr><tr id="headerTableRow3"><td align="left">SecondaryDatabaseConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>SetLockTimeout Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_Transaction_SetLockTimeout" /><meta name="guid" content="M_BerkeleyDB_Transaction_SetLockTimeout" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.Transaction.SetLockTimeout(System.UInt32)" /><MSHelp:TOCTitle Title="SetLockTimeout Method " /><MSHelp:RLTitle Title="Transaction.SetLockTimeout Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.Transaction.SetLockTimeout(System.UInt32)" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBTransactionClassSetLockTimeoutTopic" /><MSHelp:Keyword Index="K" Term="SetLockTimeout method" /><MSHelp:Keyword Index="K" Term="Transaction.SetLockTimeout method" /><MSHelp:Keyword Index="F" Term="SetLockTimeout" /><MSHelp:Keyword Index="F" Term="Transaction.SetLockTimeout" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.Transaction.SetLockTimeout" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.Transaction.SetLockTimeout" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the timeout value for locks for this transaction." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"

style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandAllImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>
 <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.SetLockTimeout Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See
Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MovePrev Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript"

src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="M_BerkeleyDB_SecondaryCursor_MovePrev_1" /><meta name="guid"
content="M_BerkeleyDB_SecondaryCursor_MovePrev_1" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.SecondaryCursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berke
leyDB.DatabaseEntry)" /><MSHelp:TOCTitle Title="MovePrev Method (DatabaseEntry, DatabaseEntry,
DatabaseEntry)" /><MSHelp:RLTitle Title="SecondaryCursor.MovePrev Method (DatabaseEntry, DatabaseEntry,
DatabaseEntry) (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.SecondaryCursor.MovePrev(BerkeleyDB.DatabaseEntry,BerkeleyDB.DatabaseEntry,Berkel
eyDB.DatabaseEntry)" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.SecondaryCursor.MovePrev" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang"
Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType"
Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract"
Value="If the cursor is not yet initialized, MovePrev is identical to . Otherwise, move the cursor to the previous
key/data pair of the database, and store the secondary key and primary key/data pair in ..." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage"
style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img id="dropDownHoverImage"
style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img id="copyImage"
style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label
id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"

onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryCursor..::.MovePrev Method (DatabaseEntry, DatabaseEntry, DatabaseEntry)</td></tr><tr id="headerTableRow3"><td align="left">SecondaryCursor Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MasterEnvID Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_ReplicationStats_MasterEnvID" /><meta name="guid" content="P_BerkeleyDB_ReplicationStats_MasterEnvID" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.ReplicationStats.MasterEnvID" /><MSHelp:TOCTitle Title="MasterEnvID Property " /><MSHelp:RLTitle Title="ReplicationStats.MasterEnvID Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.ReplicationStats.MasterEnvID" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationStatsClassMasterEnvIDTopic" /><MSHelp:Keyword Index="K" Term="MasterEnvID property" /><MSHelp:Keyword Index="K" Term="ReplicationStats.MasterEnvID property" /><MSHelp:Keyword Index="F" Term="MasterEnvID" /><MSHelp:Keyword Index="F" Term="ReplicationStats.MasterEnvID" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationStats.MasterEnvID" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.MasterEnvID" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationStats.get_MasterEnvID" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Env. ID of the current master." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="dropDownImage"

style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationStats..::.MasterEnvID Property </td></tr><tr id="headerTableRow3"><td align="left">ReplicationStats Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>CDB_ALLDB Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_CDB_ALLDB" /><meta name="guid"

content="P_BerkeleyDB_DatabaseEnvironment_CDB_ALLDB" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.DatabaseEnvironment.CDB_ALLDB" /><MSHelp:TOCTitle Title="CDB_ALLDB
Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.CDB_ALLDB Property (BerkeleyDB)"
/><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.CDB_ALLDB"
/><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassCDB_ALLDBTopic"
/><MSHelp:Keyword Index="K" Term="CDB_ALLDB property" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironment.CDB_ALLDB property" /><MSHelp:Keyword Index="F" Term="CDB_ALLDB"
/><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.CDB_ALLDB" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironment.CDB_ALLDB" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.CDB_ALLDB" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.DatabaseEnvironment.get_CDB_ALLDB" /><MSHelp:Attr Name="DevLang"
Value="CSharp" /><MSHelp:Attr Name="DevLang"
Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us"
/><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref"
/><MSHelp:Attr Name="Abstract" Value="If true, Berkeley DB Concurrent Data Store applications will perform
locking on an environment-wide basis rather than on a per-database basis." /><MSHelp:Attr
Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif"
/><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'"
value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"

cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.CDB_ALLDB Property </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>BTreeCursor Members</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="AllMembers_T_BerkeleyDB_BTreeCursor" /><meta name="guid" content="AllMembers_T_BerkeleyDB_BTreeCursor" /><xml><MSHelp:Attr Name="AssetID" Value="AllMembers.T:BerkeleyDB.BTreeCursor" /><MSHelp:TOCTitle Title="BTreeCursor Members" /><MSHelp:RLTitle Title="BTreeCursor Members (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="AllMembers.T:BerkeleyDB.BTreeCursor" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBBTreeCursorMembersTopic" /><MSHelp:Keyword Index="K" Term="BTreeCursor class" /><MSHelp:Keyword Index="K" Term="BTreeCursor class, all members" /><MSHelp:Keyword Index="K" Term="BerkeleyDB.BTreeCursor class" /><MSHelp:Keyword Index="F" Term="BTreeCursor" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.BTreeCursor" /><MSHelp:Attr Name="HelpPriority" Value="1" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:

none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BTreeCursor Members</td></tr><tr id="headerTableRow3"><td align="left">BTreeCursor Class Methods Properties See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>PrintStats Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">
 </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js">

</script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_SecondaryHashDatabase_PrintStats" /><meta name="guid" content="Overload_BerkeleyDB_SecondaryHashDatabase_PrintStats" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.SecondaryHashDatabase.PrintStats" /><MSHelp:TOCTitle Title="PrintStats Method " /><MSHelp:RLTitle Title="SecondaryHashDatabase.PrintStats Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.SecondaryHashDatabase.PrintStats" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBSecondaryHashDatabaseClassPrintStatsTopic" /><MSHelp:Keyword Index="K" Term="PrintStats method" /><MSHelp:Keyword Index="K" Term="SecondaryHashDatabase.PrintStats method" /><MSHelp:Keyword Index="F" Term="PrintStats" /><MSHelp:Keyword Index="F" Term="SecondaryHashDatabase.PrintStats" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.SecondaryHashDatabase.PrintStats" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)"

/><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">SecondaryHashDatabase..::.PrintStats Method </td></tr><tr id="headerTableRow3"><td align="left">SecondaryHashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Open Method (String, HashDatabaseConfig, Transaction)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_HashDatabase_Open_1" /><meta name="guid" content="M_BerkeleyDB_HashDatabase_Open_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.HashDatabase.Open(System.String,BerkeleyDB.HashDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:TOCTitle Title="Open Method (String, HashDatabaseConfig, Transaction)" /><MSHelp:RLTitle Title="HashDatabase.Open Method (String, HashDatabaseConfig, Transaction) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.HashDatabase.Open(System.String,BerkeleyDB.HashDatabaseConfig,BerkeleyDB.Transaction)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.HashDatabase.Open" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Instantiate a new HashDatabase object and open the database represented by ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img

id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none;
height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><img ID="toggleAllImage" class="toggleAll" src="../icons/collapse_all.gif"
/> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">HashDatabase..::.Open
Method (String, HashDatabaseConfig, Transaction)</td></tr><tr id="headerTableRow3"><td align="left">HashDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>DelayClientSync Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js">

</script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_ReplicationConfig_DelayClientSync" /><meta name="guid" content="F_BerkeleyDB_ReplicationConfig_DelayClientSync" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.ReplicationConfig.DelayClientSync" /><MSHelp:TOCTitle Title="DelayClientSync Field" /><MSHelp:RLTitle Title="ReplicationConfig.DelayClientSync Field (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="F:BerkeleyDB.ReplicationConfig.DelayClientSync" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBReplicationConfigClassDelayClientSyncTopic" /><MSHelp:Keyword Index="K" Term="DelayClientSync field" /><MSHelp:Keyword Index="K" Term="ReplicationConfig.DelayClientSync field" /><MSHelp:Keyword Index="F" Term="DelayClientSync" /><MSHelp:Keyword Index="F" Term="ReplicationConfig.DelayClientSync" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.ReplicationConfig.DelayClientSync" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.ReplicationConfig.DelayClientSync" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="If true, the client will delay synchronizing to a newly declared master (defaults to false). Clients configured in this way will remain unsynchronized until the application calls ." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">ReplicationConfig..::.DelayClientSync Field</td></tr><tr id="headerTableRow3"><td align="left">ReplicationConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>MaxLogFileSize Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="P_BerkeleyDB_DatabaseEnvironment_MaxLogFileSize" /><meta name="guid" content="P_BerkeleyDB_DatabaseEnvironment_MaxLogFileSize" /><xml><MSHelp:Attr Name="AssetID" Value="P:BerkeleyDB.DatabaseEnvironment.MaxLogFileSize" /><MSHelp:TOCTitle Title="MaxLogFileSize Property " /><MSHelp:RLTitle Title="DatabaseEnvironment.MaxLogFileSize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="P:BerkeleyDB.DatabaseEnvironment.MaxLogFileSize" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassMaxLogFileSizeTopic" /><MSHelp:Keyword Index="K" Term="MaxLogFileSize property" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.MaxLogFileSize property" /><MSHelp:Keyword Index="F" Term="MaxLogFileSize" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.MaxLogFileSize" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.MaxLogFileSize" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.MaxLogFileSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.get_MaxLogFileSize" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.set_MaxLogFileSize" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The maximum size of a single file in the log, in bytes. Because LSN Offsets are unsigned four-byte values, the size may not be larger than the maximum unsigned four-byte value." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"

/><img id="expandImage"
style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img
id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" /><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll"
src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage" style="display:
none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand
All</label>   <img
id="devlangsDropdownImage" src="../icons/dropdown.gif" /> <label id="devlangsMenuAllLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label
id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span
id="nsrTitle">DatabaseEnvironment.<span
class="vb">.<span
class="cpp">::.MaxLogFileSize Property </td></tr><tr
id="headerTableRow3"><td align="left"><a
href="T_BerkeleyDB_DatabaseEnvironment.htm">DatabaseEnvironment Class <a href="#seeAlsoToggle"
onclick="OpenSection(seeAlsoToggle)">See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Pagesize
Property </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"

src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta
name="file" content="P_BerkeleyDB_BaseDatabase_Pagesize" /><meta name="guid"
content="P_BerkeleyDB_BaseDatabase_Pagesize" /><xml><MSHelp:Attr Name="AssetID"
Value="P:BerkeleyDB.BaseDatabase.Pagesize" /><MSHelp:TOCTitle Title="Pagesize Property "
/><MSHelp:RLTitle Title="BaseDatabase.Pagesize Property (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="P:BerkeleyDB.BaseDatabase.Pagesize" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBBaseDatabaseClassPagesizeTopic"
/><MSHelp:Keyword Index="K" Term="Pagesize property" /><MSHelp:Keyword Index="K"
Term="BaseDatabase.Pagesize property" /><MSHelp:Keyword Index="F" Term="Pagesize" /><MSHelp:Keyword
Index="F" Term="BaseDatabase.Pagesize" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.BaseDatabase.Pagesize" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.Pagesize" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.BaseDatabase.get_Pagesize" /><MSHelp:Attr Name="DevLang" Value="CSharp"
/><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++"
/><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax"
/><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="The database's
current page size." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input
type="hidden" id="userDataCache"
class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="collapseImage"
style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image" /><img
id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand Image"
/><img
id="expandAllImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" /><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif" /><img
id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image" /><img
id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual Basic </nobr></label><label
id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:
Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox"
type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label
class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox"
type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label

class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Pagesize Property </td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Close Method (Boolean)</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_BaseDatabase_Close_1" /><meta name="guid" content="M_BerkeleyDB_BaseDatabase_Close_1" /><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.BaseDatabase.Close(System.Boolean)" /><MSHelp:TOCTitle Title="Close Method (Boolean)" /><MSHelp:RLTitle Title="BaseDatabase.Close Method (Boolean) (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.BaseDatabase.Close(System.Boolean)" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.BaseDatabase.Close" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Optionally flush any cached database information to disk, close any open objects, free any allocated resources, and close any underlying files." /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"

title="CopyHover image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">BaseDatabase..::.Close Method (Boolean)</td></tr><tr id="headerTableRow3"><td align="left">BaseDatabase Class See Also /opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>IntermediateDirMode Field</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="F_BerkeleyDB_DatabaseEnvironmentConfig_IntermediateDirMode" /><meta name="guid" content="F_BerkeleyDB_DatabaseEnvironmentConfig_IntermediateDirMode" /><xml><MSHelp:Attr Name="AssetID" Value="F:BerkeleyDB.DatabaseEnvironmentConfig.IntermediateDirMode" /><MSHelp:TOCTitle Title="IntermediateDirMode Field" /><MSHelp:RLTitle

Title="DatabaseEnvironmentConfig.IntermediateDirMode
Field (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="F:BerkeleyDB.DatabaseEnvironmentConfig.IntermediateDirMode" /><MSHelp:Keyword Index="A"
Term="frlrfBerkeleyDBDatabaseEnvironmentConfigClassIntermediateDirModeTopic" /><MSHelp:Keyword
Index="K" Term="IntermediateDirMode field" /><MSHelp:Keyword Index="K"
Term="DatabaseEnvironmentConfig.IntermediateDirMode field" /><MSHelp:Keyword Index="F"
Term="IntermediateDirMode" /><MSHelp:Keyword Index="F"
Term="DatabaseEnvironmentConfig.IntermediateDirMode" /><MSHelp:Keyword Index="F"
Term="BerkeleyDB.DatabaseEnvironmentConfig.IntermediateDirMode" /><MSHelp:Attr Name="APIType"
Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr
Name="APIName" Value="BerkeleyDB.DatabaseEnvironmentConfig.IntermediateDirMode" /><MSHelp:Attr
Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr
Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr
Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr
Name="Abstract" Value="The permissions for any intermediate directories created by Berkeley DB."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden"
id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img
id="collapseImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif" title="Collapse image"
/><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand
Image" /><img id="collapseAllImage" style="display:none; height:0; width:0;" src="../icons/collapse_all.gif"
/><img
id="dropDownImage" style="display:none; height:0; width:0;" src="../icons/dropdown.gif" /><img
id="dropDownHoverImage" style="display:none; height:0; width:0;" src="../icons/dropdownHover.gif"
/><img id="copyImage" style="display:none; height:0; width:0;" src="../icons/copycode.gif" title="Copy image"
/><img id="copyHoverImage" style="display:none; height:0; width:0;" src="../icons/copycodeHighlight.gif"
title="CopyHover image" /> <table id="topTable" cellspacing="0"
cellpadding="0"><tr><td><span onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All
</nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display:
none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel"
for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label
id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual
Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage"
style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table><div
id="devlangsMenu"><input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input
id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on"
onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual
Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox"
data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0"
cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET
API Documentation</td></tr><tr id="headerTableRow2"><td align="left"><span

id="nsrTitle">DatabaseEnvironmentConfig..::.IntermediateDirMode Field</td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironmentConfig Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp"
 xmlns:mshelp="http://msdn.microsoft.com/mshelp"
xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type"
CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Commit Method
</title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet"
type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript"
src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js">
</script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript"
src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js">
</script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript"
src="../scripts/CommonUtilities.js">
 </script><meta name="container" content="BerkeleyDB" /><meta name="file"
content="M_BerkeleyDB_Transaction_Commit" /><meta name="guid"
content="M_BerkeleyDB_Transaction_Commit" /><xml><MSHelp:Attr Name="AssetID"
Value="M:BerkeleyDB.Transaction.Commit" /><MSHelp:TOCTitle Title="Commit Method " /><MSHelp:RLTitle
Title="Transaction.Commit Method (BerkeleyDB)" /><MSHelp:Keyword Index="A"
Term="M:BerkeleyDB.Transaction.Commit" /><MSHelp:Attr Name="APIType" Value="Managed"
/><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName"
Value="BerkeleyDB.Transaction.Commit" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr
Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr
Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr
Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="End the transaction."
/><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0"
 /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden"
id="hiddenScrollOffset" /><img id="collapseImage" style="display:none; height:0; width:0;"
src="../icons/collapse_all.gif" title="Collapse image" /><img id="expandImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" title="Expand Image" /><img id="collapseAllImage" style="display:none;
height:0; width:0;" src="../icons/collapse_all.gif" /><img id="expandAllImage" style="display:none; height:0;
width:0;" src="../icons/expand_all.gif" /><img id="dropDownImage" style="display:none; height:0; width:0;"
src="../icons/dropdown.gif" /><img id="dropDownHoverImage" style="display:none; height:0; width:0;"
src="../icons/dropdownHover.gif" /><img id="copyImage" style="display:none; height:0; width:0;"
src="../icons/copycode.gif" title="Copy image" /><img id="copyHoverImage" style="display:none; height:0;
width:0;" src="../icons/copycodeHighlight.gif" title="CopyHover
 image" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td><span
onclick="ExpandCollapseAll(toggleAllImage)" style="cursor:default;"
onkeypress="ExpandCollapseAll_CheckKey(toggleAllImage, event)" tabindex="0"><img ID="toggleAllImage"
class="toggleAll" src="../icons/collapse_all.gif" /> <label id="collapseAllLabel" for="toggleAllImage"
style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display:
none;">Expand All</label>   <span id="devlangsDropdown" class="filter"
tabindex="0"> <label
id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code:

All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">Transaction..::.Commit Method </td></tr><tr id="headerTableRow3"><td align="left">Transaction Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<%@ Page Language="C#" EnableViewState="False" %>

Found in path(s):
* Report Feedback on this item in the Oracle Technology Network Forum <p />Copyright (c) 2008, 2013 Oracle. All rights reserved. </body></html>
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_windows. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_windows. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!--$Id: witold.so,v 10.5 2001/06/09 14:34:45 bostic Exp $-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD
HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD
HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar

(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE
HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE
HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE
HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC
"-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD
HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD
HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar

(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML
4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE
HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE
HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML
PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC
"-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD
HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML
4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">

(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE
HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"

"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML
PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC
"-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD
HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8"
standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!--Id-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)db-5.3.28/docs/api_reference/STL/stlDbstlElemTraitslength.html/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0"
encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)db-5.3.28/docs/api_reference/STL/stlDbstlElemTraitslt.html/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<?xml version="1.0" encoding="UTF-8" standalone="no"?>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<%@ Page Language="C#" EnableViewState="False" %>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<%@ Page Language="C#" EnableViewState="False" %>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META
HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Panic Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js"> </script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="M_BerkeleyDB_DatabaseEnvironment_Panic" /><meta name="guid" content="M_BerkeleyDB_DatabaseEnvironment_Panic"
/><xml><MSHelp:Attr Name="AssetID" Value="M:BerkeleyDB.DatabaseEnvironment.Panic" /><MSHelp:TOCTitle Title="Panic Method " /><MSHelp:RLTitle Title="DatabaseEnvironment.Panic Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="M:BerkeleyDB.DatabaseEnvironment.Panic" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBDatabaseEnvironmentClassPanicTopic" /><MSHelp:Keyword Index="K" Term="Panic method" /><MSHelp:Keyword Index="K" Term="DatabaseEnvironment.Panic method" /><MSHelp:Keyword Index="F" Term="Panic" /><MSHelp:Keyword Index="F" Term="DatabaseEnvironment.Panic" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.DatabaseEnvironment.Panic" /><MSHelp:Attr Name="APIType" Value="Managed" /><MSHelp:Attr Name="APILocation" Value="libdb_dotnet53.dll" /><MSHelp:Attr Name="APIName" Value="BerkeleyDB.DatabaseEnvironment.Panic" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale"
Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="Abstract" Value="Set the panic state for the database environment. (Database environments in a panic state normally refuse all attempts to call Berkeley DB functions, throwing .)" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /><img id="expandImage" style="display:none; height:0; width:0;" src="../icons/expand_all.gif" title="Expand

Image" /><img id="dropDownImage" style="display:none; height:0;
width:0;" src="../icons/dropdown.gif" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <img id="devlangsDropdownImage" src="../icons/dropdown.gif"
/> <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label></td></tr></table> <input id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel"
for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">DatabaseEnvironment..::.Panic Method </td></tr><tr id="headerTableRow3"><td align="left">DatabaseEnvironment Class See Also
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)//==========
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)//==========
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<%@ Page Language="C#" EnableViewState="False" %>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights
reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)<!--Copyright (c) 1999, 2013 Oracle and/or its affiliates. All rights reserved.-->
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/env perl -p
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<html>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar

(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/***
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)=head1 NAME
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)#!/usr/local/bin/perl
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)package Test::More;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package Test::Builder;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/local/bin/perl
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1) BerkeleyDB
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)=head1 NAME
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/perl
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)--- #YAML:1.0
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)#!/usr/local/bin/perl
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# DB_File.pm -- Perl 5 interface to Berkeley DB
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1) DB_File
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)--- #YAML:1.0
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)#
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/**********
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package SQLite.JDBC2x;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package SQLite.JDBC2z;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package SQLite.JDBC1;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package SQLite.JDBC2y;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package SQLite.JDBC0;

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)package SQLite.JDBC2z1;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)package SQLite.JDBC2;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)This software is copyrighted by Christian Werner <chw@ch-werner.de> and others.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# generated automatically by aclocal 1.11.1 -*- Autoconf -*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN""http://www.w3.org/
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# Generated from ltmain.m4sh.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)%global __provides_exclude_from ^%{_libdir}/%{name}/.*\.so$
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)%define
name sqlite
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# generated automatically by aclocal 1.10.2 -*- Autoconf -*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# 2001 September 15
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# 2006 September 14
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# 2010 July 16
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# 2006 September 14
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# 2006 September 14
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# 2006 October 1
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)%!PS-Adobe-3.1 EPSF-3.0
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# Generated from ltmain.m4sh.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)%define name sqliteodbc
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)This software is copyrighted by Christian Werner <chw@ch-werner.de>
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# libtool.m4 - Configure libtool for the host system. -*-Autoconf-*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#include <winresrc.h>

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)This package was debianized by Sam Clegg <samo@debian.org> on
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# ltmain.sh - Provide generalized library-building
support services.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)%define name sqliteodbc
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<Project DefaultTargets="Build"
xmlns="http://schemas.microsoft.com/developer/msbuild/2003" ToolsVersion="3.5">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)#!/usr/bin/stap
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -s
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/usr/sbin/dtrace -qs
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_vxworks. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by
dist/s_vxworks. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_vxworks. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh
-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)aa
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)Copyright (c) 1996, 2013 Oracle and/or its affiliates. All rights reserved.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh -
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh -
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# Copyright (c) 2011, 2013 Oracle and/or its affiliates. All rights reserved.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)dnl Copyright (C) 2005, 2006, 2007 Free Software Foundation, Inc.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# Id
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# libtool.m4 - Configure libtool for the host system. -*-Autoconf-*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# Helper functions for option handling. -*- Autoconf -*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# ltversion.m4 -- version numbers -*- Autoconf -*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# Id
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# ltsugar.m4 -- libtool m4 base layer. -*-Autoconf-*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# lt~obsolete.m4 -- aclocal satisfying obsolete definitions. -*-Autoconf-*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)#!/bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#! /bin/sh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_android. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/* DO NOT EDIT: automatically built by dist/s_android. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar

(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)// Microsoft Visual C++ generated resource script.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)using System.Reflection;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)using System.Reflection;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)using System.Reflection;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)using System.Reflection;
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_windows. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/* DO NOT EDIT: automatically built by dist/s_windows. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/* DO NOT EDIT: automatically built by dist/s_windows. */
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file
LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See
the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE
for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the
file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE
for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the
file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for
redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file

LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#
See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE
for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the
file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)Rules for the Berkeley DB and Berkeley DB-XML test suites
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution
information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for
redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file
LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)addresser
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See
the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)#!/bin/ksh
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)NOTE
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar

(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1) / See the file LICENSE for redistribution information.
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)# Id
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-
xz/db5.3_5.3.28.orig.tar

(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<!DOCTYPE doctype PUBLIC "-//w3c//dtd
html 4.0 transitional//en">
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)Synchronization in the Locking Subsystem
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-

xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/**
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/**
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)/*-
/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar
(1)/*-

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2762550384_1763069395.3320098/0/db5-3-5-3-28-orig-tar/db5-3-5-3-28-orig-tar-1-xz/db5.3_5.3.28.orig.tar (1)<html xmlns:MSHelp="http://msdn.microsoft.com/mshelp" xmlns:mshelp="http://msdn.microsoft.com/mshelp" xmlns:ddue="http://ddue.schemas.microsoft.com/authoring/2003/5" xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:msxsl="urn:schemas-microsoft-com:xslt"><head><META HTTP-EQUIV="Content-Type" CONTENT="text/html; charset=UTF-8" /><META NAME="save" CONTENT="history" /><title>Put Method </title><link rel="stylesheet" type="text/css" href="../styles/presentation.css" /><link rel="stylesheet" type="text/css" href="ms-help://Hx/HxRuntime/HxLink.css" /><script type="text/javascript" src="../scripts/EventUtilities.js"> </script><script type="text/javascript" src="../scripts/SplitScreen.js"> </script><script type="text/javascript" src="../scripts/Dropdown.js"> </script><script type="text/javascript" src="../scripts/script_manifold.js">

</script><script type="text/javascript" src="../scripts/script_feedBack.js"> </script><script type="text/javascript" src="../scripts/CheckboxMenu.js"> </script><script type="text/javascript" src="../scripts/CommonUtilities.js"> </script><meta name="container" content="BerkeleyDB" /><meta name="file" content="Overload_BerkeleyDB_RecnoDatabase_Put" /><meta name="guid" content="Overload_BerkeleyDB_RecnoDatabase_Put" /><xml><MSHelp:Attr Name="AssetID" Value="Overload:BerkeleyDB.RecnoDatabase.Put" /><MSHelp:TOCTitle Title="Put Method " /><MSHelp:RLTitle Title="RecnoDatabase.Put Method (BerkeleyDB)" /><MSHelp:Keyword Index="A" Term="Overload:BerkeleyDB.RecnoDatabase.Put" /><MSHelp:Keyword Index="A" Term="frlrfBerkeleyDBRecnoDatabaseClassPutTopic" /><MSHelp:Keyword Index="K" Term="Put method" /><MSHelp:Keyword Index="K" Term="RecnoDatabase.Put method" /><MSHelp:Keyword Index="F" Term="Put" /><MSHelp:Keyword Index="F" Term="RecnoDatabase.Put" /><MSHelp:Keyword Index="F" Term="BerkeleyDB.RecnoDatabase.Put" /><MSHelp:Attr Name="DevLang" Value="CSharp" /><MSHelp:Attr Name="DevLang" Value="VB" /><MSHelp:Attr Name="DevLang" Value="C++" /><MSHelp:Attr Name="Locale" Value="en-us" /><MSHelp:Attr Name="TopicType" Value="kbSyntax" /><MSHelp:Attr Name="TopicType" Value="apiref" /><MSHelp:Attr Name="AssemblyVersion" Value="5.3.28.0" /></xml></head><body><input type="hidden" id="userDataCache" class="userDataStyle" /><input type="hidden" id="hiddenScrollOffset" /> <table id="topTable" cellspacing="0" cellpadding="0"><tr><td> <label id="collapseAllLabel" for="toggleAllImage" style="display: none;">Collapse All</label><label id="expandAllLabel" for="toggleAllImage" style="display: none;">Expand All</label>   <label id="devlangsMenuAllLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: All </nobr></label><label id="devlangsMenuMultipleLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Multiple </nobr></label><label id="devlangsMenuCSharpLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: C# </nobr></label><label id="devlangsMenuVisualBasicLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual Basic </nobr></label><label id="devlangsMenuManagedCPlusPlusLabel" for="devlangsDropdownImage" style="display: none;"><nobr>Code: Visual C++ </nobr></label> <label id="memberOptionsMenuAllLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Show All </nobr></label><label id="memberOptionsMenuMultipleLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuProtectedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label><label id="memberOptionsMenuInheritedLabel" for="memberOptionsDropdownImage" style="display: none;"><nobr>Members: Filtered </nobr></label></td></tr></table> <input

id="CSharpCheckbox" type="checkbox" data="CSharp,cs,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="CSharpCheckbox">C#</label>
<input id="VisualBasicCheckbox" type="checkbox" data="VisualBasic,vb,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="VisualBasicCheckbox">Visual Basic</label>
<input id="ManagedCPlusPlusCheckbox" type="checkbox" data="ManagedCPlusPlus,cpp,'persist'" value="on" onClick="SetLanguage(this)" /><label class="checkboxLabel" for="ManagedCPlusPlusCheckbox">Visual C++</label>
 <input id="ProtectedCheckbox" type="checkbox" data="Protected" value="on" onClick="SetMemberOptions(this, 'vis')" /><label class="checkboxLabel" for="ProtectedCheckbox">Include Protected Members</label>
<input id="InheritedCheckbox" type="checkbox" data="Inherited" value="on" onClick="SetMemberOptions(this, 'decl')" /><label class="checkboxLabel" for="InheritedCheckbox">Include Inherited Members</label>
 <table id="bottomTable" cellpadding="0" cellspacing="0"><tr id="headerTableRow1"><td align="left">Berkeley DB .NET API Documentation</td></tr><tr id="headerTableRow2"><td align="left">RecnoDatabase..::.Put Method </td></tr><tr id="headerTableRow3"><td align="left">RecnoDatabase Class See Also

Found in path(s):
* Report Feedback on this item in the Oracle Technology Network Forum <p />Copyright (c) 2008, 2013 Oracle. All rights reserved. </body></html>db-5.3.28/docs/csharp/html/Overload_BerkeleyDB_RecnoDatabase_Put.htm

1.170 chkconfig 1.24-2.el9

1.170.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on

the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.171 libtool 2.4.6-46.el9

1.171.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave

you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into

another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that,

in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of

the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these

materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if

you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR

CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which

gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.

Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that
contains a notice placed by the copyright holder saying it can be
distributed under the terms of this License. Such a notice grants a
world-wide, royalty-free license, unlimited in duration, to use that
work under the conditions stated herein. The ``Document'', below,
refers
to any such manual or work. Any member of the public is a
licensee, and is addressed as ``you''. You accept the license if you
copy, modify or distribute the work in a way requiring permission
under copyright law.

A ``Modified Version'' of the Document means any work containing the
Document or a portion of it, either copied verbatim, or with
modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section
of the Document that deals exclusively with the relationship of the
publishers or authors of the Document to the Document's overall
subject (or to related matters) and contains nothing that could fall
directly within that overall subject. (Thus, if the Document is in
part a textbook of mathematics, a Secondary Section may not explain
any mathematics.) The relationship could be a matter of historical
connection with the subject or with related matters, or of legal,
commercial, philosophical, ethical or political
position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles
are designated, as being those of Invariant Sections, in the notice
that says that the Document is released under this License. If a
section does not fit the above definition of Secondary then it is not
allowed to be designated as Invariant. The Document may contain zero
Invariant Sections. If the Document does not identify any Invariant
Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,
as Front-Cover Texts or Back-Cover Texts, in the notice that says that
the Document is released under this License. A Front-Cover Text may
be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,
represented in a format whose specification is available to the
general public, that is suitable for revising the document
straightforwardly with generic text editors or (for
 images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
ASCII without markup, Texinfo input format, La@TeX{} input
format, SGML or XML using a publicly available
DTD, and standard-conforming simple HTML,
PostScript or PDF designed for human modification. Examples
of transparent image formats include PNG, XCF and
JPG@. Opaque formats include proprietary formats that can be
read and edited only by proprietary word
 processors, SGML or
XML for which the DTD and/or processing tools are
not generally available, and the machine-generated HTML,
PostScript or PDF produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means
the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'',
 or ``History''.)  To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which
states that this License applies to the Document. These Warranty
Disclaimers are considered to be included by reference in this
License, but only as regards disclaiming warranties: any other
implication that these Warranty Disclaimers may have is void and has
no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either
commercially or noncommercially, provided that this License, the
copyright notices, and the license notice saying this License applies
to the Document are reproduced in all copies, and that you add no other
conditions whatsoever to those of this License. You may not use
technical measures to obstruct or control the reading or further
copying of the copies
 you make or distribute. However, you may accept
compensation in exchange for copies. If you distribute a large enough
number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and
you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have
printed covers) of the Document, numbering more than 100, and the
Document's license notice requires Cover Texts, you must enclose the
copies in covers that carry, clearly and legibly, all these Cover
Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on
the back cover. Both covers must also clearly and legibly identify
you as the publisher of these copies. The front cover must present
the full title with all words of the title equally prominent and
visible. You may add other material on the covers in addition.

Copying with changes limited to the covers, as long as they preserve
the
title of the Document and satisfy these conditions, can be treated
as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit
legibly, you should put the first ones listed (as many as fit
reasonably) on the actual cover, and continue the rest onto adjacent
pages.

If you publish or distribute Opaque copies of the Document numbering
more than 100, you must either include a machine-readable Transparent
copy along with each Opaque copy, or state in or with each Opaque copy
a computer-network location from which the general network-using
public has access to download using public-standard network protocols
a complete Transparent copy of the Document, free of added material.
If you use the latter option, you must take reasonably prudent steps,
when you begin distribution of Opaque copies in quantity, to ensure
that this Transparent copy will remain thus accessible at the stated
location until at least one year after the last time you distribute
an
Opaque copy (directly or through your agents or retailers) of that
edition to the public.

It is requested, but not required, that you contact the authors of the
Document well before redistributing any large number of copies, to give
them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under
the conditions of sections 2 and 3 above, provided that you release
the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same
title as a previous version
if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the
Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History'' section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item
For any
section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document, you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant
Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old

one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if
known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History''
in the various original documents, forming one section Entitled
``History''; likewise combine any sections Entitled ``Acknowledgements'',
and any sections Entitled ``Dedications''. You must delete all
sections Entitled ``Endorsements.''

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License
into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an ``aggregate'' if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'', ``Dedications'', or ``History'', the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and

will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for
any work) from that
copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See @uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License ``or any later version'' applies to it, you have the option of following the terms and
conditions either of that specified version or
of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'') contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons
 Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License
 in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License''.

@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts."@: line with this:

@smallexample
@group
  with the Invariant Sections being @var{list their titles}, with
  the Front-Cover Texts being @var{list}, and with the Back-Cover Texts
  being @var{list}.
@end group
@end smallexample

If you have Invariant
 Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:

1.172 gmp 4.3.4

1.172.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

 The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to

using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide

a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or

otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions

either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least

the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may

consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1)
assert copyright on the software, and (2) offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all

the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts,

regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and

only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of

that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an

organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license,

and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a

covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY

APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions

of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of

interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not

convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or
modification of the work as a means of enforcing, against the work's
users, your or third parties' legal rights to forbid circumvention of
technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you
receive it, in any medium, provided that you conspicuously and
appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to

produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular

product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the

entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of
it. (Additional permissions may be written to require their own
removal in certain cases when you modify the work.) You may place
additional permissions on material, added by you to a covered work,
for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you
add to a covered work, you may (if authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or
author attributions in that material or in the Appropriate Legal
Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains

a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work

occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant

patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory

patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the

GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/philosophy/why-not-lgpl.html>.

1.173 langpacks 3.0-16.el9

1.173.1 Available under license :

No license file was found, but licenses were detected in source scan.

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

Name: langpacks

Found in path(s):
* /langpacks-3.0-16.el9.src.rpm-cosi-expand-archive-j1wGpSTD/langpacks.spec

1.174 zstd 1.5.5-1.el9

1.174.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on

the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

BSD License

For Zstandard software

Copyright (c) Meta Platforms, Inc. and affiliates. All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.

* Neither the name Facebook, nor Meta, nor the names of its contributors may
  be used to endorse or promote products derived from this software without
  specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
 PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.175 xz 5.2.5-8.el9_0

1.175.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public

License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such

interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution

and only if you
  received the program in object code or executable form with such
  an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
 code, even though third parties are not
compelled to copy the source along with the object code.

 4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

 5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
 or modifying
the Program or works based on it.

 6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing

version number. If the Program
specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)
assert copyright on the software, and (2) offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains
that there is no warranty for this free software. For both users' and
authors' sake, the GPL requires that modified versions be marked as
changed, so that their problems will not be attributed erroneously to
authors of previous versions.

Some devices are designed to deny users access to install or run
modified versions of the software inside them, although the manufacturer
can do so. This is fundamentally incompatible with the aim of
protecting users' freedom to change the software. The systematic
pattern of such abuse occurs in the area of products for individuals to
use, which is precisely where it is most unacceptable. Therefore, we
have designed this version of the GPL to prohibit the practice for those
products. If such problems arise substantially in other domains, we
stand
ready to extend this provision to those domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.
States should not allow patents to restrict development and use of
software on general-purpose computers, but in those that do, we wish to
avoid the special danger that patents applied to a free program could
make it effectively proprietary. To prevent this, the GPL assures that
patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and
modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of
works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this
License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work
in a fashion requiring copyright permission, other than the making of an

exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to

produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;

section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from

a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work,

for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions;

the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and

propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a

party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the
option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where

the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

XZ Utils Licensing
==========

Different licenses apply to different files in this package. Here
is a rough summary of which licenses apply to which parts of this
package (but check the individual files to be sure!):

- liblzma is in the public domain.

- xz, xzdec, and lzmadec command line tools are in the public
domain unless GNU getopt_long had to be compiled and linked
in from the lib directory. The getopt_long code is under
GNU LGPLv2.1+.

- The scripts to grep, diff, and view compressed files have been
adapted from gzip. These scripts and their documentation are
under GNU GPLv2+.

- All the documentation in the doc directory and most of the
XZ Utils specific documentation files in other directories
are in the public domain.

- Translated messages are in the public domain.

- The build system contains public domain files, and files that
are under GNU GPLv2+ or GNU
GPLv3+. None of these files end up
in the binaries being built.

- Test files and test code in the tests directory, and debugging
utilities in the debug directory are in the public domain.

- The extra directory may contain public domain files, and files
that are under various free software licenses.

You can do whatever you want with the files that have been put into
the public domain. If you find public domain legally problematic,
take the previous sentence as a license grant. If you still find
the lack of copyright legally problematic, you have too many
lawyers.

As usual, this software is provided "as is", without any warranty.

If you copy significant amounts of public domain code from XZ Utils
into your project, acknowledging this somewhere in your software is
polite (especially if it is proprietary, non-free software), but
naturally it is not legally required. Here is an example of a good
notice to
put into "about box" or into documentation:

This software includes code from XZ Utils <https://tukaani.org/xz/>.

The following license texts are included in the following files:
- COPYING.LGPLv2.1: GNU Lesser General Public License version 2.1
- COPYING.GPLv2: GNU General Public License version 2
- COPYING.GPLv3: GNU General Public License version 3

Note that the toolchain (compiler, linker etc.) may add some code
pieces that are copyrighted. Thus, it is possible that e.g. liblzma
binary wouldn't actually be in the public domain in its entirety
even though it contains no copyrighted code from the XZ Utils source
package.

If you have questions, don't hesitate to ask the author(s) for more
information.

1.176 nghttp2 1.43.0-6.el9

1.176.1 Available under license :

The MIT License

Copyright (c) 2012, 2014, 2015, 2016 Tatsuhiro Tsujikawa
Copyright (c) 2012, 2014, 2015, 2016 nghttp2 contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
 WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
See COPYING
Copyright Joyent, Inc. and other Node contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
This software is licensed under the MIT License.

Copyright Fedor Indutny, 2018.

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.
If not otherwise noted, the extensions in this package are licensed
under the following license.

Copyright (c) 2010 by the contributors (see AUTHORS file).
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are

met:

* Redistributions of source code must retain the above copyright
 notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
 notice, this list of conditions and the following disclaimer in the
 documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL,
 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.177 gdbm 1:1.23-1.el9

1.177.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007, 2011 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not

price. Our General Public Licenses
 are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

 To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

 For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

 Developers that use the GNU GPL protect your rights with two steps:
(1) assert copyright on the software, and (2)
 offer you this License
giving you legal permission to copy, distribute and/or modify it.

 For the developers' and authors' protection, the GPL clearly explains
that there is no warranty for this free software. For both users' and
authors' sake, the GPL requires that modified versions be marked as
changed, so that their problems will not be attributed erroneously to
authors of previous versions.

 Some devices are designed to deny users access to install or run
modified versions of the software inside them, although the manufacturer
can do so. This is fundamentally incompatible with the aim of
protecting users' freedom to change the software. The systematic
pattern of such abuse occurs in the area of products for individuals to
use, which is precisely where it is most unacceptable. Therefore, we
have designed this version of the GPL to prohibit the practice for those
products. If such problems arise substantially in other domains, we
stand ready to extend this provision to those
 domains in future versions
of the GPL, as needed to protect the freedom of users.

 Finally, every program is threatened constantly by software patents.
States should not allow patents to restrict development and use of
software on general-purpose computers, but in those that do, we wish to
avoid the special danger that patents applied to a free program could
make it effectively proprietary. To prevent this, the GPL assures that
patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays
"Appropriate Legal Notices"
to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work

for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other
than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing
those activities but
which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its

content,
constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed; section 10
makes it unnecessary.

3. Protecting Users'
Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or
modification of the work as a means of enforcing, against the work's
users, your or third parties' legal rights to forbid circumvention of
technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you
receive it, in any medium, provided that you conspicuously and
appropriately publish on each copy an appropriate copyright notice;
keep
intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,

and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must
license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation
and its resulting copyright are not
used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and
execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information
does not include a
requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included
in this License, to the extent
that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections
15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive

additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above requirements apply either way.

8. Termination.

You
may not propagate or modify a covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your
license from a particular copyright holder is reinstated (a)
provisionally, unless and until the copyright holder explicitly and
finally terminates your license, and (b) permanently, if the copyright
holder fails to notify you of the violation by some reasonable means
prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days
after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, you do not qualify to receive new licenses for the same
material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted

by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered

work if you are a party to an arrangement with a third party that is
in the business of distributing software, under which you make payment
to the third party based on the extent of your activity of conveying
the work, and under which the third party grants, to any of the
parties who would receive the covered work from you, a discriminatory
patent license (a) in connection with copies of the covered work
conveyed by you (or copies made from those copies), or (b) primarily
for and in connection with specific products or compilations that
contain the covered work, unless you entered into that arrangement,
or that patent license was granted, prior to
28 March 2007.

Nothing in this License shall be construed as excluding or limiting
any implied license or other defenses to infringement that may
otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot convey a
covered work so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you may
not convey it at all. For example, if you agree to terms that obligate you
to collect a royalty for further conveying from those to whom you convey
the Program, the only way you could satisfy both those terms and this
License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this
License, you have
permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the

Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms,

reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief
idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes
with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands

might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.178 dejavu-fonts 2.37-18.el9

1.178.1 Available under license :

Fonts are (c) Bitstream (see below). DejaVu changes are in public domain. Glyphs imported from Arev fonts are (c) Tavmjong Bah (see below)

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font

Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: fonts at gnome dot org.

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font
Software, and to permit
persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: tavmjong @ free . fr.

TeX Gyre DJV Math

Fonts are (c) Bitstream (see below). DejaVu changes are in public domain.

Math extensions done by B. Jackowski, P. Strzelczyk and P. Pianowski (on behalf of TeX users groups) are in public domain.

Letters imported from Euler Fraktur from AMSfonts are (c) American Mathematical Society (see below).
Bitstream Vera Fonts Copyright
Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license (Fonts) and associated documentation files (the Font Software), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following

conditions:

The above copyright and trademark notices and this permission notice shall be
included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular
the designs of glyphs or characters in the Fonts may be modified and additional
glyphs
or characters may be added to the Fonts, only if the fonts are renamed
to names not containing either the words Bitstream or the word Vera.

This License becomes null and void to the extent applicable to Fonts or Font Software
that has been modified and is distributed under the Bitstream Vera names.

The Font Software may be sold as part of a larger software package but no copy
of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION
BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO
USE
THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.
Except as contained in this notice, the names of GNOME, the GNOME Foundation,
and Bitstream Inc., shall not be used in advertising or otherwise to promote
the sale, use or other dealings in this Font Software without prior written
authorization from the GNOME Foundation or Bitstream Inc., respectively.
For further information, contact: fonts at gnome dot org.

AMSFonts (v. 2.2) copyright

The PostScript Type 1 implementation of the AMSFonts produced by and
previously distributed by Blue Sky Research and Y&Y, Inc. are now freely
available for general use. This has been accomplished through the
cooperation

of a consortium of scientific publishers with Blue Sky Research and Y&Y.
Members of this consortium include:

Elsevier Science IBM Corporation Society for Industrial and Applied
Mathematics (SIAM) Springer-Verlag American Mathematical Society (AMS)

In order to assure the authenticity of these fonts, copyright will be
held
by
the American Mathematical Society. This is not meant to restrict in any way
the legitimate use of the fonts, such as (but not limited to) electronic
distribution of documents containing these fonts, inclusion of these fonts
into other public domain or commercial font collections or computer
applications, use of the outline data to create derivative fonts and/or
faces, etc. However, the AMS does require that the AMS copyright notice be
removed from any derivative versions of the fonts which have been altered in
any way. In addition, to ensure the fidelity of TeX documents using Computer
Modern fonts, Professor Donald Knuth, creator of the Computer Modern faces,
has requested that any alterations which yield different font metrics be
given a different name.

Id

1.179 ca-certificates 2025.2.80_v9.0.305-91.el9

1.179.1 Available under license :

No license file was found, but licenses were detected in source scan.

%define pkidir %{_sysconfdir}/pki

Found in path(s):
* /ca-certificates-2025.2.80_v9.0.305-91.el9.src.rpm-cosi-expand-archive-xKpJBFPS/ca-certificates.spec
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2771616477_1764765399.2345111/0/ca-certificates-2025.2.80_v9.0.305-91.el9.src.rpm-cosi-expand-archive-xKpJBFPS/ca-legacy.8.txt////
/opt/cola/permits/2771616477_1764765399.2345111/0/ca-certificates-2025.2.80_v9.0.305-91.el9.src.rpm-cosi-expand-archive-xKpJBFPS/certdata.txt#
/opt/cola/permits/2771616477_1764765399.2345111/0/ca-certificates-2025.2.80_v9.0.305-91.el9.src.rpm-cosi-expand-archive-xKpJBFPS/certdata2pem.py#!/usr/bin/python
/opt/cola/permits/2771616477_1764765399.2345111/0/ca-certificates-2025.2.80_v9.0.305-91.el9.src.rpm-cosi-expand-archive-xKpJBFPS/nssckbi.h/* This Source Code Form is subject to the terms of the Mozilla Public
/opt/cola/permits/2771616477_1764765399.2345111/0/ca-certificates-2025.2.80_v9.0.305-91.el9.src.rpm-cosi-expand-archive-xKpJBFPS/update-ca-trust.8.txt////

Found in path(s):
*

1.180 libpeas 1.30.0-4.el9

1.180.1 Available under license :

Ignacio Casal Quinteiro: Friday 30th October 2009
- Changed license from GPL to LGPL
(See https://bugzilla.gnome.org/show_bug.cgi?id=599120 for details)
This was done with the permission of all copyright holders as listed below:

Paolo Maggi <paolo@gnome.org>
Paolo Borelli <pborelli@katamail.com>
Jesse van den Kieboom <jesse@icecrew.nl>
Steve Frcinaux <code@istique.net>
Ignacio Casal Quinteiro <icq@gnome.org>
Raphal Slinckx <rslinckx@gmail.com>
James Willcox <jwillcox@gnome.org>
Adam Hooper <adamh@densi.com>
Christian Persch <chpe@svn.gnome.org
Crispin Flowerday <gnome@flowerday.cx>
Marco Pesenti Gritti <mpg@redhat.com>

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether

this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use

this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into
another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library

with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.

Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the
Library, but is designed to work with the Library by being compiled or
linked with it, is called a "work that uses the Library". Such a
work, in isolation, is not a derivative work of the Library, and
therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library
creates an executable that is a derivative of the Library (because it
contains portions of the Library), rather than a "work that
uses the
library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the

Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply,

and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system
 which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

 12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

 13. The Free Software Foundation may publish
 revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

 14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
 will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.181 microdnf 3.9.1-3.el9

1.181.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on

the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.182 okhttp 5.3.2

1.182.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Authenticator.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Cache.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/CacheControl.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Call.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Callback.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/CertificatePinner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Challenge.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/CipherSuite.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/CompressionInterceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Connection.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/ConnectionPool.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/ConnectionSpec.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Cookie.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/CookieJar.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Credentials.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Dispatcher.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Dns.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/EventListener.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/FormBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Gzip.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-

jar/commonJvmAndroid/okhttp3/Handshake.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/Headers.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/HttpUrl.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/Interceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/MediaType.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/MultipartBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/MultipartReader.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/OkHttp.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/OkHttpClient.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/Protocol.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/Request.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/RequestBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/Response.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/ResponseBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/Route.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/TlsVersion.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/TrailersSource.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/WebSocket.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/WebSocketListener.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/-CacheControlCommon.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/-HeadersCommon.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/-HostnamesCommon.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/-InternalVersion.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/-NormalizeJvm.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-

jar/commonJvmAndroid/okhttp3/internal/-UtilCommon.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/-UtilJvm.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/IsProbablyUtf8.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/NativeImageTestsAccessors.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/SuppressSignatureCheck.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/Tags.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/UnreadableResponseBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/authenticator/JavaNetAuthenticator.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache/CacheInterceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache/CacheRequest.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache/CacheStrategy.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache/DiskLruCache.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache/FaultHidingSink.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache2/FileOperator.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/cache2/Relay.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/concurrent/Lockable.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/concurrent/Task.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/concurrent/TaskLogger.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/concurrent/TaskQueue.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/concurrent/TaskRunner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/AddressPolicy.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/BufferedSocket.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/ConnectInterceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/ConnectPlan.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-

jar/commonJvmAndroid/okhttp3/internal/connection/ConnectionListener.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/Exchange.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/ExchangeFinder.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/FailedPlan.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/FastFallbackExchangeFinder.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/ForceConnectRoutePlanner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/InetAddressOrder.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RealCall.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RealConnection.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RealConnectionPool.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RealRoutePlanner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RetryTlsHandshake.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/ReusePlan.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RouteDatabase.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RoutePlanner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/RouteSelector.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/connection/SequentialExchangeFinder.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/BridgeInterceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/CallServerInterceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/DateFormatting.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/ExchangeCodec.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/GzipRequestBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/HttpHeaders.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/HttpMethod.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-

jar/commonJvmAndroid/okhttp3/internal/http/HttpStatusCodes.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/RealInterceptorChain.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/RealResponseBody.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/RequestLine.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/RetryAndFollowUpInterceptor.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http/StatusLine.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http1/HeadersReader.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http1/Http1ExchangeCodec.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/ConnectionShutdownException.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/ErrorCode.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/FlowControlListener.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Header.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Hpack.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Http2.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Http2Connection.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Http2ExchangeCodec.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Http2Reader.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Http2Stream.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Http2Writer.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Huffman.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/PushObserver.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/Settings.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/StreamResetException.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/http2/flowcontrol/WindowCounter.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-

jar/commonJvmAndroid/okhttp3/internal/idn/IdnaMappingTable.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/idn/Punycode.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/internal.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/platform/Jdk9Platform.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/platform/Platform.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/platform/PlatformRegistry.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/proxy/NullProxySelector.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/publicsuffix/BasePublicSuffixList.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/publicsuffix/PublicSuffixDatabase.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/publicsuffix/PublicSuffixList.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/publicsuffix/ResourcePublicSuffixList.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/tls/BasicCertificateChainCleaner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/tls/BasicTrustRootIndex.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/tls/CertificateChainCleaner.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/tls/OkHostnameVerifier.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/tls/TrustRootIndex.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/url/-Url.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/MessageDeflater.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/MessageInflater.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/RealWebSocket.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/WebSocketExtensions.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/WebSocketProtocol.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/WebSocketReader.kt/*
/opt/cola/permits/2779994456_1764848552.6837845/0/okhttp-5-3-2-sources-
jar/commonJvmAndroid/okhttp3/internal/ws/WebSocketWriter.kt/*

Found
in path(s):
*
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 The Android Open Source Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-5-3-2-sources-jar/commonJvmAndroid/okhttp3/Address.kt

1.183 libxml2 2.9.13-14.el9_7

1.183.1 Available under license :

Except where otherwise noted in the source code (e.g. the files hash.c,
list.c and the trio files, which are covered by a similar licence but
with different Copyright notices) all the files are:

Copyright (C) 1998-2012 Daniel Veillard. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is fur-
nished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FIT-
NESS FOR A PARTICULAR PURPOSE

AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.184 systemd-libs 252-55.el9_7.7

1.184.1 Available under license :

systemd Project Licensing

Main License

The systemd project uses single-line references to Unique License Identifiers as
defined by the Linux Foundation's SPDX project (https://spdx.org/). The line in
each individual source file identifies the license applicable to that file.

The current set of valid, predefined SPDX identifiers can be found on the SPDX
License List at https://spdx.org/licenses/.

The 'LICENSES/' directory contains all the licenses used by the sources included in
the systemd project source tree.

Unless otherwise noted, the systemd project sources are licensed under the terms
and conditions of the **GNU Lesser General Public License v2.1 or later**.

New sources that cannot be distributed under LGPL-2.1-or-later will no longer
be accepted for inclusion in the systemd project to maintain license uniformity.

Other Licenses

The following exceptions apply:

* some udev sources under src/udev/ are licensed under **GPL-2.0-or-later**, so the
  udev binaries as a
 whole are also distributed under **GPL-2.0-or-later**.
* the header files contained in src/basic/linux/ and src/shared/linux/ are copied
  verbatim from the Linux kernel source tree and are licensed under **GPL-2.0 WITH
  Linux-syscall-note** and are used within the scope of the Linux-syscall-note
  exception provisions
* the src/shared/initreq.h header is licensed under original license,
  LGPL-2.0-or-later.
* the src/shared/linux/bpf_insn.h header is copied from the Linux kernel
  source tree and is licensed under either **BSD-2-Clause** or **GPL-2.0-only**,
  and thus is included in the systemd build under the BSD-2-Clause license.
* The src/basic/linux/wireguard.h header is copied from the Linux kernel
  source tree and is licensed under either **MIT** or **GPL-2.0 WITH Linux-syscall-note**,

and thus is included in the systemd build under the MIT license.
* the following sources are licensed under the **MIT** license (in case of our
scripts, to facilitate copying
and reuse of those helpers to other projects):
- hwdb.d/parse_hwdb.py
- src/basic/linux/batman_adv.h
- src/basic/sparse-endian.h
- tools/catalog-report.py
* the following sources are licensed under the **CC0-1.0** license:
- src/basic/siphash24.c
- src/basic/siphash24.h
- tools/check-includes.pl
* the following sources are licensed under the **MIT-0** license:
- all examples under man/
- src/systemctl/systemd-sysv-install.SKELETON
- config files and examples under /network
* the following sources are under **Public Domain** (LicenseRef-murmurhash2-public-domain):
- src/basic/MurmurHash2.c
- src/basic/MurmurHash2.h
* the following sources are under **Public Domain** (LicenseRef-lookup3-public-domain):
- src/libsystemd/sd-journal/lookup3.c
- src/libsystemd/sd-journal/lookup3.h
* the tools/chromiumos/gen_autosuspend_rules.py script is licensed under the
BSD-3-Clause license.
* Heebo fonts under docs/fonts/ are licensed under the
SIL Open Font License 1.1,
* any files under test/ without an explicit license we assume non-copyrightable
(eg: computer-generated fuzzer data)

OpenSSL Notes

Note that building the systemd project with OpenSSL does not affect the libsystemd.so
shared library, which is not linked with the OpenSSL library.
MurmurHash2 was written by Austin Appleby, and is placed in the public
domain. The author hereby disclaims copyright to this source code.
GNU LIBRARY GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public
Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it.
And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most
GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public
License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library".
The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright
law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that
uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole.
If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections
1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because
it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work
is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you
must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may
place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void,
and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or

modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may
not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of
this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted
in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify
a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting

the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the
public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

one line to give the library's name and an idea of what it does.
Copyright (C) year name of author

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write

to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in
the library `Frob' (a library for tweaking knobs) written
by James Random Hacker.

signature of Ty Coon, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
// Copyright 2014 The Chromium OS Authors. All rights reserved.
//
// Redistribution and use in source and binary forms, with or without
// modification, are permitted provided that the following conditions are
// met:
//
//   * Redistributions of source code must retain the above copyright
// notice, this list of conditions and the following disclaimer.
//   * Redistributions in binary form must reproduce the above
// copyright notice, this list of conditions and the following disclaimer
// in the documentation and/or other materials provided with the
// distribution.
//   * Neither the name of Google Inc. nor the names of its
// contributors may be used to endorse or promote products derived from
// this software without specific prior written permission.
//
// THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
// "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
// LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
// A PARTICULAR
 PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
// OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
// SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
// LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
// DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
// THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
// (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
// OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
lookup3.c, by Bob Jenkins, May 2006, Public Domain.
Copyright (c) <dates>, <Copyright Holder> (<URL|email>),
with Reserved Font Name <Reserved Font Name>.
Copyright (c) <dates>, <additional Copyright Holder> (<URL|email>),
with Reserved Font Name <additional Reserved Font Name>.

Copyright (c) <dates>, <additional Copyright Holder> (<URL|email>).

This Font Software is licensed under the SIL Open Font License, Version 1.1.
This license is copied below, and is also available with a FAQ at:
http://scripts.sil.org/OFL

SIL OPEN FONT LICENSE Version 1.1 - 26 February 2007

PREAMBLE
The goals of the Open Font License (OFL) are to stimulate worldwide development of collaborative font projects, to support the font creation efforts of academic and linguistic communities, and to provide a free and open framework in which fonts may be shared and improved in partnership with others.

The OFL allows the licensed fonts to be used, studied,
modified and
redistributed freely as long as they are not sold by themselves. The fonts, including any derivative works, can be bundled, embedded, redistributed and/or sold with any software provided that any reserved names are not used by derivative works. The fonts and derivatives, however, cannot be released under any other type of license. The requirement for fonts to remain under this license does not apply to any document created using the fonts or their derivatives.

DEFINITIONS
"Font Software" refers to the set of files released by the Copyright Holder(s) under this license and clearly marked as such. This may include source files, build scripts and documentation.

"Reserved Font Name" refers to any names specified as such after the copyright statement(s).

"Original Version" refers to the collection of Font Software components as distributed by the Copyright Holder(s).

"Modified Version" refers to any derivative made by adding to, deleting, or substituting -- in part
or in whole -- any of the components of the
Original Version, by changing formats or by porting the Font Software to a new environment.

"Author" refers to any designer, engineer, programmer, technical writer or other person who contributed to the Font Software.

PERMISSION & CONDITIONS
Permission is hereby granted, free of charge, to any person obtaining
a copy of the Font Software, to use, study, copy, merge, embed, modify,
redistribute, and sell modified and unmodified copies of the Font
Software, subject to the following conditions:

1) Neither the Font Software nor any of its individual components,
in Original or Modified Versions, may be sold by itself.

2) Original or Modified Versions of the Font Software may be bundled,
redistributed and/or sold with any software, provided that each copy
contains the above copyright notice and this license. These can be
included either as stand-alone text files, human-readable headers or
in the appropriate machine-readable metadata fields within
text or
binary files as long as those fields can be easily viewed by the user.

3) No Modified Version of the Font Software may use the Reserved Font
Name(s) unless explicit written permission is granted by the corresponding
Copyright Holder. This restriction only applies to the primary font name as
presented to the users.

4) The name(s) of the Copyright Holder(s) or the Author(s) of the Font
Software shall not be used to promote, endorse or advertise any
Modified Version, except to acknowledge the contribution(s) of the
Copyright Holder(s) and the Author(s) or with their explicit written
permission.

5) The Font Software, modified or unmodified, in part or in whole,
must be distributed entirely under this license, and must not be
distributed under any other license. The requirement for fonts to
remain under this license does not apply to any document created
using the Font Software.

TERMINATION
This license becomes null and void if any of the above conditions are
not met.

DISCLAIMER
THE
FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT
OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL THE
COPYRIGHT HOLDER BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL
DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM

OTHER DEALINGS IN THE FONT SOFTWARE.

NOTE! This copyright does *not* cover user programs that use kernel services by normal system calls - this is merely considered normal use of the kernel, and does *not* fall under the heading of "derived work". Also note that the GPL below is copyrighted by the Free Software Foundation, but the instance of code that it refers to (the Linux kernel) is copyrighted by me and others who actually wrote it.

Also note that the only valid version of the GPL as far as the kernel is concerned is _this_ particular version of the license (ie v2, not v2.2 or v3.x or whatever), unless explicitly otherwise stated.

Linus Torvalds

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that

you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies

of the Program's
source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole
or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest

your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the

source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution
of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any

patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through
 any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

 8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

 9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number
 of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

 10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

 11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along

with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w'
and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
MIT License

Copyright (c) <year> <copyright holders>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A

PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (c) <year> <owner> All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
MIT No Attribution

Copyright <YEAR> <COPYRIGHT HOLDER>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES

REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons")
that the public can reliably and without fear
of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal
effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
ii. moral rights retained by the original author(s) and/or performer(s);
iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
vi. database rights (such as those arising under Directive 96/9/EC of the

European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation

thereof, including any amended or successor version of such directive); and

vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's

express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.
b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.
c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.
d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

1.185 systemd 252-55.el9_7.7

1.185.1 Available under license :

systemd Project Licensing

Main License

The systemd project uses single-line references to Unique License Identifiers as defined by the Linux Foundation's SPDX project (https://spdx.org/). The line in each individual source file identifies the license applicable to that file.

The current set of valid, predefined SPDX identifiers can be found on the SPDX License List at https://spdx.org/licenses/.

The 'LICENSES/' directory contains all the licenses used by the sources included in the systemd project source tree.

Unless otherwise noted, the systemd project sources are licensed under the terms and conditions of the **GNU Lesser General Public License v2.1 or later**.

New sources that cannot be distributed under LGPL-2.1-or-later will no longer be accepted for inclusion in the systemd project to maintain license uniformity.

Other Licenses

The following exceptions apply:

* some udev sources under src/udev/ are licensed under **GPL-2.0-or-later**, so the
  udev binaries as a
 whole are also distributed under **GPL-2.0-or-later**.
* the header files contained in src/basic/linux/ and src/shared/linux/ are copied
  verbatim from the Linux kernel source tree and are licensed under **GPL-2.0 WITH
  Linux-syscall-note** and are used within the scope of the Linux-syscall-note
  exception provisions
* the src/shared/initreq.h header is licensed under original license,
  LGPL-2.0-or-later.
* the src/shared/linux/bpf_insn.h header is copied from the Linux kernel
  source tree and is licensed under either **BSD-2-Clause** or **GPL-2.0-only**,
  and thus is included in the systemd build under the BSD-2-Clause license.
* The src/basic/linux/wireguard.h header is copied from the Linux kernel
  source tree and is licensed under either **MIT** or **GPL-2.0 WITH Linux-syscall-note**,
  and thus is included in the systemd build under the MIT license.
* the following sources are licensed under the **MIT** license (in case of our
  scripts, to facilitate copying
 and reuse of those helpers to other projects):
  - hwdb.d/parse_hwdb.py
  - src/basic/linux/batman_adv.h
  - src/basic/sparse-endian.h
  - tools/catalog-report.py
* the following sources are licensed under the **CC0-1.0** license:
  - src/basic/siphash24.c
  - src/basic/siphash24.h
  - tools/check-includes.pl
 * the following sources are licensed under the **MIT-0** license:
  - all examples under man/
  - src/systemctl/systemd-sysv-install.SKELETON
  - config files and examples under /network
* the following sources are under **Public Domain** (LicenseRef-murmurhash2-public-domain):
  - src/basic/MurmurHash2.c
  - src/basic/MurmurHash2.h
* the following sources are under **Public Domain** (LicenseRef-lookup3-public-domain):
  - src/libsystemd/sd-journal/lookup3.c
  - src/libsystemd/sd-journal/lookup3.h
* the tools/chromiumos/gen_autosuspend_rules.py script is licensed under the
  BSD-3-Clause license.
* Heebo fonts under docs/fonts/ are licensed under the
 SIL Open Font License 1.1,
* any files under test/ without an explicit license we assume non-copyrightable
  (eg: computer-generated fuzzer data)

OpenSSL Notes

Note that building the systemd project with OpenSSL does not affect the libsystemd.so
shared library, which is not linked with the OpenSSL library.
MurmurHash2 was written by Austin Appleby, and is placed in the public
domain. The author hereby disclaims copyright to this source code.
GNU LIBRARY GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public
Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it.
And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that

what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most
GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public
License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library".
The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A

"work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you

distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work
under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections
1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because
it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether

it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work
is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you
must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may
place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate

distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted
in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify
a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the
public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public

License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

one line to give the library's name and an idea of what it does.
Copyright (C) year name of author

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in
the library `Frob' (a library for tweaking knobs) written
by James Random Hacker.

signature of Ty Coon, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
// Copyright 2014 The Chromium OS Authors. All rights reserved.
//
// Redistribution and use in source and binary forms, with or without
// modification, are permitted provided that the following conditions are
// met:
//
//   * Redistributions of source code must retain the above copyright
// notice, this list of conditions and the following disclaimer.
//   * Redistributions in binary form must reproduce the above
// copyright notice, this list of conditions and the following disclaimer
// in the documentation and/or other materials provided with the
// distribution.
//   * Neither the name of Google Inc. nor the names of its
// contributors may be used to endorse or promote products derived from

// this software without specific prior written permission.
//
// THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
// "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
// LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
// A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
// OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
// SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
// LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
// DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
// THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
// (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
// OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
lookup3.c, by Bob Jenkins, May 2006, Public Domain.
Copyright (c) <dates>, <Copyright Holder> (<URL|email>),
with Reserved Font Name <Reserved Font Name>.
Copyright (c) <dates>, <additional Copyright Holder> (<URL|email>),
with Reserved Font Name <additional Reserved Font Name>.
Copyright (c) <dates>, <additional Copyright Holder> (<URL|email>).

This Font Software is licensed under the SIL Open Font License, Version 1.1.
This license is copied below, and is also available with a FAQ at:
http://scripts.sil.org/OFL

SIL OPEN FONT LICENSE Version 1.1 - 26 February 2007

PREAMBLE
The goals of the Open Font License (OFL) are to stimulate worldwide
development of collaborative font projects, to support the font creation
efforts of academic and linguistic communities, and to provide a free and
open framework in which fonts may be shared and improved in partnership
with others.

The OFL allows the licensed fonts to be used, studied,
modified and
redistributed freely as long as they are not sold by themselves. The
fonts, including any derivative works, can be bundled, embedded,
redistributed and/or sold with any software provided that any reserved
names are not used by derivative works. The fonts and derivatives,
however, cannot be released under any other type of license. The
requirement for fonts to remain under this license does not apply
to any document created using the fonts or their derivatives.

DEFINITIONS

"Font Software" refers to the set of files released by the Copyright Holder(s) under this license and clearly marked as such. This may include source files, build scripts and documentation.

"Reserved Font Name" refers to any names specified as such after the copyright statement(s).

"Original Version" refers to the collection of Font Software components as distributed by the Copyright Holder(s).

"Modified Version" refers to any derivative made by adding to, deleting, or substituting -- in part or in whole -- any of the components of the Original Version, by changing formats or by porting the Font Software to a new environment.

"Author" refers to any designer, engineer, programmer, technical writer or other person who contributed to the Font Software.

PERMISSION & CONDITIONS
Permission is hereby granted, free of charge, to any person obtaining a copy of the Font Software, to use, study, copy, merge, embed, modify, redistribute, and sell modified and unmodified copies of the Font Software, subject to the following conditions:

1) Neither the Font Software nor any of its individual components, in Original or Modified Versions, may be sold by itself.

2) Original or Modified Versions of the Font Software may be bundled, redistributed and/or sold with any software, provided that each copy contains the above copyright notice and this license. These can be included either as stand-alone text files, human-readable headers or in the appropriate machine-readable metadata fields within text or binary files as long as those fields can be easily viewed by the user.

3) No Modified Version of the Font Software may use the Reserved Font Name(s) unless explicit written permission is granted by the corresponding Copyright Holder. This restriction only applies to the primary font name as presented to the users.

4) The name(s) of the Copyright Holder(s) or the Author(s) of the Font Software shall not be used to promote, endorse or advertise any Modified Version, except to acknowledge the contribution(s) of the Copyright Holder(s) and the Author(s) or with their explicit written permission.

5) The Font Software, modified or unmodified, in part or in whole,

must be distributed entirely under this license, and must not be
distributed under any other license. The requirement for fonts to
remain under this license does not apply to any document created
using the Font Software.

TERMINATION
This license becomes null and void if any of the above conditions are
not met.

DISCLAIMER
THE
FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL THE COPYRIGHT HOLDER BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

NOTE! This copyright does *not* cover user programs that use kernel
services by normal system calls - this is merely considered normal use
of the kernel, and does *not* fall under the heading of "derived work".
Also note that the GPL below is copyrighted by the Free Software
Foundation, but the instance of code that it refers to (the Linux
kernel) is copyrighted by me and others who actually wrote it.

Also note that the only valid version of the GPL as far as the kernel
is concerned is _this_ particular version of the license (ie v2, not
v2.2 or v3.x or whatever), unless explicitly otherwise stated.

Linus Torvalds

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to

using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which

contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide

a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or

executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the
source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number

of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest

to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

  <one line to give the program's name and a brief idea of what it does.>
  Copyright (C) <year> <name of author>

  This program is free software; you can redistribute it and/or modify
  it under the terms of the GNU General Public License as published by
  the Free Software Foundation; either version 2 of the License,
or
  (at your option) any later version.

  This program is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
  GNU General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w'
 and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.
MIT License

Copyright (c) <year> <copyright holders>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (c) <year> <owner> All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
MIT No Attribution

Copyright <YEAR> <COPYRIGHT HOLDER>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons")
that the public can reliably and without fear
of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its

terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal
effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
ii. moral rights retained by the original author(s) and/or performer(s);
iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation

thereof, including any amended or successor version of such directive); and
vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the
Waiver for the benefit of each
member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the

Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable
law or treaty (including future
time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected
by this document.
b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.
c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.
d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with
respect to
this CC0 or use of the Work.

1.186 tzdata 2025c-1.el9

1.186.1 Available under license :

Unless specified below, all files in the tz code and data (including this LICENSE file) are in the public domain.

If the files date.c, newstrftime.3, and strftime.c are present, they contain material derived from BSD and use the BSD 3-clause license.

1.187 log4j-jcl 2.25.3

1.187.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Log4j Commons Logging Bridge
Copyright 1999-2025 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.188 log4j-api 2.25.3

1.188.1 Available under license :

Apache Log4j API
Copyright 1999-2025 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License

Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,

except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the

same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.189 apache-log4j 2.25.3

1.189.1 Available under license :

Apache Log4j Core
Copyright 1999-2012 Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

ResolverUtil.java
Copyright 2005-2006 Tim Fennell

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright 1999-2005 The Apache Software Foundation

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and

limitations under the License.

1.190 jctools-core 4.0.1

1.190.1 Available under license :

No license file was found, but licenses were detected in source scan.

<name>Apache License, Version 2.0</name>
<url>http://www.apache.org/licenses/LICENSE-2.0.txt</url>

Found in path(s):
* /jctools-core-4-0-1-java-jar/META-INF/maven/org.jctools/jctools-core/pom.xml
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /jctools-core-4-0-1-java-jar/org/jctools/queues/BaseSpscLinkedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/InternalAPI.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscChunkedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpmcUnboundedXaddArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/SpscChunkedUnpaddedArrayQueue.java
*
 /jctools-core-4-0-1-java-jar/org/jctools/queues/SpscChunkedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SpscGrowableAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SpscUnboundedAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/ConcurrentCircularArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/BaseLinkedAtomicQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/NonBlockingSetInt.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/MpmcAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/ConcurrentSequencedCircularUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/MpscChunkedUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/BaseMpscLinkedUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/MpscUnpaddedArrayQueue.java
*

/jctools-core-4-0-1-java-jar/org/jctools/queues/MpscBlockingConsumerArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/MpscAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SpmcAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/SpscGrowableArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SpscAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/MpscLinkedAtomicQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/SpscUnboundedUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscUnboundedXaddChunk.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/RangeUtil.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/ConcurrentCircularUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/NonBlockingHashMap.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/SpscUnboundedArrayQueue.java
*
/jctools-core-4-0-1-java-jar/org/jctools/queues/MessagePassingQueueUtil.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/BaseMpscLinkedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/SpmcUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/MpscUnboundedUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/SpscGrowableUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/SpscUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/MpscGrowableAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/ConcurrentSequencedCircularArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SequencedAtomicReferenceArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/UnsafeJvmInfo.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/BaseMpscLinkedAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscLinkedQueue.java
*
/jctools-core-4-0-1-java-jar/org/jctools/queues/SpmcArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/LinkedQueueAtomicNode.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/LinkedQueueNode.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/AbstractEntry.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscUnboundedXaddArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/AtomicReferenceArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/PaddedAtomicLong.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/UnsafeRefArrayAccess.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/BaseSpscLinkedAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MessagePassingQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/SpscLinkedQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/NonBlockingIdentityHashMap.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpmcArrayQueue.java
*
/jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/MpscUnboundedAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/MpscLinkedUnpaddedQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/NonBlockingHashMapLong.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/SpscLinkedUnpaddedQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/UnsafeAccess.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/SpscArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/ConcurrentAutoTable.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscArrayQueue.java

* /jctools-core-4-0-1-java-jar/org/jctools/util/PortableJvmInfo.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/MpscGrowableUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscUnboundedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SpscLinkedAtomicQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/BaseLinkedUnpaddedQueue.java
*
/jctools-core-4-0-1-java-jar/org/jctools/util/Pow2.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/SpscChunkedAtomicArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/package-info.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/BaseSpscLinkedUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/IndexedQueueSizeUtil.java
* /jctools-core-4-0-1-java-jar/org/jctools/util/UnsafeLongArrayAccess.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/unpadded/MpmcUnpaddedArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscGrowableArrayQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/maps/NonBlockingHashSet.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/BaseLinkedQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpscCompoundQueue.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/MpmcUnboundedXaddChunk.java
* /jctools-core-4-0-1-java-jar/org/jctools/queues/atomic/MpscChunkedAtomicArrayQueue.java
*
/jctools-core-4-0-1-java-jar/org/jctools/queues/SupportsIterator.java

1.191 gnupg 2.3.3-5.el9_7

1.191.1 Available under license :

Here is a list with collected copyright notices. For details see the
description of each individual package. [Compiled by wk 2017-11-07]

GNUPG is

Copyright (C) 1997-2017 Werner Koch
Copyright (C) 1994-2017 Free Software Foundation, Inc.
Copyright (C) 2003-2017 g10 Code GmbH
Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 1995-1997, 2000-2007 Ulrich Drepper <drepper@gnu.ai.mit.edu>
Copyright (C) 1994 X Consortium
Copyright (C) 1998 by The Internet Society.
Copyright (C) 1998-2004 The OpenLDAP Foundation
Copyright (C) 1998-2004 Kurt D. Zeilenga.
Copyright (C) 1998-2004 Net Boolean Incorporated.
Copyright (C) 2001-2004 IBM Corporation.
Copyright (C) 1999-2003 Howard Y.H. Chu.
Copyright (C) 1999-2003 Symas Corporation.
Copyright (C) 1998-2003 Hallvard B. Furuseth.
Copyright (C) 1992-1996 Regents of the University of Michigan.
Copyright (C) 2000 Dimitrios Souflis

Copyright (C) 2008,2009,2010,2012-2016 William Ahern

GnuPG is free software;
you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

GnuPG is distributed in the hope that it will be useful, but WITHOUT
ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public
License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <https://www.gnu.org/licenses/>.

LIBGCRYPT is

Copyright (C) 1989,1991-2017 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 1996 L. Peter Deutsch
Copyright (C) 1997 Werner Koch
Copyright (C) 1998 The Internet Society
Copyright (C) 1996-1999 Peter Gutmann, Paul Kendall, and Chris Wedgwood
Copyright (C) 1996-2006 Peter Gutmann, Matt Thomlinson and Blake Coverett
Copyright (C) 2003 Nikos Mavroyanopoulos
Copyright (C) 2006-2007 NTT (Nippon Telegraph and Telephone Corporation)
Copyright (C) 2012-2017 g10 Code GmbH
Copyright (C) 2012 Simon Josefsson, Niels Mller
Copyright (c) 2012 Intel Corporation
Copyright (C) 2013 Christian Grothoff
Copyright (C) 2013-2017 Jussi Kivilinna
Copyright (C) 2013-2014 Dmitry Eremin-Solenikov
Copyright (C) 2014 Stephan Mueller
Copyright (C) 2017 Bundesamt fr Sicherheit in der Informationstechnik

Libgcrypt is free software; you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

Libgcrypt is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Lesser General Public License for more details.

You should have received a copy of the

GNU Lesser General Public
License along with this program; if not, see <http://www.gnu.org/licenses/>.

LIBGPG-ERROR is

Copyright (C) 2003-2004, 2010, 2013-2017 g10 Code GmbH

libgpg-error is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public License
as published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

libgpg-error is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License
along with this program; if not, see <http://www.gnu.org/licenses/>.

LIBASSUAN is

Copyright (C) 1992-2013 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 2000 Werner Koch (dd9jn)
Copyright (C)
2001-2016 g10 Code GmbH
Copyright (C) 2004 Simon Josefsson

Assuan is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

Assuan is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this program; if not, see <http://www.gnu.org/licenses/>.

LIBKSBA is

Copyright (C) 2001, 2002, 2003, 2004, 2005, 2006, 2010, 2011

2012, 2013, 2014, 2015 g10 Code GmbH
Copyright (C) 2001, 2002, 2003, 2007 Free Software Foundation, Inc.
Copyright (C) 2000, 2001 Fabio Fiorina

The library and the header files are distributed under
the following
terms (LGPLv3+/GPLv2+):

KSBA is free software; you can redistribute it and/or modify
it under the terms of either

- the GNU Lesser General Public License as published by the Free
  Software Foundation; either version 3 of the License, or (at
  your option) any later version.

or

- the GNU General Public License as published by the Free
  Software Foundation; either version 2 of the License, or (at
  your option) any later version.

or both in parallel, as here.

KSBA is distributed in the hope that it will be useful, but WITHOUT
ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public
License for more details.

The other parts (e.g. manual, build system, tests) are distributed
under the following terms (GPLv3):

KSBA is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the
Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

KSBA is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

NPTH is

Copyright (C) 2011, 2012, 2014, 2015, 2017 g10 Code GmbH

nPth is free software; you can redistribute it and/or modify

it under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

nPth is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See
the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this program;
if not, see <https://www.gnu.org/licenses/>.

NTBTLS is

Copyright (C) 2006-2014 Brainspark B.V.
Copyright (C) 2014-2017 g10 Code GmbH

NTBTLS is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

NTBTLS is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <http://www.gnu.org/licenses/>.

PINENTRY is

Copyright (C) 1999 Robert Bihlmeyer <robbe@orcus.priv.at>
Copyright (C) 2001-2004, 2007-2008, 2010, 2015-2016 g10 Code GmbH
Copyright (C) 2002, 2008 Klarlvdalens Datakonsult AB (KDAB)
Copyright (C) 2004 by Albrecht
Dre <albrecht.dress@arcor.de>
Copyright 2007 Ingo Klcker
Copyright (C) 2014 Serge Voilokov
Copyright (C) 2015 Daiki Ueno
Copyright (C) 2015 Daniel Kahn Gillmor <dkg@fifthhorseman.net>
Copyright 2016 Intevation GmbH

PINENTRY is free software; you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by

the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

PINENTRY is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <https://www.gnu.org/licenses/>.

GPGME is

Copyright (C) 1991-2013 Free Software Foundation, Inc.
Copyright (C) 2000-2001 Werner Koch
Copyright (C) 2001-2017 g10 Code GmbH

Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 2004-2008 Igor Belyi
Copyright (C) 2002 John Goerzen
Copyright (C) 2014, 2015 Martin Albrecht
Copyright (C) 2015 Ben McGinnes
Copyright (C) 2015-2016 Bundesamt fr Sicherheit in der Informationstechnik
Copyright (C) 2016 Intevation GmbH

GPGME is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

GPGME is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License
along with this program; if not, see <http://www.gnu.org/licenses/>.

NSIS is

Copyright 1999-2009 Nullsoft and Contributors
Copyright 2002-2008 Amir Szekely
Copyright 2003 Ramon

This license applies to everything in the NSIS package, except where
otherwise noted.

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

The user interface used with the installer is

Copyright 2002-2009 Joost Verburg

[It is distributed along with NSIS and the same conditions as stated above apply]

TinySCHEME is part of the GnuPG package and is

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED
BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LIBDNS is part of the GnuPG package and is

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"),
to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.

ZLIB is

(C) 1995-2013 Jean-loup Gailly and Mark Adler

This software is provided
'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

BZIP2 is

This program, "bzip2", the associated library "libbzip2", and all
documentation,
are copyright (C) 1996-2010 Julian R Seward. All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must
   not claim that you wrote the original software. If you use this
   software in a product, an acknowledgment in the product
   documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
   not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote
   products derived from this software without specific prior written
   permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS
OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

SQLITE has

been put into the public-domain by its author D. Richard Hipp:
The author disclaims copyright to this source code. In place of
a legal notice, here is a blessing:

May you do good and not evil.
May you find forgiveness for yourself and forgive others.
May you share freely, never taking more than you give.

[Note that only a few files are distributed under this license.]

Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing
to a commons of creative, cultural and
scientific works ("Commons") that the public can reliably and without fear of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific

works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
ii. moral rights retained by the original author(s) and/or performer(s);
iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and
vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each

member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.
b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.
c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.
d. Affirmer understands and acknowledges that Creative Commons is

not a
party to this document and has no duty or obligation with respect to
this CC0 or use of the Work.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1) assert copyright on the software, and (2) offer
you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those
domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To
"modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate
Legal Notices"
to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than
the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all

the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users'

Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep
intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license
the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7

additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This

alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge.
You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object
code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute
modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because

modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you

add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections
15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional
terms are considered "further
restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may
not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your
receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time
you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not
impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control"
includes the right to grant
patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not

excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING,
BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer
of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea

of what it does.>
  Copyright (C) <year> <name of author>

  This program is free software: you can redistribute it and/or modify
  it under the terms of the GNU General Public License as published by
  the Free Software Foundation, either version 3 of the License, or
  (at your option) any later version.

  This program is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
  GNU General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

 If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

  <program> Copyright (C) <year> <name of author>
  This program comes with ABSOLUTELY
 NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

 You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

 The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But first,
 please read
<https://www.gnu.org/philosophy/why-not-lgpl.html>.
                GNU GENERAL PUBLIC LICENSE
                  Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free

program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause

any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the

Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if

necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically
libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get

it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected
by problems that might be
introduced by others.
^L
Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original

library. The ordinary
General Public License therefore permits such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it
becomes a de-facto standard. To achieve this, non-free programs must
be allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free
libraries. In this
case, there is little to gain by limiting the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating
system.

Although the Lesser General Public License is Less protective of the
users' freedom, it does ensure that the user of a program that is
linked with the Library has the freedom and the wherewithal to run
that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and
modification follow. Pay close attention to the difference between a
"work based on the library" and a "work that uses the library". The
former contains code derived from the library,
whereas the latter must
be combined with the library in order to run.
^L
GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other
program which contains a notice placed by the copyright holder or
other authorized party saying it may be distributed under the terms of

this Lesser General Public License (also called "this License").
Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data
prepared so as to be conveniently linked with application programs
(which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work
which has been distributed under these terms. A "work based on the
Library" means either the Library or any derivative work under
copyright law: that is to say, a work containing the Library or a
portion of it, either verbatim
or with modifications and/or translated
straightforwardly into another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for
making modifications to it. For a library, complete source code means
all the source code for all modules it contains, plus any associated
interface definition files, plus the scripts used to control
compilation and installation of the library.

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running a program using the Library is not restricted, and output from
such a program is covered only if its contents constitute a work based
on the Library (independent of the use of the Library in a tool for
writing it). Whether that is true depends on what the Library does
and what the program that uses the Library does.

1. You may copy and distribute verbatim copies
of the Library's
complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an
appropriate copyright notice and disclaimer of warranty; keep intact
all the notices that refer to this License and to the absence of any
warranty; and distribute a copy of this License along with the
Library.

You may charge a fee for the physical act of transferring a copy,
and you may at your option offer warranty protection in exchange for a
fee.

2. You may modify your copy or copies of the Library or any portion
of it, thus forming a work based on the Library, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections
1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library
(because it
contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if

the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the
materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.
^L
7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library
with a copy of the same work
based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the
Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole

purpose of protecting the
integrity of the free software distribution system which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License
may add an explicit geographical distribution limitation excluding those
countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written
in the body of this License.

13. The Free Software Foundation may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.
^L
14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the
Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY
OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It
is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free
Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

LICENSE TERMS

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the

Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without
being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material
is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library

facilities that are not Applications and are not
covered by this
License, and convey such a combined library under terms of your
choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based
on the Library, uncombined with any other library facilities,
conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it
is a work based on the Library, and explaining where to find the
accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions
of the GNU Lesser General Public License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the
Library as you received it specifies that a certain numbered version
of the GNU Lesser General Public License "or
any later version"
applies to it, you have the option of following the terms and
conditions either of that published version or of any later version
published by the Free Software Foundation. If the Library as you
received it does not specify a version number of the GNU Lesser
General Public License, you may choose any version of the GNU Lesser
General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide
whether future versions of the GNU Lesser General Public License shall
apply, that proxy's public statement of acceptance of any version is
permanent authorization for you to choose that version for the
Library.
COPYING.other -*- org -*-
#+TITLE: List of code with permissive licenses as used by GnuPG.
#+STARTUP: showall

* DNS resolver (dirmngr/dns.c)

dns.c - Recursive, Reentrant DNS Resolver.

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY
OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.

* TinySCHEME (tests/gpgscm/LICENSE.TinySCHEME)

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided
with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

* Regular
expression support

regexp/jimregexp.[ch]:

Originally:

Copyright (c) 1986 by University of Toronto.
Written by Henry Spencer. Not derived from licensed software.

Subsequently modified by:

1986 John Gilmore hoptoad!gnu
1987 James A. Woods ames!jaw
1993 Christopher Seiwald seiwald@vix.com
2000, 2002 Christopher Seiwald <seiwald@perforce.com>
2010 Steve Bennett <steveb@workware.net.au>
2020 NIIBE Yutaka <gniibe@fsij.org>

Permission is granted to anyone to use this software for any
purpose on any computer system, and to redistribute it freely,
subject to the following restrictions:

1. The author is not responsible for the consequences of use of
this software, no matter how awful, even if they arise
from defects in it.

2. The origin of this software must not be misrepresented, either
by explicit claim or by omission.

3. Altered versions must be plainly marked as such, and must not
be misrepresented as being the
original software.

regexp/utf8.[ch] (see regexp/LICENSE):

(c) 2010-2016 Steve Bennett <steveb@workware.net.au>

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above
   copyright notice, this list of conditions and the following
   disclaimer in the documentation and/or other materials
   provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE JIM TCL PROJECT ``AS IS'' AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
JIM TCL PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation
are those of the authors and should not be interpreted as representing
official policies, either expressed or implied, of the Jim Tcl Project.

UnicodeData.txt:

Copyright 1991-2020 Unicode, Inc. All rights reserved.
Distributed under the Terms of Use in https://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining
a copy of the Unicode data files and any associated documentation
(the "Data Files") or Unicode software and any associated documentation
(the "Software")
to deal in the Data Files or Software
without restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, and/or sell copies of
the Data Files or Software, and to permit persons to whom the Data Files
or Software are furnished to do so, provided that either
(a) this copyright and permission notice appear with all copies
of the Data Files or Software, or
(b) this copyright and permission notice appear in associated
Documentation.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF
ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT OF THIRD PARTY RIGHTS.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS

NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.

1.192 glib 2.68.4-18.el9_7.1

1.192.1 Available under license :

This work may be reproduced and distributed in whole or in part, in any medium, physical or electronic, so as long as this copyright notice remains intact and unchanged on all copies. Commercial redistribution is permitted and encouraged, but you may not redistribute, in whole or in part, under terms more restrictive than those under which you received it. If you redistribute a modified or translated version of this work, you must also make the source code to the modified or translated version available in electronic form without charge. However, mere aggregation as part of a larger work shall not count as a modification for this purpose.

All code examples in this work are placed into the public domain, and may be used, modified and redistributed without restriction.

BECAUSE THIS WORK IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE WORK, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE WORK "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. SHOULD THE WORK PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY REPAIR OR CORRECTION.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE WORK AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE WORK, EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

PCRE LICENCE

Please see the file LICENCE in the PCRE distribution for licensing details.

End

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave

you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into

another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that,

in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of

the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these

materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if

you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR

CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.193 curl-minimal 7.76.1-35.el9_7.3

1.193.1 Available under license :

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1996 - 2021, Daniel Stenberg, <daniel@haxx.se>, and many
contributors, see the THANKS file.

All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright
notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE
OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not
be used in advertising or otherwise to promote the sale, use or other
dealings
in this Software without prior written authorization of the copyright holder.

1.194 libcurl 7.76.1-35.el9_7.3

1.194.1 Available under license :

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1996 - 2021, Daniel Stenberg, <daniel@haxx.se>, and many
contributors, see the THANKS file.

All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright

notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not
be used in advertising or otherwise to promote the sale, use or other
dealings
in this Software without prior written authorization of the copyright holder.

1.195 curl 7.76.1-35.el9_7.3

1.195.1 Available under license :

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1996 - 2021, Daniel Stenberg, <daniel@haxx.se>, and many
contributors, see the THANKS file.

All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright
notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not
be used in advertising or otherwise to promote the sale, use or other
dealings
in this Software without prior written authorization of the copyright holder.

1.196 openssl 1:3.5.1-7.el9_7

1.196.1 Available under license :

This software is copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software; you can redistribute it and/or modify it under
the same terms as the Perl 5 programming language system itself.

Terms of the Perl programming language system itself

a) the GNU General Public License as published by the Free
  Software Foundation; either version 1, or (at your option) any
  later version, or
b) the "Artistic License"

--- The GNU General Public License, Version 1, February 1989 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

 The GNU General Public License, Version 1, February 1989

                GNU GENERAL PUBLIC LICENSE
                 Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

                     Preamble

 The license agreements of most software companies try to keep users
at the mercy of those companies. By contrast, our General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. The
General Public License applies to the Free Software Foundation's
software and to any other program whose authors commit to using it.
You can use it for your programs, too.

 When we speak of free software, we are referring to freedom, not
price. Specifically, the General Public License is designed to make
sure that you have the freedom to give away or sell copies of free
software, that you receive source code or can get it if you want it,
that you can change the software or use pieces of it in new free
programs; and that you know you can do these things.

 To protect your rights, we need to make restrictions that forbid

anyone to deny you these rights or to ask you to surrender
the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

The precise terms and conditions
for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which
contains a notice placed by the copyright holder saying it may be
distributed under the terms of this General Public License. The
"Program", below, refers to any such program or work, and a "work based
on the Program" means either the Program or any work containing the
Program or a portion of it, either verbatim or with modifications. Each
licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source
code as you receive it, in any medium, provided that you conspicuously and
appropriately publish on each copy an appropriate copyright notice and
disclaimer of warranty; keep intact all the notices that refer to this
General Public License and to the absence of any warranty; and give any
other recipients of the
Program a copy of this General Public License
along with the Program. You may charge a fee for the physical act of
transferring a copy.

2. You may modify your copy or copies of the Program or any portion of
it, and copy and distribute such modifications under the terms of Paragraph

1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use
in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three years, to give any third party free (except for a nominal charge for the cost of distribution) a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the corresponding source code may be obtained. (This alternative is allowed only for noncommercial distribution and only if you

received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making modifications to it. For an executable file, complete source code means all the source code for all modules it contains; but, as a special exception, it need not include source code for modules which are standard libraries that
accompany the operating system on which the executable file runs, or for standard header files or definitions files that accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the Program except as expressly provided under this General Public License. Any attempt otherwise to copy, modify, sublicense, distribute or transfer the Program is void, and will automatically terminate your rights to use the Program under this License. However, parties who have received copies, or rights to use copies, from you under this General Public License will not have their licenses terminated so long as such parties remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based on the Program) you indicate your acceptance of this license to do so, and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the
original
licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of the license which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free programs whose distribution
conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free

Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to humanity, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so,
attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by

the Free Software Foundation; either version 1, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19xx name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the
appropriate parts of the General Public License. Of course, the
commands you use may be called something other than `show w' and `show
c'; they could even be mouse-clicks or menu items--whatever suits your
program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here a sample; alter
the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (a program to direct compilers to make passes
at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

--- The Artistic License 1.0 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The Artistic License 1.0

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

- "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.
- "Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.
- "Copyright Holder" is whoever is named in the copyright or copyrights for the package.
- "You" is you, if you're thinking about copying or distributing this Package.
- "Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)
- "Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as ftp.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified
Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names,
and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package.

7. C or perl subroutines supplied by you and linked into this Package
shall not
be considered part of this Package.

8. The name of the Copyright Holder may not be used to endorse or promote
products derived from this software without specific prior written permission.

9. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF
MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s)

with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.197 commons-jexl3 3.6.1

1.197.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

https://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons JEXL
Copyright 2001-2025 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

1.198 disruptor 3.3.6-java8

1.198.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.199 commons-codec 1.15.0

1.199.1 Available under license :

Apache Commons Codec
Copyright 2002-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

src/test/org/apache/commons/codec/language/DoubleMetaphoneTest.java
contains test data from http://aspell.net/test/orig/batch0.tab.
Copyright (C) 2002 Kevin Atkinson (kevina@gnu.org)

==========

The content of package org.apache.commons.codec.language.bm has been translated
from the original php source code available at http://stevemorse.org/phoneticinfo.htm
with permission from the original authors.
Original source copyright:
Copyright (c) 2008 Alexander Beider & Stephen P. Morse.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.200 io-opentelemetry-proto 0.11.0

1.200.1 Available under license :

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint$Buckets.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint$BucketsOrBuilder.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint$Buckets$Builder.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/ExponentialHistogramOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/ExponentialHistogram$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/Gauge.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/GaugeOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/Gauge$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/Histogram.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/HistogramDataPoint.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntGaugeOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntGauge$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntHistogram.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntHistogramDataPoint.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntHistogramDataPointOrBuilder.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntHistogramDataPoint$Builder.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntHistogramOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntHistogram$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntSum.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntSumOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntSum$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/Sum.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-

jar/io/opentelemetry/proto/metrics/v1/SumOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/metrics/v1/Sum$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/metrics/v1/Summary.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/metrics/v1/SummaryOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/metrics/v1/Summary$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/trace/v1/Span.class
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/trace/v1/SpanOrBuilder.class
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/collector/metrics/v1/metrics_service.proto//
Copyright 2019, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/collector/trace/v1/trace_service.proto//
Copyright 2019, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/common/v1/common.proto// Copyright 2019, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/logs/v1/logs.proto// Copyright 2020, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/metrics/experimental/metrics_config_service.proto// Copyright 2019, OpenTelemetry
Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/metrics/v1/metrics.proto// Copyright 2019, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/resource/v1/resource.proto//
Copyright 2019, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/trace/v1/trace.proto// Copyright 2019, OpenTelemetry Authors
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/trace/v1/trace_config.proto// Copyright 2019, OpenTelemetry Authors

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/io/opentelemetry/proto/trace/v1/Span$Builder.class
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-
jar/opentelemetry/proto/collector/logs/v1/logs_service.proto// Copyright 2020, OpenTelemetry Authors

Found in path(s):
* getEventsList

No license file was found, but licenses were detected in source scan.

/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/HistogramDataPointOrBuilder.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/HistogramDataPoint$Builder.class getBucketCountsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/HistogramOrBuilder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/Histogram$Builder.class getDataPointsList
/opt/cola/permits/2914852324_1770198320.6169837/0/opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/IntGauge.class getDataPointsList

Found in path(s):
*
No license file was found, but licenses were detected in source scan.

4
6io/opentelemetry/proto/metrics/v1/ExponentialHistogram <init>
T(Lcom/google/protobuf/CodedInputStream;Lcom/google/protobuf/ExtensionRegistryLite;)V
PARSER Lcom/google/protobuf/Parser;

unknownFields %Lcom/google/protobuf/UnknownFieldSet; alwaysUseFieldBuilders Z aggregationTemporality_ I
dataPoints_ Ljava/util/List;
3(Lcom/google/protobuf/GeneratedMessageV3$Builder;)V
&com/google/protobuf/GeneratedMessageV3 " #$ memoizedIsInitialized B
& ' ()V
)* + ,- java/util/Collections emptyList ()Ljava/util/List;
& 0 java/lang/NullPointerException
/&
34 5 67 #com/google/protobuf/UnknownFieldSet
newBuilder /()Lcom/google/protobuf/UnknownFieldSet$Builder;
9: ; <= $com/google/protobuf/CodedInputStream readTag ()I ? java/util/ArrayList
>&
BC D EF ?io/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint parser ()Lcom/google/protobuf/Parser;
9H IJ readMessage
j(Lcom/google/protobuf/Parser;Lcom/google/protobuf/ExtensionRegistryLite;)Lcom/google/protobuf/MessageLite;
LM N OP java/util/List add (Ljava/lang/Object;)Z
9R S= readEnum
U VW parseUnknownField
(Lcom/google/protobuf/CodedInputStream;Lcom/google/protobuf/UnknownFieldSet$Builder;Lcom/google/protobuf/ExtensionRegistryLite;I)Z
)Y Z[unmodifiableList "(Ljava/util/List;)Ljava/util/List;
]^ _ `a +com/google/protobuf/UnknownFieldSet$Builder build '()Lcom/google/protobuf/UnknownFieldSet;
c d' makeExtensionsImmutable f 2com/google/protobuf/InvalidProtocolBufferException
eh ij setUnfinishedMessage
W(Lcom/google/protobuf/MessageLite;)Lcom/google/protobuf/InvalidProtocolBufferException; l
java/io/IOException

en o (Ljava/io/IOException;)V qr s tu .io/opentelemetry/proto/metrics/v1/MetricsProto
Ninternal_static_opentelemetry_proto_metrics_v1_ExponentialHistogram_descriptor
,Lcom/google/protobuf/Descriptors$Descriptor; qw xy
Vinternal_static_opentelemetry_proto_metrics_v1_ExponentialHistogram_fieldAccessorTable
;Lcom/google/protobuf/GeneratedMessageV3$FieldAccessorTable; {
>io/opentelemetry/proto/metrics/v1/ExponentialHistogram$Builder
}~ • 9com/google/protobuf/GeneratedMessageV3$FieldAccessorTable ensureFieldAccessorsInitialized
_(Ljava/lang/Class;Ljava/lang/Class;)Lcom/google/protobuf/GeneratedMessageV3$FieldAccessorTable; L = size L   get
(I)Ljava/lang/Object; Hio/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPointOrBuilder
  8io/opentelemetry/proto/metrics/v1/AggregationTemporality valueOf
=(I)Lio/opentelemetry/proto/metrics/v1/AggregationTemporality;   UNRECOGNIZED
:Lio/opentelemetry/proto/metrics/v1/AggregationTemporality;   com/google/protobuf/MessageLite
  %com/google/protobuf/CodedOutputStream writeMessage %(ILcom/google/protobuf/MessageLite;)V
#AGGREGATION_TEMPORALITY_UNSPECIFIED
 = getNumber
  writeEnum (II)V
3   writeTo *(Lcom/google/protobuf/CodedOutputStream;)V   memoizedSize
  computeMessageSize %(ILcom/google/protobuf/MessageLite;)I
  computeEnumSize (II)I
3 = getSerializedSize
 P equals
 - getDataPointsList L
3   memoizedHashCode

getDescriptor .()Lcom/google/protobuf/Descriptors$Descriptor;
 = java/lang/Object hashCode
 = getDataPointsCount L
3   com/google/protobuf/Parser parseFrom)(Ljava/nio/ByteBuffer;)Ljava/lang/Object;
T(Ljava/nio/ByteBuffer;Lcom/google/protobuf/ExtensionRegistryLite;)Ljava/lang/Object;
4(Lcom/google/protobuf/ByteString;)Ljava/lang/Object;
_(Lcom/google/protobuf/ByteString;Lcom/google/protobuf/ExtensionRegistryLite;)Ljava/lang/Object;
([B)Ljava/lang/Object;   A([BLcom/google/protobuf/ExtensionRegistryLite;)Ljava/lang/Object;
   parseWithIOException P(Lcom/google/protobuf/Parser;Ljava/io/InputStream;)Lcom/google/protobuf/Message;

{(Lcom/google/protobuf/Parser;Ljava/io/InputStream;Lcom/google/protobuf/ExtensionRegistryLite;)Lcom/google/
protobuf/Message;
   parseDelimitedWithIOException

  a(Lcom/google/protobuf/Parser;Lcom/google/protobuf/CodedInputStream;)Lcom/google/protobuf/Message;

(Lcom/google/protobuf/Parser;Lcom/google/protobuf/CodedInputStream;Lcom/google/protobuf/ExtensionRegistry
Lite;)Lcom/google/protobuf/Message;
 6 B()Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram$Builder;   DEFAULT_INSTANCE
8Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;
      toBuilder
z   mergeFrom
z(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;)Lio/opentelemetry/proto/metrics/v1/ExponentialHisto
gram$Builder;

z =(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram$1;)V
z
s(Lcom/google/protobuf/GeneratedMessageV3$BuilderParent;Lio/opentelemetry/proto/metrics/v1/ExponentialHisto
gram$1;)V
newBuilderForType
x(Lcom/google/protobuf/GeneratedMessageV3$BuilderParent;)Lio/opentelemetry/proto/metrics/v1/ExponentialHist
ogram$Builder;

getDefaultInstanceForType :()Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;
8io/opentelemetry/proto/metrics/v1/ExponentialHistogram$1
& ?io/opentelemetry/proto/metrics/v1/ExponentialHistogramOrBuilder serialVersionUID J
ConstantValue DATA_POINTS_FIELD_NUMBER Signature
SLjava/util/List<Lio/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint;>;
$AGGREGATION_TEMPORALITY_FIELD_NUMBER
VLcom/google/protobuf/Parser<Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;>; Code
LineNumberTable LocalVariableTable this builder 0Lcom/google/protobuf/GeneratedMessageV3$Builder;
LocalVariableTypeTable 3Lcom/google/protobuf/GeneratedMessageV3$Builder<*>;
6(Lcom/google/protobuf/GeneratedMessageV3$Builder<*>;)V newInstance
S(Lcom/google/protobuf/GeneratedMessageV3$UnusedPrivateParameter;)Ljava/lang/Object; unused
?Lcom/google/protobuf/GeneratedMessageV3$UnusedPrivateParameter; getUnknownFields rawValue tag done e
4Lcom/google/protobuf/InvalidProtocolBufferException; Ljava/io/IOException; input
&Lcom/google/protobuf/CodedInputStream; extensionRegistry +Lcom/google/protobuf/ExtensionRegistryLite;
mutable_bitField0_ -Lcom/google/protobuf/UnknownFieldSet$Builder;
StackMapTable D)com/google/protobuf/ExtensionRegistryLite F java/lang/Throwable
Exceptions internalGetFieldAccessorTable =()Lcom/google/protobuf/GeneratedMessageV3$FieldAccessorTable;
U()Ljava/util/List<Lio/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint;>;
getDataPointsOrBuilderList
_()Ljava/util/List<+Lio/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPointOrBuilder;>;
getDataPoints D(I)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPoint; index
getDataPointsOrBuilder M(I)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogramDataPointOrBuilder;
getAggregationTemporalityValue getAggregationTemporality
<()Lio/opentelemetry/proto/metrics/v1/AggregationTemporality; result
isInitialized ()Z i output 'Lcom/google/protobuf/CodedOutputStream; obj Ljava/lang/Object; other hash
O(Ljava/nio/ByteBuffer;)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram; data Ljava/nio/ByteBuffer;
z(Ljava/nio/ByteBuffer;Lcom/google/protobuf/ExtensionRegistryLite;)Lio/opentelemetry/proto/metrics/v1/Exponen
tialHistogram; Z(Lcom/google/protobuf/ByteString;)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;
Lcom/google/protobuf/ByteString;
(Lcom/google/protobuf/ByteString;Lcom/google/protobuf/ExtensionRegistryLite;)Lio/opentelemetry/proto/metrics/
v1/ExponentialHistogram; <([B)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram; [B
g([BLcom/google/protobuf/ExtensionRegistryLite;)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;
O(Ljava/io/InputStream;)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram; Ljava/io/InputStream;
z(Ljava/io/InputStream;Lcom/google/protobuf/ExtensionRegistryLite;)Lio/opentelemetry/proto/metrics/v1/Exponen
tialHistogram; parseDelimitedFrom
`(Lcom/google/protobuf/CodedInputStream;)Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;
(Lcom/google/protobuf/CodedInputStream;Lcom/google/protobuf/ExtensionRegistryLite;)Lio/opentelemetry/proto/
metrics/v1/ExponentialHistogram; prototype parent 6Lcom/google/protobuf/GeneratedMessageV3$BuilderParent;
@Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram$Builder; getDefaultInstance
X()Lcom/google/protobuf/Parser<Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;>; getParserForType

](Lcom/google/protobuf/GeneratedMessageV3$BuilderParent;)Lcom/google/protobuf/Message$Builder;
'()Lcom/google/protobuf/Message$Builder; +()Lcom/google/protobuf/MessageLite$Builder;
#()Lcom/google/protobuf/MessageLite; ()Lcom/google/protobuf/Message;
access$200
m(Lcom/google/protobuf/GeneratedMessageV3$Builder;Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram
$1;)V x0 x1 :Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram$1;
access$402 Z(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;Ljava/util/List;)Ljava/util/List;
access$502 <(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;I)I
access$400 J(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;)Ljava/util/List;
access$600
access$500 ;(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;)I
access$700 _(Lio/opentelemetry/proto/metrics/v1/ExponentialHistogram;)Lcom/google/protobuf/UnknownFieldSet;
access$800
(Lcom/google/protobuf/CodedInputStream;Lcom/google/protobuf/ExtensionRegistryLite;Lio/opentelemetry/proto/
metrics/v1/ExponentialHistogram$1;)V x2 <clinit>
SourceFile ExponentialHistogram.java InnerClasses .com/google/protobuf/GeneratedMessageV3$Builder Builder
*com/google/protobuf/Descriptors$Descriptor com/google/protobuf/Descriptors
Descriptor FieldAccessorTable 4com/google/protobuf/GeneratedMessageV3$BuilderParent
BuilderParent =com/google/protobuf/GeneratedMessageV3$UnusedPrivateParameter UnusedPrivateParameter
#com/google/protobuf/Message$Builder com/google/protobuf/Message 'com/google/protobuf/MessageLite$Builder1
" # $ % & #$
': (Y *+ * !)
* + , - . , / # 0 ' (P *%* !*(*) * + 1 2 (< Y.)
* + 3 4 5a (/ *) & * + (*., /Y1 >2: 6 +86 c !
' T 6 O ~ *>Y@ >* +A,GBK W"+Q6 * *+ , T 6 ~ ** X * \ *b?: *g: eY m*g: ~ ** X * \ *b e k)(, - . 0 2 4 5
6%7H9K:N<T=_>c@hAr@xB{EGHKMRYZ\]^STUVWYZ\]^_ *f
6 %u 7 8 9 : 9 ; + < = > ? @
A Bc 9 C] - O eH kO E 9 C] E 9 C] G e (p) b H I (= v z|) h i
h * + - (/ *) t * + # J K- (/ *) | * + # L = (4
*) *
+ M N (B * B) * + O P Q (B *) * + O R= (/ *) * + S T (^ * L+ +)
* + U B @ V W (j *!< * !) * + V$ B (F = * + * * + * * +) !'4=E *
% X F +F Y Z B
$ G k = (`*< < = * * `< * * `< * `<*)6
$17DJOY^ * ' X ` + [B & P (J+* + *++ M*, * , * ,)*
+8H * J +J [\ 1] B = ( ]* *)< h`<* % h `< 5 h* `< % h `< 5 h* `< h* `<*)2 ")8?IV[*] + N ^ B + _
*) *
`a G e b (B *+ ) * `a > ? G e c (7
*)
*
`d G e e (B *+ ) * `d > ? G e f (7
*) *
`g G e h (B *+ ) * `g > ? G e i (= *) ! "
! * <j G k k (H *+) ( ) (* <j > ? G k l i (= *) - .
- * <j G k l k (H *+) 4 5 4 * <j > ? G k m (= *) : ;
: * <= G k n (H *+) A B A * <= > ? G k (.) F * +6 ( ) H 6 (5 *) K * o (^ * zY zY
M,)
V

W *
+ p q
, r s ( ) r EF ( ) # t uF (.) * + # t (.) * + D v (0 *+
) * + A w (/ *) * + A w (/ *) * + A x (/ *) * + A x (/ *) * + A y (/ *) * + A
*) * } F ( ) (O *+,) ** + } = ~ ? • G e ' (1 Y. Y)
n
v R
]3 } z

Found
in path(s):
* /opentelemetry-proto-0-11-0-alpha-jar/io/opentelemetry/proto/metrics/v1/ExponentialHistogram.class

1.201 io-opentelemetry-exporter-otlp 1.29.0

1.201.1 Available under license :

Apache-2.0

1.202 io-opentelemetry-semconv 1.29.0-alpha

1.202.1 Available under license :

Apache-2.0

1.203 io-opentelemetry-sdk-autoconfigure-spi 1.29.0

1.203.1 Available under license :

Copyright 2020 Robert Winkler, Bohdan Storozhuk, Mahmoud Romeh, Dan Maas and others

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.
Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You"
(or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations,
or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"

means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems
that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants
to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work
or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not

pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution
of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental,
or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted
against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.204 libuuid 2.37.4-21.el9_7

1.204.1 Available under license :

NR START END SECTORS SIZE NAME UUID
1 32 7679 7648 3.7M 8f8378c0-01
2 7680 16383 8704 4.3M 8f8378c0-02
5 7936 12799 4864 2.4M
6 12544 16127 3584 1.8M

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better

strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those

libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of

a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file

that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the

Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it

if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in

themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component

itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals

of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of

protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy,
is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require,

such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to

the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent

works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source

may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded
from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,
procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the
Corresponding Source conveyed under this section must be accompanied
by the Installation Information. But this requirement does not apply
if neither you nor any third party retains the ability to install
modified object code on the User Product (for example, the work has

been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty
or limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or
requiring that modified versions of such material be marked in
reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or
authors of the material; or

e) Declining to grant rights under trademark law for use of some
trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that
material by anyone who conveys the material (or modified versions of
it) with contractual assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further
restrictions" within the meaning of section 10. If the Program as you
received it, or any part of it, contains a notice stating that it is
governed by this License along with a term that is a further
restriction, you may remove that term. If a license document contains
a further restriction but permits relicensing or conveying under this
License, you may add to a covered work material governed by the terms
of that license document, provided that the further restriction does
not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you
must place, in the relevant source files, a statement of the
additional terms that apply to those files, or a notice indicating
where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the
form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly
provided under this License. Any attempt otherwise to propagate or
modify it is void, and will automatically terminate your rights under
this License (including any patent licenses granted under the third
paragraph of section 11).

However, if you cease all violation of this License, then your
license from a particular copyright holder is reinstated (a)
provisionally, unless and until the copyright holder explicitly and

finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have

permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS
THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This library is free software; you can redistribute it and/or
modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
../Documentation/licenses/COPYING.BSD-3-Clause file.
Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later
version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPL-2.1-or-later
This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later
version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPL-2.1-or-later file.
#ifndef UTIL_LINUX_PT_BSD_H
#define UTIL_LINUX_PT_BSD_H

#define BSD_MAXPARTITIONS 16
#define BSD_FS_UNUSED 0

#ifndef BSD_DISKMAGIC
define BSD_DISKMAGIC   ((uint32_t) 0x82564557)
#endif

```
#define BSD_LINUX_BOOTDIR "/usr/ucb/mdec"

#if defined (__alpha__) || defined (__powerpc__) || \
  defined (__ia64__) || defined (__hppa__)
# define BSD_LABELSECTOR   0
# define BSD_LABELOFFSET   64
#else
# define BSD_LABELSECTOR   1
# define BSD_LABELOFFSET   0
#endif

#define BSD_BBSIZE        8192  /* size of boot area, with label */
#define BSD_SBSIZE        8192  /* max size of fs superblock */

struct bsd_disklabel {
 uint32_t d_magic;  /* the magic number */
 int16_t  d_type;   /* drive type */
 int16_t  d_subtype;  /* controller/d_type specific */
 char  d_typename[16];  /* type name, e.g. "eagle" */
 char  d_packname[16];  /* pack identifier */

  /* disk geometry: */
 uint32_t d_secsize;  /* # of bytes per sector */
 uint32_t d_nsectors;  /* # of data sectors per track */
 uint32_t d_ntracks;  /*
 # of tracks per cylinder */
 uint32_t d_ncylinders;  /* # of data cylinders per unit */
 uint32_t d_secpercyl;  /* # of data sectors per cylinder */
 uint32_t d_secperunit;  /* # of data sectors per unit */

 /*
  * Spares (bad sector replacements) below
  * are not counted in d_nsectors or d_secpercyl.
  * Spare sectors are assumed to be physical sectors
  * which occupy space at the end of each track and/or cylinder.
  */
 uint16_t d_sparespertrack; /* # of spare sectors per track */
 uint16_t d_sparespercyl;  /* # of spare sectors per cylinder */

 /*
  * Alternate cylinders include maintenance, replacement,
  * configuration description areas, etc.
  */
 uint32_t d_acylinders;  /* # of alt. cylinders per unit */

  /* hardware characteristics: */
 /*
```

```
 * d_interleave, d_trackskew and d_cylskew describe perturbations
 * in the media format used to compensate for a slow controller.
 * Interleave is physical sector interleave, set up by the formatter
 * or controller
when formatting.  When interleaving is in use,
 * logically adjacent sectors are not physically contiguous,
 * but instead are separated by some number of sectors.
 * It is specified as the ratio of physical sectors traversed
 * per logical sector.  Thus an interleave of 1:1 implies contiguous
 * layout, while 2:1 implies that logical sector 0 is separated
 * by one sector from logical sector 1.
 * d_trackskew is the offset of sector 0 on track N
 * relative to sector 0 on track N-1 on the same cylinder.
 * Finally, d_cylskew is the offset of sector 0 on cylinder N
 * relative to sector 0 on cylinder N-1.
 */
uint16_t d_rpm;   /* rotational speed */
uint16_t d_interleave;  /* hardware sector interleave */
uint16_t d_trackskew;  /* sector 0 skew, per track */
uint16_t d_cylskew;  /* sector 0 skew, per cylinder */
uint32_t d_headswitch;  /* head switch time, usec */
uint32_t d_trkseek;  /* track-to-track seek, usec */
uint32_t d_flags;  /* generic flags */
uint32_t d_drivedata[5];  /*
drive-type specific information */
uint32_t d_spare[5];  /* reserved for future use */
uint32_t d_magic2;  /* the magic number (again) */
uint16_t d_checksum;  /* xor of data incl. partitions */

  /* filesystem and partition information: */
uint16_t d_npartitions;        /* number of partitions in following */
uint32_t d_bbsize;         /* size of boot area at sn0, bytes */
uint32_t d_sbsize;         /* max size of fs superblock, bytes */

struct bsd_partition  {  /* the partition table */
 uint32_t p_size;         /* number of sectors in partition */
 uint32_t p_offset;       /* starting sector */
 uint32_t p_fsize;        /* filesystem basic fragment size */
 uint8_t  p_fstype; /* filesystem type, see below */
 uint8_t  p_frag;  /* filesystem fragments per block */
 uint16_t p_cpg;         /* filesystem cylinders per group */
} __attribute__((packed)) d_partitions[BSD_MAXPARTITIONS]; /* actually may be more */
} __attribute__((packed));



/* d_type values:
 */
#define BSD_DTYPE_SMD  1  /* SMD, XSMD; VAX hp/up */
```

```
#define BSD_DTYPE_MSCP  2  /* MSCP */
#define BSD_DTYPE_DEC  3  /* other DEC (rk, rl) */
#define BSD_DTYPE_SCSI  4  /* SCSI */
#define BSD_DTYPE_ESDI  5  /* ESDI interface */
#define BSD_DTYPE_ST506  6  /* ST506 etc. */
#define BSD_DTYPE_HPIB  7  /* CS/80 on HP-IB */
#define BSD_DTYPE_HPFL  8  /* HP Fiber-link */
#define BSD_DTYPE_FLOPPY 10  /* floppy */

/* d_subtype values: */
#define BSD_DSTYPE_INDOSPART 0x8  /* is inside dos partition */
#define BSD_DSTYPE_DOSPART(s) ((s) & 3) /* dos partition number */
#define BSD_DSTYPE_GEOMETRY 0x10  /* drive params in label */

/*
* Filesystem type and version.
* Used to interpret other filesystem-specific
* per-partition information.
*/
#define BSD_FS_UNUSED 0  /* unused */
#define BSD_FS_SWAP     1  /* swap */
#define BSD_FS_V6       2  /* Sixth Edition */
#define BSD_FS_V7       3  /* Seventh Edition */
#define BSD_FS_SYSV     4  /* System V */
#define BSD_FS_V71K     5  /* V7
 with 1K blocks (4.1, 2.9) */
#define BSD_FS_V8       6  /* Eighth Edition, 4K blocks */
#define BSD_FS_BSDFFS 7  /* 4.2BSD fast file system */
#define BSD_FS_BSDLFS 9  /* 4.4BSD log-structured file system */
#define BSD_FS_OTHER 10  /* in use, but unknown/unsupported */
#define BSD_FS_HPFS 11  /* OS/2 high-performance file system */
#define BSD_FS_ISO9660 12  /* ISO-9660 filesystem (cdrom) */
#define BSD_FS_ISOFS BSD_FS_ISO9660
#define BSD_FS_BOOT 13  /* partition contains bootstrap */
#define BSD_FS_ADOS 14  /* AmigaDOS fast file system */
#define BSD_FS_HFS 15  /* Macintosh HFS */
#define BSD_FS_ADVFS 16  /* Digital Unix AdvFS */

/* this is annoying, but it's also the way it is :-( */
#ifdef __alpha__
#define BSD_FS_EXT2 8  /* ext2 file system */
#else
#define BSD_FS_MSDOS 8  /* MS-DOS file system */
#endif

/*
* flags shared by various drives:
*/
```

```
#define BSD_D_REMOVABLE 0x01  /* removable media */
#define BSD_D_ECC       0x02  /* supports ECC */
#define BSD_D_BADSECT 0x04  /* supports
 bad sector forw. */
#define BSD_D_RAMDISK 0x08  /* disk emulator */
#define BSD_D_CHAIN     0x10  /* can do back-back transfers */
#define BSD_D_DOSPART 0x20  /* within MSDOS partition */

#endif /* UTIL_LINUX_PT_BSD_H */
/*
* Copyright (c) 1989 The Regents of the University of California.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
*    must display the following acknowledgement:
* This product includes software developed by the University of
* California, Berkeley and its contributors.
* 4. Neither the name of the University nor the names of its contributors
*    may be used to endorse or promote products derived from this software
*
 without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED.  IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*/
```

1.205 util-linux 2.37.4-21.el9_7

1.205.1 Available under license :

NR START END SECTORS SIZE NAME UUID
1 32 7679 7648 3.7M 8f8378c0-01
2 7680 16383 8704 4.3M 8f8378c0-02
5 7936 12799 4864 2.4M
6 12544 16127 3584 1.8M

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,

whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many

libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a

portion of it, either verbatim or with modifications and/or translated straightforwardly into
another language. (Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,
provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the
terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses

the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be
reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the

object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or
link a "work that uses the Library" with the Library to produce a
work containing portions of the Library, and distribute that work
under terms of your choice, provided that the terms permit
modification of the work for the customer's own use and reverse
engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the
Library is used in it and that the Library and its use are covered by
this License. You must supply a copy of this License. If the work
during execution displays copyright notices, you must include the
copyright notice for the Library among them, as well as a reference
directing the user to the copy of this License. Also, you must do one
of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable "work that
uses the Library", as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (1) uses at run time a
copy of the library already present on the user's computer system,
rather than copying library functions into the executable, and (2)
will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above

specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally
distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or

distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Library under this License may add
an explicit geographical distribution limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision
will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,

BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and

(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under

the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such

parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to

decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,

REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1)
assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we
stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that

patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally
available free
programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated

conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is
covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all

recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the

machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded
from the Corresponding Source

as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,
procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the
Corresponding Source conveyed under this section must be accompanied
by the Installation Information. But this requirement does not apply
if neither you nor any third party retains the ability to install
modified object code on the User Product (for example, the work has
been installed in
ROM).

The requirement to provide Installation Information does not include a
requirement to continue to provide support service, warranty, or updates
for a work that has been modified or installed by the recipient, or for
the User Product in which it has been modified or installed. Access to a
network may be denied when the modification itself materially and
adversely affects the operation of the network or violates the rules and
protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided,
in accord with this section must be in a format that is publicly
documented (and with an implementation available to the public in

source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under

this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims

owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is

conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or
that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate

parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

 You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

 The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
 to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, and the entire permission notice in its entirety,
  including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
  products derived from this software without specific prior
  written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
 DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This library is free software; you can redistribute it and/or
modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
../Documentation/licenses/COPYING.BSD-3-Clause file.
Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above

copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later
version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPL-2.1-or-later
This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later
version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPL-2.1-or-later file.

```
#ifndef UTIL_LINUX_PT_BSD_H
#define UTIL_LINUX_PT_BSD_H

#define BSD_MAXPARTITIONS 16
#define BSD_FS_UNUSED  0

#ifndef BSD_DISKMAGIC
# define BSD_DISKMAGIC     ((uint32_t) 0x82564557)
#endif

#define BSD_LINUX_BOOTDIR "/usr/ucb/mdec"

#if defined (__alpha__) || defined (__powerpc__) || \
   defined (__ia64__) || defined (__hppa__)
# define BSD_LABELSECTOR   0
# define BSD_LABELOFFSET   64
#else
# define BSD_LABELSECTOR   1
# define BSD_LABELOFFSET   0
#endif

#define BSD_BBSIZE        8192  /* size of boot area, with label */
#define BSD_SBSIZE        8192  /* max size of fs superblock */
```

```
struct bsd_disklabel {
 uint32_t d_magic;  /* the magic number */
 int16_t  d_type;   /* drive type */
 int16_t  d_subtype;  /* controller/d_type specific */
 char  d_typename[16];  /* type name, e.g. "eagle" */
 char  d_packname[16];  /* pack identifier */

  /* disk geometry: */
 uint32_t d_secsize;  /* # of bytes per sector */
 uint32_t d_nsectors;  /* # of data sectors per track */
 uint32_t d_ntracks;  /*
 # of tracks per cylinder */
 uint32_t d_ncylinders;  /* # of data cylinders per unit */
 uint32_t d_secpercyl;  /* # of data sectors per cylinder */
 uint32_t d_secperunit;  /* # of data sectors per unit */

 /*
  * Spares (bad sector replacements) below
  * are not counted in d_nsectors or d_secpercyl.
  * Spare sectors are assumed to be physical sectors
  * which occupy space at the end of each track and/or cylinder.
  */
 uint16_t d_sparespertrack; /* # of spare sectors per track */
 uint16_t d_sparespercyl;  /* # of spare sectors per cylinder */

 /*
  * Alternate cylinders include maintenance, replacement,
  * configuration description areas, etc.
  */
 uint32_t d_acylinders;  /* # of alt. cylinders per unit */

  /* hardware characteristics: */
 /*
  * d_interleave, d_trackskew and d_cylskew describe perturbations
  * in the media format used to compensate for a slow controller.
  * Interleave is physical sector interleave, set up by the formatter
  * or controller
 when formatting.  When interleaving is in use,
  * logically adjacent sectors are not physically contiguous,
  * but instead are separated by some number of sectors.
  * It is specified as the ratio of physical sectors traversed
  * per logical sector.  Thus an interleave of 1:1 implies contiguous
  * layout, while 2:1 implies that logical sector 0 is separated
  * by one sector from logical sector 1.
  * d_trackskew is the offset of sector 0 on track N
  * relative to sector 0 on track N-1 on the same cylinder.
  * Finally, d_cylskew is the offset of sector 0 on cylinder N
```

```
 * relative to sector 0 on cylinder N-1.
 */
uint16_t d_rpm;   /* rotational speed */
uint16_t d_interleave;  /* hardware sector interleave */
uint16_t d_trackskew;  /* sector 0 skew, per track */
uint16_t d_cylskew;  /* sector 0 skew, per cylinder */
uint32_t d_headswitch;  /* head switch time, usec */
uint32_t d_trkseek;  /* track-to-track seek, usec */
uint32_t d_flags;  /* generic flags */
uint32_t d_drivedata[5];  /*
drive-type specific information */
uint32_t d_spare[5];  /* reserved for future use */
uint32_t d_magic2;  /* the magic number (again) */
uint16_t d_checksum;  /* xor of data incl. partitions */

  /* filesystem and partition information: */
uint16_t d_npartitions;        /* number of partitions in following */
uint32_t d_bbsize;         /* size of boot area at sn0, bytes */
uint32_t d_sbsize;         /* max size of fs superblock, bytes */

struct bsd_partition  {  /* the partition table */
 uint32_t p_size;         /* number of sectors in partition */
 uint32_t p_offset;       /* starting sector */
 uint32_t p_fsize;        /* filesystem basic fragment size */
 uint8_t  p_fstype; /* filesystem type, see below */
 uint8_t  p_frag;  /* filesystem fragments per block */
 uint16_t p_cpg;         /* filesystem cylinders per group */
} __attribute__((packed)) d_partitions[BSD_MAXPARTITIONS]; /* actually may be more */
} __attribute__((packed));


/* d_type values:
 */
#define BSD_DTYPE_SMD  1  /* SMD, XSMD; VAX hp/up */
#define BSD_DTYPE_MSCP  2  /* MSCP */
#define BSD_DTYPE_DEC  3  /* other DEC (rk, rl) */
#define BSD_DTYPE_SCSI  4  /* SCSI */
#define BSD_DTYPE_ESDI  5  /* ESDI interface */
#define BSD_DTYPE_ST506  6  /* ST506 etc. */
#define BSD_DTYPE_HPIB  7  /* CS/80 on HP-IB */
#define BSD_DTYPE_HPFL  8  /* HP Fiber-link */
#define BSD_DTYPE_FLOPPY 10  /* floppy */

/* d_subtype values: */
#define BSD_DSTYPE_INDOSPART 0x8  /* is inside dos partition */
#define BSD_DSTYPE_DOSPART(s) ((s) & 3) /* dos partition number */
#define BSD_DSTYPE_GEOMETRY 0x10  /* drive params in label */
```

```
/*
* Filesystem type and version.
* Used to interpret other filesystem-specific
* per-partition information.
*/
#define BSD_FS_UNUSED 0  /* unused */
#define BSD_FS_SWAP     1  /* swap */
#define BSD_FS_V6       2  /* Sixth Edition */
#define BSD_FS_V7       3  /* Seventh Edition */
#define BSD_FS_SYSV     4  /* System V */
#define BSD_FS_V71K     5  /* V7
 with 1K blocks (4.1, 2.9) */
#define BSD_FS_V8       6  /* Eighth Edition, 4K blocks */
#define BSD_FS_BSDFFS 7  /* 4.2BSD fast file system */
#define BSD_FS_BSDLFS 9  /* 4.4BSD log-structured file system */
#define BSD_FS_OTHER 10  /* in use, but unknown/unsupported */
#define BSD_FS_HPFS 11  /* OS/2 high-performance file system */
#define BSD_FS_ISO9660 12  /* ISO-9660 filesystem (cdrom) */
#define BSD_FS_ISOFS BSD_FS_ISO9660
#define BSD_FS_BOOT 13  /* partition contains bootstrap */
#define BSD_FS_ADOS 14  /* AmigaDOS fast file system */
#define BSD_FS_HFS 15  /* Macintosh HFS */
#define BSD_FS_ADVFS 16  /* Digital Unix AdvFS */

/* this is annoying, but it's also the way it is :-( */
#ifdef __alpha__
#define BSD_FS_EXT2 8  /* ext2 file system */
#else
#define BSD_FS_MSDOS 8  /* MS-DOS file system */
#endif

/*
* flags shared by various drives:
*/
#define BSD_D_REMOVABLE 0x01  /* removable media */
#define BSD_D_ECC       0x02  /* supports ECC */
#define BSD_D_BADSECT 0x04  /* supports
 bad sector forw. */
#define BSD_D_RAMDISK 0x08  /* disk emulator */
#define BSD_D_CHAIN     0x10  /* can do back-back transfers */
#define BSD_D_DOSPART 0x20  /* within MSDOS partition */

#endif /* UTIL_LINUX_PT_BSD_H */
/*
* Copyright (c) 1989 The Regents of the University of California.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
```

* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
*   must display the following acknowledgement:
* This product includes software developed by the University of
* California, Berkeley and its contributors.
* 4. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*
 without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*/

1.206 libmount 2.37.4-21.el9_7

1.206.1 Available under license :

NR START   END SECTORS SIZE NAME UUID
1   32 7679   7648 3.7M   8f8378c0-01
2 7680 16383   8704 4.3M   8f8378c0-02
5 7936 12799   4864 2.4M
6 12544 16127   3584 1.8M
                GNU LESSER GENERAL PUBLIC LICENSE
                  Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence

the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be

introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU
operating system, as well as its variant, the GNU/Linux operating

system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does

and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be

reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not

compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one

of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable "work that
uses the Library", as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (1) uses at run time a
copy of the library already present on the user's computer system,
rather than copying library functions into the executable, and (2)
will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally

accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and

"any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision
will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the

ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to

address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest

possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they

know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy,
is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The
"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A

"Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section

4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no

more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded
from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,

procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the
Corresponding Source conveyed under this section must be accompanied
by the Installation Information. But this requirement does not apply
if neither you nor any third party retains the ability to install
modified object code on the User Product (for example, the work has
been installed in
ROM).

The requirement to provide Installation Information does not include a
requirement to continue to provide support service, warranty, or updates
for a work that has been modified or installed by the recipient, or for
the User Product in which it has been modified or installed. Access to a
network may be denied when the modification itself materially and
adversely affects the operation of the network or violates the rules and
protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided,
in accord with this section must be in a format that is publicly
documented (and with an implementation available to the public in
source code form), and must require no special password or key for
unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this
License by making exceptions from one or more of its conditions.
Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent
that they are valid under applicable law. If additional permissions
apply only to part of the Program, that part may be used separately
under those permissions, but the entire Program remains governed by
this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option
remove any additional permissions from that copy, or from any part of

it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty
or limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For
purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent

(such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different

permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively

state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want
to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions

are met:
1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
This library is free software; you can redistribute it and/or
modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
../Documentation/licenses/COPYING.BSD-3-Clause file.
Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later
version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPL-2.1-or-later

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later
version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPL-2.1-or-later file.

```
#ifndef UTIL_LINUX_PT_BSD_H
#define UTIL_LINUX_PT_BSD_H

#define BSD_MAXPARTITIONS 16
#define BSD_FS_UNUSED  0

#ifndef BSD_DISKMAGIC
# define BSD_DISKMAGIC     ((uint32_t) 0x82564557)
#endif

#define BSD_LINUX_BOOTDIR "/usr/ucb/mdec"

#if defined (__alpha__) || defined (__powerpc__) || \
   defined (__ia64__) || defined (__hppa__)
# define BSD_LABELSECTOR   0
# define BSD_LABELOFFSET   64
#else
# define BSD_LABELSECTOR   1
# define BSD_LABELOFFSET   0
#endif

#define BSD_BBSIZE        8192  /* size of boot area, with label */
#define BSD_SBSIZE        8192  /* max size of fs superblock */

struct bsd_disklabel {
 uint32_t d_magic;  /* the magic number */
 int16_t  d_type;   /* drive type */
 int16_t  d_subtype;  /* controller/d_type specific */
 char  d_typename[16];  /* type name, e.g. "eagle" */
 char  d_packname[16];  /* pack identifier */

   /* disk geometry: */
 uint32_t d_secsize;  /* # of bytes per sector */
 uint32_t d_nsectors;  /* # of data sectors per track */
 uint32_t d_ntracks;  /*
 # of tracks per cylinder */
 uint32_t d_ncylinders;  /* # of data cylinders per unit */
 uint32_t d_secpercyl;  /* # of data sectors per cylinder */
 uint32_t d_secperunit;  /* # of data sectors per unit */
```

```
/*
 * Spares (bad sector replacements) below
 * are not counted in d_nsectors or d_secpercyl.
 * Spare sectors are assumed to be physical sectors
 * which occupy space at the end of each track and/or cylinder.
 */
uint16_t d_sparespertrack; /* # of spare sectors per track */
uint16_t d_sparespercyl;  /* # of spare sectors per cylinder */

/*
 * Alternate cylinders include maintenance, replacement,
 * configuration description areas, etc.
 */
uint32_t d_acylinders;  /* # of alt. cylinders per unit */

  /* hardware characteristics: */
/*
 * d_interleave, d_trackskew and d_cylskew describe perturbations
 * in the media format used to compensate for a slow controller.
 * Interleave is physical sector interleave, set up by the formatter
 * or controller
when formatting.  When interleaving is in use,
 * logically adjacent sectors are not physically contiguous,
 * but instead are separated by some number of sectors.
 * It is specified as the ratio of physical sectors traversed
 * per logical sector.  Thus an interleave of 1:1 implies contiguous
 * layout, while 2:1 implies that logical sector 0 is separated
 * by one sector from logical sector 1.
 * d_trackskew is the offset of sector 0 on track N
 * relative to sector 0 on track N-1 on the same cylinder.
 * Finally, d_cylskew is the offset of sector 0 on cylinder N
 * relative to sector 0 on cylinder N-1.
 */
uint16_t d_rpm;   /* rotational speed */
uint16_t d_interleave;  /* hardware sector interleave */
uint16_t d_trackskew;  /* sector 0 skew, per track */
uint16_t d_cylskew;  /* sector 0 skew, per cylinder */
uint32_t d_headswitch;  /* head switch time, usec */
uint32_t d_trkseek;  /* track-to-track seek, usec */
uint32_t d_flags;  /* generic flags */
uint32_t d_drivedata[5];  /*
drive-type specific information */
uint32_t d_spare[5];  /* reserved for future use */
uint32_t d_magic2;  /* the magic number (again) */
uint16_t d_checksum;  /* xor of data incl. partitions */

  /* filesystem and partition information: */
uint16_t d_npartitions;         /* number of partitions in following */
```

```
 uint32_t d_bbsize;         /* size of boot area at sn0, bytes */
 uint32_t d_sbsize;         /* max size of fs superblock, bytes */

 struct bsd_partition  {  /* the partition table */
  uint32_t p_size;         /* number of sectors in partition */
  uint32_t p_offset;       /* starting sector */
  uint32_t p_fsize;        /* filesystem basic fragment size */
  uint8_t  p_fstype; /* filesystem type, see below */
  uint8_t  p_frag;  /* filesystem fragments per block */
  uint16_t p_cpg;          /* filesystem cylinders per group */
 } __attribute__((packed)) d_partitions[BSD_MAXPARTITIONS]; /* actually may be more */
} __attribute__((packed));


/* d_type values:
 */
#define BSD_DTYPE_SMD  1  /* SMD, XSMD; VAX hp/up */
#define BSD_DTYPE_MSCP  2  /* MSCP */
#define BSD_DTYPE_DEC  3  /* other DEC (rk, rl) */
#define BSD_DTYPE_SCSI  4  /* SCSI */
#define BSD_DTYPE_ESDI  5  /* ESDI interface */
#define BSD_DTYPE_ST506  6  /* ST506 etc. */
#define BSD_DTYPE_HPIB  7  /* CS/80 on HP-IB */
#define BSD_DTYPE_HPFL  8  /* HP Fiber-link */
#define BSD_DTYPE_FLOPPY 10  /* floppy */

/* d_subtype values: */
#define BSD_DSTYPE_INDOSPART 0x8  /* is inside dos partition */
#define BSD_DSTYPE_DOSPART(s) ((s) & 3) /* dos partition number */
#define BSD_DSTYPE_GEOMETRY 0x10  /* drive params in label */

/*
* Filesystem type and version.
* Used to interpret other filesystem-specific
* per-partition information.
*/
#define BSD_FS_UNUSED 0  /* unused */
#define BSD_FS_SWAP     1  /* swap */
#define BSD_FS_V6       2  /* Sixth Edition */
#define BSD_FS_V7       3  /* Seventh Edition */
#define BSD_FS_SYSV     4  /* System V */
#define BSD_FS_V71K     5  /* V7
 with 1K blocks (4.1, 2.9) */
#define BSD_FS_V8       6  /* Eighth Edition, 4K blocks */
#define BSD_FS_BSDFFS 7  /* 4.2BSD fast file system */
#define BSD_FS_BSDLFS 9  /* 4.4BSD log-structured file system */
#define BSD_FS_OTHER 10  /* in use, but unknown/unsupported */
#define BSD_FS_HPFS 11  /* OS/2 high-performance file system */
```

```
#define BSD_FS_ISO9660 12  /* ISO-9660 filesystem (cdrom) */
#define BSD_FS_ISOFS BSD_FS_ISO9660
#define BSD_FS_BOOT 13  /* partition contains bootstrap */
#define BSD_FS_ADOS 14  /* AmigaDOS fast file system */
#define BSD_FS_HFS 15  /* Macintosh HFS */
#define BSD_FS_ADVFS 16  /* Digital Unix AdvFS */

/* this is annoying, but it's also the way it is :-( */
#ifdef __alpha__
#define BSD_FS_EXT2 8  /* ext2 file system */
#else
#define BSD_FS_MSDOS 8  /* MS-DOS file system */
#endif

/*
* flags shared by various drives:
*/
#define BSD_D_REMOVABLE 0x01  /* removable media */
#define BSD_D_ECC       0x02  /* supports ECC */
#define BSD_D_BADSECT 0x04  /* supports
 bad sector forw. */
#define BSD_D_RAMDISK 0x08  /* disk emulator */
#define BSD_D_CHAIN     0x10  /* can do back-back transfers */
#define BSD_D_DOSPART 0x20  /* within MSDOS partition */

#endif /* UTIL_LINUX_PT_BSD_H */
/*
* Copyright (c) 1989 The Regents of the University of California.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
*    must display the following acknowledgement:
* This product includes software developed by the University of
* California, Berkeley and its contributors.
* 4. Neither the name of the University nor the names of its contributors
*    may be used to endorse or promote products derived from this software
*
 without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
```

* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*/

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries.To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

©2026 Cisco Systems, Inc. All rights reserved.